Ethernet		4c	fb	45	65	e4	df	44	1c	a8	48	90	35	80	00		
dst	4c:fb:45:65:e4:df_				<u> </u>											45	
src	44:1c:a8:48:90:35		4	10	c7	40	00	3f	11	75	ed	c0	a8	2b	de	ac	<u>d9</u>
type	IPv4	<u>18</u>	64	2.4		0.1					10						
IP IP		+		84	76	01	bb	03	61	37	d3	0.1		<u> </u>	ГΛ	<u></u>	
version	4L	07	06	ch	51	30	33	35	<u> </u>	hf	60					66 2b	
ihl	5L————————————————————————————————————															2f	
tos	0x0															a7	
len	885	1														5a	
id	4295															bd	
flags	DF															74	
frag	0L	45	90	d6	4e	ее	d4	65	a 6	91	29	ed	f7	e6	39	0a	8a
ttl	63	71	57	ff	8d	1a	61	03	84	9f	91	f4	52	5f	с7	3f	Зе
proto	udp															сЗ	
chksum	0×75ed															ca	
src	192.168.43.222															8a	
dst	172.217.24.100															50	
options																Of	
UDP																26 b8	
sport	33910															e2	
dport	https															65	
len	865	89														d1	
chksum	0x37d3	b7														76	
Raw																ea	
load	'\r\xcanPf\x00\x97[]	f0	95	37	3с	de	c4	d2	9с	7b	сЗ	07	01	d0	25	0f	90
		20	12	00	75	Of	38	c1	3b	93	2a	e7	dd	f5	82	43	3d
																03	
																ed	
																db	
																f4	
																72	
																a2	
																fe 90	
																55	
																51	
																95	
																a0	
																b8	
																48	
	\	ес	df	ed	е9	СС	df	с6	92	a 6	f3	25	9с	55	4f	09	27
		3d	52	d3	a8	3a	89	88	a 9	d6	59	14	се	d6	14	c4	e4
																d0	
																50	
																4c	
																2a	
																bd	
																41 14	
																6c	
																69	
																cd	
																8d	
																49	
																17	
																42	
																29	
		98	75	13													