Ethernet		44	1c	a8	48	90	35	b8	98	f7	9a	a9	54	80	00		
dst	44:1c:a8:48:90:35				T											45	
src	b8:98:f7:9a:a9:54			10	c7	40	00	40	11	74	ed	c0	a8	2b	de	ac	d9
type	IPv4	- <u>18</u>	64							\angle							
		-/		84	76	01	bb	03	61	37	d3	0.1					/
IP	41	107	0.0		F 4	20	22	25	/	1.6	C -					66	
version ihl	4L 5L															2b 2f	
tos	0x0															a7	
len	885	1														5a	1
id	4295															bd	
flags	DF															74	
frag	0L															0a	
ttl	64															3f	
proto	udp															сЗ	
chksum	0x74ed	a2	df	a2	3d	6c	fa	ae	0d	7d	9d	dd	05	d9	8d	ca	3b
src	192.168.43.222	80	76	20	36	87	е9	99	6с	4f	a3	02	dc	20	53	8a	e4
dst	172.217.24.100	22	af	4d	98	7b	5c	d1	9a	77	ae	29	5b	63	94	50	9f
options																Of	
UDP																26	
sport	33910															b8	
dport	https															e2	
len	865	b8														65	
chksum	0×37d3	89														d1	
D.																76	1
Raw	'\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\															ea	
load	'\r\xcanPf\x00\x97[]															0f 43	
																03	
																ed	
																db	
																f4	
																72	
																a2	
		9e	45	a7	ae	53	bd	27	07	06	f5	a5	7a	79	41	fe	4e
		15	1b	e4	db	28	a8	0e	14	64	b2	8a	9a	eb	17	90	25
	\	56	a6	9a	01	db	34	23	15	00	с5	95	b5	2e	0e	55	9с
		a2	bc	03	5a	45	eb	f4	b6	be	ес	ed	56	d7	01	51	71
		2d	2c	95	b9	f4	36	d8	с7	9d	45	f8	7a	1f	9d	95	3d
																a 0	
																b8	
																48	
		1														09	
																c4	
																d0 50	
																4c	
																2a	
																bd	
																41	
																14	1
																6c	
																69	
																cd	
																8d	
																49	
		1f	51	18	93	16	00	4f	с9	50	54	9f	dd	14	26	17	Зс
		48	f8	f6	27	39	02	92	a4	с7	24	77	29	a8	d9	42	6d
						28	77	6c	fe	87	4d	d9	5b	e7	b3	29	8e
		98	75	13													