

Redis setup with Redis Insight in Docker

Author: Asif Zaman

Step-by-step setup

Step 1: First of all, we need to download the Redis and Redis Insights Docker image's latest version

```
docker pull redis:latest
docker pull redis/redisinsight:latest
```

Step 2: Then we need to set up the containers to run them

Manually create volume to store the redis data and some configs if those are needed and run the containers or use the docker CLI

```
docker run -d --name redis -p 6379:6379 -v redis-data:/data redis:latest
redis-server --appendonly yes

docker run -d --name redisinsight -p 5540:5540 -v redisinsight-data:/data
redis/redisinsight:latest
```

Step 3: We have to run them from a same network, so create a network in docker and assign them in the same network

```
>>>docker network create redis-net
>>>6ea7229b353fa65b93a98b6131e8e6f7925d0e2233a836b5cf631c1a10fa20d7

>>>docker network connect redis-net redisinsight
>>>docker network inspect redis-net
[
  {
    "Name": "redis-net",
    "Id":
"904ac4f3a9aac8e7e66684226991d99e1c32f7989475b11ae12becf6ae805be2",
    "Created": "2026-09-04T16:26:26.496645417Z",
    "Scope": "local",
    "Driver": "bridge",
    "EnableIPv4": true,
    "EnableIPv6": false,
```

```

    "IPAM": {
        "Driver": "default",
        "Options": {},
        "Config": [
            {
                "Subnet": "172.18.0.0/16",
                "Gateway": "172.18.0.1"
            }
        ]
    },
    "Internal": false,
    "Attachable": false,
    "Ingress": false,
    "ConfigFrom": {
        "Network": ""
    },
    "ConfigOnly": false,
    "Options": {
        "com.docker.network.enable_ipv4": "true",
        "com.docker.network.enable_ipv6": "false"
    },
    "Labels": {},
    "Containers": {

"6ea7229b353fa65b93a98b6131e8e6f7925d0e2233a836b5cf631c1a10fa20d7": {
        "Name": "redisinsight",
        "EndpointID":
"5f20f61ebce5efec7a532e210ee435732763afb40b4f037b0226ff416f5c55f5",
        "MacAddress": "e2:15:51:7c:dc:6b",
        "IPv4Address": "172.18.0.2/16",
        "IPv6Address": ""
    }
},
    "Status": {
        "IPAM": {
            "Subnets": {
                "172.18.0.0/16": {
                    "IPsInUse": 4,
                    "DynamicIPsAvailable": 65532
                }
            }
        }
    }
}
]

```

```

>>>docker network connect redis-net redis-container
>>>docker network inspect redis-net
[
  {
    "Name": "redis-net",
    "Id":
"904ac4f3a9aac8e7e66684226991d99e1c32f7989475b11ae12becf6ae805be2",
    "Created": "2026-09-04T16:26:26.496645417Z",
    "Scope": "local",
    "Driver": "bridge",
    "EnableIPv4": true,
    "EnableIPv6": false,
    "IPAM": {
      "Driver": "default",
      "Options": {},
      "Config": [
        {
          "Subnet": "172.18.0.0/16",
          "Gateway": "172.18.0.1"
        }
      ]
    },
    "Internal": false,
    "Attachable": false,
    "Ingress": false,
    "ConfigFrom": {
      "Network": ""
    },
    "ConfigOnly": false,
    "Options": {
      "com.docker.network.enable_ipv4": "true",
      "com.docker.network.enable_ipv6": "false"
    },
    "Labels": {},
    "Containers": {

"2d3466cc8e978cf8c8951925a1788ea9d9d67a1186c81d8f65ccc45e6e6082b7": {
      "Name": "redis-container",
      "EndpointID":
"2f2d9ae8705e87d16368f363e46f34fb479ce7d582226873ed5fcdfb08e3266a",
      "MacAddress": "ee:76:11:dd:7d:a7",
      "IPv4Address": "172.18.0.3/16",
      "IPv6Address": ""
    },

"6ea7229b353fa65b93a98b6131e8e6f7925d0e2233a836b5cf631c1a10fa20d7": {

```

```
        "Name": "redisinsight",
        "EndpointID":
"5f20f61ebce5efec7a532e210ee435732763afb40b4f037b0226ff416f5c55f5",
        "MacAddress": "e2:15:51:7c:dc:6b",
        "IPv4Address": "172.18.0.2/16",
        "IPv6Address": ""
    }
},
    "Status": {
        "IPAM": {
            "Subnets": {
                "172.18.0.0/16": {
                    "IPsInUse": 5,
                    "DynamicIPsAvailable": 65531
                }
            }
        }
    }
}
]
```