Assignment no. 2

Name : Asim Sultan

Reg # : 9008

Q1 The Hardcoded Menu Server

```
http://localhost:3000/menu
```

http://localhost:3000/order

Q2 Visual Catalog (Image Links)

Pretty-print

[{"name":"Margherita Pizza","price":450,"category":"Pizza","image":"https://images.unsplash.com/photo-1601924638867-3ec4c4c38c58"},{"name":"Zinger Burger","price":380,"category":"Burger","image":"https://images.unsplash.com/photo-1550547660-d9450f859349"},{"name":"Alfredo Pasta","price":590,"category":"Pasta","image":"https://images.unsplash.com/photo-1621996346565-e3dbc353d2e5"},{"name":"Chocolate Lava Cake","price":350,"category":"Dessert","image":"https://images.unsplash.com/photo-1606313564200-e75d5e30476c"}]

Q3 The "Order Logger"

```
PS C:\Users\Asim sultan\cheezious-app> node server.js
Server running on http://localhost:3001
New Order Received:
{
  items: [
    {
      id: 1,
      name: 'Margherita Pizza',
      price: 450,
      img: '🍕',
      category: 'Pizza',
      quantity: 1
    }
  ],
  total: 600,
  paymentMethod: 'cod'
}
```

When user order something my server will get a notification on terminal. Which is new order then all info of user's order will appear on server.This proves the frontend and backend are talking to each other.

Deliverables on git

A Single Server File: One file containing both the code and the menu data.

Working Links: A URL that, when opened, shows the "Catalog" of products in text format.

Updated README: Simple instructions on how to run the server (e.g., "Type node app.js to start").