Section 10

Regular Expressions

Mohammed Asir Shahid

2021-08-03

Contents

| 1 | Reg | gular Expression Basics | 1 | |
|----------|--|--|----|--|
| | 1.1 | The re Module | ٩ | |
| 2 | Regex Groups and the Pipe Character | | | |
| | 2.1 | Groups | 4 | |
| | 2.2 | Pipe Character | | |
| 3 | Repetition in Regex Patterns and Greedy/Nongreedy Match- | | | |
| | ing | | 6 | |
| | 3.1 | ? (zero or one) | (| |
| | 3.2 | * (zero or more) | 7 | |
| | 3.3 | + (one or more) | 8 | |
| | 3.4 | Escaping ?, *, and $+ \dots \dots \dots \dots \dots \dots$ | Ć | |
| | 3.5 | $\{x\}$ (exactly x) | Ć | |
| | 3.6 | $\{x,y\}$ (at least x, at most y) | 10 | |
| 4 | Regex Character Classes and the findall() Method | | | |
| | 4.1 | Character Classes | 14 | |
| | 4.2 | 12 Days of Christmas Example | 14 | |
| | 4.3 | Making Your Own Character Classes | 15 | |

1 Regular Expression Basics

In this lesson, we will be working with pattern matching and regular expressions. Regular expressions allow you to specify a pattern of text to search for.

An example of a text pattern would be a phone number. 415-555-0000. In the US, this is the standard way of writing up phone numbers. If we had that same number but without the hyphens, we would not recognize it as a phone number.

```
def isPhoneNumber(text):
    if len(text) != 12:
        return False
    for i in range(0, 3):
        if not text[i].isdecimal():
            return False
    if text[3] != '-':
        return False
    for i in range(4, 7):
        if not text[i].isdecimal():
            return False
    if text[7] != '-':
        return False
    for i in range(8, 12):
        if not text[i].isdecimal():
            return False
    return True
print(isPhoneNumber("415-555-1234"))
print(isPhoneNumber("My Phone Number"))
True
False
```

That's a lot of code for a relatively simple task. If we want to find phone numbers in large strings, we'd need to write some more code.

```
def isPhoneNumber(text):
    if len(text) != 12:
        return False
    for i in range(0, 3):
        if not text[i].isdecimal():
            return False
    if text[3] != '-':
```

```
return False
    for i in range(4, 7):
        if not text[i].isdecimal():
            return False
    if text[7] != '-':
        return False
    for i in range (8, 12):
        if not text[i].isdecimal():
            return False
    return True
print(isPhoneNumber("415-555-1234"))
print(isPhoneNumber("My Phone Number"))
message="Call me at 415-555-1011 tomorrow, or 415-555-9999 for my office line"
foundNuumber=False
for i in range(len(message)):
    chunk=message[i:i+12]
    if isPhoneNumber(chunk) == True:
        print("Phone number found")
        foundNumber=True
if not foundNumber:
    print("Could not find any phone numbers")
True
False
Phone number found
Phone number found
```

1.1 The re Module

We can write the previous code much faster using regular expressions.

```
import re
message="Call me at 415-555-1011 tomorrow, or 415-555-9999 for my office line"
```

2 Regex Groups and the Pipe Character

We can try some more of Python's more powerful pattern matching capabilities.

Let's say we want to seperate the area code from a phone number.

```
import re
phoneNumRegex = re.compile(r"\d\d\d-\d\d\d\d\d\d")
mo=phoneNumRegex.search("My number is 415-555-4242")
print(mo.group())

415-555-4242
```

2.1 Groups

Let's say we only want the phone number or only the phone number portion of the number. We can do this sing parentheses to mark out groups in the string.

```
import re

phoneNumRegex = re.compile(r"(\d\d\d)-(\d\d\d\d\d)")
mo=phoneNumRegex.search("My number is 415-555-4242")
print(mo.group())

print(mo.group(1))
print(mo.group(2))

415-555-4242
415
555-4242
```

The parentheses there can be useful syntax when we want to find specific parts of something. However, what can we do when we want to find literal parentheses? We would escape them using parentheses.

```
import re
phoneNumRegex = re.compile(r"\(\d\d\d\) \d\d-\d\d\d\d")
mo=phoneNumRegex.search("My number is (415) 555-4242")
print(mo.group())

(415) 555-4242
```

2.2 Pipe Character |

Pipes can be used to match one of several patterns as part of the regular expression.

Let's say we wanted to match any of the strings "Batman", "Batmobile", "Batcopter", or "Batbat"

```
import re
batRegex = re.compile(r"Bat(man|mobile|copter|bat)")
mo=batRegex.search("Batmobile lost a wheel.")
print(mo.group())
```

```
print(mo.group(1))
Batmobile
mobile
```

If the search method can't find the regular expression pattern, it will return None. In that case, we can risk running into errors.

3 Repetition in Regex Patterns and Greedy/Nongreedy Matching

How can we match a certain number of repetitions of a group? For example, one or more repitions, between 7 and 10 repitions, etc.

3.1 ? (zero or one)

This says match the preceding group either 0 or 1 times.

```
import re

#batRegex=re.compile(r"Batman|Batwoman")
batRegex=re.compile(r"Bat(wo)?man")

mo=batRegex.search("The Adventures of Batman")
print(mo.group())

mo=batRegex.search("The Adventures of Batwoman")
print(mo.group())

mo=batRegex.search("The Adventures of Batwowoman")
print(mo)

Batman
Batwoman
None
```

Using our earlier phone number example, we can make a regular expression that looks for phone numbers that do or do not have an area code. With our previous code, if we did not have an area code then the regex would not find the phone number.

If we need to match a question mark as part of the expression, we can simply escape it by doing $\?$.

3.2 * (zero or more)

The asterisk means match 0 or more times.

```
import re
batRegex=re.compile(r"Bat(wo)*man")
```

```
mo=batRegex.search("The Adventures of Batman")
print(mo.group())
mo=batRegex.search("The Adventures of Batwoman")
print(mo.group())
mo=batRegex.search("The Adventures of Batwowowoman")
print(mo.group())
Batman
Batwoman
Batwowowoman
   If you need to match an * that appears in the pattern, you can escape it
by doing \*.
3.3
     + (one or more)
Unlike the star, the group preceding a + must appear in the pattern.
import re
batRegex=re.compile(r"Bat(wo)+man")
mo=batRegex.search("The Adventures of Batman")
print(mo)
mo=batRegex.search("The Adventures of Batwoman")
print(mo.group())
mo=batRegex.search("The Adventures of Batwowowoman")
print(mo.group())
None
Batwoman
Batwowowoman
   If you need to match a + that appears in the pattern, you can escape it
```

by doing $\setminus +$.

3.4 Escaping ?, *, and +

```
import re
regex = re.compile(r"\+\*\?")
mo=regex.search("I learned about +*? regex syntax")
print(mo.group())
```

We could also put the above +*? into a group and then putting a + after it to say that the group needs to appear at least once.

```
import re
regex = re.compile(r"(\+\*\?)+")
mo=regex.search("I learned about +*?+*?+*? regex syntax")
print(mo.group())
+*?+*?+*?
```

$3.5 \quad \{x\} \text{ (exactly x)}$

This can be used if you wanted to match a specific number of repetitions of a group.

```
import re
haRegex=re.compile(r"(Ha){3}")
mo=haRegex.search("He said \"HaHaHa\"")
print(mo.group())
```

НаНаНа

+*?

While the above is a simple example, we could do it for many other, more complex examples.

```
import re
phoneRegex=re.compile(r"((\d\d\-)?\d\d\-\d\d\d\,)?){3}")
mo=phoneRegex.search("My numbers are 415-555-1234,555-4242,212-555-0000")
print(mo.group())
415-555-1234,555-4242,212-555-0000
    \{x,y\} (at least x, at most y)
import re
haRegex=re.compile(r"(Ha){3,5}")
mo=haRegex.search("He said \"HaHaHa\"")
print(mo.group())
mo=haRegex.search("He said \"HaHaHaHaHa\"")
print(mo.group())
mo=haRegex.search("He said \"HaHaHaHaHaHa\"")
print(mo)
НаНаНа
НаНаНаНа
<re.Match object; span=(9, 19), match='HaHaHaHaHa'>
   We can also have no y value which would have no maximum and be
unbounded, x or more.
import re
digitRegex=re.compile(r"(\d){3,5}")
mo=digitRegex.search("1234567890")
print(mo.group())
12345
```

As we can see above, there was a match of the first 5 digits even though the first 3 also would have sufficed. By default, Python regular expressions do greedy matches. This means that it tries to match the longest possible string that matches the pattern.

In order to do a nongreedy match, we can specify a question mark following the curly braces. Then it matches the first, shortest pattern.

```
import re
digitRegex=re.compile(r"(\d){3,5}?")
mo=digitRegex.search("1234567890")
print(mo.group())
```

123

4 Regex Character Classes and the findall() Method

In this lesson, we'll talk about the findall() method with regular expressions.

```
import re
resume="""

JESSE KENDALL

123 Elm Street, Fall River, MA 02723, Cell: 508-555-5555, Home: 508-555-1234 twemel@ch.
```

SUMMARY OF QUALIFICATIONS

Dedicated cell phone sales professional with demonstrated success in retail management

```
SALES SUCCESS
RETAIL STORE SALES MANAGER, 20xx - 20xx
ABC CELLULAR, Fall River, MA
```

Recruited, hired, trained, developed, and directed retail sales teams for two retail ${\tt A}{\tt B}$

Implemented a sales-tracking spreadsheet to replace a manual form writing process to in Developed innovative and effective marketing programs; exceeded store sales quotas.

Successfully managed one of the highest-producing ABC Wireless dealer locations in the Received several "Sales Manager of the Month" Awards.

Created a team spirit within the stores that resulted in increased sales, long-term empter CELL PHONE SALES REPRESENTATIVE, 20xx - 20xx

BCD CELL PHONE HUT, Fall River, MA

Partnered with a high-performing sales staff to provided quality customer service. Ser

Effectively delivered post-sale care services, exceeding clients' expectations in a composition of the compo

CDE CELLULAR SERVICES, Fall River, MA

Responded to billing inquiries, assisted in technical troubleshooting, and performed ra

Chosen to facilitate training in an outsourced call center.

EDUCATION

Bachelor of Arts in Communication (Major: Advertising), 20xx XYZ UNIVERSITY, Milwaukee, WI

REFERENCES

Excellent references provided upon request.

```
phoneRegex=re.compile(r"\d{3}-\d{4}")
mo=phoneRegex.findall(resume)
print(mo)
```

```
['508-555-5555', '508-555-1234']
```

We used findall() above so we can easily find all of the matches. If we used search() like we did earlier, it would only return the first match.

There is an important distinction between search() and findall(). The search() method returns Match Objects while the findall() method returns a list of strings.

If the regular expression string has 0 or 1 groups, then the findall() method will jstu return a list of strings which each string in the list is the text that was found.

However, with regex objects that have 2 or more groups, the following occurs.

import re

resume="""

JESSE KENDALL

123 Elm Street, Fall River, MA 02723, Cell: 508-555-5555, Home: 508-555-1234 twemel@cha

SUMMARY OF QUALIFICATIONS

Dedicated cell phone sales professional with demonstrated success in retail management

SALES SUCCESS

RETAIL STORE SALES MANAGER, 20xx - 20xx

ABC CELLULAR, Fall River, MA

Recruited, hired, trained, developed, and directed retail sales teams for two retail Al

Implemented a sales-tracking spreadsheet to replace a manual form writing process to in Developed innovative and effective marketing programs; exceeded store sales quotas.

Successfully managed one of the highest-producing ABC Wireless dealer locations in the Received several "Sales Manager of the Month" Awards.

Created a team spirit within the stores that resulted in increased sales, long-term emportant PHONE SALES REPRESENTATIVE, 20xx - 20xx

BCD CELL PHONE HUT, Fall River, MA

Partnered with a high-performing sales staff to provided quality customer service. Ser

Effectively delivered post-sale care services, exceeding clients' expectations in a composition of Dbtained significant business by delivering presale presentations to demonstrate new places of CUSTOMER SERVICE REPRESENTATIVE, 20xx - 20xx

CDE CELLULAR SERVICES, Fall River, MA

Responded to billing inquiries, assisted in technical troubleshooting, and performed ra

Chosen to facilitate training in an outsourced call center.

EDUCATION

Bachelor of Arts in Communication (Major: Advertising), 20xx XYZ UNIVERSITY, Milwaukee, WI

REFERENCES

Excellent references provided upon request.

```
phoneRegex=re.compile(r"(\d{3})-(\d{3}-\d{4})")
mo=phoneRegex.findall(resume)
print(mo)

[('508', '555-5555'), ('508', '555-1234')]
```

Now, instead of returning a list of strings, a list of tuples containing strings is returned. Each string in the tuple is the contents of each group.

4.1 Character Classes

We've already looked at one character class (). It represents any numeric digit between 0 and 9. Character classes are shortcuts that make our code easier to read and write.

| Shorthand character class | Represents |
|--------------------------------|---|
| Any numeric digit from 0 to 9. | |
| | Any character that is not a numeric digit from 0 to 9. |
| | Any letter, numeric digit, or the underscore character. (Think of the |
| | Any character that is not a letter, numeric digit, or the underscore |
| | Any space, tab, or newline character. (Think of this as matching "s |
| § | Any character that is not a space, tab, or newline. |

4.2 12 Days of Christmas Example

We can use regular expressions to find patterns where we have some number followed by some words.

```
import re
lyrics= "12 drummers drumming, 11 pipers piping, 10 lords a leaping, 9 ladies dancing,
xmasRegex=re.compile(r"\d+\s\w+")
print(xmasRegex.findall(lyrics))
```

['12 drummers', '11 pipers', '10 lords', '9 ladies', '7 swans', '6 geese', '5 golden',

4.3 Making Your Own Character Classes

Above we showed the existing shorthand character classes, but we can create our own character classes as well. Let's say we want to create a shorthand for vowels, then we can use r"[aeiouAEIOU]" for our Regex. If we want to make a negative character class, we can put in a ^ at the start of the square brackets.

```
import re
vowelRegex=re.compile(r"[aeiouAEIOU]")

print(vowelRegex.findall("Robocop eats baby food."))

doublevowelRegex=re.compile(r"[aeiouAEIOU]{2}")

print(doublevowelRegex.findall("Robocop eats baby food."))

consonantsRegex=re.compile(r"[^aeiouAEIOU]")

print(consonantsRegex.findall("Robocop eats baby food."))

['o', 'o', 'o', 'e', 'a', 'a', 'o', 'o']
['ea', 'oo']
['R', 'b', 'c', 'p', '', 't', 's', ', 'b', 'b', 'y', '', 'f', 'd', '.']
```