

Prime Straight Ring Type Striking Wrenches are designed to be struck by a hammer on the anvil area, specially designed for most rugged industrial application in order to loosed frozen nuts or to tighten fastener. Anvil are proportional to wrench opening size. Specially selected alloy steel & best suited heat treatment process follows for maximum durability for longer life and to withstand the severe working conditions. Industrial rust resistance black finish provides super finish and resistance to corrosion in industrial use.



Prime Straight Ring Type Slugging Wrench

WRENCH SIZE (A/F)		WRENCH SIZE (A/F)		HEAD DIA	HEAD THK.	LENGTH (MM)
METRIC	SAE	METRIC	SAE			
PART NO.	SIZE	PART NO.	SIZE			
PSM-19	19	PSI-25	3/4"	54	18	175
PSM-22	22	PSI-28	7/8"	54	18	175
PSM-24	24	PSI-29	15/16"	54	18	175
PSM-27	27	PSI-31	1.1/16"	54	18	175
PSM-29	29	PSI-32	1.1/8"	54	18	175
PSM-30	30	PSI-33	1.3/16"	68	22	210
PSM-32	32	PSI-34	1.1/4"	68	22	210
PSM-33	33	PSI-35	1.5/16"	68	22	210
PSM-35	35	PSI-36	1.3/8"	68	22	210
PSM-36	36	PSI-37	1.7/16"	68	22	210
PSM-38	38	PSI-38	1.1/2"	68	22	210
PSM-41	41	PSI-39	1.5/8"	80	28	245
PSM-43	43	PSI-40	1.11/16"	80	28	245
PSM-44	44	PSI-41	1.3/4"	80	28	245
PSM-46	46	PSI-42	1.13/16"	80	28	245
PSM-47	47	PSI-43	1.7/8"	80	28	245
PSM-50	50	PSI-45	2"	80	35	245
PSM-52	52	PSI-46	2.1/16"	102	35	285
PSM-44	55	PSI-47	2.3/16"	102	35	285
PSM-57	57	PSI-48	2.1/4"	102	35	285
PSM-60	60	PSI-50	2.3/8"	102	35	285
PSM-62	62	PSI-51	2.7/16"	102	35	285
PSM-63	63	PSI-52	2.1/2"	102	35	285
PSM-65	65	PSI-53	2.9/16"	102	40	285
PSM-67	67	PSI-54	2.5/8"	122	40	322
PSM-70	70	PSI-56	2.3/4"	122	40	322
PSM-71	71	PSI-57	2.13/16"	122	40	322
PSM-75	75	PSI-59	2.15/16"	122	40	322
PSM-76	76	PSI-60	3"	122	40	322
PSM-80	80	PSI-61	3.1/8"	122	40	322

WRENCH SIZE (A/F)		WRENCH SIZE (A/F)		HEAD DIA	HEAD THK.	LENGTH (MM)
METRIC	SAE	METRIC	SAE			
PART NO.	SIZE	PART NO.	SIZE			
PSM-85	85	PSI-63	3.1/8"	130	40	340
PSM-90	90	PSI-64	3.5/8"	136	45	350
PSM-95	95	PSI-65	3.3/4"	140	45	475
-	-	PSI-66	3.7/8"	158	50	415
PSM-100	100	PSI-67	4"	158	50	415
PSM-105	105	PSI-68	4.1/8"	164	50	450
PSM-110	110	PSI-69	4.1/4"	170	55	450
PSM-115	115	PSI-70	4.1/2"	175	55	465
PSM-120	120	PSI-72	4.3/4"	190	60	490
PSM-125	125	PSI-73	4.7/8"	200	60	510
PSM-130	130	PSI-74	5"	210	65	515
PSM-135	135	PSI-75	5.3/8"	222	65	540
PSM-140	140	PSI-76	5.1/2"	130	70	550
PSM-145	145	PSI-78	5.3/4"	130	70	565
PSM-150	150	PSI-80	6"	130	70	565
PSM-155	155	PSI-81	6.1/8"	130	70	565
PSM-160	160	PSI-82	6.1/4"	170	70	-
PSM-165	165	PSI-84	6.1/2"	270	70	635
PSM-170	170	PSI-86	6.3/4"	270	70	635
PSM-175	175	PSI-87	6.7/8"	270	70	635
PSM-180	180	PSI-89	7.1/8"	270	70	635
PSM-185	185	PSI-90	7.1/4"	295	75	680
PSM-190	190	PSI-92	7.1/2"	295	75	680
PSM-195	195	PSI-93	7.5/8"	295	75	680
PSM-200	200	PSI-95	7.7/8"	295	75	680
PSM-205	205	PSI-97	8.1/8"	295	75	680
PSM-210	210	PSI-98	8.1/4"	325	80	725
PSM-215	215	PSI-100	8.1/2"	325	80	725
PSM-220	220	PSI-101	8.5/8"	325	80	725
PSM-225	225	PSI-103	8.7/8"	325	80	725
PSM-230	230	PSI-105	9.1/8"	325	80	725