## **NUT RUNNERS (BIT SOCKETS) & CROWFOOT WRENCH**



## Nut Runners (Bit Sockets)

Prime Nut Runners are designed to be used with Pneumatic / Electrical Screwdrivers. These nut runners are available in standard length of 75,100 & 150 mm and can be manufactured as per customer requirement as well. These nut runners are available in standard type and can be manufactured with central magnet type, wall magnet type and spring loaded magnetic type and swivel type as well, as per application.



PART NO.	HEX DRIVE	ACROSS FLAT (MM)	SOCKET NOSE DIA (MM)	OAL (MM)
PNR-106	1/4"	6	11.0	75
PNR-106L	1/4"	6	11.0	100
PNR-106X	1/4"	6	11.0	150
PNR-107	1/4"	7	12.0	75
PNR-107L	1/4"	7	12.0	100
PNR-107X	1/4"	7	12.0	150
PNR-108	1/4"	8	13.0	75
PNR-108L	1/4"	8	13.0	100
PNR-108X	1/4"	8	13.0	150
PNR-109	1/4"	9	15.0	75
PNR-109L	1/4"	9	15.0	100
PNR-109X	1/4"	9	15.0	150
PNR-110	1/4"	10	16.0	75
PNR-110L	1/4"	10	16.0	100
PNR-110X	1/4"	10	16.0	150
PNR-111	1/4"	11	17.5	75
PNR-111L	1/4"	11	17.5	100
PNR-111X	1/4"	11	17.5	150
PNR-112	1/4"	12	18.5	75
PNR-112L	1/4"	12	18.5	100
PNR-112X	1/4"	12	18.5	150
PNR-113	1/4"	13	19.5	75
PNR-113L	1/4"	13	19.5	100
PNR-113X	1/4"	13	19.5	150
PNR-114	1/4"	14	20.5	75
PNR-114L	1/4"	14	20.5	100
PNR-114X	1/4"	14	20.5	150
PNR-117	1/4"	17	26.0	75
PNR-119	1/4"	19	28.0	75
PNR-121	1/4"	21	30.0	75
PNR-124	1/4"	24	38.0	75

<sup>\*</sup> We also manufacture Nut Runner with Fix, Swivel type for angular tightening and spring loaded magnet for bolt clearance on request.

## **Crowfoot Wrenches**



3/8" Square Drive

OAL (MM)	
OAL (MM)	
40	
40	
40	
40	
45	
45	
45	
֡֡֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜	

1/2" Square Drive

PART NO.	Size (MM)	OAL (MM)	
PCW-308	8	50	
PCW-309	9	50	
PCW-310	10	50	
PCW-311	11	50	
PCW-312	12	50	
PCW-313	13	50	
PCW-314	14	50	
PCW-315	15	55	
PCW-316	16	55	
PCW-317	17	55	
PCW-318	18	55	
PCW-319	19	55	
PCW-320	20	60	
PCW-321	21	60	
PCW-322	22	60	
PCW-324	24	65	
PCW-327	27	65	
PCW-330	30	70	
PCW-332	32	70	