



**PRIME** Click Type Torque Wrench are designed to give consistently accurate readings and rugged performance. We have Torque Wrenches Range from 2 NM to 2700 NM which is covered in 16 different models. Pre-set Type Torque Wrenches are available on request, specifically for use on production lines where many fasteners are to be tightened to the same torque value. **PRIME** Torque Wrenches are calibrated on precision Torque Tester and are traceable to NPLas per ISO 9000 norms.



TECHNICAL SPECIFICATION

Standard Type Model No.	Ratchet Type Model No.	Torque Range			Square Drive	OAL (MM)	Unit Weight
		NM	LB.FT	KGFM			
PTW-10	PTWR-10	2-14	2-10	0.2-1.4	3/8"	320	0.65
PTW-25	PTWR-25	5-35	5-25	0.5-3.5	3/8"	430	0.7
PTW-50	PTWR-50	10-70	8-50	1-7	1/2"	485	1.0
PTW-100	PTWR-100	25-135	20-100	3-14	1/2"	585	2.0
PTW-160	PTWR-160	50-220	40-160	5-23	1/2"	610	2.5
PTW-250	PTWR-250	70-340	50-250	7-35	1/2"	835	3.5
PTW-300	PTWR-300	80-400	60-300	8-40	3/4"	895	4.5
PTW-400	PTWR-400	135-540	100-400	14-56	3/4"	1120	8.0
PTW-500	PTWR-500	135-675	100-500	14-70	3/4"	1150	8.0
PTW-500S	PTWR-500S	135-780	100-560	14-78	3/4"	1150	8.0
PTW-600	PTWR-600	200-810	140-600	22-82	3/4"	1400	8.0
PTW-750	PTWR-750	475-1015	350-750	49-105	3/4"	1305	14.0
PTW-750S	PTWR-750S	475-1015	350-750	49-105	1"	1305	14.0
PTW-1000	PTWR-1000	540-1380	400-1000	55-140	1"	1305	18.0
PTW-1400	PTWR-1400	1000-1900	750-1400	105-195	1"	1450	19.0
PTW-2000	PTWR-2000	1350-2700	1000-2000	135-275	1"	1450	23.5

We also offer Torque Wrenches of following Types:

<b>Open Jaw Fixed Head Type:</b> Open jaw type fix head type Torque Wrenches are the most suitable for confined and pipe application. Torque Wrenches are available in different Across Flat sizes from 10 mm to 55 mm with torque pre-set to one particular value as per bolt torque capacity or customer requirement. These torque wrenches can be used directly on bolt, there is no need of socket.	
<b>Bi-Hex Ring Type</b> Bi-Ring head type fix head torque valueare available in different Across Flat sizes from 10 mm to 55 mm with torque pre-set to one value as per bolt torque capacity or customer requirement. These torque wrenches can be used directly on bolt,These torque wrench are best suitable for confined application.	
<b>Preset Torque Production Type</b> Presettypes of Torque Wrenches are designed specifically for use on production lines where all bolts are to be tightened to the same torque value. It improves working efficiency of workmen. Operation may not change the torque value itself, however torque may be changed on the torque calibration only.	