```sql
--task 1
BEGIN ;

SELECT * FROM booking WHERE booking_id = 2;

DELETE FROM booking WHERE booking_id = 2;

SELECT * FROM booking WHERE booking_id = 2 ;

COMMIT;


BEGIN ;

SELECT * FROM booking WHERE booking_id = 'abc';

DELETE FROM booking WHERE booking_id = 'abc';

SELECT * FROM booking;

ROLLBACK;

COMMIT;


-- task2

BEGIN;

SELECT * FROM flights WHERE flight_id = 1;
```

```sql
UPDATE flights  SET scheduled_departure = '2020-10-01' WHERE flight_id = 1;

SELECT * FROM flights WHERE flight_id = 1;

COMMIT;


BEGIN;

SELECT * FROM flights WHERE flight_id = 'abc';

UPDATE flights  SET scheduled_departure = '2020-10-01' WHERE flight_id = 'abc';

SELECT * FROM flights WHERE flight_id = 'abc';

ROLLBACK;

COMMIT;


--task 3

BEGIN;

SELECT * FROM booking b
JOIN booking_flight bf ON b.booking_id = bf.booking_id
JOIN flights f ON f.flight_id = bf.flight_id
WHERE f.flight_id = 15;

UPDATE booking b
SET price = b.price - 10
```

```sql
FROM booking_flight bf
JOIN flights f ON f.flight_id = bf.flight_id
WHERE b.booking_id = bf.booking_id
 AND f.flight_id = 15;



SELECT * FROM booking b
JOIN booking_flight bf ON b.booking_id = bf.booking_id
JOIN flights f ON f.flight_id = bf.flight_id
WHERE f.flight_id = 15;



COMMIT;



BEGIN;



SELECT * FROM booking b
JOIN booking_flight bf ON b.booking_id = bf.booking_id
JOIN flights f ON f.flight_id = bf.flight_id
WHERE f.flight_id = 'abc';

UPDATE booking b
SET price = b.price - 10
FROM booking_flight bf
JOIN flights f ON f.flight_id = bf.flight_id
WHERE b.booking_id = bf.booking_id
 AND f.flight_id = 'abc';



SELECT * FROM booking b
JOIN booking_flight bf ON b.booking_id = bf.booking_id
JOIN flights f ON f.flight_id = bf.flight_id
```

```sql
WHERE f.flight_id = 'abc';

ROLLBACK;

COMMIT;

--task 4

BEGIN;

SELECT * FROM passengers WHERE passenger_id = 1;

UPDATE passengers  SET last_name = 'Alan'
WHERE passenger_id = 1;

SELECT * FROM passengers WHERE passenger_id = 1;

COMMIT;


--task 5

BEGIN;

SELECT * FROM passengers;

INSERT INTO passengers(passenger_id, first_name, last_name, date_of_birth, gender,
country_of_citizenship, country_of_residence, passport_number, created_at, update_at)
VALUES(202,'Sasha', 'Go', '2025-01-01', 'Male', 'Russia', 'RU', '2-2', '2000-02-13', '2022-12-04');



INSERT INTO booking(booking_id, passenger_id, booking_platform, created_at, update_at, status, price)
VALUES(501,202, 'Kazak', '2024-01-01', '2023-12-20', 'Female', 1000);
```

```sql
SELECT * FROM booking WHERE booking_id = 501;

COMMIT;


--task 6

BEGIN;

SELECT b.booking_id, b.price, f.flight_no
FROM booking b
JOIN booking_flight bf ON b.booking_id = bf.booking_id
JOIN flights f ON f.flight_id = bf.flight_id
WHERE f.flight_id = 15;


UPDATE booking b SET price = price - 10
FROM flights f
JOIN booking_flight bf ON bf.booking_id = b.booking_id
WHERE f.flight_id = bf.flight_id
AND f.flight_id = 15;


SELECT b.booking_id, b.price, f.flight_no
FROM booking b
JOIN booking_flight bf ON b.booking_id = bf.booking_id
JOIN flights f ON f.flight_id = bf.flight_id
WHERE f.flight_id = 15;


COMMIT;

--task 7
BEGIN;
```

```sql
SELECT ba.* FROM baggage ba
JOIN booking b ON ba.booking_id = b.booking_id
JOIN passengers p ON p.passenger_id = b.passenger_id
WHERE p.passenger_id = 1;


UPDATE baggage ba SET weight_in_kg = 12
FROM booking b
JOIN passengers p ON p.passenger_id = b.passenger_id
WHERE ba.booking_id = b.booking_id
AND p.passenger_id = 1;


SELECT ba.* FROM baggage ba
JOIN booking b ON ba.booking_id = b.booking_id
JOIN passengers p ON p.passenger_id = b.passenger_id
WHERE p.passenger_id = 1;


COMMIT;


-- task 8


BEGIN;


SELECT b.* FROM booking b
JOIN passengers p
ON b.passenger_id = p.passenger_id
WHERE b.passenger_id = 15;
```

```sql
UPDATE booking b SET price = b.price * 0.9

FROM passengers p

WHERE p.passenger_id = b.passenger_id

AND b.passenger_id = 15;


SELECT b.* FROM booking b

JOIN passengers p

ON b.passenger_id = p.passenger_id

WHERE b.passenger_id = 15;


COMMIT;


BEGIN;


SELECT b.* FROM booking b

JOIN passengers p

ON b.passenger_id = p.passenger_id

WHERE b.passenger_id = 'abc';


UPDATE booking b SET b.price = b.price * 0.9

FROM passengers p

WHERE p.passenger_id = b.passenger_id

AND b.passenger_id = 'abc';


SELECT b.* FROM booking b

JOIN passengers p

ON b.passenger_id = p.passenger_id
```

```sql
WHERE b.passenger_id = 'abc';

ROLLBACK;

COMMIT;

--task 9

BEGIN;

SELECT * FROM booking_flight WHERE flight_id = 339;

UPDATE booking_flight SET flight_id = 62 WHERE flight_id = 339;

SELECT * FROM booking_flight WHERE flight_id = 62;

COMMIT;
```