

eSIM Access API

Partner API

Deliver eSIM data plan packages via the [eSIM Access](#) HTTP API. [Step by step overview](#).

Quick Start

1. [Create an account](#) at **eSIM Access**
2. [Deposit funds](#) for testing and refunding
3. [Copy your AccessCode](#)
4. Add your `AccessCode` below and run in your terminal or powershell to make your first API call

bash

```
curl --location --request POST 'https://api.esimaccess.com/api/v1/open/balance/query'
--header 'RT-AccessCode: YOUR_ACCESS_CODE'
--data ''
```

powershell

```
curl -Uri "https://api.esimaccess.com/api/v1/open/balance/query" `
-Method POST `
-Headers @{ "RT-AccessCode"="YOUR_ACCESS_CODE" } `
-Body ""
```

Version - V1

Version 1 - OCT 11, 2022 - Initial Release

Version 1.1 - JUN 6, 2023 - Updates:

- Single Profile ordering changed to batch Profile ordering [via Order Profiles request]
- Offline post-paying changed to online pre-paying [via Order Profiles request]
- esim/list endpoint removed, status function found in esim/query
- Cancel, Suspend, Unsuspend and Revoke functions added
- Country filter added to Query All Data Packages
- Webhook for order status checking added

Version 1.2 - JUL 26, 2023 - Updates:

- Added Top Up endpoint for adding data to existing eSIM profiles

- Query available Top Up plans with `iccid` or `packageCode`
- `Price` and `amount` optional when ordering a profile

Version 1.3 - DEC 12, 2023 - Updates:

- Adds `slug` as an alias to package code
- Adds additional package data like `speed`, `network`, and `favorite`

Version 1.4 Mar 12, 2024 - Updates:

- Add SMS send to `iccid` ability
- Adds ability to write webhooks

Version 1.5 July 28, 2024 - Updates:

- Adds **daypass plans** with `periodNum` parameter in Order Profiles
- Adds rate limit of 8 requests per second

Version 1.6 Dec 20, 2024 - Updates:

- Adds fields `supportTopUpType` and `ipExport`

Update Mar 8, 2025

- Adds additional webhook for low balance now at 25% and 10% remaining
- Adds balance check endpoint with last updated date

Update Mar 19, 2025

- Adds two new endpoints for **balance check** and **current regions**

Update May 28, 2025

- Add new webhooks - `SMDP_EVENT` which give SM-DP+ server events

Update July 24, 2025

- Top Up packages can be added after esim is created.

Update Dec 2, 2025

- Adds `datatype` search `fuppolicy` result when viewing data packages.

Environments and Endpoints

Sandbox:

There is no Sandbox environment. Cancel eSIM orders as needed in our live environment. **Request** funds for testing.

Production:

`https://api.esimaccess.com`

Image assets:

<https://static.redteago.com/>

Authentication

Request your API keys in your [online account](#).

Standards

Time codes are presented in UTC. Country codes use Alpha-2 ISO. Data values are in Bytes.

Status

[Server status](#) tracked via postman monitors.

Rate Limit

8 API request per second are allowed.

Error Codes

Code	Message
000001	Server error
000101	Request header (mandatory) is null
000102	Wrong request header format
000103	This https request method (get/post) is not supported
000104	Request in invalid JSON format
000105	Request parameters (mandatory) are not contained
000106	Request parameter (mandatory) is null
000107	The length of the request parameter does not meet the requirement.
101001	The timestamp of the request has expired.
101002	This IP is in the blacklist.

200002	This operation is not allowed due to the order status.
200005	Package <code>price</code> error. Check price.
200006	Total order price <code>amount</code> is wrong. Check prices.
200007	Insufficient account balance
200008	Order parameters error, please contact customer service.
200009	Abnormal order status
200010	Profile is being downloaded for the order.
200011	Insufficient available Profiles for the package, please contact the customer service.
310201	The bundle.code does not exist.
310211	The data_plan_location.id does not exist.
310221	The currencyId does not exist.
310231	The carrierId does not exist.

AUTHORIZATION API Key

Key RT-AccessCode

Value

API

Authentication methods

Key in Header

Use the `AccessCode` as the API key in header authentication method.

HMAC Signature

HMAC-SHA256 signature calculation (hash-based message authentication code) uses a secret key to generate a unique signature for a message. The signature is then used to verify the authenticity of the message.

Request Header Authenticaion

Name	Description
RT-AccessCode	Access Key found in your account, used in signData
RT-RequestID	Request ID with the uuid.v4() method generates a new random UUID (Universally Unique Identifier).
RT-Signature	Signature (HexString) of the request
RT-Timestamp	Request sending timestamp (in milliseconds) as a string
SecretKey	Used in the signature request, found in your account.

Calculation by HMAC-SHA256:

- signData = Timestamp + RequestID + AccessCode + RequestBody
- signature = HMACSHA256(signData, SecretCode)

java

```
// Concatenate RT-Timestamp, RT-RequestID, RT-AccessCode, and requestBody into one string.
// This string, signStr, will be used as the data to hash in the HMAC-SHA256 function.
String signStr = RT-Timestamp + RT-RequestID + RT-AccessCode + requestBody
// Generate an HMAC-SHA256 hash of the signStr using the secretKey.
// The resulting hash is converted to all lowercase characters for standardization purposes.
sign = HMACSha256(signStr, secretKey).toLowerCase();
```

Signature Example

Plain Text

```
Timestamp=1628670421
RequestID=4ce9d9cdac9e4e17b3a2c66c358c1ce2
AccessCode=11111
SecretKey=1111
RequestBody={"imsi":"326543826"}
signStr=16286704214ce9d9cdac9e4e17b3a2c66c358c1ce211111{"imsi":"326543826"}
Signature=7EB765E27DF5373DEA2DBC8C41A7D9557743E46C8054750F3D851B3FD01D0835
```

AUTHORIZATION API Key

This folder is using API Key from collection [eSIM Access API](#)

POST Get All Data Packages



<https://api.esimaccess.com/api/v1/open/package/list>

Request a list of all the available data packages offered. Optionally filter by country or region.

Additionally request all of the Top Up plans available for a specific `packageCode` , `slug` or `ICCID` . Specific top ups work with specific plans. In general, countries can be reloaded with same country top up and region with same region top up.

Request Parameters

Name	Type	MOC	Description	Example
<code>locationCode</code>	String	optional	Filter by Alpha-2 ISO Country Code <code>!RG</code> = Regional <code>!GL</code> = Global	<code>JP</code> <code>!GL</code> <code>!RG</code>
<code>type</code>	String	optional	<code>BASE</code> - Default product list <code>TOPUP</code> - Top up product list	<code>BASE</code> <code>TOPUP</code>
<code>packageCode</code>	String	optional	Used with <code>TOPUP</code> to view top up package for a <code>packageCode</code>	<code>JC016</code>
<code>slug</code>	String	optional	<code>slug</code> is alias of <code>packageCode</code>	<code>AU_1_7</code>
<code>iccid</code>	String	optional	Include <code>iccid</code> with <code>TOPUP</code> to see available TOPUP plans	<code>48584984747372838</code>
<code>dataType</code>	String	optional	<code>2</code> = Day Pass	<code>2</code>

Reponse Parameters

Name	Type	MOC	Description	Example
<code>success</code>	String	mandatory	<code>true</code> : succeeded <code>false</code> : failed	<code>true</code>
<code>errorCode</code>	String	optional	<code>null</code> or <code>0</code> when successful. Error code when failed.	<code>null</code>
<code>errorMessage</code>	String	optional	Error code explanation	<code>null</code>
<code>obj</code>	Object	optional	<code>null</code> : failed. Success includes: <code>packageList</code>	

Domain	Type	MOC	Description	Example
<code>packageList</code>	List	mandatory	Available data packages, including: <code>packageCode</code> <code>name</code> <code>price</code> <code>currencyCode</code> <code>volume</code> <code>unusedValidTime</code> <code>duration</code> <code>durationUnit</code> <code>location</code> <code>description</code> <code>activeType</code>	
<code>packageCode</code>	String	mandatory	Package code	<code>JC016</code>
<code>slug</code>	String	mandatory	Package alias	<code>AU_1_7</code>
<code>name</code>	String	mandatory	Package name	<code>Asia 11 countries 1GB 30 Days</code>
<code>price</code>	Integer	mandatory	Package price, value * 10,000	<code>10000</code>

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

Body raw (json)

```
json

{
  "locationCode": "",
  "type": "TOPUP",
  "slug": "VN_0.1_7",
  "packageCode": "",
  "iccid": ""
}
```

POST Order Profiles



Order profiles individually or in batch. After successful ordering, the SM-DP+ server will return the `OrderNo` and allocate profiles asynchronously for the order.

To make an order

1. Provide a unique `transactionId` for each order. Duplicate `transactionId` will be identified as the same request.
2. Provide the `packageCode` or `slug` of the data package(s) you will order.
3. Provide the `count` for each package needed.
4. Optional price check: Provide the `price` and multiply with `count` for the total cost to provide the `amount`.
5. Optional period: For daily plans include the `periodNum` corresponding to the number of days of the plan.

A successful order will generate an `orderNo`. Query all the allocated profiles in the endpoint `/api/v1/open/esim/query`

Request Parameters

Name	Type	MOC	Description	Example
<code>transactionId</code>	String	mandatory	User generated unique transaction ID. Max 50 chars, utf8mb4. If the request is retired, it needs to be contained; otherwise, a new transaction will be created.	<code>ABC-210-2s7Fr</code>
<code>amount</code>	Long	optional	Total order amount	<code>20000</code>
<code>packageInfoList</code>	List	mandatory	<code>packageCode</code> or <code>slug</code> , <code>count</code> , <code>price</code>	

Domain	Type	MOC	Description	Example
<code>packageCode</code>	String	mandatory	Order with <code>slug</code> or <code>packageCode</code> (prefer slug)a	<code>AU_1_7</code> <code>JC016</code>
<code>count</code>	Integer	mandatory	Number of packages to be ordered	<code>2</code>
<code>price</code>	Integer	optional	Package price, value * 10,000 (10000 = \$1.00)	<code>10000</code>
<code>periodNum</code>	Integer	optional	Days of a daily plan. From 1-365.	<code>7</code>

Response Parameters

Name	Type	MOC	Description	Example
<code>success</code>	String	mandatory	<code>true</code> : success <code>false</code> : failed	<code>true</code>
<code>errorCode</code>	String	optional	<code>null</code> or <code>0</code> when successful. Error code when failed.	<code>null</code>
<code>errorMessage</code>	String	optional	Error code explanation	<code>null</code>
<code>obj</code>	Object	optional	Includes: <code>orderNo</code>	

Domain	Type	MOC	Description	Example
<code>orderNo</code>	String	mandatory	Order number	<code>B221020100753</code> <code>11</code>

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

Body raw (json)

```
json
```

```
{
  "transactionId": "your_txn_id",
  "amount": 15000,
  "packageInfoList": [{
    "packageCode": "7aa948d363",
    "count": 1,
    "price": 15000
  }]
}
```

POST Query All Allocated Profiles



<https://api.esimaccess.com/api/v1/open/esim/query>

Query all eSIM profiles for both new eSIMs, and in use eSIMs.

Get New Orders

Query by `orderNo` or `startTime` and `endTime` range with paging options.

Use `orderNo` to request newly ordered eSIM profiles. The response will return the eSIM payload after all the allocated profiles are asynchronously allocated by the server. Expect wait times of up to **30 seconds**. You can **order up to 30 eSIMs in one batch** and all profiles will be returned with `orderNo` results.

If the profiles are not yet ready for download, the error will be returned (error code will be `200010`, meaning SM-DP+ is still allocating profiles for the order).

Use the webhook notification `"notifyType": "ORDER_STATUS"` to inform your first get eSIM request. `ORDER_STATUS` webhook will trigger when the eSIM profiles have been created and ready for retrieval.

Get Status of Existing Orders

Use `esimTranNo`, `orderNo`, or `iccid` to request the status of an eSIM including its current `orderUsage` and `eSIMStatus`. Or use `startTime` and `endTime` range. `esimTranNo` and `iccid` will return a **single eSIM**, while `orderNo` will return the **batch order of eSIMs**.

Important Note: The value of `orderUsage` is updated within **2-3 hours after eSIM is in use**.

Note: `iccids` are reused, thus the suggested method of eSIM status check is via `esimTranNo`.

Note: Rate limiting limits to 8 requests per second.

Understanding eSIM Profile Status

Results of several parameters can identify the current state of any eSIM profile. For example:

eSIM Status	smdpStatus	esimStatus	orderUsage	eid
New	RELEASED	GOT_RESOURCE	0	" "
Onboard	ENABLED	IN_USE GOT_RESOURCE	0	"890...222"
In Use	ENABLED DISABLED	IN_USE	123	"890...222"
Depleted	ENABLED DISABLED	USED_UP	999	"890...222"
Deleted	DELETED	USED_UP IN_USE	999	"890...222"

Request Parameters

Name	Type	MOC	Description	Example
orderNo	String	optional	Order number	B2210206381924
iccid	String	optional	eSIM ICCID	89852246280001113119
startTime	String	optional	Starting time (ISO UTC time)	2010-06-30T01:20+00:00
endTime	String	optional	End time (ISO UTC time)	2010-06-30T02:20+00:00
pager	PageParam	mandatory	Page parameters: pageSize pageNum	

Domain	Type	MOC	Description	Example
pageSize	Integer	mandatory	Page size, value range: [5, 500]	10
pageNum	Integer	mandatory	Page number, value range: [1, 10000]	1

Response Parameters

Name	Type	MOC	Description	Example
<code>success</code>	String	mandatory	<code>true</code> : succeeded <code>false</code> : failed	<code>true</code>
<code>errorCode</code>	String	optional	<code>null</code> or <code>0</code> when successful. Error code when failed	<code>null</code>
<code>errorMessage</code>	String	optional	Explanation of the error code	<code>null</code>
<code>obj</code>	Object	optional	Includes: <code>esimList</code> <code>pager</code>	

Domain	Type	MOC	Description	Example
<code>pager</code>	PageParam	mandatory	Includes: <code>pageSize</code> <code>pageNum</code>	
<code>esimList</code>	List	mandatory	List of eSIM Profiles, including: <code>esimTranNo</code> <code>orderNo</code> <code>imsi</code> <code>iccid</code> <code>ac</code> <code>qrCodeUrl</code> <code>smdpStatus</code> <code>eid</code> <code>activeType</code> <code>expiredTime</code> <code>totalVolume</code> <code>totalDuration</code> <code>durationUnit</code> <code>orderUsage</code> <code>esimStatus</code> <code>packageList</code>	

PageParam Domain	Type	MOC	Description	Example
<code>pageSize</code>	Integer	mandatory	Page size, range: [5, 500]	<code>10</code>
<code>pageNum</code>	Integer	mandatory	Page number, value range: [1, 10000]	<code>1</code>
<code>total</code>	Long	mandatory	Total number of	<code>120</code>

Local	Long	Mandatory	Local number of Profiles	220
-------	------	-----------	--------------------------	-----

eSIM Domain	Type	MOC	Description	Example
esimTranNo	String	mandatory	eSIM transaction number	22102706381912
orderNo	String	mandatory	Order number	B22102706381924
imsi	String	optional	IMSI	454006109846571
iccid	String	optional	ICCID	89852245280000942210
msisdn	String	optional	MSISDN	xxxxx
smsStatus	Integer	mandatory	0 Does not support SMS 1 Can accept SMS sent by mobile phones and API 2 Only SMS sent by API is acceptable.	0
dataType	Integer	mandatory	1 .Data in Total 2 .Daily Limit	1

eSIM Domain	Type	MOC	Description	Example
packageCode	String	mandatory	Package ID	CKH179
duration	Integer	mandatory	Valid period of the order	7
volume	Long	mandatory	Data volume (in bytes) in the order	1073741824
locationCode	String	mandatory	Country code of plan	JP

AUTHORIZATION API Key

This request is using API Key from collection **eSIM Access API**

Body raw (json)

json
{

```
{
  "orderNo": "B25080914060004",
  "iccid": "",
  "pager": {
    "pageNum": 1,
    "pageSize": 50
  }
}
```

POST Cancel Profile



<https://api.esimaccess.com/api/v1/open/esim/cancel>

Cancel an inactive, unused eSIM profile.

The eSIM `price` is refunded to your balance.

This operation is available when `esimStatus` is `GOT_RESOURCE` and `smdpStatus` is `RELEASED` meaning the eSIM was created, but not installed on a device.

Cancel endpoint not available once user has **used data** with the eSIM.

It is recommended to use the `esimTranNo` when making a cancel request.

Use the Cancel Profile endpoint to make refunds, test eSIM purchases and return the value of unused eSIM to your account balance.

Request Parameters

Name	Type	MOC	Description	Example
<code>iccid</code>	String	optional	eSIM ICCID	<code>89852246280001113119</code>
<code>esimTranNo</code>	String	optional	get from "Query All Allocated Profiles" use "iccid" or "esimTranNo", can't be blank at the same time recommended.	<code>24111319542101</code>

Response Parameters

Name	Type	MOC	Description	Example
<code>success</code>	String	mandatory	<code>true</code> : succeeded <code>false</code> : failed	<code>true</code>
<code>errorCode</code>	String	optional	<code>null</code> or <code>0</code> when successful. Error code when failed	<code>null</code>
<code>errorMessage</code>	String	optional	Explanation of the error code	<code>null</code>
<code>obj</code>	Object	optional	Includes	<code>{}</code>

AUTHORIZATION API Key

This request is using API Key from collection **eSIM Access API**

Body raw (json)

json

```
{
  "esimTranNo": "23120118156818"
}
```

POST Suspend Profile



<https://api.esimaccess.com/api/v1/open/esim/suspend>

Request to suspend or pause data service to an esim profile.

Request Parameters

Name	Type	MOC	Description	Example
<code>iccid</code>	String	optional	eSIM ICCID	<code>89852246280001113119</code>
<code>esimTranNo</code>	String	optional	get from "Query All Allocated Profiles" use "iccid" or "esimTranNo", can't be blank at the same time recommended.	<code>24111319542101</code>

Response Parameters

Name	Type	MOC	Description	Example
<code>success</code>	String	mandatory	<code>true</code> : succeeded <code>false</code> : failed	<code>true</code>
<code>errorCode</code>	String	optional	<code>null</code> or <code>0</code> when successful. Error code when failed	<code>null</code>
<code>errorMessage</code>	String	optional	Explanation of the error code	<code>null</code>
<code>obj</code>	Object	optional	Includes	<code>{}</code>

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

Body raw (json)

json

```
{
  "iccid": "89852245280001138065"
}
```

<https://api.esimaccess.com/api/v1/open/esim/unsuspend>

Request to unsuspend or reactivate data service to an esim profile.

Request Parameters

Name	Type	MOC	Description	Example
<code>iccid</code>	String	optional	eSIM ICCID	<code>89852246280001113119</code>
<code>esimTranNo</code>	String	optional	get from "Query All Allocated Profiles" use "iccid" or "esimTranNo", can't be blank at the same time recommended.	<code>24111319542101</code>

Response Parameters

Name	Type	MOC	Description	Example
<code>success</code>	String	mandatory	<code>true</code> : succeeded <code>false</code> : failed	<code>true</code>
<code>errorCode</code>	String	optional	<code>null</code> or <code>0</code> when successful. Error code when failed	<code>null</code>
<code>errorMessage</code>	String	optional	Explanation of the error code	<code>null</code>
<code>obj</code>	Object	optional	Includes	<code>{}</code>

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

Body raw (json)

```
json
```

```
{  
  "iccid": "89852245280001138065"  
}
```

POST Revoke Profile



<https://api.esimaccess.com/api/v1/open/esim/revoke>

Request to close and remove an active eSIM and data plan. Non-refundable.

Request Parameters

Name	Type	MOC	Description	Example
iccid	String	optional	eSIM ICCID	89852246280001113119
esimTranNo	String	optional	get from "Query All Allocated Profiles" use "iccid" or "esimTranNo", can't be blank at the same time recommended.	24111319542101

Response Parameters

Name	Type	MOC	Description	Example
success	String	mandatory	true : succeeded false : failed	true
errorCode	String	optional	null or 0 when successful. Error code when failed	null
errorMessage	String	optional	Explanation of the error code	null
obj	Object	optional	Includes	{}

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

Body raw (json)

json

```
{
  "iccid": "89852245280001138065"
}
```

POST Balance Query



<https://api.esimaccess.com/api/v1/open/balance/query>

Query the `balance` of a merchant account. Balance is used when ordering data profiles.

Request Parameters

None.

Reponse Parameters

Name	Type	MOC	Description	Example
<code>success</code>	String	mandatory	<code>true</code> : succeeded <code>false</code> : failed	<code>true</code>
<code>errorCode</code>	String	optional	<code>null</code> or <code>0</code> when successful. Error code when failed.	<code>null</code>
<code>errorMessage</code>	String	optional	Explanation of the error code	<code>null</code>
<code>obj</code>	Object	optional	Includes: <code>balance</code>	
Domain	Type	MOC	Description	Example
<code>balance</code>	Long	mandatory	Merchant balance, expressed *10000 (100000 = \$10.00)	<code>100000</code>

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

POST Top Up



<https://api.esimaccess.com/api/v1/open/esim/topup>

Before making a top up, it is recommended to query the available top up plans (Get All Data Packages endpoint) for a specific `iccid`, `esimTranNo` or `packageCode` first. This will give you available top up packages specific to this eSIM. [Learn more about top ups.](#)

The top up endpoint allows an existing installed eSIM to be loaded with a new plan. To top up the plan, you need its ICCID or esimTranNo and the **compatible** top up data plan `packageCode`.

Top ups can be requested while the eSIM is in New, In Use or Depleted status, but not after eSIM expiry.

Request Parameters

Name	Type	MOC	Description	Example
<code>iccid</code>	String	optional	eSIM ICCID (deprecated, use <code>esimTranNo</code>)	<code>89852246280001113119</code>
<code>esimTranNo</code>	String	optional	get from "Query All Allocated Profiles" use "iccid" or "esimTranNo", can't be blank at the same time recommended.	<code>24111319542101</code>
<code>packageCode</code>	String	required	Use a recharge <code>packageCode</code> starting with "TOPUP_" or use <code>slug</code> Learn more	<code>TOPUP_SM001AU_1_7</code>
<code>amount</code>	String	optional	Price of package, if used will be	<code>10000</code>

Response Parameters

obj	Type	MOC	Description	Example
<code>transactionId</code>	String	required	Transaction ID returned	<code>TXN-123</code>
<code>iccid</code>	String	required	ICCID of the eSIM	<code>89852245280001354019</code>
<code>expiredTime</code>	Long	required	New date of package expiry	<code>2023-08-17T17:01:37+0000</code>
<code>totalVolume</code>	Long	required	New volume of data	<code>4294967296</code>
<code>totalDuration</code>	Integer	required	New duration in days	<code>28</code>
<code>orderUsage</code>	Long	required	Total data usage	<code>207239584</code>

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

Body raw (json)

json

```
{
  "esimTranNo": "",
  "iccid": "89852000263213655345",
  "packageCode": "TOPUP_JC172",
  "transactionId": "1747191693771_topup_partner7"
}
```

POST Set Webhook



<https://api.esimaccess.com/api/v1/open/webhook/save>

Set or update your webhook URL via an API call. You can find the result in your console account [here](#).

You can also view the currently set webhook with the following endpoint:

`/api/v1/open/webhook/query`

AUTHORIZATION API Key

This request is using API Key from collection **eSIM Access API**

Body raw (json)

json

```
{"webhook": "https://webhook.endpoint.site/unique-webhook"}
```

POST Send SMS



<https://api.esimaccess.com/api/v1/open/esim/sendSms>

This endpoint is used to send SMS to an eSIM via `iccid` or `esimTranNo`. Supported by some networks. Only installed eSIMs that supports receiving SMS will work.

The `smsStatus` parameter in the `/order` and `/package` endpoints indicates whether the eSIM supports receiving SMS (`"smsStatus": 1` or `2`). There is currently no cost for SMS delivery.

Request Parameters

Name	Type	MOC	Description	Example
<code>iccid</code>	String	optional	eSIM ICCID	<code>89852246280001113119</code>
<code>esimTranNo</code>		optional	get from "Query All Allocated Profiles" use "iccid" or "esimTranNo", can't be blank at the same time recommended.	<code>24111319542101</code>
<code>message</code>	String(500)	required	SMS message, up to 500 characters.	"Thank you for using our eSIM service"

AUTHORIZATION API Key

This request is using API Key from collection **eSIM Access API**

Body raw (json)

json

```
{
  "esimTranNo": "23072017992029",
  "message": "Your Message!"
}
```

POST Usage Check



<https://api.esimaccess.com/api/v1/open/esim/usage/query>

Check the data usage of up to 10 eSIMs via their `esimTranNo`. Returns the amount of `dataUsage`, the `totalData` in the plan, and the `lastUpdateTime` timestamp of the most recent data used value update.

Important Note: Data usage is updated **every 2-3 hours** and is not real time.

Field	Type	Description	Example
<code>esimTranNo</code>	String	eSIM transaction number	<code>23072017992029</code>
<code>dataUsage</code>	Long	Data usage in Bytes	<code>1453344832</code>
<code>totalData</code>	Long	Total data in Bytes	<code>5368709120</code>
<code>lastUpdateTime</code>	String	The timestamp for the last call record update. For file-based records, this is the last full hour of settlement; for carrier data usage notifications, it is the settlement time recorded in the notification; for the carrier's real-time call record API, it is the time when the API was called.	<code>2025-03-19T18:00:00+0000</code>

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

Body raw (json)

json

```
{
  "esimTranNoList": ["25030303480009"]
}
```

POST Supported Regions



<https://api.esimaccess.com/api/v1/open/location/list>

Check our currently supported countries and plan codes.

Field	Type	Description	Example
<code>code</code>	String	Region code	<code>ES</code> <code>NA-3</code>
<code>name</code>	String	Region name	<code>Spain</code> <code>North America</code>
<code>type</code>	Integer	Region type: 1 for single-country, 2 for multi-country	<code>1</code>
<code>subLocation</code>	List	Sub-regions (exists only when type = 2)	

Each `SubLocation` object contains:

Field	Type	Description	Example
<code>code</code>	String	Region code	
<code>name</code>	String	Region name	

AUTHORIZATION API Key

This request is using API Key from collection [eSIM Access API](#)

Body raw (json)

json

```
{}
```

Webhooks

Endpoint Setup

Adding your webhook the first time will trigger a test webhook send. If you have a correctly working endpoint, you will receive an `CHECK_HEALTH` event. If our test send fails, your endpoint cannot be saved. To check a valid endpoint try <https://webhook.site/>

```
{"notifyType":"CHECK_HEALTH","content":{"orderNo":"1234567890","orderStatus":"Test"}} **
```

Set your webhook URL to receive POST requests** **in your account.**

The notifications contain a `notifyType` field indicating the event category and a `content` object with specific details. Here are the types you can expect:

1. `ORDER_STATUS`
 - a. **Trigger:** Sent when an eSIM is created and ready for retrieval.
 - b. **Key** `content` **field:** `orderStatus` will be `"GOT_RESOURCE"`.
 - c. **Example Use:** Used to know when your eSIM order is ready for download.
2. `SMDP_EVENT`
 - a. **Trigger:** Sent during real-time eSIM profile lifecycle events as they occur on the SM-DP+ server.
 - b. **Key** `content` **fields:**
 - i. `eid` : eUICC identifier of the device.
 - ii. `iccid` : ID of the eSIM.
 - iii. `esimStatus` : Current eSIM state (typically `GOT_RESOURCE` during provisioning, `IN_USE` when active).
 - iv. `smdpStatus` : SM-DP+ server status indicating the specific operation:
 - a. `DOWNLOAD` : eSIM profile is being downloaded to the device.
 - b. `INSTALLATION` : eSIM profile is being installed on the device.
 - c. `ENABLED` : eSIM has been activated/enabled on the device.
 - d. `DISABLED` : eSIM profile has been deactivated/disabled on the device..
 - e. `DELETED` : eSIM profile has been removed from the device.
 - c. **Example Use:** Track real-time eSIM provisioning progress and profile state changes for detailed lifecycle monitoring.
3. `ESIM_STATUS`
 - a. **Trigger:** Sent when the status of an individual eSIM changes after it has been allocated. This covers various lifecycle events.
 - b. **Key** `content` **fields:**
 - i. `esimStatus` : Indicates the current state. Common values observed include:
 - a. `IN_USE` : The eSIM has been installed/activated on a device.
 - b. `USED_UP` : The eSIM data allowance has been fully consumed.
 - c. `USED_EXPIRED` : The eSIM data is used up, and expired.
 - d. `UNUSED_EXPIRED` : The eSIM expired with data remaining.

e. `CANCEL` : The eSIM has been canceled / refunded.

f. `REVOKED` : The eSIM profile has been revoked.

ii. `smdpStatus` : SM-DP+ server status (e.g., `ENABLED` , `DISABLED` , `RELEASED` , `DELETED` , `INSTALLATION`).

c. **Example Use:** Track activation, data exhaustion, expiration, or cancellations for specific eSIMs and notify customers.

4. `DATA_USAGE`

a. **Trigger:** 3 data usage webhooks will be sent when reaching 50% (0.5) data used, 80%(0.8) data used and 90%(0.9) data used.

b. **Key** `content` **fields:**

i. `totalVolume` : Total data allowance in bytes.

ii. `orderUsage` : Data used so far in bytes.

iii. `remain` : Remaining data in bytes.

iv. `remainThreshold` : Values can be: 0.5, 0.2 and 0.1

c. **Example Use:** Proactively notify end-users about low data balance.

5. `VALIDITY_USAGE`

a. **Trigger:** Sent when the remaining validity period of an active eSIM reaches 1 day.

b. **Key** `content` **fields:**

i. `remain` : The remaining validity duration (e.g., 1).

ii. `durationUnit` : The unit for the duration (e.g., "DAY").

iii. `expiredTime` : The exact timestamp when the eSIM will expire.

iv. `totalDuration` : The original validity duration.

c. **Example Use:** Warn end-users that their plan is about to expire.

IP Whitelist

For additional security, you can whitelist the following sender IPs:

- `3.1.131.226`
- `54.254.74.88`
- `18.136.190.97`
- `18.136.60.197`
- `18.136.19.137`

Note: The `content` object structure may vary slightly. Always inspect the received payload to understand all available fields for each `notifyType` .

[Look at our example webhook sending and test trigger form.](#)

json

```
{
  "notifyType": "ORDER_STATUS",
  "content": {
    "orderNo": "B23072016497499",
    "status": "NOT_ACTIVATED"
```

```
      "orderStatus": "GOT_RESOURCE"
    }
  }
}
```

json

```
{
  "notifyType": "SMDP_EVENT",
  "eventGenerateTime": "2025-09-11T13:28:09+0000",
  "notifyId": "5fcc219e32dc484598d3fd700cf3738d",
  "content": {
    "eid": "89049032007108882600137544319616",
    "iccid": "8997250230000292199",
    "esimStatus": "GOT_RESOURCE",
    "smdpStatus": "DOWNLOAD",
    "orderNo": "B25091113270004",
    "esimTranNo": "25091113270004".
  }
}
```

json

```
{
  "notifyType": "DATA_USAGE",
  "eventGenerateTime": "2025-07-21T10:57:28Z",
  "notifyId": "f776267e8d6745db8cc316e4c146ea0c",
  "content": {
    "orderNo": "B25052822150009",
    "transactionId": "unique_id_from_partner",
    "esimTranNo": "25052822150009",
    "iccid": "8943108170001029631",
    "totalVolume": 53687091200,
    "orderUsage": 48335585458.
  }
}
```

json

```
{
  "notifyType": "VALIDITY_USAGE",
  "content": {
    "orderNo": "B23072016497499",
    "transactionId": "Your_txn_id",
    "iccid": "894310817000000003",
    "durationUnit": "DAY",
    "totalDuration": 30,
    "expiredTime": "2024-01-11T08:10:19Z",
    "remain": 1
  }
}
```

json

```
{
  "notifyType": "ESIM_STATUS",
  "eventGenerateTime": "2025-08-09T00:23:45Z",
  "notifyId": "4038b3dfb1b050bf9f02501df67284f3",
  "content": {
    "orderNo": "B25080823490018",
  }
}
```

```
"esimTranNo": "25080323490020",  
"transactionId": "e23111e4d07746889c7bce41cf3f1b16",  
"iccid": "89852000263413436720",  
"esimStatus": "CANCEL",  
"esimStatus": "CANCEL"
```

AUTHORIZATION API Key

This folder is using API Key from collection [eSIM Access API](#)