

MyProxyApi - Private Dedicated Proxy Reseller API

Unlock seamless reselling capabilities with the Proxy Reseller API, designed exclusively for MyProxyApi partners. This robust API empowers users to effortlessly integrate and resell proxy plans directly on their websites, automating both purchase processes and order management.

Tailored for simplicity, our API ensures a straightforward implementation process, accessible to programmers of all skill levels. Backed by comprehensive documentation, the Proxy Reseller API streamlines your reselling operations, enhancing efficiency and scalability.

Our API provides a comprehensive suite of proxy solutions, including:

- Datacenter Proxies
- ISP Proxies
- Premium ISP Proxies
- Static Residential Proxies
- Residential Rotating Proxies
- Mobile Proxies

AUTHORIZATION Bearer Token

General

Upon registering on our Partners Reseller Program, you will receive a unique Secret Key. It's crucial to securely store this Secret Key, as it serves as a key component in accessing our API.

Secure Storage:

- **Security Reminder:** Ensure to keep your Secret Key confidential and stored securely. It's recommended to store it in a safe location to prevent unauthorized access.

IMPORTANT: You will not be able to use MyProxyApi - Proxy Reseller API while a Partner manager didn't give your Secret Key.

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

POST Get Auth Token

https://reseller.myproxyapi.com/api/v1/getToken

Generating Bearer Token:

1. **Secret ID Usage:** The Secret Key is exclusively used in the `getToken` endpoint. This endpoint is specifically designed for generating a Bearer Token.
2. **Bearer Token Usage:** Once you've obtained the Bearer Token using your Secret ID, you will use this token for authentication in subsequent API calls.

Authorization in API Calls:

- **Bearer Token:** For all other API endpoints, including those related to managing products, orders, and user accounts, you will need to include the Bearer Token in the Authorization header of your HTTP requests.

By following these steps, you'll be able to authenticate and access our API seamlessly, empowering you to leverage the full capabilities of our Partner Proxy Reseller Program.

Parameters:

Parameter	Type	Required	Description	Requirements
username	String	yes	Reseller username on our partner website.	Active account on a partner website.
secret	String	yes	Secret ID received from our partner website.	Valid Secret ID generated by a partner website.

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

Body raw (json)

json

```
{
  "username": "TestUser",
  "secret": "<YOUR SECRET KEY>"
}
```

GET Reseller Account

https://reseller.myproxyapi.com/api/v1/account-info

This endpoint retrieves comprehensive details about the reseller account, including deposited funds, order history, and available balance. The response provides key metrics such as total deposited amount, number of deposit transactions, total order amount, order count, available balance, and currency. Additionally, it includes user-specific information like reseller ID, username, and discount percentage.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Countries Invoicing

<https://reseller.myproxyapi.com/api/v1/countries>

This endpoint provides a comprehensive list of countries available for invoicing purposes. It facilitates users in selecting the correct country for their billing information, ensuring accuracy in the invoicing process.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Deposit

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

GET Payments All

https://reseller.myproxyapi.com/api/v1/deposit/payments

This endpoint displays a comprehensive list of all payments, including transactions made by both resellers and subusers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Payments User

https://reseller.myproxyapi.com/api/v1/deposit/payments/12345

This endpoint presents a list of payments specific to a particular user.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

POST Make Payment Stripe

https://reseller.myproxyapi.com/api/v1/deposit/payment/stripe

This endpoint enables the creation of a checkout link on the Stripe Payment Gateway for processing payments. It streamlines the payment process by generating a secure link for users to complete their transactions seamlessly.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you are creating the checkout link.	Active order ID.
amount	Integer	Yes	Payment amount.	Integer number.
currency	String	Yes	Payment currency.	Valid option: USD
success_url	URL	Yes	Return URL for completed payment.	Valid URL.
cancel_url	URL	Yes	Return URL for canceled payment.	Valid URL.
user_ip	IP	Yes	Current user IP.	Valid IP address.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "user_id": "12345",
  "amount": "10",
  "currency": "USD",
  "success_url": "https://mywebsite.com/thank-you-page",
  "cancel_url": "https://mywebsite.com/payment-cancelled",
  "user_ip": "192.168.0.1"
}
```

POST Make Payment xMoney

<https://reseller.myproxyapi.com/api/v1/deposit/payment/xmoney>

This endpoint facilitates the creation of a checkout link on the xMoney Payment Gateway, simplifying the payment process for users. It generates a secure link for users to proceed with their transactions efficiently.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you are creating the checkout link.	Active order ID.
amount	Integer	Yes	Payment amount.	Integer number.
currency	String	Yes	Payment currency.	Valid option: USD
success_url	URL	Yes	Return URL for completed payment.	Valid URL.
cancel_url	URL	Yes	Return URL for canceled payment.	Valid URL.
user_ip	IP	Yes	Current user IP.	Valid IP address.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "user_id": "12345",
  "amount": "10",
```

```
{
  "currency": "USD",
  "success_url": "https://mywebsite.com/thank-you-page",
  "cancel_url": "https://mywebsite.com/payment-cancelled",
  "user_ip": "192.168.0.1"
}
```

POST Make Payment Cryptomus

<https://reseller.myproxyapi.com/api/v1/deposit/payment/cryptomus>

This endpoint facilitates the creation of a checkout link on the xMoney Payment Gateway, simplifying the payment process for users. It generates a secure link for users to proceed with their transactions efficiently.

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you are creating the checkout link.	Active order ID.
amount	Integer	Yes	Payment amount.	Integer number.
currency	String	Yes	Payment currency.	Valid option: USD
success_url	URL	Yes	Return URL for completed payment.	Valid URL.
cancel_url	URL	Yes	Return URL for canceled payment.	Valid URL.
user_ip	IP	Yes	Current user IP.	Valid IP address.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type	application/json
--------------	------------------

```
{
  "user_id": "12345",
  "amount": "10",
  "currency": "USD",
  "success_url": "https://mywebsite.com/thank-you-page",
  "cancel_url": "https://mywebsite.com/payment-cancelled",
  "user_ip": "192.168.0.1"
}
```

GET Invoices All

https://reseller.myproxyapi.com/api/v1/deposit/payments/invoices

This endpoint displays a comprehensive list of all invoices, including transactions made by both resellers and subusers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Invoices User

https://reseller.myproxyapi.com/api/v1/deposit/payments/invoices/39755

This endpoint presents a list of invoices specific to a particular user.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
Content-Type	application/json

GET Orders All

https://reseller.myproxyapi.com/api/v1/deposit/orders

This endpoint displays a comprehensive list of all orders transactions, including transactions made by both resellers and subusers.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
Content-Type	application/json

GET Orders User

https://reseller.myproxyapi.com/api/v1/deposit/orders/31347

This endpoint presents a list of orders transactions specific to a particular user.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
Content-Type	application/json

Users

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

GET Users List

`https://reseller.myproxyapi.com/api/v1/users`

This endpoint provides a comprehensive list of all subusers associated with a reseller account. It facilitates resellers in managing their user base by offering detailed information about each subuser.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Content-Type	application/json
--------------	------------------

GET User Full Details

`https://reseller.myproxyapi.com/api/v1/users/32125`

This endpoint displays complete details of a user, providing comprehensive information about the user's profile.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Content-Type	application/json
--------------	------------------

POST User Create

<https://reseller.myproxyapi.com/api/v1/users>

This endpoint allows the creation of a subuser, enabling resellers to add new users to their account.

Parameters:

Parameter	Type	Required	Description	Requirements
username	String	Yes	Customer username.	Active order ID.
email	Email	Yes	Customer email address.	Valid email address.
customer_name	String	Yes	Customer full name.	Complete name. Name will be used on invoices.
customer_country	Integer	Yes	Customer country.	Valid country ID from Countries Invoices endpoint. Country will be used on invoices.
customer_city	String	Yes	Customer city.	Valid city name. City will be used on invoices.
user_ip	IP	Yes	Current user IP.	Valid IP address.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "username": "lei123d",
  "email": "lei123_4@gmail.com",
```

```
{
  "customer_name": "lei fuzhonge",
  "customer_country": "232",
  "customer_city": "Dover",

  "user_ip": "192.0.2.1"
}
```

PATCH User Update

<https://reseller.myproxyapi.com/api/v1/users/31478>

This endpoint facilitates the update of basic details for a subuser.

Parameters:

Parameter	Type	Required	Description	Requirements
username	String	Yes	Customer username.	Active order ID.
email	Email	Yes	Customer email address.	Valid email address.
customer_name	String	Yes	Customer full name.	Complete name. Name will be used on invoices.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "username": "NewUsername",
  "email": "email@yahoo.com",
  "customer_name": "New Name"
}
```

Products

Our API offers a comprehensive range of proxy categories, including Datacenter Proxies, ISP Proxies, Premium ISP Proxies, Static Residential Proxies, Residential Rotating Proxies, and Mobile Proxies. These endpoints provide full access to our diverse proxy solutions, catering to a wide array of needs.

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

GET Proxy Categories

`https://reseller.myproxyapi.com/api/v1/products-categories`

This endpoint facilitates the retrieval of all proxy categories available on our Partner Platform.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Content-Type	application/json
--------------	------------------

Body	urlencoded
------	------------

GET View all products

`https://reseller.myproxyapi.com/api/v1/products/all`

This endpoint facilitates the retrieval of all proxy plans across multiple proxy categories available on our Partner Platform.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body urlencoded

GET Static IPs - Datacenter

<https://reseller.myproxyapi.com/api/v1/products/datacenter>

This endpoint facilitates the retrieval of all proxy plans across Datacenter proxies category available on our Partner Platform.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body urlencoded

GET Static IPs - ISP

<https://reseller.myproxyapi.com/api/v1/products/isp>

This endpoint facilitates the retrieval of all proxy plans across Datacenter proxies category available on our Partner Platform.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body urlencoded

GET Static IPs - Premium ISP

<https://reseller.myproxyapi.com/api/v1/products/premium-isp>

This endpoint facilitates the retrieval of all proxy plans across Premium ISP proxies category available on our Partner Platform.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body urlencoded

GET Static IPs - Static Residential

<https://reseller.myproxyapi.com/api/v1/products/static-residential>

This endpoint facilitates the retrieval of all proxy plans across Static Residential proxies category available on our Partner Platform.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body urlencoded

GET Residential Rotating

<https://reseller.myproxyapi.com/api/v1/products/residential-vpn>

This endpoint facilitates the retrieval of all proxy plans across Residential Rotating proxies category available on our Partner Platform.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body urlencoded

GET Mobile

<https://reseller.myproxyapi.com/api/v1/products/mobile>

This endpoint facilitates the retrieval of all proxy plans across Mobile proxies category available on our Partner Platform.

AUTHORIZATION Bearer Token

Token

<YOUR BEARER TOKEN>

HEADERS

Authorization

Bearer <YOUR BEARER TOKEN>

Content-Type

application/json

Body urlencoded

GET Residential VPN

<https://reseller.myproxyapi.com/api/v1/products/residential-vpn>

This endpoint facilitates the retrieval of all proxy plans across Residential VPN proxies category available on our Partner Platform.

AUTHORIZATION Bearer Token

Token

<YOUR BEARER TOKEN>

HEADERS

Authorization

Bearer <YOUR BEARER TOKEN>

Content-Type

application/json

Body urlencoded

Place order

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

https://reseller.myproxyapi.com/api/v1/products/get-price

This endpoint facilitates the retrieval of the order price by providing the product ID and desired order period to receive accurate pricing information tailored to your preferences.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you are getting the price.	Active user ID.
product	Integer	Yes	Product ID from proxy plans listing.	Active proxy plan ID.
period	Integer	Yes	Static IPs: Desired duration of the order, specified in months. Residential Rotating: Desired amount of traffic in GB. Mobile IPs: Desired number of IPs.	Static IPs: Valid options: 1w 1 3 6 12 Residential Rotating: Minimum 1. Mobile IPs: Minimum 1.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "user_id": 10362,
  "product" : "84", // DCH 10 ISP 57 PISP 84 STR 105 RR 122, VPN 141
  "period" : "1"
}
```

POST Place Order Deposit

<https://reseller.myproxyapi.com/api/v1/products/place-order>

This endpoint facilitates the initiation of orders, with the associated amount deducted from the reseller's deposit.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you are creating the deposit.	Active user ID.
product	Integer	Yes	Product ID from proxy plans listing.	Active proxy plan ID.
period	Integer	Yes	Static IPs: Desired duration of the order, specified in months. Residential Rotating: Desired amount of traffic in GB. Mobile IPs: Desired number of	Static IPs: Valid options: 1d 1w 1 3 6 12 Residential Rotating: Minimum 1.

- Please note that default username and password for new orders are random generated by the system. After delivery, users can change the credentials.
- Mobile IPs work only with a Whitelisted IP, they don't work with User:Pass authentication.

AUTHORIZATION Bearer Token

Token

<YOUR BEARER TOKEN>

HEADERS

Authorization

Bearer <YOUR BEARER TOKEN>

Content-Type

application/json

Body raw

```
{
  "user_id": 10362,
  "product": 141,
  "period": "1",
  "protocol": "http",
  "locations": "93",
  "whitelist_ip": "192.0.2.1",
  "debug": "test 1"
}
```

POST Place Order Checkout

<https://reseller.myproxyapi.com/api/v1/products/place-order-checkout>

This endpoint facilitates the initiation of orders with direct checkout through payment gateways.

We offer secure payment options for both Card and Cryptocurrency transactions, processed through Stripe for Card payments and xMoney for Crypto payments. All transactions are protected and securely handled by these trusted payment gateways.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you are creating the deposit.	Active user ID.
payment_method	String	Yes	Payment method provider. Stripe for Card payments, xmoney for crypto payments	Valid options: stripe, xmoney
subscription	String	No	Available for Card Subscription.	Valid options: true, false.
success_url	URL	Yes	Return URL for completed payment.	Valid URL.
cancel_url	URL	Yes	Return URL for canceled payment.	Valid URL.
product	Integer	Yes	Product ID from	Active proxy plan

- Please note that default username and password for new orders are random generated by the system. After delivery, users can change the credentials.
- Mobile IPs work only with a Whitelisted IP, they don't work with User:Pass authentication.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "user_id": 10362, //10370. 10362
```

```
"payment_method": "stripe",
"subscription": "false",
"success_url": "https://mywebsite.com/thank-you-page",

"cancel_url": "https://mywebsite.com/payment-cancelled",
"product": 84, //57 122 132
"period": "1",
"protocol": "socks5",
"locations": "93", //"57", // 61 1
"whitelist_ip": "163.5.128.2"
}
```

Extend orders

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

POST Place Extend Deposit

<https://reseller.myproxyapi.com/api/v1/products/place-extend>

Designed exclusively for Static IPs and VPN orders, this endpoint facilitates the initiation of extend for active orders, with the associated amount deducted from the reseller's deposit.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you are creating the deposit.	Active user ID.
order_id	String	Yes	Order ID where you intend to make updates.	Active order ID.
period	Integer	Yes	Desired duration for subscription extend, specified in months.	Static IPs: Valid options: 1d 1w 1 3 6 12 **Residential VPN: **Active plan id, for plan period

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "user_id": "10362",
  "order_id": "vpnBPP-1922",
  "period": "141"
}
```

POST Place Extend Checkout

https://reseller.myproxyapi.com/api/v1/products/place-extend-checkout

Designed exclusively for Static IPs, this endpoint facilitates the initiation of extend for active subscriptions, with direct checkout through payment gateways.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you are creating the deposit.	Active user ID.
payment_method	String	Yes	Payment method provider. stripe for Card payments, xmoney for crypto payments	Valid options: stripe, xmoney
success_url	URL	Yes	Return URL for completed payment.	Valid URL.
cancel_url	URL	Yes	Return URL for canceled payment.	Valid URL.
order_id	String	Yes	Order ID where you intend to make updates.	Active order ID.
period	Integer	Yes	Desired duration	Static IPs

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "user_id": "10362",
  "payment_method": "stripe",
  "success_url": "https://mywebsite.com/thank-you-page",
  "cancel_url": "https://mywebsite.com/payment-cancelled",
  "order_id": "vpnBPP-1922",
  "period": "142"
}
```

Static IPs

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

Orders

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

GET Active Orders All

<https://reseller.myproxyapi.com/api/v1/orders/active>

This endpoint facilitates the retrieval of all active orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Active Orders User

https://reseller.myproxyapi.com/api/v1/orders/active/10362

This endpoint facilitates the retrieval of all active orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Expired Orders All

https://reseller.myproxyapi.com/api/v1/orders/expired

This endpoint facilitates the retrieval of all expired orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Expired Orders User

https://reseller.myproxyapi.com/api/v1/orders/expired/10362

This endpoint facilitates the retrieval of all expired orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Order Details

<https://reseller.myproxyapi.com/api/v1/orders/view/0ER97229AL279313A>

This endpoint facilitates the retrieval of provided order details.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID required for retrieving information.	Active order ID.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Order settings

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

PATCH Change Protocol

https://reseller.myproxyapi.com/api/v1/orders/change-protocol

This endpoint empowers users to modify the protocol used, offering the choice between HTTP/HTTPS and SOCKS5 protocols for enhanced flexibility and customization.

Protocols options:

http - HTTP/HTTPS

socks5 - SOCKS5

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates.	Active order ID.
protocol	String	Yes	New protocol for specified subscription proxies.	Valid option: http socks5

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw (json)

```
json
{
  "order_id": "A17XXXXXXXXXXXXXXXXXX",
  "protocol": "socks5"
}
```

PATCH Change Credentials

This endpoint facilitate users to update their proxy authentication credentials, empowering them to modify their username and password as needed for secure and personalized proxy access. The change will be applied across all proxies included in your subscription.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates.	Active order ID.
username	String	Yes	New authentication username.	Alphanumeric characters allowed only. Minimum 5 characters. Maximum 20 characters.
password	String	Yes	New authentication password.	Alphanumeric characters allowed only. Minimum 5 characters. Maximum 20 characters.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "order_id": "A17XXXXXXXXXXXXXXXXXX",
  "username": "TestUser",
  "password": "Password123"
}
```

PATCH Replacement

`https://reseller.myproxyapi.com/api/v1/orders/replacement`

This endpoint is used to replace proxies associated with an active order. Once triggered, the system will generate new proxies in place of the existing ones, based on the eligibility of the plan. New IPs are automatically assigned within approximately 1 minute after the endpoint request is processed.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates.	Active order ID.
locations	String	No	New locations for replacement.	Locations need to be compatible with specified proxy plan. To retain the existing location(s), submit the request with only the order_id, without providing the locations field, or set the locations field to null.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "order_id": "A1YQJ0PAVHX8090H0G26",
  "locations": "null" //132
}
```

POST Whitelist Add

<https://reseller.myproxyapi.com/api/v1/orders/whitelist-add>

This endpoint facilitate users to whitelist their IP addresses for proxy access without requiring a username and password.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates..	Active order ID.
ip	IP	Yes	IP address that you need to add in authentication whitelist.	The IP address does not exist in the subscription whitelist. Valid IP format.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "order_id": "A17XXXXXXXXXXXXXXXXXX",
  "ip": "192.0.2.123",
  "description": "Laptop IP"
}
```

```
}
```

DELETE Whitelist Delete

<https://reseller.myproxyapi.com/api/v1/orders/whitelist-delete>

This endpoint facilitate users to remove IP addresses from the whitelist.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates..	Active order ID.
ip	IP	Yes	IP address that you need to remove from authentication whitelist.	The IP address exist in your subscription whitelist. Valid IP format.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "order_id": "A17XXXXXXXXXXXXXXXXXX",
  "ip": "192.0.2.1"
}
```

POST Card Subscription Cancel

https://reseller.myproxyapi.com/api/v1/orders/subscription/cancel

This endpoint allows users to cancel their card subscription. When canceled, automatic card payments will be stopped, but the subscription service will remain active until the current billing period ends.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you need to cancel subscription.	Active user ID.
order_id	String	Yes	Order ID where you intend to cancel subscription.	Active order ID.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "user_id": "39541",
  "order_id": "I-A1IGYIQTm1JUGWMQK4TP"
}
```

POST Subscription Card Update

https://reseller.myproxyapi.com/api/v1/orders/subscription/update_card

This endpoint allows users to update the payment card associated with their Stripe subscription.

Parameters:

Parameter	Type	Required	Description	Requirements
user_id	Integer	Yes	User ID of the customer for which you need to cancel subscription.	Active user ID.
order_id	String	Yes	Order ID where you intend to cancel subscription.	Active order ID.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "user_id": "12345",
  "order_id": "I-AAAAAAAAA"
}
```

Residential Rotating IPs

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

Orders

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

GET Orders All

<https://reseller.myproxyapi.com/api/v1/orders-residential-rotating>

This endpoint facilitates the retrieval of all active residential rotating orders placed by the reseller customers.

Each user is allocated a single residential rotating plan order. Subsequent purchases of additional plans will augment the initial order's traffic allocation with the new plan's amount.

Each order have 3 month valability for the traffic.

Please note that all traffic information is displayed in bytes for accurate measurement.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Content-Type	application/json
--------------	------------------

GET Order Details

<https://reseller.myproxyapi.com/api/v1/orders-residential-rotating/32031>

This endpoint facilitates the retrieval of provided order details.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Orders settings

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

POST Create Proxy Account

https://reseller.myproxyapi.com/api/v1/residential-rotating/create-proxy-account

This endpoint allows the creation of a Proxy Account. In order to use residential rotating order, customer need to create minimum one proxy account.

Parameters:

Parameter	Type	Required	Description	Requirements
username	String	Yes	Customer username from Residential Order.	Active Residential Rotating Username.
proxy_username	String	Yes	Desired proxy username.	Minimum 3 characters.
proxy_password	String	Yes	Desired proxy password.	Minimum 3 characters.
traffic_limit	Int/Float	Yes	Traffic limit for current proxy username.	Value in GB. Ex: 1 or 0.5

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "username": "MPU95736_lei123",
  "proxy_username": "testDev123",
  "proxy_password": "232aaa2aa",
  "traffic_limit": "1"
}
```

POST Update Proxy Account

<https://reseller.myproxyapi.com/api/v1/residential-rotating/update-proxy-account>

This endpoint allows the update of a Proxy Account.

Parameters:

Parameter	Type	Required	Description	Requirements
username	String	Yes	Customer username from Residential Order.	Active Residential Rotating Username.
proxy_username	String	Yes	Desired proxy username.	Minimum 3 characters.
proxy_password	String	Yes	Desired proxy password.	Minimum 3 characters.
traffic_limit	Int/Float	Yes	Traffic limit for current proxy username.	Value in GB. Ex: 1 or 0.5
status	Int	Yes	Proxy Account status.	Valid options: 1 for active, 2 for inactive.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "username": "NET_test3",
  "proxy_username_id": "85959",
  "proxy_username": "testproxyaccount1",
  "proxy_password": "1234",
  "traffic_limit": "1",
  "status": "2"
}
```

POST View Proxy Account

https://reseller.myproxyapi.com/api/v1/residential-rotating/view-proxy-account

This endpoint facilitates the retrieval of provided Proxy Account.

Parameters:

Parameter	Type	Required	Description	Requirements
username	String	Yes	Customer username from Residential Order.	Active Residential Rotating Username.
proxy_username	String	Yes	Proxy Account username that need to be retrieved.	Active proxy account username.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw (json)

```
.
```

json

```
{
  "username": "NET_test3",
  "proxy_username": "testuser"
}
```

POST Traffic Logs - Main User

<https://reseller.myproxyapi.com/api/v1/residential-rotating/username-traffic-logs>

This endpoint facilitates the retrieval of Traffic log for Specific Residential User and Period.

Parameters:

Parameter	Type	Required	Description	Requirements
username	String	Yes	Customer username from Residential Order.	Active Residential Rotating Username.
start_time	String	Yes	Start time for logs.	Date in Unix timestamp.
end_time	String	Yes	End time for logs.	Date in Unix timestamp.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "username": "NET_BogdanTD2",
  "start_time": "1714694400",
  "end_time": "1714694400"
}
```

POST Traffic Logs - Proxy Account

https://reseller.myproxyapi.com/api/v1/residential-rotating/proxy-account-traffic-logs

This endpoint facilitates the retrieval of Residential Network available hostnames for proxy connection.

Hostnames are available for 3 areas:

- North America
- Europe
- Asia

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "username": "NET_test3",
  "proxy_username": "testbgg1",
  "start_time": "1714694400",
  "end_time": "1714694400"
}
```

Proxy Generator

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

GET Get Settings

<https://reseller.myproxyapi.com/api/v1/residential-rotating/get-settings>

This endpoint displays a comprehensive list of all payments, including transactions made by both resellers and subusers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Get Countries

<https://reseller.myproxyapi.com/api/v1/residential-rotating/get-countries>

This endpoint facilitates the retrieval of Residential Network available Countries list.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Get States

<https://reseller.myproxyapi.com/api/v1/residential-rotating/get-states/us>

This endpoint facilitates the retrieval of Residential Network available States for a specific Country.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
Content-Type	application/json

GET Get Cities

<https://reseller.myproxyapi.com/api/v1/residential-rotating/get-cities/us/newyork>

This endpoint facilitates the retrieval of Residential Network available States for a specific State.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
Content-Type	application/json

GET Get ISP

<https://reseller.myproxyapi.com/api/v1/residential-rotating/get-isp/us>

This endpoint facilitates the retrieval of Residential Network available ISP for a specific Country.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
Content-Type	application/json

POST Generate Proxy

<https://reseller.myproxyapi.com/api/v1/residential-rotating/generate-proxy>

This endpoint facilitates generating Proxy List.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
"user_id": 12345, // required
"targeting": "state_city", // required: state_city or isp
"proxy_rotation": "12", // required: rotating or a number between 1 and 120 for sticky
"country": "us", // one country code like: us, gb, fr ...
"state" : "alabama", // one state slug like: alabama, arizona ...
// "city" : "newcassel", // one city slug like: newcassel, newyork ...
// "isp" : "AS10242", // one ISP asn like: AS10242
"hostname": "resi-na.myproxyapi.com:16666", // required: resi-na.myproxyapi.com:16666 or 43
"username" : "aaa", // required
"password" : "bbb", // required
"quantity" : "3", // required
"format" : "hostname:port:username:password" // required: hostname:port:username:password or
```

Mobile IPs

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

Orders

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

GET Active Orders All

<https://reseller.myproxyapi.com/api/v1/mobile-orders/active>

This endpoint facilitates the retrieval of all active orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Active Orders User

<https://reseller.myproxyapi.com/api/v1/mobile-orders/active/40253>

This endpoint facilitates the retrieval of all active orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Expired Orders All

https://reseller.myproxyapi.com/api/v1/mobile-orders/expired

This endpoint facilitates the retrieval of all expired orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Expired Orders User

https://reseller.myproxyapi.com/api/v1/mobile-orders/expired/10362

This endpoint facilitates the retrieval of all expired orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Order Details

https://reseller.myproxyapi.com/api/v1/mobile-orders/view/A1NGD4TWHVJTA8VTJQJG

This endpoint facilitates the retrieval of provided order details.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	string	Yes	Order ID	API Key

order_id	String	Yes	Order ID required for retrieving information.	Active order ID.
----------	--------	-----	---	------------------

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Orders settings

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

PATCH Update Whitelisted IP

https://reseller.myproxyapi.com/api/v1/mobile-orders/update-whitelisted-ip

This endpoint facilitate users to whitelist their IP addresses for proxy access without requiring a username and password.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates..	Active order ID.
ip	IP	Yes	IP address that you need to add in authentication whitelist.	The IP address does not exist in the subscription whitelist. Valid IP format.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization

Bearer <YOUR BEARER TOKEN>

Content-Type

application/json

Body raw

```
{
  "order_id": "A1XLE70DIXDDU3S4ZQX1",
  "ip": "208.124.20.62"
}
```

PATCH Update Rotation

https://reseller.myproxyapi.com/api/v1/mobile-orders/update-rotation

This endpoint empowers users to modify the protocol used, offering the choice between HTTP/HTTPS and SOCKS5 protocols for enhanced flexibility and customization.

Status options:

- on** - Active rotation 30 minutes
- off** - Rotation is disabled

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates.	Active order ID.
status	String	Yes	Rotation status.	Valid option: on off

AUTHORIZATION Bearer Token

Token

<YOUR BEARER TOKEN>

HEADERS

Authorization

Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw (json)

json

```
{
  "order_id": "A1XLE70DIXDDU3S4ZQX1",
  "status": "on"
}
```

Residential VPN

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

Orders

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

GET Active Orders All

<https://reseller.myproxyapi.com/api/v1/orders/vpn>

This endpoint facilitates the retrieval of all active orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Active Orders User

<https://reseller.myproxyapi.com/api/v1/orders/vpn/active/10362>

This endpoint facilitates the retrieval of all active orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Expired Orders All

<https://reseller.myproxyapi.com/api/v1/orders/vpn/expired>

This endpoint facilitates the retrieval of all expired orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Expired Orders User

<https://reseller.myproxyapi.com/api/v1/orders/vpn/expired/10362>

This endpoint facilitates the retrieval of all expired orders placed by the reseller customers.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET Order Details

https://reseller.myproxyapi.com/api/v1/orders/vpn/view/vpnMPA-1934

This endpoint facilitates the retrieval of provided order details.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID required for retrieving information.	Active order ID.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Orders settings

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

PATCH Change Credentials

<https://reseller.myproxyapi.com/api/v1/orders/vpn/change-credentials>

This endpoint facilitate users to update their VPN authentication credentials, empowering them to modify their username and password as needed for secure and personalized VPN access.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates.	Active order ID.
username	String	Yes	New authentication username.	Alphanumeric characters allowed only. Minimum 5 characters. Maximum 20 characters.
password	String	Yes	New authentication password.	Alphanumeric characters allowed only. Minimum 5 characters. Maximum 20 characters.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "order_id": "vpnBPP-1922",
  "username": "test1",
```

```
    "password": "pass2"
  }
```

GET VPN Restart

https://reseller.myproxyapi.com/api/v1/orders/vpn/restart/vpnBPP-1922

This endpoint facilitate users to restart the VPN in case something is wrong with the connection.

Parameters:

Parameter	Type	Required	Description	Requirements
order_id	String	Yes	Order ID where you intend to make updates.	Active order ID.
username	String	Yes	New authentication username.	Alphanumeric characters allowed only. Minimum 5 characters. Maximum 20 characters.
password	String	Yes	New authentication password.	Alphanumeric characters allowed only. Minimum 5 characters. Maximum 20 characters.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

GET VPN Config Source

https://reseller.myproxyapi.com/api/v1/orders/vpn/download/vpnBPP-1922

This endpoint facilitate users to view the VPN configuration.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Content-Type	application/json
--------------	------------------

GET VPN Download .ovpn

https://reseller.myproxyapi.com/api/v1/orders/vpn/download/vpnBPP-1922?download=1

This endpoint facilitate users to download the VPN .ovpn file.

AUTHORIZATION Bearer Token

Token	<YOUR BEARER TOKEN>
-------	---------------------

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Content-Type	application/json
--------------	------------------

PARAMS

download	1
----------	---

Static ISP Proxy - NEW

AUTHORIZATION Bearer Token

GET Order Configuration Details

<https://reseller.myproxyapi.com/api/v1/ext1/details/isp>

This endpoint facilitates the retrieval of all settings that you need in order to place an order.

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Accept	application/json
--------	------------------

POST Check Order Price

<https://reseller.myproxyapi.com/api/v1/ext1/check-order-price>

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

HEADERS

Authorization	Bearer <YOUR BEARER TOKEN>
---------------	----------------------------

Accept	application/json
--------	------------------

Body raw (json)

json

```
{
  "periodId": "7d",           // Required
  "quantity": 1,             // Required, limited to 1
}
```

```
"countryId": 4200941,           // Required
"targetSectionId": 221,        // Optional
"targetId": 3281093            // Optional

// "customTargetName": "example.com" // Optional (Required if targetId is 0 and target is not 0)
}
```

POST Create Order

<https://reseller.myproxyapi.com/api/v1/ext1/create-order>

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Accept application/json

Body raw (json)

json

```
{
  "periodId": "7d",           // Required
  "quantity": 1,              // Required, limited to 1
  "countryId": 3347226,       // Required
  "targetSectionId": 221,     // Optional
  "targetId": 3281093         // Optional
  // "customTargetName": "example.com" // Optional (Required if targetId is 0 and target is not 0)
}
```

GET Orders List

<https://reseller.myproxyapi.com/api/v1/ext1/orders>

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

HEADERS

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Accept application/json

GET Order Details

<https://reseller.myproxyapi.com/api/v1/ext1/order-details/A1B731ONYBC1LZDBXJU31>

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Accept application/json

POST Check Extend Price

<https://reseller.myproxyapi.com/api/v1/ext1/check-extend-price>

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Accept application/json

Body raw (json)

```
json
```

```
{
  "type": "isp",
  "order_id": "A13J0IPH1ZRBR2H9MK9I",
  "periodId": "7d"
}
```

POST Extend Order

<https://reseller.myproxyapi.com/api/v1/ext1/extend-order>

AUTHORIZATION Bearer Token

This request is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Accept application/json

Body raw (json)

json

```
{
  "type": "isp",
  "order_id": "A1B7310NYBC1LZDBXJU31",
  "periodId": "7d"
}
```

Tools

AUTHORIZATION Bearer Token

This folder is using Bearer Token from collection [MyProxyApi - Private Dedicated Proxy Reseller API](#)

POST Proxy Locator

<https://reseller.myproxyapi.com/api/v1/proxy-locator>

Designed exclusively for Static IPs, this endpoint allows users to accurately locate their order ID based on IP address.

Parameters:

Parameter	Type	Required	Description	Requirements
ip	IP	Yes	The IP address associated with the subscription you wish to locate.	Active proxy in your orders. Valid IP format.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "ip": "192.0.2.1"
}
```

POST Proxy Location

<https://reseller.myproxyapi.com/api/v1/proxy-location>

This endpoint enables users to retrieve the geographical location associated with an IPV4 IP address.

Parameters:

Parameter	Type	Required	Description	Requirements
ip	IP	Yes	IP address that you need to check location.	Active proxy in your orders. Valid IP format.

AUTHORIZATION Bearer Token

Token <YOUR BEARER TOKEN>

HEADERS

Authorization Bearer <YOUR BEARER TOKEN>

Content-Type application/json

Body raw

```
{
  "ip": "192.0.2.1"
}
```