



## **Hotel\_MultiSingleAvailability\_10.0\_Reply**

### **Technical Reference**

*Amadeus IT Group, S.A.*

485, Route du Pin Montard  
BP 69  
06902 Sophia-Antipolis Cedex

(Amadeus Proprietary and Confidential Information: unauthorized use and disclosure strictly forbidden. 2011 - Amadeus s.a.s - All Rights Reserved.)

## Introduction

This document is the technical reference for an Amadeus functional interface. This reference is not directly bundled to Amadeus Programming Interface development or any other development flavour. It is just a generic description of the interface through all the services it publishes.

### Structure hierarchy

- \* A service contains an input message and an output message.
- \* A query/reply structure contains a list of simple structures and a list of grouped structures.
- \* A grouped structure contains a list of simple structures and a list of grouped structures.
- \* A simple structure contains a list of data elements and grouped data elements.
- \* A data element can be coded, therefore a code list is described in a separate table.

### Document structure

- \* Service overview.
- \* Query and output messages for the service, with their corresponding description.
- \* For each query/reply structure, a table describing its higher level entities of the query/reply structure.
- \* For each grouped or simple structure, a table describing the entities they are built with.
- \* For each coded entity, a table describing the possible coded values it can take.

**Grouped structures introduces the 'level' concept within a structure. This level is reflected in the structure tables via indentation.**

### Document navigation

The document uses internal links to quickly navigate between referenced entities and its corresponding structure and substructures (if any).

## Glossary

### Element representation

#### *Format Description*

| Name               | Type                                                           | Occ                                       | Nil                                                                                | Description                 |
|--------------------|----------------------------------------------------------------|-------------------------------------------|------------------------------------------------------------------------------------|-----------------------------|
| The element's name | The simple type that defines the textual content of an element | Minimum occurrences / Maximum occurrences | Nilable (Specifies whether an explicit null value can be assigned to the element.) | The element's documentation |

#### *Attributes*

| Name                  | Type                                             | Use                                                    | Value                                            | Description                    |
|-----------------------|--------------------------------------------------|--------------------------------------------------------|--------------------------------------------------|--------------------------------|
| The attributes's name | The attributes's type, if it has a declared type | The attributes's use. optional   prohibited   required | FIXED: The attribute 'fixed' or 'default' value. | The attribtues's documentation |

## Table of contents

|                                           |    |
|-------------------------------------------|----|
| 1. Technical Reference . . . . .          | 1  |
| 1.1. OTA_HotelAvailRS . . . . .           | 1  |
| 1.1.1. Success . . . . .                  | 2  |
| 1.1.2. Warnings . . . . .                 | 3  |
| 1.1.2.1. Warning . . . . .                | 3  |
| 1.1.3. HotelStays . . . . .               | 4  |
| 1.1.3.1. HotelStay . . . . .              | 4  |
| 1.1.3.1.1. Availability . . . . .         | 5  |
| 1.1.3.1.1.1. Restriction . . . . .        | 6  |
| 1.1.3.1.2. BasicPropertyInfo . . . . .    | 6  |
| 1.1.3.1.2.1. VendorMessages . . . . .     | 8  |
| 1.1.3.1.2.1.1. VendorMessage . . . . .    | 8  |
| 1.1.3.1.2.1.1.1. SubSection . . . . .     | 9  |
| 1.1.3.1.2.1.1.1.1. Paragraph . . . . .    | 10 |
| 1.1.3.1.2.1.1.1.1.1. Text . . . . .       | 11 |
| 1.1.3.1.2.1.1.1.2. ListItem . . . . .     | 11 |
| 1.1.3.1.2.2. Position . . . . .           | 12 |
| 1.1.3.1.2.3. Address . . . . .            | 13 |
| 1.1.3.1.2.3.1. StreetNmbr . . . . .       | 14 |
| 1.1.3.1.2.3.2. BldgRoom . . . . .         | 14 |
| 1.1.3.1.2.3.3. AddressLine . . . . .      | 14 |
| 1.1.3.1.2.3.4. CityName . . . . .         | 15 |
| 1.1.3.1.2.3.5. PostalCode . . . . .       | 15 |
| 1.1.3.1.2.3.6. County . . . . .           | 15 |
| 1.1.3.1.2.3.7. StateProv . . . . .        | 15 |
| 1.1.3.1.2.3.8. CountryName . . . . .      | 16 |
| 1.1.3.1.2.4. ContactNumbers . . . . .     | 16 |
| 1.1.3.1.2.4.1. ContactNumber . . . . .    | 17 |
| 1.1.3.1.2.5. Award . . . . .              | 17 |
| 1.1.3.1.2.6. RelativePosition . . . . .   | 18 |
| 1.1.3.1.2.6.1. Transportations . . . . .  | 18 |
| 1.1.3.1.2.6.1.1. Transportation . . . . . | 19 |
| 1.1.3.1.2.7. HotelAmenity . . . . .       | 19 |
| 1.1.3.1.2.8. HotelFeature . . . . .       | 20 |

|                                       |    |
|---------------------------------------|----|
| 1.1.3.1.2.9. Recreation               | 20 |
| 1.1.3.1.2.10. Service                 | 20 |
| 1.1.3.1.2.11. Policy                  | 21 |
| 1.1.3.1.2.12. HotelMeetingFacility    | 21 |
| 1.1.3.1.3. Price                      | 22 |
| 1.1.4. RoomStays                      | 23 |
| 1.1.4.1. RoomStay                     | 23 |
| 1.1.4.1.1. RoomTypes                  | 25 |
| 1.1.4.1.1.1. RoomType                 | 25 |
| 1.1.4.1.1.1.1. Occupancy              | 26 |
| 1.1.4.1.1.1.2. TPA_Extensions         | 26 |
| 1.1.4.1.2. RatePlans                  | 27 |
| 1.1.4.1.2.1. RatePlan                 | 27 |
| 1.1.4.1.2.1.1. Guarantee              | 29 |
| 1.1.4.1.2.1.1.1. GuaranteesAccepted   | 30 |
| 1.1.4.1.2.1.1.1.1. GuaranteeAccepted  | 30 |
| 1.1.4.1.2.1.1.1.1.1. PaymentCard      | 31 |
| 1.1.4.1.2.1.1.1.1.1.1. CardHolderName | 32 |
| 1.1.4.1.2.1.1.1.1.1.2. CardIssuerName | 32 |
| 1.1.4.1.2.1.1.1.1.1.3. Address        | 32 |
| 1.1.4.1.2.1.1.1.1.1.3.1. StreetNmbr   | 33 |
| 1.1.4.1.2.1.1.1.1.1.3.2. BldgRoom     | 33 |
| 1.1.4.1.2.1.1.1.1.1.3.3. AddressLine  | 34 |
| 1.1.4.1.2.1.1.1.1.1.3.4. CityName     | 34 |
| 1.1.4.1.2.1.1.1.1.1.3.5. PostalCode   | 34 |
| 1.1.4.1.2.1.1.1.1.1.3.6. County       | 35 |
| 1.1.4.1.2.1.1.1.1.1.3.7. StateProv    | 35 |
| 1.1.4.1.2.1.1.1.1.1.3.8. CountryName  | 35 |
| 1.1.4.1.2.1.1.1.1.4. Telephone        | 36 |
| 1.1.4.1.2.1.1.1.1.5. Email            | 36 |
| 1.1.4.1.2.1.1.1.2. BankAcct           | 37 |
| 1.1.4.1.2.1.1.1.3. DirectBill         | 37 |
| 1.1.4.1.2.1.1.1.4. Voucher            | 37 |
| 1.1.4.1.2.1.1.1.5. LoyaltyRedemption  | 38 |
| 1.1.4.1.2.1.1.1.6. MiscChargeOrder    | 38 |
| 1.1.4.1.2.1.1.1.7. Ticket             | 39 |

|                                               |    |
|-----------------------------------------------|----|
| 1.1.4.1.2.1.1.1.1.8. Cash                     | 39 |
| 1.1.4.1.2.1.1.2. Deadline                     | 39 |
| 1.1.4.1.2.1.1.3. Comments                     | 40 |
| 1.1.4.1.2.1.1.3.1. Comment                    | 40 |
| 1.1.4.1.2.1.1.3.1.1. Text                     | 41 |
| 1.1.4.1.2.1.1.3.1.2. ListItem                 | 42 |
| 1.1.4.1.2.1.1.4. GuaranteeDescription         | 42 |
| 1.1.4.1.2.1.1.4.1. Text                       | 43 |
| 1.1.4.1.2.1.1.4.2. ListItem                   | 44 |
| 1.1.4.1.2.1.2. CancelPenalties                | 45 |
| 1.1.4.1.2.1.2.1. CancelPenalty                | 45 |
| 1.1.4.1.2.1.2.1.1. Deadline                   | 46 |
| 1.1.4.1.2.1.2.1.2. AmountPercent              | 46 |
| 1.1.4.1.2.1.2.1.3. PenaltyDescription         | 48 |
| 1.1.4.1.2.1.2.1.3.1. Text                     | 48 |
| 1.1.4.1.2.1.2.1.3.2. ListItem                 | 49 |
| 1.1.4.1.2.1.3. RatePlanDescription            | 50 |
| 1.1.4.1.2.1.3.1. Text                         | 51 |
| 1.1.4.1.2.1.3.2. ListItem                     | 51 |
| 1.1.4.1.2.1.4. RatePlanInclusions             | 52 |
| 1.1.4.1.2.1.4.1. RatePlanInclusionDescription | 53 |
| 1.1.4.1.2.1.4.1.1. Text                       | 53 |
| 1.1.4.1.2.1.4.1.2. ListItem                   | 54 |
| 1.1.4.1.2.1.5. Commission                     | 55 |
| 1.1.4.1.2.1.5.1. CommissionPayableAmount      | 56 |
| 1.1.4.1.2.1.5.2. Comment                      | 56 |
| 1.1.4.1.2.1.5.2.1. Text                       | 57 |
| 1.1.4.1.2.1.5.2.2. ListItem                   | 58 |
| 1.1.4.1.2.1.6. MealsIncluded                  | 59 |
| 1.1.4.1.2.1.7. RestrictionStatus              | 59 |
| 1.1.4.1.2.1.8. AdditionalDetails              | 59 |
| 1.1.4.1.2.1.8.1. AdditionalDetail             | 60 |
| 1.1.4.1.2.1.8.1.1. DetailDescription          | 60 |
| 1.1.4.1.2.1.8.1.1.1. Text                     | 61 |
| 1.1.4.1.2.1.8.1.1.2. ListItem                 | 62 |
| 1.1.4.1.2.1.9. ModificationFee                | 63 |

|                                            |    |
|--------------------------------------------|----|
| 1.1.4.1.2.1.9.1. CancelPenalty             | 64 |
| 1.1.4.1.2.1.9.1.1. Deadline                | 64 |
| 1.1.4.1.2.1.9.1.2. AmountPercent           | 65 |
| 1.1.4.1.2.1.9.1.3. PenaltyDescription      | 66 |
| 1.1.4.1.2.1.9.1.3.1. Text                  | 67 |
| 1.1.4.1.2.1.9.1.3.2. ListItem              | 67 |
| 1.1.4.1.3. RoomRates                       | 68 |
| 1.1.4.1.3.1. RoomRate                      | 69 |
| 1.1.4.1.3.1.1. Rates                       | 71 |
| 1.1.4.1.3.1.1.1. Rate                      | 71 |
| 1.1.4.1.3.1.1.1.1. Base                    | 73 |
| 1.1.4.1.3.1.1.1.1.1. Taxes                 | 74 |
| 1.1.4.1.3.1.1.1.1.1.1. Tax                 | 74 |
| 1.1.4.1.3.1.1.1.1.1.1. TaxDescription      | 75 |
| 1.1.4.1.3.1.1.1.1.1.1.1. Text              | 76 |
| 1.1.4.1.3.1.1.1.1.1.1.2. ListItem          | 77 |
| 1.1.4.1.3.1.1.1.2. Fees                    | 78 |
| 1.1.4.1.3.1.1.1.2.1. Fee                   | 78 |
| 1.1.4.1.3.1.1.1.2.1.1. Taxes               | 80 |
| 1.1.4.1.3.1.1.1.2.1.1.1. Tax               | 80 |
| 1.1.4.1.3.1.1.1.2.1.1.1.1. TaxDescription  | 81 |
| 1.1.4.1.3.1.1.1.2.1.1.1.1.1. Text          | 82 |
| 1.1.4.1.3.1.1.1.2.1.1.1.2. ListItem        | 83 |
| 1.1.4.1.3.1.1.1.2.1.2. Description         | 84 |
| 1.1.4.1.3.1.1.1.2.1.2.1. Text              | 84 |
| 1.1.4.1.3.1.1.1.2.1.2.2. ListItem          | 85 |
| 1.1.4.1.3.1.1.1.3. PaymentPolicies         | 86 |
| 1.1.4.1.3.1.1.1.3.1. GuaranteePayment      | 87 |
| 1.1.4.1.3.1.1.1.3.1.1. AcceptedPayments    | 88 |
| 1.1.4.1.3.1.1.1.3.1.1.1. AcceptedPayment   | 89 |
| 1.1.4.1.3.1.1.1.3.1.1.1.1. PaymentCard     | 89 |
| 1.1.4.1.3.1.1.1.3.1.1.2. BankAcct          | 90 |
| 1.1.4.1.3.1.1.1.3.1.1.3. DirectBill        | 91 |
| 1.1.4.1.3.1.1.1.3.1.1.4. Voucher           | 91 |
| 1.1.4.1.3.1.1.1.3.1.1.5. LoyaltyRedemption | 92 |
| 1.1.4.1.3.1.1.1.3.1.1.6. MiscChargeOrder   | 92 |

|                                             |     |
|---------------------------------------------|-----|
| 1.1.4.1.3.1.1.1.3.1.1.1.7. Ticket           | 92  |
| 1.1.4.1.3.1.1.1.3.1.1.1.8. Cash             | 93  |
| 1.1.4.1.3.1.1.1.3.1.2. AmountPercent        | 93  |
| 1.1.4.1.3.1.1.1.3.1.2.1. Taxes              | 95  |
| 1.1.4.1.3.1.1.1.3.1.2.1.1. Tax              | 96  |
| 1.1.4.1.3.1.1.1.3.1.2.1.1.1. TaxDescription | 97  |
| 1.1.4.1.3.1.1.1.3.1.2.1.1.1.1. Text         | 98  |
| 1.1.4.1.3.1.1.1.3.1.2.1.1.1.2. ListItem     | 98  |
| 1.1.4.1.3.1.1.1.3.1.3. Deadline             | 99  |
| 1.1.4.1.3.1.1.1.3.1.4. Description          | 100 |
| 1.1.4.1.3.1.1.1.3.1.4.1. Text               | 101 |
| 1.1.4.1.3.1.1.1.3.1.4.2. ListItem           | 102 |
| 1.1.4.1.3.1.1.1.3.1.5. Address              | 102 |
| 1.1.4.1.3.1.1.1.3.1.5.1. StreetNmbr         | 103 |
| 1.1.4.1.3.1.1.1.3.1.5.2. AddressLine        | 104 |
| 1.1.4.1.3.1.1.1.3.1.5.3. CityName           | 104 |
| 1.1.4.1.3.1.1.1.3.1.5.4. PostalCode         | 104 |
| 1.1.4.1.3.1.1.1.3.1.5.5. County             | 105 |
| 1.1.4.1.3.1.1.1.3.1.5.6. StateProv          | 105 |
| 1.1.4.1.3.1.1.1.3.1.5.7. CountryName        | 105 |
| 1.1.4.1.3.1.1.1.3.1.6. TPA_Extensions       | 106 |
| 1.1.4.1.3.1.1.1.4. Total                    | 106 |
| 1.1.4.1.3.1.1.1.4.1. Taxes                  | 107 |
| 1.1.4.1.3.1.1.1.4.1.1. Tax                  | 108 |
| 1.1.4.1.3.1.1.1.4.1.1.1. TaxDescription     | 109 |
| 1.1.4.1.3.1.1.1.4.1.1.1.1. Text             | 110 |
| 1.1.4.1.3.1.1.1.4.1.1.1.2. ListItem         | 110 |
| 1.1.4.1.3.1.1.1.5. RateDescription          | 111 |
| 1.1.4.1.3.1.1.1.5.1. Text                   | 112 |
| 1.1.4.1.3.1.1.1.5.2. ListItem               | 113 |
| 1.1.4.1.3.1.1.1.6. AdditionalCharges        | 114 |
| 1.1.4.1.3.1.1.1.6.1. AdditionalCharge       | 114 |
| 1.1.4.1.3.1.1.1.6.1.1. Amount               | 115 |
| 1.1.4.1.3.1.1.1.6.1.1.1. Taxes              | 116 |
| 1.1.4.1.3.1.1.1.6.1.1.1.1. Tax              | 116 |
| 1.1.4.1.3.1.1.1.6.1.1.1.1.1. TaxDescription | 117 |



|                                          |     |
|------------------------------------------|-----|
| 1.1.4.1.3.1.1.1.6.1.1.1.1.1.1. Text      | 118 |
| 1.1.4.1.3.1.1.1.6.1.1.1.1.1.2. ListItem  | 119 |
| 1.1.4.1.3.1.1.1.7. TPA_Extensions        | 120 |
| 1.1.4.1.3.1.2. RoomRateDescription       | 120 |
| 1.1.4.1.3.1.2.1. Text                    | 121 |
| 1.1.4.1.3.1.2.2. ListItem                | 122 |
| 1.1.4.1.3.1.3. Features                  | 123 |
| 1.1.4.1.3.1.3.1. Feature                 | 123 |
| 1.1.4.1.3.1.3.1.1. Description           | 124 |
| 1.1.4.1.3.1.3.1.1.1. Text                | 125 |
| 1.1.4.1.3.1.3.1.1.2. ListItem            | 125 |
| 1.1.4.1.3.1.4. Total                     | 126 |
| 1.1.4.1.3.1.4.1. Taxes                   | 127 |
| 1.1.4.1.3.1.4.1.1. Tax                   | 128 |
| 1.1.4.1.3.1.4.1.1.1. TaxDescription      | 128 |
| 1.1.4.1.3.1.4.1.1.1.1. Text              | 129 |
| 1.1.4.1.3.1.4.1.1.1.2. ListItem          | 130 |
| 1.1.4.1.3.1.5. Availability              | 131 |
| 1.1.4.1.3.1.6. AdvanceBookingRestriction | 131 |
| 1.1.4.1.3.1.7. ServiceRPHs               | 132 |
| 1.1.4.1.3.1.7.1. ServiceRPH              | 132 |
| 1.1.4.1.3.1.8. GuestCounts               | 133 |
| 1.1.4.1.3.1.8.1. GuestCount              | 133 |
| 1.1.4.1.3.2. TPA_Extensions              | 134 |
| 1.1.4.1.4. GuestCounts                   | 134 |
| 1.1.4.1.4.1. GuestCount                  | 135 |
| 1.1.4.1.5. TimeSpan                      | 135 |
| 1.1.4.1.5.1. DateWindowRange             | 136 |
| 1.1.4.1.5.2. StartDateWindow             | 136 |
| 1.1.4.1.5.3. EndDateWindow               | 137 |
| 1.1.4.1.6. Total                         | 137 |
| 1.1.4.1.6.1. Taxes                       | 138 |
| 1.1.4.1.6.1.1. Tax                       | 138 |
| 1.1.4.1.6.1.1.1. TaxDescription          | 139 |
| 1.1.4.1.6.1.1.1.1. Text                  | 140 |
| 1.1.4.1.6.1.1.1.2. ListItem              | 141 |

|                                |     |
|--------------------------------|-----|
| 1.1.4.1.7. TPA_Extensions      | 141 |
| 1.1.4.1.8. Reference           | 142 |
| 1.1.4.1.8.1. CompanyName       | 143 |
| 1.1.4.1.9. ServiceRPHs         | 143 |
| 1.1.4.1.9.1. ServiceRPH        | 144 |
| 1.1.5. Services                | 144 |
| 1.1.5.1. Service               | 144 |
| 1.1.5.1.1. Price               | 146 |
| 1.1.5.1.1.1. Base              | 146 |
| 1.1.5.1.1.2. Total             | 147 |
| 1.1.5.1.2. ServiceDetails      | 148 |
| 1.1.5.1.2.1. GuestCounts       | 148 |
| 1.1.5.1.2.1.1. GuestCount      | 149 |
| 1.1.5.1.2.2. TimeSpan          | 149 |
| 1.1.5.1.2.2.1. DateWindowRange | 150 |
| 1.1.5.1.2.3. Comments          | 150 |
| 1.1.5.1.2.3.1. Comment         | 151 |
| 1.1.5.1.2.3.1.1. Text          | 151 |
| 1.1.5.1.2.3.1.2. ListItem      | 152 |
| 1.1.5.1.2.4. Total             | 153 |
| 1.1.5.1.3. TPA_Extensions      | 153 |
| 1.1.6. Areas                   | 154 |
| 1.1.6.1. Area                  | 154 |
| 1.1.7. Criteria                | 155 |
| 1.1.7.1. Criterion             | 155 |
| 1.1.7.1.1. Position            | 156 |
| 1.1.7.1.2. RefPoint            | 157 |
| 1.1.7.1.3. CodeRef             | 157 |
| 1.1.7.1.4. Radius              | 158 |
| 1.1.7.1.5. MapArea             | 158 |
| 1.1.7.1.6. TPA_Extensions      | 158 |
| 1.1.8. CurrencyConversions     | 159 |
| 1.1.8.1. CurrencyConversion    | 159 |
| 1.1.9. TPA_Extensions          | 160 |
| 1.1.10. Errors                 | 160 |
| 1.1.10.1. Error                | 161 |

|                                |     |
|--------------------------------|-----|
| 2. Common Simple Types         | 162 |
| 2.1. AlphaLength3              | 162 |
| 2.2. AmountDeterminationType   | 162 |
| 2.3. AvailabilityStatusType    | 162 |
| 2.4. DateOrDateTimeType        | 162 |
| 2.5. DateOrTimeOrDateTimeType  | 163 |
| 2.6. DayOfWeekType             | 163 |
| 2.7. DurationType              | 163 |
| 2.8. InfoSourceType            | 163 |
| 2.9. ISO3166                   | 164 |
| 2.10. ListOfOTA_CodeType       | 164 |
| 2.11. ListOfRPH                | 164 |
| 2.12. Money                    | 164 |
| 2.13. NightDurationType        | 165 |
| 2.14. Numeric0to99             | 165 |
| 2.15. Numeric0to999            | 165 |
| 2.16. Numeric1to99             | 165 |
| 2.17. Numeric1to999            | 166 |
| 2.18. NumericStringLength1to16 | 166 |
| 2.19. NumericStringLength1to5  | 166 |
| 2.20. NumericStringLength1to8  | 166 |
| 2.21. OTA_CodeType             | 167 |
| 2.22. PaymentCardCodeType      | 167 |
| 2.23. Percentage               | 168 |
| 2.24. PricingType              | 168 |
| 2.25. RateIndicatorType        | 168 |
| 2.26. RPH_Type                 | 169 |
| 2.27. StateProvCodeType        | 169 |
| 2.28. StringLength0to128       | 169 |
| 2.29. StringLength0to64        | 170 |
| 2.30. StringLength1to128       | 170 |
| 2.31. StringLength1to16        | 170 |
| 2.32. StringLength1to255       | 171 |
| 2.33. StringLength1to32        | 171 |
| 2.34. StringLength1to64        | 171 |
| 2.35. StringLength1to8         | 171 |

|                                      |     |
|--------------------------------------|-----|
| 2.36. TimeOrDateTimeType .....       | 172 |
| 2.37. TimeUnitType .....             | 172 |
| 2.38. UpperCaseAlphaLength1to2 ..... | 172 |

# 1. Technical Reference

## 1.1. OTA\_HotelAvailRS

XPath :/OTA\_HotelAvailRS

### Format Description

| Name             | Type | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                 |
|------------------|------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OTA_HotelAvailRS |      | 1 / 1 | false | Returns information about hotel properties that meet the requested criteria, indicating whether the requested service, rate, room stay, etc. is available within the date(s) specified. The response message may include Warnings from business processing rules, or Errors if the request did not succeed. |

### Elements

| Name                                | Type               | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                 |
|-------------------------------------|--------------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                     |                    | 1 / 1 |       |                                                                                                                                                                                                                                                                                                             |
| <i>choice</i>                       |                    | 1 / 1 |       |                                                                                                                                                                                                                                                                                                             |
| <i>sequence</i>                     |                    | 1 / 1 |       |                                                                                                                                                                                                                                                                                                             |
| <a href="#">Success</a>             | SuccessType        | 1 / 1 | false | An element that is not intended to contain any data. The mere presence of a success element within the response message indicates that the incoming request message was processed successfully.                                                                                                             |
| <a href="#">Warnings</a>            | WarningsType       | 0 / 1 | false | Indicates that the recipient of the request message identified one or more business-level warnings/errors, but the message itself was successfully processed.                                                                                                                                               |
| <a href="#">HotelStays</a>          |                    | 0 / 1 | false | A collection of summarized information about the requested hotels' general availability for each day in the requested range.                                                                                                                                                                                |
| <a href="#">RoomStays</a>           |                    | 0 / 1 | false | A collection of details on the Room Stay including Guest Counts, Time Span of this Room Stay, and financial information related to the Room Stay, including Guarantee, Deposit and Payment and Cancellation Penalties.                                                                                      |
| <a href="#">Services</a>            | ServicesType       | 0 / 1 | false | A collection of Service objects. This is the collection of all services associated with any part of this reservation (the reservation in its entirety, one or more guests, or one or more room stays). Which services are attributable to which part is determined by each object's ServiceRPHs collection. |
| <a href="#">Areas</a>               | AreasType          | 0 / 1 | false | Defines a collection of areas determined by the hotel reservation system.                                                                                                                                                                                                                                   |
| <a href="#">Criteria</a>            |                    | 0 / 1 | false | The availability search criteria specified in the request message.                                                                                                                                                                                                                                          |
| <a href="#">CurrencyConversions</a> |                    | 0 / 1 | false | A collection of currency conversion elements.                                                                                                                                                                                                                                                               |
| <a href="#">TPA_Extensions</a>      | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA).                                                                                                                                                                             |

|                        |            |       |       |                                                                                                                                                                 |
|------------------------|------------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">Errors</a> | ErrorsType | 1 / 1 | false | Indicates that an error occurred in the processing of the incoming request message. An error is defined as a malformed XML message that could not be processed. |
|------------------------|------------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Attributes

| Name                             | Type                               | Use      | Value | Description                                                                                                                                                                                                    |
|----------------------------------|------------------------------------|----------|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EchoToken                        | <a href="#">StringLength1to128</a> | required |       | A reference for additional message identification, assigned by the requesting host system.<br>Set to MultiSingle.                                                                                              |
| TimeStamp                        | xs:dateTime                        | optional |       | Transaction date and time. Received for tracking purposes.                                                                                                                                                     |
| Version                          | xs:decimal                         | required |       | Set to value 7.000                                                                                                                                                                                             |
| TransactionIdentifier            | xs:string                          | optional |       | Unique identifier to relate all messages within a transaction (e.g. this would be sent in all request and response messages that are part of an on-going transaction).<br>Unique identifier of the transaction |
| PrimaryLangID                    | xs:language                        | required |       | Requested language.                                                                                                                                                                                            |
| <a href="#">SearchCacheLevel</a> |                                    | optional |       |                                                                                                                                                                                                                |

Attribute: SearchCacheLevel

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description |
|-------------|-------------|
| Live        |             |
| VeryRecent  |             |
| LessRecent  |             |

### 1.1.1.1. Success

XPath :/OTA\_HotelAvailRS/Success

## Format Description

| Name    | Type        | Occ   | Nil   | Description                                                                                                                                                                                     |
|---------|-------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Success | SuccessType | 1 / 1 | false | An element that is not intended to contain any data. The mere presence of a success element within the response message indicates that the incoming request message was processed successfully. |

### 1.1.2. Warnings

XPath :/OTA\_HotelAvailRS/Warnings

#### Format Description

| Name     | Type         | Occ   | Nil   | Description                                                                                                                                                   |
|----------|--------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Warnings | WarningsType | 0 / 1 | false | Indicates that the recipient of the request message identified one or more business-level warnings/errors, but the message itself was successfully processed. |

#### Elements

| Name                    | Type        | Occ     | Nil   | Description                                                              |
|-------------------------|-------------|---------|-------|--------------------------------------------------------------------------|
| <i>sequence</i>         |             | 1 / 1   |       |                                                                          |
| <a href="#">Warning</a> | WarningType | 1 / 999 | false | Used in conjunction with the Success element to define a business error. |

#### 1.1.2.1. Warning

XPath :/OTA\_HotelAvailRS/Warnings/Warning

#### Format Description

| Name    | Type      | Occ     | Nil   | Description                                                              |
|---------|-----------|---------|-------|--------------------------------------------------------------------------|
| Warning | xs:string | 1 / 999 | false | Used in conjunction with the Success element to define a business error. |

#### Attributes

| Name      | Type                              | Use      | Value | Description                                                                                                                                                                                                                                                                                                                          |
|-----------|-----------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Language  | xs:language                       | optional |       | Language identification.                                                                                                                                                                                                                                                                                                             |
| Type      | <a href="#">OTA_CodeType</a>      | required |       | The Warning element MUST contain the Type attribute that uses a recommended set of values to indicate the warning type. The validating XSD can expect to accept values that it has NOT been explicitly coded for and process them by using Type ="Unknown". Refer to OpenTravel Code List Error Warning Type (EWT).<br><br>Set to 3. |
| ShortText | <a href="#">StringLength1to64</a> | optional |       | Hotel code of the hotel that generated the warning                                                                                                                                                                                                                                                                                   |
| Code      | <a href="#">OTA_CodeType</a>      | optional |       | If present, this refers to a table of coded values exchanged between applications to identify errors or warnings. Refer to OpenTravel Code List Error Codes (ERR).                                                                                                                                                                   |

|        |                                   |          |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|--------|-----------------------------------|----------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Status | <a href="#">StringLength1to64</a> | optional |  | concatenation of the status type (among 1AC, 1AD, PRV) and the number of properties with this status.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Tag    | xs:string                         | optional |  | AVL: Properties for which the rate code is not available<br>CLS: Properties closed<br>CSF: Central system failure<br>ERR: Properties for which the provider sent an error at message level<br>LOC: Properties for which the requested rate code is not at location<br>OK: Properties with a rate range<br>PE: 1A processing error<br>PUE: Provider unknown error<br>QU: Properties filtered due to rate limit or rate range<br>RST: Properties for which the requested rate code is restricted<br>PG: Properties belonging to a partially opened country (see Search by Distance for more information) |
| RPH    | <a href="#">RPH_Type</a>          | optional |  | Reference Place Holder used as an index for this warning.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

### 1.1.3. HotelStays

XPath :/OTA\_HotelAvailRS/HotelStays

#### Format Description

| Name       | Type | Occ   | Nil   | Description                                                                                                                  |
|------------|------|-------|-------|------------------------------------------------------------------------------------------------------------------------------|
| HotelStays |      | 0 / 1 | false | A collection of summarized information about the requested hotels' general availability for each day in the requested range. |

#### Elements

| Name                      | Type | Occ               | Nil   | Description                                                                                     |
|---------------------------|------|-------------------|-------|-------------------------------------------------------------------------------------------------|
| <i>sequence</i>           |      | 1 / 1             |       |                                                                                                 |
| <a href="#">HotelStay</a> |      | 1 / unbound<br>ed | false | A quick view of the requested hotels' general availability for each day in the requested range. |

### 1.1.3.1. HotelStay

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay

#### Format Description

| Name      | Type | Occ               | Nil   | Description                                                                                     |
|-----------|------|-------------------|-------|-------------------------------------------------------------------------------------------------|
| HotelStay |      | 1 / unbound<br>ed | false | A quick view of the requested hotels' general availability for each day in the requested range. |



## Elements

| Name                              | Type                  | Occ            | Nil   | Description                                                                                           |
|-----------------------------------|-----------------------|----------------|-------|-------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                   |                       | 1 / 1          |       |                                                                                                       |
| <a href="#">Availability</a>      |                       | 0 / unbound ed | false | Details on the hotel stay including the type of availability and the date range for which it applies. |
| <a href="#">BasicPropertyInfo</a> | BasicPropertyInfoType | 0 / 1          | false | Property Information for the Hotel Stay.                                                              |
| <a href="#">Price</a>             |                       | 0 / unbound ed | false | Pricing for the hotel stay including the date range for which it applies.                             |

## Attributes

| Name        | Type                      | Use      | Value | Description                                                        |
|-------------|---------------------------|----------|-------|--------------------------------------------------------------------|
| RoomStayRPH | <a href="#">ListOfRPH</a> | optional |       | References one or more room stays associated with this hotel stay. |

### 1.1.3.1.1. Availability

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/Availability

## Format Description

| Name         | Type | Occ            | Nil   | Description                                                                                           |
|--------------|------|----------------|-------|-------------------------------------------------------------------------------------------------------|
| Availability |      | 0 / unbound ed | false | Details on the hotel stay including the type of availability and the date range for which it applies. |

## Elements

| Name                        | Type | Occ   | Nil   | Description                                  |
|-----------------------------|------|-------|-------|----------------------------------------------|
| <i>sequence</i>             |      | 1 / 1 |       |                                              |
| <a href="#">Restriction</a> |      | 0 / 5 | false | Restrictions pertaining to the availability. |

## Attributes

| Name   | Type                                   | Use      | Value | Description                                                                    |
|--------|----------------------------------------|----------|-------|--------------------------------------------------------------------------------|
| Status | <a href="#">AvailabilityStatusType</a> | required |       | Used to specify an availability status at the Hotel Stay level for a property. |

### 1.1.3.1.1.1. Restriction

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/Availability/Restriction

#### Format Description

| Name        | Type | Occ   | Nil   | Description                                  |
|-------------|------|-------|-------|----------------------------------------------|
| Restriction |      | 0 / 5 | false | Restrictions pertaining to the availability. |

#### Attributes

| Name                            | Type                         | Use      | Value | Description                                                                                                                                                   |
|---------------------------------|------------------------------|----------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">RestrictionType</a> |                              | optional |       | Stay restriction that applies to the availability.                                                                                                            |
| Time                            | xs:integer                   | optional |       | Used in conjunction with the RestrictionType and the TimeUnit to define the restriction length.                                                               |
| TimeUnit                        | <a href="#">TimeUnitType</a> | optional |       | A time unit used to apply this status message to other inventory, and with more granularity than daily. Values: Year, Month, Week, Day, Hour, Minute, Second. |

Attribute: RestrictionType

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration    | description                                                              |
|----------------|--------------------------------------------------------------------------|
| MinLOS         | Indicates the time unit is for the minimum length of stay restriction.   |
| MaxLOS         | Indicates the time unit is for the maximum length of stay restriction.   |
| FixedLOS       | Indicates the time unit is for the fixed length of stay restriction.     |
| MinAdvanceBook | Indicates the time unit is for the minimum advanced booking restriction. |

### 1.1.3.1.2. BasicPropertyInfo

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo

#### Format Description

| Name              | Type                  | Occ   | Nil   | Description                              |
|-------------------|-----------------------|-------|-------|------------------------------------------|
| BasicPropertyInfo | BasicPropertyInfoType | 0 / 1 | false | Property Information for the Hotel Stay. |

## Elements

| Name                                 | Type                 | Occ               | Nil   | Description                                                                                                                                                                       |
|--------------------------------------|----------------------|-------------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                      |                      | 1 / 1             |       |                                                                                                                                                                                   |
| <a href="#">VendorMessages</a>       | VendorMessagesType   | 0 / 1             | false | A collection of VenderMessages.                                                                                                                                                   |
| <a href="#">Position</a>             |                      | 0 / 1             | false | An element that identifies the geographic position of the hotel. The Position element uses the representation defined by ISO Standard 6709 to define a geographic point location. |
| <a href="#">Address</a>              | AddressInfoType      | 0 / 1             | false | Public address of the hotel property.                                                                                                                                             |
| <a href="#">ContactNumbers</a>       |                      | 0 / 1             | false | Collection of hotel contact numbers.                                                                                                                                              |
| <a href="#">Award</a>                |                      | 0 / 5             | false | An element that identifies the hotel ratings.                                                                                                                                     |
| <a href="#">RelativePosition</a>     | RelativePositionType | 0 / 1             | false | Describes the location of the property and available to/from transportation methods.                                                                                              |
| <a href="#">HotelAmenity</a>         |                      | 0 / unbound<br>ed | false | Hotel-level amenities (pool, etc) for searching. OTA Code Type HAC                                                                                                                |
| <a href="#">HotelFeature</a>         |                      | 0 / unbound<br>ed | false | Identifies features of a property.                                                                                                                                                |
| <a href="#">Recreation</a>           |                      | 0 / unbound<br>ed | false | Identifies recreation facilities or amenities of interest.                                                                                                                        |
| <a href="#">Service</a>              |                      | 0 / unbound<br>ed | false | Identifies business services of interest.                                                                                                                                         |
| <a href="#">Policy</a>               |                      | 0 / 1             | false | Policy information for this hotel.                                                                                                                                                |
| <a href="#">HotelMeetingFacility</a> |                      | 0 / unbound<br>ed | false | Identifies hotel meeting facility information for a property.                                                                                                                     |

## Attributes

| Name             | Type                               | Use      | Value | Description                                                                                                                                                                                                                        |
|------------------|------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ChainCode        | <a href="#">StringLength1to8</a>   | optional |       | The code that identifies a hotel chain or management group. The hotel chain code is decided between vendors. This attribute is optional if the hotel is an independent property that can be identified by the HotelCode attribute. |
| HotelCode        | <a href="#">StringLength1to16</a>  | optional |       | The code that uniquely identifies a single hotel property. The hotel code is decided between vendors.                                                                                                                              |
| HotelCityCode    | <a href="#">StringLength1to8</a>   | optional |       | The IATA city code; for example DCA, ORD.                                                                                                                                                                                          |
| HotelName        | <a href="#">StringLength1to128</a> | optional |       | A text field used to communicate the proper name of the hotel.                                                                                                                                                                     |
| HotelCodeContext | <a href="#">StringLength1to32</a>  | optional |       | A text field used to communicate the context (or source of - ex Sabre, Galileo, Worldspan, Amadeus) the HotelReferenceGroup codes.                                                                                                 |
| ChainName        | <a href="#">StringLength1to64</a>  | optional |       | The name of the hotel chain (e.g., Hilton, Marriott, Hyatt, Starwood).                                                                                                                                                             |

|                          |                                         |          |  |                                                                                                                                                                                                                                                                                                                                                        |
|--------------------------|-----------------------------------------|----------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ArealID                  | <a href="#">NumericStringLength1to8</a> | optional |  | An identifier of an area as defined by a hotel reservation system.                                                                                                                                                                                                                                                                                     |
| HotelSegmentCategoryCode | <a href="#">OTA_CodeType</a>            | optional |  | Identifies the segment (e.g., luxury, upscale, extended stay) of the hotel. Refer to OpenTravel Codelist Segment Category Code (SEG).                                                                                                                                                                                                                  |
| SupplierIntegrationLevel | xs:nonNegativeInteger                   | optional |  | The level of integration of a property to provide automated transaction information. The lower the number, the higher the integration (e.g., a 1 means the supplier has the highest level of integration automation).                                                                                                                                  |
| CurrencyCode             | <a href="#">AlphaLength3</a>            | optional |  | The code specifying a monetary unit. Use ISO 4217, three alpha code.                                                                                                                                                                                                                                                                                   |
| MasterChainCode          | <a href="#">StringLength1to8</a>        | optional |  | The code that identifies a hotel chain or management group. The hotel chain code is decided between vendors. This attribute is optional if the hotel is an independent property that can be identified by the HotelCode attribute. Use it in conjunction with the chain code to determine the actual chain code that is used between trading partners. |

### 1.1.3.1.2.1. VendorMessages

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/VendorMessages

#### Format Description

| Name           | Type               | Occ   | Nil   | Description                     |
|----------------|--------------------|-------|-------|---------------------------------|
| VendorMessages | VendorMessagesType | 0 / 1 | false | A collection of VenderMessages. |

#### Elements

| Name                          | Type              | Occ    | Nil   | Description                                     |
|-------------------------------|-------------------|--------|-------|-------------------------------------------------|
| <i>sequence</i>               |                   | 1 / 1  |       |                                                 |
| <a href="#">VendorMessage</a> | VendorMessageType | 1 / 99 | false | A specific message associated with this vendor. |

### 1.1.3.1.2.1.1. VendorMessage

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/VendorMessages/VendorMessage

#### Format Description

| Name          | Type              | Occ    | Nil   | Description                                     |
|---------------|-------------------|--------|-------|-------------------------------------------------|
| VendorMessage | FormattedTextType | 1 / 99 | false | A specific message associated with this vendor. |

#### Elements

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|                            |                             |        |       |                                        |
|----------------------------|-----------------------------|--------|-------|----------------------------------------|
| <i>sequence</i>            |                             | 1 / 1  |       |                                        |
| <a href="#">SubSection</a> | FormattedTextSubSectionType | 1 / 99 | false | Subsection formatted text information. |

## Attributes

| Name     | Type                              | Use      | Value | Description                                                                                                                                                                                                                                                            |
|----------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Title    | <a href="#">StringLength1to64</a> | optional |       | This attribute may be used to provide a title for the formatted free text, for example, Driving Directions. Each of the sub sections that are defined to be a part of the formatted text would provide detailed information about the subject identified by the title. |
| Language | xs:language                       | optional |       | The language in which the content is provided.                                                                                                                                                                                                                         |
| InfoType | <a href="#">OTA_CodeType</a>      | required |       | To define the type of information such as Description, Policy, Marketing, etc. Refer to OpenTravel Code List Information Type (INF).<br>Current values used:<br>3 for Marketing text<br>15 for Services                                                                |

### 1.1.3.1.2.1.1.1. SubSection

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/VendorMessages/VendorMessage/SubSection

## Format Description

| Name       | Type                        | Occ    | Nil   | Description                            |
|------------|-----------------------------|--------|-------|----------------------------------------|
| SubSection | FormattedTextSubSectionType | 1 / 99 | false | Subsection formatted text information. |

## Elements

| Name                      | Type          | Occ    | Nil   | Description                                                      |
|---------------------------|---------------|--------|-------|------------------------------------------------------------------|
| <i>sequence</i>           |               | 1 / 1  |       |                                                                  |
| <a href="#">Paragraph</a> | ParagraphType | 1 / 99 | false | Details and content of a paragraph for a formatted text message. |

## Attributes

| Name | Type | Use | Value | Description |
|------|------|-----|-------|-------------|
|------|------|-----|-------|-------------|

|                  |                                   |          |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------|-----------------------------------|----------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SubTitle         | <a href="#">StringLength1to64</a> | optional |  | This attribute may be used to provide a title for a sub-section of the formatted free text. A sub-section may have multiple related paragraphs of information. For example, if used to provide driving directions there may be multiple paragraphs, and these paragraphs may be grouped into a sub-section called "Driving from the North". A second subsection may be titled "Driving from the South", and may contain several paragraphs to describe the driving directions when driving from the south. |
| SubCode          | <a href="#">StringLength1to8</a>  | optional |  | An optional code that may be assigned to this sub-section of formatted free text.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| SubSectionNumber | <a href="#">Numeric1to999</a>     | optional |  | This attribute may be used when there is a need to number all of the sub-sections of information that is to be presented.                                                                                                                                                                                                                                                                                                                                                                                  |

### 1.1.3.1.2.1.1.1.1. Paragraph

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/VendorMessages/VendorMessage/SubSection/Paragraph

#### Format Description

| Name      | Type          | Occ    | Nil   | Description                                                      |
|-----------|---------------|--------|-------|------------------------------------------------------------------|
| Paragraph | ParagraphType | 1 / 99 | false | Details and content of a paragraph for a formatted text message. |

#### Elements

| Name                     | Type              | Occ            | Nil   | Description                                                       |
|--------------------------|-------------------|----------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbound ed |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1          | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1          | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1          | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1          | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name            | Type                              | Use      | Value | Description                                                                                                                                                                        |
|-----------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name            | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime  | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID       | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |

|                    |                                   |          |  |                                                                                         |
|--------------------|-----------------------------------|----------|--|-----------------------------------------------------------------------------------------|
| LastModifyDateTime | xs:dateTime                       | optional |  | Time stamp of last modification.                                                        |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |  | Identifies the last software system or person to modify a record.                       |
| PurgeDate          | xs:date                           | optional |  | Date an item will be purged from a database (e.g., from a live database to an archive). |
| Language           | xs:language                       | optional |  | Language identification.                                                                |

### 1.1.3.1.2.1.1.1.1.1. Text

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/VendorMessages/VendorMessage/SubSection/Paragraph/Text

#### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.3.1.2.1.1.1.1.2. ListItem

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/VendorMessages/VendorMessage/SubSection/Paragraph/ListItem

### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.3.1.2.2. Position

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Position

### Format Description

| Name     | Type | Occ   | Nil   | Description                                                                                                                                                                       |
|----------|------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Position |      | 0 / 1 | false | An element that identifies the geographic position of the hotel. The Position element uses the representation defined by ISO Standard 6709 to define a geographic point location. |

### Attributes



| Name                      | Type                              | Use      | Value | Description                                                                                                                                                                           |
|---------------------------|-----------------------------------|----------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Latitude                  | <a href="#">StringLength1to16</a> | required |       | The measure of the angular distance on a meridian north or south of the equator.                                                                                                      |
| Longitude                 | <a href="#">StringLength1to16</a> | required |       | The measure of the angular distance on a meridian east or west of the prime meridian.                                                                                                 |
| Altitude                  | <a href="#">StringLength1to16</a> | optional |       | The height of an item, typically above sea level.                                                                                                                                     |
| AltitudeUnitOfMeasureCode | <a href="#">OTA_CodeType</a>      | optional |       | Provides the unit of measure for the altitude (e.g., feet, meters, miles, kilometers). Refer to OpenTravel Code List Unit of Measure Code (UOM).                                      |
| PositionAccuracyCode      | <a href="#">OTA_CodeType</a>      | optional |       | Indicates the accuracy of the property's geo-coding, since the property's longitude and latitude may not always be exact. Refer to OpenTravel Code List Position Accuracy Code (PAC). |
| MapURL                    | xs:anyURI                         | optional |       | The URL of a map image.                                                                                                                                                               |

### 1.1.3.1.2.3. Address

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address

#### Format Description

| Name    | Type        | Occ   | Nil   | Description                           |
|---------|-------------|-------|-------|---------------------------------------|
| Address | AddressType | 0 / 1 | false | Public address of the hotel property. |

#### Elements

| Name                        | Type                               | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                                   |
|-----------------------------|------------------------------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>             |                                    | 1 / 1 |       |                                                                                                                                                                                                                                                                                                                               |
| <a href="#">StreetNmbr</a>  |                                    | 0 / 1 | false | May contain the street number and optionally the street name.                                                                                                                                                                                                                                                                 |
| <a href="#">BldgRoom</a>    |                                    | 0 / 2 | false | Building name, room, apartment, or suite number.                                                                                                                                                                                                                                                                              |
| <a href="#">AddressLine</a> | <a href="#">StringLength1to255</a> | 0 / 5 | false | When the address is unformatted (FormattedInd="false") these lines will contain free form address details. When the address is formatted and street number and street name must be sent independently, the street number will be sent using StreetNmbr, and the street name will be sent in the first AddressLine occurrence. |
| <a href="#">CityName</a>    | <a href="#">StringLength1to64</a>  | 0 / 1 | false | City (e.g., Dublin), town, or postal station (i.e., a postal service territory, often used in a military address).                                                                                                                                                                                                            |
| <a href="#">PostalCode</a>  | <a href="#">StringLength1to16</a>  | 0 / 1 | false | Post Office Code number.                                                                                                                                                                                                                                                                                                      |
| <a href="#">County</a>      | <a href="#">StringLength1to32</a>  | 0 / 1 | false | County or Region Name (e.g., Fairfax).                                                                                                                                                                                                                                                                                        |
| <a href="#">StateProv</a>   | StateProvType                      | 0 / 1 | false | State or Province name (e.g., Texas).                                                                                                                                                                                                                                                                                         |
| <a href="#">CountryName</a> | CountryNameType                    | 0 / 1 | false | Country name (e.g., Ireland).                                                                                                                                                                                                                                                                                                 |

#### Attributes

| Name         | Type       | Use      | Value | Description                                                                                                            |
|--------------|------------|----------|-------|------------------------------------------------------------------------------------------------------------------------|
| FormattedInd | xs:boolean | optional |       | Specifies if the associated data is formatted or not. When true, then it is formatted; when false, then not formatted. |

### 1.1.3.1.2.3.1. StreetNmbr

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address/StreetNmbr

#### Format Description

| Name       | Type                              | Occ   | Nil   | Description                                                   |
|------------|-----------------------------------|-------|-------|---------------------------------------------------------------|
| StreetNmbr | <a href="#">StringLength0to64</a> | 0 / 1 | false | May contain the street number and optionally the street name. |

#### Attributes

| Name             | Type                                    | Use      | Value | Description                                                                             |
|------------------|-----------------------------------------|----------|-------|-----------------------------------------------------------------------------------------|
| PO_Box           | <a href="#">StringLength1to16</a>       | optional |       | Defines a Post Office Box number.                                                       |
| StreetNmbrSuffix | <a href="#">StringLength1to8</a>        | optional |       | Usually a letter right after the street number (A in 66-A, B in 123-B etc).             |
| StreetDirection  | <a href="#">StringLength1to8</a>        | optional |       | Street direction of an address (e.g., N, E, S, NW, SW).                                 |
| RuralRouteNmbr   | <a href="#">NumericStringLength1to5</a> | optional |       | Numerical equivalent of a rural township as defined within a given area (e.g., 12, 99). |

### 1.1.3.1.2.3.2. BldgRoom

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address/BldgRoom

#### Format Description

| Name     | Type                              | Occ   | Nil   | Description                                      |
|----------|-----------------------------------|-------|-------|--------------------------------------------------|
| BldgRoom | <a href="#">StringLength0to64</a> | 0 / 2 | false | Building name, room, apartment, or suite number. |

#### Attributes

| Name              | Type       | Use      | Value | Description                                    |
|-------------------|------------|----------|-------|------------------------------------------------|
| BldgNameIndicator | xs:boolean | optional |       | When true, the information is a building name. |

### 1.1.3.1.2.3.3. AddressLine

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address/AddressLine

### Format Description

| Name        | Type                               | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                                   |
|-------------|------------------------------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AddressLine | <a href="#">StringLength1to255</a> | 0 / 5 | false | When the address is unformatted (FormattedInd="false") these lines will contain free form address details. When the address is formatted and street number and street name must be sent independently, the street number will be sent using StreetNmbr, and the street name will be sent in the first AddressLine occurrence. |

#### 1.1.3.1.2.3.4. CityName

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address/CityName

### Format Description

| Name     | Type                              | Occ   | Nil   | Description                                                                                                        |
|----------|-----------------------------------|-------|-------|--------------------------------------------------------------------------------------------------------------------|
| CityName | <a href="#">StringLength1to64</a> | 0 / 1 | false | City (e.g., Dublin), town, or postal station (i.e., a postal service territory, often used in a military address). |

#### 1.1.3.1.2.3.5. PostalCode

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address/PostalCode

### Format Description

| Name       | Type                              | Occ   | Nil   | Description              |
|------------|-----------------------------------|-------|-------|--------------------------|
| PostalCode | <a href="#">StringLength1to16</a> | 0 / 1 | false | Post Office Code number. |

#### 1.1.3.1.2.3.6. County

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address/County

### Format Description

| Name   | Type                              | Occ   | Nil   | Description                            |
|--------|-----------------------------------|-------|-------|----------------------------------------|
| County | <a href="#">StringLength1to32</a> | 0 / 1 | false | County or Region Name (e.g., Fairfax). |

#### 1.1.3.1.2.3.7. StateProv

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address/StateProv

### Format Description

| Name      | Type                              | Occ   | Nil   | Description                           |
|-----------|-----------------------------------|-------|-------|---------------------------------------|
| StateProv | <a href="#">StringLength0to64</a> | 0 / 1 | false | State or Province name (e.g., Texas). |

### Attributes

| Name      | Type                              | Use      | Value | Description                                                           |
|-----------|-----------------------------------|----------|-------|-----------------------------------------------------------------------|
| StateCode | <a href="#">StateProvCodeType</a> | optional |       | The standard code or abbreviation for the state, province, or region. |

## 1.1.3.1.2.3.8. CountryName

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Address/CountryName

### Format Description

| Name        | Type                              | Occ   | Nil   | Description                   |
|-------------|-----------------------------------|-------|-------|-------------------------------|
| CountryName | <a href="#">StringLength0to64</a> | 0 / 1 | false | Country name (e.g., Ireland). |

### Attributes

| Name | Type                    | Use      | Value | Description                  |
|------|-------------------------|----------|-------|------------------------------|
| Code | <a href="#">ISO3166</a> | optional |       | ISO 3166 code for a country. |

## 1.1.3.1.2.4. ContactNumbers

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/ContactNumbers

### Format Description

| Name           | Type | Occ   | Nil   | Description                          |
|----------------|------|-------|-------|--------------------------------------|
| ContactNumbers |      | 0 / 1 | false | Collection of hotel contact numbers. |

### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

|                               |  |                   |       |                                                                                |
|-------------------------------|--|-------------------|-------|--------------------------------------------------------------------------------|
| <a href="#">ContactNumber</a> |  | 0 / unbound<br>ed | false | Contact numbers of the hotel property. Examples are telephone and fax numbers. |
|-------------------------------|--|-------------------|-------|--------------------------------------------------------------------------------|

### 1.1.3.1.2.4.1. **ContactNumber**

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/ContactNumbers/ContactNumber

#### Format Description

| Name          | Type | Occ               | Nil   | Description                                                                    |
|---------------|------|-------------------|-------|--------------------------------------------------------------------------------|
| ContactNumber |      | 0 / unbound<br>ed | false | Contact numbers of the hotel property. Examples are telephone and fax numbers. |

#### Attributes

| Name          | Type                              | Use      | Value | Description                                                                                                                                                                       |
|---------------|-----------------------------------|----------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PhoneTechType | <a href="#">OTA_CodeType</a>      | optional |       | Indicates type of technology associated with this telephone number, such as Voice, Data, Fax, Pager, Mobile, TTY, etc. Refer to OpenTravel Code List Phone Technology Type (PTT). |
| PhoneNumber   | <a href="#">StringLength1to32</a> | required |       | Telephone number assigned to a single location.                                                                                                                                   |
| FormattedInd  | xs:boolean                        | optional |       | Specifies if the associated data is formatted or not. When true, then it is formatted; when false, then not formatted.                                                            |

### 1.1.3.1.2.5. **Award**

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Award

#### Format Description

| Name  | Type | Occ   | Nil   | Description                                   |
|-------|------|-------|-------|-----------------------------------------------|
| Award |      | 0 / 5 | false | An element that identifies the hotel ratings. |

#### Attributes

| Name     | Type      | Use      | Value | Description                                                                                                  |
|----------|-----------|----------|-------|--------------------------------------------------------------------------------------------------------------|
| Provider | xs:string | optional |       | The name of the award: AAA, MOB, MIC, LSR, NSM<br>For Leisure category LSR is the only one used (with value) |
| Rating   | xs:string | optional |       | Rating value<br>For AAA, MOB, MIC, LSR, NSM, value possible are 1 to 5<br>For OHG value possible are D, F, T |

### 1.1.3.1.2.6. RelativePosition

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/RelativePosition

#### Format Description

| Name             | Type                | Occ   | Nil   | Description                                                                          |
|------------------|---------------------|-------|-------|--------------------------------------------------------------------------------------|
| RelativePosition | TransportationsType | 0 / 1 | false | Describes the location of the property and available to/from transportation methods. |

#### Elements

| Name                            | Type               | Occ   | Nil   | Description                                                                               |
|---------------------------------|--------------------|-------|-------|-------------------------------------------------------------------------------------------|
| <i>sequence</i>                 |                    | 1 / 1 |       |                                                                                           |
| <a href="#">Transportations</a> | TransportationType | 0 / 1 | false | Collection of directions to/from a specific location via various modes of transportation. |

#### Attributes

| Name                   | Type                         | Use      | Value | Description                                                                                                                                                                           |
|------------------------|------------------------------|----------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Direction              | xs:string                    | optional |       | Defines the cardinal direction (e.g., north, south, southwest).                                                                                                                       |
| Distance               | xs:string                    | required |       | Defines the distance between two points.                                                                                                                                              |
| UnitOfMeasureCode      | <a href="#">OTA_CodeType</a> | required |       | The unit of measure in a code format. Refer to OpenTravel Code List Unit of Measure Code (UOM).                                                                                       |
| ApproximateDistanceInd | xs:boolean                   | optional |       | When true, the distance information is approximate.                                                                                                                                   |
| PositionAccuracy       | <a href="#">OTA_CodeType</a> | optional |       | Indicates the accuracy of the property's geo-coding, since the property's longitude and latitude may not always be exact. Refer to OpenTravel Code List Position Accuracy Code (PAC). |

### 1.1.3.1.2.6.1. Transportations

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/RelativePosition/Transportations

#### Format Description

| Name            | Type               | Occ   | Nil   | Description                                                                               |
|-----------------|--------------------|-------|-------|-------------------------------------------------------------------------------------------|
| Transportations | TransportationType | 0 / 1 | false | Collection of directions to/from a specific location via various modes of transportation. |

## Elements

| Name                           | Type | Occ            | Nil   | Description                          |
|--------------------------------|------|----------------|-------|--------------------------------------|
| <i>sequence</i>                |      | 1 / 1          |       |                                      |
| <a href="#">Transportation</a> |      | 1 / unbound ed | false | Detailed transportation information. |

### 1.1.3.1.2.6.1.1. Transportation

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/RelativePosition/Transportations/Transportation

## Format Description

| Name           | Type | Occ            | Nil   | Description                          |
|----------------|------|----------------|-------|--------------------------------------|
| Transportation |      | 1 / unbound ed | false | Detailed transportation information. |

## Elements

| Name            | Type | Occ   | Nil | Description |
|-----------------|------|-------|-----|-------------|
| <i>sequence</i> |      | 1 / 1 |     |             |

## Attributes

| Name               | Type                         | Use      | Value | Description                                                                          |
|--------------------|------------------------------|----------|-------|--------------------------------------------------------------------------------------|
| TransportationCode | <a href="#">OTA_CodeType</a> | optional |       | The mode of transportation. Refer to OpenTravel Code List Transportation Code (TRP). |

### 1.1.3.1.2.7. HotelAmenity

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/HotelAmenity

## Format Description

| Name         | Type | Occ            | Nil   | Description                                                           |
|--------------|------|----------------|-------|-----------------------------------------------------------------------|
| HotelAmenity |      | 0 / unbound ed | false | Hotel-level amenities (pool, etc) for searching.<br>OTA Code Type HAC |

### Attributes

| Name | Type                         | Use      | Value | Description                                             |
|------|------------------------------|----------|-------|---------------------------------------------------------|
| Code | <a href="#">OTA_CodeType</a> | optional |       | Refer to OpenTravel Code List Hotel Amenity Code (HAC). |

### 1.1.3.1.2.8. HotelFeature

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/HotelFeature

### Format Description

| Name         | Type | Occ            | Nil   | Description                        |
|--------------|------|----------------|-------|------------------------------------|
| HotelFeature |      | 0 / unbound ed | false | Identifies features of a property. |

### Attributes

| Name                | Type                         | Use      | Value | Description                                                                                                      |
|---------------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------|
| SecurityFeatureCode | <a href="#">OTA_CodeType</a> | optional |       | Identifies a security feature at a property. Refer to OpenTravel Code list Security Feature Code (SEC).          |
| AccessibilityCode   | <a href="#">OTA_CodeType</a> | optional |       | Identifies an accessibility feature for a property. Refer to OpenTravel Code list Disability Feature Code (PHY). |

### 1.1.3.1.2.9. Recreation

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Recreation

### Format Description

| Name       | Type | Occ            | Nil   | Description                                                |
|------------|------|----------------|-------|------------------------------------------------------------|
| Recreation |      | 0 / unbound ed | false | Identifies recreation facilities or amenities of interest. |

### Attributes

| Name | Type                         | Use      | Value | Description                                                                                               |
|------|------------------------------|----------|-------|-----------------------------------------------------------------------------------------------------------|
| Code | <a href="#">OTA_CodeType</a> | optional |       | Used to identify a specific recreation activity. Refer to OpenTravel Code list Recreation Svc Type (RST). |



### 1.1.3.1.2.10. Service

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Service

#### Format Description

| Name    | Type | Occ            | Nil   | Description                               |
|---------|------|----------------|-------|-------------------------------------------|
| Service |      | 0 / unbound ed | false | Identifies business services of interest. |

#### Attributes

| Name                | Type                         | Use      | Value | Description                                                                                          |
|---------------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------------|
| BusinessServiceCode | <a href="#">OTA_CodeType</a> | optional |       | Used to identify a specific business service. Refer to OpenTravel Code list Business Svc Type (BUS). |

### 1.1.3.1.2.11. Policy

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/Policy

#### Format Description

| Name   | Type | Occ   | Nil   | Description                        |
|--------|------|-------|-------|------------------------------------|
| Policy |      | 0 / 1 | false | Policy information for this hotel. |

#### Attributes

| Name         | Type    | Use      | Value | Description                                               |
|--------------|---------|----------|-------|-----------------------------------------------------------|
| CheckInTime  | xs:time | optional |       | The checkin time required by this hotel for a room stay.  |
| CheckOutTime | xs:time | optional |       | The checkout time required by this hotel for a room stay. |

### 1.1.3.1.2.12. HotelMeetingFacility

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/BasicPropertyInfo/HotelMeetingFacility

#### Format Description

| Name                 | Type | Occ            | Nil   | Description                                                   |
|----------------------|------|----------------|-------|---------------------------------------------------------------|
| HotelMeetingFacility |      | 0 / unbound ed | false | Identifies hotel meeting facility information for a property. |

## Attributes

| Name                   | Type                         | Use      | Value | Description                                                                                                                                                                                                    |
|------------------------|------------------------------|----------|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MeetingRoomCount       | xs:nonNegativeInteger        | optional |       | The total number of unique meeting rooms provided at the hotel facility. For example, if the hotel has a grand ballroom that breaks into Salon A, B, and C -the total number of unique meeting rooms is three. |
| LargestSeatingCapacity | xs:nonNegativeInteger        | optional |       | The largest seating capacity available in the largest meeting room - generally this is for theatre-style room setup.                                                                                           |
| LargestRoomSpace       | xs:nonNegativeInteger        | optional |       | The amount of room space for the largest unique meeting room at the hotel facility.                                                                                                                            |
| UnitOfMeasureCode      | <a href="#">OTA_CodeType</a> | optional |       | The unit of measure in a code format (e.g., inches, pixels, centimeters). Refer to OpenTravel Code List Unit of Measure Code (UOM).                                                                            |
| MeetingRoomCode        | <a href="#">OTA_CodeType</a> | optional |       | Used as a qualifier when searching for properties. Refer to OpenTravel Code list Meeting Room Code (MRC).                                                                                                      |

### 1.1.3.1.3. Price

XPath :/OTA\_HotelAvailRS/HotelStays/HotelStay/Price

## Format Description

| Name  | Type | Occ            | Nil   | Description                                                               |
|-------|------|----------------|-------|---------------------------------------------------------------------------|
| Price |      | 0 / unbound ed | false | Pricing for the hotel stay including the date range for which it applies. |

## Attributes

| Name            | Type                                     | Use      | Value | Description                                                                                                                                                                                                                                                                                 |
|-----------------|------------------------------------------|----------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Start           | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The starting value of the time span.                                                                                                                                                                                                                                                        |
| Duration        | <a href="#">DurationType</a>             | optional |       | The duration datatype represents a combination of year, month, day and time values representing a single duration of time, encoded as a single string.                                                                                                                                      |
| End             | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The ending value of the time span.                                                                                                                                                                                                                                                          |
| AmountBeforeTax | <a href="#">Money</a>                    | optional |       | The available price before tax.                                                                                                                                                                                                                                                             |
| AmountAfterTax  | <a href="#">Money</a>                    | optional |       | The available price after tax.                                                                                                                                                                                                                                                              |
| CurrencyCode    | <a href="#">AlphaLength3</a>             | optional |       | The code specifying a monetary unit. Use ISO 4217, three alpha code.                                                                                                                                                                                                                        |
| Decimal         | xs:nonNegativeInteger                    | optional |       | Indicates the number of decimal places for a particular currency. This is equivalent to the ISO 4217 standard "minor unit". Typically used when the amount provided includes the minor unit of currency without a decimal point (e.g., USD 8500 needs DecimalPlaces="2" to represent \$85). |

### 1.1.4. RoomStays

XPath :/OTA\_HotelAvailRS/RoomStays

#### Format Description

| Name      | Type | Occ   | Nil   | Description                                                                                                                                                                                                            |
|-----------|------|-------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RoomStays |      | 0 / 1 | false | A collection of details on the Room Stay including Guest Counts, Time Span of this Room Stay, and financial information related to the Room Stay, including Guarantee, Deposit and Payment and Cancellation Penalties. |

#### Elements

| Name                     | Type | Occ         | Nil   | Description                                                                                                                                                                                            |
|--------------------------|------|-------------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sequence                 |      | 1 / 1       |       |                                                                                                                                                                                                        |
| <a href="#">RoomStay</a> |      | 1 / unbound | false | Details on the Room Stay including Guest Counts, Time Span of this Room Stay, and financial information related to the Room Stay, including Guarantee, Deposit and Payment and Cancellation Penalties. |

#### Attributes

| Name          | Type                               | Use      | Value | Description                                                                                                                                                                                                                                   |
|---------------|------------------------------------|----------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MoreIndicator | <a href="#">StringLength1to128</a> | optional |       | A text field used to indicate that there are additional rates that cannot fit in the availability response. The text returned should be meaningful in identifying where to begin the next block of data and sent in the availability request. |

### 1.1.4.1. RoomStay

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay

#### Format Description

| Name     | Type         | Occ         | Nil   | Description                                                                                                                                                                                            |
|----------|--------------|-------------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RoomStay | RoomStayType | 1 / unbound | false | Details on the Room Stay including Guest Counts, Time Span of this Room Stay, and financial information related to the Room Stay, including Guarantee, Deposit and Payment and Cancellation Penalties. |

#### Elements

| Name                           | Type               | Occ   | Nil   | Description                                                                                                                                                                                                                             |
|--------------------------------|--------------------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                |                    | 1 / 1 |       |                                                                                                                                                                                                                                         |
| <a href="#">RoomTypes</a>      |                    | 0 / 1 | false | A collection of Room Types associated with a particular Room Stay.                                                                                                                                                                      |
| <a href="#">RatePlans</a>      |                    | 0 / 1 | false | A collection of Rate Plans associated with a particular Room Stay.                                                                                                                                                                      |
| <a href="#">RoomRates</a>      |                    | 0 / 1 | false | A collection of Room Rates associated with a particular Room Stay. Each Room Rate combination can have multiple rates. Example King room, Rack rate plan, Monday through Thursday, weekday amount, Friday and Saturday, weekend amount. |
| <a href="#">GuestCounts</a>    | GuestCountType     | 0 / 1 | false | (guest count per room)                                                                                                                                                                                                                  |
| <a href="#">TimeSpan</a>       | DateTimeSpanType   | 0 / 1 | false | The Time Span which covers the Room Stay.                                                                                                                                                                                               |
| <a href="#">Total</a>          | TotalType          | 0 / 1 | false | The total amount charged for the Room Stay including additional occupant amounts and fees. If TaxInclusive is set to True, then taxes are included in the total amount.                                                                 |
| <a href="#">TPA_Extensions</a> | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA).                                                                                                         |
| <i>sequence</i>                |                    | 1 / 1 |       |                                                                                                                                                                                                                                         |
| <a href="#">Reference</a>      |                    | 0 / 1 | false | Information by which this availability quote can be later cross-referenced.                                                                                                                                                             |
| <a href="#">ServiceRPHs</a>    | ServiceRPHsType    | 0 / 1 | false | A container for the unique references to the services for the room stay.                                                                                                                                                                |

## Attributes

| Name               | Type                               | Use      | Value | Description                                                                                                                                                                 |
|--------------------|------------------------------------|----------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MarketCode         | <a href="#">StringLength1to64</a>  | optional |       | Element returning some general information e.g. multiploom or group. see User Guide for detailed explanation.                                                               |
| SourceOfBusiness   | <a href="#">StringLength1to64</a>  | optional |       | Returning general information about the booking, the pricing, ... e.g 1-Step, 2-Step. see User Guided for detailed explanation                                              |
| WarningRPH         | <a href="#">ListOfRPH</a>          | optional |       | This references the RPH found in the Warning element. Used to identify the warnings associated with this RoomStay.                                                          |
| IsAlternate        | xs:boolean                         | optional |       | False by default True in the case of an 'Alternate property list' response                                                                                                  |
| AvailabilityStatus | <a href="#">RateIndicatorType</a>  | optional |       | Used to specify an availability status at the room stay level for a property.                                                                                               |
| MoreDataEchoToken  | <a href="#">StringLength1to128</a> | optional |       | Applicable for MultiSource / Leisure:<br>Contains the number of dupe property associated to the property of this roomstay which are not return in the availability response |
| InfoSource         | <a href="#">InfoSourceType</a>     | optional |       | Used to specify the source of the data being exchanged as determined by trading partners.<br>1A for Amadeus<br>Chaincode for Provider                                       |
| RPH                | <a href="#">RPH_Type</a>           | required |       | Identifies the room stay for use in the hotel stay.                                                                                                                         |

|                    |            |          |  |                                                                                                                                                                                                                                                      |
|--------------------|------------|----------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AvailableIndicator | xs:boolean | optional |  | May be used as a simple true/false to indicate availability or used in conjunction with @AvailabilityStatus to indicate if restricted rate qualifications have been met e.g. Exclusive and Available (true) vs. Exclusive but not Available (false). |
|--------------------|------------|----------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### 1.1.4.1.1. RoomTypes

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomTypes

#### Format Description

| Name      | Type | Occ   | Nil   | Description                                                        |
|-----------|------|-------|-------|--------------------------------------------------------------------|
| RoomTypes |      | 0 / 1 | false | A collection of Room Types associated with a particular Room Stay. |

#### Elements

| Name                     | Type         | Occ               | Nil   | Description |
|--------------------------|--------------|-------------------|-------|-------------|
| <i>sequence</i>          |              | 1 / 1             |       |             |
| <a href="#">RoomType</a> | RoomTypeType | 1 / unbound<br>ed | false |             |

### 1.1.4.1.1.1. RoomType

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomTypes/RoomType

#### Format Description

| Name     | Type         | Occ               | Nil   | Description |
|----------|--------------|-------------------|-------|-------------|
| RoomType | RoomTypeType | 1 / unbound<br>ed | false |             |

#### Elements

| Name                           | Type               | Occ   | Nil   | Description                                                                                                                     |
|--------------------------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                |                    | 1 / 1 |       |                                                                                                                                 |
| <a href="#">Occupancy</a>      |                    | 0 / 5 | false | Provides parameters of occupancy limits.                                                                                        |
| <a href="#">TPA_Extensions</a> | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

## Attributes

| Name                   | Type                               | Use      | Value | Description                                                                                                                                                                                                                                |
|------------------------|------------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RoomType               | <a href="#">StringLength1to16</a>  | optional |       | (Formerly, RoomInventoryCode) A code value that indicates the type of room for which this request is made, e.g.: double, king, etc. Values may use the Hotel Descriptive Content table or a codes specific to the property or hotel brand. |
| RoomTypeCode           | <a href="#">StringLength1to16</a>  | optional |       | Specific system room type code, ex: A1K, A1Q etc.                                                                                                                                                                                          |
| RoomCategory           | <a href="#">OTA_CodeType</a>       | optional |       | Indicates the category of the room. Typical values would be Moderate, Standard, or Deluxe. Refer to OpenTravel Code List Segment Category Code (SEG).                                                                                      |
| RoomViewCode           | <a href="#">OTA_CodeType</a>       | optional |       | Indicates the view of the room. Typical values would be "Ocean view", "Pool view" or "Garden View". Refer to OpenTravel Code List Room View Type (RVT).                                                                                    |
| BedTypeCode            | <a href="#">ListOfOTA_CodeType</a> | optional |       | Indicates the type of bed(s) found in the room. Typical values would be Double, Twin, Queen, or King. Refer to OpenTravel Code List Bed Type Code (BED).                                                                                   |
| NonSmoking             | xs:boolean                         | optional |       | Non-smoking indicator.                                                                                                                                                                                                                     |
| RoomClassificationCode | <a href="#">OTA_CodeType</a>       | optional |       | Specifies the room classification (e.g., cabin, apartment). Refer to OpenTravel Code List Guest Room Info (GRI).                                                                                                                           |

#### 1.1.4.1.1.1.1. Occupancy

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomTypes/RoomType/Occupancy

### Format Description

| Name      | Type | Occ   | Nil   | Description                              |
|-----------|------|-------|-------|------------------------------------------|
| Occupancy |      | 0 / 5 | false | Provides parameters of occupancy limits. |

### Attributes

| Name              | Type                         | Use      | Value | Description                                                            |
|-------------------|------------------------------|----------|-------|------------------------------------------------------------------------|
| MinOccupancy      | <a href="#">Numeric0to99</a> | optional |       | Minimum number of persons allowed in a unit of accommodation or place. |
| MaxOccupancy      | <a href="#">Numeric1to99</a> | required |       | Maximum number of persons allowed in a unit of accommodation or place. |
| AgeQualifyingCode | <a href="#">OTA_CodeType</a> | required |       | Blank for total occupancy<br>10 for adults                             |

#### 1.1.4.1.1.1.2. TPA Extensions

XPath :/OTA HotelAvailRS/RoomStays/RoomStay/RoomTypes/RoomType/TPA Extensions

### Format Description

| Name           | Type               | Occ   | Nil   | Description                                                                                                                     |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| TPA_Extensions | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

### Elements

| Name     | Type | Occ               | Nil | Description |
|----------|------|-------------------|-----|-------------|
| sequence |      | 1 / 1             |     |             |
| any      |      | 0 / unbound<br>ed |     |             |

#### 1.1.4.1.2. RatePlans

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans

### Format Description

| Name      | Type | Occ   | Nil   | Description                                                        |
|-----------|------|-------|-------|--------------------------------------------------------------------|
| RatePlans |      | 0 / 1 | false | A collection of Rate Plans associated with a particular Room Stay. |

### Elements

| Name                     | Type         | Occ               | Nil   | Description |
|--------------------------|--------------|-------------------|-------|-------------|
| sequence                 |              | 1 / 1             |       |             |
| <a href="#">RatePlan</a> | RatePlanType | 1 / unbound<br>ed | false |             |

#### 1.1.4.1.2.1. RatePlan

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan

### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|          |              |                |       |  |
|----------|--------------|----------------|-------|--|
| RatePlan | RatePlanType | 1 / unbound ed | false |  |
|----------|--------------|----------------|-------|--|

## Elements

| Name                                | Type                  | Occ   | Nil   | Description                                                                                                                                                                                                        |
|-------------------------------------|-----------------------|-------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                     |                       | 0 / 1 |       |                                                                                                                                                                                                                    |
| <a href="#">Guarantee</a>           |                       | 0 / 3 | false | Guarantee information that applies to the rate plan.                                                                                                                                                               |
| <a href="#">CancelPenalties</a>     | CancelPenaltiesType   | 0 / 1 | false | Collection of cancellation penalties.                                                                                                                                                                              |
| <a href="#">RatePlanDescription</a> | ParagraphType         | 0 / 1 | false | Describes the rate plan.                                                                                                                                                                                           |
| <a href="#">RatePlanInclusions</a>  |                       | 0 / 1 | false | Defines charges that are included in this rate plan. This element allows for future extension should there be a need.                                                                                              |
| <a href="#">Commission</a>          | CommissionType        | 0 / 1 | false | Commission associated with the RatePlan. This can be a percentage or a flat amount.                                                                                                                                |
| <a href="#">MealsIncluded</a>       |                       | 0 / 1 | false | Defines which meals are included with this rate program.                                                                                                                                                           |
| <a href="#">RestrictionStatus</a>   |                       | 0 / 1 | false | Used to indicate whether the rate is on request or available.                                                                                                                                                      |
| <a href="#">AdditionalDetails</a>   | AdditionalDetailsType | 0 / 1 | false | Additional information related to a rate plan.                                                                                                                                                                     |
| <a href="#">ModificationFee</a>     | CancelPenaltiesType   | 0 / 1 | false | A collection of modification fees. Note that although this modification fee is typed as CancelPenaltiesType to promote reuse, cancellation penalties information should be entered in the CancelPenalties element. |

## Attributes

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                                                                          |
|--------------------|-----------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RatePlanCode       | <a href="#">StringLength1to16</a> | required |       | Rate plan code                                                                                                                                                                                                                       |
| RateIndicator      | <a href="#">RateIndicatorType</a> | optional |       | Set to "AvailableForSale" the rate is sold at the hotel Set to "ChangeDuringStay" if there are rate changes during the stay                                                                                                          |
| RatePlanType       | <a href="#">OTA_CodeType</a>      | optional |       | It should be used only when for asking a given rate category                                                                                                                                                                         |
| RatePlanID         | <a href="#">StringLength1to64</a> | optional |       | A text field used to provide a special ID code that is associated with the rate and is required in the reservation request in order to obtain the rate. Examples are a corporate ID number, a promotion code or a membership number. |
| RatePlanName       | <a href="#">StringLength1to64</a> | optional |       | Provides the name of the rate plan or group. Typically used with RatePlanType to further describe the rate plan.                                                                                                                     |
| AvailabilityStatus | <a href="#">RateIndicatorType</a> | optional |       | Used to specify an availability status for the rate plan.                                                                                                                                                                            |
| ID_RequiredInd     | xs:boolean                        | optional |       | When true, indicates proof of qualification for this rate is required.                                                                                                                                                               |
| PriceViewableInd   | xs:boolean                        | optional |       | True to indicate that the rate plan confidential                                                                                                                                                                                     |
| QualificationType  | <a href="#">OTA_CodeType</a>      | optional |       | Indicates the type of document required by the guest to qualify for this rate plan. Refer to OpenTravel Code List Document Type (DOC).                                                                                               |
| AvailableQuantity  | xs:integer                        | optional |       | Related to the rate plan numeric availability Returns only for trusted channels                                                                                                                                                      |
| PrepaidIndicator   | xs:boolean                        | optional |       | Indicates if the rate is prepaid (True) or not prepaid (False)                                                                                                                                                                       |



### 1.1.4.1.2.1.1. Guarantee

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee

#### Format Description

| Name      | Type          | Occ   | Nil   | Description                                          |
|-----------|---------------|-------|-------|------------------------------------------------------|
| Guarantee | GuaranteeType | 0 / 3 | false | Guarantee information that applies to the rate plan. |

#### Elements

| Name                                 | Type          | Occ   | Nil   | Description                                            |
|--------------------------------------|---------------|-------|-------|--------------------------------------------------------|
| <i>sequence</i>                      |               | 1 / 1 |       |                                                        |
| <a href="#">GuaranteesAccepted</a>   |               | 0 / 1 | false |                                                        |
| <a href="#">Deadline</a>             |               | 0 / 1 | false | Guarantee deadline, absolute or relative.              |
| <a href="#">Comments</a>             | CommentType   | 0 / 1 | false |                                                        |
| <a href="#">GuaranteeDescription</a> | ParagraphType | 0 / 9 | false | Text description of the Guarantee in a given language. |
| <i>sequence</i>                      |               | 1 / 1 |       |                                                        |

#### Attributes

| Name                          | Type                              | Use      | Value | Description                                                                                                                                                                 |
|-------------------------------|-----------------------------------|----------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GuaranteeCode                 | <a href="#">StringLength1to32</a> | optional |       | 31 for Guarantee 8 for Deposit At list 1 of the fields: @GuaranteeCode or @HoldTime have to be present in the message                                                       |
| <a href="#">GuaranteeType</a> |                                   | optional |       | For a guarantee required: GuaranteeCode=31 and guarantee type="GuaranteeRequired" For a deposit required: GuaranteeCode=8 and guarantee type="Deposit" or "DepositRequired" |
| HoldTime                      | xs:time                           | optional |       | The room will held up until this time without a guarantee.                                                                                                                  |

Attribute: GuaranteeType

Variety: atomic

Base: [StringLength1to32](#)

Documentation:

| Enumeration       | description               |
|-------------------|---------------------------|
| GuaranteeRequired | A guarantee is required.  |
| None              | No guarantee is required. |

|                 |                                                                            |
|-----------------|----------------------------------------------------------------------------|
| CC/DC/Voucher   |                                                                            |
| Profile         |                                                                            |
| Deposit         |                                                                            |
| PrePay          | Indicates prepayment, typically this means payment is required at booking. |
| DepositRequired | A deposit is required.                                                     |

### 1.1.4.1.2.1.1.1.1. GuaranteesAccepted

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted

#### Format Description

| Name               | Type | Occ   | Nil   | Description |
|--------------------|------|-------|-------|-------------|
| GuaranteesAccepted |      | 0 / 1 | false |             |

#### Elements

| Name                              | Type | Occ         | Nil   | Description       |
|-----------------------------------|------|-------------|-------|-------------------|
| <i>sequence</i>                   |      | 1 / 1       |       |                   |
| <a href="#">GuaranteeAccepted</a> |      | 1 / unbound | false | Guarantee Detail. |

### 1.1.4.1.2.1.1.1.1.1. GuaranteeAccepted

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted

#### Format Description

| Name              | Type            | Occ         | Nil   | Description       |
|-------------------|-----------------|-------------|-------|-------------------|
| GuaranteeAccepted | PaymentFormType | 1 / unbound | false | Guarantee Detail. |

#### Elements

| Name                        | Type            | Occ   | Nil   | Description                        |
|-----------------------------|-----------------|-------|-------|------------------------------------|
| <i>choice</i>               |                 | 0 / 1 |       |                                    |
| <a href="#">PaymentCard</a> | PaymentCardType | 1 / 1 | false | Details of a debit or credit card. |
| <a href="#">BankAcct</a>    | BankAcctType    | 1 / 1 | false | Details of a bank account.         |

|                                   |                |       |       |                                                                  |
|-----------------------------------|----------------|-------|-------|------------------------------------------------------------------|
| <a href="#">DirectBill</a>        | DirectBillType | 1 / 1 | false | If present, DirectBill is accepted as guarantee or deposit       |
| <a href="#">Voucher</a>           |                | 1 / 1 | false | Details of a paper or electronic document indicating prepayment. |
| <a href="#">LoyaltyRedemption</a> |                | 1 / 1 | false | If present, Loyalty Redemption is accepted as guarantee          |
| <a href="#">MiscChargeOrder</a>   |                | 1 / 1 | false | If present, MCO is accepted as guarantee                         |
| <a href="#">Ticket</a>            |                | 1 / 1 | false |                                                                  |
| <a href="#">Cash</a>              |                | 1 / 1 | false | Used to indicate payment in cash.                                |

## Attributes

| Name                      | Type                               | Use      | Value | Description                                                                    |
|---------------------------|------------------------------------|----------|-------|--------------------------------------------------------------------------------|
| Remark                    | <a href="#">StringLength1to128</a> | optional |       | A remark associated with the payment form.                                     |
| BookingSourceAllowedInd   | xs:boolean                         | optional |       | When true, the booking source may be used to guarantee the booking.            |
| CorpDiscountNbrAllowedInd | xs:boolean                         | optional |       | When true, the corporate discount number may be used to guarantee the booking. |

### 1.1.4.1.2.1.1.1.1.1. PaymentCard

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/

PaymentCard

## Format Description

| Name        | Type            | Occ   | Nil   | Description                        |
|-------------|-----------------|-------|-------|------------------------------------|
| PaymentCard | PaymentCardType | 1 / 1 | false | Details of a debit or credit card. |

## Elements

| Name                           | Type                              | Occ   | Nil   | Description                                                                               |
|--------------------------------|-----------------------------------|-------|-------|-------------------------------------------------------------------------------------------|
| <i>sequence</i>                |                                   | 1 / 1 |       |                                                                                           |
| <a href="#">CardHolderName</a> | <a href="#">StringLength1to64</a> | 0 / 1 | false | Indicates if one or two fields for the name are needed and if the Nationality is required |
| <a href="#">CardIssuerName</a> |                                   | 0 / 1 | false |                                                                                           |
| <a href="#">Address</a>        | AddressType                       | 0 / 1 | false | Indicates which address information is needed.                                            |
| <a href="#">Telephone</a>      |                                   | 0 / 5 | false | Card holder's telephone number used for additional authorization checks.                  |
| <a href="#">Email</a>          | EmailType                         | 0 / 3 | false | Card holder's email address(es) used for additional authorization checks.                 |

| Name       | Type                                    | Use      | Value | Description                                                                                 |
|------------|-----------------------------------------|----------|-------|---------------------------------------------------------------------------------------------|
| CardType   | <a href="#">OTA_CodeType</a>            | optional |       | Indicates the type of magnetic striped card. Refer to OpenTravel Code List Card Type (CDT). |
| CardCode   | <a href="#">PaymentCardCodeType</a>     | required |       | The 2 character code of the credit card issuer.                                             |
| SeriesCode | <a href="#">NumericStringLength1to8</a> | optional |       | indicates if CVV code is required                                                           |

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/CardHolderName

| Name           | Type                              | Occ   | Nil   | Description                                                                               |
|----------------|-----------------------------------|-------|-------|-------------------------------------------------------------------------------------------|
| CardHolderName | <a href="#">StringLength1to64</a> | 0 / 1 | false | Indicates if one or two fields for the name are needed and if the Nationality is required |

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/CardIssuerName

| Name           | Type | Occ   | Nil   | Description |
|----------------|------|-------|-------|-------------|
| CardIssuerName |      | 0 / 1 | false |             |

| Name   | Type              | Use      | Value | Description                    |
|--------|-------------------|----------|-------|--------------------------------|
| BankID | StringLength1to64 | optional |       | Code of bank issuing the card. |

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/Address

Copyright 1987-2010 Amadeus IT Group SA | Page 32

| Name    | Type        | Occ   | Nil   | Description                                    |
|---------|-------------|-------|-------|------------------------------------------------|
| Address | AddressType | 0 / 1 | false | Indicates which address information is needed. |

## Elements

| Name                        | Type                               | Occ   | Nil   | Description                                                         |
|-----------------------------|------------------------------------|-------|-------|---------------------------------------------------------------------|
| <i>sequence</i>             |                                    | 1 / 1 |       |                                                                     |
| <a href="#">StreetNmbr</a>  |                                    | 0 / 1 | false |                                                                     |
| <a href="#">BldgRoom</a>    |                                    | 0 / 2 | false |                                                                     |
| <a href="#">AddressLine</a> | <a href="#">StringLength1to255</a> | 0 / 5 | false | Indicates if one/two addresslines are required or if it is optional |
| <a href="#">CityName</a>    | <a href="#">StringLength1to64</a>  | 0 / 1 | false | Indicates if the CityName is required                               |
| <a href="#">PostalCode</a>  | <a href="#">StringLength1to16</a>  | 0 / 1 | false | Indicates if the PostalCode is required                             |
| <a href="#">County</a>      | <a href="#">StringLength1to32</a>  | 0 / 1 | false |                                                                     |
| <a href="#">StateProv</a>   | StateProvType                      | 0 / 1 | false | Indicates if the StateProv is required                              |
| <a href="#">CountryName</a> | CountryNameType                    | 0 / 1 | false | Indicates if the CountryName is required                            |

### 1.1.4.1.2.1.1.1.1.1.3.1. [StreetNmbr](#)

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/Address/StreetNmbr

## Format Description

| Name       | Type                              | Occ   | Nil   | Description |
|------------|-----------------------------------|-------|-------|-------------|
| StreetNmbr | <a href="#">StringLength0to64</a> | 0 / 1 | false |             |

## Attributes

| Name             | Type                                    | Use      | Value | Description                                                                             |
|------------------|-----------------------------------------|----------|-------|-----------------------------------------------------------------------------------------|
| PO_Box           | <a href="#">StringLength1to16</a>       | optional |       | Defines a Post Office Box number.                                                       |
| StreetNmbrSuffix | <a href="#">StringLength1to8</a>        | optional |       | Usually a letter right after the street number (A in 66-A, B in 123-B etc).             |
| StreetDirection  | <a href="#">StringLength1to8</a>        | optional |       | Street direction of an address (e.g., N, E, S, NW, SW).                                 |
| RuralRouteNmbr   | <a href="#">NumericStringLength1to5</a> | optional |       | Numerical equivalent of a rural township as defined within a given area (e.g., 12, 99). |

### 1.1.4.1.2.1.1.1.1.1.3.2. [BldgRoom](#)

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/

PaymentCard/Address/BldgRoom

### Format Description

| Name     | Type                              | Occ   | Nil   | Description |
|----------|-----------------------------------|-------|-------|-------------|
| BldgRoom | <a href="#">StringLength0to64</a> | 0 / 2 | false |             |

### Attributes

| Name              | Type       | Use      | Value | Description                                    |
|-------------------|------------|----------|-------|------------------------------------------------|
| BldgNameIndicator | xs:boolean | optional |       | When true, the information is a building name. |

## 1.1.4.1.2.1.1.1.1.3.3. AddressLine

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/

PaymentCard/Address/AddressLine

### Format Description

| Name        | Type                               | Occ   | Nil   | Description                                                         |
|-------------|------------------------------------|-------|-------|---------------------------------------------------------------------|
| AddressLine | <a href="#">StringLength1to255</a> | 0 / 5 | false | Indicates if one/two addresslines are required or if it is optional |

## 1.1.4.1.2.1.1.1.1.3.4. CityName

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/

PaymentCard/Address/CityName

### Format Description

| Name     | Type                              | Occ   | Nil   | Description                           |
|----------|-----------------------------------|-------|-------|---------------------------------------|
| CityName | <a href="#">StringLength1to64</a> | 0 / 1 | false | Indicates if the CityName is required |

## 1.1.4.1.2.1.1.1.1.3.5. PostalCode

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/

PaymentCard/Address/PostalCode

### Format Description

| Name       | Type                              | Occ   | Nil   | Description                             |
|------------|-----------------------------------|-------|-------|-----------------------------------------|
| PostalCode | <a href="#">StringLength1to16</a> | 0 / 1 | false | Indicates if the PostalCode is required |

### 1.1.4.1.2.1.1.1.1.3.6. **County**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/Address/County

#### Format Description

| Name   | Type                              | Occ   | Nil   | Description |
|--------|-----------------------------------|-------|-------|-------------|
| County | <a href="#">StringLength1to32</a> | 0 / 1 | false |             |

### 1.1.4.1.2.1.1.1.1.3.7. **StateProv**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/Address/StateProv

#### Format Description

| Name      | Type                              | Occ   | Nil   | Description                            |
|-----------|-----------------------------------|-------|-------|----------------------------------------|
| StateProv | <a href="#">StringLength0to64</a> | 0 / 1 | false | Indicates if the StateProv is required |

#### Attributes

| Name      | Type                              | Use      | Value | Description                                                           |
|-----------|-----------------------------------|----------|-------|-----------------------------------------------------------------------|
| StateCode | <a href="#">StateProvCodeType</a> | optional |       | The standard code or abbreviation for the state, province, or region. |

### 1.1.4.1.2.1.1.1.1.3.8. **CountryName**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/Address/CountryName

#### Format Description

| Name        | Type                              | Occ   | Nil   | Description                              |
|-------------|-----------------------------------|-------|-------|------------------------------------------|
| CountryName | <a href="#">StringLength0to64</a> | 0 / 1 | false | Indicates if the CountryName is required |

## Attributes

| Name | Type                    | Use      | Value | Description                  |
|------|-------------------------|----------|-------|------------------------------|
| Code | <a href="#">ISO3166</a> | optional |       | ISO 3166 code for a country. |

### 1.1.4.1.2.1.1.1.1.4. Telephone

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/Telephone

## Format Description

| Name      | Type | Occ   | Nil   | Description                                                              |
|-----------|------|-------|-------|--------------------------------------------------------------------------|
| Telephone |      | 0 / 5 | false | Card holder's telephone number used for additional authorization checks. |

## Attributes

| Name        | Type                              | Use      | Value | Description                              |
|-------------|-----------------------------------|----------|-------|------------------------------------------|
| PhoneNumber | <a href="#">StringLength1to32</a> | required |       | Indicates if the PhoneNumber is required |

### 1.1.4.1.2.1.1.1.1.5. Email

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/  
PaymentCard/Email

## Format Description

| Name  | Type                 | Occ   | Nil   | Description                                                               |
|-------|----------------------|-------|-------|---------------------------------------------------------------------------|
| Email | StringLength1to128 * | 0 / 3 | false | Card holder's email address(es) used for additional authorization checks. |

Element: Email

Variety: atomic

Base: xs:string

Documentation: Indicates if the Email is required.

| Restriction | Value |
|-------------|-------|
|-------------|-------|



|                  |     |
|------------------|-----|
| <b>minlength</b> | 1   |
| <b>maxlength</b> | 128 |

### 1.1.4.1.2.1.1.1.1.2. **BankAcct**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/BankAcct

#### *Format Description*

| Name     | Type         | Occ   | Nil   | Description                |
|----------|--------------|-------|-------|----------------------------|
| BankAcct | BankAcctType | 1 / 1 | false | Details of a bank account. |

#### *Elements*

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

#### *Attributes*

| Name              | Type       | Use      | Value | Description                                                      |
|-------------------|------------|----------|-------|------------------------------------------------------------------|
| ChecksAcceptedInd | xs:boolean | required |       | If true, checks are accepted. If false, checks are not accepted. |

### 1.1.4.1.2.1.1.1.1.3. **DirectBill**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/DirectBill

#### *Format Description*

| Name       | Type           | Occ   | Nil   | Description                                                |
|------------|----------------|-------|-------|------------------------------------------------------------|
| DirectBill | DirectBillType | 1 / 1 | false | If present, DirectBill is accepted as guarantee or deposit |

#### *Elements*

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

### 1.1.4.1.2.1.1.1.1.4. **Voucher**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/Voucher

#### Format Description

| Name    | Type | Occ   | Nil   | Description                                                      |
|---------|------|-------|-------|------------------------------------------------------------------|
| Voucher |      | 1 / 1 | false | Details of a paper or electronic document indicating prepayment. |

#### Attributes

| Name               | Type                              | Use      | Value | Description                                                           |
|--------------------|-----------------------------------|----------|-------|-----------------------------------------------------------------------|
| SupplierIdentifier | <a href="#">StringLength1to64</a> | optional |       | Unique identifier of the electronic voucher, created by the supplier. |
| Identifier         | <a href="#">StringLength1to64</a> | optional |       | Unique identifier of the electronic voucher.                          |
| ValueType          | <a href="#">StringLength1to32</a> | optional |       | Defines the type of voucher (e.g., full credit or partial credit).    |

### 1.1.4.1.2.1.1.1.1.5. **LoyaltyRedemption**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/

LoyaltyRedemption

#### Format Description

| Name              | Type | Occ   | Nil   | Description                                             |
|-------------------|------|-------|-------|---------------------------------------------------------|
| LoyaltyRedemption |      | 1 / 1 | false | If present, Loyalty Redemption is accepted as guarantee |

#### Elements

| Name            | Type | Occ   | Nil | Description |
|-----------------|------|-------|-----|-------------|
| <i>sequence</i> |      | 1 / 1 |     |             |

### 1.1.4.1.2.1.1.1.1.6. **MiscChargeOrder**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/

MiscChargeOrder

#### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|                 |  |       |       |                                          |
|-----------------|--|-------|-------|------------------------------------------|
| MiscChargeOrder |  | 1 / 1 | false | If present, MCO is accepted as guarantee |
|-----------------|--|-------|-------|------------------------------------------|

### 1.1.4.1.2.1.1.1.1.7. Ticket

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/Ticket

#### Format Description

| Name   | Type | Occ   | Nil   | Description |
|--------|------|-------|-------|-------------|
| Ticket |      | 1 / 1 | false |             |

#### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

### 1.1.4.1.2.1.1.1.1.8. Cash

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteesAccepted/GuaranteeAccepted/Cash

#### Format Description

| Name | Type | Occ   | Nil   | Description                       |
|------|------|-------|-------|-----------------------------------|
| Cash |      | 1 / 1 | false | Used to indicate payment in cash. |

#### Attributes

| Name          | Type       | Use      | Value | Description                                        |
|---------------|------------|----------|-------|----------------------------------------------------|
| CashIndicator | xs:boolean | optional |       | If exist, Cash is accepted as guarantee or deposit |

### 1.1.4.1.2.1.1.2. Deadline

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/Deadline

#### Format Description

| Name     | Type | Occ   | Nil   | Description                               |
|----------|------|-------|-------|-------------------------------------------|
| Deadline |      | 0 / 1 | false | Guarantee deadline, absolute or relative. |

## Attributes

| Name             | Type                               | Use      | Value | Description                                                                      |
|------------------|------------------------------------|----------|-------|----------------------------------------------------------------------------------|
| AbsoluteDeadline | <a href="#">TimeOrDateTimeType</a> | optional |       | Defines the absolute deadline. Either this or the offset attributes may be used. |

### 1.1.4.1.2.1.1.3. Comments

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/Comments

## Format Description

| Name     | Type        | Occ   | Nil   | Description |
|----------|-------------|-------|-------|-------------|
| Comments | CommentType | 0 / 1 | false |             |

## Elements

| Name                    | Type | Occ               | Nil   | Description      |
|-------------------------|------|-------------------|-------|------------------|
| <i>sequence</i>         |      | 1 / 1             |       |                  |
| <a href="#">Comment</a> |      | 1 / unbound<br>ed | false | Comment details. |

### 1.1.4.1.2.1.1.3.1. Comment

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/Comments/Comment

## Format Description

| Name    | Type          | Occ               | Nil   | Description      |
|---------|---------------|-------------------|-------|------------------|
| Comment | ParagraphType | 1 / unbound<br>ed | false | Comment details. |

## Elements

| Name                 | Type              | Occ               | Nil   | Description             |
|----------------------|-------------------|-------------------|-------|-------------------------|
| <i>choice</i>        |                   | 0 / unbound<br>ed |       |                         |
| <a href="#">Text</a> | FormattedTextType | 1 / 1             | false | Formatted text content. |

|                          |           |       |       |                                                                   |
|--------------------------|-----------|-------|-------|-------------------------------------------------------------------|
| Image                    | xs:string | 1 / 1 | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI | 1 / 1 | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |           | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name | Type                              | Use      | Value | Description                                                                                                                                                                        |
|------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |

### 1.1.4.1.2.1.1.3.1.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/Comments/Comment/Text

## Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.1.3.1.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/Comments/Comment/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.1.4. GuaranteeDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteeDescription

#### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|                      |               |       |       |                                                        |
|----------------------|---------------|-------|-------|--------------------------------------------------------|
| GuaranteeDescription | ParagraphType | 0 / 9 | false | Text description of the Guarantee in a given language. |
|----------------------|---------------|-------|-------|--------------------------------------------------------|

## Elements

| Name                     | Type              | Occ               | Nil   | Description                                                       |
|--------------------------|-------------------|-------------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbound<br>ed |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1             | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1             | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1             | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1             | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name            | Type                              | Use      | Value | Description                                                                                                                                                                        |
|-----------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name            | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |

### 1.1.4.1.2.1.1.4.1. **Text**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteeDescription/Text

## Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

## Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

1.1.4.1.2.1.1.4.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Guarantee/GuaranteeDescription/ListItem

*Format Description*

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

*Attributes*

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

## Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |



### 1.1.4.1.2.1.2. **CancelPenalties**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/CancelPenalties

#### *Format Description*

| Name            | Type                | Occ   | Nil   | Description                           |
|-----------------|---------------------|-------|-------|---------------------------------------|
| CancelPenalties | CancelPenaltiesType | 0 / 1 | false | Collection of cancellation penalties. |

#### *Elements*

| Name                          | Type              | Occ            | Nil   | Description                                             |
|-------------------------------|-------------------|----------------|-------|---------------------------------------------------------|
| <i>sequence</i>               |                   | 1 / 1          |       |                                                         |
| <a href="#">CancelPenalty</a> | CancelPenaltyType | 0 / unbound ed | false | Defines the cancellation penalty of the hotel facility. |

#### *Attributes*

| Name                  | Type       | Use      | Value | Description                                            |
|-----------------------|------------|----------|-------|--------------------------------------------------------|
| CancelPolicyIndicator | xs:boolean | optional |       | False if no cancellation policy apply. True otherwise. |

### 1.1.4.1.2.1.2.1. **CancelPenalty**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/CancelPenalties/CancelPenalty

#### *Format Description*

| Name          | Type              | Occ            | Nil   | Description                                             |
|---------------|-------------------|----------------|-------|---------------------------------------------------------|
| CancelPenalty | CancelPenaltyType | 0 / unbound ed | false | Defines the cancellation penalty of the hotel facility. |

#### *Elements*

| Name                     | Type | Occ   | Nil   | Description                                  |
|--------------------------|------|-------|-------|----------------------------------------------|
| <i>sequence</i>          |      | 1 / 1 |       |                                              |
| <a href="#">Deadline</a> |      | 0 / 1 | false | Cancellation deadline, absolute or relative. |

|                                    |                   |       |       |                                                                                |
|------------------------------------|-------------------|-------|-------|--------------------------------------------------------------------------------|
| <a href="#">AmountPercent</a>      | AmountPercentType | 0 / 1 | false | Cancellation fee expressed as a fixed amount, or percentage of/or room nights. |
| <a href="#">PenaltyDescription</a> | ParagraphType     | 0 / 9 | false | Text description of the Penalty in a given language.                           |

### Attributes

| Name          | Type                                     | Use      | Value | Description                                                                                                                                            |
|---------------|------------------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| PolicyCode    | <a href="#">StringLength1to16</a>        | required |       | PolicyCode = Cancellation                                                                                                                              |
| NonRefundable | xs:boolean                               | optional |       | Indicates that any prepayment for the reservation is non refundable, therefore a 100% penalty on the prepayment is applied, irrespective of deadline.  |
| Start         | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The starting value of the time span.                                                                                                                   |
| Duration      | <a href="#">DurationType</a>             | optional |       | The duration datatype represents a combination of year, month, day and time values representing a single duration of time, encoded as a single string. |
| End           | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The ending value of the time span.                                                                                                                     |

#### 1.1.4.1.2.1.2.1.1. Deadline

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/CancelPenalties/CancelPenalty/Deadline

### Format Description

| Name     | Type | Occ   | Nil   | Description                                  |
|----------|------|-------|-------|----------------------------------------------|
| Deadline |      | 0 / 1 | false | Cancellation deadline, absolute or relative. |

### Attributes

| Name             | Type                               | Use      | Value | Description                                                                      |
|------------------|------------------------------------|----------|-------|----------------------------------------------------------------------------------|
| AbsoluteDeadline | <a href="#">TimeOrDateTimeType</a> | optional |       | Defines the absolute deadline. Either this or the offset attributes may be used. |

#### 1.1.4.1.2.1.2.1.2. AmountPercent

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/CancelPenalties/CancelPenalty/AmountPercent

### Format Description

| Name          | Type              | Occ   | Nil   | Description                                                                    |
|---------------|-------------------|-------|-------|--------------------------------------------------------------------------------|
| AmountPercent | AmountPercentType | 0 / 1 | false | Cancellation fee expressed as a fixed amount, or percentage of/or room nights. |

## Elements

| Name            | Type | Occ   | Nil | Description |
|-----------------|------|-------|-----|-------------|
| <i>sequence</i> |      | 1 / 1 |     |             |

## Attributes

| Name                      | Type                       | Use      | Value | Description                                                                       |
|---------------------------|----------------------------|----------|-------|-----------------------------------------------------------------------------------|
| NmbrOfNights              | xs:nonNegativeInteger      | optional |       | The number of nights of the hotel stay that are used to calculate the fee amount. |
| <a href="#">BasisType</a> |                            | optional |       | Provides the basis for how the amount of the guarantee is calculated.             |
| Percent                   | <a href="#">Percentage</a> | optional |       | Cancellation fee percentage                                                       |
| <a href="#">ApplyAs</a>   |                            | optional |       | Used to specify how the amount needs to be applied with respect to the stay.      |

### Attribute: BasisType

Variety: atomic

Base: [StringLength1to16](#)

Documentation:

| Enumeration | description                                 |
|-------------|---------------------------------------------|
| FullStay    | Uses the full stay as the basis.            |
| Nights      | Uses the nights as the basis.               |
| FirstLast   | Uses the first and last night as the basis. |

### Attribute: ApplyAs

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration              | description                                                      |
|--------------------------|------------------------------------------------------------------|
| FirstNightDeposit        | Amount to be applied as a deposit for the first night.           |
| LastNightDeposit         | Amount to be applied as a deposit for the last night.            |
| FirstAndLastNightDeposit | Amount to be applied as a deposit for the first and last nights. |

|                          |                                                                |
|--------------------------|----------------------------------------------------------------|
| FirstNightPayment        | Amount to be applied as payment for the first night.           |
| LastNightPayment         | Amount to be applied as payment for the last night.            |
| FirstAndLastNightPayment | Amount to be applied as payment for the first and last nights. |

### 1.1.4.1.2.1.2.1.3. **PenaltyDescription**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/CancelPenalties/CancelPenalty/PenaltyDescription

#### Format Description

| Name               | Type          | Occ   | Nil   | Description                                          |
|--------------------|---------------|-------|-------|------------------------------------------------------|
| PenaltyDescription | ParagraphType | 0 / 9 | false | Text description of the Penalty in a given language. |

#### Elements

| Name                     | Type              | Occ               | Nil   | Description                                                       |
|--------------------------|-------------------|-------------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbound<br>ed |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1             | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1             | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1             | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1             | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name | Type                              | Use      | Value | Description                                                                                                                                                                        |
|------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |

### 1.1.4.1.2.1.2.1.3.1. **Text**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/CancelPenalties/CancelPenalty/PenaltyDescription/Text

#### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.4.1.2.1.2.1.3.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/CancelPenalties/CancelPenalty/PenaltyDescription/ListItem

## Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.3. RatePlanDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/RatePlanDescription

#### Format Description

| Name                | Type          | Occ   | Nil   | Description              |
|---------------------|---------------|-------|-------|--------------------------|
| RatePlanDescription | ParagraphType | 0 / 1 | false | Describes the rate plan. |

#### Elements

| Name                     | Type              | Occ            | Nil   | Description                                                       |
|--------------------------|-------------------|----------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbound ed |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1          | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1          | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1          | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1          | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name      | Type                              | Use      | Value | Description                                                                                                                                                                        |
|-----------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name      | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| CreatorID | <a href="#">StringLength1to32</a> | optional |       | Same value than the one returned in the CreatorID linking both rate and room in case of packages                                                                                   |

### 1.1.4.1.2.1.3.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/RatePlanDescription/Text

#### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | required |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.3.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/RatePlanDescription/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.4.1.2.1.4. RatePlanInclusions

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/RatePlanInclusions

### Format Description

| Name               | Type | Occ   | Nil   | Description                                                                                                           |
|--------------------|------|-------|-------|-----------------------------------------------------------------------------------------------------------------------|
| RatePlanInclusions |      | 0 / 1 | false | Defines charges that are included in this rate plan. This element allows for future extension should there be a need. |

## Elements

| Name                                         | Type          | Occ   | Nil   | Description                                       |
|----------------------------------------------|---------------|-------|-------|---------------------------------------------------|
| sequence                                     |               | 1 / 1 |       |                                                   |
| <a href="#">RatePlanInclusionDescription</a> | ParagraphType | 0 / 1 | false | Description of what is included in the rate plan. |



## Attributes

| Name                | Type       | Use      | Value | Description |
|---------------------|------------|----------|-------|-------------|
| TaxInclusive        | xs:boolean | optional |       |             |
| ServiceFeeInclusive | xs:boolean | optional |       |             |

### 1.1.4.1.2.1.4.1. RatePlanInclusionDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/RatePlanInclusions/RatePlanInclusionDescription

## Format Description

| Name                         | Type          | Occ   | Nil   | Description                                       |
|------------------------------|---------------|-------|-------|---------------------------------------------------|
| RatePlanInclusionDescription | ParagraphType | 0 / 1 | false | Description of what is included in the rate plan. |

## Elements

| Name                     | Type                  | Occ           | Nil   | Description                                                       |
|--------------------------|-----------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                       | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextTextType | 1 / 1         | false | Formatted text content.                                           |
| Image                    | xs:string             | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI             | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                       | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name            | Type                              | Use      | Value | Description                                                                                                                                                                        |
|-----------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name            | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |

### 1.1.4.1.2.1.4.1.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/RatePlanInclusions/RatePlanInclusionDescription/Text

## Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.4.1.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/RatePlanInclusions/RatePlanInclusionDescription/ListItem

### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

### Attributes

| Name      | Type        | Use      | Value | Description                                                                                                   |
|-----------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language  | xs:language | optional |       | Language identification.                                                                                      |

|                            |            |          |  |                                                                                |
|----------------------------|------------|----------|--|--------------------------------------------------------------------------------|
| <a href="#">TextFormat</a> |            | optional |  | Indicates the format of text used in the description e.g. unformatted or html. |
| ListItem                   | xs:integer | optional |  | The item or sequence number.                                                   |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.5. Commission

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Commission

#### Format Description

| Name       | Type           | Occ   | Nil   | Description                                                                         |
|------------|----------------|-------|-------|-------------------------------------------------------------------------------------|
| Commission | CommissionType | 0 / 1 | false | Commission associated with the RatePlan. This can be a percentage or a flat amount. |

#### Elements

| Name                                    | Type          | Occ   | Nil   | Description                          |
|-----------------------------------------|---------------|-------|-------|--------------------------------------|
| <i>sequence</i>                         |               | 1 / 1 |       |                                      |
| <a href="#">CommissionPayableAmount</a> |               | 0 / 1 | false | The amount of commission to be paid. |
| <a href="#">Comment</a>                 | ParagraphType | 0 / 1 | false | Text related to the commission.      |

#### Attributes

| Name                       | Type                       | Use      | Value | Description                                                                                                                                           |
|----------------------------|----------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">StatusType</a> |                            | required |       | 2 possible values:<br>If the rate is not applicable then value set as "Non-paying"<br>If rate is commissionable then value is set to "Commissionable" |
| Percent                    | <a href="#">Percentage</a> | optional |       | The percent applied to the commissionable amount to determine the commission payable amount.                                                          |

|               |                              |          |  |                                                                                                |
|---------------|------------------------------|----------|--|------------------------------------------------------------------------------------------------|
| CurrencyCode  | <a href="#">AlphaLength3</a> | optional |  | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |  | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

Attribute: StatusType

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration    | description                                                                                                              |
|----------------|--------------------------------------------------------------------------------------------------------------------------|
| Full           | Indicates full commission.                                                                                               |
| Partial        | Indicates partial commission.                                                                                            |
| Non-paying     | Indicates no commission.                                                                                                 |
| No-show        | Indicates customer did not use the reserved product or service and did not cancel. This "no show" may impact commission. |
| Adjustment     | Indicates the commission is being adjusted.                                                                              |
| Commissionable | Indicates the requested rate is commissionable.                                                                          |

### 1.1.4.1.2.1.5.1. CommissionPayableAmount

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Commission/CommissionPayableAmount

#### Format Description

| Name                    | Type | Occ   | Nil   | Description                          |
|-------------------------|------|-------|-------|--------------------------------------|
| CommissionPayableAmount |      | 0 / 1 | false | The amount of commission to be paid. |

#### Attributes

| Name          | Type                         | Use      | Value | Description                                                                                    |
|---------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| Amount        | <a href="#">Money</a>        | required |       | A monetary amount.                                                                             |
| CurrencyCode  | <a href="#">AlphaLength3</a> | required |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.2.1.5.2. Comment

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Commission/Comment

### Format Description

| Name    | Type          | Occ   | Nil   | Description                     |
|---------|---------------|-------|-------|---------------------------------|
| Comment | ParagraphType | 0 / 1 | false | Text related to the commission. |

### Elements

| Name                     | Type              | Occ           | Nil   | Description                                                       |
|--------------------------|-------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1         | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

### 1.1.4.1.2.1.5.2.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Commission/Comment/Text

### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.5.2.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/Commission/Comment/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.6. MealsIncluded

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/MealsIncluded

#### Format Description

| Name          | Type | Occ   | Nil   | Description                                              |
|---------------|------|-------|-------|----------------------------------------------------------|
| MealsIncluded |      | 0 / 1 | false | Defines which meals are included with this rate program. |

#### Attributes

| Name              | Type                               | Use      | Value | Description                                                                                                        |
|-------------------|------------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------|
| Breakfast         | xs:boolean                         | optional |       | When true, indicates breakfast is included.                                                                        |
| MealPlanIndicator | xs:boolean                         | optional |       | When true, a meal plan is included in this rate plan. When false, a meal plan is not included in this rate plan.   |
| MealPlanCodes     | <a href="#">ListOfOTA_CodeType</a> | optional |       | Used to identify the types of meals included with a rate plan. Refer to OpenTravel Code List Meal Plan Type (MPT). |

### 1.1.4.1.2.1.7. RestrictionStatus

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/RestrictionStatus

#### Format Description

| Name              | Type | Occ   | Nil   | Description                                                   |
|-------------------|------|-------|-------|---------------------------------------------------------------|
| RestrictionStatus |      | 0 / 1 | false | Used to indicate whether the rate is on request or available. |

### 1.1.4.1.2.1.8. AdditionalDetails

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/AdditionalDetails

#### Format Description

| Name              | Type                  | Occ   | Nil   | Description                                    |
|-------------------|-----------------------|-------|-------|------------------------------------------------|
| AdditionalDetails | AdditionalDetailsType | 0 / 1 | false | Additional information related to a rate plan. |

#### Elements

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|                                  |                      |                   |       |                                      |
|----------------------------------|----------------------|-------------------|-------|--------------------------------------|
| <i>sequence</i>                  |                      | 1 / 1             |       |                                      |
| <a href="#">AdditionalDetail</a> | AdditionalDetailType | 1 / unbound<br>ed | false | Used to send additional information. |

### 1.1.4.1.2.1.8.1. **AdditionalDetail**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/AdditionalDetails/AdditionalDetail

#### Format Description

| Name             | Type                 | Occ               | Nil   | Description                          |
|------------------|----------------------|-------------------|-------|--------------------------------------|
| AdditionalDetail | AdditionalDetailType | 1 / unbound<br>ed | false | Used to send additional information. |

#### Elements

| Name                              | Type          | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------|---------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                   |               | 1 / 1 |       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <a href="#">DetailDescription</a> | ParagraphType | 0 / 1 | false | Name or sub-type of the detail: <ul style="list-style-type: none"> <li>if Type=8:<br/>"check-in" for check-in details<br/>"check-out" for check-out details<br/>"express check-in" for express check-in available<br/>"express check-out" for express check-out available</li> <li>if Type=20:<br/>not used</li> <li>if Type=29:<br/>"minimum stay" for minimum length of stay details<br/>"maximum stay" for maximum length of stay details</li> <li>else:<br/>free text.</li> </ul> |

#### Attributes

| Name | Type                              | Use      | Value | Description                                                                                                                                                                                                                                                                                                                          |
|------|-----------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type | <a href="#">OTA_CodeType</a>      | required |       | Type of the additional detail:<br>8 for Check-in check-out details<br>9 for Extra charge details<br>11 for Service charge inclusion details<br>14 for Miscellaneous details<br>16 for Inclusion details<br>20 for advanced booking restrictions details<br>29 for Booking guideline details<br>53 for Internal Rate Code Information |
| Code | <a href="#">StringLength1to16</a> | optional |       | Code associated to the Type defined previously                                                                                                                                                                                                                                                                                       |



### 1.1.4.1.2.1.8.1.1. DetailDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/AdditionalDetails/AdditionalDetail/DetailDescription

#### Format Description

| Name              | Type          | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-------------------|---------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DetailDescription | ParagraphType | 0 / 1 | false | Name or sub-type of the detail: <ul style="list-style-type: none"> <li>if Type=8:<br/>"check-in" for check-in details<br/>"check-out" for check-out details<br/>"express check-in" for express check-in available<br/>"express check-out" for express check-out available</li> <li>if Type=20:<br/>not used</li> <li>if Type=29:<br/>"minimum stay" for minimum length of stay details<br/>"maximum stay" for maximum length of stay details</li> <li>else:<br/>free text.</li> </ul> |

#### Elements

| Name                     | Type              | Occ           | Nil   | Description                                                       |
|--------------------------|-------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1         | false | Textual description                                               |
| Image                    | xs:string         | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name | Type                              | Use      | Value | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|------|-----------------------------------|----------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name | <a href="#">StringLength1to64</a> | optional |       | Name or sub-type of the detail: <ul style="list-style-type: none"> <li>if Type=8:<br/>"check-in" for check-in details<br/>"check-out" for check-out details<br/>"express check-in" for express check-in available<br/>"express check-out" for express check-out available</li> <li>if Type=20:<br/>not used</li> <li>if Type=29:<br/>"minimum stay" for minimum length of stay details<br/>"maximum stay" for maximum length of stay details</li> <li>else:<br/>free text.</li> </ul> |

### 1.1.4.1.2.1.8.1.1.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/AdditionalDetails/AdditionalDetail/DetailDescription/Text

#### Format Description

| Name | Type      | Occ   | Nil   | Description         |
|------|-----------|-------|-------|---------------------|
| Text | xs:string | 1 / 1 | false | Textual description |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.8.1.1.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/AdditionalDetails/AdditionalDetail/DetailDescription/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.9. ModificationFee

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/ModificationFee

## Format Description

| Name            | Type                | Occ   | Nil   | Description                                                                                                                                                                                                        |
|-----------------|---------------------|-------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ModificationFee | CancelPenaltiesType | 0 / 1 | false | A collection of modification fees. Note that although this modification fee is typed as CancelPenaltiesType to promote reuse, cancellation penalties information should be entered in the CancelPenalties element. |

## Elements

| Name                          | Type              | Occ               | Nil   | Description                                             |
|-------------------------------|-------------------|-------------------|-------|---------------------------------------------------------|
| sequence                      |                   | 1 / 1             |       |                                                         |
| <a href="#">CancelPenalty</a> | CancelPenaltyType | 0 / unbound<br>ed | false | Defines the cancellation penalty of the hotel facility. |

## Attributes

| Name                  | Type       | Use      | Value | Description                                                                                                                                         |
|-----------------------|------------|----------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| CancelPolicyIndicator | xs:boolean | optional |       | When true, indicates a cancel policy exists. When false, no cancel policy exists. Typically this indicator is used when details are not being sent. |

### 1.1.4.1.2.1.9.1. CancelPenalty

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/ModificationFee/CancelPenalty

## Format Description

| Name          | Type              | Occ           | Nil   | Description                                             |
|---------------|-------------------|---------------|-------|---------------------------------------------------------|
| CancelPenalty | CancelPenaltyType | 0 / unbounded | false | Defines the cancellation penalty of the hotel facility. |

## Elements

| Name                               | Type              | Occ   | Nil   | Description                                                                     |
|------------------------------------|-------------------|-------|-------|---------------------------------------------------------------------------------|
| <i>sequence</i>                    |                   | 1 / 1 |       |                                                                                 |
| <a href="#">Deadline</a>           |                   | 0 / 1 | false | Cancellation deadline, absolute or relative.                                    |
| <a href="#">AmountPercent</a>      | AmountPercentType | 0 / 1 | false | Cancellation fee expressed as a fixed amount, or percentage of/for room nights. |
| <a href="#">PenaltyDescription</a> | ParagraphType     | 0 / 9 | false | Text description of the Penalty in a given language.                            |

## Attributes

| Name          | Type                                     | Use      | Value | Description                                                                                                                                            |
|---------------|------------------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| PolicyCode    | <a href="#">StringLength1to16</a>        | required |       | Policy Code = Modification                                                                                                                             |
| NonRefundable | xs:boolean                               | optional |       | Indicates that any prepayment for the reservation is non refundable, therefore a 100% penalty on the prepayment is applied, irrespective of deadline.  |
| Start         | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The starting value of the time span.                                                                                                                   |
| Duration      | <a href="#">DurationType</a>             | optional |       | The duration datatype represents a combination of year, month, day and time values representing a single duration of time, encoded as a single string. |
| End           | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The ending value of the time span.                                                                                                                     |

### 1.1.4.1.2.1.9.1.1. Deadline

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/ModificationFee/CancelPenalty/Deadline

#### Format Description

| Name     | Type | Occ   | Nil   | Description                                  |
|----------|------|-------|-------|----------------------------------------------|
| Deadline |      | 0 / 1 | false | Cancellation deadline, absolute or relative. |

#### Attributes

| Name             | Type                               | Use      | Value | Description                                                                      |
|------------------|------------------------------------|----------|-------|----------------------------------------------------------------------------------|
| AbsoluteDeadline | <a href="#">TimeOrDateTimeType</a> | optional |       | Defines the absolute deadline. Either this or the offset attributes may be used. |

### 1.1.4.1.2.1.9.1.2. AmountPercent

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/ModificationFee/CancelPenalty/AmountPercent

#### Format Description

| Name          | Type              | Occ   | Nil   | Description                                                                    |
|---------------|-------------------|-------|-------|--------------------------------------------------------------------------------|
| AmountPercent | AmountPercentType | 0 / 1 | false | Cancellation fee expressed as a fixed amount, or percentage of/or room nights. |

#### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

#### Attributes

| Name                      | Type                         | Use      | Value | Description                                                                       |
|---------------------------|------------------------------|----------|-------|-----------------------------------------------------------------------------------|
| NmbrOfNights              | xs:nonNegativeInteger        | optional |       | The number of nights of the hotel stay that are used to calculate the fee amount. |
| <a href="#">BasisType</a> |                              | optional |       | Provides the basis for how the amount of the guarantee is calculated.             |
| Percent                   | <a href="#">Percentage</a>   | optional |       | The percentage used to calculate the amount.                                      |
| Amount                    | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                |
| CurrencyCode              | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.              |

|               |                       |          |  |                                                                                                |
|---------------|-----------------------|----------|--|------------------------------------------------------------------------------------------------|
| DecimalPlaces | xs:nonNegativeInteger | optional |  | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |
|---------------|-----------------------|----------|--|------------------------------------------------------------------------------------------------|

Attribute: BasisType

Variety: atomic

Base: [StringLength1to16](#)

Documentation:

| Enumeration | description                                 |
|-------------|---------------------------------------------|
| FullStay    | Uses the full stay as the basis.            |
| Nights      | Uses the nights as the basis.               |
| FirstLast   | Uses the first and last night as the basis. |

### 1.1.4.1.2.1.9.1.3. PenaltyDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/ModificationFee/CancelPenalty/PenaltyDescription

#### Format Description

| Name               | Type          | Occ   | Nil   | Description                                          |
|--------------------|---------------|-------|-------|------------------------------------------------------|
| PenaltyDescription | ParagraphType | 0 / 9 | false | Text description of the Penalty in a given language. |

#### Elements

| Name                     | Type              | Occ           | Nil   | Description                                                       |
|--------------------------|-------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1         | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name | Type | Use | Value | Description |
|------|------|-----|-------|-------------|
|------|------|-----|-------|-------------|

|      |                                   |          |  |                                                                                                                                                                                    |
|------|-----------------------------------|----------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name | <a href="#">StringLength1to64</a> | optional |  | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
|------|-----------------------------------|----------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### 1.1.4.1.2.1.9.1.3.1. **Text**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/ModificationFee/CancelPenalty/PenaltyDescription/Text

#### *Format Description*

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

#### *Attributes*

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.2.1.9.1.3.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RatePlans/RatePlan/ModificationFee/CancelPenalty/PenaltyDescription/ListItem

#### *Format Description*

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|          |           |       |       |                                                                   |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |
|----------|-----------|-------|-------|-------------------------------------------------------------------|

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

### Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.4.1.3. RoomRates

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates

### Format Description

| Name      | Type | Occ   | Nil   | Description                                                                                                                                                                                                                             |
|-----------|------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| RoomRates |      | 0 / 1 | false | A collection of Room Rates associated with a particular Room Stay. Each Room Rate combination can have multiple rates. Example King room, Rack rate plan, Monday through Thursday, weekday amount, Friday and Saturday, weekend amount. |

## Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |



|                                |                    |                   |       |                                                                                                                                 |
|--------------------------------|--------------------|-------------------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">RoomRate</a>       |                    | 1 / unbound<br>ed | false |                                                                                                                                 |
| <a href="#">TPA_Extensions</a> | TPA_ExtensionsType | 0 / 1             | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

## Attributes

| Name              | Type       | Use      | Value | Description                                                                          |
|-------------------|------------|----------|-------|--------------------------------------------------------------------------------------|
| MoreRatesExistInd | xs:boolean | optional |       | When true, indicates more rates exist. When false, all rate information is provided. |

### 1.1.4.1.3.1. RoomRate

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate

## Format Description

| Name     | Type         | Occ               | Nil   | Description |
|----------|--------------|-------------------|-------|-------------|
| RoomRate | RoomRateType | 1 / unbound<br>ed | false |             |

## Elements

| Name                                      | Type            | Occ   | Nil   | Description                                                                                                 |
|-------------------------------------------|-----------------|-------|-------|-------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                           |                 | 1 / 1 |       |                                                                                                             |
| <a href="#">Rates</a>                     | RateType        | 0 / 1 | false | Individual rate amount. This rate is valid for a range of number of occupants and an occupant type.         |
| <a href="#">RoomRateDescription</a>       | ParagraphType   | 0 / 1 | false | Room and rate description                                                                                   |
| <a href="#">Features</a>                  |                 | 0 / 1 | false | A collection of features that are made available as part of this specific room and this specific rate plan. |
| <a href="#">Total</a>                     | TotalType       | 0 / 1 | false | Total amount of the number of rooms of the room rate                                                        |
| <a href="#">Availability</a>              |                 | 0 / 5 | false | Provides information on the availability of the room rate.                                                  |
| <i>sequence</i>                           |                 | 1 / 1 |       |                                                                                                             |
| <a href="#">AdvanceBookingRestriction</a> |                 | 0 / 1 | false | The restriction will only be specified for the first Rate occurrence.                                       |
| <a href="#">ServiceRPHs</a>               | ServiceRPHsType | 0 / 1 | false | A container for the unique references to the services for the room stay.                                    |
| <a href="#">GuestCounts</a>               |                 | 0 / 1 | false | Guest count per room mandatory when multiple room                                                           |

## Attributes

| Name                               | Type                              | Use      | Value | Description                                                                                                                                                                               |
|------------------------------------|-----------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BookingCode                        | <a href="#">StringLength1to16</a> | optional |       | Booking code: internal identifier of the the rate plan product pair = ProductCode-RatePlanCode                                                                                            |
| EffectiveDate                      | xs:date                           | optional |       | Indicates the starting date.                                                                                                                                                              |
| ExpireDate                         | xs:date                           | optional |       | Indicates the ending date.                                                                                                                                                                |
| ExpireDateExclusiveIndicator       | xs:boolean                        | optional |       | When true, indicates that the ExpireDate is the first day after the applicable period (e.g. when expire date is Oct 15 the last date of the period is Oct 14).                            |
| RoomTypeCode                       | <a href="#">StringLength1to16</a> | required |       | Specific system room type code, ex: A1K, A1Q etc.                                                                                                                                         |
| NumberOfUnits                      | xs:integer                        | optional |       | The number of rooms.                                                                                                                                                                      |
| RatePlanType                       | <a href="#">OTA_CodeType</a>      | optional |       | An enumerated type that allows the query to specify a rate category type, and provides major categories for comparison across brands. Refer to OpenTravel Code List Rate Plan Type (RPT). |
| RatePlanCode                       | <a href="#">StringLength1to64</a> | required |       | Rate plan code                                                                                                                                                                            |
| RatePlanID                         | <a href="#">StringLength1to64</a> | optional |       | Corporate discount number                                                                                                                                                                 |
| RatePlanQualifier                  | xs:boolean                        | optional |       | The Rate Plan Qualifier is used to control the sort order of RatePlans. Those Rate Plans that are not qualified will appear first, those that are qualified will appear last.             |
| RatePlanCategory                   | <a href="#">StringLength1to64</a> | optional |       |                                                                                                                                                                                           |
| <a href="#">AvailabilityStatus</a> | RateIndicatorType *               | required |       | Used to specify an availability status for the room rate.                                                                                                                                 |
| RoomID                             | <a href="#">StringLength1to16</a> | optional |       | A string value representing the unique identification of a room.                                                                                                                          |

### Attribute: AvailabilityStatus

Variety: atomic

Base: [StringLength1to32](#)

Documentation: Set to "AvailableForSale" if no rate change applies

Set to "OnRequest" if the rate is On-request

| Enumeration         | description                                                                                          |
|---------------------|------------------------------------------------------------------------------------------------------|
| ChangeDuringStay    |                                                                                                      |
| MultipleNights      |                                                                                                      |
| Exclusive           | Availability is limited based on guest qualification criteria e.g. AAA member or Government Employee |
| OnRequest           |                                                                                                      |
| LimitedAvailability |                                                                                                      |
| AvailableForSale    |                                                                                                      |
| ClosedOut           |                                                                                                      |
| OtherAvailable      |                                                                                                      |
| UnableToProcess     | Indicates an issue that precluded the ability to provide the information.                            |
| NoAvailability      |                                                                                                      |
| RoomTypeClosed      |                                                                                                      |

|                |                                                                                                        |
|----------------|--------------------------------------------------------------------------------------------------------|
| RatePlanClosed |                                                                                                        |
| LOS_Restricted |                                                                                                        |
| Restricted     | Availability is limited based on distribution channel qualification criteria (e.g., Expedia or Sabre). |
| DoesNotExist   | The rate plan does not exist.                                                                          |

### 1.1.4.1.3.1.1. Rates

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates

#### Format Description

| Name  | Type     | Occ   | Nil   | Description                                                                                         |
|-------|----------|-------|-------|-----------------------------------------------------------------------------------------------------|
| Rates | RateType | 0 / 1 | false | Individual rate amount. This rate is valid for a range of number of occupants and an occupant type. |

#### Elements

| Name                 | Type | Occ               | Nil   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------|------|-------------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>      |      | 1 / 1             |       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <a href="#">Rate</a> |      | 1 / unbound<br>ed | false | The Rate contains a collection of elements that define the amount of the rate, associated fees, additional occupant amounts as well as payment and cancellation policies. Taxes can be broken out or included within the various amounts. A currency can be associated to each amount. The applicable period of the the rate are indicated by the effective dates. Restrictions that may apply to that rate, such as the minimum or maximum length of stay, stay-over dates (such as a Saturday night), min/max guests applicable for the rate, and age group (ex Adult) are attributes of Rate. It indicates the number of units that the quoted rate is based upon, as well as the TimeUnits type used that the rate is based upon, e.g.: 3days at \$100.00 per day. |

### 1.1.4.1.3.1.1.1. Rate

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate

#### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|      |            |                |       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|------|------------|----------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rate | AmountType | 1 / unbound ed | false | The Rate contains a collection of elements that define the amount of the rate, associated fees, additional occupant amounts as well as payment and cancellation policies. Taxes can be broken out or included within the various amounts. A currency can be associated to each amount. The applicable period of the the rate are indicated by the effective dates. Restrictions that may apply to that rate, such as the minimum or maximum length of stay, stay-over dates (such as a Saturday night), min/max guests applicable for the rate, and age group (ex Adult) are attributes of Rate. It indicates the number of units that the quoted rate is based upon, as well as the TimeUnits type used that the rate is based upon, e.g.: 3days at \$100.00 per day. |
|------|------------|----------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Elements

| Name                              | Type                       | Occ   | Nil   | Description                                                                                                                                                                                                                                               |
|-----------------------------------|----------------------------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                   |                            | 1 / 1 |       |                                                                                                                                                                                                                                                           |
| <a href="#">Base</a>              | TotalType                  | 0 / 1 | false | The base amount charged for the accommodation or service per unit of time (ex: Nightly, Weekly, etc). If TaxInclusive is set to True, then taxes are included in the base amount. Note that any additional charges should itemized in the other elements. |
| <a href="#">Fees</a>              | FeesType                   | 0 / 1 | false | A collection of Fees.                                                                                                                                                                                                                                     |
| <a href="#">PaymentPolicies</a>   | RequiredPaymentsType       | 0 / 1 | false | A collection of Payment Policies.                                                                                                                                                                                                                         |
| <a href="#">Total</a>             | TotalType                  | 0 / 1 | false | Total amount of 1 room. Sent only if several rooms are requested in the room rate. In the case of NH, this is an intermediate total including the taxes payable online, but not the taxes payable at the hotel                                            |
| <a href="#">RateDescription</a>   | ParagraphType              | 0 / 1 | false |                                                                                                                                                                                                                                                           |
| <a href="#">AdditionalCharges</a> | HotelAdditionalChargesType | 0 / 1 | false | Collection of additional charges.                                                                                                                                                                                                                         |
| <i>sequence</i>                   |                            | 1 / 1 |       |                                                                                                                                                                                                                                                           |
| <a href="#">TPA_Extensions</a>    | TPA_ExtensionsType         | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA).                                                                                                                           |

## Attributes

| Name               | Type                         | Use      | Value | Description                                                                  |
|--------------------|------------------------------|----------|-------|------------------------------------------------------------------------------|
| EffectiveDate      | xs:date                      | optional |       | Indicates the starting date.                                                 |
| ExpireDate         | xs:date                      | optional |       | Indicates the ending date.                                                   |
| NumberOfUnits      | xs:integer                   | optional |       |                                                                              |
| RateTimeUnit       | <a href="#">TimeUnitType</a> | optional |       | Indicates the time unit for the rate.                                        |
| UnitMultiplier     | xs:positiveInteger           | required |       | Indicates the number of rate time units such as "3 Days".                    |
| MaxGuestApplicable | xs:positiveInteger           | optional |       |                                                                              |
| MinLOS             | xs:nonNegativeInteger        | optional |       | Minimum length of stay / Only given on the 1st occurrence of the rate change |
| MaxLOS             | xs:nonNegativeInteger        | optional |       | Maximum length of stay / Only given on the 1st occurrence of the rate change |

|                 |                                   |          |  |                                                                                                                                     |
|-----------------|-----------------------------------|----------|--|-------------------------------------------------------------------------------------------------------------------------------------|
| StayOverDate    | <a href="#">DayOfWeekType</a>     | optional |  | Day of week guest is required to stay over in order to be eligible for this rate.                                                   |
| ChargeType      | <a href="#">OTA_CodeType</a>      | optional |  | The type of the amount being charged, e.g. per night. Refer to OpenTravel Code List Charge Type Code (CHG).                         |
| RateMode        | <a href="#">OTA_CodeType</a>      | optional |  | For MultiSingle when the product can't be identified (no booking code) for the hotels then the RateMode value is set to 1 (minimum) |
| CachedIndicator | xs:boolean                        | optional |  | When true, this indicates the rate data is not real-time.                                                                           |
| RateSource      | <a href="#">StringLength1to32</a> | optional |  | Indicates if the rate coming from the provider is the best available rate or not (correspond to BAR indicator only)                 |
| RateTypeCode    | <a href="#">OTA_CodeType</a>      | optional |  | Used to identify the type of rate. Refer to OpenTravel Code list Rate Plan Type (RPT).                                              |
| RoomPricingType | <a href="#">PricingType</a>       | optional |  | Specifies how the room is priced (per night, per person, etc.).                                                                     |

### 1.1.4.1.3.1.1.1.1. Base

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Base

#### Format Description

| Name | Type      | Occ   | Nil   | Description                                                                                                                                                                                                                                               |
|------|-----------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base | TotalType | 0 / 1 | false | The base amount charged for the accommodation or service per unit of time (ex: Nightly, Weekly, etc). If TaxInclusive is set to True, then taxes are included in the base amount. Note that any additional charges should itemized in the other elements. |

#### Elements

| Name                  | Type      | Occ   | Nil   | Description            |
|-----------------------|-----------|-------|-------|------------------------|
| <i>sequence</i>       |           | 1 / 1 |       |                        |
| <a href="#">Taxes</a> | TaxesType | 0 / 1 | false | A collection of taxes. |

#### Attributes

| Name                            | Type                         | Use      | Value | Description                                                                                                               |
|---------------------------------|------------------------------|----------|-------|---------------------------------------------------------------------------------------------------------------------------|
| AmountBeforeTax                 | <a href="#">Money</a>        | optional |       | Amount before taxes. At least AmountBeforeTax or AmountAfterTax is compulsory, but both can not be sent at the same time. |
| AmountAfterTax                  | <a href="#">Money</a>        | optional |       | Amount before taxes. At least AmountBeforeTax or AmountAfterTax is compulsory, but both can not be sent at the same time. |
| CurrencyCode                    | <a href="#">AlphaLength3</a> | required |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                      |
| DecimalPlaces                   | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                            |
| AdditionalFeesExcludedIndicator | xs:boolean                   | optional |       | When true, amounts do not contain additional fees or charges.                                                             |

|      |                              |          |  |                                                                  |
|------|------------------------------|----------|--|------------------------------------------------------------------|
| Type | <a href="#">OTA_CodeType</a> | optional |  | Type of charge. Refer to OpenTravel Code List Charge Type (CHG). |
|------|------------------------------|----------|--|------------------------------------------------------------------|

### 1.1.4.1.3.1.1.1.1.1. Taxes

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Base/Taxes

#### Format Description

| Name  | Type      | Occ   | Nil   | Description            |
|-------|-----------|-------|-------|------------------------|
| Taxes | TaxesType | 0 / 1 | false | A collection of taxes. |

#### Elements

| Name                | Type    | Occ    | Nil   | Description        |
|---------------------|---------|--------|-------|--------------------|
| sequence            |         | 1 / 1  |       |                    |
| <a href="#">Tax</a> | TaxType | 0 / 99 | false | An individual tax. |

#### Attributes

| Name          | Type                         | Use      | Value | Description                                                                                    |
|---------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| Amount        | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                             |
| CurrencyCode  | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.3.1.1.1.1.1. Tax

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Base/Taxes/Tax

#### Format Description

| Name | Type    | Occ    | Nil   | Description        |
|------|---------|--------|-------|--------------------|
| Tax  | TaxType | 0 / 99 | false | An individual tax. |

#### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

|                |               |       |       |                                                    |
|----------------|---------------|-------|-------|----------------------------------------------------|
| TaxDescription | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |
|----------------|---------------|-------|-------|----------------------------------------------------|

## Attributes

| Name                         | Type                                    | Use      | Value | Description                                                                                                                                                      |
|------------------------------|-----------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                         | <a href="#">AmountDeterminationType</a> | optional |       | Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).              |
| Code                         | <a href="#">OTA_CodeType</a>            | optional |       | Code identifying the fee (e.g., agency fee, municipality fee). Refer to OpenTravel Code List Fee Tax Type (FTT).                                                 |
| Percent                      | <a href="#">Percentage</a>              | optional |       | Fee percentage; if zero, assume use of the Amount attribute (Amount or Percent must be a zero value).                                                            |
| Amount                       | <a href="#">Money</a>                   | optional |       | A monetary amount.                                                                                                                                               |
| CurrencyCode                 | <a href="#">AlphaLength3</a>            | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                             |
| DecimalPlaces                | xs:nonNegativeInteger                   | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                   |
| EffectiveDate                | xs:date                                 | optional |       | Indicates the starting date.                                                                                                                                     |
| ExpireDate                   | xs:date                                 | optional |       | Indicates the ending date.                                                                                                                                       |
| ExpireDateExclusiveIndicator | xs:boolean                              | optional |       | When true, indicates that the ExpireDate is the first day after the applicable period (e.g. when expire date is Oct 15 the last date of the period is Oct 14).   |
| ChargeUnit                   | <a href="#">OTA_CodeType</a>            | optional |       | This is the unit for which the charge applies (e.g. room, person, seat). Refer to OpenTravel Code List Charge Type (CHG).                                        |
| ChargeFrequency              | <a href="#">OTA_CodeType</a>            | optional |       | This is the timeframe used to apply the charge during the course of the reservation (e.g. Daily, Weekly, Stay). Refer to OpenTravel Code List Charge Type (CHG). |
| ChargeUnitExempt             | xs:positiveInteger                      | optional |       | Number of units permitted before charges are applied (e.g., more than 4 persons).                                                                                |
| ChargeFrequencyExempt        | xs:positiveInteger                      | optional |       | ChargeFrequency exemptions before charges are applied (e.g. after 2 nights).                                                                                     |
| MaxChargeUnitApplies         | xs:positiveInteger                      | optional |       | Maximum number of Units for which the charge will be applied (e.g., waive charges above 10 rooms).                                                               |
| MaxChargeFrequencyApplies    | xs:positiveInteger                      | optional |       | Maximum number of times the charge will be applied (e.g. waive charges above 30 nights).                                                                         |

#### 1.1.4.1.3.1.1.1.1.1.1. TaxDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Base/Taxes/Tax/TaxDescription

### Format Description

| Name           | Type          | Occ   | Nil   | Description                                        |
|----------------|---------------|-------|-------|----------------------------------------------------|
| TaxDescription | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

| Name                     | Type                  | Occ            | Nil   | Description                                                       |
|--------------------------|-----------------------|----------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                       | 0 / unbound ed |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextTextType | 1 / 1          | false | Formatted text content.                                           |
| Image                    | xs:string             | 1 / 1          | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI             | 1 / 1          | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                       | 1 / 1          | false | Formatted text content and an associated item or sequence number. |

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                        |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name               | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber    | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime     | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID          | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |
| LastModifyDateTime | xs:dateTime                       | optional |       | Time stamp of last modification.                                                                                                                                                   |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |       | Identifies the last software system or person to modify a record.                                                                                                                  |
| PurgeDate          | xs:date                           | optional |       | Date an item will be purged from a database (e.g., from a live database to an archive).                                                                                            |
| Language           | xs:language                       | optional |       | Language identification.                                                                                                                                                           |

XPath :/OTA HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Base/Taxes/Tax/TaxDescription/Text

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

| Name | Type | Use | Value | Description |
|------|------|-----|-------|-------------|
|------|------|-----|-------|-------------|



|                            |             |          |  |                                                                                                               |
|----------------------------|-------------|----------|--|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |  | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |  | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |  | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.1.1.1.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Base/Taxes/Tax/TaxDescription/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.2. Fees

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees

#### Format Description

| Name | Type    | Occ   | Nil   | Description           |
|------|---------|-------|-------|-----------------------|
| Fees | FeeType | 0 / 1 | false | A collection of Fees. |

#### Elements

| Name                | Type    | Occ               | Nil   | Description |
|---------------------|---------|-------------------|-------|-------------|
| <i>sequence</i>     |         | 1 / 1             |       |             |
| <a href="#">Fee</a> | FeeType | 1 / unbound<br>ed | false |             |

### 1.1.4.1.3.1.1.1.2.1. Fee

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee

#### Format Description

| Name | Type    | Occ               | Nil   | Description |
|------|---------|-------------------|-------|-------------|
| Fee  | FeeType | 1 / unbound<br>ed | false |             |

#### Elements

| Name            | Type | Occ   | Nil | Description |
|-----------------|------|-------|-----|-------------|
| <i>sequence</i> |      | 1 / 1 |     |             |

|                             |               |       |       |                                                   |
|-----------------------------|---------------|-------|-------|---------------------------------------------------|
| <a href="#">Taxes</a>       | TaxesType     | 0 / 1 | false | Used for taxes on the associated fee.             |
| <a href="#">Description</a> | ParagraphType | 0 / 5 | false | Text description of the fees in a given language. |

## Attributes

| Name                         | Type                                    | Use      | Value | Description                                                                                                                                                                                                                                                                         |
|------------------------------|-----------------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TaxInclusive                 | xs:boolean                              | optional |       | Indicates whether taxes are included when figuring the fees.                                                                                                                                                                                                                        |
| Type                         | <a href="#">AmountDeterminationType</a> | optional |       | Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).                                                                                                                                 |
| Code                         | <a href="#">OTA_CodeType</a>            | optional |       | Tax = ???<br>Service = 14 Service charge<br>Fee = 34 Local fee ????<br>Surcharge = 16 Surcharge<br>Inclusion = No code<br>Meal = ???<br>Extra occupant = 31 Extra person charge<br>Extra bedding = 38 Rollaway fee<br>Extra = 41 Not known ????<br>Miscellaneous = 27 Miscellaneous |
| Percent                      | <a href="#">Percentage</a>              | optional |       | Fee percentage; if zero, assume use of the Amount attribute (Amount or Percent must be a zero value).                                                                                                                                                                               |
| Amount                       | <a href="#">Money</a>                   | optional |       | A monetary amount.                                                                                                                                                                                                                                                                  |
| CurrencyCode                 | <a href="#">AlphaLength3</a>            | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                                                                                                                                                |
| DecimalPlaces                | xs:nonNegativeInteger                   | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                                                                                                                                      |
| EffectiveDate                | xs:date                                 | optional |       | Indicates the starting date.                                                                                                                                                                                                                                                        |
| ExpireDate                   | xs:date                                 | optional |       | Indicates the ending date.                                                                                                                                                                                                                                                          |
| ExpireDateExclusiveIndicator | xs:boolean                              | optional |       | When true, indicates that the ExpireDate is the first day after the applicable period (e.g. when expire date is Oct 15 the last date of the period is Oct 14).                                                                                                                      |
| MandatoryIndicator           | xs:boolean                              | optional |       | When true, indicates the fee is mandatory. When false, the fee is not mandatory.                                                                                                                                                                                                    |
| ChargeUnit                   | <a href="#">OTA_CodeType</a>            | optional |       | This is the unit for which the charge applies (e.g. room, person, seat). Refer to OpenTravel Code List Charge Type (CHG).                                                                                                                                                           |
| ChargeFrequency              | <a href="#">OTA_CodeType</a>            | optional |       | This is the timeframe used to apply the charge during the course of the reservation (e.g. Daily, Weekly, Stay). Refer to OpenTravel Code List Charge Type (CHG).                                                                                                                    |
| ChargeUnitExempt             | xs:positiveInteger                      | optional |       | Number of units permitted before charges are applied (e.g., more than 4 persons).                                                                                                                                                                                                   |
| ChargeFrequencyExempt        | xs:positiveInteger                      | optional |       | ChargeFrequency exemptions before charges are applied (e.g. after 2 nights).                                                                                                                                                                                                        |
| MaxChargeUnitApplies         | xs:positiveInteger                      | optional |       | Maximum number of Units for which the charge will be applied (e.g., waive charges above 10 rooms).                                                                                                                                                                                  |
| MaxChargeFrequencyApplies    | xs:positiveInteger                      | optional |       | Maximum number of times the charge will be applied (e.g. waive charges above 30 nights).                                                                                                                                                                                            |
| TaxableIndicator             | xs:boolean                              | optional |       | When true, indicates that the fee is subject to tax.                                                                                                                                                                                                                                |

### 1.1.4.1.3.1.1.1.2.1.1. Taxes

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee/Taxes

#### Format Description

| Name  | Type      | Occ   | Nil   | Description                           |
|-------|-----------|-------|-------|---------------------------------------|
| Taxes | TaxesType | 0 / 1 | false | Used for taxes on the associated fee. |

#### Elements

| Name                | Type    | Occ    | Nil   | Description        |
|---------------------|---------|--------|-------|--------------------|
| sequence            |         | 1 / 1  |       |                    |
| <a href="#">Tax</a> | TaxType | 0 / 99 | false | An individual tax. |

#### Attributes

| Name          | Type                         | Use      | Value | Description                                                                                    |
|---------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| Amount        | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                             |
| CurrencyCode  | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.3.1.1.1.2.1.1.1. Tax

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee/Taxes/Tax

#### Format Description

| Name | Type    | Occ    | Nil   | Description        |
|------|---------|--------|-------|--------------------|
| Tax  | TaxType | 0 / 99 | false | An individual tax. |

#### Elements

| Name                           | Type          | Occ   | Nil   | Description                                        |
|--------------------------------|---------------|-------|-------|----------------------------------------------------|
| sequence                       |               | 1 / 1 |       |                                                    |
| <a href="#">TaxDescription</a> | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

## Attributes

| Name                         | Type                                    | Use      | Value | Description                                                                                                                                                      |
|------------------------------|-----------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                         | <a href="#">AmountDeterminationType</a> | optional |       | Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).              |
| Code                         | <a href="#">OTA_CodeType</a>            | optional |       | Code identifying the fee (e.g., agency fee, municipality fee). Refer to OpenTravel Code List Fee Tax Type (FTT).                                                 |
| Percent                      | <a href="#">Percentage</a>              | optional |       | Fee percentage; if zero, assume use of the Amount attribute (Amount or Percent must be a zero value).                                                            |
| Amount                       | <a href="#">Money</a>                   | optional |       | A monetary amount.                                                                                                                                               |
| CurrencyCode                 | <a href="#">AlphaLength3</a>            | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                             |
| DecimalPlaces                | xs:nonNegativeInteger                   | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                   |
| EffectiveDate                | xs:date                                 | optional |       | Indicates the starting date.                                                                                                                                     |
| ExpireDate                   | xs:date                                 | optional |       | Indicates the ending date.                                                                                                                                       |
| ExpireDateExclusiveIndicator | xs:boolean                              | optional |       | When true, indicates that the ExpireDate is the first day after the applicable period (e.g. when expire date is Oct 15 the last date of the period is Oct 14).   |
| ChargeUnit                   | <a href="#">OTA_CodeType</a>            | optional |       | This is the unit for which the charge applies (e.g. room, person, seat). Refer to OpenTravel Code List Charge Type (CHG).                                        |
| ChargeFrequency              | <a href="#">OTA_CodeType</a>            | optional |       | This is the timeframe used to apply the charge during the course of the reservation (e.g. Daily, Weekly, Stay). Refer to OpenTravel Code List Charge Type (CHG). |
| ChargeUnitExempt             | xs:positiveInteger                      | optional |       | Number of units permitted before charges are applied (e.g., more than 4 persons).                                                                                |
| ChargeFrequencyExempt        | xs:positiveInteger                      | optional |       | ChargeFrequency exemptions before charges are applied (e.g. after 2 nights).                                                                                     |
| MaxChargeUnitApplies         | xs:positiveInteger                      | optional |       | Maximum number of Units for which the charge will be applied (e.g., waive charges above 10 rooms).                                                               |
| MaxChargeFrequencyApplies    | xs:positiveInteger                      | optional |       | Maximum number of times the charge will be applied (e.g. waive charges above 30 nights).                                                                         |

### 1.1.4.1.3.1.1.1.2.1.1.1.1. TaxDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee/Taxes/Tax/TaxDescription

## Format Description

| Name           | Type          | Occ   | Nil   | Description                                        |
|----------------|---------------|-------|-------|----------------------------------------------------|
| TaxDescription | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

## Elements

| Name                     | Type              | Occ           | Nil   | Description                                                       |
|--------------------------|-------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1         | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                        |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name               | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber    | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime     | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID          | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |
| LastModifyDateTime | xs:dateTime                       | optional |       | Time stamp of last modification.                                                                                                                                                   |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |       | Identifies the last software system or person to modify a record.                                                                                                                  |
| PurgeDate          | xs:date                           | optional |       | Date an item will be purged from a database (e.g., from a live database to an archive).                                                                                            |
| Language           | xs:language                       | optional |       | Language identification.                                                                                                                                                           |

### 1.1.4.1.3.1.1.1.2.1.1.1.1.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee/Taxes/Tax/TaxDescription/Text

## Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

## Attributes

| Name | Type | Use | Value | Description |
|------|------|-----|-------|-------------|
|------|------|-----|-------|-------------|

|                            |             |          |  |                                                                                                               |
|----------------------------|-------------|----------|--|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |  | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |  | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |  | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

[Documentation:](#)

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.2.1.1.1.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee/Taxes/Tax/TaxDescription/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.2.1.2. Description

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee/Description

#### Format Description

| Name        | Type          | Occ   | Nil   | Description                                       |
|-------------|---------------|-------|-------|---------------------------------------------------|
| Description | ParagraphType | 0 / 5 | false | Text description of the fees in a given language. |

#### Elements

| Name                     | Type              | Occ           | Nil   | Description                                                       |
|--------------------------|-------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1         | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name | Type                              | Use      | Value | Description                                                                                                                                                                        |
|------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |

### 1.1.4.1.3.1.1.1.2.1.2.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee/Description/Text



### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.4.1.3.1.1.1.2.1.2.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Fees/Fee/Description/ListItem

### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

### Attributes

| Name | Type | Use | Value | Description |
|------|------|-----|-------|-------------|
|------|------|-----|-------|-------------|

|                            |             |          |  |                                                                                                               |
|----------------------------|-------------|----------|--|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |  | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |  | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |  | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |  | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.3. PaymentPolicies

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies

#### Format Description

| Name            | Type                 | Occ   | Nil   | Description                       |
|-----------------|----------------------|-------|-------|-----------------------------------|
| PaymentPolicies | RequiredPaymentsType | 0 / 1 | false | A collection of Payment Policies. |

#### Elements

| Name                             | Type | Occ               | Nil   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------|------|-------------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                  |      | 1 / 1             |       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <a href="#">GuaranteePayment</a> |      | 1 / unbound<br>ed | false | <p>List of Form of Payment with if needed amount/percent associated to.<br/>The first GuaranteePayment element contains only PaymentCode, GuaranteeType, AmountPercent (Deposit/Guarantee), Deadline, Description.<br/>For the form of payments a dedicated guarantepayment element is used, if an AmountPercent element is used it will be considered as a fee for that specific form of payment.</p> <p>One GuaranteePayment element including one AcceptedPayments element has to be used per form of payment, as the Amount element will be considered as fee.</p> |

### 1.1.4.1.3.1.1.1.3.1. GuaranteePayment

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment

#### Format Description

| Name             | Type | Occ            | Nil   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|------------------|------|----------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GuaranteePayment |      | 1 / unbound ed | false | <p>List of Form of Payment with if needed amount/percent associated to.</p> <p>The first GuaranteePayment element contains only PaymentCode, GuaranteeType, AmountPercent (Deposit/Guarantee), Deadline, Description.</p> <p>For the form of payments a dedicated guarantepayment element is used, if an AmountPercent element is used it will be considered as a fee for that specific form of payment.</p> <p>One GuaranteePayment element including one AcceptedPayments element has to be used per form of payment, as the Amount element will be considered as fee.</p> |

#### Elements

| Name                             | Type                 | Occ   | Nil   | Description                                                                                                                     |
|----------------------------------|----------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                  |                      | 1 / 1 |       |                                                                                                                                 |
| <a href="#">AcceptedPayments</a> | AcceptedPaymentsType | 0 / 1 | false | Collection of forms of payment accepted for payment.                                                                            |
| <a href="#">AmountPercent</a>    |                      | 0 / 1 | false | Payment expressed as a fixed amount, or a percentage of/or room nights.                                                         |
| <a href="#">Deadline</a>         |                      | 0 / 2 | false | Payment deadline, absolute or relative.                                                                                         |
| <a href="#">Description</a>      | ParagraphType        | 0 / 5 | false | Text description of the Payment in a given language.                                                                            |
| <a href="#">Address</a>          |                      | 0 / 3 | false | The address to which a deposit may be sent.                                                                                     |
| <a href="#">TPA_Extensions</a>   | TPA_ExtensionsType   | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

#### Attributes

| Name                          | Type                             | Use      | Value | Description                                                                                                                                                             |
|-------------------------------|----------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PaymentCode                   | <a href="#">StringLength1to8</a> | required |       | This defines the form of payment. Recommended usage of this is with the 31 for guarantee 8 for Deposit                                                                  |
| <a href="#">GuaranteeType</a> |                                  | optional |       | For a guarantee required: PaymentCode=31 and guarantee type="GuaranteeRequired" For a deposit required: PaymentCode=8 and guarantee type="Deposit" or "DepositRequired" |
| HoldTime                      | xs:time                          | optional |       | The room will held up until this time without a guarantee.                                                                                                              |
| Mon                           | xs:boolean                       | optional |       | When true, apply to Monday.                                                                                                                                             |
| Tue                           | xs:boolean                       | optional |       | When true, apply to Tuesday.                                                                                                                                            |

|                        |                                          |          |  |                                                                                                                                                                  |
|------------------------|------------------------------------------|----------|--|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Weds                   | xs:boolean                               | optional |  | When true, apply to Wednesday.                                                                                                                                   |
| Thur                   | xs:boolean                               | optional |  | When true, apply to Thursday.                                                                                                                                    |
| Fri                    | xs:boolean                               | optional |  | When true, apply to Friday.                                                                                                                                      |
| Sat                    | xs:boolean                               | optional |  | When true, apply to Saturday.                                                                                                                                    |
| Sun                    | xs:boolean                               | optional |  | When true, apply to Sunday.                                                                                                                                      |
| Start                  | <a href="#">DateOrTimeOrDateTimeType</a> | optional |  | The starting value of the time span.                                                                                                                             |
| Duration               | <a href="#">DurationType</a>             | optional |  | The duration datatype represents a combination of year, month, day and time values representing a single duration of time, encoded as a single string.           |
| End                    | <a href="#">DateOrTimeOrDateTimeType</a> | optional |  | The ending value of the time span.                                                                                                                               |
| NonRefundableIndicator | xs:boolean                               | optional |  | When true, indicates that any prepayment for the reservation is non refundable, therefore a 100% penalty on the prepayment is applied, irrespective of deadline. |
| PolicyCode             | <a href="#">StringLength1to16</a>        | optional |  | Used to specify the type of payment policy.                                                                                                                      |

Attribute: GuaranteeType

Variety: atomic

Base: [StringLength1to32](#)

Documentation:

| Enumeration       | description                                                                |
|-------------------|----------------------------------------------------------------------------|
| GuaranteeRequired |                                                                            |
| None              |                                                                            |
| CC/DC/Voucher     |                                                                            |
| Profile           |                                                                            |
| Deposit           |                                                                            |
| PrePay            | Indicates prepayment, typically this means payment is required at booking. |

### 1.1.4.1.3.1.1.1.3.1.1. AcceptedPayments

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/

AcceptedPayments

#### Format Description

| Name             | Type                 | Occ   | Nil   | Description                                          |
|------------------|----------------------|-------|-------|------------------------------------------------------|
| AcceptedPayments | AcceptedPaymentsType | 0 / 1 | false | Collection of forms of payment accepted for payment. |

## Elements

| Name                            | Type            | Occ               | Nil   | Description                    |
|---------------------------------|-----------------|-------------------|-------|--------------------------------|
| <i>sequence</i>                 |                 | 1 / 1             |       |                                |
| <a href="#">AcceptedPayment</a> | PaymentFormType | 1 / unbound<br>ed | false | An acceptable form of payment. |

### 1.1.4.1.3.1.1.1.3.1.1.1. AcceptedPayment

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/  
AcceptedPayments/AcceptedPayment

## Format Description

| Name            | Type            | Occ               | Nil   | Description                    |
|-----------------|-----------------|-------------------|-------|--------------------------------|
| AcceptedPayment | PaymentFormType | 1 / unbound<br>ed | false | An acceptable form of payment. |

## Elements

| Name                              | Type            | Occ   | Nil   | Description                                                                    |
|-----------------------------------|-----------------|-------|-------|--------------------------------------------------------------------------------|
| <i>choice</i>                     |                 | 0 / 1 |       |                                                                                |
| <a href="#">PaymentCard</a>       | PaymentCardType | 1 / 1 | false | Details of a debit or credit card.                                             |
| <a href="#">BankAcct</a>          | BankAcctType    | 1 / 1 | false | Details of a bank account.                                                     |
| <a href="#">DirectBill</a>        | DirectBillType  | 1 / 1 | false | Details of a direct billing arrangement.                                       |
| <a href="#">Voucher</a>           |                 | 1 / 1 | false |                                                                                |
| <a href="#">LoyaltyRedemption</a> |                 | 1 / 1 | false | Details of a loyalty redemption arrangement. This is normally miles or points. |
| <a href="#">MiscChargeOrder</a>   |                 | 1 / 1 | false | Details of a miscellaneous charge order (MCO).                                 |
| <a href="#">Ticket</a>            |                 | 1 / 1 | false | Details of a ticket to be exchanged.                                           |
| <a href="#">Cash</a>              |                 | 1 / 1 | false | Used to indicate payment in cash.                                              |

## Attributes

| Name   | Type                               | Use      | Value | Description                                |
|--------|------------------------------------|----------|-------|--------------------------------------------|
| Remark | <a href="#">StringLength1to128</a> | optional |       | A remark associated with the payment form. |

### 1.1.4.1.3.1.1.1.3.1.1.1.1. PaymentCard

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/  
AcceptedPayments/AcceptedPayment/PaymentCard

### Format Description

| Name        | Type            | Occ   | Nil   | Description                        |
|-------------|-----------------|-------|-------|------------------------------------|
| PaymentCard | PaymentCardType | 1 / 1 | false | Details of a debit or credit card. |

### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

### Attributes

| Name     | Type                                | Use      | Value | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------|-------------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CardCode | <a href="#">PaymentCardCodeType</a> | optional |       | The 2 character code of the credit card issuer.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Remark   | <a href="#">StringLength1to128</a>  | optional |       | <p>In case of Leisure/MultiSource:<br/>A remark associated with this payment card</p> <p>For Transhotel:</p> <ul style="list-style-type: none"> <li>• "TravelAgent Immediate" if the payment is done immediately by the TA</li> <li>• "TravelAgent Delayed" if the payment is not done immediately by the TA</li> <li>• "Customer Immediate" if the payment is done immediately by the customer</li> <li>• "Customer Delayed" if the payment is not done immediately by the customer</li> <li>• "CreditLine" if the payment is done with a credit line</li> </ul> |

### 1.1.4.1.3.1.1.1.3.1.1.2. BankAcct

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/  
AcceptedPayments/AcceptedPayment/BankAcct

### Format Description

| Name     | Type         | Occ   | Nil   | Description                |
|----------|--------------|-------|-------|----------------------------|
| BankAcct | BankAcctType | 1 / 1 | false | Details of a bank account. |

### Elements

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|          |  |       |  |  |
|----------|--|-------|--|--|
| sequence |  | 1 / 1 |  |  |
|----------|--|-------|--|--|

### Attributes

| Name              | Type       | Use      | Value | Description                                                      |
|-------------------|------------|----------|-------|------------------------------------------------------------------|
| ChecksAcceptedInd | xs:boolean | optional |       | If true, checks are accepted. If false, checks are not accepted. |

### 1.1.4.1.3.1.1.1.3.1.1.1.3. DirectBill

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/AcceptedPayments/AcceptedPayment/DirectBill

### Format Description

| Name       | Type           | Occ   | Nil   | Description                              |
|------------|----------------|-------|-------|------------------------------------------|
| DirectBill | DirectBillType | 1 / 1 | false | Details of a direct billing arrangement. |

### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

### 1.1.4.1.3.1.1.1.3.1.1.1.4. Voucher

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/AcceptedPayments/AcceptedPayment/Voucher

### Format Description

| Name    | Type | Occ   | Nil   | Description |
|---------|------|-------|-------|-------------|
| Voucher |      | 1 / 1 | false |             |

### Attributes

| Name                         | Type       | Use      | Value | Description                                                                                                                                                    |
|------------------------------|------------|----------|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EffectiveDate                | xs:date    | optional |       | Indicates the starting date.                                                                                                                                   |
| ExpireDate                   | xs:date    | optional |       | Indicates the ending date.                                                                                                                                     |
| ExpireDateExclusiveIndicator | xs:boolean | optional |       | When true, indicates that the ExpireDate is the first day after the applicable period (e.g. when expire date is Oct 15 the last date of the period is Oct 14). |

|                     |                                   |          |  |                                                                                                                                                                                                                                             |
|---------------------|-----------------------------------|----------|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SeriesCode          | <a href="#">StringLength1to32</a> | optional |  | Identification of a series of coupons or vouchers identified by serial number(s).                                                                                                                                                           |
| BillingNumber       | <a href="#">StringLength1to64</a> | optional |  | Reference of the billing account which handles the payment transaction.                                                                                                                                                                     |
| SupplierIdentifier  | <a href="#">StringLength1to64</a> | optional |  | Unique identifier of the electronic voucher, created by the supplier.                                                                                                                                                                       |
| Identifier          | <a href="#">StringLength1to64</a> | optional |  | Unique identifier of the electronic voucher.                                                                                                                                                                                                |
| ValueType           | <a href="#">StringLength1to32</a> | optional |  | Defines the type of voucher (e.g., full credit or partial credit).                                                                                                                                                                          |
| ElectronicIndicator | xs:boolean                        | optional |  | When true, indicates the voucher is electronic. An E-voucher is a value document issued by the Travel Agent for the customer. The e-voucher can be used as a proof of reservation, but more normally, as a full-payment or partial payment. |

### 1.1.4.1.3.1.1.1.3.1.1.1.5. **LoyaltyRedemption**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/AcceptedPayments/AcceptedPayment/LoyaltyRedemption

#### Format Description

| Name              | Type | Occ   | Nil   | Description                                                                    |
|-------------------|------|-------|-------|--------------------------------------------------------------------------------|
| LoyaltyRedemption |      | 1 / 1 | false | Details of a loyalty redemption arrangement. This is normally miles or points. |

#### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

### 1.1.4.1.3.1.1.1.3.1.1.1.6. **MiscChargeOrder**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/AcceptedPayments/AcceptedPayment/MiscChargeOrder

#### Format Description

| Name            | Type | Occ   | Nil   | Description                                    |
|-----------------|------|-------|-------|------------------------------------------------|
| MiscChargeOrder |      | 1 / 1 | false | Details of a miscellaneous charge order (MCO). |

### 1.1.4.1.3.1.1.1.3.1.1.1.7. **Ticket**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/



AcceptedPayments/AcceptedPayment/Ticket

### Format Description

| Name   | Type | Occ   | Nil   | Description                          |
|--------|------|-------|-------|--------------------------------------|
| Ticket |      | 1 / 1 | false | Details of a ticket to be exchanged. |

### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

## 1.1.4.1.3.1.1.1.3.1.1.1.8. Cash

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/

AcceptedPayments/AcceptedPayment/Cash

### Format Description

| Name | Type | Occ   | Nil   | Description                       |
|------|------|-------|-------|-----------------------------------|
| Cash |      | 1 / 1 | false | Used to indicate payment in cash. |

### Attributes

| Name          | Type       | Use      | Value | Description                                 |
|---------------|------------|----------|-------|---------------------------------------------|
| CashIndicator | xs:boolean | required |       | If true, this indicates cash is being used. |

## 1.1.4.1.3.1.1.1.3.1.2. AmountPercent

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/

AmountPercent

### Format Description

| Name          | Type              | Occ   | Nil   | Description                                                             |
|---------------|-------------------|-------|-------|-------------------------------------------------------------------------|
| AmountPercent | AmountPercentType | 0 / 1 | false | Payment expressed as a fixed amount, or a percentage of/or room nights. |

## Elements

| Name                  | Type      | Occ   | Nil   | Description            |
|-----------------------|-----------|-------|-------|------------------------|
| <i>sequence</i>       |           | 1 / 1 |       |                        |
| <a href="#">Taxes</a> | TaxesType | 0 / 1 | false | A collection of taxes. |

## Attributes

| Name                      | Type                         | Use      | Value | Description                                                                                                                           |
|---------------------------|------------------------------|----------|-------|---------------------------------------------------------------------------------------------------------------------------------------|
| TaxInclusive              | xs:boolean                   | optional |       | Indicates whether taxes are included when figuring the base amount.                                                                   |
| FeesInclusive             | xs:boolean                   | optional |       | Indicates whether fees, such as those imposed by a travel agency or other booking agent, are included when figuring cancel penalties. |
| NmbrOfNights              | xs:nonNegativeInteger        | optional |       | The number of nights of the hotel stay that are used to calculate the fee amount.                                                     |
| <a href="#">BasisType</a> |                              | optional |       | Provides the basis for how the amount of the guarantee is calculated.                                                                 |
| Percent                   | <a href="#">Percentage</a>   | optional |       | The percentage used to calculate the amount.                                                                                          |
| Amount                    | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                                                                    |
| CurrencyCode              | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                  |
| DecimalPlaces             | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                        |
| <a href="#">ApplyAs</a>   |                              | optional |       | Used to specify how the amount needs to be applied with respect to the stay.                                                          |
| OverriddenAmountIndicator | xs:boolean                   | optional |       | When true, indicates that the amount has been overridden.                                                                             |

### Attribute: BasisType

Variety: atomic

Base: [StringLength1to16](#)

Documentation:

| Enumeration | description                                 |
|-------------|---------------------------------------------|
| FullStay    | Uses the full stay as the basis.            |
| Nights      | Uses the nights as the basis.               |
| FirstLast   | Uses the first and last night as the basis. |

Attribute: ApplyAs

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration              | description                                                      |
|--------------------------|------------------------------------------------------------------|
| FirstNightDeposit        | Amount to be applied as a deposit for the first night.           |
| LastNightDeposit         | Amount to be applied as a deposit for the last night.            |
| FirstAndLastNightDeposit | Amount to be applied as a deposit for the first and last nights. |
| FirstNightPayment        | Amount to be applied as payment for the first night.             |
| LastNightPayment         | Amount to be applied as payment for the last night.              |
| FirstAndLastNightPayment | Amount to be applied as payment for the first and last nights.   |

### 1.1.4.1.3.1.1.1.3.1.2.1. Taxes

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/AmountPercent/Taxes

#### Format Description

| Name  | Type      | Occ   | Nil   | Description            |
|-------|-----------|-------|-------|------------------------|
| Taxes | TaxesType | 0 / 1 | false | A collection of taxes. |

#### Elements

| Name                | Type    | Occ    | Nil   | Description        |
|---------------------|---------|--------|-------|--------------------|
| <i>sequence</i>     |         | 1 / 1  |       |                    |
| <a href="#">Tax</a> | TaxType | 0 / 99 | false | An individual tax. |

#### Attributes

| Name          | Type                         | Use      | Value | Description                                                                                    |
|---------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| Amount        | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                             |
| CurrencyCode  | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.3.1.1.1.3.1.2.1.1. Tax

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/  
AmountPercent/Taxes/Tax

#### Format Description

| Name | Type    | Occ    | Nil   | Description        |
|------|---------|--------|-------|--------------------|
| Tax  | TaxType | 0 / 99 | false | An individual tax. |

#### Elements

| Name                           | Type          | Occ   | Nil   | Description                                        |
|--------------------------------|---------------|-------|-------|----------------------------------------------------|
| sequence                       |               | 1 / 1 |       |                                                    |
| <a href="#">TaxDescription</a> | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

#### Attributes

| Name                         | Type                                    | Use      | Value | Description                                                                                                                                                      |
|------------------------------|-----------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                         | <a href="#">AmountDeterminationType</a> | optional |       | Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).              |
| Code                         | <a href="#">OTA_CodeType</a>            | optional |       | Code identifying the fee (e.g., agency fee, municipality fee). Refer to OpenTravel Code List Fee Tax Type (FTT).                                                 |
| Percent                      | <a href="#">Percentage</a>              | optional |       | Fee percentage; if zero, assume use of the Amount attribute (Amount or Percent must be a zero value).                                                            |
| Amount                       | <a href="#">Money</a>                   | optional |       | A monetary amount.                                                                                                                                               |
| CurrencyCode                 | <a href="#">AlphaLength3</a>            | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                             |
| DecimalPlaces                | xs:nonNegativeInteger                   | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                   |
| EffectiveDate                | xs:date                                 | optional |       | Indicates the starting date.                                                                                                                                     |
| ExpireDate                   | xs:date                                 | optional |       | Indicates the ending date.                                                                                                                                       |
| ExpireDateExclusiveIndicator | xs:boolean                              | optional |       | When true, indicates that the ExpireDate is the first day after the applicable period (e.g. when expire date is Oct 15 the last date of the period is Oct 14).   |
| ChargeUnit                   | <a href="#">OTA_CodeType</a>            | optional |       | This is the unit for which the charge applies (e.g. room, person, seat). Refer to OpenTravel Code List Charge Type (CHG).                                        |
| ChargeFrequency              | <a href="#">OTA_CodeType</a>            | optional |       | This is the timeframe used to apply the charge during the course of the reservation (e.g. Daily, Weekly, Stay). Refer to OpenTravel Code List Charge Type (CHG). |
| ChargeUnitExempt             | xs:positiveInteger                      | optional |       | Number of units permitted before charges are applied (e.g., more than 4 persons).                                                                                |

|                           |                    |          |  |                                                                                                    |
|---------------------------|--------------------|----------|--|----------------------------------------------------------------------------------------------------|
| ChargeFrequencyExempt     | xs:positiveInteger | optional |  | ChargeFrequency exemptions before charges are applied (e.g. after 2 nights).                       |
| MaxChargeUnitApplies      | xs:positiveInteger | optional |  | Maximum number of Units for which the charge will be applied (e.g., waive charges above 10 rooms). |
| MaxChargeFrequencyApplies | xs:positiveInteger | optional |  | Maximum number of times the charge will be applied (e.g. waive charges above 30 nights).           |

### 1.1.4.1.3.1.1.1.3.1.2.1.1.1. TaxDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/AmountPercent/Taxes/Tax/TaxDescription

#### Format Description

| Name           | Type          | Occ   | Nil   | Description                                        |
|----------------|---------------|-------|-------|----------------------------------------------------|
| TaxDescription | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

#### Elements

| Name                     | Type              | Occ         | Nil   | Description                                                       |
|--------------------------|-------------------|-------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbound |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1       | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1       | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1       | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1       | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                        |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name               | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber    | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime     | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID          | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |
| LastModifyDateTime | xs:dateTime                       | optional |       | Time stamp of last modification.                                                                                                                                                   |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |       | Identifies the last software system or person to modify a record.                                                                                                                  |

|           |             |          |  |                                                                                         |
|-----------|-------------|----------|--|-----------------------------------------------------------------------------------------|
| PurgeDate | xs:date     | optional |  | Date an item will be purged from a database (e.g., from a live database to an archive). |
| Language  | xs:language | optional |  | Language identification.                                                                |

### 1.1.4.1.3.1.1.1.3.1.2.1.1.1.1. **Text**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/  
AmountPercent/Taxes/Tax/TaxDescription/Text

#### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.3.1.2.1.1.1.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/  
AmountPercent/Taxes/Tax/TaxDescription/ListItem

### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.4.1.3.1.1.1.3.1.3. Deadline

XPath: [:/OTA\\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Deadline](#)

### Format Description

| Name     | Type | Occ   | Nil   | Description                             |
|----------|------|-------|-------|-----------------------------------------|
| Deadline |      | 0 / 2 | false | Payment deadline, absolute or relative. |

### Attributes

| Name | Type | Use | Value | Description |
|------|------|-----|-------|-------------|
|------|------|-----|-------|-------------|

|                                |                                    |          |  |                                                                                  |
|--------------------------------|------------------------------------|----------|--|----------------------------------------------------------------------------------|
| AbsoluteDeadline               | <a href="#">TimeOrDateTimeType</a> | optional |  | Defines the absolute deadline. Either this or the offset attributes may be used. |
| OffsetTimeUnit                 | <a href="#">TimeUnitType</a>       | optional |  | The units of time, e.g.: days, hours, etc., that apply to the deadline.          |
| OffsetUnitMultiplier           | <a href="#">Numeric0to999</a>      | optional |  | The number of units of DeadlineTimeUnit.                                         |
| <a href="#">OffsetDropTime</a> |                                    | optional |  | An enumerated type indicating when the deadline drop time goes into effect.      |
| OverrideIndicator              | xs:boolean                         | optional |  | When true, indicates that the deadline has been overridden.                      |

Attribute: OffsetDropTime

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration       | description                                                                                                                                        |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| BeforeArrival     |                                                                                                                                                    |
| AfterBooking      |                                                                                                                                                    |
| AfterConfirmation | The deadline information applies from when the reservation was confirmed. In some systems the confirmation time will differ from the booking time. |
| AfterArrival      | The deadline applies after the scheduled arrival time.                                                                                             |

### 1.1.4.1.3.1.1.1.3.1.4. Description

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Description

#### Format Description

| Name        | Type          | Occ   | Nil   | Description                                          |
|-------------|---------------|-------|-------|------------------------------------------------------|
| Description | ParagraphType | 0 / 5 | false | Text description of the Payment in a given language. |

#### Elements

| Name                 | Type              | Occ           | Nil   | Description                  |
|----------------------|-------------------|---------------|-------|------------------------------|
| choice               |                   | 0 / unbounded |       |                              |
| <a href="#">Text</a> | FormattedTextType | 1 / 1         | false | Formatted text content.      |
| Image                | xs:string         | 1 / 1         | false | An image for this paragraph. |
| URL                  | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.    |



|                          |  |       |       |                                                                   |
|--------------------------|--|-------|-------|-------------------------------------------------------------------|
| <a href="#">ListItem</a> |  | 1 / 1 | false | Formatted text content and an associated item or sequence number. |
|--------------------------|--|-------|-------|-------------------------------------------------------------------|

## Attributes

| Name            | Type                              | Use      | Value | Description                                                                                                                                                                        |
|-----------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name            | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |

### 1.1.4.1.3.1.1.1.3.1.4.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Description/  
Text

## Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.3.1.4.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Description/  
ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.3.1.5. Address

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Address

#### Format Description

| Name    | Type            | Occ   | Nil   | Description                                 |
|---------|-----------------|-------|-------|---------------------------------------------|
| Address | AddressInfoType | 0 / 3 | false | The address to which a deposit may be sent. |

## Elements

| Name                        | Type                               | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                                   |
|-----------------------------|------------------------------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>             |                                    | 1 / 1 |       |                                                                                                                                                                                                                                                                                                                               |
| <a href="#">StreetNmbr</a>  |                                    | 0 / 1 | false | May contain the street number and optionally the street name.                                                                                                                                                                                                                                                                 |
| <a href="#">AddressLine</a> | <a href="#">StringLength1to255</a> | 0 / 5 | false | When the address is unformatted (FormattedInd="false") these lines will contain free form address details. When the address is formatted and street number and street name must be sent independently, the street number will be sent using StreetNmbr, and the street name will be sent in the first AddressLine occurrence. |
| <a href="#">CityName</a>    | <a href="#">StringLength1to64</a>  | 0 / 1 | false | City (e.g., Dublin), town, or postal station (i.e., a postal service territory, often used in a military address).                                                                                                                                                                                                            |
| <a href="#">PostalCode</a>  | <a href="#">StringLength1to16</a>  | 0 / 1 | false | Post Office Code number.                                                                                                                                                                                                                                                                                                      |
| <a href="#">County</a>      | <a href="#">StringLength1to32</a>  | 0 / 1 | false | County or Region Name (e.g., Fairfax).                                                                                                                                                                                                                                                                                        |
| <a href="#">StateProv</a>   | StateProvType                      | 0 / 1 | false | State or Province name (e.g., Texas).                                                                                                                                                                                                                                                                                         |
| <a href="#">CountryName</a> | CountryNameType                    | 0 / 1 | false | Country name (e.g., Ireland).                                                                                                                                                                                                                                                                                                 |

## Attributes

| Name          | Type                              | Use      | Value | Description                                                                                                                     |
|---------------|-----------------------------------|----------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| FormattedInd  | xs:boolean                        | optional |       | Specifies if the associated data is formatted or not. When true, then it is formatted; when false, then not formatted.          |
| Type          | <a href="#">OTA_CodeType</a>      | optional |       | Defines the type of address (e.g. home, business, other). Refer to OpenTravel Code List Communication Location Type (CLT).      |
| UseType       | <a href="#">OTA_CodeType</a>      | optional |       | Describes the use of the address (e.g. mailing, delivery, billing, etc.). Refer to OpenTravel Code List Address Use Type (AUT). |
| AddresseeName | <a href="#">StringLength1to64</a> | optional |       | The name of the reciever of the payment.                                                                                        |

### 1.1.4.1.3.1.1.1.3.1.5.1. StreetNmbr

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Address/StreetNmbr

## Format Description

| Name       | Type                              | Occ   | Nil   | Description                                                   |
|------------|-----------------------------------|-------|-------|---------------------------------------------------------------|
| StreetNmbr | <a href="#">StringLength0to64</a> | 0 / 1 | false | May contain the street number and optionally the street name. |

## Attributes

| Name             | Type                                    | Use      | Value | Description                                                                             |
|------------------|-----------------------------------------|----------|-------|-----------------------------------------------------------------------------------------|
| PO_Box           | <a href="#">StringLength1to16</a>       | optional |       | Defines a Post Office Box number.                                                       |
| StreetNmbrSuffix | <a href="#">StringLength1to8</a>        | optional |       | Usually a letter right after the street number (A in 66-A, B in 123-B etc).             |
| StreetDirection  | <a href="#">StringLength1to8</a>        | optional |       | Street direction of an address (e.g., N, E, S, NW, SW).                                 |
| RuralRouteNmbr   | <a href="#">NumericStringLength1to5</a> | optional |       | Numerical equivalent of a rural township as defined within a given area (e.g., 12, 99). |

### 1.1.4.1.3.1.1.1.3.1.5.2. AddressLine

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Address/AddressLine

#### Format Description

| Name        | Type                               | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                                   |
|-------------|------------------------------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AddressLine | <a href="#">StringLength1to255</a> | 0 / 5 | false | When the address is unformatted (FormattedInd="false") these lines will contain free form address details. When the address is formatted and street number and street name must be sent independently, the street number will be sent using StreetNmbr, and the street name will be sent in the first AddressLine occurrence. |

### 1.1.4.1.3.1.1.1.3.1.5.3. CityName

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Address/CityName

#### Format Description

| Name     | Type                              | Occ   | Nil   | Description                                                                                                        |
|----------|-----------------------------------|-------|-------|--------------------------------------------------------------------------------------------------------------------|
| CityName | <a href="#">StringLength1to64</a> | 0 / 1 | false | City (e.g., Dublin), town, or postal station (i.e., a postal service territory, often used in a military address). |

### 1.1.4.1.3.1.1.1.3.1.5.4. PostalCode

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Address/PostalCode

#### Format Description

| Name       | Type                              | Occ   | Nil   | Description              |
|------------|-----------------------------------|-------|-------|--------------------------|
| PostalCode | <a href="#">StringLength1to16</a> | 0 / 1 | false | Post Office Code number. |

### 1.1.4.1.3.1.1.1.3.1.5.5. **County**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Address/

County

#### *Format Description*

| Name   | Type                              | Occ   | Nil   | Description                            |
|--------|-----------------------------------|-------|-------|----------------------------------------|
| County | <a href="#">StringLength1to32</a> | 0 / 1 | false | County or Region Name (e.g., Fairfax). |

### 1.1.4.1.3.1.1.1.3.1.5.6. **StateProv**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Address/

StateProv

#### *Format Description*

| Name      | Type                              | Occ   | Nil   | Description                           |
|-----------|-----------------------------------|-------|-------|---------------------------------------|
| StateProv | <a href="#">StringLength0to64</a> | 0 / 1 | false | State or Province name (e.g., Texas). |

#### *Attributes*

| Name      | Type                              | Use      | Value | Description                                                           |
|-----------|-----------------------------------|----------|-------|-----------------------------------------------------------------------|
| StateCode | <a href="#">StateProvCodeType</a> | optional |       | The standard code or abbreviation for the state, province, or region. |

### 1.1.4.1.3.1.1.1.3.1.5.7. **CountryName**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/Address/

CountryName

#### *Format Description*

| Name        | Type                              | Occ   | Nil   | Description                   |
|-------------|-----------------------------------|-------|-------|-------------------------------|
| CountryName | <a href="#">StringLength0to64</a> | 0 / 1 | false | Country name (e.g., Ireland). |

## Attributes

| Name | Type                    | Use      | Value | Description                  |
|------|-------------------------|----------|-------|------------------------------|
| Code | <a href="#">ISO3166</a> | optional |       | ISO 3166 code for a country. |

### 1.1.4.1.3.1.1.1.3.1.6. TPA\_Extensions

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/PaymentPolicies/GuaranteePayment/

TPA\_Extensions

## Format Description

| Name           | Type               | Occ   | Nil   | Description                                                                                                                     |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| TPA_Extensions | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

## Elements

| Name     | Type | Occ               | Nil | Description |
|----------|------|-------------------|-----|-------------|
| sequence |      | 1 / 1             |     |             |
| any      |      | 0 / unbound<br>ed |     |             |

### 1.1.4.1.3.1.1.1.4. Total

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Total

## Format Description

| Name  | Type      | Occ   | Nil   | Description                                                                                                                                                                                                    |
|-------|-----------|-------|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Total | TotalType | 0 / 1 | false | Total amount of 1 room. Sent only if several rooms are requested in the room rate. In the case of NH, this is an intermediate total including the taxes payable online, but not the taxes payable at the hotel |

## Elements

| Name                  | Type      | Occ   | Nil   | Description            |
|-----------------------|-----------|-------|-------|------------------------|
| sequence              |           | 1 / 1 |       |                        |
| <a href="#">Taxes</a> | TaxesType | 0 / 1 | false | A collection of taxes. |

## Attributes

| Name                            | Type                         | Use      | Value | Description                                                                                                                                                                                                                                     |
|---------------------------------|------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AmountBeforeTax                 | <a href="#">Money</a>        | optional |       | Total amount of the room taxes excluded. At least AmountBeforeTax or AmountAfterTax is compulsory, but both cannot be sent at the same time.                                                                                                    |
| AmountAfterTax                  | <a href="#">Money</a>        | optional |       | Total Amount of the room taxes included. At least AmountBeforeTax or AmountAfterTax is compulsory, but both cannot be sent at the same time. In the case of NH, this is the total payable online, not including the taxes payable at the hotel. |
| CurrencyCode                    | <a href="#">AlphaLength3</a> | required |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                                                                                                            |
| DecimalPlaces                   | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                                                                                                  |
| AdditionalFeesExcludedIndicator | xs:boolean                   | optional |       | When true, amounts do not contain additional fees or charges.                                                                                                                                                                                   |
| Type                            | <a href="#">OTA_CodeType</a> | optional |       | Type of charge. Refer to OpenTravel Code List Charge Type (CHG).                                                                                                                                                                                |

## 1.1.4.1.3.1.1.1.4.1. Taxes

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Total/Taxes

## Format Description

| Name  | Type      | Occ   | Nil   | Description            |
|-------|-----------|-------|-------|------------------------|
| Taxes | TaxesType | 0 / 1 | false | A collection of taxes. |

## Elements

| Name                | Type    | Occ    | Nil   | Description        |
|---------------------|---------|--------|-------|--------------------|
| <i>sequence</i>     |         | 1 / 1  |       |                    |
| <a href="#">Tax</a> | TaxType | 0 / 99 | false | An individual tax. |

## Attributes

| Name          | Type                         | Use      | Value | Description                                                                                    |
|---------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| Amount        | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                             |
| CurrencyCode  | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.3.1.1.1.4.1.1. Tax

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Total/Taxes/Tax

#### Format Description

| Name | Type    | Occ    | Nil   | Description        |
|------|---------|--------|-------|--------------------|
| Tax  | TaxType | 0 / 99 | false | An individual tax. |

#### Elements

| Name                           | Type          | Occ   | Nil   | Description                                        |
|--------------------------------|---------------|-------|-------|----------------------------------------------------|
| sequence                       |               | 1 / 1 |       |                                                    |
| <a href="#">TaxDescription</a> | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

#### Attributes

| Name                         | Type                                    | Use      | Value | Description                                                                                                                                                      |
|------------------------------|-----------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                         | <a href="#">AmountDeterminationType</a> | optional |       | Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).              |
| Code                         | <a href="#">OTA_CodeType</a>            | required |       | Code identifying the fee (e.g., agency fee, municipality fee). Refer to OpenTravel Code List Fee Tax Type (FTT).                                                 |
| Percent                      | <a href="#">Percentage</a>              | optional |       | Fee percentage; if zero, assume use of the Amount attribute (Amount or Percent must be a zero value).                                                            |
| Amount                       | <a href="#">Money</a>                   | optional |       | A monetary amount.                                                                                                                                               |
| CurrencyCode                 | <a href="#">AlphaLength3</a>            | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                             |
| DecimalPlaces                | xs:nonNegativeInteger                   | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                   |
| EffectiveDate                | xs:date                                 | optional |       | Indicates the starting date.                                                                                                                                     |
| ExpireDate                   | xs:date                                 | optional |       | Indicates the ending date.                                                                                                                                       |
| ExpireDateExclusiveIndicator | xs:boolean                              | optional |       | When true, indicates that the ExpireDate is the first day after the applicable period (e.g. when expire date is Oct 15 the last date of the period is Oct 14).   |
| ChargeUnit                   | <a href="#">OTA_CodeType</a>            | optional |       | This is the unit for which the charge applies (e.g. room, person, seat). Refer to OpenTravel Code List Charge Type (CHG).                                        |
| ChargeFrequency              | <a href="#">OTA_CodeType</a>            | optional |       | This is the timeframe used to apply the charge during the course of the reservation (e.g. Daily, Weekly, Stay). Refer to OpenTravel Code List Charge Type (CHG). |
| ChargeUnitExempt             | xs:positiveInteger                      | optional |       | Number of units permitted before charges are applied (e.g., more than 4 persons).                                                                                |
| ChargeFrequencyExempt        | xs:positiveInteger                      | optional |       | ChargeFrequency exemptions before charges are applied (e.g. after 2 nights).                                                                                     |



|                           |                    |          |  |                                                                                                    |
|---------------------------|--------------------|----------|--|----------------------------------------------------------------------------------------------------|
| MaxChargeUnitApplies      | xs:positiveInteger | optional |  | Maximum number of Units for which the charge will be applied (e.g., waive charges above 10 rooms). |
| MaxChargeFrequencyApplies | xs:positiveInteger | optional |  | Maximum number of times the charge will be applied (e.g. waive charges above 30 nights).           |

### 1.1.4.1.3.1.1.1.4.1.1.1. TaxDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Total/Taxes/Tax/TaxDescription

#### Format Description

| Name           | Type          | Occ   | Nil   | Description                                        |
|----------------|---------------|-------|-------|----------------------------------------------------|
| TaxDescription | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

#### Elements

| Name                     | Type              | Occ           | Nil   | Description                                                       |
|--------------------------|-------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1         | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                        |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name               | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber    | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime     | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID          | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |
| LastModifyDateTime | xs:dateTime                       | optional |       | Time stamp of last modification.                                                                                                                                                   |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |       | Identifies the last software system or person to modify a record.                                                                                                                  |
| PurgeDate          | xs:date                           | optional |       | Date an item will be purged from a database (e.g., from a live database to an archive).                                                                                            |
| Language           | xs:language                       | optional |       | Language identification.                                                                                                                                                           |

### 1.1.4.1.3.1.1.1.4.1.1.1.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Total/Taxes/Tax/TaxDescription/Text

#### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.4.1.1.1.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/Total/Taxes/Tax/TaxDescription/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

### Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.4.1.3.1.1.1.5. RateDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/RateDescription

### Format Description

| Name            | Type          | Occ   | Nil   | Description |
|-----------------|---------------|-------|-------|-------------|
| RateDescription | ParagraphType | 0 / 1 | false |             |

## Elements

| Name                 | Type              | Occ           | Nil   | Description                  |
|----------------------|-------------------|---------------|-------|------------------------------|
| <i>choice</i>        |                   | 0 / unbounded |       |                              |
| <a href="#">Text</a> | FormattedTextType | 1 / 1         | false | Formatted text content.      |
| Image                | xs:string         | 1 / 1         | false | An image for this paragraph. |
| URL                  | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.    |

|                          |  |       |       |                                                                   |
|--------------------------|--|-------|-------|-------------------------------------------------------------------|
| <a href="#">ListItem</a> |  | 1 / 1 | false | Formatted text content and an associated item or sequence number. |
|--------------------------|--|-------|-------|-------------------------------------------------------------------|

### Attributes

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                        |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name               | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber    | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime     | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID          | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |
| LastModifyDateTime | xs:dateTime                       | optional |       | Time stamp of last modification.                                                                                                                                                   |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |       | Identifies the last software system or person to modify a record.                                                                                                                  |
| PurgeDate          | xs:date                           | optional |       | Date an item will be purged from a database (e.g., from a live database to an archive).                                                                                            |
| Language           | xs:language                       | optional |       | Language identification.                                                                                                                                                           |

### 1.1.4.1.3.1.1.1.5.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/RateDescription/Text

### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.5.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/RateDescription/ListItem

#### *Format Description*

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### *Attributes*

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.6. AdditionalCharges

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/AdditionalCharges

#### Format Description

| Name              | Type                       | Occ   | Nil   | Description                       |
|-------------------|----------------------------|-------|-------|-----------------------------------|
| AdditionalCharges | HotelAdditionalChargesType | 0 / 1 | false | Collection of additional charges. |

#### Elements

| Name                             | Type | Occ    | Nil   | Description                                      |
|----------------------------------|------|--------|-------|--------------------------------------------------|
| sequence                         |      | 1 / 1  |       |                                                  |
| <a href="#">AdditionalCharge</a> |      | 1 / 99 | false | Amenities or services to which a charge applies. |

#### Attributes

| Name            | Type                         | Use      | Value | Description                                                                                    |
|-----------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| AmountBeforeTax | <a href="#">Money</a>        | optional |       | Total additional charges before taxes.                                                         |
| AmountAfterTax  | <a href="#">Money</a>        | optional |       | Total additional charges after taxes.                                                          |
| CurrencyCode    | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces   | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.3.1.1.1.6.1. AdditionalCharge

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/AdditionalCharges/AdditionalCharge

#### Format Description

| Name             | Type | Occ    | Nil   | Description                                      |
|------------------|------|--------|-------|--------------------------------------------------|
| AdditionalCharge |      | 1 / 99 | false | Amenities or services to which a charge applies. |

#### Elements

| Name                   | Type      | Occ   | Nil   | Description                                   |
|------------------------|-----------|-------|-------|-----------------------------------------------|
| sequence               |           | 1 / 1 |       |                                               |
| <a href="#">Amount</a> | TotalType | 0 / 1 | false | The amount charged for an amenity or service. |

## Attributes

| Name            | Type                         | Use      | Value | Description                                                                                                              |
|-----------------|------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------|
| RoomAmenityCode | <a href="#">OTA_CodeType</a> | optional |       | Identifies the types of room amenities to which a charge applies. Refer to OpenTravel Code List Room Amenity Type (RMA). |
| Quantity        | xs:nonNegativeInteger        | optional |       | Used to define the quantity for an associated element or attribute.                                                      |

### 1.1.4.1.3.1.1.1.6.1.1. Amount

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/AdditionalCharges/AdditionalCharge/Amount

## Format Description

| Name   | Type      | Occ   | Nil   | Description                                   |
|--------|-----------|-------|-------|-----------------------------------------------|
| Amount | TotalType | 0 / 1 | false | The amount charged for an amenity or service. |

## Elements

| Name                  | Type      | Occ   | Nil   | Description            |
|-----------------------|-----------|-------|-------|------------------------|
| <i>sequence</i>       |           | 1 / 1 |       |                        |
| <a href="#">Taxes</a> | TaxesType | 0 / 1 | false | A collection of taxes. |

## Attributes

| Name                            | Type                         | Use      | Value | Description                                                                                          |
|---------------------------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------------|
| AmountBeforeTax                 | <a href="#">Money</a>        | optional |       | The total amount not including any associated tax (e.g., sales tax, VAT, GST or any associated tax). |
| AmountAfterTax                  | <a href="#">Money</a>        | optional |       | The total amount including all associated taxes (e.g., sales tax, VAT, GST or any associated tax).   |
| CurrencyCode                    | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                 |
| DecimalPlaces                   | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.       |
| AdditionalFeesExcludedIndicator | xs:boolean                   | optional |       | When true, amounts do not contain additional fees or charges.                                        |
| Type                            | <a href="#">OTA_CodeType</a> | optional |       | Type of charge. Refer to OpenTravel Code List Charge Type (CHG).                                     |
| ServiceOverrideIndicator        | xs:boolean                   | optional |       | When true indicates that the service amount has been overridden.                                     |
| RateOverrideIndicator           | xs:boolean                   | optional |       | When true indicates that the rate amount has been overridden.                                        |

|                       |                       |          |  |                                        |
|-----------------------|-----------------------|----------|--|----------------------------------------|
| AmountIncludingMarkup | <a href="#">Money</a> | optional |  | This amount includes markup and taxes. |
|-----------------------|-----------------------|----------|--|----------------------------------------|

### 1.1.4.1.3.1.1.1.6.1.1.1. Taxes

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/AdditionalCharges/AdditionalCharge/Amount/Taxes

#### Format Description

| Name  | Type      | Occ   | Nil   | Description            |
|-------|-----------|-------|-------|------------------------|
| Taxes | TaxesType | 0 / 1 | false | A collection of taxes. |

#### Elements

| Name                | Type    | Occ    | Nil   | Description        |
|---------------------|---------|--------|-------|--------------------|
| sequence            |         | 1 / 1  |       |                    |
| <a href="#">Tax</a> | TaxType | 0 / 99 | false | An individual tax. |

#### Attributes

| Name          | Type                         | Use      | Value | Description                                                                                    |
|---------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| Amount        | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                             |
| CurrencyCode  | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.3.1.1.1.6.1.1.1.1. Tax

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/AdditionalCharges/AdditionalCharge/Amount/Taxes/

Tax

#### Format Description

| Name | Type    | Occ    | Nil   | Description        |
|------|---------|--------|-------|--------------------|
| Tax  | TaxType | 0 / 99 | false | An individual tax. |

#### Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |



|                                |               |       |       |                                                    |
|--------------------------------|---------------|-------|-------|----------------------------------------------------|
| <a href="#">TaxDescription</a> | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |
|--------------------------------|---------------|-------|-------|----------------------------------------------------|

## Attributes

| Name                         | Type                                    | Use      | Value | Description                                                                                                                                                      |
|------------------------------|-----------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type                         | <a href="#">AmountDeterminationType</a> | optional |       | Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).              |
| Code                         | <a href="#">OTA_CodeType</a>            | optional |       | Code identifying the fee (e.g., agency fee, municipality fee). Refer to OpenTravel Code List Fee Tax Type (FTT).                                                 |
| Percent                      | <a href="#">Percentage</a>              | optional |       | Fee percentage; if zero, assume use of the Amount attribute (Amount or Percent must be a zero value).                                                            |
| Amount                       | <a href="#">Money</a>                   | optional |       | A monetary amount.                                                                                                                                               |
| CurrencyCode                 | <a href="#">AlphaLength3</a>            | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                             |
| DecimalPlaces                | xs:nonNegativeInteger                   | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                   |
| EffectiveDate                | xs:date                                 | optional |       | Indicates the starting date.                                                                                                                                     |
| ExpireDate                   | xs:date                                 | optional |       | Indicates the ending date.                                                                                                                                       |
| ExpireDateExclusiveIndicator | xs:boolean                              | optional |       | When true, indicates that the ExpireDate is the first day after the applicable period (e.g. when expire date is Oct 15 the last date of the period is Oct 14).   |
| ChargeUnit                   | <a href="#">OTA_CodeType</a>            | optional |       | This is the unit for which the charge applies (e.g. room, person, seat). Refer to OpenTravel Code List Charge Type (CHG).                                        |
| ChargeFrequency              | <a href="#">OTA_CodeType</a>            | optional |       | This is the timeframe used to apply the charge during the course of the reservation (e.g. Daily, Weekly, Stay). Refer to OpenTravel Code List Charge Type (CHG). |
| ChargeUnitExempt             | xs:positiveInteger                      | optional |       | Number of units permitted before charges are applied (e.g., more than 4 persons).                                                                                |
| ChargeFrequencyExempt        | xs:positiveInteger                      | optional |       | ChargeFrequency exemptions before charges are applied (e.g. after 2 nights).                                                                                     |
| MaxChargeUnitApplies         | xs:positiveInteger                      | optional |       | Maximum number of Units for which the charge will be applied (e.g., waive charges above 10 rooms).                                                               |
| MaxChargeFrequencyApplies    | xs:positiveInteger                      | optional |       | Maximum number of times the charge will be applied (e.g. waive charges above 30 nights).                                                                         |

### 1.1.4.1.3.1.1.1.6.1.1.1.1.1. TaxDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/AdditionalCharges/AdditionalCharge/Amount/Taxes/Tax/TaxDescription

## Format Description

| Name           | Type          | Occ   | Nil   | Description                                        |
|----------------|---------------|-------|-------|----------------------------------------------------|
| TaxDescription | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

### Attributes

| Name                     | Type                  | Occ            | Nil   | Description                                                       |
|--------------------------|-----------------------|----------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                       | 0 / unbound ed |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextTextType | 1 / 1          | false | Formatted text content.                                           |
| Image                    | xs:string             | 1 / 1          | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI             | 1 / 1          | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                       | 1 / 1          | false | Formatted text content and an associated item or sequence number. |

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                        |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name               | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber    | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime     | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID          | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |
| LastModifyDateTime | xs:dateTime                       | optional |       | Time stamp of last modification.                                                                                                                                                   |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |       | Identifies the last software system or person to modify a record.                                                                                                                  |
| PurgeDate          | xs:date                           | optional |       | Date an item will be purged from a database (e.g., from a live database to an archive).                                                                                            |
| Language           | xs:language                       | optional |       | Language identification.                                                                                                                                                           |

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/AdditionalCharges/AdditionalCharge/Amount/Taxes/  
Tax/TaxDescription/Text

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.6.1.1.1.1.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/AdditionalCharges/AdditionalCharge/Amount/Taxes/Tax/TaxDescription/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.1.1.7. TPA\_Extensions

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Rates/Rate/TPA\_Extensions

#### Format Description

| Name           | Type               | Occ   | Nil   | Description                                                                                                                     |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| TPA_Extensions | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

#### Elements

| Name     | Type | Occ               | Nil | Description |
|----------|------|-------------------|-----|-------------|
| sequence |      | 1 / 1             |     |             |
| any      |      | 0 / unbound<br>ed |     |             |

### 1.1.4.1.3.1.2. RoomRateDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/RoomRateDescription

#### Format Description

| Name                | Type          | Occ   | Nil   | Description               |
|---------------------|---------------|-------|-------|---------------------------|
| RoomRateDescription | ParagraphType | 0 / 1 | false | Room and rate description |

## Elements

| Name                     | Type              | Occ           | Nil   | Description                                                       |
|--------------------------|-------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1         | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name      | Type                              | Use      | Value | Description                                                                  |
|-----------|-----------------------------------|----------|-------|------------------------------------------------------------------------------|
| Name      | <a href="#">StringLength1to64</a> | optional |       | Name of the room                                                             |
| CreatorID | <a href="#">StringLength1to32</a> | optional |       | Mandatory in Leisure/MultiSource, to link requested rooms to returned rooms. |

### 1.1.4.1.3.1.2.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/RoomRateDescription/Text

## Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.2.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/RoomRateDescription/ListItem

#### *Format Description*

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### *Attributes*

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.3. Features

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Features

#### Format Description

| Name     | Type | Occ   | Nil   | Description                                                                                                 |
|----------|------|-------|-------|-------------------------------------------------------------------------------------------------------------|
| Features |      | 0 / 1 | false | A collection of features that are made available as part of this specific room and this specific rate plan. |

#### Elements

| Name                    | Type | Occ    | Nil   | Description                                                                                                                                                                                                                                                              |
|-------------------------|------|--------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>         |      | 1 / 1  |       |                                                                                                                                                                                                                                                                          |
| <a href="#">Feature</a> |      | 0 / 99 | false | Allows for the description of any features and/or amenities that are made available as part of this specific room and this specific rate plan, for example, large screen television, video/DVD player in room, room service breakfast, and details about that breakfast. |

### 1.1.4.1.3.1.3.1. Feature

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Features/Feature

#### Format Description

| Name    | Type | Occ    | Nil   | Description                                                                                                                                                                                                                                                              |
|---------|------|--------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Feature |      | 0 / 99 | false | Allows for the description of any features and/or amenities that are made available as part of this specific room and this specific rate plan, for example, large screen television, video/DVD player in room, room service breakfast, and details about that breakfast. |

#### Elements

| Name                        | Type          | Occ   | Nil   | Description |
|-----------------------------|---------------|-------|-------|-------------|
| <i>sequence</i>             |               | 1 / 1 |       |             |
| <a href="#">Description</a> | ParagraphType | 0 / 5 | false |             |

#### Attributes

| Name | Type | Use | Value | Description |
|------|------|-----|-------|-------------|
|------|------|-----|-------|-------------|

|                   |                               |          |  |                                                                                                                     |
|-------------------|-------------------------------|----------|--|---------------------------------------------------------------------------------------------------------------------|
| RoomAmenity       | <a href="#">OTA_CodeType</a>  | required |  | Refer to OpenTravel Code List Room Amenity Type (RMA). Defines a room amenity associated to the rate plan / product |
| Quantity          | <a href="#">Numeric0to999</a> | optional |  | Provides the quantity of the amenity in the room. When zero, the amenity is either unavailable or not allowed.      |
| RoomViewCode      | <a href="#">OTA_CodeType</a>  | optional |  | Specifies the type of view a room has. Refer to OpenTravel Code List Room View Type (RVT).                          |
| AccessibilityCode | <a href="#">OTA_CodeType</a>  | optional |  | A hotel accessibility feature. Please use a value from the OpenTravel Disability Feature Code (PHY) code list.      |

### 1.1.4.1.3.1.3.1.1. Description

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Features/Feature/Description

#### Format Description

| Name        | Type          | Occ   | Nil   | Description |
|-------------|---------------|-------|-------|-------------|
| Description | ParagraphType | 0 / 5 | false |             |

#### Elements

| Name                     | Type              | Occ           | Nil   | Description                                                       |
|--------------------------|-------------------|---------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbounded |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1         | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1         | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1         | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                        |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name               | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber    | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime     | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID          | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |
| LastModifyDateTime | xs:dateTime                       | optional |       | Time stamp of last modification.                                                                                                                                                   |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |       | Identifies the last software system or person to modify a record.                                                                                                                  |



|           |             |          |  |                                                                                         |
|-----------|-------------|----------|--|-----------------------------------------------------------------------------------------|
| PurgeDate | xs:date     | optional |  | Date an item will be purged from a database (e.g., from a live database to an archive). |
| Language  | xs:language | optional |  | Language identification.                                                                |

### 1.1.4.1.3.1.3.1.1.1. **Text**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Features/Feature/Description/Text

#### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.3.1.1.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Features/Feature/Description/ListItem

#### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|          |           |       |       |                                                                   |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |
|----------|-----------|-------|-------|-------------------------------------------------------------------|

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.4.1.3.1.4. Total

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Total

## Format Description

| Name  | Type      | Occ   | Nil   | Description                                          |
|-------|-----------|-------|-------|------------------------------------------------------|
| Total | TotalType | 0 / 1 | false | Total amount of the number of rooms of the room rate |

## Elements

| Name                  | Type      | Occ   | Nil   | Description            |
|-----------------------|-----------|-------|-------|------------------------|
| sequence              |           | 1 / 1 |       |                        |
| <a href="#">Taxes</a> | TaxesType | 0 / 1 | false | A collection of taxes. |

## Attributes

| Name                            | Type                         | Use      | Value | Description                                                                                                                                  |
|---------------------------------|------------------------------|----------|-------|----------------------------------------------------------------------------------------------------------------------------------------------|
| AmountBeforeTax                 | <a href="#">Money</a>        | optional |       | Total amount of the room taxes excluded At least AmountBeforeTax or AmountAfterTax is compulsory, but both can not be sent at the same time. |
| AmountAfterTax                  | <a href="#">Money</a>        | optional |       | Total amount of the room taxes excluded At least AmountBeforeTax or AmountAfterTax is compulsory, but both can not be sent at the same time. |
| CurrencyCode                    | <a href="#">AlphaLength3</a> | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                         |
| DecimalPlaces                   | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                               |
| AdditionalFeesExcludedIndicator | xs:boolean                   | optional |       | When true, amounts do not contain additional fees or charges.                                                                                |
| Type                            | <a href="#">OTA_CodeType</a> | optional |       | Type of charge. Refer to OpenTravel Code List Charge Type (CHG).                                                                             |

### 1.1.4.1.3.1.4.1. Taxes

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Total/Taxes

## Format Description

| Name  | Type      | Occ   | Nil   | Description            |
|-------|-----------|-------|-------|------------------------|
| Taxes | TaxesType | 0 / 1 | false | A collection of taxes. |

## Elements

| Name                | Type    | Occ    | Nil   | Description        |
|---------------------|---------|--------|-------|--------------------|
| <i>sequence</i>     |         | 1 / 1  |       |                    |
| <a href="#">Tax</a> | TaxType | 0 / 99 | false | An individual tax. |

## Attributes

| Name          | Type                         | Use      | Value | Description                                                                                    |
|---------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| Amount        | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                             |
| CurrencyCode  | <a href="#">AlphaLength3</a> | required |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.3.1.4.1.1. Tax

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Total/Taxes/Tax

#### Format Description

| Name | Type    | Occ    | Nil   | Description        |
|------|---------|--------|-------|--------------------|
| Tax  | TaxType | 0 / 99 | false | An individual tax. |

#### Elements

| Name                           | Type          | Occ   | Nil   | Description                                        |
|--------------------------------|---------------|-------|-------|----------------------------------------------------|
| sequence                       |               | 1 / 1 |       |                                                    |
| <a href="#">TaxDescription</a> | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

#### Attributes

| Name            | Type                                    | Use      | Value | Description                                                                                                                                                      |
|-----------------|-----------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type            | <a href="#">AmountDeterminationType</a> | optional |       | Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).              |
| Code            | <a href="#">OTA_CodeType</a>            | required |       | Code identifying the fee (e.g., agency fee, municipality fee). Refer to OpenTravel Code List Fee Tax Type (FTT).                                                 |
| Percent         | <a href="#">Percentage</a>              | optional |       | Fee percentage; if zero, assume use of the Amount attribute (Amount or Percent must be a zero value).                                                            |
| Amount          | <a href="#">Money</a>                   | optional |       | A monetary amount.                                                                                                                                               |
| CurrencyCode    | <a href="#">AlphaLength3</a>            | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                             |
| DecimalPlaces   | xs:nonNegativeInteger                   | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                   |
| EffectiveDate   | xs:date                                 | optional |       | Indicates the starting date.                                                                                                                                     |
| ExpireDate      | xs:date                                 | optional |       | Indicates the ending date.                                                                                                                                       |
| ChargeUnit      | <a href="#">OTA_CodeType</a>            | optional |       | This is the unit for which the charge applies (e.g. room, person, seat). Refer to OpenTravel Code List Charge Type (CHG).                                        |
| ChargeFrequency | <a href="#">OTA_CodeType</a>            | optional |       | This is the timeframe used to apply the charge during the course of the reservation (e.g. Daily, Weekly, Stay). Refer to OpenTravel Code List Charge Type (CHG). |

### 1.1.4.1.3.1.4.1.1.1. TaxDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Total/Taxes/Tax/TaxDescription

## Elements

| Name           | Type          | Occ   | Nil   | Description                                        |
|----------------|---------------|-------|-------|----------------------------------------------------|
| TaxDescription | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

## Elements

| Name                     | Type                  | Occ            | Nil   | Description                                                       |
|--------------------------|-----------------------|----------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                       | 0 / unbound ed |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextTextType | 1 / 1          | false | Formatted text content.                                           |
| Image                    | xs:string             | 1 / 1          | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI             | 1 / 1          | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                       | 1 / 1          | false | Formatted text content and an associated item or sequence number. |

|              |
|--------------|
| ParagraphNum |
| 0            |

| Name               | Type                              | Use      | Value | Description                                                                                                                                                                        |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name               | <a href="#">StringLength1to64</a> | optional |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| ParagraphNumber    | xs:nonNegativeInteger             | optional |       | The sequence number for the paragraph.                                                                                                                                             |
| CreateDateTime     | xs:dateTime                       | optional |       | Time stamp of the creation.                                                                                                                                                        |
| CreatorID          | <a href="#">StringLength1to32</a> | optional |       | ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.                                                     |
| LastModifyDateTime | xs:dateTime                       | optional |       | Time stamp of last modification.                                                                                                                                                   |
| LastModifierID     | <a href="#">StringLength1to32</a> | optional |       | Identifies the last software system or person to modify a record.                                                                                                                  |
| PurgeDate          | xs:date                           | optional |       | Date an item will be purged from a database (e.g., from a live database to an archive).                                                                                            |
| Language           | xs:language                       | optional |       | Language identification.                                                                                                                                                           |

#### 1.1.4.1.3.1.4.1.1.1.1. Text

XPath :/OTA HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Total/Taxes/Tax/TaxDescription/Text

### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|      |           |       |       |                         |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |
|------|-----------|-------|-------|-------------------------|

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

## 1.1.4.1.3.1.4.1.1.2. ListItem

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Total/Taxes/Tax/TaxDescription/ListItem

## Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

|          |            |          |  |                              |
|----------|------------|----------|--|------------------------------|
| ListItem | xs:integer | optional |  | The item or sequence number. |
|----------|------------|----------|--|------------------------------|

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.3.1.5. Availability

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/Availability

#### Format Description

| Name         | Type | Occ   | Nil   | Description                                                |
|--------------|------|-------|-------|------------------------------------------------------------|
| Availability |      | 0 / 5 | false | Provides information on the availability of the room rate. |

#### Attributes

| Name               | Type                              | Use      | Value | Description                                                                                          |
|--------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------|
| AvailabilityStatus | <a href="#">RateIndicatorType</a> | required |       | Set to "AvailableForSale" if no rate change applies<br>Set to "On-Request" if the rate is On-request |

### 1.1.4.1.3.1.6. AdvanceBookingRestriction

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/AdvanceBookingRestriction

#### Format Description

| Name                      | Type | Occ   | Nil   | Description                                                           |
|---------------------------|------|-------|-------|-----------------------------------------------------------------------|
| AdvanceBookingRestriction |      | 0 / 1 | false | The restriction will only be specified for the first Rate occurrence. |

## Attributes

| Name                    | Type                                     | Use      | Value | Description                                                                                                                                            |
|-------------------------|------------------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Start                   | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The starting value of the time span.                                                                                                                   |
| Duration                | <a href="#">DurationType</a>             | optional |       | The duration datatype represents a combination of year, month, day and time values representing a single duration of time, encoded as a single string. |
| End                     | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The ending value of the time span.                                                                                                                     |
| MinAdvanceBookingOffset | xs:duration                              | optional |       | The minimum lead time required for the booking.                                                                                                        |
| MaxAdvanceBookingOffset | xs:duration                              | optional |       | The maximum lead time required for the booking.                                                                                                        |
| Mon                     | xs:boolean                               | optional |       | When true, apply to Monday.                                                                                                                            |
| Tue                     | xs:boolean                               | optional |       | When true, apply to Tuesday.                                                                                                                           |
| Weds                    | xs:boolean                               | optional |       | When true, apply to Wednesday.                                                                                                                         |
| Thur                    | xs:boolean                               | optional |       | When true, apply to Thursday.                                                                                                                          |
| Fri                     | xs:boolean                               | optional |       | When true, apply to Friday.                                                                                                                            |
| Sat                     | xs:boolean                               | optional |       | When true, apply to Saturday.                                                                                                                          |
| Sun                     | xs:boolean                               | optional |       | When true, apply to Sunday.                                                                                                                            |

### 1.1.4.1.3.1.7. ServiceRPHs

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/ServiceRPHs

## Format Description

| Name        | Type            | Occ   | Nil   | Description                                                              |
|-------------|-----------------|-------|-------|--------------------------------------------------------------------------|
| ServiceRPHs | ServiceRPHsType | 0 / 1 | false | A container for the unique references to the services for the room stay. |

## Elements

| Name                       | Type | Occ               | Nil   | Description                                                                                    |
|----------------------------|------|-------------------|-------|------------------------------------------------------------------------------------------------|
| <i>sequence</i>            |      | 1 / 1             |       |                                                                                                |
| <a href="#">ServiceRPH</a> |      | 1 / unbound<br>ed | false | This is a reference placeholder used as an index for a service to be associated with this stay |

### 1.1.4.1.3.1.7.1. ServiceRPH

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/ServiceRPHs/ServiceRPH

## Format Description



| Name       | Type | Occ         | Nil   | Description                                                                                    |
|------------|------|-------------|-------|------------------------------------------------------------------------------------------------|
| ServiceRPH |      | 1 / unbound | false | This is a reference placeholder used as an index for a service to be associated with this stay |

### Attributes

| Name      | Type                     | Use      | Value | Description                                         |
|-----------|--------------------------|----------|-------|-----------------------------------------------------|
| RPH       | <a href="#">RPH_Type</a> | optional |       | Provides a unique reference to the service.         |
| IsPerRoom | xs:boolean               | optional |       | Defines whether this is for each room of a RoomStay |

## 1.1.4.1.3.1.8. GuestCounts

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/GuestCounts

### Format Description

| Name        | Type | Occ   | Nil   | Description                                       |
|-------------|------|-------|-------|---------------------------------------------------|
| GuestCounts |      | 0 / 1 | false | Guest count per room mandatory when multiple room |

### Elements

| Name                       | Type | Occ    | Nil   | Description                                                                                    |
|----------------------------|------|--------|-------|------------------------------------------------------------------------------------------------|
| <i>sequence</i>            |      | 1 / 1  |       |                                                                                                |
| <a href="#">GuestCount</a> |      | 1 / 99 | false | One for all adult guests.<br>For Leisure/MultiSource a dedicated one can be used for children. |

## 1.1.4.1.3.1.8.1. GuestCount

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/RoomRate/GuestCounts/GuestCount

### Format Description

| Name       | Type | Occ    | Nil   | Description                                                                                    |
|------------|------|--------|-------|------------------------------------------------------------------------------------------------|
| GuestCount |      | 1 / 99 | false | One for all adult guests.<br>For Leisure/MultiSource a dedicated one can be used for children. |

### Attributes

| Name              | Type                          | Use      | Value | Description                                                   |
|-------------------|-------------------------------|----------|-------|---------------------------------------------------------------|
| AgeQualifyingCode | <a href="#">OTA_CodeType</a>  | required |       | Guest type can be sent back OTA Code AQC                      |
| Age               | <a href="#">Numeric0to999</a> | optional |       | Defines the age of a guest.<br>Mandatory in case of children. |
| Count             | <a href="#">Numeric1to999</a> | required |       | Occupancy for the adult guests, maximum i                     |

### 1.1.4.1.3.2. TPA\_Extensions

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/RoomRates/TPA\_Extensions

#### Format Description

| Name           | Type               | Occ   | Nil   | Description                                                                                                                     |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| TPA_Extensions | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

#### Elements

| Name     | Type | Occ               | Nil | Description |
|----------|------|-------------------|-----|-------------|
| sequence |      | 1 / 1             |     |             |
| any      |      | 0 / unbound<br>ed |     |             |

### 1.1.4.1.4. GuestCounts

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/GuestCounts

#### Format Description

| Name        | Type           | Occ   | Nil   | Description            |
|-------------|----------------|-------|-------|------------------------|
| GuestCounts | GuestCountType | 0 / 1 | false | (guest count per room) |

#### Elements

| Name                       | Type | Occ    | Nil   | Description                                                                                    |
|----------------------------|------|--------|-------|------------------------------------------------------------------------------------------------|
| sequence                   |      | 1 / 1  |       |                                                                                                |
| <a href="#">GuestCount</a> |      | 1 / 99 | false | One for all adult guests.<br>For Leisure/MultiSource a dedicated one can be used for children. |

## Attributes

| Name      | Type       | Use      | Value | Description                                                                                                                                                                                                                                                             |
|-----------|------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IsPerRoom | xs:boolean | optional |       | IsPerRoom means that the guests defined in the GuestCounts object apply to each room in the NumberOfRooms for the RoomStay. Value of "false" means that the guests defined in the GuestCounts object apply to all rooms combined in the NumberOfRooms for the RoomStay. |

### 1.1.4.1.4.1. GuestCount

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/GuestCounts/GuestCount

## Format Description

| Name       | Type | Occ    | Nil   | Description                                                                                    |
|------------|------|--------|-------|------------------------------------------------------------------------------------------------|
| GuestCount |      | 1 / 99 | false | One for all adult guests.<br>For Leisure/MultiSource a dedicated one can be used for children. |

## Attributes

| Name              | Type                          | Use      | Value | Description                                                                                                                                                                                                                                                                                    |
|-------------------|-------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AgeQualifyingCode | <a href="#">OTA_CodeType</a>  | required |       | A code representing a business rule that determines the charges for a guest based upon age range (e.g. Adult, Child, Senior, Child With Adult, Child Without Adult). This attribute allows for an increase in rate by occupant class. Refer to OpenTravel Code List Age Qualifying Code (AQC). |
| Age               | <a href="#">Numeric0to999</a> | optional |       | Defines the age of a guest.<br>Mandatory in case of children.                                                                                                                                                                                                                                  |
| Count             | <a href="#">Numeric1to999</a> | optional |       | The number of guests in one AgeQualifyingCode or Count.                                                                                                                                                                                                                                        |

### 1.1.4.1.5. TimeSpan

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/TimeSpan

## Format Description

| Name     | Type             | Occ   | Nil   | Description                               |
|----------|------------------|-------|-------|-------------------------------------------|
| TimeSpan | DateTimeSpanType | 0 / 1 | false | The Time Span which covers the Room Stay. |

## Elements

| Name                            | Type            | Occ   | Nil   | Description                                                                     |
|---------------------------------|-----------------|-------|-------|---------------------------------------------------------------------------------|
| <i>choice</i>                   |                 | 1 / 1 |       |                                                                                 |
| <a href="#">DateWindowRange</a> | TimeInstantType | 1 / 1 | false | Specifies a time period that can be applied before and/or after the start date. |
| <i>sequence</i>                 |                 | 1 / 1 |       |                                                                                 |
| <a href="#">StartDateWindow</a> |                 | 0 / 1 | false | The earliest and latest dates acceptable for the start date.                    |
| <a href="#">EndDateWindow</a>   |                 | 0 / 1 | false | The earliest and latest dates acceptable for the end date.                      |

## Attributes

| Name  | Type                                     | Use      | Value | Description                          |
|-------|------------------------------------------|----------|-------|--------------------------------------|
| Start | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The starting value of the time span. |
| End   | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The ending value of the time span.   |

### 1.1.4.1.5.1. DateWindowRange

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/TimeSpan/DateWindowRange

## Format Description

| Name            | Type                               | Occ   | Nil   | Description                                                                     |
|-----------------|------------------------------------|-------|-------|---------------------------------------------------------------------------------|
| DateWindowRange | <a href="#">DateOrDateTimeType</a> | 1 / 1 | false | Specifies a time period that can be applied before and/or after the start date. |

### 1.1.4.1.5.2. StartDateWindow

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/TimeSpan/StartDateWindow

## Format Description

| Name            | Type | Occ   | Nil   | Description                                                  |
|-----------------|------|-------|-------|--------------------------------------------------------------|
| StartDateWindow |      | 0 / 1 | false | The earliest and latest dates acceptable for the start date. |

## Attributes

| Name | Type                          | Use      | Value | Description                                                                                                                                                                                           |
|------|-------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOW  | <a href="#">DayOfWeekType</a> | required |       | The Day of Week of the starting date for the availability requested. Enumerated values of StartDOW are the seven days of the week: Monday, Tuesday, Wednesday, Thursday, Friday, Saturday, or Sunday. |

### 1.1.4.1.5.3. EndDateWindow

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/TimeSpan/EndDateWindow

#### Format Description

| Name          | Type | Occ   | Nil   | Description                                                |
|---------------|------|-------|-------|------------------------------------------------------------|
| EndDateWindow |      | 0 / 1 | false | The earliest and latest dates acceptable for the end date. |

#### Attributes

| Name | Type                          | Use      | Value | Description                                                                                                                                                                                           |
|------|-------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOW  | <a href="#">DayOfWeekType</a> | required |       | The Day of Week of the starting date for the availability requested. Enumerated values of StartDOW are the seven days of the week: Monday, Tuesday, Wednesday, Thursday, Friday, Saturday, or Sunday. |

### 1.1.4.1.6. Total

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/Total

#### Format Description

| Name  | Type      | Occ   | Nil   | Description                                                                                                                                                             |
|-------|-----------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Total | TotalType | 0 / 1 | false | The total amount charged for the Room Stay including additional occupant amounts and fees. If TaxInclusive is set to True, then taxes are included in the total amount. |

#### Elements

| Name                  | Type      | Occ   | Nil   | Description            |
|-----------------------|-----------|-------|-------|------------------------|
| <i>sequence</i>       |           | 1 / 1 |       |                        |
| <a href="#">Taxes</a> | TaxesType | 0 / 1 | false | A collection of taxes. |

#### Attributes

| Name            | Type                  | Use      | Value | Description                                                                                          |
|-----------------|-----------------------|----------|-------|------------------------------------------------------------------------------------------------------|
| AmountBeforeTax | <a href="#">Money</a> | optional |       | The total amount not including any associated tax (e.g., sales tax, VAT, GST or any associated tax). |
| AmountAfterTax  | <a href="#">Money</a> | optional |       | The total amount including all associated taxes (e.g., sales tax, VAT, GST or any associated tax).   |

|                                 |                              |          |  |                                                                                                |
|---------------------------------|------------------------------|----------|--|------------------------------------------------------------------------------------------------|
| CurrencyCode                    | <a href="#">AlphaLength3</a> | required |  | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces                   | xs:nonNegativeInteger        | optional |  | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |
| AdditionalFeesExcludedIndicator | xs:boolean                   | optional |  | Total Amount of the room taxes included                                                        |

### 1.1.4.1.6.1. Taxes

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/Total/Taxes

#### Format Description

| Name  | Type      | Occ   | Nil   | Description            |
|-------|-----------|-------|-------|------------------------|
| Taxes | TaxesType | 0 / 1 | false | A collection of taxes. |

#### Elements

| Name                | Type    | Occ    | Nil   | Description        |
|---------------------|---------|--------|-------|--------------------|
| <i>sequence</i>     |         | 1 / 1  |       |                    |
| <a href="#">Tax</a> | TaxType | 0 / 99 | false | An individual tax. |

#### Attributes

| Name          | Type                         | Use      | Value | Description                                                                                    |
|---------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------|
| Amount        | <a href="#">Money</a>        | optional |       | A monetary amount.                                                                             |
| CurrencyCode  | <a href="#">AlphaLength3</a> | required |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                           |
| DecimalPlaces | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency. |

### 1.1.4.1.6.1.1. Tax

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/Total/Taxes/Tax

#### Format Description

| Name | Type    | Occ    | Nil   | Description        |
|------|---------|--------|-------|--------------------|
| Tax  | TaxType | 0 / 99 | false | An individual tax. |

#### Elements

| Name                           | Type          | Occ   | Nil   | Description                                        |
|--------------------------------|---------------|-------|-------|----------------------------------------------------|
| <i>sequence</i>                |               | 1 / 1 |       |                                                    |
| <a href="#">TaxDescription</a> | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

## Attributes

| Name            | Type                                    | Use      | Value | Description                                                                                                                                                      |
|-----------------|-----------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type            | <a href="#">AmountDeterminationType</a> | optional |       | Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).              |
| Code            | <a href="#">OTA_CodeType</a>            | optional |       | Code identifying the fee (e.g., agency fee, municipality fee). Refer to OpenTravel Code List Fee Tax Type (FTT).                                                 |
| Percent         | <a href="#">Percentage</a>              | optional |       | Fee percentage; if zero, assume use of the Amount attribute (Amount or Percent must be a zero value).                                                            |
| Amount          | <a href="#">Money</a>                   | optional |       | A monetary amount.                                                                                                                                               |
| CurrencyCode    | <a href="#">AlphaLength3</a>            | optional |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                                                                             |
| DecimalPlaces   | xs:nonNegativeInteger                   | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.                                                                   |
| ChargeUnit      | <a href="#">OTA_CodeType</a>            | required |       | This is the unit for which the charge applies (e.g. room, person, seat). Refer to OpenTravel Code List Charge Type (CHG).                                        |
| ChargeFrequency | <a href="#">OTA_CodeType</a>            | optional |       | This is the timeframe used to apply the charge during the course of the reservation (e.g. Daily, Weekly, Stay). Refer to OpenTravel Code List Charge Type (CHG). |

### 1.1.4.1.6.1.1.1. TaxDescription

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/Total/Taxes/Tax/TaxDescription

## Format Description

| Name           | Type          | Occ   | Nil   | Description                                        |
|----------------|---------------|-------|-------|----------------------------------------------------|
| TaxDescription | ParagraphType | 0 / 5 | false | Text description of the taxes in a given language. |

## Elements

| Name                 | Type              | Occ           | Nil   | Description                  |
|----------------------|-------------------|---------------|-------|------------------------------|
| <i>choice</i>        |                   | 0 / unbounded |       |                              |
| <a href="#">Text</a> | FormattedTextType | 1 / 1         | false | Formatted text content.      |
| Image                | xs:string         | 1 / 1         | false | An image for this paragraph. |
| URL                  | xs:anyURI         | 1 / 1         | false | A URL for this paragraph.    |

|                          |  |       |       |                                                                   |
|--------------------------|--|-------|-------|-------------------------------------------------------------------|
| <a href="#">ListItem</a> |  | 1 / 1 | false | Formatted text content and an associated item or sequence number. |
|--------------------------|--|-------|-------|-------------------------------------------------------------------|

## Attributes

| Name     | Type                              | Use      | Value | Description                                                                                                                                                                        |
|----------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name     | <a href="#">StringLength1to64</a> | required |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |
| Language | xs:language                       | optional |       | Language identification.                                                                                                                                                           |

### 1.1.4.1.6.1.1.1.1. Text

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/Total/Taxes/Tax/TaxDescription/Text

## Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

## Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |



### 1.1.4.1.6.1.1.1.2. **ListItem**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/Total/Taxes/Tax/TaxDescription/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.4.1.7. **TPA\_Extensions**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/TPA\_Extensions

#### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|                |                    |       |       |                                                                                                                                 |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| TPA_Extensions | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|

## Elements

| Name     | Type | Occ               | Nil | Description |
|----------|------|-------------------|-----|-------------|
| sequence |      | 1 / 1             |     |             |
| any      |      | 0 / unbound<br>ed |     |             |

### 1.1.4.1.8. Reference

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/Reference

## Format Description

| Name      | Type          | Occ   | Nil   | Description                                                                 |
|-----------|---------------|-------|-------|-----------------------------------------------------------------------------|
| Reference | UniqueID_Type | 0 / 1 | false | Information by which this availability quote can be later cross-referenced. |

## Elements

| Name                        | Type            | Occ   | Nil   | Description                                                  |
|-----------------------------|-----------------|-------|-------|--------------------------------------------------------------|
| sequence                    |                 | 1 / 1 |       |                                                              |
| <a href="#">CompanyName</a> | CompanyNameType | 0 / 1 | false | Identifies the company that is associated with the UniqueID. |

## Attributes

| Name       | Type                              | Use      | Value | Description                                                                                                                                                                                                                                   |
|------------|-----------------------------------|----------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| URL        | xs:anyURI                         | optional |       | URL that identifies the location associated with the record identified by the UniqueID.                                                                                                                                                       |
| Type       | <a href="#">OTA_CodeType</a>      | required |       | A reference to the type of object defined by the UniqueID element. Refer to OpenTravel Code List Unique ID Type (UIT).                                                                                                                        |
| Instance   | <a href="#">StringLength1to32</a> | optional |       | The identification of a record as it exists at a point in time. An instance is used in update messages where the sender must assure the server that the update sent refers to the most recent modification level of the object being updated. |
| ID         | <a href="#">StringLength1to32</a> | required |       | A unique identifying value assigned by the creating system. The ID attribute may be used to reference a primary-key value within a database or in a particular implementation.                                                                |
| ID_Context | <a href="#">StringLength1to32</a> | optional |       | Used to identify the source of the identifier (e.g., IATA, ABTA).                                                                                                                                                                             |

|          |             |          |  |                                                                        |
|----------|-------------|----------|--|------------------------------------------------------------------------|
| DateTime | xs:dateTime | optional |  | The date and time at which this availability quote was made available. |
|----------|-------------|----------|--|------------------------------------------------------------------------|

### 1.1.4.1.8.1. **CompanyName**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/Reference/CompanyName

#### Format Description

| Name        | Type                               | Occ   | Nil   | Description                                                  |
|-------------|------------------------------------|-------|-------|--------------------------------------------------------------|
| CompanyName | <a href="#">StringLength0to128</a> | 0 / 1 | false | Identifies the company that is associated with the UniqueID. |

#### Attributes

| Name             | Type                              | Use      | Value | Description                                                                                                                      |
|------------------|-----------------------------------|----------|-------|----------------------------------------------------------------------------------------------------------------------------------|
| CompanyShortName | <a href="#">StringLength1to32</a> | optional |       | Used to provide the company common name.                                                                                         |
| TravelSector     | <a href="#">OTA_CodeType</a>      | optional |       | The travel sector the company is associated with, such as air, car and hotel. Refer to OpenTravel Code List Travel Sector (TVS). |
| Code             | <a href="#">StringLength1to16</a> | optional |       | Identifies a company by the company code.                                                                                        |
| CodeContext      | <a href="#">StringLength1to32</a> | optional |       | Identifies the context of the identifying code, such as DUNS, IATA or internal code, etc.                                        |
| Division         | <a href="#">StringLength1to32</a> | optional |       | The division name or ID with which the contact is associated.                                                                    |
| Department       | <a href="#">StringLength1to32</a> | optional |       | The department name or ID with which the contact is associated.                                                                  |

### 1.1.4.1.9. **ServiceRPHs**

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/ServiceRPHs

#### Format Description

| Name        | Type            | Occ   | Nil   | Description                                                              |
|-------------|-----------------|-------|-------|--------------------------------------------------------------------------|
| ServiceRPHs | ServiceRPHsType | 0 / 1 | false | A container for the unique references to the services for the room stay. |

#### Elements

| Name                       | Type | Occ         | Nil   | Description                                                                                    |
|----------------------------|------|-------------|-------|------------------------------------------------------------------------------------------------|
| <i>sequence</i>            |      | 1 / 1       |       |                                                                                                |
| <a href="#">ServiceRPH</a> |      | 1 / unbound | false | This is a reference placeholder used as an index for a service to be associated with this stay |

### 1.1.4.1.9.1. ServiceRPH

XPath :/OTA\_HotelAvailRS/RoomStays/RoomStay/ServiceRPHs/ServiceRPH

#### Format Description

| Name       | Type | Occ            | Nil   | Description                                                                                    |
|------------|------|----------------|-------|------------------------------------------------------------------------------------------------|
| ServiceRPH |      | 1 / unbound ed | false | This is a reference placeholder used as an index for a service to be associated with this stay |

#### Attributes

| Name      | Type                     | Use      | Value | Description                                         |
|-----------|--------------------------|----------|-------|-----------------------------------------------------|
| RPH       | <a href="#">RPH_Type</a> | optional |       | Provides a unique reference to the service.         |
| IsPerRoom | xs:boolean               | optional |       | Defines whether this is for each room of a RoomStay |

### 1.1.5. Services

XPath :/OTA\_HotelAvailRS/Services

#### Format Description

| Name     | Type         | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                 |
|----------|--------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Services | ServicesType | 0 / 1 | false | A collection of Service objects. This is the collection of all services associated with any part of this reservation (the reservation in its entirety, one or more guests, or one or more room stays). Which services are attributable to which part is determined by each object's ServiceRPHs collection. |

#### Elements

| Name                    | Type        | Occ            | Nil   | Description                                                                                                                    |
|-------------------------|-------------|----------------|-------|--------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>         |             | 1 / 1          |       |                                                                                                                                |
| <a href="#">Service</a> | ServiceType | 1 / unbound ed | false | A Service object represents a non-room product provided to guests. Service products may have associated inventory and charges. |

### 1.1.5.1. Service

XPath :/OTA\_HotelAvailRS/Services/Service

## Format Description

| Name    | Type        | Occ         | Nil   | Description                                                                                                                    |
|---------|-------------|-------------|-------|--------------------------------------------------------------------------------------------------------------------------------|
| Service | ServiceType | 1 / unbound | false | A Service object represents a non-room product provided to guests. Service products may have associated inventory and charges. |

## Elements

| Name                           | Type                | Occ    | Nil   | Description                                                                                                                                                                                                                                                                                                             |
|--------------------------------|---------------------|--------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>                |                     | 1 / 1  |       |                                                                                                                                                                                                                                                                                                                         |
| <a href="#">Price</a>          | AmountType          | 0 / 99 | false | The selling price of this Service.                                                                                                                                                                                                                                                                                      |
| <a href="#">ServiceDetails</a> | ResCommonDetailType | 0 / 1  | false | Details on the Service including Guest Counts, Time Span of this Service, pointers to Res Guests, guest Memberships, Comments and Special Requests pertaining to this particular Service and finally financial information related to the Service, including Guarantee, Deposit and Payment and Cancellation Penalties. |
| <a href="#">TPA_Extensions</a> | TPA_ExtensionsType  | 0 / 1  | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA).                                                                                                                                                                                         |

## Attributes

| Name                 | Type                              | Use      | Value | Description                                                                                                                                                                    |
|----------------------|-----------------------------------|----------|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ServicePricingType   | <a href="#">PricingType</a>       | optional |       | An enumerated type that defines how a service is priced. Values: Per stay, Per person, Per night, Per person per night, Per use.                                               |
| ServiceRPH           | <a href="#">RPH_Type</a>          | required |       | A unique ID for a service that may be referenced elsewhere in the schema.<br>ServiceRPH=RPH use to link the service to a RoomStay                                              |
| ServiceInventoryCode | <a href="#">StringLength1to16</a> | required |       | The representation of the specific service being reserved.                                                                                                                     |
| Inclusive            | xs:boolean                        | optional |       | Whether the price for this service is included in the room rate. Values: False (or No), and True (or Yes).                                                                     |
| Quantity             | <a href="#">Numeric1to999</a>     | optional |       | The number of tickets, rounds of golf, etc. Also serves as the number of persons when pricing class is per person or per person per night.                                     |
| Type                 | <a href="#">OTA_CodeType</a>      | required |       | A reference to the type of object defined by the UniqueID element. Refer to OpenTravel Code List Unique ID Type (UIT).                                                         |
| ID                   | <a href="#">StringLength1to32</a> | required |       | A unique identifying value assigned by the creating system. The ID attribute may be used to reference a primary-key value within a database or in a particular implementation. |
| ID_Context           | <a href="#">StringLength1to32</a> | optional |       | Indicates if @ID is a CRS code or a distributed code                                                                                                                           |

### 1.1.5.1.1. Price

XPath :/OTA\_HotelAvailRS/Services/Service/Price

#### Format Description

| Name  | Type       | Occ    | Nil   | Description                        |
|-------|------------|--------|-------|------------------------------------|
| Price | AmountType | 0 / 99 | false | The selling price of this Service. |

#### Elements

| Name                  | Type      | Occ   | Nil   | Description                                                                                                                                                                                                                                               |
|-----------------------|-----------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>       |           | 1 / 1 |       |                                                                                                                                                                                                                                                           |
| <a href="#">Base</a>  | TotalType | 0 / 1 | false | The base amount charged for the accommodation or service per unit of time (ex: Nightly, Weekly, etc). If TaxInclusive is set to True, then taxes are included in the base amount. Note that any additional charges should itemized in the other elements. |
| <a href="#">Total</a> | TotalType | 0 / 1 | false | The total amount charged for this rate including additional occupant amounts and fees.                                                                                                                                                                    |

#### Attributes

| Name           | Type                         | Use      | Value | Description                                                                                                 |
|----------------|------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------|
| EffectiveDate  | xs:date                      | required |       | Indicates the starting date.                                                                                |
| ExpireDate     | xs:date                      | required |       | Indicates the ending date.                                                                                  |
| RateTimeUnit   | <a href="#">TimeUnitType</a> | required |       | Indicates the time unit for the rate.                                                                       |
| UnitMultiplier | xs:positiveInteger           | required |       | Indicates the number of rate time units such as "3 Days".                                                   |
| ChargeType     | <a href="#">OTA_CodeType</a> | optional |       | The type of the amount being charged, e.g. per night. Refer to OpenTravel Code List Charge Type Code (CHG). |

### 1.1.5.1.1.1. Base

XPath :/OTA\_HotelAvailRS/Services/Service/Price/Base

#### Format Description

| Name | Type      | Occ   | Nil   | Description                                                                                                                                                                                                                                               |
|------|-----------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Base | TotalType | 0 / 1 | false | The base amount charged for the accommodation or service per unit of time (ex: Nightly, Weekly, etc). If TaxInclusive is set to True, then taxes are included in the base amount. Note that any additional charges should itemized in the other elements. |

## Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

## Attributes

| Name                            | Type                         | Use      | Value | Description                                                                                          |
|---------------------------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------------|
| AmountBeforeTax                 | <a href="#">Money</a>        | optional |       | The total amount not including any associated tax (e.g., sales tax, VAT, GST or any associated tax). |
| AmountAfterTax                  | <a href="#">Money</a>        | optional |       | The total amount including all associated taxes (e.g., sales tax, VAT, GST or any associated tax).   |
| CurrencyCode                    | <a href="#">AlphaLength3</a> | required |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                 |
| DecimalPlaces                   | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.       |
| AdditionalFeesExcludedIndicator | xs:boolean                   | optional |       | When true, amounts do not contain additional fees or charges.                                        |
| Type                            | <a href="#">OTA_CodeType</a> | optional |       | Type of charge. Refer to OpenTravel Code List Charge Type (CHG).                                     |

### 1.1.5.1.1.2. Total

XPath :/OTA\_HotelAvailRS/Services/Service/Price/Total

## Format Description

| Name  | Type      | Occ   | Nil   | Description                                                                            |
|-------|-----------|-------|-------|----------------------------------------------------------------------------------------|
| Total | TotalType | 0 / 1 | false | The total amount charged for this rate including additional occupant amounts and fees. |

## Elements

| Name     | Type | Occ   | Nil | Description |
|----------|------|-------|-----|-------------|
| sequence |      | 1 / 1 |     |             |

## Attributes

| Name            | Type                  | Use      | Value | Description                                                                                          |
|-----------------|-----------------------|----------|-------|------------------------------------------------------------------------------------------------------|
| AmountBeforeTax | <a href="#">Money</a> | optional |       | The total amount not including any associated tax (e.g., sales tax, VAT, GST or any associated tax). |

|                |                              |          |  |                                                                                                    |
|----------------|------------------------------|----------|--|----------------------------------------------------------------------------------------------------|
| AmountAfterTax | <a href="#">Money</a>        | optional |  | The total amount including all associated taxes (e.g., sales tax, VAT, GST or any associated tax). |
| CurrencyCode   | <a href="#">AlphaLength3</a> | required |  | An ISO 4217 (3) alpha character code that specifies a monetary unit.                               |
| DecimalPlaces  | xs:nonNegativeInteger        | optional |  | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.     |
| Type           | <a href="#">OTA_CodeType</a> | optional |  | Type of charge. Refer to OpenTravel Code List Charge Type (CHG).                                   |

### 1.1.5.1.2. ServiceDetails

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails

#### Format Description

| Name           | Type                | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                             |
|----------------|---------------------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ServiceDetails | ResCommonDetailType | 0 / 1 | false | Details on the Service including Guest Counts, Time Span of this Service, pointers to Res Guests, guest Memberships, Comments and Special Requests pertaining to this particular Service and finally financial information related to the Service, including Guarantee, Deposit and Payment and Cancellation Penalties. |

#### Elements

| Name                        | Type           | Occ   | Nil   | Description                                                                                                                                                                 |
|-----------------------------|----------------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sequence</i>             |                | 1 / 1 |       |                                                                                                                                                                             |
| <a href="#">GuestCounts</a> | GuestCountType | 0 / 1 | false | A collection of Guest Counts associated to the whole Reservation or a particular Room Stay or Service. A child Guest Count element is required for each distinct age group. |
| <a href="#">TimeSpan</a>    |                | 0 / 1 | false | The Time Span which covers the Reservation, Room Stay or Service.                                                                                                           |
| <a href="#">Comments</a>    | CommentType    | 0 / 1 | false | A collection of Comment objects. Comments which apply to the whole Reservation or a particular Room Stay or Service.                                                        |
| <a href="#">Total</a>       | TotalType      | 0 / 1 | false | The total amount charged for the accommodation including additional occupant amounts and fees. If TaxInclusive is set to True, then taxes are included in the total amount. |

### 1.1.5.1.2.1. GuestCounts

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/GuestCounts

#### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|



|             |                |       |       |                                                                                                                                                                             |
|-------------|----------------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| GuestCounts | GuestCountType | 0 / 1 | false | A collection of Guest Counts associated to the whole Reservation or a particular Room Stay or Service. A child Guest Count element is required for each distinct age group. |
|-------------|----------------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Elements

| Name                       | Type | Occ    | Nil   | Description                                                                      |
|----------------------------|------|--------|-------|----------------------------------------------------------------------------------|
| <i>sequence</i>            |      | 1 / 1  |       |                                                                                  |
| <a href="#">GuestCount</a> |      | 1 / 99 | false | A recurring element that identifies the number of guests and ages of the guests. |

### 1.1.5.1.2.1.1. GuestCount

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/GuestCounts/GuestCount

## Format Description

| Name       | Type | Occ    | Nil   | Description                                                                      |
|------------|------|--------|-------|----------------------------------------------------------------------------------|
| GuestCount |      | 1 / 99 | false | A recurring element that identifies the number of guests and ages of the guests. |

## Attributes

| Name              | Type                          | Use      | Value | Description                                                                                                                                                                                                                                                                                    |
|-------------------|-------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AgeQualifyingCode | <a href="#">OTA_CodeType</a>  | optional |       | A code representing a business rule that determines the charges for a guest based upon age range (e.g. Adult, Child, Senior, Child With Adult, Child Without Adult). This attribute allows for an increase in rate by occupant class. Refer to OpenTravel Code List Age Qualifying Code (AQC). |
| Age               | <a href="#">Numeric0to999</a> | optional |       | Defines the age of a guest.                                                                                                                                                                                                                                                                    |
| Count             | <a href="#">Numeric1to999</a> | optional |       | The number of guests in one AgeQualifyingCode or Count.                                                                                                                                                                                                                                        |

### 1.1.5.1.2.2. TimeSpan

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/TimeSpan

## Format Description

| Name     | Type             | Occ   | Nil   | Description                                                       |
|----------|------------------|-------|-------|-------------------------------------------------------------------|
| TimeSpan | DateTimeSpanType | 0 / 1 | false | The Time Span which covers the Reservation, Room Stay or Service. |

## Elements

| Name                            | Type            | Occ   | Nil   | Description                                                                     |
|---------------------------------|-----------------|-------|-------|---------------------------------------------------------------------------------|
| choice                          |                 | 1 / 1 |       |                                                                                 |
| <a href="#">DateWindowRange</a> | TimeInstantType | 1 / 1 | false | Specifies a time period that can be applied before and/or after the start date. |
| sequence                        |                 | 1 / 1 |       |                                                                                 |

## Attributes

| Name  | Type                                     | Use      | Value | Description                          |
|-------|------------------------------------------|----------|-------|--------------------------------------|
| Start | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The starting value of the time span. |
| End   | <a href="#">DateOrTimeOrDateTimeType</a> | optional |       | The ending value of the time span.   |

### 1.1.5.1.2.2.1. DateWindowRange

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/TimeSpan/DateWindowRange

## Format Description

| Name            | Type                               | Occ   | Nil   | Description                                                                     |
|-----------------|------------------------------------|-------|-------|---------------------------------------------------------------------------------|
| DateWindowRange | <a href="#">DateOrDateTimeType</a> | 1 / 1 | false | Specifies a time period that can be applied before and/or after the start date. |

### 1.1.5.1.2.3. Comments

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/Comments

## Format Description

| Name     | Type        | Occ   | Nil   | Description                                                                                                          |
|----------|-------------|-------|-------|----------------------------------------------------------------------------------------------------------------------|
| Comments | CommentType | 0 / 1 | false | A collection of Comment objects. Comments which apply to the whole Reservation or a particular Room Stay or Service. |

## Elements

| Name                    | Type | Occ               | Nil   | Description      |
|-------------------------|------|-------------------|-------|------------------|
| sequence                |      | 1 / 1             |       |                  |
| <a href="#">Comment</a> |      | 1 / unbound<br>ed | false | Comment details. |

### 1.1.5.1.2.3.1. Comment

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/Comments/Comment

#### Format Description

| Name    | Type          | Occ            | Nil   | Description      |
|---------|---------------|----------------|-------|------------------|
| Comment | ParagraphType | 1 / unbound ed | false | Comment details. |

#### Elements

| Name                     | Type              | Occ            | Nil   | Description                                                       |
|--------------------------|-------------------|----------------|-------|-------------------------------------------------------------------|
| <i>choice</i>            |                   | 0 / unbound ed |       |                                                                   |
| <a href="#">Text</a>     | FormattedTextType | 1 / 1          | false | Formatted text content.                                           |
| Image                    | xs:string         | 1 / 1          | false | An image for this paragraph.                                      |
| URL                      | xs:anyURI         | 1 / 1          | false | A URL for this paragraph.                                         |
| <a href="#">ListItem</a> |                   | 1 / 1          | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name | Type                              | Use      | Value | Description                                                                                                                                                                        |
|------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Name | <a href="#">StringLength1to64</a> | required |       | In many cases the description repeats, this will allow you to define the information that is being sent, typically used when multiple occurrences of ParagraphType are being sent. |

### 1.1.5.1.2.3.1.1. Text

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/Comments/Comment/Text

#### Format Description

| Name | Type      | Occ   | Nil   | Description             |
|------|-----------|-------|-------|-------------------------|
| Text | xs:string | 1 / 1 | false | Formatted text content. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | required |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | required |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.5.1.2.3.1.2. ListItem

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/Comments/Comment/ListItem

#### Format Description

| Name     | Type      | Occ   | Nil   | Description                                                       |
|----------|-----------|-------|-------|-------------------------------------------------------------------|
| ListItem | xs:string | 1 / 1 | false | Formatted text content and an associated item or sequence number. |

#### Attributes

| Name                       | Type        | Use      | Value | Description                                                                                                   |
|----------------------------|-------------|----------|-------|---------------------------------------------------------------------------------------------------------------|
| Formatted                  | xs:boolean  | optional |       | Textual information, which may be formatted as a line of information, or unformatted, as a paragraph of text. |
| Language                   | xs:language | optional |       | Language identification.                                                                                      |
| <a href="#">TextFormat</a> |             | optional |       | Indicates the format of text used in the description e.g. unformatted or html.                                |
| ListItem                   | xs:integer  | optional |       | The item or sequence number.                                                                                  |

Attribute: TextFormat

Variety: atomic

Base: xs:NMTOKEN

Documentation:

| Enumeration | description                           |
|-------------|---------------------------------------|
| PlainText   | Textual data that is in ASCII format. |
| HTML        | HTML formatted text.                  |

### 1.1.5.1.2.4. Total

XPath :/OTA\_HotelAvailRS/Services/Service/ServiceDetails/Total

#### Format Description

| Name  | Type      | Occ   | Nil   | Description                                                                                                                                                                 |
|-------|-----------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Total | TotalType | 0 / 1 | false | The total amount charged for the accommodation including additional occupant amounts and fees. If TaxInclusive is set to True, then taxes are included in the total amount. |

#### Elements

| Name            | Type | Occ   | Nil | Description |
|-----------------|------|-------|-----|-------------|
| <i>sequence</i> |      | 1 / 1 |     |             |

#### Attributes

| Name            | Type                         | Use      | Value | Description                                                                                          |
|-----------------|------------------------------|----------|-------|------------------------------------------------------------------------------------------------------|
| AmountBeforeTax | <a href="#">Money</a>        | optional |       | The total amount not including any associated tax (e.g., sales tax, VAT, GST or any associated tax). |
| AmountAfterTax  | <a href="#">Money</a>        | optional |       | The total amount including all associated taxes (e.g., sales tax, VAT, GST or any associated tax).   |
| CurrencyCode    | <a href="#">AlphaLength3</a> | required |       | An ISO 4217 (3) alpha character code that specifies a monetary unit.                                 |
| DecimalPlaces   | xs:nonNegativeInteger        | optional |       | The ISO 4217 standard "minor unit" for the number of decimal places for a particular currency.       |
| Type            | <a href="#">OTA_CodeType</a> | optional |       | Type of charge. Refer to OpenTravel Code List Charge Type (CHG).                                     |

### 1.1.5.1.3. TPA\_Extensions

XPath :/OTA\_HotelAvailRS/Services/Service/TPA\_Extensions

#### Format Description

| Name           | Type               | Occ   | Nil   | Description                                                                                                                     |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| TPA_Extensions | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

#### Elements

| Name     | Type | Occ               | Nil | Description |
|----------|------|-------------------|-----|-------------|
| sequence |      | 1 / 1             |     |             |
| any      |      | 0 / unbound<br>ed |     |             |

### 1.1.6. Areas

XPath :/OTA\_HotelAvailRS/Areas

#### Format Description

| Name  | Type      | Occ   | Nil   | Description                                                               |
|-------|-----------|-------|-------|---------------------------------------------------------------------------|
| Areas | AreasType | 0 / 1 | false | Defines a collection of areas determined by the hotel reservation system. |

#### Elements

| Name                 | Type | Occ   | Nil   | Description                                         |
|----------------------|------|-------|-------|-----------------------------------------------------|
| sequence             |      | 1 / 1 |       |                                                     |
| <a href="#">Area</a> |      | 1 / 1 | false | An area determined by the hotel reservation system. |

#### 1.1.6.1. Area

XPath :/OTA\_HotelAvailRS/Areas/Area

#### Format Description

| Name | Type | Occ | Nil | Description |
|------|------|-----|-----|-------------|
|------|------|-----|-----|-------------|

|      |  |       |       |                                                     |
|------|--|-------|-------|-----------------------------------------------------|
| Area |  | 1 / 1 | false | An area determined by the hotel reservation system. |
|------|--|-------|-------|-----------------------------------------------------|

## Elements

| Name            | Type | Occ   | Nil | Description |
|-----------------|------|-------|-----|-------------|
| <i>sequence</i> |      | 1 / 1 |     |             |

### 1.1.7. Criteria

XPath :/OTA\_HotelAvailRS/Criteria

#### Format Description

| Name     | Type | Occ   | Nil   | Description                                                        |
|----------|------|-------|-------|--------------------------------------------------------------------|
| Criteria |      | 0 / 1 | false | The availability search criteria specified in the request message. |

## Elements

| Name                      | Type                     | Occ               | Nil   | Description |
|---------------------------|--------------------------|-------------------|-------|-------------|
| <i>sequence</i>           |                          | 1 / 1             |       |             |
| <a href="#">Criterion</a> | HotelSearchCriterionType | 1 / unbound<br>ed | false |             |

### 1.1.7.1. Criterion

XPath :/OTA\_HotelAvailRS/Criteria/Criterion

#### Format Description

| Name      | Type                    | Occ               | Nil   | Description |
|-----------|-------------------------|-------------------|-------|-------------|
| Criterion | ItemSearchCriterionType | 1 / unbound<br>ed | false |             |

## Elements

| Name            | Type | Occ   | Nil | Description |
|-----------------|------|-------|-----|-------------|
| <i>sequence</i> |      | 1 / 1 |     |             |

|                                |                    |         |       |                                                                                                                                                                                                                                                                                                                                     |
|--------------------------------|--------------------|---------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">Position</a>       |                    | 0 / 1   | false | The Position element contains three attributes, Latitude, Longitude, and Altitude, used to indicate the geographic location(s) requested by the search, expressed in notation specified by ISO standard 6709. It is likely that only the first two attributes, Latitude and Longitude, would be needed to define a geographic area. |
| <a href="#">RefPoint</a>       |                    | 0 / 999 | false | The Reference Point element allows for a search by proximity to a designated reference point by name.                                                                                                                                                                                                                               |
| <a href="#">CodeRef</a>        |                    | 0 / 1   | false | Indicates the location of points of interest.                                                                                                                                                                                                                                                                                       |
| <a href="#">Radius</a>         |                    | 0 / 1   | false | Used to specify the extent of a search area. The extent is relative to an element (position, address, hotel reference, etc.) present in this ItemSearchCriterionType that specifies a location.                                                                                                                                     |
| <a href="#">MapArea</a>        |                    | 0 / 1   | false | Provides coordinates used to define the area of a map.                                                                                                                                                                                                                                                                              |
| <i>sequence</i>                |                    | 1 / 1   |       |                                                                                                                                                                                                                                                                                                                                     |
| <a href="#">TPA_Extensions</a> | TPA_ExtensionsType | 0 / 1   | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA).                                                                                                                                                                                                     |

## Attributes

| Name       | Type       | Use      | Value | Description                                                                                            |
|------------|------------|----------|-------|--------------------------------------------------------------------------------------------------------|
| ExactMatch | xs:boolean | optional |       | Values of "true" or "false", indicating whether the string of the search value must be an exact match. |

### 1.1.7.1.1. Position

XPath :/OTA\_HotelAvailRS/Criteria/Criterion/Position

## Format Description

| Name     | Type | Occ   | Nil   | Description                                                                                                                                                                                                                                                                                                                         |
|----------|------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Position |      | 0 / 1 | false | The Position element contains three attributes, Latitude, Longitude, and Altitude, used to indicate the geographic location(s) requested by the search, expressed in notation specified by ISO standard 6709. It is likely that only the first two attributes, Latitude and Longitude, would be needed to define a geographic area. |

## Attributes

| Name      | Type                              | Use      | Value | Description                                                                           |
|-----------|-----------------------------------|----------|-------|---------------------------------------------------------------------------------------|
| Latitude  | <a href="#">StringLength1to16</a> | optional |       | The measure of the angular distance on a meridian north or south of the equator.      |
| Longitude | <a href="#">StringLength1to16</a> | optional |       | The measure of the angular distance on a meridian east or west of the prime meridian. |



|                      |                              |          |  |                                                                                                                                                                                       |
|----------------------|------------------------------|----------|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PositionAccuracyCode | <a href="#">OTA_CodeType</a> | optional |  | Indicates the accuracy of the property's geo-coding, since the property's longitude and latitude may not always be exact. Refer to OpenTravel Code List Position Accuracy Code (PAC). |
|----------------------|------------------------------|----------|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### 1.1.7.1.2. RefPoint

XPath :/OTA\_HotelAvailRS/Criteria/Criterion/RefPoint

#### Format Description

| Name     | Type                              | Occ     | Nil   | Description                                                                                           |
|----------|-----------------------------------|---------|-------|-------------------------------------------------------------------------------------------------------|
| RefPoint | <a href="#">StringLength0to64</a> | 0 / 999 | false | The Reference Point element allows for a search by proximity to a designated reference point by name. |

#### Attributes

| Name         | Type                               | Use      | Value | Description                                                                                                                        |
|--------------|------------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------------|
| StateProv    | <a href="#">StateProvCodeType</a>  | optional |       | The state or province in which the reference point is located.                                                                     |
| CountryCode  | <a href="#">ISO3166</a>            | optional |       | The country in which the reference point is located.                                                                               |
| RefPointType | <a href="#">OTA_CodeType</a>       | optional |       | Indicates the type of location being referenced (e.g., Airport, Hotel). Refer to the OpenTravel Code table Index Point Code (IPC). |
| Name         | <a href="#">StringLength1to128</a> | optional |       | The name of the reference point.                                                                                                   |

### 1.1.7.1.3. CodeRef

XPath :/OTA\_HotelAvailRS/Criteria/Criterion/CodeRef

#### Format Description

| Name    | Type      | Occ   | Nil   | Description                                   |
|---------|-----------|-------|-------|-----------------------------------------------|
| CodeRef | xs:string | 0 / 1 | false | Indicates the location of points of interest. |

#### Attributes

| Name         | Type                              | Use      | Value | Description                                                                                          |
|--------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------|
| LocationCode | <a href="#">StringLength1to16</a> | required |       | IATA location for Point of reference search (as defined in OTA specification)                        |
| CodeContext  | <a href="#">StringLength1to32</a> | required |       | Identifies the context of the identifying code (e.g., IATA, ARC, or internal code).<br>Set to "IATA" |

### 1.1.7.1.4. Radius

XPath :/OTA\_HotelAvailRS/Criteria/Criterion/Radius

#### Format Description

| Name   | Type | Occ   | Nil   | Description                                                                                                                                                                                     |
|--------|------|-------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Radius |      | 0 / 1 | false | Used to specify the extent of a search area. The extent is relative to an element (position, address, hotel reference, etc.) present in this ItemSearchCriterionType that specifies a location. |

#### Attributes

| Name              | Type                                     | Use      | Value | Description                                                                                                                                               |
|-------------------|------------------------------------------|----------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Distance          | <a href="#">NumericStringLength1to16</a> | optional |       | An optional attribute indicating the distance to/from a reference point. When used in conjunction with DistanceMax, this represents the minimum distance. |
| UnitOfMeasureCode | <a href="#">OTA_CodeType</a>             | optional |       | The unit of measure in a code format. Refer to OpenTravel Code List Unit of Measure Code (UOM).                                                           |

### 1.1.7.1.5. MapArea

XPath :/OTA\_HotelAvailRS/Criteria/Criterion/MapArea

#### Format Description

| Name    | Type | Occ   | Nil   | Description                                            |
|---------|------|-------|-------|--------------------------------------------------------|
| MapArea |      | 0 / 1 | false | Provides coordinates used to define the area of a map. |

#### Attributes

| Name          | Type                              | Use      | Value | Description                                       |
|---------------|-----------------------------------|----------|-------|---------------------------------------------------|
| NorthLatitude | <a href="#">StringLength1to16</a> | optional |       | The latitude of the northern boundary of the map. |
| SouthLatitude | <a href="#">StringLength1to16</a> | optional |       | The latitude of the southern boundary of the map. |
| EastLongitude | <a href="#">StringLength1to16</a> | optional |       | The longitude of the eastern boundary of the map. |
| WestLongitude | <a href="#">StringLength1to16</a> | optional |       | The longitude of the western boundary of the map. |

### 1.1.7.1.6. TPA\_Extensions

XPath :/OTA\_HotelAvailRS/Criteria/Criterion/TPA\_Extensions

### Format Description

| Name           | Type               | Occ   | Nil   | Description                                                                                                                     |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| TPA_Extensions | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

### Elements

| Name     | Type | Occ               | Nil | Description |
|----------|------|-------------------|-----|-------------|
| sequence |      | 1 / 1             |     |             |
| any      |      | 0 / unbound<br>ed |     |             |

## 1.1.8. CurrencyConversions

XPath :/OTA\_HotelAvailRS/CurrencyConversions

### Format Description

| Name                | Type | Occ   | Nil   | Description                                   |
|---------------------|------|-------|-------|-----------------------------------------------|
| CurrencyConversions |      | 0 / 1 | false | A collection of currency conversion elements. |

### Elements

| Name                               | Type | Occ               | Nil   | Description                                              |
|------------------------------------|------|-------------------|-------|----------------------------------------------------------|
| sequence                           |      | 1 / 1             |       |                                                          |
| <a href="#">CurrencyConversion</a> |      | 1 / unbound<br>ed | false | Provides a rate conversion from one currency to another. |

## 1.1.8.1. CurrencyConversion

XPath :/OTA\_HotelAvailRS/CurrencyConversions/CurrencyConversion

### Format Description

| Name               | Type | Occ               | Nil   | Description                                              |
|--------------------|------|-------------------|-------|----------------------------------------------------------|
| CurrencyConversion |      | 1 / unbound<br>ed | false | Provides a rate conversion from one currency to another. |

## Attributes

| Name                  | Type                              | Use      | Value | Description                                                                                                                  |
|-----------------------|-----------------------------------|----------|-------|------------------------------------------------------------------------------------------------------------------------------|
| RateConversion        | xs:decimal                        | required |       | The conversion factor to apply against the source currency to obtain the requested currency.                                 |
| SourceCurrencyCode    | <a href="#">AlphaLength3</a>      | required |       | The code specifying the source currency (use ISO 4217, three alpha code).                                                    |
| RequestedCurrencyCode | <a href="#">AlphaLength3</a>      | required |       | The code specifying the requested currency (use ISO 4217, three alpha code).                                                 |
| DecimalPlaces         | xs:nonNegativeInteger             | optional |       | Indicates the number of decimal places for the requested currency. This is equivalent to the ISO 4217 standard "minor unit". |
| Source                | <a href="#">StringLength1to64</a> | required |       | The source of the rate conversion information.                                                                               |

### 1.1.9. TPA\_Extensions

XPath :/OTA\_HotelAvailRS/TPA\_Extensions

#### Format Description

| Name           | Type               | Occ   | Nil   | Description                                                                                                                     |
|----------------|--------------------|-------|-------|---------------------------------------------------------------------------------------------------------------------------------|
| TPA_Extensions | TPA_ExtensionsType | 0 / 1 | false | A placeholder in the schema to allow for additional elements and attributes to be included per Trading Partner Agreement (TPA). |

## Elements

| Name     | Type | Occ               | Nil | Description |
|----------|------|-------------------|-----|-------------|
| sequence |      | 1 / 1             |     |             |
| any      |      | 0 / unbound<br>ed |     |             |

### 1.1.10. Errors

XPath :/OTA\_HotelAvailRS/Errors

#### Format Description

| Name   | Type       | Occ   | Nil   | Description                                                                                                                                                     |
|--------|------------|-------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Errors | ErrorsType | 1 / 1 | false | Indicates that an error occurred in the processing of the incoming request message. An error is defined as a malformed XML message that could not be processed. |

## Elements

| Name                  | Type      | Occ    | Nil   | Description                                                |
|-----------------------|-----------|--------|-------|------------------------------------------------------------|
| <i>sequence</i>       |           | 1 / 1  |       |                                                            |
| <a href="#">Error</a> | ErrorType | 1 / 99 | false | An error that occurred during the processing of a message. |

### 1.1.10.1. Error

XPath :/OTA\_HotelAvailRS/Errors/Error

## Format Description

| Name  | Type      | Occ    | Nil   | Description                                                |
|-------|-----------|--------|-------|------------------------------------------------------------|
| Error | xs:string | 1 / 99 | false | An error that occurred during the processing of a message. |

## Attributes

| Name      | Type                              | Use      | Value | Description                                                                                                                                                                                                                                                                                                                                                                               |
|-----------|-----------------------------------|----------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Language  | xs:language                       | optional |       | Language identification.                                                                                                                                                                                                                                                                                                                                                                  |
| Type      | <a href="#">OTA_CodeType</a>      | required |       | Set to "1"                                                                                                                                                                                                                                                                                                                                                                                |
| ShortText | <a href="#">StringLength1to64</a> | optional |       | An abbreviated version of the error in textual format.                                                                                                                                                                                                                                                                                                                                    |
| Code      | <a href="#">OTA_CodeType</a>      | required |       | If present, this refers to a table of coded values exchanged between applications to identify errors or warnings. Refer to OpenTravel Code List Error Codes (ERR).                                                                                                                                                                                                                        |
| Status    | <a href="#">StringLength1to64</a> | optional |       | Identify where the error comes from:<br>"1A" for Amadeus<br>Chain code for provider                                                                                                                                                                                                                                                                                                       |
| Tag       | xs:string                         | optional |       | If present, this attribute may identify an unknown or misspelled tag that caused an error in processing. It is recommended that the Tag attribute use XPath notation to identify the location of a tag in the event that more than one tag of the same name is present in the document.<br>Alternatively, the tag name alone can be used to identify missing data [Type=ReqFieldMissing]. |

## 2. Common Simple Types

### 2.1. AlphaLength3

**Variety:** atomic

**Base:** xs:string

**Documentation:** The code specifying a monetary unit. Use ISO 4217, three alpha code.

| Restriction | Value       |
|-------------|-------------|
| pattern     | [a-zA-Z]{3} |

### 2.2. AmountDeterminationType

**Variety:** atomic

**Base:** xs:string

**Documentation:** Used to indicate if the amount is inclusive or exclusive of other charges, such as taxes, or is cumulative (amounts have been added to each other).

| Enumeration | description |
|-------------|-------------|
| Inclusive   |             |
| Exclusive   |             |
| Cumulative  |             |

### 2.3. AvailabilityStatusType

**Variety:** atomic

**Base:** xs:NMTOKENS

**Documentation:** Used to specify an availability status at the Hotel Stay level for a property.

| Enumeration              | description                                                         |
|--------------------------|---------------------------------------------------------------------|
| Open                     | Inventory is available for sale.                                    |
| Close                    | Inventory is not available for sale.                                |
| ClosedOnArrival          | Inventory is not available for sale to arriving guests.             |
| ClosedOnArrivalOnRequest | Inventory may not be available for sale to arriving guests.         |
| OnRequest                | Inventory may be available.                                         |
| RemoveCloseOnly          | Remove Close restriction while keeping other restrictions in place. |

## 2.4. DateOrDateTimeType

**Variety:** union

**Member types:** xs:date xs:dateTime

**Documentation:** A construct to validate either a date or a dateTime value.

## 2.5. DateOrTimeOrDateTimeType

**Variety:** union

**Member types:** xs:date xs:dateTime xs:time

**Documentation:** The starting value of the time span.

## 2.6. DayOfWeekType

**Variety:** atomic

**Base:** xs:NMTOKEN

**Documentation:** Day of week guest is required to stay over in order to be eligible for this rate.

| Enumeration | description |
|-------------|-------------|
| Mon         |             |
| Tue         |             |
| Wed         |             |
| Thu         |             |
| Fri         |             |
| Sat         |             |
| Sun         |             |

## 2.7. DurationType

**Variety:** union

**Member types:** xs:duration [NightDurationType](#)

**Documentation:** The duration datatype represents a combination of year, month, day and time values representing a single duration of time, encoded as a single string.

## 2.8. InfoSourceType

**Variety:** atomic

**Base:** xs:string

**Documentation:** Used to specify the source of the data being exchanged as determined by trading partners.

| Restriction | Value |
|-------------|-------|
| minlength   | 1     |
| maxlength   | 32    |

## 2.9. ISO3166

**Variety:** atomic

**Base:** xs:string

**Documentation:** ISO 3166 code for a country.

| Restriction | Value       |
|-------------|-------------|
| pattern     | [a-zA-Z]{2} |

## 2.10. ListOfOTA\_CodeType

**Variety:** list

**Item type:** [OTA\\_CodeType](#)

**Documentation:** Indicates the type of bed(s) found in the room. Typical values would be Double, Twin, Queen, or King. Refer to OpenTravel Code List Bed Type Code (BED).

## 2.11. ListOfRPH

**Variety:** list

**Item type:** [RPH\\_Type](#)

**Documentation:** References one or more room stays associated with this hotel stay.

## 2.12. Money

**Variety:** atomic

**Base:** xs:decimal

**Documentation:** The available price before tax.

| Restriction    | Value |
|----------------|-------|
| fractiondigits | 3     |



## 2.13. NightDurationType

**Variety:** atomic

**Base:** xs:string

**Documentation:** Provides the ability to define a duration in terms of nights rather than days.

| Restriction | Value        |
|-------------|--------------|
| pattern     | P[0-9]{1,3}N |

## 2.14. Numeric0to99

**Variety:** atomic

**Base:** xs:integer

**Documentation:** Minimum number of persons allowed in a unit of accommodation or place.

| Restriction  | Value |
|--------------|-------|
| mininclusive | 0     |
| maxinclusive | 99    |

## 2.15. Numeric0to999

**Variety:** atomic

**Base:** xs:integer

**Documentation:** The number of units of DeadlineTimeUnit.

| Restriction  | Value |
|--------------|-------|
| mininclusive | 0     |
| maxinclusive | 999   |

## 2.16. Numeric1to99

**Variety:** atomic

**Base:** xs:integer

**Documentation:** Maximum number of persons allowed in a unit of accommodation or place.

| Restriction  | Value |
|--------------|-------|
| mininclusive | 1     |
| maxinclusive | 99    |

## 2.17. Numeric1to999

**Variety:** atomic

**Base:** xs:integer

**Documentation:** This attribute may be used when there is a need to number all of the sub-sections of information that is to be presented.

| Restriction  | Value |
|--------------|-------|
| mininclusive | 1     |
| maxinclusive | 999   |

## 2.18. NumericStringLength1to16

**Variety:** atomic

**Base:** xs:string

**Documentation:** An optional attribute indicating the distance to/from a reference point. When used in conjunction with DistanceMax, this represents the minimum distance.

| Restriction | Value       |
|-------------|-------------|
| pattern     | [0-9]{1,16} |

## 2.19. NumericStringLength1to5

**Variety:** atomic

**Base:** xs:string

**Documentation:** Numerical equivalent of a rural township as defined within a given area (e.g., 12, 99).

| Restriction | Value      |
|-------------|------------|
| pattern     | [0-9]{1,5} |

## 2.20. NumericStringLength1to8

**Variety:** atomic

**Base:** xs:string

**Documentation:** An identifier of an area as defined by a hotel reservation system.

| Restriction | Value |
|-------------|-------|
|-------------|-------|

|         |            |
|---------|------------|
| pattern | [0-9]{1,8} |
|---------|------------|

## 2.21. OTA\_CodeType

**Variety:** atomic

**Base:** xs:string

**Documentation:** The Warning element MUST contain the Type attribute that uses a recommended set of values to indicate the warning type. The validating XSD can expect to accept values that it has NOT been explicitly coded for and process them by using Type ="Unknown". Refer to OpenTravel Code List Error Warning Type (EWT).

| Restriction | Value                                    |
|-------------|------------------------------------------|
| pattern     | [0-9A-Z]{1,3}(\.[A-Z]{3}(\.X){0,1}){0,1} |

## 2.22. PaymentCardCodeType

**Variety:** union

**Member types:** *anonymous* *anonymous*

**Documentation:** The 2 character code of the credit card issuer.

### Member types

**Variety:** atomic

**Base:** [UpperCaseAlphaLength1to2](#)

**Documentation:**

| Enumeration | description                        |
|-------------|------------------------------------|
| AX          | American Express                   |
| BC          | Bank Card                          |
| BL          | Carte Bleu                         |
| CB          | Carte Blanche                      |
| DN          | Diners Club                        |
| DS          | Discover Card                      |
| EC          | Eurocard                           |
| JC          | Japanese Credit Bureau Credit Card |
| MA          | Maestro                            |
| MC          | Master Card                        |
| TP          | Universal Air Travel Card          |
| VI          | Visa                               |

**Variety:** atomic

**Base:** [UpperCaseAlphaLength1to2](#)

**Documentation:** This is intended to be used when the above enumeration list does not meet your needs.

## 2.23. Percentage

**Variety:** atomic

**Base:** xs:decimal

**Documentation:** The percentage used to calculate the amount.

| Restriction  | Value  |
|--------------|--------|
| mininclusive | 0.00   |
| maxinclusive | 100.00 |

## 2.24. PricingType

**Variety:** atomic

**Base:** [StringLength1to32](#)

**Documentation:** Specifies how the room is priced (per night, per person, etc.).

| Enumeration          | description |
|----------------------|-------------|
| Per stay             |             |
| Per person           |             |
| Per night            |             |
| Per person per night |             |
| Per use              |             |

## 2.25. RateIndicatorType

**Variety:** atomic

**Base:** [StringLength1to32](#)

**Documentation:** Information pertaining to the availability of the rate plan.

| Enumeration | description |
|-------------|-------------|
|-------------|-------------|

|                     |                                                                                                        |
|---------------------|--------------------------------------------------------------------------------------------------------|
| ChangeDuringStay    |                                                                                                        |
| MultipleNights      |                                                                                                        |
| Exclusive           | Availability is limited based on guest qualification criteria e.g. AAA member or Government Employee   |
| OnRequest           |                                                                                                        |
| LimitedAvailability |                                                                                                        |
| AvailableForSale    |                                                                                                        |
| ClosedOut           |                                                                                                        |
| OtherAvailable      |                                                                                                        |
| UnableToProcess     | Indicates an issue that precluded the ability to provide the information.                              |
| NoAvailability      |                                                                                                        |
| RoomTypeClosed      |                                                                                                        |
| RatePlanClosed      |                                                                                                        |
| LOS_Restricted      |                                                                                                        |
| Restricted          | Availability is limited based on distribution channel qualification criteria (e.g., Expedia or Sabre). |
| DoesNotExist        | The rate plan does not exist.                                                                          |

## 2.26. RPH\_Type

**Variety:** atomic

**Base:** xs:string

**Documentation:** Reference Place Holder used as an index for this warning.

| Restriction | Value      |
|-------------|------------|
| pattern     | [0-9]{1,8} |

## 2.27. StateProvCodeType

**Variety:** atomic

**Base:** [StringLength1to8](#)

**Documentation:** The standard code or abbreviation for the state, province, or region.

| Restriction | Value |
|-------------|-------|
| minlength   | 2     |

## 2.28. StringLength0to128

**Variety:** atomic

**Base:** xs:string

**Documentation:** Used for Character Strings, length 0 to 128.

| Restriction | Value |
|-------------|-------|
| minlength   | 0     |
| maxlength   | 128   |

## 2.29. StringLength0to64

**Variety:** atomic

**Base:** xs:string

**Documentation:** Used for Character Strings, length 0 to 64.

| Restriction | Value |
|-------------|-------|
| minlength   | 0     |
| maxlength   | 64    |

## 2.30. StringLength1to128

**Variety:** atomic

**Base:** xs:string

**Documentation:** A text field used to communicate the proper name of the hotel.

| Restriction | Value |
|-------------|-------|
| minlength   | 1     |
| maxlength   | 128   |

## 2.31. StringLength1to16

**Variety:** atomic

**Base:** xs:string

**Documentation:** Used for Character Strings, length 1 to 16.

| Restriction | Value |
|-------------|-------|
| minlength   | 1     |
| maxlength   | 16    |

## 2.32. StringLength1to255

**Variety:** atomic

**Base:** xs:string

**Documentation:** When the address is unformatted (FormattedInd="false") these lines will contain free form address details. When the address is formatted and street number and street name must be sent independently, the street number will be sent using StreetNmbr, and the street name will be sent in the first AddressLine occurrence.

| Restriction | Value |
|-------------|-------|
| minlength   | 1     |
| maxlength   | 255   |

## 2.33. StringLength1to32

**Variety:** atomic

**Base:** xs:string

**Documentation:** ID of creator. The creator could be a software system identifier or an identifier of an employee responsible for the creation.

| Restriction | Value |
|-------------|-------|
| minlength   | 1     |
| maxlength   | 32    |

## 2.34. StringLength1to64

**Variety:** atomic

**Base:** xs:string

**Documentation:** An abbreviated version of the error in textual format.

| Restriction | Value |
|-------------|-------|
| minlength   | 1     |
| maxlength   | 64    |

## 2.35. StringLength1to8

**Variety:** atomic

**Base:** xs:string

**Documentation:** An optional code that may be assigned to this sub-section of formatted free text.

| Restriction | Value |
|-------------|-------|
| minlength   | 1     |
| maxlength   | 8     |

## 2.36. TimeOrDateTimeType

**Variety:** union

**Member types:** xs:dateTime xs:time

**Documentation:** Defines the absolute deadline. Either this or the offset attributes may be used.

## 2.37. TimeUnitType

**Variety:** atomic

**Base:** [StringLength1to16](#)

**Documentation:** A time unit used to apply this status message to other inventory, and with more granularity than daily. Values: Year, Month, Week, Day, Hour, Minute, Second.

| Enumeration  | description |
|--------------|-------------|
| Year         |             |
| Month        |             |
| Week         |             |
| Day          |             |
| Hour         |             |
| Second       |             |
| FullDuration |             |
| Minute       |             |

## 2.38. UpperCaseAlphaLength1to2

**Variety:** atomic

**Base:** xs:string

**Documentation:** Used for an Alpha String, length 1 to 2 (for letter codes).

| Restriction | Value      |
|-------------|------------|
| pattern     | [A-Z]{1,2} |



