

```
from collections import deque

def bfs(graph, start_vertex):
    visited = set()
    queue = deque([start_vertex])

    while queue:
        current_vertex = queue.popleft()
        if current_vertex not in visited:
            print(current_vertex, end=' ')
            visited.add(current_vertex)

            queue.extend(neighbor for neighbor in graph[current_vertex] if neighbor not in visited)

graph = {
    0: [1, 3],
    1: [0, 2, 3],
    2: [1, 4, 5],
    3: [0, 1, 4],
    4: [2, 3, 5],
    5: [2, 4],
}

start_vertex = 0
print("BFS traversal starting from vertex", start_vertex, ":")
bfs(graph, start_vertex)

    BFS traversal starting from vertex 0 :
    0 1 3 2 4 5
```

```

def dfs(graph, start):
    visited = set()
    stack = [start]

    while stack:
        current_node = stack.pop()

        if current_node not in visited:
            print(current_node, end=' ')
            visited.add(current_node)

            # Push neighboring nodes onto the stack in reverse order to maintain desired order
            stack.extend(neighbor for neighbor in reversed(graph[current_node]) if neighbor not in visited)

# Example graph represented as an adjacency list
graph = {
    'A': ['B', 'S'],
    'B': ['A'],
    'C': ['D', 'E', 'F', 'S'],
    'D': ['C'],
    'E': ['H', 'C'],
    'F': ['C', 'G'],
    'G': ['S', 'H', 'F'],
    'H': ['G', 'E'],
    'S': ['A', 'C', 'G'],
}

start_node = 'A'
print("DFS traversal starting from node", start_node)
dfs(graph, start_node)

    DFS traversal starting from node A
    A B S C D E H G F

from copy import deepcopy
import numpy as np
import time

def bestsolution(state):
    bestsol = np.array([], int).reshape(-1, 9)
    count = len(state) - 1

```

```

while count != -1:
    bestsol = np.insert(bestsol, 0, state[count]['puzzle'], 0)
    count = (state[count]['parent'])
return bestsol.reshape(-1, 3, 3)

# checks for the uniqueness of the iteration(it).
def all(checkarray):
    set=[]
    for it in set:
        for checkarray in it:
            return 1
    else:
        return 0

# number of misplaced tiles
def misplaced_tiles(puzzle,goal):
    mscost = np.sum(puzzle != goal) - 1
    return mscost if mscost > 0 else 0

def coordinates(puzzle):
    pos = np.array(range(9))
    for p, q in enumerate(puzzle):
        pos[q] = p
    return pos

# start of 8 puzzle evaluation, using Misplaced tiles heuristics
def evaluat_misplaced(puzzle, goal):
    steps = np.array([('up', [0, 1, 2], -3),('down', [6, 7, 8], 3),('left', [0, 3, 6], -1),('right', [2, 5, 8], 1)],
        dtype = [('move', str, 1),('position', list),('head', int)])

    dtstate = [('puzzle', list),('parent', int),('gn', int),('hn', int)]

    costg = coordinates(goal)

    # initializing the parent, gn and hn, where hn is misplaced_tiles function call
    parent = -1
    gn = 0
    hn = misplaced_tiles(coordinates(puzzle), costg)

```

```

state = np.array([(puzzle, parent, gn, hn)], dtstate)

#priority queues with position as keys and fn as value.
dtpriority = [('position', int), ('fn', int)]

priority = np.array([(0, hn)], dtpriority)

while 1:
    priority = np.sort(priority, kind='mergesort', order=['fn', 'position'])
    position, fn = priority[0]
    # sort priority queue using merge sort, the first element is picked for exploring.
    priority = np.delete(priority, 0, 0)
    puzzle, parent, gn, hn = state[position]
    puzzle = np.array(puzzle)

    blank = int(np.where(puzzle == 0)[0])

    gn = gn + 1
    c = 1
    start_time = time.time()
    for s in steps:
        c = c + 1
        if blank not in s['position']:
            openstates = deepcopy(puzzle)
            openstates[blank], openstates[blank + s['head']] = openstates[blank + s['head']], openstates[blank]

        if ~(np.all(list(state['puzzle']) == openstates, 1)).any():
            end_time = time.time()
            if ((end_time - start_time) > 2):
                print("The 8 puzzle is unsolvable \n")
                break

        hn = misplaced_tiles(coordinates(openstates), costg)
        # generate and add new state in the list
        q = np.array([(openstates, position, gn, hn)], dtstate)
        state = np.append(state, q, 0)
        # f(n) is the sum of cost to reach node
        fn = gn + hn

        q = np.array([(len(state) - 1, fn)], dtpriority)
        priority = np.append(priority, q, 0)

```

```
        if np.array_equal(openstates, goal):
            print(' The 8 puzzle is solvable \n')
            return state, len(priority)

    return state, len(priority)

# initial state
puzzle = []

puzzle.append(2)
puzzle.append(8)
puzzle.append(3)
puzzle.append(7)
puzzle.append(1)
puzzle.append(4)
puzzle.append(0)
puzzle.append(6)
puzzle.append(5)

#goal state
goal = []

goal.append(1)
goal.append(2)
goal.append(3)
goal.append(8)
goal.append(0)
goal.append(4)
goal.append(7)
goal.append(6)
goal.append(5)

state, visited = evaluvate_misplaced(puzzle, goal)
bestpath = bestsolution(state)
print(str(bestpath).replace('[', ' ').replace(']', ''))
totalmoves = len(bestpath) - 1
print('\nSteps to reach goal:',totalmoves)
visit = len(state) - visited
print('Total nodes visited: ',visit, "\n")
```



The 8 puzzle is solvable

2 8 3
7 1 4
0 6 5

2 8 3
0 1 4
7 6 5

2 8 3
1 0 4
7 6 5

2 0 3
1 8 4
7 6 5

0 2 3
1 8 4
7 6 5

1 2 3
0 8 4
7 6 5

1 2 3
8 0 4
7 6 5

Steps to reach goal: 6
Total nodes visited: 11

