

# Monadic Operations in C++23



ROBERT SCHIMKOWITSCH

<https://mastodon.social/@asperamanca>

<https://github.com/Asperamanca/>

<https://cppusergroupvienna.org/>

# Calling successive functions that might fail

```
bool getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    CElement element;
    if ( ! getElement(db, key, element))           { return false; }

    CTableData table;
    if ( ! getTable(element, table))               { return false; }

    CTableCell cell;
    if ( ! getCell(table, location, cell))         { return false; }

    int value;
    if ( ! getNumericCellValue(cell, value))       { return false; }

    result = (value < 0);
    return true;
}
```

# Calling successive functions that might fail

```
bool getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    CElement element;
    if ( ! getElement(db, key, element))           { return false; }

    CTableData table;
    if ( ! getTable(element, table))               { return false; }

    CTableCell cell;
    if ( ! getCell(table, location, cell))         { return false; }

    int value;
    if ( ! getNumericCellValue(cell, value))      { return false; }

    result = (value < 0);
    return true;
}
```

## ...with exceptions

```
bool getNumericTableValueNegative(const CDb& db, const Key& key,
                                  const CLocation& location)
{
    auto table = getTable(getElement(db, key));
    auto cell = getCell(table, cellLocation);
    return (getNumericCellValue(cell) < 0);
}
```

# But I can't use exceptions!

```
bool getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    CElement element;
    if ( ! getElement(db, key, element))           { return false; }

    CTableData table;
    if ( ! getTable(element, table))               { return false; }

    CTableCell cell;
    if ( ! getCell(table, location, cell))         { return false; }

    int value;
    if ( ! getNumericCellValue(cell, value))       { return false; }

    result = (value < 0);
    return true;
}
```

# Does an error flag help?

```
class CMyClass
{
    //...
    bool m_bError{false};
};

bool CMyClass::getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    auto table = getTable(getElement(db, key))
    auto cell = getCell(table, location)
    auto value = getNumericCellValue(cell)
    if (m_bError) { return false; }

    result = (value < 0);
    return true;
}
```

# Does an error flag help?

```
class CMyClass
{
    //...
    bool m_bError{false};
};

bool CMyClass::getNumericTableValueNegative
(const CDb& db, const Key& key, ...
const CLocation& location, bool& out)
{
    auto table = getTable(getElement(db, key))
    auto cell = getCell(table, location)
    auto value = getNumericCellValue(cell)
    if (m_bError) { return false; }

    result = (value < 0);
    return true;
}

CTableData CMyClass::getTable
{
    if (m_bError)
    {
        return{};
    }
}
```

# Does an error flag help?



```
class CMyClass
{
    //...
    bool m_bError{false};
};

bool CMyClass::getNumericTableValueNegative
(const CDb& db, const Key& key,
const CLocation& location, bool& out)
{
    auto table = getTable(getElement(db, key))
    auto cell = getCell(table, location)
    auto value = getNumericCellValue(cell)
    if (m_bError) { return false; }

    result = (value < 0);
    return true;
}
```



# Can std::optional help?

```
std::optional<bool> isNumericTableCellValueNegative
(const CDb& db, const Key& key, const CLocation& location)
{
    auto oElement = getElement(db, key);
    if ( ! oElement.has_value()) { return {}; }

    auto oTable = getTable(oElement.value());
    if ( ! oTable.has_value())    { return {}; }

    auto oCell = getCell(oTable.value(), location);
    if ( ! oCell.has_value())    { return {}; }

    auto oValue = getNumericCellValue(oCell.value());
    if ( ! oValue.has_value())    { return {}; }

    return (oValue.value() < 0);
}
```

# C++23: Begone, Boilerplate!

```
std::optional<bool> isNumericTableCellValueNegative  
    (const CDb& db, const Key& key, const CLocation& location)  
{  
    return getElement(db, key)  
        .and_then(getTable)  
        .and_then(std::bind_back(&getCell, location))  
        .and_then(getNumericCellValue)  
        .transform(isNegative);  
}
```




**Robert Schimkowitsch**

<https://mastodon.social/@asperamanca>

<https://github.com/Asperamanca/>

<https://cppusergroupvienna.org/>





# Functors

WRAP & TRANSFORM




# What is a Functor?

```
class CNegator
{
public:
    int operator()(const int value) const
    {
        return -value;
    }
};
```



```
// ...
```

```
CNegator negator;
auto x = negator(5); // -5
```

# Now really, what is a Functor?



# Two rules for the Transformation



## Example: From Classic Loop to Functor

```
auto v = std::vector{1.5,2.0,2.5};
```

```
std::vector<std::string> strings;  
for(const auto& value : v)  
{  
    strings.push_back(std::format("{:}",  
                                  std::pow(value,2.0)));  
}  
// 'strings' now contains {"2.25","4","6.25"}
```



## Example: From Classic Loop to Functor

```
auto v = std::vector{1.5,2.0,2.5};  
  
std::vector<std::string> strings;  
for(const auto& value : v)  
{  
    strings.push_back(std::format("{:}",  
                                std::pow(value,2.0)));  
}  
// 'strings' now contains {"2.25","4","6.25"}
```





## Example: From Classic Loop to Functor

```
auto v = std::vector{1.5,2.0,2.5};

std::vector<std::string> strings;
for(const auto& value : v)
{
    strings.push_back(std::format("{:}",
                                std::pow(value,2.0)));
}
// 'strings' now contains {"2.25","4","6.25"}
```



## Example: From Classic Loop to Functor

```
auto v = std::vector{1.5,2.0,2.5};

std::vector<std::string> strings;
for(const auto& value : v)
{
    strings.push_back(std::format("{:}",
                                   std::pow(value,2.0)));
}
// 'strings' now contains {"2.25","4","6.25"}
```



## Example: From Classic Loop to Functor

```
auto v = std::vector{1.5,2.0,2.5};

std::vector<std::string> strings;
for(const auto& value : v)
{
    strings.push_back(std::format("{:}",
                                   std::pow(value,2.0)));
}
// 'strings' now contains {"2.25","4","6.25"}
```



## Example: From Classic Loop to Functor

```
#include <format>
```

```
double makeSquared(const double value)
{
    return std::pow(value,2.0);
}
```

```
std::string dblToStr(const double value)
{
    return std::format("{:}",value);
}
```



## Example: From Classic Loop to Functor

```
auto v = std::vector{1.5,2.0,2.5};

std::vector<std::string> strings;
for(const auto& value : v)
{
    strings.push_back(dbToStr(makeSquared(value)));
}

// 'strings' now contains {"2.25","4","6.25"}
```



## Example: From Classic Loop to Functor

```
#include <format>
```

```
double makeSquared(const double value)
{
    return std::pow(value, 2.0);
}
```

```
std::string dblToStr(const double value)
{
    return std::format("{:}", value);
}
```



# Example: From Classic Loop to Functor

```
#include <format>
```

```
double makeSquared(const double value)
{
    return std::pow(value, 2.0);
}
```

```
std::string dblToStr(const double value)
{
    return std::format("{:}", value);
}
```

A thought bubble containing the text "KYSS" in a stylized font. The "K" and "S" are teal, and the "Y" is orange. The bubble has a grey outline and three small circles leading to it.

KYSS



## Example: From Classic Loop to Functor

```
#include <ranges>

auto v = std::vector{1.5, 2.0, 2.5};

auto strings = std::views::transform
               (std::views::transform(v, makeSquared),
                dblToStr);

// {"2.25", "4", "6.25"}
```





## Example: From Classic Loop to Functor

```
#include <ranges>
```

```
auto v = std::vector{1.5,2.0,2.5};
```

```
auto strings = std::views::transform  
               (std::views::transform(v,makeSquared),  
                dblToStr);
```

```
// {"2.25", "4", "6.25"}
```



## Example: From Classic Loop to Functor

```
#include <ranges>
```

```
auto v = std::vector{1.5,2.0,2.5};
```

```
auto strings = std::views::transform  
               (std::views::transform(v,makeSquared),  
                dblToStr);
```

```
// {"2.25", "4", "6.25"}
```



# The Pipe to the Rescue

```
#include <ranges>

auto v = std::vector{1.5, 2.0, 2.5};

auto strings = v
    | std::views::transform(makeSquared)
    | std::views::transform(dblToStr);

// {"2.25", "4", "6.25"}
```




# The Pipe to the Rescue

```
#include <ranges>

auto v = std::vector{1.5, 2.0, 2.5};

auto strings = v | std::views::transform(makeSquared)
                | std::views::transform(dblToStr);

// {"2.25", "4", "6.25"}
```



# Classic Solution vs. Functor Solution

```
std::vector<std::string> strings;  
for(const auto& value : v)  
{  
    strings.push_back(dbToStr(makeSquared(value)));  
}
```


```
auto strings = v  
    | std::views::transform(makeSquared)  
    | std::views::transform(dbToStr);
```

View: Does not own or copy its data

# Classic Solution vs. Functor Solution

```
std::vector<std::string> strings;  
for(const auto& value : v)  
{  
    strings.push_back(dbToStr(makeSquared(value)));  
}
```

```
auto strings = v  
    | std::views::transform(makeSquared)  
    | std::views::transform(dbToStr);
```



# It's a Trap!

```
struct CEntry {  
    int m_X{};  
    int m_Y{};  
    std::string m_Text{}; };  
  
CEntry getNearestEntry(const int x) {...}  
  
using namespace std;  
auto v = vector{1,3,7};  
  
auto strings = v  
    | views::transform(getNearestEntry)  
    | views::transform(&CEntry::m_Text);  
  
printOutput(strings);
```



# It's a Trap!

```
struct CEntry {
    int m_X{};
    int m_Y{};
    std::string m_Text{}; };
```

```
CEntry getNearestEntry(const int x) {...}
```

```
using namespace std;
auto v = vector{1,3,7};
```

```
auto strings = v
    | views::transform(getNearestEntry)
    | views::transform(&CEntry::m_Text);
```

```
printOutput(strings);
```





# It's a Trap!

```
struct CEntry {  
    int m_X{};  
    int m_Y{};  
    std::string m_Text{}; };
```

```
CEntry getNearestEntry(const int x) {...}
```

```
using namespace std;  
auto v = vector{1,3,7};
```


```
auto strings = v  
    | views::transform(getNearestEntry)  
    | views::transform(&CEntry::m_Text);
```

```
printOutput(strings);
```



# The Type of the Resulting View

```
class std::ranges::transform_view
<class std::ranges::transform_view
  <class std::ranges::ref_view
    <class std::vector
      <double,class std::allocator<double>>
    >,double (__cdecl*)(double)
  >,
class std::basic_string
  <char,struct std::char_traits<char>,
    class std::allocator<char>
  > (__cdecl*)(double)
>
```



# Converting the output of views into a container

```
std::vector<std::string> convertViewResultToContainer()
{
    using namespace std;
    auto v = vector{1.5, 2.0, 2.5};

    auto strings = v
        | views::transform(makeSquared)
        | views::transform(db1ToStr);

    return ranges::to<vector<string>>(strings);
}
```



# Inlining functions that return views

```
inline auto getSquaredNumbersAsString  
    (const std::vector<int>& vector)  
{  
    using namespace std;  
  
    auto strings = v  
        | views::transform(makeSquared)  
        | views::transform(db1ToStr);  
  
    return strings;  
}
```



# Callables

DIFFERENT WAYS TO  
FEED YOUR FUNCTOR (OR MONAD)



# Callable: Free functions

```
double makeSquared(const double value) {...}
```

```
auto v = vector{1.5,2.0,2.5};  
auto strings = v  
    | std::views::transform(makeSquared)  
    | std::views::transform(dblToStr);
```



# Callable: (Class) Static Functions

```
class CConv
{
public:
    static double makeSquaredStatic(const double value);
    //...
};
//...

auto v = vector{1.5,2.0,2.5};
auto strings = v
    | std::views::transform(CConv::makeSquaredStatic)
    | //...
```

# Callables: Inline Lambda

```
using namespace std;
```

```
auto v = vector{1.5,2.0,2.5};
```

```
auto strings = v
```

```
| views::transform([](const double& value)  
| {return value * value;})
```

```
| //...
```





# Callables: Inject Parameters via Inline Lambda

```
using namespace std;

const double power = 2.0;
auto v = vector{1.5, 2.0, 2.5};
auto strings = v
    | views::transform([power](const double& value)
        {return std::pow(value, power);})
    | //...
```



## Callables: Inject Parameters via std::bind\*

```
foo( int , bool , double )
```

```
std::bind_front ( foo, 42 , true ) -> f(double)
```

```
std::bind_back ( foo, true , 3.14 ) -> f(int)
```



# Callables: Inject Parameters via `std::bind_back`

```
using namespace std;
```

```
const double power = 2.0;
```

```
auto v = vector{1.5, 2.0, 2.5};
```

```
auto strings = v
```

```
    | views::transform(
```

```
    |     std::bind_back(std::pow<double, double>, power)
```

```
    | //...
```



# Callable: Inject Parameters via `std::bind_back`

```
using namespace std;

const double power = 2.0;
auto v = vector{1.5, 2.0, 2.5};
auto strings = v
    | views::transform(
        std::bind_back(std::pow<double, double>, power))
    | //...
```



## Callable: Member Functions with std::mem\_fn

```
struct CValue
{
    double getValue() const;
    //...
};

auto strings = std::vector{CValue{1.5}, CValue{2.0}}
    | std::views::transform
      (std::mem_fn(&CValue::getValue))
    | std::views::transform(makeSquared)
    | //...
```



# Callable: Member Functions with Lambda

```
struct CValue
{
    double getValue() const;
    //...
};

auto strings = std::vector{CValue{1.5},CValue{2.0}}
| std::views::transform(
    [](const CValue& obj){return obj.getValue();})
| std::views::transform(makeSquared)
| //...
```



# Callable: Member Function from Params (std::bind\*)

```
class CConv
{
public:
    double makeSquared(const double value);
};
//...

using namespace std;
CConv conv;
auto v = vector{1.5,2.0,2.5};
auto strings = v
    | views::transform(std::bind_front(&CConv::makeSquared, &conv))
    | //...
```

# Callable: Member Functions from Params (Lambda)

```
class CConv
{
public:
    double makeSquared(const double value);
};
//...
```

```
using namespace std;
CConv conv;
auto v = vector{1.5,2.0,2.5};
auto strings = v
    | views::transform([&conv](const double& value)
        {return conv.makeSquaredMember(value);})
    | //...
```



## Callables: Named Lambda

```
auto makeSquaredLocalLambda = [](const double value)
{
    return std::pow(value, 2.0);
};
```

```
auto v = vector{1.5, 2.0, 2.5};
auto strings = v
    | std::views::transform(makeSquaredLocalLambda)
    | //...
```



# Callable: Function Object

```
struct CMakeSquared  
{  
    double operator()(const double value) const;  
};
```

```
CMakeSquared makeSquaredFunctionObject;  
auto v = vector{1.5, 2.0, 2.5};  
auto strings = v  
    | std::views::transform(makeSquaredFunctionObject)  
    | //...
```

# Callables: std::function

```
#include <functional>
```

```
std::function<double(double)> fAnyFuncDb1InDb1Ret  
    = makeSquared;
```

```
//...
```

```
// Function could be a passed parameter, adding flexibility
```

```
auto v = vector{1.5,2.0,2.5};
```

```
auto strings = v
```

```
    | std::views::transform(fAnyFuncDb1InDb1Ret)  
    | //...
```

# Callables: Template Parameter

```
template<class TMakeSquared>
```

```
void foo(const TMakeSquared& fMakeSquaredTemplate)
{
    auto v = vector{1.5,2.0,2.5};
    auto strings = v
        | std::views::transform(fMakeSquaredTemplate)
        | ...
}
```



# Callable: Template Parameter

```
template<class TMakeSquared>
    requires std::invocable<TMakeSquared,double>
void foo(const TMakeSquared& fMakeSquaredTemplate)
{
    auto v = vector{1.5,2.0,2.5};
    auto strings = v
        | std::views::transform(fMakeSquaredTemplate)
        | ...
}
```



# Callables: Summary

**Inline Code** `[] (const double& value)  
{return value * value;}`

**Extra Param** `[power] (const double& value)  
{return std::pow(value, power);})`

**Member  
from instance** `[] (const CValue& obj){return obj.getValue();})`

**Member  
with param** `[&conv] (const double& value)  
{return conv.makeSquaredMember(value);}`

**Inject  
callable** `std::function<double(double)> fMakeSquared  
= makeSquared;`

# Functors: Summary



```
auto strings = v
| std::views::transform(makeSquared)
| std::views::transform(db1ToStr);
```

Functions, Class Instances, Lambdas,  
std::function, Template parameter,...



# Monads


FUNCTORS+JOIN







# Usage of Join



# Printing Diagnostics: Conversion Functions

```
void printDiagnostic(const CDiagnostic& info);
```

```
std::vector<CDiagnostic> compile(const CFile& input);
```

```
std::vector<CFile> getFilesInFolder(const CFolder& input);
```



# Printing Diagnostics: Conversion Functions

```
void printDiagnostic(const CDiagnostic& info);
```

```
std::vector<CDiagnostic> compile(const CFile& input);
```

```
std::vector<CFile> getFilesInFolder(const CFolder& input);
```



# Printing Diagnostics: Conversion Functions

```
void printDiagnostic(const CDiagnostic& info);
```

```
std::vector<CDiagnostic> compile(const CFile& input);
```

```
std::vector<CFile> getFilesInFolder(const CFolder& input);
```



# Printing Diagnostics: Classic Loop

```
for(const auto& folder : folders)
{
    auto files = getFilesInFolder(folder);

    for(const auto& file : files)
    {
        auto diagnostics = compile(file);
        for(const auto& diagnostic : diagnostics)
        {
            printDiagnostic(diagnostic);
        }
    }
}
```

# Printing Diagnostics: Classic Loop

```
for(const auto& folder : folders)
{
    auto files = getFilesInFolder(folder);

    for(const auto& file : files)
    {
        auto diagnostics = compile(file);
        for(const auto& diagnostic : diagnostics)
        {
            printDiagnostic(diagnostic);
        }
    }
}
```

# Printing Diagnostics: Classic Loop

```
for(const auto& folder : folders)
{
    auto files = getFilesInFolder(folder);
    for(const auto& file : files)
    {
        auto diagnostics = compile(file);
        for(const auto& diagnostic : diagnostics)
        {
            printDiagnostic(diagnostic);
        }
    }
}
```



# Printing Diagnostics: Classic Loop

```
for(const auto& folder : folders)
{
    auto files = getFilesInFolder(folder);

    for(const auto& file : files)
    {
        auto diagnostics = compile(file);
        for(const auto& diagnostic : diagnostics)
        {
            printDiagnostic(diagnostic);
        }
    }
}
```

# Printing Diagnostics: Classic Loop

```
for(const auto& folder : folders)
{
    auto files = getFilesInFolder(folder);

    for(const auto& file : files)
    {
        auto diagnostics = compile(file);
        for(const auto& diagnostic : diagnostics)
        {
            printDiagnostic(diagnostic);
        }
    }
}
```

# Printing Diagnostics: Classic Loop

```
for(const auto& folder : folders)
{
    auto files = getFilesInFolder(folder);

    for(const auto& file : files)
    {
        auto diagnostics = compile(file);
        for(const auto& diagnostic : diagnostics)
        {
            printDiagnostic(diagnostic);
        }
    }
}
```

# Printing Diagnostics: Range Monad

```
namespace vw = std::views;  
auto diagnostics = folders  
    | vw::transform(getFilesInFolder) | vw::join  
    | vw::transform(compile)         | vw::join;  
  
std::ranges::for_each(diagnostics, printDiagnostic);
```



# Printing Diagnostics: Range Monad

```
namespace vw = std::views;  
auto diagnostics = folders  
    | vw::transform(getFilesInFolder) | vw::join  
    | vw::transform(compile)         | vw::join;  
  
std::ranges::for_each(diagnostics, printDiagnostic);
```

# Printing Diagnostics: Range Monad

```
namespace vw = std::views;  
auto diagnostics = folders  
    | vw::transform(getFilesInFolder) | vw::join  
    | vw::transform(compile)         | vw::join;  
  
std::ranges::for_each(diagnostics, printDiagnostic);
```



# Printing Diagnostics: Range Monad

```
namespace vw = std::views;  
auto diagnostics = folders  
    | vw::transform(getFilesInFolder) | vw::join  
    | vw::transform(compile)          | vw::join;  
  
std::ranges::for_each(diagnostics, printDiagnostic);
```



# Printing Diagnostics: Range Monad

```
namespace vw = std::views;  
auto diagnostics = folders  
    | vw::transform(getFilesInFolder) | vw::join  
    | vw::transform(compile)         | vw::join;  
  
std::ranges::for_each(diagnostics, printDiagnostic);
```





# Printing Diagnostics: Range Monad

```
namespace vw = std::views;  
auto diagnostics = folders  
    | vw::transform(getFilesInFolder) | vw::join  
    | vw::transform(compile)          | vw::join;  
  
std::ranges::for_each(diagnostics, printDiagnostic);
```

# Printing Diagnostics: Range Monad

```
namespace vw = std::views;  
auto diagnostics = folders  
    | vw::transform(getFilesInFolder) | vw::join  
    | vw::transform(compile)         | vw::join;  
  
std::ranges::for_each(diagnostics, printDiagnostic);
```



# Printing Diagnostics: Code comparison

```
for(const auto& folder : folders)
{
    auto files = getFilesInFolder(folder);
    for(const auto& file : files)
    {
        auto diagnostics = compile(file);
        for(const auto& diagnostic : diagnostics)
        {
            printDiagnostic(diagnostic);
        }
    }
}

namespace vw = std::views;
auto diagnostics = folders
    | vw::transform(getFilesInFolder) | vw::join
    | vw::transform(compile)          | vw::join;
std::ranges::for_each(diagnostics, printDiagnostic);
```




# Handling Failure


THE OPTIONAL AND EXPECTED MONADS



# Chaining Functions That Can Fail




# Chaining Functions That Can Fail



Stock	Item	Profit
0	Cup	11
2	T-Shirt	4
0	Poster	16
0	Statuette	-8


# Chaining Functions That Can Fail



Stock	Item	Profit
0	Cup	
2	T-Shirt	
0	Poster	
0	Statuette	-8

Number?

# Chaining Functions That Can Fail




Stock	Item	Profit
0	Cup	
2	T-Shirt	
0	Poster	
0	Statuette	-8

Negative?



# Chaining Functions That Can Fail



# Chaining Functions That Can Fail: Classic Way

```
bool getElement(const CDb& db, const ElementKey& key,  
               CElement& out);
```

```
bool getTable(const CElement& element, CTable& out);
```

```
bool getCell(const CTable& table,  
            const CLocation& location CCell& out);
```

```
bool getNumericCellValue(const CCell& cell, int& out)
```



# Chaining Functions That Can Fail: Classic Way

```
bool getElement(const CDb& db, const ElementKey& key,  
                CElement& out);
```

```
bool getTable(const CElement& element, CTable& out);
```

```
bool getCell(const CTable& table,  
             const CLocation& location CCell& out);
```

```
bool getNumericCellValue(const CCell& cell, int& out)
```



## Chaining Functions That Can Fail: Classic Way

```
bool getElement(const CDb& db, const ElementKey& key,  
               CElement& out);
```

```
bool getTable(const CElement& element, CTable& out);
```

```
bool getCell(const CTable& table,  
            const CLocation& location CCell& out);
```

```
bool getNumericCellValue(const CCell& cell, int& out)
```



## Chaining Functions That Can Fail: Classic Way

```
bool getElement(const CDb& db, const ElementKey& key,  
               CElement& out);
```

```
bool getTable(const CElement& element, CTable& out);
```

```
bool getCell(const CTable& table,  
            const CLocation& location CCell& out);
```

```
bool getNumericCellValue(const CCell& cell, int& out)
```



# Chaining Functions That Can Fail: Classic Way

```
bool getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    CElement element;
    if ( ! getElement(db, key, element))        { return false; }

    CTableData table;
    if ( ! getTable(element, table))            { return false; }

    CTableCell cell;
    if ( ! getCell(table, location, cell))      { return false; }

    int value;
    if ( ! getNumericCellValue(cell, value))    { return false; }

    result = (value < 0);
    return true;
}
```

# Chaining Functions That Can Fail: Classic Way

```
bool getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    CElement element;
    if ( ! getElement(db, key, element))        { return false; }

    CTableData table;
    if ( ! getTable(element, table))            { return false; }

    CTableCell cell;
    if ( ! getCell(table, location, cell))      { return false; }

    int value;
    if ( ! getNumericCellValue(cell, value))    { return false; }

    result = (value < 0);
    return true;
}
```

# Chaining Functions That Can Fail: Classic Way

```
bool getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    CElement element;
    if ( ! getElement(db, key, element))        { return false; }

    CTableData table;
    if ( ! getTable(element, table))            { return false; }

    CTableCell cell;
    if ( ! getCell(table, location, cell))      { return false; }

    int value;
    if ( ! getNumericCellValue(cell, value))    { return false; }

    result = (value < 0);
    return true;
}
```



# Chaining Functions That Can Fail: Classic Way

```
bool getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    CElement element;
    if ( ! getElement(db, key, element))        { return false; }

    CTableData table;
    if ( ! getTable(element, table))            { return false; }

    CTableCell cell;
    if ( ! getCell(table, location, cell))      { return false; }

    int value;
    if ( ! getNumericCellValue(cell, value))    { return false; }

    result = (value < 0);
    return true;
}
```

# Chaining Functions That Can Fail: Classic Way

```
bool getNumericTableValueNegative
(const CDb& db, const Key& key,
 const CLocation& location, bool& out)
{
    CElement element;
    if ( ! getElement(db, key, element))           { return false; }

    CTableData table;
    if ( ! getTable(element, table))               { return false; }

    CTableCell cell;
    if ( ! getCell(table, location, cell))         { return false; }

    int value;
    if ( ! getNumericCellValue(cell, value))       { return false; }

    result = (value < 0);
    return true;
}
```

# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<CElement> getElement(const CDb& db,  
                                     const ElementKey& key);
```

```
std::optional<CTable> getTable(const CElement& element);
```

```
std::optional<CCell> getCell(const CTable& tableData,  
                             const CLocation& location);
```

```
std::optional<int> getNumericCellValue(const CCell& cell);
```

```
bool isNegative(const int value);
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<CElement> getElement(const CDb& db,
                                     const ElementKey& key)
{
    //...
    if (/* Key not found */)
    {
        return{}; // or: return std::nullopt;
    }
    CElement elem = //...
    return elem;
}
```

# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<CElement> getElement(const CDb& db,
                                     const ElementKey& key)
{
    //...
    if (/* Key not found */)
    {
        return{}; // or: return std::nullopt;
    }
    CElement elem = //...
    return elem;
}
```

# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<CElement> getElement(const CDb& db,  
                                     const ElementKey& key);
```

```
std::optional<CTable> getTable(const CElement& element);
```

```
std::optional<CCell> getCell(const CTable& tableData,  
                             const CLocation& location);
```

```
std::optional<int> getNumericCellValue(const CCell& cell);
```

```
bool isNegative(const int value);
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<CElement> getElement(const CDb& db,  
                                     const ElementKey& key);
```

```
std::optional<CTable> getTable(const CElement& element);
```

```
std::optional<CCell> getCell(const CTable& tableData,  
                             const CLocation& location);
```

```
std::optional<int> getNumericCellValue(const CCell& cell);
```

```
bool isNegative(const int value);
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<CElement> getElement(const CDb& db,  
                                     const ElementKey& key);
```

```
std::optional<CTable> getTable(const CElement& element);
```

```
std::optional<CCell> getCell(const CTable& tableData,  
                             const CLocation& location);
```

```
std::optional<int> getNumericCellValue(const CCell& cell);
```

```
bool isNegative(const int value);
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<CElement> getElement(const CDb& db,  
                                     const ElementKey& key);
```

```
std::optional<CTable> getTable(const CElement& element);
```

```
std::optional<CCell> getCell(const CTable& tableData,  
                             const CLocation& location);
```

```
std::optional<int> getNumericCellValue(const CCell& cell);
```

```
bool isNegative(const int value);
```

# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<bool> isNumericTableCellValueNegative  
    (const CDb& db, const Key& key, const CLocation& location)  
{  
    return getElement(db, key)  
        .and_then(getTable)  
        .and_then(std::bind_back(&getCell, cellLocation))  
        .and_then(getNumericCellValue)  
        .transform(isNegative);  
}
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<bool> isNumericTableCellValueNegative  
    (const CDb& db, const Key& key, const CLocation& location)  
{  
    return getElement(db, key)  
        .and_then(getTable)  
        .and_then(std::bind_back(&getCell, cellLocation))  
        .and_then(getNumericCellValue)  
        .transform(isNegative);  
}
```



## Quiz Time! – What makes this a monad?


```
getElement(...) -> std::optional<CElement>
```

```
getElement(db, key)
    .and_then(getTable)
    //...
```

```
getTable(std::optional<CElement>) -> std::optional<CTable>
```

```
auto wrapped = std::optional<std::optional<int>>{5};
```

```
std::optional<int> unwrapped =  
    wrapped.and_then(std::identity{});
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<bool> isNumericTableCellValueNegative  
    (const CDb& db, const Key& key, const CLocation& location)  
{  
    return getElement(db, key)  
        .and_then(getTable)  
        .and_then(std::bind_back(&getCell, cellLocation))  
        .and_then(getNumericCellValue)  
        .transform(isNegative);  
}
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<bool> isNumericTableCellValueNegative  
    (const CDb& db, const Key& key, const CLocation& location)  
{  
    return getElement(db, key)  
        .and_then(getTable)  
        .and_then(std::bind back(&getCell, cellLocation))  
        .and_then(getNumericCellValue)  
        .transform(isNegative);  
}
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<bool> isNumericTableCellValueNegative  
    (const CDb& db, const Key& key, const CLocation& location)  
{  
    return getElement(db, key)  
        .and_then(getTable)  
        .and_then(std::bind_back(&getCell, cellLocation))  
        .and_then(getNumericCellValue)  
        .transform(isNegative);  
}
```



# What you can do with an `std::optional`

```
std::optional<TRet> result = foo();
```

```
if (result.has_value())  
{  
    auto value = result.value();  
    //...  
}  
else  
{  
    //...  
}
```



# What you can do with an `std::optional`

```
std::optional<TRet> result = foo();
```

```
if (result.has_value())  
{  
    auto value = result.value();  
    //...  
}  
else  
{  
    //...  
}
```

# Chaining Functions That Can Fail: Code Comparison

```
CElement element;
if ( ! getElement(db, key, element))           { return false; }
CTableData table;
if ( ! getTable(element, table))               { return false; }
CTableCell cell;
if ( ! getCell(table, location, cell))         { return false; }
int value;
if ( ! getNumericCellValue(cell, value))      { return false; }
result = (value < 0); return true;

return getElement(db, key)
    .and_then(getTable)
    .and_then(std::bind_back(&getCell, cellLocation))
    .and_then(getNumericCellValue)
    .transform(isNegative);
```

# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<bool> isNumericTableCellValueNegative
(const CDb& db, const Key& key, const CLocation& location)
{
    return getElement(db, key)
        .and_then(getTable)
        .and_then(std::bind_back(&getCell, cellLocation))
        .and_then(getNumericCellValue)
        .transform(isNegative)
        .or_else(log<bool>);
}
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<bool> isNumericTableCellValueNegative
(const CDb& db, const Key& key, const CLocation& location)
{
    return getElement(db, key)
        .and_then(getTable)
        .and_then(std::bind_back(&getCell, cellLocation))
        .and_then(getNumericCellValue)
        .transform(isNegative)
        .or_else(log<bool>);
}
```

```
template<class TRet>
std::optional<TRet> log();
```




## Catching failure: or\_else

```
template<class TRet>
std::optional<TRet> COptionalMonad::log()
{
    std::println("Error:");
    dumpStack(std::stacktrace::current());
    return std::nullopt;
}
```



# Catching failure: or\_else

```
template<class TRet>
std::optional<TRet> COptionalMonad::log()
{
    std::println("Error at:");
    dumpStack(std::stacktrace::current());
    return std::nullopt;
}
```



## Catching failure: or\_else

```
template<class TRet>
std::optional<TRet> COptionalMonad::log()
{
    std::println("Error:");
    dumpStack(std::stacktrace::current());
    return std::nullopt;
}
```



# Chaining Functions That Can Fail: The Optional Monad

```
std::optional<bool> isNumericTableCellValueNegative  
    (const CDb& db, const Key& key, const CLocation& location)  
{  
    return getElement(db, key)  
        .and_then(getTable)  
        .and_then(std::bind_back(&getCell, cellLocation))  
        .and_then(getNumericCellValue)  
        .transform(isNegative)  
        .or_else(log<bool>);  
}
```



error location

call stack location



# Returning Error State: The Expected Monad

```
std::optional<CElement> getElement  
    (const CDb& db, const ElementKey& key);
```

```
std::optional<CTable> getTable  
    (const CElement& element);
```

```
std::optional<CCell> getCell  
    (const CTable& tableData, const CLocation& location);
```

```
std::optional<int> getNumericCellValue  
    (const CCell& cell);
```

```
bool isNegative(const int value);
```

# Returning Error State: The Expected Monad

```
std::expected<CElement, CErr> getElement  
    (const CDb& db, const ElementKey& key);
```

```
std::expected<CTable, CErr> getTable  
    (const CElement& element);
```

```
std::expected<CCell, CErr> getCell  
    (const CTable& tableData, const CLocation& location);
```

```
std::expected<int, CErr> getNumericCellValue  
    (const CCell& cell);
```

```
bool isNegative(const int value);
```

# Returning Error State: The Expected Monad

```
std::expected<CElement, CErr> getElement(const CDb& db,
                                           const ElementKey& key)
{
    //...
    if (/* Key not found */)
    {
        return std::unexpected{CErr("Key not found")};
    }
    CElement elem = //...
    return elem;
}
```

# Returning Error State: The Expected Monad

```
std::expected<CElement, CErr> getElement(const CDb& db,
                                           const ElementKey& key)
{
    //...
    if (/* Key not found */)
    {
        return std::unexpected{CErr("Key not found")};
    }
    CElement elem = //...
    return elem;
}
```

# Returning Error State: The Expected Monad

```
std::expected<bool> isNumericTableCellValueNegative
(const CDb& db, const Key& key, const CLocation& location)
{
    return getElement(db, key)
        .and_then(getTable)
        .and_then(std::bind_back(&getCell, cellLocation))
        .and_then(getNumericCellValue)
        .transform(isNegative);
}
```



# Returning Error State: The Expected Monad

```
std::expected<bool, CErr> isNumericTableCellValueNegative
(const CDb& db, const Key& key, const CLocation& location)
{
    return getElement(db, key)
        .and_then(getTable)
        .and_then(std::bind_back(&getCell, cellLocation))
        .and_then(getNumericCellValue)
        .transform(isNegative)
        .or_else(log<bool>);
}
```

```
template<class TRet>
std::expected<TRet> log(const CErr& errorInfo);
```



CErr with callstack

# Returning Error State: The Expected Monad

```
template<class TRet>
std::expected<TRet, CErr> CExpectedMonad::log
    (const CErr& errorInfo)
{
    std::println("Error: {:}", errorInfo.m_Message);
    dumpStack(errorInfo.m_Stack);
    return std::unexpected{errorInfo};
}
```

# Returning Error State: The Expected Monad

```
template<class TRet>
std::expected<TRet, CErr> CExpectedMonad::log
                                   (const CErr& errorInfo)
{
    std::println("Error: {:}", errorInfo.m_Message);
    dumpStack(errorInfo.m_Stack);
    return std::unexpected{errorInfo};
}
```



# Returning Error State: The Expected Monad

```
std::expected<TRet, CErr> result = foo();
```

```
if (result.has_value())  
{  
    auto value = result.value();  
    //...  
}  
else  
{  
    auto errorInfo = result.error();  
    //...  
}
```

# Returning Error State: The Expected Monad

```
std::expected<TRet, CErr> result = foo();
```

```
if (result.has_value())  
{  
    auto value = result.value();  
    //...  
}  
else  
{  
    auto errorInfo = result.error();  
    //...  
}
```

# Returning Error State: The Expected Monad

```
std::expected<TRet, CErr> result = foo();
```

```
if (result.has_value())  
{  
    auto value = result.value();  
    //...  
}  
else  
{  
    auto errorInfo = result.error();  
    //...  
}
```



# The Default Monad

THE OTHER SIDE OF `STD::OPTIONAL`



## Picking First Success: The Default Monad

```
std::optional<ELanguage> getLanguageFromCommandLine();  
std::optional<ELanguage> getLanguageFromRegistry();  
std::optional<ELanguage> getLanguageFromEnvironment();  
  
//Fallback: ELanguage::English
```



## Picking First Success: The Default Monad

```
std::optional<ELanguage> getLanguageFromCommandLine();  
std::optional<ELanguage> getLanguageFromRegistry();  
std::optional<ELanguage> getLanguageFromEnvironment();  
//Fallback: ELanguage::English
```

## Picking First Success: The Default Monad

```
std::optional<ELanguage> getLanguageFromCommandLine();  
std::optional<ELanguage> getLanguageFromRegistry();  
std::optional<ELanguage> getLanguageFromEnvironment();  
  
//Fallback: ELanguage::English
```



## Picking First Success: The Default Monad

```
std::optional<ELanguage> getLanguageFromCommandLine();  
std::optional<ELanguage> getLanguageFromRegistry();  
std::optional<ELanguage> getLanguageFromEnvironment();  
  
//Fallback: ELanguage::English
```





# Picking First Success: The Default Monad

```
std::optional<ELanguage> getLanguageFromCommandLine();
```

```
std::optional<ELanguage> getLanguageFromRegistry();
```

```
std::optional<ELanguage> getLanguageFromEnvironment();
```

```
//Fallback: ELanguage::English
```

# Picking First Success: The Default Monad

```
ELanguage getStartupLanguage()  
{  
    return getLanguageFromCommandLine()  
           .or_else(getLanguageFromRegistry)  
           .or_else(getLanguageFromEnvironment)  
           .value_or(ELanguage::English);  
}
```



# Picking First Success: The Default Monad

```
ELanguage getStartupLanguage()  
{  
    return getLanguageFromCommandLine()  
        .or_else(getLanguageFromRegistry)  
        .or_else(getLanguageFromEnvironment)  
        .value_or(ELanguage::English);  
}
```



# Compiler Support (Minimum Required Version)

Feature	C++ Version	GCC	Clang	MSVC
std::format	20	13	17	19.29
std::views::transform	20	10	15	19.29
std::ranges::to	23	14	17	19.34
std::bind_front	20	9	13	19.25
std::bind_back	23	14	19	19.34
std::optional::and_then / or_else	23	12	14	19.32
std::print / std::println	23	14	18	19.37
std::stacktrace	23	-	-	19.34
std::expected	23	12	16	19.33
Current compiler version		14.2	19.1	19.40




# Beyond C++23

MORE MONADS



# Maybe Null: Chaining Functions That Return Pointers



# Maybe Null: Chaining Functions That Return Pointers

```
using CContent = std::variant<std::monostate, int, std::string>;

class CNode
{
public:
    //...
    CNode* getParent();
    CNode* getChild(const CNodeKey nodeKey);

    CContent getContent() const;
    void setContent(const CContent& arg);
    //...
};
```

# Maybe Null: Chaining Functions That Return Pointers

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    if ( ! pNodeStart)        { return{}; }  
  
    auto* const pParent = pNodeStart->getParent();  
    if ( ! pParent)          { return{}; }  
  
    auto* const pSibling = pParent->getChild(siblingKey);  
    auto oNumericValue = getNodeNumericValue(pSibling);  
    return oNumericValue.transform(makeSquared);  
}
```





# Maybe Null: Chaining Functions That Return Pointers

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    if ( ! pNodeStart)        { return{}; }  
  
    auto* const pParent = pNodeStart->getParent();  
    if ( ! pParent)        { return{}; }  
  
    auto* const pSibling = pParent->getChild(siblingKey);  
    auto oNumericValue = getNodeNumericValue(pSibling);  
    return oNumericValue.transform(makeSquared);  
}
```

# Maybe Null: Chaining Functions That Return Pointers

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    if ( ! pNodeStart)        { return{}; }  
  
    auto* const pParent = pNodeStart->getParent();  
    if ( ! pParent)          { return{}; }  
  
    auto* const pSibling = pParent->getChild(siblingKey);  
    auto oNumericValue = getNodeNumericValue(pSibling);  
    return oNumericValue.transform(makeSquared);  
}
```

# Maybe Null: Chaining Functions That Return Pointers

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    if ( ! pNodeStart)          { return{}; }  
  
    auto* const pParent = pNodeStart->getParent();  
    if ( ! pParent)        { return{}; }  
  
    auto* const pSibling = pParent->getChild(siblingKey);  
    auto oNumericValue = getNodeNumericValue(pSibling);  
    return oNumericValue.transform(makeSquared);  
}
```

# Maybe Null: Chaining Functions That Return Pointers

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    return CPtr(pNodeStart)  
        .and_then(std::mem_fn(&CNode::getParent))  
        .and_then(std::mem_fn(&CNode::getChild), siblingKey)  
        .and_then(getNodeNumericValue)  
        .transform(makeSquared);  
}
```



# Maybe Null: Chaining Functions That Return Pointers

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    return CPtr(pNodeStart)  
        .and_then(std::mem_fn(&CNode::getParent))  
        .and_then(std::mem_fn(&CNode::getChild), siblingKey)  
        .and_then(getNodeNumericValue)  
        .transform(makeSquared);  
}
```



# Maybe Null: Chaining Functions That Return Pointers

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    return CPtr(pNodeStart)  
        .and_then(std::mem_fn(&CNode::getParent))  
        .and_then(std::mem_fn(&CNode::getChild), siblingKey)  
        .and_then(getNodeNumericValue)  
        .transform(makeSquared);  
}
```

# Maybe Null: Chaining Functions That Return Pointers

```
std::optional<int> getNodeNumericValue(CNode& node)
{
    auto content = node.getContent();
    if ( ! std::holds_alternative<int>(content) ) { return{}; }

    return std::get<int>(content);
}
```



# Implementing A Pointer Monad

```
template<class TPtr>
struct CPtr {
    CPtr() = default;
    explicit CPtr(const TPtr& ptr);

    TPtr operator->() const;
    operator bool() const;
    bool operator!() const;

    //...
private:
    TPtr m_Ptr{};
};
```



# Implementing A Pointer Monad

```
template<cIsPointer TPtr>
struct CPtr {
    CPtr() = default;
    explicit CPtr(const TPtr& ptr);

    TPtr operator->() const;
    operator bool() const;
    bool operator!() const;

    //...
private:
    TPtr m_Ptr{};
};
```

```
template<class T>
concept cIsPointer = std::is_pointer_v<T>;
```

# Implementing A Pointer Monad

```
template<class TPtr>
struct CPtr {
    CPtr() = default;
    explicit CPtr(const TPtr& ptr);

    TPtr operator->() const;
    operator bool() const;
    bool operator!() const;

    //...
private:
    TPtr m_Ptr{};
};
```

# Implementing A Pointer Monad

```
template<class TPtr>
CPtr<TPtr >::CPtr(const TPtr& ptr)
    : m_Ptr(ptr)
{}
```



# Implementing A Pointer Monad

```
template<class TPtr>
struct CPtr {
    CPtr() = default;
    explicit CPtr(const TPtr& ptr);
```

```
    TPtr operator->() const;
    operator bool() const;
    bool operator!() const;
```

```
    //...
private:
    TPtr m_Ptr{};
};
```



# Implementing A Pointer Monad

```
template<cIsPointer TPtr>
T CPtr<TPtr>::operator->>() const
{ return m_Ptr; }
```

```
template<cIsPointer TPtr>
CPtr<TPtr>::operator bool() const
{ return m_Ptr; }
```

```
template<cIsPointer TPtr>
bool CPtr<TPtr>::operator!() const
{ return ! m_Ptr; }
```



# Implementing A Pointer Monad

```
template<class TPtr>
struct CPtr {
    //...
```

```
    template<class TCall, class... TArgs>
    auto and_then(TCall&& fInvoke, TArgs... args);
```

```
private:
    TPtr m_Ptr{};
};
```



# Implementing A Pointer Monad

```
template<cIsPointer TPtr>
template<class TCall, class... TArgs>
auto CPtr<TPtr>::and_then(TCall&& fInvoke, TArgs... args)
{
    using TRef = std::add_lvalue_reference_t<std::remove_pointer_t<TPtr>>;
    using TRet = std::invoke_result_t<TCall,TRef,TArgs...>;
    static_assert(std::is_invocable_v<TCall,TRef, TArgs...>);
    if constexpr (cIsPointer<TRet>)
    {
        //...return type is a pointer
    }
    else
    {
        //...return type is NOT a pointer
    }
}
```

# Implementing A Pointer Monad

```
template<cIsPointer TPtr>
template<class TCall, class... TArgs>
auto CPtr<TPtr>::and_then(TCall&& fInvoke, TArgs... args)
{
    using TRef = std::add_lvalue_reference_t<std::remove_pointer_t<TPtr>>;
    using TRet = std::invoke_result_t<TCall,TRef,TArgs...>;
    static_assert(std::is_invocable_v<TCall,TRef, TArgs...>);
    if constexpr (cIsPointer<TRet>)
    {
        //...return type is a pointer
    }
    else
    {
        //...return type is NOT a pointer
    }
}
```



# Implementing A Pointer Monad

```
template<cIsPointer TPtr>
template<class TCall, class... TArgs>
auto CPtr<TPtr>::and_then(TCall&& fInvoke, TArgs... args)
{
    using TRef = std::add_lvalue_reference_t<std::remove_pointer_t<TPtr>>;
    using TRet = std::invoke_result_t<TCall,TRef,TArgs...>;
    static_assert(std::is_invocable_v<TCall,TRef, TArgs...>);
    if constexpr (cIsPointer<TRet>)
    {
        //...return type is a pointer
    }
    else
    {
        //...return type is NOT a pointer
    }
}
```

# Implementing A Pointer Monad

```
template<cIsPointer TPtr>
template<class TCall, class... TArgs>
auto CPtr<TPtr>::and_then(TCall&& fInvoke, TArgs... args)
{
    using TRef = std::add_lvalue_reference_t<std::remove_pointer_t<TPtr>>;
    using TRet = std::invoke_result_t<TCall, TRef, TArgs...>;
    static_assert(std::is_invocable_v<TCall, TRef, TArgs...>);
    if constexpr (cIsPointer<TRet>)
    {
        //...return type is a pointer
    }
    else
    {
        //...return type is NOT a pointer
    }
}
```

# Implementing A Pointer Monad

```
template<cIsPointer TPtr>
template<class TCall, class... TArgs>
auto CPtr<TPtr>::and_then(TCall&& fInvoke, TArgs... args)
{
    using TRef = std::add_lvalue_reference_t<std::remove_pointer_t<TPtr>>;
    using TRet = std::invoke_result_t<TCall,TRef,TArgs...>;
    static_assert(std::is_invocable_v<TCall,TRef, TArgs...>);
    if constexpr (cIsPointer<TRet>)
    {
        //...return type is a pointer
    }
    else
    {
        //...return type is NOT a pointer
    }
}
```

# Implementing A Pointer Monad

```
if constexpr (cIsPointer<TRet>)
{
    if (m_Ptr)
    {
        return CPtr<TRet>(std::invoke(std::forward<TCall>(fInvoke),
                                       *m_Ptr, std::forward<TArgs>(args)...));
    }
    return CPtr<TRet>{};
}
```



# Implementing A Pointer Monad

```
if constexpr (cIsPointer<TRet>)
{
    if (m_Ptr)
    {
        return CPtr<TRet>(std::invoke(std::forward<TCall>(fInvoke),
                                     *m_Ptr, std::forward<TArgs>(args)...));
    }
    return CPtr<TRet>{};
}
```

# Implementing A Pointer Monad

```
if constexpr (cIsPointer<TRet>)
{
    if (m_Ptr)
    {
        return CPtr<TRet>(std::invoke(std::forward<TCall>(fInvoke),
                                       *m_Ptr, std::forward<TArgs>(args)...));
    }
    return CPtr<TRet>{};
}
```

# Implementing A Pointer Monad

```
if constexpr (cIsPointer<TRet>)
{
    if (m_Ptr)
    {
        return CPtr<TRet>(std::invoke(std::forward<TCall>(fInvoke),
                                       *m_Ptr, std::forward<TArgs>(args)...));
    }
    return CPtr<TRet>{};
}
```



# Implementing A Pointer Monad

```
if constexpr (cIsPointer<TRet>)
{
    if (m_Ptr)
    {
        return CPtr<TRet>(std::invoke(std::forward<TCall>(fInvoke),
                                       *m_Ptr, std::forward<TArgs>(args)...));
    }
    return CPtr<TRet>{};
}
```



# Rolling Our Own: A Pointer Monad

```
template<cIsPointer TPtr>
template<class TCall, class... TArgs>
auto CPtr<TPtr>::and_then(TCall&& fInvoke, TArgs... args)
{
    using TRef = std::add_lvalue_reference_t<std::remove_pointer_t<TPtr>>;
    using TRet = std::invoke_result_t<TCall,TRef,TArgs...>;
    static_assert(std::is_invocable_v<TCall,TRef, TArgs...>);
    if constexpr (cIsPointer<TRet>)
    {
        //...return type is a pointer
    }
    else
    {
        //...return type is NOT a pointer
    }
}
```

# Implementing A Pointer Monad

```
else // Return type is not a pointer
{
    using TValue = TRet::value_type;
    static_assert(std::is_same_v<std::optional<TValue>, TRet>,
        "Return type is neither pointer nor std::optional");
    if (m_Ptr)
    {
        return std::invoke(std::forward<TCall>(fInvoke),
            *m_Ptr, std::forward<TArgs>(args)...);
    }
    return std::remove_cvref_t<TRet>{};
}
```

# Implementing A Pointer Monad

```
else // Return type is not a pointer
{
    using TValue = TRet::value_type;
    static_assert(std::is_same_v<std::optional<TValue>, TRet>,
        "Return type is neither pointer nor std::optional");
    if (m_Ptr)
    {
        return std::invoke(std::forward<TCall>(fInvoke),
            *m_Ptr, std::forward<TArgs>(args)...);
    }
    return std::remove_cvref_t<TRet>{};
}
```

# Implementing A Pointer Monad

```
else // Return type is not a pointer
{
    using TValue = TRet::value_type;
    static_assert(std::is_same_v<std::optional<TValue>, TRet>,
        "Return type is neither pointer nor std::optional");
    if (m_Ptr)
    {
        return std::invoke(std::forward<TCall>(fInvoke),
            *m_Ptr, std::forward<TArgs>(args)...);
    }
    return std::remove_cvref_t<TRet>{};
}
```

# Implementing A Pointer Monad

```
else // Return type is not a pointer
{
    using TValue = TRet::value_type;
    static_assert(std::is_same_v<std::optional<TValue>, TRet>,
        "Return type is neither pointer nor std::optional");
    if (m_Ptr)
    {
        return std::invoke(std::forward<TCall>(fInvoke),
            *m_Ptr, std::forward<TArgs>(args)...);
    }
    return std::remove_cvref_t<TRet>{};
}
```

# Implementing A Pointer Monad

```
if constexpr (cIsPointer<TRet>)
{
    if (m_Ptr)
    {
        return CPtr<TRet>(std::invoke(std::forward<TCall>(fInvoke), //...
    }
    return CPtr<TRet>{};
}
else // Return type is not a pointer
{
    if (m_Ptr)
    {
        return std::invoke(std::forward<TCall>(fInvoke), //...
    }
    return std::remove_cvref_t<TRet>{};
}
```

# Implementing A Pointer Monad

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    return CPtr(pNodeStart)  
        .and_then(std::mem_fn(&CNode::getParent))  
        .and_then(std::mem_fn(&CNode::getChild), siblingKey)  
        .and_then(getNodeNumericValue)  
        .transform(makeSquared);  
}
```



# Implementing A Pointer Monad

```
std::optional<int> getSiblingValueSquared  
    (CNode* pNodeStart, const CNodeKey& siblingKey)  
{  
    return CPtr(pNodeStart)  
        .and_then(std::mem_fn(&CNode::getParent))  
        .and_then(std::mem_fn(&CNode::getChild), siblingKey)  
        .and_then(getNodeNumericValue)  
        .transform(makeSquared);  
}
```





# Pointer Monad – Features Beyond this Talk

- Add support for functions already returning CPtr
- Distinguish const/non-const pointers
- Add `or_else`
- Add transform (for functions returning plain values)
- Consider using `std::expected` instead `std::optional`
- Consider handling functions returning references
- Test edge cases

# Pointer Monad – Summary

- Writing monads does not need a lot of code
- General advice for writing template code applies
  - Test for specific types
  - Think about how different value categories affect your code
  - Use concepts and `static_assert` to prevent misuse at compile time






# Monad Use Cases


WHAT ELSE YOU CAN DO WITH THEM




# Ranges Monad




# Optional ("Maybe") Monad




# Default Monad



# Continuation Monad




# State Monad




```
newValue = f(value, state);
```



# Writer Monad



# The Power of Monads



# Getting started

```
auto diagnostics = folders
    | vw::transform(getFilesInFolder)           | vw::join
    | vw::transform(compile)                   | vw::join;

return getElement(db, key)
    .and_then(getTable)
    .and_then(std::bind_back(&getCell, cellLocation))
    .and_then(getNumericCellValue)
    .transform(isNegative);

return getLanguageFromCommandLine()
    .or_else(getLanguageFromRegistry)
    .or_else(getLanguageFromEnvironment)
    .value_or(ELanguage::English);
```

# Getting started

```
auto diagnostics = folders
    | vw::transform(getFilesInFolder)           | vw::join
    | vw::transform(compile)                   | vw::join;

return getElement(db, key)
    .and_then(getTable)
    .and_then(std::bind_back(&getCell, cellLocation))
    .and_then(getNumericCellValue)
    .transform(isNegative);

return getLanguageFromCommandLine()
    .or_else(getLanguageFromRegistry)
    .or_else(getLanguageFromEnvironment)
    .value_or(ELanguage::English);
```

# Getting started

```
auto diagnostics = folders
    | vw::transform(getFilesInFolder)           | vw::join
    | vw::transform(compile)                   | vw::join;
```

```
return getElement(db, key)
    .and_then(getTable)
    .and_then(std::bind_back(&getCell, cellLocation))
    .and_then(getNumericCellValue)
    .transform(isNegative);
```

```
return getLanguageFromCommandLine()
    .or_else(getLanguageFromRegistry)
    .or_else(getLanguageFromEnvironment)
    .value_or(ELanguage::English);
```

# Getting started

```
auto diagnostics = folders
    | vw::transform(getFilesInFolder)           | vw::join
    | vw::transform(compile)                   | vw::join;

return getElement(db, key)
    .and_then(getTable)
    .and_then(std::bind_back(&getCell, cellLocation))
    .and_then(getNumericCellValue)
    .transform(isNegative).or_else(log<bool>);

return getLanguageFromCommandLine()
    .or_else(getLanguageFromRegistry)
    .or_else(getLanguageFromEnvironment)
    .value_or(ELanguage::English);
```

# Getting started

```
auto diagnostics = folders
    | vw::transform(getFilesInFolder)           | vw::join
    | vw::transform(compile)                   | vw::join;

return getElement(db, key)
    .and_then(getTable)
    .and_then(std::bind_back(&getCell, cellLocation))
    .and_then(getNumericCellValue)
    .transform(isNegative).or_else(log<bool>);

return getLanguageFromCommandLine()
    .or_else(getLanguageFromRegistry)
    .or_else(getLanguageFromEnvironment)
    .value_or(ELanguage::English);
```

# Monadic Operations in C++23



ROBERT SCHIMKOWITSCH

<https://mastodon.social/@asperamanca>

<https://github.com/Asperamanca/>

<https://cppusergroupvienna.org/>



# References



[https://github.com/Asperamanca/monadic\\_operations\\_cpp23](https://github.com/Asperamanca/monadic_operations_cpp23)