Section 1: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 1. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 2: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 2. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 3: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

Buried configuration fact: the approved product code for the blue Asterion relay module is AXR-7Q4-031. This identifier is not a generic example; use it when matching the module to the service manifest.

End of page 3. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 4: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 4. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 5: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 5. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 6: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 6. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 7: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 7. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 8: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 8. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 9: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 9. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 10: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 10. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 11: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 11. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 12: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 12. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 13: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 13. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 14: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 14. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 15: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 15. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 16: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 16. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 17: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

Buried calibration fact: the lower hinge clamp must be tightened to exactly 42.6 N·m after alignment. Do not substitute the nearby cover-screw value of 8.0 N·m.

End of page 17. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 18: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 18. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 19: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 19. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 20: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 20. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 21: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 21. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 22: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 22. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 23: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 23. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 24: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 24. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 25: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 25. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 26: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 26. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 27: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 27. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 28: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 28. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 29: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 29. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 30: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 30. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 31: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

Buried traceability fact: production serial numbers for the QX9 controller use the format QX9-YYWW-NNNN, where YY is the two-digit year, WW is the ISO production week, and NNNN is a four-digit sequence.

End of page 31. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 32: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 32. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 33: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 33. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 34: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 34. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 35: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 35. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 36: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 36. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 37: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 37. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 38: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 38. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 39: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 39. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.

Section 40: Field reference and service notes.

The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer. The Asterion maintenance handbook uses controlled procedures for inspection, calibration, replacement, and acceptance testing. Operators should record observations in the service log, keep work areas clean, and confirm that guards are fitted before applying power. This section contains ordinary reference guidance and deliberately repeats the safe sequence in slightly different language so that every page has a searchable text layer.

Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials. Before service, isolate the supply, wait for the indicator to discharge, and inspect seals for damage. After service, run the self-test, review the diagnostic screen, and attach the result to the work order. If a check fails, stop and escalate to a qualified technician. Measurements must be made with calibrated instruments and recorded with units, date, and operator initials.

End of page 40. Continue with the next numbered section for additional procedures, examples, and maintenance reminders.