The GummiArm

ShanghAl Lectures 2016


Dr Martin F. Stoelen



Plymouth University 2016



A developing mind requires a robust body...





Part of the **DeCoRo** Marie Curie Intra-European Fellowship at Plymouth (Stoelen & Cangelosi) Opportunities abound for soft + precise robots (?)




The GummiArm (some months ago)













http://mstoelen.github.io/GummiArm/





http://mstoelen.github.io/GummiArm/





Towards replicable robot experiments? (Bonsignorio, Hallam, del Pobil, 2007)

http://mstoelen.github.io/GummiArm/

Detailed IKEA-style build instructions


Lower arm

Required:

- 1.82x M2x8mm screws
- 2.74x M2 washers
- 3. 80x M2 nuts
- 4. 6x M2.5x12mm screws
- 5. 6x M2.5 nuts
- 6. 4x M2.5 washers
- 7. 1x M3x10mm with bearing bushing
 - 1. Screw the two elbow parts on servo 21 with M2x8mm. (Figure 1)
 - 2. Screw now the same servo to the lower plate but upside down and put a M2.5 nut in this plate. (Figure 2 and 2.5)
 - 3. Fix all the AX-18 and the AX-12 at the end of the forearm with the reinforcement plastic parts with M2x8mm. (Figure 3 and 3.5)
 - 4. Fix the wrist thank to the M3x10mm and M2x8mm screws. (Figure 4 and 4.5) 5. Fix the prepared wheels on the two middle servos and fix the muscles underneath the wrist's muscle fixer (M2.5x12mm). (Figure 5 and 5.5)







Rubbery agonist-antagonist joints



© Pearson Education Inc., 2011

Rubbery agonist-antagonist joints






© Pearson Education Inc., 2011

Rubbery agonist-antagonist joints






© Pearson Education Inc., 2011










Equilibrium point (p) and co-contraction (c)


$$lpha_{
m flexor} = p rac{\gamma}{4} - c rac{\pi}{2},$$
 $lpha_{
m extensor} = p rac{\gamma}{4} + c rac{\pi}{2}.$

p in range [-1,1]*c* in range [0,1]

Stiffness varied through co-contraction (c)









Good response even when starting "loose"


Good response even when starting "loose"



Ballistic/feedback control

Good response even when starting "loose"






Feedback control only

Ballistic/feedback control


3D printed, but not necessarily fragile




Varying stiffness helps physical interaction



https://youtu.be/QEHxqkwRZZE







Neuromechanics 2016

GummiArm: 3D Printed Robo

4th - 6th October, 2016

★ q △ d q e t i f y

By Gadget Junkie - October 6 @ 27 P 0

Germany



FUTURE V FITNESS

1st UK Robot Manipulation Workshop



Birmingham: Nicholson Building (G11) lunch and refresh
A number of invite
and there will be

orkshop is e for UK R thers and i

The Fourteenth International Conference on SIMULATION OF ADAPTIVE BEHAVIOUR:

From animals to animals
Aberystwyth, Wales, UK
23-26 August 2016



Meet the GummiArm: a 3D printed robotic arm that uses A

INDIA-UK

TECH

SUMMIT

Taj Palace, New Delhi, 7-9 Nov 2016

VIP Speakers







Rt Hon Theresa May
Prime Minister
United Kingdom



BERNSTEIN CENTER FOR COMPUTATIONAL NEUROSCIENCE BERLIN





Albu-Schäffer et al., "Soft robotics", Robotics & Automation Magazine, IEEE, vol. 15, no. 3, pp. 20-30, 2008.

Bonsignorio, F., Hallam, J., del Pobil, A.P. (eds.), "GEM Guidelines, Euron GEM Sig Report", 2008. Available at http://www.heronrobots.com/EuronGEMSig/

Ham, R.V., Sugar, T.G., Vanderborght, B., Hollander, K.W., and Lefeber, D., "Compliant actuator designs", IEEE Robotics & Automation Magazine, vol. 16, no. 3, pp. 81-94, 2009.

Hauser, H., Füchslin, R.M., and Pfeifer, R., "Opinions and Outlooks on Morphological Computation", E-book, ISBN 978-3-033-04515-6, available at: http://www.merlin.uzh.ch/publication/show/10528, 2014.

Laschi, C., and Cianchetti, M., "Soft robotics: new perspectives for robot bodyware and control", Frontiers in bioengineering and biotechnology, vol. 2, 2014.

Rus, D., and Tolley, M.T., "Design, fabrication and control of soft robots", Nature, vol. 521, no. 7553, pp. 467-475, 2015.

Vanderborght, B., et al., "Variable impedance actuators: A review", Robotics and Autonomous Systems, vol. 61, no.12, pp. 1601-1614, 2013.

Zinn, M., Roth, B., Khatib, O., and Salisbury, J. K., "A new actuation approach for human friendly robot design", The International Journal of Robotics Research, 23(4-5), pp. 379-398, 2004.

Gribble, P.L., Mullin, L.I., Cothros, N. and Mattar, A., "Role of cocontraction in arm movement accuracy", Journal of neurophysiology, vol. 89, no. 5, pp. 2396-2405, 2003.

Stoelen, M.F., Bonsignorio, F. and Cangelosi, A., 2016, August. Co-exploring Actuator Antagonism and Bio-inspired Control in a Printable Robot Arm. In International Conference on Simulation of Adaptive Behavior (pp. 244-255). Springer International Publishing.