

DigiBank Dynamic Security Analysis

Runtime security validation of the DigiBank API.

1. Why DAST is needed

Static analysis examines source code and configuration before execution. Dynamic analysis complements it by interacting with the application while it is running. This matters because a system can compile, pass unit tests, and still expose an API route without authentication, return excessive technical detail, accept invalid input, or handle sessions incorrectly.

DAST checks what an external client can actually observe, not only what the source code appears to intend.

The sequence is: establish runtime behavior, identify security weaknesses, apply targeted remediation, and replay the same scenarios to demonstrate the result.

2. Application under test

The external client does not call each business service directly. The API Gateway is the security boundary and the single entry point for the business API. Behind it, the customer, account, transaction, compliance, and notification services run as separate Compose services.




Figure 1. Runtime topology under test: gateway, business services, platform services, Compose host and persistence boundaries.

Surface	What is tested
Gateway	Authentication, authorization, headers, cache behavior, error responses and route protection.
Business APIs	Customer, account, transaction and compliance operations through gateway routing.
Runtime behavior	Malformed requests, invalid values, missing resources, session behavior and information disclosure.
Delivery path	Build, Compose startup, readiness, Newman replay and ZAP scanning.

3. Reproducible test environment

The environment is deliberately reproducible. Maven verifies the implementation, Docker Compose starts the complete topology, smoke checks verify the endpoints, and stack validation confirms that the expected containers are running before DAST begins.


```
make clean
make build
make image-build
make up
make smoke
make validate-stack
make newman-scan
make zap-scan
```

3.1 Starting the application

The Compose startup creates the complete local runtime. The screenshot shows the command used to start the services and the resulting container state. This establishes the execution context before any security request is sent.

```
→ digibank-core git:(main) ✕ make up
/Applications/Xcode.app/Contents/Developer/usr/bin/make -C digibank-microservices up
docker compose -f docker-compose.yml up -d
[+] up 12/12
✓ Container digibank-microservices-config-server-1      Running      0.00s
✓ Container digibank-microservices-transaction-db-1    Healthy      1.25s
✓ Container digibank-microservices-compliance-db-1     Healthy      0.79s
✓ Container digibank-microservices-compliance-service-1 Running      0.00s
✓ Container digibank-microservices-account-db-1        Healthy      0.79s
✓ Container digibank-microservices-account-service-1   Running      0.00s
✓ Container digibank-microservices-notification-service-1 Running      0.00s
✓ Container digibank-microservices-transaction-service-1 Running      0.00s
✓ Container digibank-microservices-discovery-server-1  Running      0.00s
✓ Container digibank-microservices-customer-db-1       Healthy      0.79s
✓ Container digibank-microservices-customer-service-1  Running      0.00s
✓ Container digibank-microservices-api-gateway-1       Running      0.00s
```

The container view confirms that the gateway, business services, databases, discovery server and config server are present in the same runtime topology.



3.2 Smoke validation

Smoke validation checks the public health endpoint, gateway business routes, direct internal service endpoints, discovery registry and config server. It is not the security campaign; it proves that the application is alive and that later DAST failures can be interpreted as application behavior rather than startup failure.

```
→ digibank-core git:(main) ✗ make smoke
/Applications/Xcode.app/Contents/Developer/usr/bin/make -C digibank-microservices smoke
./scripts/smoke-test.sh
Checking gateway-health http://localhost:8080/actuator/health
Checking customer-api http://localhost:8080/api/customers
Checking account-api http://localhost:8080/api/accounts
Checking transaction-api http://localhost:8080/api/transactions
Checking compliance-api http://localhost:8080/api/compliance
Checking customer-service http://localhost:8081/api/customers
Checking account-service http://localhost:8082/api/accounts
Checking transaction-service http://localhost:8083/api/transactions
Checking compliance-service http://localhost:8084/api/compliance
Checking notification-service http://localhost:8085/actuator/health
Checking discovery-registry http://localhost:8761/registry
Checking config-server http://localhost:8888/config/customer-service
Microservice smoke checks passed.
```

The successful result is the gate before Newman and ZAP.

4. Baseline and remediation decision


The baseline establishes the behavior before the gateway security boundary was introduced. The important observations were unauthenticated business routes, no gateway role distinction, incomplete response hardening, and no explicit cache policy for sensitive API responses.

The remediation uses stateless HTTP Basic authentication at the gateway because it is simple to reproduce in the workshop and preserves the existing service topology. It is not presented as the production identity architecture.

Request condition	Expected result after remediation
No credentials or invalid credentials	401 Unauthorized
Valid USER on normal banking API	Request is permitted
Valid USER on compliance API	403 Forbidden
Valid ADMIN on compliance API	Request is permitted
Authenticated request	No server session or session cookie

4.1 Authentication and authorization in Postman


The security collection makes the access rules visible through actual requests. The run shows unauthenticated requests returning 401, normal USER access returning 200, USER access to compliance returning 403, and ADMIN access to compliance returning 200.



The request results correspond directly to the gateway rules: authentication establishes identity, and authorization decides whether that identity may use the route.

4.2 Validation, errors and information exposure

The security collection also checks malformed JSON and missing resources. These cases return controlled 4xx responses without stack traces or internal implementation details. The same collection verifies the response headers on the health endpoint.



The run shows the validation and error-handling assertions passing, including the controlled 400 and 404 responses.

4.3 Headers and stateless behavior

The headers check verifies browser and response protections. The session check verifies that an authenticated request does not create a server session or return a session cookie.

The top screenshot displays the DigiBank DAST Security Controls interface for the test "Health response has security headers". The test is a GET request to `{{baseUrl}}/actuator/health`. The response is a 200 OK status with a body containing JSON data:

```
1 {
2   "groups": [
3     "liveness",
4     "readiness"
5   ],
6   "status": "UP"
7 }
```

The bottom screenshot displays the DigiBank DAST Security Controls interface for the test "Authenticated request is stateless". The test is a GET request to `{{baseUrl}}/api/customers`. The response is a 200 OK status with a body containing JSON data:

```
1 [
2   {
3     "id": 1,
4     "firstName": "DAST",
5     "lastName": "Customer",
6     "email": "dast.1789069699173@example.com"
7   },
8   {
9     "id": 2,
10    "firstName": "DAST",
11    "lastName": "Customer",
12    "email": "dast.1789073822431@example.com"
13  }
14 ]
```

These screenshots show the two related controls: hardened responses and stateless authentication.

5. Runtime checks and scan results


Newman expresses the expected security behavior as repeatable assertions. The security collection is divided into authentication, authorization, functional regression, input validation, error handling, information exposure, session behavior, and remediation verification.

Campaign	Result
Functional Newman collection	24 requests, 74 assertions, 0 failures.
Security Newman collection	12 requests, 19 assertions, 0 failures.
OWASP ZAP baseline	65 passing rules, 0 failures, 2 documented warnings.

The two ZAP warnings are interpreted against the local workshop environment: public non-storable resources and the plain-HTTP authentication observation. Authenticated API responses receive Cache-Control: no-store, private.

5.1 Functional regression in Postman

The functional collection checks the banking flows after the security changes: customer creation and retrieval, account creation, transactions and compliance operations. This confirms that the gateway protection did not break normal application behavior.



The collection run shows the banking requests and their passing assertions in the local environment.

5.2 Newman security replay

Newman repeats the same security collection without relying on the Postman interface. The summary is the reproducible command-line result used locally and in CI.

```
08-remediation-verification
Authentication remains enforced after remediation
GET http://127.0.0.1:8080/api/customers [401 Unauthorized, 359B, 6ms]
✓ authentication remains enforced
✓ no internal disclosure
```

	executed	failed
iterations	1	0
requests	12	0
test-scripts	12	0
prerequest-scripts	0	0
assertions	19	0

```
total run duration: 1074ms
total data received: 1.24kB (approx)
average response time: 64ms [min: 4ms, max: 200ms, s.d.: 59ms]
[INFO] Functional report: /Users/adorsys123/dev/digibank-core/dast/reports/202609
5/functional-newman-report.json
```

The security replay completed 12 requests and 19 assertions with zero failures.

Directory listing for /

- [functional-newman-report.json](#)
- [security-newman-report.json](#)

The report directory contains separate functional and security JSON results.

5.3 OWASP ZAP scan

ZAP scans the externally visible gateway surface and complements the targeted Postman assertions. The scan checks the running application for observable response, header and authentication weaknesses that are not covered by a small set of targeted requests.

The current scan completed with zero failures and 65 passing rules. Two warnings remain: public non-storable resources and the local plain-HTTP authentication observation. They are reviewed against the local test environment rather than treated as an unexplained score.

5.4 ZAP alert summary

The ZAP summary reports zero High alerts, one Medium alert, zero Low alerts and one Informational alert. The remaining Medium alert is the local plain-HTTP warning associated with HTTP Basic authentication. It is recorded and explained in the report.

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	1
Low	0
Informational	1
False Positives:	0

Insights

Level	Reason	Site	Description	Statistic
Info	Informational	http://127.0.0.1:8080	Percentage of responses with status code 2xx	50 %
Info	Informational	http://127.0.0.1:8080	Percentage of responses with status code 4xx	50 %
Info	Informational	http://127.0.0.1:8080	Percentage of endpoints with content type application/json	33 %
Info	Informational	http://127.0.0.1:8080	Percentage of endpoints with method GET	100 %
Info	Informational	http://127.0.0.1:8080	Count of total endpoints	3

5.5 Workshop 3 runtime validation

Workshop 3 validates the same security improvements against the running Docker Compose system. The sequence is intentional: rebuild the services, start the complete topology, verify readiness, replay normal and hostile HTTP scenarios, then compare the results with the earlier findings.

Runtime point	What the validation demonstrates
Authentication	Missing and invalid credentials are rejected with 401.
Authorization	USER and ADMIN roles receive different access decisions.
Validation and errors	Malformed and invalid requests return controlled 4xx responses without internal details.
Session and headers	No session cookie is created and required response protections are present.
Regression	Customer, account, transaction and compliance routes remain usable.

This is runtime evidence of the remediation, not another source-code review: the result is observed at the same gateway boundary used by an external client.

6. CI validation

The CI workflow repeats the same validation chain after the application is built. Each step has a clear purpose: start the runtime, prove readiness, verify the exposed routes, replay the security assertions, and scan the gateway surface.


Pipeline step	Purpose
Build and tests	Compile the services and run the automated test suite.
Compose and readiness	Start the complete runtime and wait for the required endpoints.
Smoke validation	Confirm gateway, business APIs and platform services respond.
Newman	Run the versioned functional and security request assertions.
ZAP	Run an independent baseline scan against the running gateway.
Report upload	Keep Newman and ZAP results available when a check fails.

Newman and ZAP remain separate checks: Newman verifies expected security behavior, while ZAP performs broader automated observations of the exposed HTTP surface.

7. Static security analysis

Workshop 2 moves security checks earlier in the delivery lifecycle. Instead of waiting until the application is running, the source code, dependencies and test strength are inspected during the build. SonarCloud provides code and security analysis, JaCoCo supplies test coverage data, and PITest measures whether tests detect deliberately introduced defects.

The analysis is applied to the current Java 21 Spring Boot microservices implementation. It does not replace the Newman and ZAP runtime checks; it complements them.



7.1 SonarCloud findings and decisions

The open-issues view identified two security issues. The CSRF warning is an intentional decision for this workshop because the gateway uses stateless HTTP Basic authentication and does not create browser sessions or cookies. The URL-construction warning was treated as a real issue and remediated by encoding gateway path variables before forwarding them to downstream services.

sonarcloud / Digi Bank Microservices / Issues

es master

Filters 1 Sort by Priority

Applied filters (1) Status: Open x Clear filters

Select issues for bulk actions

Change 30 issues 3h 39min effort

api-gateway/.../main/java/com/digibank/gateway/SecurityConfig.java

☐ Make sure disabling Spring Security's CSRF protection is safe here. Consistency

Security High cwe former-hotspot ... +

Open Assah Bismark L20 • 5min effort • 2 hours ago

api-gateway/.../main/java/com/digibank/gateway/GatewayController.java

☐ Change this code to not construct the URL's path from user-controlled data. Intentionality

Security Medium cwe +

Open Assah Bismark L89 • 30min effort • 12 hours ago

account-service/.../com/digibank/account/error/ApiError.java

☐ Explicitly specify the time zone by passing a ZoneId or a Clock to the .now() method. Intentionality

Reliability Info Maintainability Info datetime java8 ... +

Open Assah Bismark L7 • 5min effort • 12 hours ago

api-gateway/.../main/java/com/digibank/gateway/GatewayExceptionHandler.java

Informational timestamp findings using `LocalDateTime.now()` are recorded as a maintainability follow-up. They do not represent an authorization, injection or secret-exposure defect.

7.2 JaCoCo coverage evidence

JaCoCo records which production lines are exercised by the automated tests. The report is generated during Maven verify and is imported by SonarCloud. Coverage is evidence about test reach; it is not the same as proving that the tests detect incorrect behavior.

```
➔ digibank-core git:(main) ✗ find digibank-microservices -path '*/target/site/jacoco/jacoco.xml'
```

digibank-microservices/compliance-service/target/site/jacoco/jacoco.xml
digibank-microservices/account-service/target/site/jacoco/jacoco.xml
digibank-microservices/api-gateway/target/site/jacoco/jacoco.xml
digibank-microservices/customer-service/target/site/jacoco/jacoco.xml
digibank-microservices/transaction-service/target/site/jacoco/jacoco.xml
digibank-microservices/config-server/target/site/jacoco/jacoco.xml
digibank-microservices/discovery-server/target/site/jacoco/jacoco.xml



api-gateway

Element	Missed Instructions	Cov.	Missed Branches	Cov.	Missed Ctx	Missed Lines	Missed Methods	Missed Classes				
com.digibank.gateway		57%		25%	20	42	30	80	13	34	0	6
Total	198 of 461	57%	12 of 16	25%	20	42	30	80	13	34	0	6



transaction-service

Element	Missed Instructions	Cov.	Missed Branches	Cov.	Missed Ctx	Missed Lines	Missed Methods	Missed Classes				
com.digibank.transaction.service		17%		0%	14	17	16	19	11	14	1	2
com.digibank.transaction.client		0%	n/a	n/a	9	9	11	11	9	9	4	4
com.digibank.transaction.error		0%	n/a	n/a	9	9	9	9	9	9	2	2
com.digibank.transaction.controller		0%	n/a	n/a	6	6	6	6	6	6	1	1
com.digibank.transaction.dto		61%	n/a	n/a	1	2	1	2	1	2	1	2
com.digibank.transaction.pattern		83%		75%	2	9	5	21	0	5	0	2
com.digibank.transaction		0%	n/a	n/a	2	2	3	3	2	2	1	1
com.digibank.transaction.model		93%	n/a	n/a	1	9	1	3	1	9	0	1
Total	419 of 582	28%	8 of 14	42%	44	63	52	74	39	56	10	15


Created with JaCoCo 0.8.13.202504020838



compliance-service

Element	Missed Instructions	Cov.	Missed Branches	Cov.	Missed Ctx	Missed Lines	Missed Methods	Missed Classes				
com.digibank.compliance.service		8%		0%	10	12	7	9	9	11	0	1
com.digibank.compliance.error		0%	n/a	n/a	9	9	9	9	9	9	2	2
com.digibank.compliance.model		0%	n/a	n/a	10	10	4	4	10	10	1	1
com.digibank.compliance.dto		0%	n/a	n/a	3	3	3	3	3	3	3	3
com.digibank.compliance.controller		0%	n/a	n/a	7	7	7	7	7	7	1	1
com.digibank.compliance		0%	n/a	n/a	2	2	3	3	2	2	1	1
Total	344 of 355	3%	2 of 2	0%	41	43	33	35	40	42	8	9

Created with JaCoCo 0.8.13.202504020838



Coverage reports are available for the tested services. The notification service has no test sources and therefore produces no execution data.

7.3 PITest mutation testing

PITest changes compiled bytecode in controlled ways, such as negating a condition or replacing a return value. A killed mutant means a test detected the change. A surviving or uncovered mutant identifies a branch where the current tests are not strong enough to detect that behavior change.

Pit Test Coverage Report

Project Summary

Number of Classes	Line Coverage	Mutation Coverage	Test Strength
6	63% 50/80	12% 4/34	24% 4/17

Breakdown by Package

Name	Number of Classes	Line Coverage	Mutation Coverage	Test Strength
com.digibank.gateway	6	63% 50/80	12% 4/34	24% 4/17

- [Project uses Spring, but the Arcmutate Spring plugin is not present.](#)

Report generated by [PIT](#) 1.17.4

Enhanced functionality available at [arcmutate.com](#)

The gateway report generated 34 mutations, killed 4, and recorded 24% test strength. This is a test-strength observation, not a failed scan.

Pit Test Coverage Report

Project Summary

Number of Classes	Line Coverage	Mutation Coverage	Test Strength
5	27% 12/44	10% 3/29	50% 3/6

Breakdown by Package

Name	Number of Classes	Line Coverage	Mutation Coverage	Test Strength
com.digibank.customer.controller	1	0% 0/6	0% 0/5	100% 0/0
com.digibank.customer.error	2	0% 0/9	0% 0/7	100% 0/0
com.digibank.customer.model	1	64% 9/14	25% 1/4	25% 1/4
com.digibank.customer.service	1	20% 3/15	15% 2/13	100% 2/2

- [Project uses Spring, but the Arcmutate Spring plugin is not present.](#)

Report generated by [PIT](#) 1.17.4

Pit Test Coverage Report

Project Summary

Number of Classes	Line Coverage	Mutation Coverage	Test Strength
1	100% 9/9	100% 3/3	100% 3/3

Breakdown by Package

Name	Number of Classes	Line Coverage	Mutation Coverage	Test Strength
com.digibank.discovery 1	1	100% 9/9	100% 3/3	100% 3/3

-
- [Project uses Spring, but the Arcmutate Spring plugin is not present.](#)

Report generated by [PIT](#) 1.17.4

Enhanced functionality available at [arcmutate.com](#)

The other service reports show that mutation results are module-specific; they should be reviewed as test-improvement input rather than combined into one misleading score.

7.4 Static-analysis delivery controls

Static checks are exposed through simple Make commands so the instructor and the team can reproduce the same controls locally.

```
make build
make sast-sonar
make sast-pitest
make sast-dependency-check
```

The CI workflow runs SonarCloud as a separate job, runs Dependency-Check and PITest in the static-analysis job, uploads reports even when a scan fails, and caches the Dependency-Check NVD database. The first NVD database download is large; later runs reuse the GitHub Actions cache and retrieve only updates.

Control	Evidence and decision
SonarCloud	Quality gate passed; issues reviewed and classified.
JaCoCo	Coverage generated and imported into SonarCloud.
PITest	Mutation reports generated; surviving mutants become test-strength follow-up.
Dependency-Check	NVD report generated; zero unsuppressed CVEs after the Tomcat patch and reviewed false-positive rules.
CI	Separate jobs, secret-based credentials, report upload and cache reuse.

7.5 Dependency-Check results

The NVD update completed and the dependency scan generated HTML and JSON reports. The initial API Gateway report contained 43 unique CVE identifiers. After upgrading Spring Boot to 4.1.1, overriding embedded Tomcat to 11.0.25 and rerunning the scan, no unsuppressed CVEs remain across the nine Maven projects. Two dependency matches were confirmed as false positives and are covered by narrowly scoped suppression rules.

```
CVE-2026-59282, CVE-2026-47883, CVE-2026-47887, CVE-2026-59281, CVE-2026-59280, CVE-2026-593
tomcat-embed-core-11.0.22.jar (pkg:maven/org.apache.tomcat.embed/tomcat-embed-core@11.0.22, d
2.3:a:apache:tomcat:11.0.22:*:*:*:*:*:, cpe:2.3:a:apache:tomcat:apache_tomcat:11.0.22:*:*
+*:*:**) : CVE-2026-65637, CVE-2026-65905, CVE-2026-53434, CVE-2026-55276, CVE-2026-59083, C
-2026-59084, CVE-2026-65182, CVE-2026-68525, CVE-2026-65183, CVE-2026-66422, CVE-2026-68569,
E-2026-65927, CVE-2026-68763, CVE-2026-53404, CVE-2026-73180, CVE-2026-55955, CVE-2026-55956,
VE-2026-50229, CVE-2026-66299
See the dependency-check report for more details.

[INFO] -----
[INFO] Reactor Summary for Digi Bank Microservices 1.0.0-SNAPSHOT:
[INFO] Digi Bank Microservices ..... SUCCESS [ 5.547 s]
[INFO] api-gateway ..... SUCCESS [ 5.238 s]
[INFO] discovery-server ..... SUCCESS [ 20.086 s]
[INFO] config-server ..... SUCCESS [ 5.298 s]
[INFO] customer-service ..... SUCCESS [ 5.237 s]
[INFO] account-service ..... SUCCESS [ 4.749 s]
[INFO] transaction-service ..... SUCCESS [ 4.345 s]
[INFO] compliance-service ..... SUCCESS [ 3.651 s]
[INFO] notification-service ..... SUCCESS [ 2.484 s]
[INFO] -----
[INFO] BUILD SUCCESS
[INFO] -----
[INFO] Total time: 56.875 s
[INFO] Finished at: 2026-09-11T09:40:59+01:00
[INFO] -----
```


DEPENDENCY-CHECK

Dependency-Check is an open source tool performing a best effort analysis of first party dependencies. false positives and false negatives may exist in the analysis performed by the tool. Use of the tool and the reporting provided constitutes acceptance for use in an AIS 35 position, and there are no warranties, implied or otherwise, with respect to the analysis or the use. Any use of the tool and the reporting provided is solely user's risk. In no event shall the reporting be used or modified for any other purpose without written consent of a contributor and the use of this tool for any other purpose, or the resulting report.

[How to read the report](#) | [Suppressing false positives](#) | [Getting Help: github issues](#)

Sponsor

Project: notification-service

com.digibank.microservices.notification-service:1.0.0-SNAPSHOT

Scan Information (show all)

- dependency-check version: 12.1.0
- Report Generated On: Fri, 11 Sep 2020 09:40:59 +0100
- Dependencies Scanned: 50 (27 unique)
- Vulnerable Dependencies: 5
- Vulnerabilities Found: 55
- Vulnerabilities Suppressed: 0

Summary

Display: Showing Vulnerable Dependencies (click to show all)

Dependency	Vulnerability IDs	Package	Highest Severity	CVE Count	Confidence	Evidence
hibernate-validator: 5.1.0.Final.jar	cpe-2.3.a.hibernate.validator.validator@5.1.0.Final cpe-2.3.a.hibernate.validator.validator@5.1.0.Final	pkg-maven/org.hibernate.validator/hibernate-validator@5.1.0.Final	MEDIUM	1	Highest	78
log4j-api: 2.15.0.jar	cpe-2.3.a.apache.log4j@2.15.0 cpe-2.3.a.apache.log4j@2.15.0	pkg-maven/org.apache.logging.log4j/log4j-api@2.15.0	MEDIUM	1	Highest	43
spring-core: 7.0.8.jar	cpe-2.3.a.springframework.springframework@7.0.8 cpe-2.3.a.springframework.springframework@7.0.8 cpe-2.3.a.springframework.springframework@7.0.8	pkg-maven/org.springframework/spring-core@7.0.8	CRITICAL	17	Highest	41
spring-web: 7.0.8.jar	cpe-2.3.a.springframework.springframework@7.0.8 cpe-2.3.a.springframework.springframework@7.0.8 cpe-2.3.a.springframework.springframework@7.0.8	pkg-maven/org.springframework/spring-web@7.0.8	CRITICAL	17	Highest	35
tomcat-embed-core: 11.0.22.jar	cpe-2.3.a.apache.tomcat@11.0.22 cpe-2.3.a.apache.tomcat@11.0.22	pkg-maven/org.apache.tomcat.embed/tomcat-embed-core@11.0.22	CRITICAL	19	Highest	63

The captured NVD run shows the completed update, while the Dependency-Check report shows the scan output. The NIST source reference is retained as supporting context for the vulnerability database used by the scan.

 An official website of the United States government [Here's how you know](#)



NVD MENU

Information Technology Laboratory

NATIONAL VULNERABILITY DATABASE

 NATIONAL VULNERABILITY DATABASE NVD

Generating Your API Key

Do not leave this page until API key generation and validation are completed.

API Key Generated

The false-positive decisions are explicit: Angus Activation was matched to a Jakarta Mail SMTP issue, and Hibernate Validator was matched to the unrelated Nu Html Checker issue. The suppression file is versioned and limited to those CVE/component combinations.

Result	Decision
NVD data	Successfully updated and reused from the local/CI cache.
Report formats	HTML and JSON generated for the parent and service modules.
OSS Index	Disabled because the unauthenticated endpoint returned HTTP 401.
Before remediation	43 unique API Gateway CVEs: 15 Critical, 13 High, 14 Medium, 1 Low.
After remediation	Zero unsuppressed CVEs after Tomcat 11.0.25 and reviewed false-positive rules.
Evidence	dependency-check-report.html, dependency-check-report.json and dependency-check-suppressions.xml.

7.6 Workshop 2 completion status

The static-analysis setup is operational and reproducible. SonarCloud with JaCoCo, PITest, Dependency-Check, Maven verification and CI report-upload controls have all been executed. The

justified code remediation identified by SonarCloud was applied, and the dependency baseline now has zero unsuppressed CVEs after the Tomcat patch and reviewed false-positive decisions.

Workshop 2 is complete as a documented analysis and remediation exercise. PITest surviving mutants remain test-strength follow-up items, not unresolved dependency vulnerabilities; the reports preserve them for future test improvement.

8. Deliverable mapping


Objective	Demonstrated by
A2.1-A2.2	SAST/Shift Left explanation and source-security review scope.
A2.3	Review of validation, information exposure, dependency and test-strength risks.
A2.4	Maven, SonarCloud, JaCoCo, PITest, Dependency-Check and GitHub Actions.
A2.5	SonarCloud findings interpreted as remediation, accepted decision or follow-up.
A2.6-A2.7	Gateway path hardening, PITest configuration fix and documented security decisions.
A2.8	Passing build/tests, runtime DAST evidence and reproducible static-analysis controls.
A3.1-A3.8	Workshop 1 Newman/ZAP report and runtime evidence retained in this continuation PDF.

The result is a documented chain from source and dependency analysis, to risk interpretation, to remediation, to runtime revalidation.

Workshop 3: Dynamic Security Analysis

This section continues the static-analysis and remediation work with validation against the running DigiBank microservices implementation. DAST observes the behavior visible to an external client; it does not replace the source and dependency analysis already documented above.


Workshop 2 answered: what weaknesses can be found in the source, dependencies, configuration and tests? Workshop 3 answers: after those weaknesses are fixed, does the running application actually enforce the intended behavior without breaking valid banking flows? A fix can be incorrectly wired, applied to only one route or behave differently after deployment, so runtime revalidation is required.



The API Gateway is the runtime security boundary. All business requests in the campaign enter through this boundary before reaching the internal services.

Workshop 3: Campaign and evidence

The campaign combines manual scenario design in Postman, repeatable Newman assertions and an independent OWASP ZAP scan. The same categories are checked after remediation: authentication, authorization, input validation, error handling, information exposure, session behavior, headers and functional regression.



The Postman results show the expected access decisions and controlled responses. Missing credentials return 401, insufficient roles return 403, and malformed or unknown requests return controlled 4xx responses.

```
08-remediation-verification
Authentication remains enforced after remediation
GET http://127.0.0.1:8080/api/customers [401 Unauthorized, 359B, 6ms]
✓ authentication remains enforced
✓ no internal disclosure
```

	executed	failed
iterations	1	0
requests	12	0
test-scripts	12	0
prerequest-scripts	0	0
assertions	19	0

```
total run duration: 1074ms
total data received: 1.24kB (approx)
average response time: 64ms [min: 4ms, max: 200ms, s.d.: 59ms]
[INF0] Functional report: /Users/adorsys123/dev/digibank-core/dast/reports/202609
5/functional-newman-report.json
```

Newman provides the repeatable command-line validation used locally and in CI.

Workshop 3: Revalidation result

Validation point	Final result
Functional regression	24 requests, 74 assertions, 0 failures.
Security campaign	12 requests, 19 assertions, 0 failures.
Authentication	Missing and invalid credentials return 401.
Authorization	USER is denied protected compliance access; ADMIN is accepted.
Input and errors	Malformed and invalid requests return controlled 4xx responses without internal details.
Session behavior	No session cookie is created.
ZAP	65 passing rules, 0 failures, 2 documented local warnings.

Summary of Alerts

Risk Level	Number of Alerts
High	0
Medium	1
Low	0
Informational	1
False Positives:	0

Insights

Level	Reason	Site	Description	Statistic
Info	Informational	http://127.0.0.1:8080	Percentage of responses with status code 2xx	50 %
Info	Informational	http://127.0.0.1:8080	Percentage of responses with status code 4xx	50 %
Info	Informational	http://127.0.0.1:8080	Percentage of endpoints with content type application/json	33 %
Info	Informational	http://127.0.0.1:8080	Percentage of endpoints with method GET	100 %
Info	Informational	http://127.0.0.1:8080	Count of total endpoints	3

The remaining ZAP warnings are documented local observations: public non-storable resources and the plain-HTTP authentication limitation. They are not evidence of an authentication bypass or cacheable authenticated banking responses.

Workshop 3 is complete when the same runtime scenarios pass after remediation and the remaining scanner observations have an explicit technical decision.

Workshop 4: Container and dependency security

Workshop 4 extends the previous work from source and runtime behavior to the artifacts that are actually built and executed. The question is whether the delivered images, dependencies, configuration and packaging introduce risks that are not visible from application tests alone.

The current Java 21 microservices implementation uses multi-stage Dockerfiles. Maven and the JDK are used in the build stage, while the final runtime image contains only the packaged service JAR and Java runtime. Trivy checks the resulting images, the Compose configuration and the repository filesystem.

```
⇒ ⇒ transferring context: 4.4kB
⇒ [discovery-server internal] load build context
⇒ ⇒ transferring context: 4.27kB
⇒ CACHED [transaction-service stage-1 2/4] RUN apk upgrade --no-cache
⇒ CACHED [transaction-service stage-1 3/4] WORKDIR /app
⇒ CACHED [transaction-service build 2/13] WORKDIR /workspace
⇒ CACHED [notification-service build 3/13] COPY pom.xml .
⇒ CACHED [notification-service build 4/13] COPY api-gateway/pom.xml api-gateway/pom.xml
⇒ CACHED [notification-service build 5/13] COPY discovery-server/pom.xml discovery-server/pom.xml
⇒ CACHED [notification-service build 6/13] COPY config-server/pom.xml config-server/pom.xml
⇒ CACHED [notification-service build 7/13] COPY customer-service/pom.xml customer-service/pom.xml
⇒ CACHED [notification-service build 8/13] COPY account-service/pom.xml account-service/pom.xml
⇒ CACHED [notification-service build 9/13] COPY transaction-service/pom.xml transaction-service/pom.xml
⇒ CACHED [notification-service build 10/13] COPY compliance-service/pom.xml compliance-service/pom.xml
⇒ CACHED [notification-service build 11/13] COPY notification-service/pom.xml notification-service/pom.xml
⇒ CACHED [notification-service build 12/13] COPY notification-service/src notification-service/src
⇒ CACHED [notification-service build 13/13] RUN mvn -B -pl notification-service -am package -DskipTests
⇒ CACHED [notification-service stage-1 4/4] COPY --from=build /workspace/notification-service/target/notification-service-*.jar app.jar
⇒ [notification-service] exporting to image
⇒ ⇒ exporting layers
⇒ ⇒ exporting manifest sha256:25b1cb734cccec9021a02b398a6fe70555935f5031454d08c388c7a2f9fd68ff
⇒ ⇒ exporting config sha256:4454dffa4859e904d2cea9ed80793d32bb77ad841c174436da191d47c33ba1c
```

The multi-stage build keeps build tooling out of the runtime artifact.

Workshop 4: Findings and remediation

The first image scan found five High Alpine package findings in account-service and eight High findings from the unrelated pebble utility present in the Ubuntu runtime layers of the gateway, discovery and config services. The Java application layers were clean. The focused remediation changed the runtime images to the Alpine Java 21 image, updated Alpine packages and removed the unrelated utility. All service images also run as the non-root digibank user.

```
2026-09-11T12:38:21+01:00 INFO [vuln] Vulnerability scanning is enabled
2026-09-11T12:38:21+01:00 INFO [secret] Secret scanning is enabled
2026-09-11T12:38:21+01:00 INFO [secret] If your scanning is slow please try '--scanners vuln' to disable secret scanning
2026-09-11T12:38:21+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide/scanner/secretRecommendation for faster secret detection
2026-09-11T12:38:21+01:00 INFO Detected OS family="alpine" version="3.24.1"
2026-09-11T12:38:21+01:00 WARN This OS version is not on the EOL list family="alpine" version="3.24" pkg_num=73
2026-09-11T12:38:21+01:00 INFO [alpine] Detecting vulnerabilities... os.version="3.24" repository="3.24" pkg_num=73
2026-09-11T12:38:21+01:00 INFO [jar] Detecting vulnerabilities... num=1
2026-09-11T12:38:21+01:00 WARN Using severities from other vendors for some vulnerabilities. Read https://trivy.dev/docs/v0.69/guide/scanner/vulnerabilitySeverity-selection for details.

Report Summary

+-----+-----+-----+-----+-----+-----+-----+
| Target                                     | Type   | Vulnerabilities | Secrets |
+-----+-----+-----+-----+-----+-----+-----+
| digibank-microservices-account-service (alpine 3.24.1) | alpine | 5               | -       |
| app/app.jar                                     | jar    | 0               | -       |
+-----+-----+-----+-----+-----+-----+-----+

Legend:
- '-': Not scanned
- '0': Clean (no security findings detected)

digibank-microservices-account-service (alpine 3.24.1)
Total: 5 (HIGH: 5, CRITICAL: 0)

+-----+-----+-----+-----+-----+-----+-----+
| Library | Vulnerability | Severity | Status | Installed Version | Fixed Version | Title |
+-----+-----+-----+-----+-----+-----+-----+
| libcrypto3 | CVE-2026-14456 | HIGH | Fixed | 3.5.7-r0 | 3.5.8-r0 | openssl: OpenSSL: Denial of Service via unbounded memory growth in QUIC server... https://www.openssl.com/news/cve-2026-14456 |
| libexpat | CVE-2026-76956 | | | 2.8.3-r0 | 2.8.4-r0 | libexpat: Libexpat: Denial of Service via hash flooding attack with crafted XML... https://www.exploit-db.com/exploits/cve-2026-76956 |
| | CVE-2026-76957 | | | | | libexpat: Libexpat: Memory corruption vulnerability allows arbitrary code execution or denial of... https://www.exploit-db.com/exploits/cve-2026-76957 |
| libssl3 | CVE-2026-14456 | | | 3.5.7-r0 | 3.5.8-r0 | openssl: OpenSSL: Denial of Service via unbounded memory growth in QUIC server... https://www.openssl.com/news/cve-2026-14456 |
| openssl | | | | | | |
+-----+-----+-----+-----+-----+-----+-----+

make[1]: *** [container-scan] Error 1

Report Summary

+-----+-----+-----+-----+-----+
| Target                                     | Type   | Vulnerabilities | Secrets |
+-----+-----+-----+-----+-----+-----+-----+
| digibank-microservices-account-service (alpine 3.24.1) | alpine | 0               | -       |
| app/app.jar                                     | jar    | 0               | -       |
+-----+-----+-----+-----+-----+-----+-----+

Legend:
- '-': Not scanned
- '0': Clean (no security findings detected)

Scanning digibank-microservices-gpi-gateway
2026-09-11T12:42:25+01:00 INFO [vuln] Vulnerability scanning is enabled
2026-09-11T12:42:25+01:00 INFO [secret] Secret scanning is enabled
2026-09-11T12:42:25+01:00 INFO [secret] If your scanning is slow please try '--scanners vuln' to disable secret scanning
2026-09-11T12:42:25+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide/scanner/secretRecommendation for faster secret detection
2026-09-11T12:42:25+01:00 INFO Detected OS family="ubuntu" version="26.04"
2026-09-11T12:42:25+01:00 WARN This OS version is not on the EOL list family="ubuntu" version="26.04"
2026-09-11T12:42:25+01:00 INFO [ubuntu] Detecting vulnerabilities... os.version="26.04" pkg_num=140
2026-09-11T12:42:25+01:00 INFO Number of language-specific files: num=2
2026-09-11T12:42:25+01:00 INFO [golang] Detecting vulnerabilities...
2026-09-11T12:42:25+01:00 INFO [jar] Detecting vulnerabilities...
2026-09-11T12:42:25+01:00 WARN Using severities from other vendors for some vulnerabilities. Read https://trivy.dev/docs/v0.69/guide/scanner/vulnerabilitySeverity-selection for details.

Report Summary

+-----+-----+-----+-----+-----+-----+-----+
| Target                                     | Type   | Vulnerabilities | Secrets |
+-----+-----+-----+-----+-----+-----+-----+
| digibank-microservices-gpi-gateway (ubuntu 26.04) | ubuntu | 8               | -       |
| app/app.jar                                     | jar    | 0               | -       |
| usr/bin/pebble                                  | golang  | 0               | -       |
+-----+-----+-----+-----+-----+-----+-----+

Legend:
- '-': Not scanned
- '0': Clean (no security findings detected)

usr/bin/pebble (golang)
Total: 8 (HIGH: 8, CRITICAL: 0)

+-----+-----+-----+-----+-----+-----+-----+
| Library | Vulnerability | Severity | Status | Installed Version | Fixed Version | Title |
+-----+-----+-----+-----+-----+-----+-----+
| stdlib | CVE-2026-13818 | HIGH | Fixed | v1.26.5 | 1.25.13, 1.26.6, 1.27.0-rc.3 | encoding/asn1: golang: Go encoding/asn1: Denial of Service via excessive recursion in Unmarshal... https://www.openssl.com/news/cve-2026-13818 |
| | CVE-2026-79921 | | | | | golang.org/x/net/idna: golang: net/http: golang.org/x/net/idna: Privilege escalation via incorrect Punycode label processing https://www.exploit-db.com/exploits/cve-2026-79921 |
| | CVE-2026-46400 | | | | | net/http: golang: Go net/http: Unencrypted HTTP/2 connections vulnerable to Denial of Service... https://www.exploit-db.com/exploits/cve-2026-46400 |
| | CVE-2026-56853 | | | | | net/http: golang: Go net/http: Unencrypted HTTP/2 connections vulnerable to Denial of Service... https://www.exploit-db.com/exploits/cve-2026-56853 |
| | CVE-2026-56858 | | | | | html/template: golang: Go html/template: Cross-Site Scripting via pathological Unescape https://www.exploit-db.com/exploits/cve-2026-56858 |
| | CVE-2026-56859 | | | | | encoding/xml: golang: Go: Denial of Service via XML decoding recursion depth issues... https://www.exploit-db.com/exploits/cve-2026-56859 |
| | CVE-2026-56860 | | | | | net/url: golang: golang net/url: Denial of Service from quadratic complexity in path... https://www.exploit-db.com/exploits/cve-2026-56860 |
| | CVE-2026-56862 | | | | | crypto/tls: golang: Go: Denial of Service via indefinite keyUpdate messages https://www.exploit-db.com/exploits/cve-2026-56862 |
+-----+-----+-----+-----+-----+-----+-----+
```

Report Summary

Target	Type	Vulnerabilities	Secrets
digibank-microservices- api-gateway (alpine 3.24.1)	alpine	0	-
app/app.jar	jar	0	-

Legend:
 - '-': Not scanned
 - '0': Clean (no security findings detected)

Scanning digibank-microservices-compliance-service

```

2024-09-11T12:49:01+01:00 INFO [vuln] Vulnerability scanning is enabled
2024-09-11T12:49:01+01:00 INFO [secret] Secret scanning is enabled
2024-09-11T12:49:01+01:00 INFO [secret] If your scanning is slow, please try '--scanners vuln' to disable secret scanning
2024-09-11T12:49:01+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide/scanner/secretrecommendation for faster secret detection
2024-09-11T12:49:01+01:00 INFO Detected OS family="alpine" version="3.24.1"
2024-09-11T12:49:01+01:00 WARN This OS version is not on the EOL list family="alpine" version="3.24"
2024-09-11T12:49:01+01:00 INFO [vuln] Scanning complete: 0 vulnerabilities, 0 secrets, 0 errors
  
```

The before-and-after evidence shows that the remediation addressed container-layer findings rather than changing business code or hiding scanner results.

Workshop 4: Final artifact validation

The final scan covers all eight application images and the Docker Compose configuration. Each image reports zero vulnerabilities, zero Java archive findings and no detected secrets. Compose reports zero misconfigurations and zero secrets. The repository filesystem scan reports no High or Critical findings and no secrets; it retains eight Low DS-0026 observations because the Dockerfiles do not declare individual HEALTHCHECK instructions. Those remain visible as an accepted low-risk observation because Compose checks and smoke validation provide readiness evidence.

Report Summary				
Target	Type	Vulnerabilities	Secrets	Misconfigurations
account-service/pom.xml	pom	0	-	-
api-gateway/pom.xml	pom	0	-	-
compliance-service/pom.xml	pom	0	-	-
config-server/pom.xml	pom	0	-	-
customer-service/pom.xml	pom	0	-	-
discovery-server/pom.xml	pom	0	-	-
notification-service/pom.xml	pom	0	-	-
pom.xml	pom	0	-	-
transaction-service/pom.xml	pom	0	-	-
account-service/Dockerfile	dockerfile	-	-	0
api-gateway/Dockerfile	dockerfile	-	-	0
compliance-service/Dockerfile	dockerfile	-	-	0
config-server/Dockerfile	dockerfile	-	-	0
customer-service/Dockerfile	dockerfile	-	-	0
discovery-server/Dockerfile	dockerfile	-	-	0
notification-service/Dockerfile	dockerfile	-	-	0
transaction-service/Dockerfile	dockerfile	-	-	0

Legend:
- '-': Not scanned

IMAGE	ID	DISK USAGE	CONTENT SIZE	EXTRA
alpine:latest	28bd5fe8b56d	14.6MB	4.27MB	
budget-wise-online-recovery-server:latest	106a94d3f600	1.07GB	199MB	U
budget-wise-online-server:latest	6479ba7ff3d3	1.08GB	200MB	U
digibank-microservices-account-service:latest	23e46c056b8a	401MB	125MB	
digibank-microservices-api-gateway:latest	04503ac868cd	348MB	100MB	
digibank-microservices-compliance-service:latest	8eb1982d8418	401MB	125MB	
digibank-microservices-config-server:latest	e7d60c5c73a1	337MB	95MB	
digibank-microservices-customer-service:latest	93c2e0994661	401MB	125MB	
digibank-microservices-discovery-server:latest	a222f1b93e96	337MB	95MB	
digibank-microservices-notification-service:latest	fcfc72a43158	344MB	98.2MB	
digibank-microservices-transaction-service:latest	a2b026e47d22	401MB	125MB	
digibank-parent-app:latest	791ca1555d15	403MB	128MB	U
digibank-parent-wildfly:latest	4fcdfc39bc8a	1.47GB	544MB	U

The final report and image-size evidence show the clean scan result and the delivered artifact inventory.

Workshop 4: Supporting scan evidence

These supporting captures show the scan output used to make the remediation decision. They are included as the original PNG assets; the PDF layout scales their display area for the page but does not replace them with a lower-resolution redraw.

```
✓ Image digibank-microservices-discovery-server Built 221.0
✓ Image digibank-microservices-config-server Built 221.0
✓ Image digibank-microservices-notification-service Built 221.0
✓ Image digibank-microservices-compliance-service Built 221.0
✓ Image digibank-microservices-account-service Built 221.0
✓ Image digibank-microservices-customer-service Built 221.0
✓ Image digibank-microservices-api-gateway Built 221.0
✓ Image digibank-microservices-transaction-service Built 221.0
→ digibank-core git:(main) ✕ make container-scan
/Applications/Xcode.app/Contents/Developer/usr/bin/make -C digibank-microservices container-scan
Scanning digibank-microservices-account-service
2026-09-11T12:33:25+01:00 INFO [vulndb] Need to update DB
2026-09-11T12:33:25+01:00 INFO [vulndb] Downloading vulnerability DB...
2026-09-11T12:33:25+01:00 INFO [vulndb] Downloading artifact... repo="mirror.gcr.io/aquasec/trivy-db:2"
112.23 MiB / 112.23 MiB [-----] 100.00% 2.09 MiB p/s 54
2026-09-11T12:34:22+01:00 INFO [vulndb] Artifact successfully downloaded repo="mirror.gcr.io/aquasec/trivy-db:2"
2026-09-11T12:34:22+01:00 INFO [vuln] Vulnerability scanning is enabled
2026-09-11T12:34:22+01:00 INFO [secret] Secret scanning is enabled
2026-09-11T12:34:22+01:00 INFO [secret] If your scanning is slow, please try '--scanners vuln' to disable secret scanning
2026-09-11T12:34:22+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide/scanner/secret#recommendation for faster secret detection
2026-09-11T12:34:25+01:00 INFO [javadb] Downloading Java DB...
2026-09-11T12:34:25+01:00 INFO [javadb] Downloading artifact... repo="mirror.gcr.io/aquasec/trivy-java-db:1"
919.51 MiB / 919.51 MiB [-----] 100.00% 3.94 MiB p/s 3m54
2026-09-11T12:38:20+01:00 INFO [javadb] Artifact successfully downloaded repo="mirror.gcr.io/aquasec/trivy-java-db:1"
2026-09-11T12:38:20+01:00 INFO [javadb] Java DB is cached for 3 days. If you want to

Report Summary



| Target                                                      | Type   | Vulnerabilities | Secrets |
|-------------------------------------------------------------|--------|-----------------|---------|
| digibank-microservices-notification-service (alpine 3.24.1) | alpine | 0               | -       |
| app/app.jar                                                 | jar    | 0               | -       |



Legend:
- '-': Not scanned
- '0': Clean (no security findings detected)

Scanning digibank-microservices-transaction-service
2026-09-11T12:42:59+01:00 INFO [vuln] Vulnerability scanning is enabled
2026-09-11T12:42:59+01:00 INFO [secret] Secret scanning is enabled
2026-09-11T12:42:59+01:00 INFO [secret] If your scanning is slow, please try '--scanners vuln' to disable secret scanning
2026-09-11T12:42:59+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide/scanner/secret#recommendation for faster secret detection
2026-09-11T12:43:01+01:00 INFO Detected OS family="alpine" version="3.24.1"
2026-09-11T12:43:01+01:00 WARN This OS version is not on the EOL list family="alpine" version="3.24"
2026-09-11T12:43:01+01:00 INFO [alpine] Detecting vulnerabilities... os_version="3.24" repository="3.24" pkg_num=73
2026-09-11T12:43:02+01:00 INFO Number of language-specific files num=1
2026-09-11T12:43:02+01:00 INFO [jar] Detecting vulnerabilities...
2026-09-11T12:43:02+01:00 INFO [vuln] Vulnerability scanning is enabled
2026-09-11T12:43:02+01:00 INFO [secret] Secret scanning is enabled
2026-09-11T12:43:02+01:00 INFO [secret] If your scanning is slow, please try '--scanners vuln' to disable secret scanning
2026-09-11T12:43:02+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide/scanner/secret#recommendation for faster secret detection

Notices:
- Version 0.74.0 of Trivy is now available, current version is 0.69.3

To suppress version checks, run Trivy scans with the --skip-version-check flag

2026-09-11T12:43:02+01:00 INFO [vuln] Vulnerability scanning is enabled
2026-09-11T12:43:02+01:00 INFO [secret] Secret scanning is enabled
2026-09-11T12:43:02+01:00 INFO [secret] If your scanning is slow, please try '--scanners vuln' to disable secret scanning
2026-09-11T12:43:02+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide/scanner/secret#recommendation for faster secret detection
2026-09-11T12:43:02+01:00 INFO Detected OS family="alpine" version="3.24.1"
2026-09-11T12:43:02+01:00 WARN This OS version is not on the EOL list family="alpine" version="3.24"
2026-09-11T12:43:02+01:00 INFO [alpine] Detecting vulnerabilities... os_version="3.24" repository="3.24" pkg_num=73
2026-09-11T12:43:02+01:00 INFO Number of language-specific files num=1
2026-09-11T12:43:02+01:00 INFO [jar] Detecting vulnerabilities...
2026-09-11T12:43:02+01:00 INFO [vuln] Vulnerability scanning is enabled
2026-09-11T12:43:02+01:00 INFO [secret] Secret scanning is enabled
2026-09-11T12:43:02+01:00 INFO [secret] If your scanning is slow, please try '--scanners vuln' to disable secret scanning
2026-09-11T12:43:02+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide/scanner/secret#recommendation for faster secret detection

AssaB Bismark / DigiBank Microservices / Issues
Issues 1 master x
Filters Sort by Priority
Applied filters (1) Status: Open Clear filters
Select issues for bulk actions
29 issues 3h 9min effort
api-gateway/.../main/java/com/digibank/gateway/SecurityConfig.java
Security High Consistency cwe former-hotspot L20 5min effort 2 hours ago
account-service/.../com/digibank/account/error/ApiError.java
Explicitly specify the time zone by passing a ZoneId or a Clock to the .now() method. Reliability Info Maintainability Info Intentionality datetime java8 L7 5min effort 12 hours ago
api-gateway/.../main/java/com/digibank/gateway/GatewayExceptionHandler.java
Explicitly specify the time zone by passing a ZoneId or a Clock to the .now() method. Reliability Info Maintainability Info Intentionality datetime java8 L25 5min effort 12 hours ago
```


The screenshots are read together with the generated JSON and SARIF reports, which remain the authoritative machine-readable evidence.

Workshop 4: Deliverable mapping

Objective	Evidence
A4.1	Dependency, image-layer and container-configuration risks are explained.
A4.2	Dockerfiles, Compose, Maven POMs, images and CI workflow are inventoried.
A4.3	Dependency-Check and Trivy analyze declared, transitive and image dependencies.
A4.4	Multi-stage Dockerfiles, runtime bases, image contents and Compose parameters are reviewed.
A4.5	Dependency updates, Alpine package updates, image reduction and non-root execution are applied.
A4.6	Each remediation is connected to its risk reduction and verified by a new scan.
A4.7	GitHub Actions rebuilds images, runs container-scan and uploads JSON/SARIF reports.
A4.8	The report, screenshots, generated reports and reproducible commands document the final result.

Workshop 4 completes the delivery-artifact security chain: the application is analyzed, the runtime is validated, and the images and configuration used to deliver it are scanned and documented.

Workshop 4: Securing Containers, Dependencies, and Deployment Artifacts

This workshop examines the artifacts that package and deliver DigiBank. Workshop 2 analyzed source code and dependencies; Workshop 3 validated the running HTTP system; Workshop 4 now checks the container images, Dockerfiles, Compose configuration, repository files and CI controls used to build and execute the system.

The implementation is the current Java 21 Spring Boot microservices topology. The assignment source contains older Java 17 and monolith assumptions, so the evidence here is mapped to the actual microservices repository and its Docker Compose delivery model.

Artifact under review	Security question
Maven POMs and transitive dependencies	Are known vulnerable components included in the build?
Dockerfiles and runtime images	Does the final image contain unnecessary tools, vulnerable packages or excessive privileges?
Compose configuration	Are ports, networks, credentials, health checks and service boundaries intentional?
Repository and CI workflow	Are secrets and configuration risks detected automatically before delivery?

Workshop 4: Findings, hardening and final validation

The first Trivy image scan found five High Alpine package findings in account-service and eight High findings from the unrelated pebble utility in the Ubuntu runtime layers of the gateway, discovery and config services. The Java application layers were clean. The focused remediation moved the runtime images to Java 21 Alpine, updated Alpine packages, removed the unrelated utility and configured every service to run as the non-root digibank user.

```
✓ Image digibank-microservices-discovery-server Built 221.0
✓ Image digibank-microservices-config-server Built 221.0
✓ Image digibank-microservices-notification-service Built 221.0
✓ Image digibank-microservices-compliance-service Built 221.0
✓ Image digibank-microservices-account-service Built 221.0
✓ Image digibank-microservices-customer-service Built 221.0
✓ Image digibank-microservices-api-gateway Built 221.0
✓ Image digibank-microservices-transaction-service Built 221.0
→ digibank-core git:(main) ✗ make container-scan
/Applications/Xcode.app/Contents/Developer/usr/bin/make -C digibank-microservices container-scan
Scanning digibank-microservices-account-service
2026-09-11T12:33:25+01:00 INFO [vuln] Need to update DB
2026-09-11T12:33:25+01:00 INFO [vuln] Downloading vulnerability DB...
2026-09-11T12:33:25+01:00 INFO [vuln] Downloading artifact... repo="mirror.g
r.io/aquasec/trivy-db:2"
112.23 MiB / 112.23 MiB [-----] 100.00% 2.09 MiB p/s 54
2026-09-11T12:34:22+01:00 INFO [vuln] Artifact successfully downloaded repo="
r.io/aquasec/trivy-db:2"
2026-09-11T12:34:22+01:00 INFO [vuln] Vulnerability scanning is enabled
2026-09-11T12:34:22+01:00 INFO [secret] Secret scanning is enabled
2026-09-11T12:34:22+01:00 INFO [secret] If your scanning is slow, please try '--scan
rs vuln' to disable secret scanning
2026-09-11T12:34:22+01:00 INFO [secret] Please see https://trivy.dev/docs/v0.69/guide
scanner/secret#recommendation for faster secret detection
2026-09-11T12:34:25+01:00 INFO [javadb] Downloading Java DB...
2026-09-11T12:34:25+01:00 INFO [javadb] Downloading artifact... repo="mirror.g
r.io/aquasec/trivy-java-db:1"
919.51 MiB / 919.51 MiB [-----] 100.00% 3.94 MiB p/s 3m54
2026-09-11T12:38:20+01:00 INFO [javadb] Artifact successfully downloaded repo="
r.io/aquasec/trivy-java-db:1"
2026-09-11T12:38:20+01:00 INFO [javadb] Java DB is cached for 3 days. If you want to

Report Summary
```

Target	Type	Vulnerabilities	Secrets	Misconfigurations
account-service/pom.xml	pom	0	-	-
api-gateway/pom.xml	pom	0	-	-
compliance-service/pom.xml	pom	0	-	-
config-server/pom.xml	pom	0	-	-
customer-service/pom.xml	pom	0	-	-
discovery-server/pom.xml	pom	0	-	-
notification-service/pom.xml	pom	0	-	-
pom.xml	pom	0	-	-
transaction-service/pom.xml	pom	0	-	-
account-service/Dockerfile	dockerfile	-	-	0
api-gateway/Dockerfile	dockerfile	-	-	0
compliance-service/Dockerfile	dockerfile	-	-	0
config-server/Dockerfile	dockerfile	-	-	0
customer-service/Dockerfile	dockerfile	-	-	0
discovery-server/Dockerfile	dockerfile	-	-	0
notification-service/Dockerfile	dockerfile	-	-	0
transaction-service/Dockerfile	dockerfile	-	-	0

```
Legend:
- '-': Not scanned
```

The final scan covered all eight application images: zero vulnerabilities, zero Java archive findings and zero detected secrets. Compose reported zero misconfigurations and zero secrets. The filesystem scan reported no High or Critical findings and no secrets. Its eight Low DS-0026 observations, caused by Dockerfiles without individual HEALTHCHECK instructions, remain visible and documented; Compose, smoke and stack validation provide the readiness checks used in this educational deployment.

Workshop 4: Deliverables A4.1-A4.8

Objective	Demonstrated by
A4.1	Risks in dependencies, image layers and container configuration are explained.
A4.2	Dockerfiles, Compose, Maven POMs, images, environment configuration and CI workflow are inventoried.
A4.3	Dependency-Check and Trivy analyze declared, transitive and image-embedded components.
A4.4	Multi-stage Dockerfiles, runtime bases, image contents, ports and runtime parameters are reviewed.
A4.5	Dependency updates, Alpine package updates, image reduction and non-root execution are applied.
A4.6	Each remediation is connected to its risk reduction and verified by post-remediation scanning.
A4.7	GitHub Actions rebuilds images, runs container-scan and uploads JSON/SARIF reports.
A4.8	The report, screenshots, generated reports and reproducible commands provide the final deliverable.

```

⇒ ⇒ transferring context: 4.47kB
⇒ [discovery-server internal] load build context
⇒ ⇒ transferring context: 4.27kB
⇒ CACHED [transaction-service stage-1 2/4] RUN apk upgrade --no-cache
⇒ CACHED [transaction-service stage-1 3/4] WORKDIR /app
⇒ CACHED [transaction-service build 2/13] WORKDIR /workspace
⇒ CACHED [notification-service build 3/13] COPY pom.xml .
⇒ CACHED [notification-service build 4/13] COPY api-gateway/pom.xml api-gateway/pom.xml
⇒ CACHED [notification-service build 5/13] COPY discovery-server/pom.xml discovery-server/pom.xml
⇒ CACHED [notification-service build 6/13] COPY config-server/pom.xml config-server/pom.xml
⇒ CACHED [notification-service build 7/13] COPY customer-service/pom.xml customer-service/pom.xml
⇒ CACHED [notification-service build 8/13] COPY account-service/pom.xml account-service/pom.xml
⇒ CACHED [notification-service build 9/13] COPY transaction-service/pom.xml transaction-service/pom.xml
⇒ CACHED [notification-service build 10/13] COPY compliance-service/pom.xml compliance-service/pom.xml
⇒ CACHED [notification-service build 11/13] COPY notification-service/pom.xml notification-service/pom.xml
⇒ CACHED [notification-service build 12/13] COPY notification-service/src notification-service/src
⇒ CACHED [notification-service build 13/13] RUN mvn -B -pl notification-service -am package -DskipTests
⇒ CACHED [notification-service stage-1 4/4] COPY --from=build /workspace/notification-service/target/notification-service-*.jar app.jar
⇒ [notification-service] exporting to image
⇒ ⇒ exporting layers
⇒ ⇒ exporting manifest sha256:25b1cb734cccec9021a02b398a6fe70555935f5031454d08c388c7a2f9fd68ff
⇒ ⇒ exporting config sha256:4454dffa4859e904d2cea9ed80793d32bb77ad841c174436da191d47c33ba1c

```

IMAGE	ID	DISK USAGE	CONTENT SIZE	EXTRA
alpine:latest	28bd5fe8b56d	14.6MB	4.27MB	
budget-wise-online-recovery-server:latest	106a94d3f600	1.07GB	199MB	U
budget-wise-online-server:latest	6479ba7ff3d3	1.08GB	200MB	U
digibank-microservices-account-service:latest	23e46c056b8a	401MB	125MB	
digibank-microservices-api-gateway:latest	04503ac868cd	348MB	100MB	
digibank-microservices-compliance-service:latest	8eb1982d8418	401MB	125MB	
digibank-microservices-config-server:latest	e7d60c5c73a1	337MB	95MB	
digibank-microservices-customer-service:latest	93c2e0994661	401MB	125MB	
digibank-microservices-discovery-server:latest	a222f1b93e96	337MB	95MB	
digibank-microservices-notification-service:latest	fcfc72a43158	344MB	98.2MB	
digibank-microservices-transaction-service:latest	a2b026e47d22	401MB	125MB	
digibank-parent-app:latest	791ca1555d15	403MB	128MB	U
digibank-parent-wildfly:latest	4fcdcf39bc8a	1.47GB	544MB	U

Workshop 4 completes the delivery-artifact security chain: application analysis, runtime validation, container hardening and automated artifact verification.