

Table of Contents

ANNEX H: INVENTORY, COIL SCIENCE & PRODUCTION STANDARDS

Zarewa Aluminium and Plastics Ltd — System of Operations v3.0

Audience: Operations, production, procurement, finance

H.1 COIL MATERIAL SCIENCE

H.1.1 Material Types

Type

Aluzinc (PPGI)

Aluminium

Stone-coated substrate

H.1.2 Gauge Selection Guide

Gauge (mm)

0.18

0.22

0.30

0.45

0.50

Sales must quote gauge per customer structural requirement — never down-gauge without written customer acknowledgement.

H.1.3 Standard Conversion Factors (kg/m)

Maintained in Procurement — Conversion tab. Example reference values (verify live system):

Gauge (mm)

0.18

0.22

0.30

0.45

0.50

Theoretical metres = kg consumed ÷ kg/m factor

H.2 COIL RECEIPT INSPECTION

H.2.1 On Arrival Checklist

- ☐ PO reference matches delivery note
- ☐ Coil numbers match supplier manifest
- ☐ Weighbridge weight within PO tolerance (typically $\pm 2\%$)
- ☐ Gauge verified with micrometer (sample)
- ☐ Colour matches PO specification (visual)
- ☐ No edge damage, rust, or oil contamination
- ☐ Mill test certificate collected

H.2.2 Rejection Criteria

Reject coil (do not GRN) if: - Weight short > agreed tolerance - Wrong gauge or colour - Visible lamination defect - Water damage

Notify Procurement and MD; photograph damage; supplier claim initiated.

H.3 PRODUCTION STANDARDS

H.3.1 Corrugation Profiles

Profile

Long-span

Step-tile

Custom

H.3.2 Quality Standards

Parameter

Profile depth

Cover width

Colour uniformity

Edge condition

Metre count

H.3.3 Stone-Coated Production

1. Substrate coil → corrugation → stone application
 2. Sheets counted; $m^2 = \text{sheets} \times \text{area per sheet}$
 3. stoneFlatsheetSheetsToM2 conversion in system
 4. Quality: stone adhesion test per batch (QCO)
-

H.4 OFFCUT MANAGEMENT

H.4.1 Normal Offcut

Production waste within 3% of theoretical — no material incident required.

H.4.2 Abnormal Offcut

Waste >3% or identifiable defect: 1. Log material incident (production_offcut type) 2. BM approves 3. Metres added to offcut pool 4. Available for smaller orders or internal use

H.4.3 Offcut Issuance

When production uses offcut pool metres: 1. Select incident on job completion 2. System decrements meters_available on incident 3. Completion record shows “supplied from offcut” 4. May affect costing (AP3) — lower material cost

H.5 STOCK REGISTER PROCEDURE (DETAILED)

H.5.1 Physical Count Scope

Asset Class

Coil lots

Finished goods

Accessories

Stone stock

WIP

H.5.2 Variance Investigation

Variance

Coil kg

FG metres

Accessories

H.5.3 BM Adjustment Window

Between store_confirmed and bm_approved: - BM may post adjustment entries with documented reason - After bm_approved: adjustments require MD and new count cycle

H.6 DELIVERY STANDARDS

H.6.1 Loading

- Secure strapping per safety standard

- Gauge/colour labels visible on bundles
- Delivery note matches system DLV lines
- Vehicle capacity not exceeded

H.6.2 Proof of Delivery

Required fields on POD: - Customer name and signature - Date and time - Metres delivered per line - Condition notes (damage at delivery) - Driver name

POD scanned and attached to delivery record in system.

End of Annex H — Inventory & Production Standards