



CONTROLLER SERVICES

- DebuggerService
- ModulesService
- InterceptorService
- ExceptionService
- PluginService
- HandlerService
- RequestService

SAMPLE HANDLER CODE

```
Component{
    this.allowedMethods = {};

    any function index(event){
        return "Hello";
    }
}
```

CORE PLUGINS

- AntiSamy
- ApplicationStorage
- BeanFactory
- CFCViewer
- ClientStorage
- ClusterStorage
- CookieStorage
- DateUtils
- FeedGenerator
- FeedReader
- FileUtils
- i18n
- IOC
- JavaLoader
- JSON
- JVMUtils
- Logger
- MailService
- MessageBox
- MethodInjector
- ORMService
- QueryHelper
- Renderer
- ResourceBundle
- SessionStorage
- StringBuffer
- Timer
- Utilities
- Validator
- Webservices
- XMLConverter
- Zip

CORE INTERCEPTORS

- Autowire
- ColdboxSideBar
- Deploy
- EnvironmentControl
- Security
- SES

HANDLER PROPERTIES

- This scope properties
- event_cache_suffix
- preHandler_only
- preHandler_except
- postHandler_only
- postHandler_except
- allowedMethods

IMPLICIT HANDLER EVENTS

- preHandler, pre{Action}
- postHandler, post{Action}
- onMissingAction

FOLDER CONVENTIONS

- Application.cfc
- index.cfm (empty)
- config
 - Coldbox.cfc
 - Routes.cfm
- handlers
- model
- modules
- layouts
- views

FRAMEWORKSUPERTYPE

- \$abort(), \$dump(), \$htmlhead(), \$include(), \$throw(), \$rethrow()
- addAsset(assetList)
- announceInterception(state, [interceptData])
- getColdBoxOCM([cachename])
- getController()
- getDatasource(alias)
- getDebugMode()
- getfwLocale()
- getInterceptor(name)
- getModel(name, [useSetterInjection], [onDICompleteUDF], [stopRecursion], [dsl], [executelnit])
- getMailSettings()
- getMyPlugin(plugin, [newInstance])
- getPlugin(plugin, [customPlugin], [newInstance])
- getResource(resource, [default], [locale])
- getSetting(name, [fwSetting])
- getSettingsBean()
- getSettingStructure([fwSetting], [DeepCopyFlag])
- includeUDF(udfLibrary)
- persistVariables(persist, [persistStruct])
- populateModel(model, scope, trustedSetter, include, exclude)
- renderExternalView(view)
- renderLayout(layout)
- renderView([view], [cache], [Timeout], [LastAccessTimeout])
- runEvent(event, [prepostExempt], [private])
- setDebugMode(mode)
- setNextEvent(event, [queryString], [addToken], [persist], [persistStruct], [ssl], [baseURL], [postProcessExempt], [URL], [URI], [statusCode])
- setSetting(name, value)
- setFWLocale(locale)
- settingExists(name, [fwSetting])

INTERCEPTOR METHODS

- configure()
- getProperties(properties)
- setProperties()
- getProperty(name)
- setProperty(name, value)
- propertyExists(name)
- unregister(state)
- clearBuffer()
- appendToBuffer(string)
- getBufferString()
- getBufferObject()


REQUEST CONTEXT COMMON METHODS (RECEIVED AS EVENT)

- buildLink(linkto, [translate], [ssl], [baseURL], [queryString])
- clearCollection()
- collectionAppend(collection, [overwrite])
- getCollection([DeepCopyFlag], [private])
- getCurrentAction()
- getCurrentEvent()
- getCurrentHandler()
- getCurrentLayout()
- getCurrentModule()
- getCurrentRoute()
- getCurrentRoutedURL()
- getCurrentView()
- getDefaultLayout()
- getDefaultView()
- getEventName()
- getHTTPHeader(header, [default])
- getHTTPMethod()
- getModuleRoot()
- getSESBaseURL(), setSESBaseURL()
- getSize()
- getTrimValue(name, [default], [private]), getValue(name, [default], [private])
- isAjax()
- isProxyRequest()
- isSES()
- isSSL()
- noExecution()
- noRender([remove])
- overrideEvent(event)
- paramValue(name, value, [private])
- renderData(type, data, [contentType], [encoding], [statusCode], [statusText], [jsonCase], [jsonQueryFormat][jsonAsText], [xmlColumnList], [xmlUseCDATA], [xmlListDelimiter], [xmlRootName])
- removeValue(name, [private])
- setHTTPHeader(statusCode, statusText, name, value, charset)
- setLayout(name)
- setValue(name, value, [private])
- setView(name, [noLayout], [cache], [cacheTimeout], [cacheLastAccessTimeout], [cacheSuffix], [layout])
- valueExists(name, [private])
- showDebugPanel(boolean)

CONTROLLER COMMON METHODS

- getAppRootPath()
- getCacheBox()
- getLogBox()
- getWireBox()
- getColdboxOCM([name])
- getColdboxSettings()
- getConfigSettings()
- getPlugin(plugin, [customPlugin], [newInstance])
- get{ServiceName}()
- getSettingStructure([fwSetting], [DeepCopyFlag])
- getSetting(name, [fwSetting])
- persistVariables(persist, [persistStruct])
- runEvent(event, [prepostExempt], [private])
- settingExists(name, [fwSetting])
- setSetting(name, value)
- setNextEvent(event, [queryString], [addToken], [persist], [persistStruct], [ssl], [baseURL], [postProcessExempt], [URL], [URI], [statusCode])

COLDBOX COMMON CLASSES





SAMPLE INTERCEPTOR

```
component{
    function configure(){
        //configure properties here
    }
    //method = interception point
    function preprocess(interceptData,
        event){
    }
}
```

SAMPLE PLUGIN

```
component singleton=true{
    function init(){
        setPluginName("MyPlugin");
        setPluginVersion("1.0");
        setPluginDescription("MyPlugin");
        setPluginAuthor("YourName");
        setPluginAuthorURL("www.my.com");
    }
}
```

COLDBOX CONFIG

- › Coldbox (struct)
- › Settings (struct)
- › Conventions (struct)
- › Environments (struct)
- › loc (struct)
- › Models (struct)
- › Debugger (struct)
- › mailSettings (struct)
- › l18n (struct)
- › BugTracers (struct)
- › WebServices (struct)
- › Datasources (struct)
- › LayoutSettings (struct)
- › Layouts (array of structs)
- › Cachebox (struct)
- › Logbox (struct)
- › InterceptorSettings (struct)
- › Interceptors (array of structs)
- › Modules (struct)

CONFIG INJECTED VARS

- › AppMapping
- › Controller
- › LogBoxConfig

SES ROUTE METHODS

- › addRouter(*)
- › addModuleRoutes(pattern, module)
- › setBaseURL()
- › setUniqueURLS()
- › setAutoReload()
- › setExtensionDetection()
- › setValidExtensions()
- › setLooseMatching()

* ADDROUTE()

- › [pattern]
- › [handler]
- › [action]
- › [matchVariables]
- › [view]
- › [viewNoLayout]
- › [valuePairTranslation]
- › [constraints]
- › [module]

SES ROUTES

- › Default Pattern : handler/:action?
- › :var ANY Placeholder
- › :var-numeric Numeric
- › :var-alpha Alpha
- › :var{X} Limit by X
- › ? = optional placeholder
- › :regex() Limit by regex
- › Valid Extensions: xml, json, json, html, htm, rss

URL ACTIONS (INDEX.CFM?)

- › fwreinit=1 or {reinitPassword}
- › debugmode=true
- › debugpass={DebugPass}
- › fwcache=anything
- › dumpvar=varlist

COLDBOX INTERCEPTION POINTS

- › afterConfigurationLoad()
- › afterAspectsLoad()
- › afterPluginCreation() *
 - › pluginPath, custom, oPlugin
- › afterHandlerCreation() *
 - › handlerPath, oHandler
- › afterModelCreation() *
 - › modelName, oModel
- › applicationStart()
- › applicationEnd()
- › onException() *
 - › exception
- › onReinit()
- › preprocess()
- › postProcess()
- › preEvent()
 - › processedEvent
- › preLayout()
- › preProxyResults()
- › preRender() *
 - › renderedContent
- › postEvent() *
 - › processedEvent
- › postRender()
- › preViewRender()
 - › View, cache, cacheTimeout, cacheLastAccessTimeout, cacheSuffix, module
- › postViewRender()
 - › View, cache, cacheTimeout, cacheLastAccessTimeout, cacheSuffix, module, renderedView
- › sessionStart()
- › sessionEnd()

* Has intercept data

CACHEBOX INTERCEPTION POINTS

- › afterCacheElementInsert()
 - › Cache, cacheObject, cacheObjectKey, cacheObjectTimeout, cacheObjectLastAccessTimeout
- › afterCacheElementRemoved()
 - › Cache, cacheObjectKey
- › afterCacheElementExpired()
 - › Cache, cacheObjectKey
- › afterCacheElementUpdated()
 - › Cache, cacheNewObject, cacheOldObject
- › afterCacheClearAll()
 - › Cache
- › afterCacheRegistration()
 - › Cache
- › afterCacheRemoval()
 - › Cache (name)
- › beforeCacheRemoval()
 - › Cache
- › beforeCacheReplacement()
 - › oldCache, newCache
- › afterCacheFactoryConfiguration()
 - › cacheFactory
- › beforeCacheFactoryShutdown()
 - › cacheFactory
- › afterCacheFactoryShutdown()
 - › cacheFactory
- › beforeCacheShutdown()
 - › cache
- › afterCacheShutdown()
 - › Cache

* Has intercept data

SES INTERCEPTOR PROPERTIES

- › configFile : relative or absolute routes file defaults to (config/Routes.cfm)

ENVIRONMENTCONTROL INTERCEPTOR PROPERTIES

- › configFile : relative or absolute file location
- › fireOnInit : [boolean=true]

SECURITY INTERCEPTOR PROPERTY

- › useRegex : [boolean=true]
- › rulesSource : [string=xml, db, ioc, ocm, model]
- › queryChecks : [boolean=true]
- › preEventSecurity : [boolean=false]
- › validator : [classpath]
- › validatorIOC : [bean name]
- › validatorModel : [model name]

OBJECT PERSISTENCE ANNOTATIONS

- › @Singleton
- › @cache = true or false
- › @cacheTimeout = minutes
- › @cacheLastAccessTimeout = minutes

PROPERTY, SETTER, ARGUMENT ANNOTATIONS

- › @inject = Autowire DSL

AUTOWIRE INTERCEPTOR PROPERTIES

- › completeDIMethodName : [string=onDIComplete]
- › enableSetterInjection : [boolean=false]
- › annotationCheck : [boolean=false]
- › entityInjection : [boolean=false]
- › entityInclude : [string]
- › entityExclude : [string]

DEPLOY INTERCEPTOR PROPERTIES

- › tagFile : relative or absolute file location
- › deployCommandObject : instantiation path
- › deployCommandModel : [model name]

COLDBOXSIDEBAR INTERCEPTOR PROPERTIES

- › baseAppPath : [string=cgi.script.name]
- › cssPath : [string]
- › jsPath : [string]
- › URLParamNameList : [string]
- › Yoffset : [numeric]
- › slideSpeed : [numeric]
- › waitTimeBeforeOpen : [numeric]
- › waitTimeBeforeClose : [numeric]
- › isScroll : [boolean]
- › Links : [array]
- › Width : [numeric]
- › visibleWidth : [numeric]
- › imagePath : [path]
- › imageVAlign : [numeric]