Device Type:	Router
Enclosure Type:	Desktop - modular - 1U
Connectivity Technology:	Wired
Data Link Protocol:	Ethernet, Fast Ethernet
Network / Transport Protocol:	IPSec
Remote Management Protocol:	SNMP 3
Encryption Algorithm:	DES, Triple DES, AES
Features:	Modular design, firewall protection, 128-bit encryption, hardware encryption, VPN support, MPLS support, URL filtering, 256-bit encryption
Compliant Standards:	CISPR 22 Class A, CISPR 24, EN 61000-3-2, VCCI Class A ITE, IEC 60950, EN 61000-3-3, EN55024, EN55022 Class A, UL 60950, EN50082-1, CSA 22.2 No. 60950, AS/NZ 3548 Class A, JATE, FCC Part 15, ICES-003 Class A, CS-03, EN 61000-6-2
RAM:	256 MB (installed) / 384 MB (max) - SDRAM
Flash Memory:	64 MB (installed) / 128 MB (max)
Status Indicators:	Power, link/activity
Expansion / Connectivity	
Interfaces:	2 x 10Base-T/100Base-TX - RJ-45 USB: 1 x Management: 1 x console - RJ-45 1 x auxiliary - RJ-45
Expansion Slots:	2 (total) / 2 (free) x HWIC 2 (total) / 2 (free) x AIM 2 (total) / 2 (free) x PVDM 1 (total) / 1 (free) x WIC 1 (total) / 1 (free) x VIC 1 memory 1 CompactFlash
Power	
Power Device:	Internal power supply
Software / System Requirements	
OS Provided:	Cisco IOS Advanced Security
Dimensions & Weight	
Width:	44.5 cm
Depth:	41.9 cm
Height:	4.37 cm
Weight:	6.2 kg
Environmental Parameters	
Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 85%