Compliant Standards:	C-Tick, VDE, IEC 60950, EN 50091-2, RoHS, EN 50091-1, REACH, EN 62040-2, IP20, EAC
Depth:	71.5 cm
Device Type:	UPS - rack-mountable / external
Efficiency:	98%
Expansion Slots:	1 (total) / 1 (free) x SmartSlot
Features:	Audible alarm, LCD display
Frequency Provided:	50/60 Hz
Frequency Required:	45 - 65 Hz
Height:	43.2 cm
Height (Rack Units):	6U
Humidity Range Operating:	0 - 95% (non-condensing)
Input Connectors:	Hardwire 5-wire (3PH + N + G), hardwire 3-wire (1PH + N + G)
Input Voltage:	AC 230 V
Interfaces:	1 x management (Ethernet) - RJ-45 ¦ 1 x management (USB) - 4 pin USB Type B ¦ 1 x EPO (emergency power off) ¦ 1 x serial - RJ-45
Max Operating Temperature:	40 °C
Min Operating Temperature:	0 °C
Output Voltage:	AC 230 V ± 3% - 50/60 Hz
Output Waveform:	Sinewave
Power Capacity:	8000 Watt / 8000 VA
Power Output Connectors Details:	6 x power IEC 60320 C13 ¦ 4 x power IEC 60320 C19 ¦ 1 x hardwire 3-wire (HN + G) ¦ 3 x IEC connector
Recharge Time:	3 hours
Remote Management Interface:	Ethernet 10/100, USB
Run Time (Up To):	5.3 min at full load ¦ 14.8 min at half load
Shipping Depth:	100 cm
Shipping Height:	46.1 cm
Shipping Weight:	126.82 kg
Shipping Width:	60 cm
Software Included:	APC PowerChute Business Edition
Sound Emission:	55 dBA
Surge Energy Rating:	480 Joules
Surge Suppression:	Yes
Technology:	Lead Acid
UPS Technology:	On-line
Version:	original
Weight:	111.82 kg
Width:	26.3 cm