

Litespeed Web Server Open 1.3.12 Log Web Console Configuration

Listeners (1) Virtual Hosts (1) Virtual Host Templates (3) Server

Virtual Host » iipsrv-vhost

FastCGI App Definition

Name

• UDS is chrooted in chroot environment.

Basic General Log Security External App Script Handler Rewrite Context SS	. Web Socket Proxy Module	s

- Give a name that easy to remember, other places will refer to this app by its name.
- Address can be IPv4 socket address "IP:PORT", like 192.168.1.3:7777 and localhost:7777 or Unix domain socket address "UDS://path" like UDS://tmp/lshttpd
- /myfcgi.sock.

iipsrv-app

- For local FCGI, Unix domain socket is preferred due to security and better performance. If you have to use IPv4 socket, set the IP part to localhost or 127.0.0.1, thus the FCGI is inaccessible from other machines.
- Local FCGI can be started by the web server. In this case, you need to specify path, backlog and number of instances.

	_	
Address	②	127.0.0.1:9000
Notes	②	IIPImage Fast-CGI server
Max Connections	2	number valid range: 1 - 2000 12
Environment	?	VERBOSITY=0 JPEG_QUALITY=90 MAX_CVT=3000 MAX_IMAGE_CACHE_SIZE=100 MEMCACHED_SERVERS=localhost
Initial Request Timeout (secs)	2	number >= 1 15
Retry Timeout (secs)	2	number >= 0 15
Persistent Connection	②	Yes No Not Set
Connection Keepalive Timeout	②	number valid range: -1 - 10000 5
Response Buffering	2	Yes A
Auto Start	②	Yes
Command	2	/var/www/fcgi-bin/iipsrv.fcgi
Back Log	2	number valid range: 1 - 100
Instances	2	number valid range: 0 - 1000
suEXEC User	2	
suEXEC Group	②	
umask	2	
Run On Start Up	2	No The No.
Max Idle Time	2	number >= -1
Priority	2	number valid range: -20 - 20