

The Welkin Standard

Oscar Bender-Stone

Conventions

- Each topic uses content from `bootstrap.welkin`. We write (n) for the n -th line in the bootstrap file.

Syntax

Terminals

- Logic
- Symbols (1): 0, 1
- Successor S
- Implication \Rightarrow
- Table of US-ASCII:

Symbol	Encoding
{	173
}	175

- A **word** is recursively defined (1).
 - Base case:
 - 0 is a word.
 - 1 is a word.
 - Recursion: let w be a word.
 - $w.0$ is a word.
 - $w.1$ is a word.
- Concatenation
 - Base case: $w.\varepsilon = w$.
 - Recursion:
 - $w.(u.0) = (w.u).0$
 - $w.(u.1) = (w.u).1$

Atoms

- Strings are words with delimiters: $d_1.w.d_2$, where $d_1 \not\in w$ and $d_2 \not\in w$.
- Identifiers are strings without white space.
- Numbers are a subset of strings with an injective function $q : \text{NUMBER} \rightarrow Q$.
 - Q is set of strings formed by scientific notation.

Grammar

- LALR
 - Not ambiguous
- Welkin Grammar:

Semantics

Equality on Terms

- Two strings are equal if they contain the same strings, in order.
- Two numbers are equal if $q(a) = q(b)$.

Valid Strings

- No relative members at toplevel (with length 2).
- No duplicate members, graphs, or connections.

Welkin Information Graphs

A **Welkin Information Graph (WIG)** is a structure $G = (T, H, L)$ with:

- A tree T ,
- A hypergraph H ,
- A tree L isomorphic to T .

AST (Recursive)

- Units:
- Members are words of units
- Connections are WIGs with
- Graphs are WIGs with
 - Derived terms as children
 - Ordered triples are arcs.

Encoding

The **encoding** $E(G)$ of the WIG G is the unique string where

- All nodes are listed in breadth-first order
- Leaves are terms ending with “#”
- Edges are enumerated, starting from 0. They are included in nodes:
 - s means source,
 - c means connector,
 - t means target.