

Hvordan rapporten hjalp unit tests

```
class= str' > ,
class="str">" ",
class="str">"A",
class="str">"AA",
class="str">"AAA",
class="str">"AAAA",
class="str">"AAAAA",
class="str">"AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA/
class="str">"AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA/
class="str">"AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA/
class="str">"player.example.com", class="com">// White box value: missing @
class="str">"player@",
class="str">"player@example", class="com">// White box value: missing dot br
class="str">"@example.com", class="com">// White box value: starts with @ br
class="str">"player.example@" class="com">// White box value: ends with @ br
})
void emailShouldRejectInvalidLengths(String email) {
    class="com">// Given
    License subject = new License();

    class="com">// Then
    assertThatThrownBy(() -> subject.setEmail(email))
        .isInstanceOf(IllegalArgumentException.class);
}
```

Coverage-rapporten gjorde testdesignet konkret. Hver branch i setEmail blev omsat til en testværdi: uden @, uden punktum, starter med @, slutter med @ og værdier ved længdegrænserne. Derfor blev testen parameterized og white-box-baseret, så den dækker både positive og negative cases kort og systematisk.