INTRO TO METAFLOW: SIMPLIFY YOUR DATA SCIENCE WORKFLOWS



FAN YANG PHD, LGSW

DR. AN'S AI GROUP

SEP, 2023



- > WHY METAFLOW
- > KEY FEATURES
- > DEMO




01

WHAT IS METAFLOW



Story about Netflix



What is metaflow?



Metaflow is a data science platform that can make data science code usable, scalable, reproducible, and production-ready.



- ① Provide a highly usable API for structuring the code as a workflow, i.e. as a directed graph of steps (usability).
- ② Persist an immutable snapshot of data, code, and external dependencies required to execute each step (reproducibility).
- Facilitate execution of the steps in various environments, from development to production (scalability, productionreadiness).
 - Record metadata about previous executions and make them easily accessible (usability, reproducibility).



Model Development

Feature Engineering

Model Operations

Architecture

Versioning

Job Scheduler

Compute Resources

Data Warehouse





02


WHY METAFLOW















Derived from: outerbound.com








```
from metaflow import FlowSpec, step
class LinearFlow(FlowSpec):
   @step
   def start(self):
        print("Starting linear flow...")
       self.next(self.end)
   @step
   def end(self):
        print("Linear flow finished.")
if __name__ == '__main__':
   LinearFlow()
```







```
from metaflow import FlowSpec, step, resources
class MyFlow(FlowSpec):
    @resources(memory=128000)
   @step
   def start(self):
       import pandas as pd
       # Assuming `big_one` is a pre-defined data structure
       df = pd.DataFrame(big_one)
       self.next(self.end)
   @step
   def end(self):
if __name__ == '__main__':
    MyFlow()
```

Terminal command:


Python myflow.py run – with batch



```
from metaflow import FlowSpec, step, resources
class MyFlow(FlowSpec):
   @step
   def start(self):
       self.params = list(range(100))
       self.next(self.train, foreach='params')
    @resources(memory=128000)
    @step
   def train(self):
       # Replace 'train(...)' with your actual training function
       self.model = "train(...)"
       self.next(self.join)
    @step
   def join(self, inputs):
       # 'inputs' will contain the outputs from the 'train' steps
       pass # Add your joining logic here
if __name__ == '__main__':
   MyFlow()
```




```
from metaflow import FlowSpec, step, S3
import pyarrow.parquet as pq
class MyFlow(FlowSpec):
    @step
    def start(self):
        import spark_client
        SQL = "CREATE TABLE mydata AS SELECT ..."
        self.table_loc = spark_client.query(SQL)
        self.next(self.load_data)
    @step
    def load_data(self):
        with S3() as s3:
            parquet = s3.get(self.table_loc)
            self.table = pq.read_table(parquet.path)
        self.next(self.end)
    @step
    def end(self):
        pass
```










Terminal command:


Python myflow.py step – functions create






```
from metaflow import FlowSpec, step, conda
class MyFlow(FlowSpec):
   # The @conda decorator specifies that this step should run in a Conda env
   # with the given libraries. In this case, TensorFlow version 2.5.0 is spe
   @conda(libraries={'tensorflow': '2.5.0'})
   @step
   def start(self):
       # Import TensorFlow within the scope of the Conda environment
       import tensorflow as tf
       # Initialize the optimizer with some alpha (not defined in this snipp
       tf.optimizer = tf.optimizers.SGD(alpha)
       # Move to the next step
       self.next(self.end)
   # The end step of the workflow.
   @step
   def end(self):
```

Define a stable execution environment





```
from metaflow import FlowSpec, step, retry, catch
class MyFlow(FlowSpec):
   # The @retry decorator specifies that this step should be retried up to
   # in case of failure.
   @retry(times=5)
   # The @catch decorator specifies that in case of a failure, the variable
   # will be set, which can be used to handle or log the failure.
   @catch(var='handle_failure')
   @step
   def start(self):
       # Import pandas and create a DataFrame (Note: 'big_one' is not define
       import pandas as pd
       pd.DataFrame(big_one)
       # Move to the next step
       self.next(self.end)
   # The end step of the workflow.
   @step
   def end(self):
        pass
```



O3 KEY FEATURES



1.Directed Graph of Operations:

- •Represents a program's flow, making it intuitive for data processing pipelines.
- •Especially suitable for machine learning workflows.

2.Flow:

- •The graph of operations.
- •Comprises steps (nodes) and transitions (edges).

3.Steps:

- Operations in the flow.
- •Every flow must have a "start" and an "end" step.

4.Run:

- Execution of the flow.
- Begins at "start" and concludes successfully at "end".

Summary: Metaflow offers a structured yet flexible approach to designing data-driven workflows, ensuring clarity from start to finish.

1.Linear Transition:

Represents a direct flow from one operation to the ne

```
start — a — end
```

A graph with two linear transitions

The journey from "start" to "end" is customizable.

```
from metaflow import FlowSpec, step
# Define a new workflow class that inherits from FlowSpec
class LinearFlow(FlowSpec):
    # Decorator that indicates the following function is a step in the workf
    @step
    def start(self):
        # Print message indicating the start of the workflow
        print("Starting linear flow...")
        # Indicate the next step to run after 'start' is 'end'
        self.next(self.end)
    # Decorator that indicates the following function is a step in the workf
```

Ensure the workflow is executed when the script is run
if __name__ == '__main__':
 # Run the LinearFlow workflow

print("Linear flow finished.")

Print message indicating the end of the workflow


Import necessary modules from Metaflow

@step

def end(self):

LinearFlow()

2. Artifacts



Key Benefits of Artifacts:

1.Automated Data Management:

- 1. Manage data flow effortlessly.
- 2. No manual data loading or storing.

2.Persistence for Future Use:

- 1. Analyze later using the Client API.
- 2. Visualize with Cards or use across different flows.


3.Consistency Across Environments:

- 1. Seamlessly transition between local and cloud environments.
- 2. No explicit data transfer required.

4.Debugging & Recovery:

- 1. Access past artifacts to inspect data before failures.
- 2. Resume past executions post bug fixes.


2. Artifacts



```
from metaflow import FlowSpec, step
class ArtifactFlow(FlowSpec):
   @step
   def start(self):
       # Create an artifact named 'greeting'
       self.greeting = "Hello, Metaflow!"
       print(self.greeting)
       self.next(self.modify)
   @step
   def modify(self):
       # Modify the artifact
       self.greeting += " How are you today?"
        print(self.greeting)
       self.next(self.end)
   @step
   def end(self):
       # Use the modified artifact
       print(f"Final message: {self.greeting}")
if __name__ == '__main__':
   ArtifactFlow()
```

3. Branch Transition

We can express parallel steps with **a branch**. In the figure below, start transitions to two parallel steps, a and b.



A benefit of a branch is performance: Metaflow can execute a and b over multiple CPU cores or over multiple instances in the cloud.

3. Branch

```
class BranchFlow(FlowSpec):
       @step
       def start(self):
           self.next(self.a, self.b)
 9
       @step
       def a(self):
           self.x = 1
           self.next(self.join)
13
14
       @step
15
       def b(self):
           self.x = 2
16
           self.next(self.join)
18
19
       @step
       def join(self, inputs):
           print('a is %s' % inputs.a.x)
           print('b is %s' % inputs.b.x)
           print('total is %d' % sum(inputs.x for inputs in [inputs.a, inputs.b]))
23
           self.next(self.end)
24
25
26
       @step
       def end(self):
28
           pass
29
30
        name == ' main ':
       BranchFlow()
```

from metaflow import FlowSpec, step

- > Card
 - •What is a Card?
 - A UI component for visualizing data and results.
 - Key Features
 - Interactive Visualizations
 - Shareable Insights
 - Traceability
 - Use Cases
 - Debugging
 - Data Exploration
 - Reporting

04DEMOS



4. Demo

> Sandbox

- •Purpose: Exclusive for testing Metaflow in data science.

 Not for production or general computation.
- •Data Caution: Test with datasets, avoid confidential, personal, or sensitive data.
- •Duration: Default access is 7 days.

Post-expiry, data is deleted.

Extend by request.

- •Connectivity: No internet in the Sandbox.
 - Common R libraries pre-installed.
- •Capabilities: Use up to 8 instances with 8 cores & 30GB RAM using the batch decorator.


05

RESOURCES AND REFERENCES

7.1 References and Resources

https://app.slack.com/

- https://docs.metaflow.org/
- https://github.com/Netflix/metaflow/tree/master/metaflow/tutorials/0 0-helloworld
- **Tutorial code on Github.**
- https://outerbounds.com/
- Sandbox



THANKS FOR LISTENING!