

```

/*:
## Exercise – Create a Protocol

Create a protocol called `Vehicle` with two requirements: a nonsettable
`numberOfWheels` property of type `Int`, and a function called `drive()`.
*/
protocol Vehicle {
    var numberOfWheels: Int { get }
    func drive()
}

//: Define a `Car` struct that implements the `Vehicle` protocol.
`numberOfWheels` should return a value of 4, and `drive()` should print
"Vroom, vroom!" Create an instance of `Car`, print its number of wheels, then
call `drive()`.
struct Car: Vehicle {
    var numberOfWheels: Int = 4

    func drive() {
        print("Vroom, vroom!")
    }
}

let c1 = Car()
print(c1.numberOfWheels)
c1.drive()
//: Define a `Bike` struct that implements the `Vehicle` protocol.
`numberOfWheels` should return a value of 2, and `drive()` should print
"Begin pedaling!". Create an instance of `Bike`, print its number of wheels,
then call `drive()`.
struct Bike: Vehicle {
    var numberOfWheels: Int = 2
    func drive() {
        print("Begin Petalling")
    }
}

let b1 = Bike()
print(b1.numberOfWheels)
b1.drive()
/*:
[Previous](@previous) | page 3 of 5 | [Next: App Exercise – Similar
Workouts](@next)
*/

```