Panorama Stitcher: User Manual

Other languages: Česky · Deutsch

A desktop program that joins overlapping photos into one panorama or mosaic: JPEG, TIFF, PNG, camera RAW and astronomical FITS images. Every step runs only when you press its button, and you can inspect and correct each result before going on. A second tab stacks star images into a low-noise night sky or star trails (Star stacking).

Contents

1. Requirements
2. Starting the program
3. The window at a glance
4. Quick start
5. Step by step
6. Navigating the view
7. Projections
8. RAW files
9. FITS files (astronomy)
10. Saving
11. Troubleshooting
12. Tips for good panoramas
13. Star stacking
14. Use from a script (no window)
15. Files

---

1. Requirements

- **Julia 1.13 or newer**
- **Camera RAW files** need nothing extra: LibRaw comes with the program. RawTherapee, darktable or dcraw are used too if you have them installed (see RAW files).
- **FITS files** need nothing extra.
- **File dialogs** need nothing extra on Windows and macOS. On Linux they use `zenity`, `kdialog` or `yad`, whichever is installed (most desktops have one). Without any of them, you type paths into the path box instead.

The Julia packages it needs are listed in `app/Project.toml` and are installed automatically the first time you start the program.

---

2. Starting the program

From a terminal:

```
cd PanoStitch        # the folder the program is in
julia bin/panostitch.jl
```

You can also list photos to load straight away:

```
julia bin/panostitch.jl ~/Pictures/pano/*.NEF
```

From VS Code: open `bin/panostitch.jl` and choose Julia: Execute File in REPL (`Alt+Enter`).

Notes:

- **Keep the terminal open** while you work. Closing it closes the program.
- The program uses all CPU cores automatically. If you start it without `-t auto`, it restarts itself with that option. In VS Code the project's setting `"julia.NumThreads": "auto"` does the same.
- **The first start** after installing or changing the code prepares (precompiles) the program. This takes up to a few minutes, once. After that the window opens in about 5 seconds.

---

3. The window at a glance

```
┌──────────────────────┬──────────────────────────────────────┬──────────────────────┐
│ [Open…] [Save proj.] │ [Image+keypoints] [Pair matches]     │ 3 · Projection       │
│ Images               │ [Panorama] [Zoom +] [Zoom -] [Fit]   │  projection menu     │
│  Add Remove Clear ▲▼ │ (o) overlays  [Undo] [Redo]          │  Focal, Yaw, Pitch,  │
│  path box            │                                      │  Roll                │
│  image list          │                                      │ 4 · Compose          │
│  Reference           │            main view                 │  Blend, Preview size │
│  RAW via, half size  │                                      │  Exposure,Brightness │
│  Preset              │                                      │  show unlinked       │
│ 1 · Features         │                                      │  Auto crop, Uncrop   │
│                      │                                      │  Nudge ← ↑ ↓ →       │
│ 2 · Matching         │                                      │ 5 · Stretch          │
│  Pairs, Model, Pair  │                                      │  histogram, sliders  │
│  pair details        │  status line (red text)              │ [Preview] [Save…]    │
└──────────────────────┴──────────────────────────────────────┴──────────────────────┘
```

- **Left column:** open and save projects, choose the images, find features, match the images.
- **Middle:** the main view, with buttons to switch views, zoom, hide the overlays, and undo or redo.
- **Right column:** projection, exposure, blending, brightness, manual placement, histogram stretch, preview and saving.
- **Red status line** (under the view): what the program is doing, results, and error messages.

The switches at the top right change the appearance: **Dark**, **Modern** (a flatter look with icons) and **Simple**. Simple mode hides the detailed controls (feature detection and matching settings, blending, stretch, nudging) and keeps what most panoramas need: the images, a preset, **Run all steps**, the projection with focal length, yaw, pitch and roll, exposure, **Even out**, crop, preview and saving. The hidden settings keep their preset values. The program remembers the switches.

4. Quick start

Photo panorama:

1. Leave **half size** on. It is faster, and plenty for checking the result.
2. Choose a **Preset** that fits your subject (see Presets).
3. Type the folder of your photos into the path box and press **Enter**, or click **Add…** and select the photos. **The order does not matter.**
4. Click **Run all steps** and wait until the status line says Done.
5. Choose a **projection** on the right: **cylindrical** for a single row, **spherical** for several rows or anything reaching far up or down. Click **Auto exposure** if it is too dark, and adjust **Pitch** if the horizon is bent. Click **Auto crop** to cut away the ragged edges.
6. Click **Save full resolution…**. Click **Save project…** if you want to come back to it later.

Deep-sky mosaic from FITS files:

1. Choose the **deep-sky mosaic** preset.
2. Load the FITS tiles (stacked or single frames). They are stretched automatically for viewing.
3. Click **Run all steps**, then **Auto stretch** to fit the stretch to the whole mosaic, and adjust it if you like.
4. Save as `.fits` to keep the linear data for further processing, or as `.tif` to get the stretched picture you see.

---

5. Step by step

Typing values: every slider has a number box next to it. Click the box, type a value and press **Enter**. The value snaps to the slider's step and range.

5.0 Presets

The **Preset** menu (left column, under RAW via) sets all matching and composing settings for a type of subject at once. Every value can still be changed afterwards.

Preset	For	Main settings
day landscape	daylight panoramas, camera rotated in place	light denoising, homography, cylindrical
astro / night landscape	night skies, Milky Way over a landscape	strong denoising, looser matching, spherical, +2 EV (then **Auto exposure**)
deep-sky mosaic	telescope mosaics of star fields, e.g. FITS	little denoising (stars are tiny), similarity model (shift + field rotation), no refinement, rectilinear; use **Auto stretch**
macro / microscope	a slide or stage moved under a fixed camera	translation model (frames only shift), no refinement, rectilinear
scan / flat document	maps, paintings, documents photographed in parts	affine model, no refinement, rectilinear

5.1 Images

Control	What it does
Add…	Opens a file dialog. You can select several files (Ctrl/Shift-click).
Path box	Type a file or **folder** path and press Enter. A folder loads all images in it, sorted by name. Files named `panorama…` (earlier results) are skipped.
Image list	Click an image to select it and show it. **Ctrl-click** adds or removes one image from the selection, **Shift-click** selects a range, and **Ctrl+A** (with the mouse over the list) selects all. Scroll with the mouse wheel.
Remove	Removes the selected images. The **Delete** key does the same while the mouse is over the list.
Clear all	Removes all images.
▲ / ▼	Moves the selected images up or down in the list. Only the sequential and grid pair modes care about the order.
Reference	The image the others are placed around; it stays undistorted. **auto (centre)** picks the image in the middle of the group, which usually gives the most even result.
RAW via	Which RAW converter to use; see RAW files. Applies to images added afterwards.
half size	Decodes RAW files and colour-camera FITS files at half resolution: about 4× faster and ¼ of the memory. Applies to images added afterwards. Turn it off before loading if you want a full-resolution result.

The list marks each entry:

Mark	Meaning
blue line	selected; the darker one is the current image (for viewing, brightness and moving)
`R`	reference image
`4345kp`	number of features (keypoints) found
`UNLINKED`	the image could not be connected to the panorama (see 5.3)

Matching results are kept when you reorder images or remove other images, so you do not have to match again.

5.2 Step 1: Features

Features (keypoints) are distinctive spots, such as corners, edges and stars, that can be recognised in two overlapping images.

Slider	Default	Meaning
Detection size (px)	2000	The image is shrunk to this size (longest side) before searching. Larger is more precise but slower.
Max keypoints	5000	Upper limit per image. Keypoints are spread evenly over the whole image.
Corner threshold	0.001	Minimum corner strength. Lower finds weaker corners (useful for sky or fog); higher keeps only strong ones.
Denoise (σ px)	1.5	Blurs away sensor noise before searching. Raise it (2–3) for **night shots** or noisy high-ISO photos; lower it (0.5–1) for star fields and clean daylight photos with fine detail.

Click **Detect features**. The view shows the current image with the keypoints as **yellow circles**. They should be spread over the parts of the image that overlap other images. Only images whose settings changed are processed again. Dark

and linear images (night shots, FITS) are handled: detection adjusts the contrast internally.

5.3 Step 2: Matching

Matching finds the same keypoints in two images. Then **RANSAC** keeps only the matches that agree with a single geometric model (the inliers).

Which pairs are tried (Pairs menu):

Pairs	Use when
all pairs	Default. Every image is tried against every other one, so **the order does not matter**, and several rows work automatically. Takes longer for many images (74 photos ≈ 35 s).
sequential	One row, images in shooting order. Each image is matched only with the next one in the list. Fastest.
grid	Several rows in a known order: **Grid columns** images per row, row after row. Neighbours to the right, below and diagonally are tried. Switch on **snake** if every second row was shot in the opposite direction.

Settings:

Control	Default	Meaning
Grid columns	5	Images per row (grid mode only).
Ratio test	0.8	How much better the best match must be than the second best. Lower is stricter (fewer, more reliable matches); higher gives more matches.
Max distance	0.35	How different two keypoints may look and still match.
RANSAC tol. (px)	5.0	How far (in pixels) a match may be from the model and still count as an inlier.
Min. inliers	20	Fewest inliers for a pair to count as a real overlap.
Model	homography	How one image maps onto another, see below.
refine	on	Global refinement, see below.

When a pair counts as a real overlap: it needs at least Min. inliers inliers, a clear majority of its matches must agree, and the transform must be plausible (it must not fold or extremely stretch the image). This filters out false matches between images that do not actually overlap.

Models:

Model	Use when
homography	Normal panoramas: camera rotated in place. The default.
affine	Scans, or photos of a flat object from far away.
similarity	Only shifting, rotating and uniform scaling, e.g. telescope mosaics with field rotation. Stable when there are few matches.
translation	Only shifting, e.g. a scanner or a microscope stage. Most robust, least flexible.

Placement and global refinement (refine): the images are linked through their strongest pairs, starting from the reference image. With **refine** on (homography model only), all pairs are then solved together as one rotating camera. That spreads small errors evenly instead of letting them add up, and closes the loops between rows; this removes most ghosting. It also estimates the lens's barrel distortion

(strong in wide-angle lenses) and corrects it when rendering. Pairs that do not fit the common solution are **rejected automatically**, because they are usually false matches or something that moved. The status line reports how many were rejected and the **typical pair error** (1–3 px is good).

Buttons:

- **Match**: matches the pairs chosen in the Pairs menu (in parallel), then places and refines.
- **Re-match pair**: matches only the pair shown, with the current settings.
- **Discard pair**: stops using the pair shown (for a match you can see is wrong); the placement is redone without it.
- **Run all steps**: features, matching, placement and preview in one go.

The **Pair matches** view shows two images side by side:

- **green lines**: inliers (correct matches)
- **red lines**: outliers. Hide them with the **outliers** switch.

The **Pair** menu lists the accepted pairs with their number of inliers. Pairs marked rejected failed one of the checks; the text below the menu says why.

What good looks like: dozens of green lines or more, all describing the same shift, and a mean error of 1–2 px.

Unlinked images: an image with no accepted pair to the rest is marked `UNLINKED` in the list and **left out of the panorama**, so it cannot spoil it. Switch on **show unlinked images** (right column) to show such images in a row below the panorama and place them by hand with **Ctrl+drag**.

5.4 Step 3: Projection

See Projections for what each one looks like.

Control	Meaning
Projection menu	14 projections, see Projections
Focal (× auto)	The focal length is estimated from the matches. This slider scales it. If the panorama looks squeezed or stretched sideways, try values between 0.8 and 1.2.
Yaw (°)	Turns the whole panorama left or right: chooses which direction is in the centre. Useful for 360° panoramas (e.g. to put the Milky Way core in the middle instead of at the edge).
Pitch (°)	Tilts the whole panorama up or down. Use it to **straighten a curved horizon** (for example if the camera was pointed down).
Roll (°)	Rotates the whole panorama. Use it to level a sloping horizon.
Reset focal / yaw / pitch / roll	Returns these four sliders to their defaults.

The view title shows the panorama size, the focal length in pixels, the field of view of the reference image, and the typical alignment error.

These controls update the preview immediately (once a preview exists).

5.5 Step 4: Compose

Control	Meaning
Blend	**smart** (default): multi-band blending with deghosting. Fine detail comes from one image per spot, so there are no double images of people, lights or close objects. Brightness differences are blended over a wide zone, so there are no hard joins. Wherever overlapping images disagree (something moved), that whole area is taken from one image. **feather**: plain smooth mixing; shows ghosts where things moved. **seam**: each pixel from the most central image; no ghosts, but hard joins. **average**: plain mean; mainly for checking alignment.
Preview size (px)	Size of the preview image (longest side). Larger is sharper but slower. Zooming in renders detail anyway (see Navigating the view).
Exposure (EV)	Brightens or darkens the whole panorama, from −3 to +8 EV (+1 EV = twice as bright). Dark astro panoramas often need +1.5 to +4.
Brightness (sel.)	Brightness factor of the **selected** images.
show unlinked images	Also shows images that could not be linked, in a row below the panorama, for placing by hand.
Auto exposure	Sets **Exposure** from the current preview: typical brightness to middle grey, without clipping more than the brightest 0.5 % (stars, lamps).
Even out	Computes per-image brightness factors that make the overlaps match.
Reset moves	Undoes all manual moves.
Auto crop	Cuts the panorama to the largest rectangle that is completely covered by images, so the black, ragged edges disappear. The preview then shows the cropped result, and **Save full resolution…** saves it. The status line says how much of the panorama is kept. Straighten the horizon (Pitch, Roll) first; a bent panorama leaves only a thin rectangle.
Uncrop	Removes the crop. The crop is also removed automatically when you change anything that moves the images (projection, focal, yaw, pitch, roll, moves, matching).
Nudge ← ↑ ↓ →	Moves the current image by one preview pixel (see below).

In the **Panorama** view, every image's outline is drawn and numbered:

- **orange**: the current image
- **light blue**: other selected images
- **cyan**: the reference image
- **white**: the other images
- **dashed yellow lines**: the links used to place the images

Switch these off with **overlays** in the toolbar to see the panorama itself.

Click inside an outline to select that image (also works with overlays off).

Moving images by hand: hold **Ctrl** and drag an image, or use the arrow keys or the **Nudge** buttons. The image moves together with the images attached to it further from the reference (along the yellow links). The reference image does not move; use Pitch and Roll to move everything.

5.6 Step 5: Stretch

Astronomical images (and dark RAW renderings) are usually **linear**: the interesting detail sits in the darkest few percent of the brightness range and the image looks almost black. The histogram stretch makes it visible.

Control	Meaning
Histogram	Brightness distribution of the panorama preview (in the Panorama view) or of the current image (in the other views), on a logarithmic scale. The **blue line** marks the black point, the **white line** the white point, and the **orange curve** shows how input brightness (left to right) maps to output brightness (bottom to top).
Black point	Everything at or below this brightness becomes black. Set it just below the sky background (the left edge of the histogram's main peak).
Midtones	Brightens (smaller values) or darkens (larger values) the middle tones without clipping. 0.5 is neutral. Deep-sky images typically need 0.005–0.05.
White point	Everything at or above this brightness becomes white.
Auto stretch	Sets all three from the current histogram: black point just below the sky background, midtones so the background ends up at about 25 % grey (the same idea as PixInsight's automatic screen stretch).
Reset stretch	Back to no stretch (0 / 0.5 / 1).

- The stretch changes only how images are **shown** and how the panorama is saved as TIFF, PNG or JPEG. Matching works on the original data either way.
- **FITS files** get an automatic stretch for viewing when they are loaded, based on all loaded FITS images together.
- Changing the stretch is instant: nothing has to be recomputed.
- **Exposure** is applied before the stretch.

5.7 Undo, redo and projects

Undo / redo: Undo and **Redo** in the toolbar, or **Ctrl+Z** and **Ctrl+Y** (also **Ctrl+Shift+Z**). The status line says what was undone, e.g. "Undone: Pitch (°) 0 → 10".

- Undoable: every slider, menu and switch of the settings; adding, removing and reordering images; matching results (Match, Re-match, Discard); the reference image; manual moves; brightness; auto crop.
- A slider drag counts as **one** step, however long you drag. Changes to two different controls are always two steps.
- Removed images are kept in memory for undo, so they come back instantly, together with their matching results.
- The last 100 steps are kept. Not undoable: view-only things (zoom, which view is shown, overlays), RAW via and half size, and saving files.

Projects: Save project… (top of the left column) writes a project file with the extension **`.panoproj`**. **Open project…** loads one again. You can also type the path of a `.panoproj` file into the path box and press Enter, or start the program with it: `julia bin/panostitch.jl my_pano.panoproj`.

A project stores:

- the images (full path, and the path relative to the project file)

- all settings: sliders, menus, switches, including the stretch
- the matching results, so nothing has to be matched again
- manual moves, brightness factors, the reference image and the crop
- RAW via and half size, so the images are loaded the same way again

It does **not** contain the images themselves; they are loaded from their files. If you move the photos together with the project file (e.g. the whole folder), they are still found through the relative path. Missing files are reported and left out.

The file is readable text (TOML format). Its size is mostly the stored match points: about 50 kB per image.

---

6. Navigating the view

Action	Mouse	Keyboard	Button
Pan	drag with **left** button	arrow keys (Image and Pair views)	
Zoom in	scroll up	`+`	**Zoom +**
Zoom out	scroll down	`-`	**Zoom -**
Reset zoom		`0` or `Home`	**Fit**
Select image (Panorama view)	click inside its outline		
Show / hide outlines, numbers, links			**overlays** switch
Move image (Panorama view)	**Ctrl + drag**	arrow keys (`Shift` = 10 steps)	← ↑ ↓ →
Undo		`Ctrl+Z`	**Undo**
Redo		`Ctrl+Y` or `Ctrl+Shift+Z`	**Redo**

The **Image + keypoints**, **Pair matches** and **Panorama** buttons switch between the three views.

Sharp zoom: the preview is a reduced image. When you zoom into the panorama and pause for a moment, the visible area is re-rendered at screen resolution from the original images, so you can check fine detail and joins.

---

7. Projections

A panorama covers more than a flat photo can show, so the program must project the view onto a flat image. Each projection distorts something:

Projection	Looks like	Best for	Limits
rectilinear	an ordinary photo: straight lines stay straight	narrow panoramas (up to ~100° wide), architecture, telescope mosaics	edges get extremely stretched as the view widens
cylindrical	horizontal straight lines bend, verticals stay vertical	most horizontal panoramas	not for tall views (top and bottom stretch)
spherical (equirectangular)	like cylindrical, with less vertical stretching	very wide or 360° panoramas, panorama viewers	straight lines curve
mercator	between cylindrical and spherical	wide panoramas with some height	stretches near top and bottom
stereographic	fisheye-like, keeps shapes round	very wide fields of view, creative shots	strong curvature
transverse_cylindrical	cylindrical turned on its side: vertical lines bend, horizontal lines stay straight	**vertical panoramas** (horizon to zenith), the Milky Way arch standing up	not for wide horizontal sweeps (they wrap over the top and bottom edges)
transverse_mercator	like transverse cylindrical, less stretched sideways	vertical panoramas with some width	as above
fisheye (equidistant)	round image, distance from the centre proportional to the angle	**all-sky views**: tilt with Pitch so the zenith is in the centre	edges compressed
fisheye_equisolid	round image that keeps areas in proportion	all-sky views, the way most fisheye lenses look	edges compressed more
little_planet	the ground in the centre, the sky around it as a ring	360° panoramas with ground, creative	needs a panorama that reaches far down
tunnel	the sky in the centre, the horizon around it	360° night skies, star trails, trees from below	needs a panorama that reaches far up
orthographic	a globe seen from outside	creative; shows one half of the sphere	the edges are very compressed
hammer (Hammer–Aitoff)	an oval map of the whole sphere with correct relative areas	full-sphere panoramas shown as one image, all-sky star maps	shapes distorted near the edges
mollweide	an oval equal-area map, flatter at the poles	as Hammer; the classic all-sky map of astronomy	shapes distorted near the edges

If the horizon looks like a smile or a frown, adjust **Pitch**. If it is tilted, adjust **Roll**. **Yaw** turns the view sideways. For the fisheye, little planet and tunnel views, Pitch decides what is in the centre.

---

8. RAW files

Supported: **Canon CR2 and CR3, Nikon NEF and NRW, Sony ARW and SRF, DNG, Fuji RAF, Olympus ORF, Panasonic RW2, Pentax PEF, Samsung SRW**,

and others. Exact camera support depends on the converter version; the LibRaw 0.22 that comes with the program knows about 1250 cameras.

RAW via chooses the converter:

Option	Converter	Character
auto	first available, in the order below; RawTherapee first if the photo has a `.pp3` file	recommended
libraw	`dcraw_emu` (comes with the program)	fastest; neutral, rather dark rendering with no automatic brightening, so all frames keep the same exposure
rawtherapee	`rawtherapee-cli`	**uses your RawTherapee edits** saved in `photo.NEF.pp3`; otherwise RawTherapee's default look
darktable	`darktable-cli`	darktable's default rendering (including lens correction where available); slowest
dcraw	`dcraw`	fallback; cannot read CR3

Only libraw is always available; the other three appear when the program is installed on your computer.

Converted images are 16-bit and are written to a temporary folder that is deleted afterwards. Nothing is written next to your photos.

Tip: for consistent colours across the panorama, use the same edits (the same `.pp3` profile) for all frames, or use **libraw** and correct the colours afterwards.

---

9. FITS files (astronomy)

Files ending in **`.fits`, `.fit`** **or** **`.fts`** are read directly, with no extra software. Supported:

Content	Examples	How it is read
8-, 16-, 32- and 64-bit integer, 32- and 64-bit float	camera captures, stacking results	scaled to 0…1 (16-bit unsigned: 0…65535)
Colour (3 planes)	stacked results from Siril, PixInsight, DSS	as RGB
Mono	mono cameras, single filters	as grey
Colour camera raw (Bayer)	frames from ZWO, ToupTek, QHY… with a `BAYERPAT` header (RGGB, BGGR, GRBG, GBRG)	debayered; with **half size** one colour pixel per 2×2 cell (fast, clean), otherwise interpolated at full size
Row order	`ROWORDER` = `TOP-DOWN` or `BOTTOM-UP` (the FITS default)	the image is shown the right way up

Not supported: **tile-compressed files (`.fz`)**. Decompress them first, e.g. with `funpack`. Extra parts of a file (tables, ICC profiles) are ignored; the first image is used.

Notes for deep-sky mosaics:

- Use the **deep-sky mosaic** preset. Telescope tiles only shift and rotate (field rotation), which the similarity model describes exactly.

- **Stacked, calibrated tiles** stitch best. Single short frames have few visible stars and a lot of noise.
- Raw colour-camera frames are not white-balanced, so they look green; the stretch does not change colour balance.
- Save as **FITS** to continue processing (background extraction, colour calibration, final stretch) in Siril or PixInsight. The FITS output keeps the linear values.

---

10. Saving

Click **Save full resolution…** and choose a file name. The file type follows the extension:

Extension	Result
`.tif` / `.tiff`	16 bits per channel, best for further editing; saved **as shown** (with exposure and stretch)
`.png`	16 bits per channel; as shown
`.jpg`	8 bits per channel, smaller file; as shown
`.fits` / `.fit` / `.fts`	32-bit float, three colour planes; **linear** (exposure and brightness factors applied, but **no stretch**, no clipping), for astronomy software

When all loaded images are FITS, the suggested file name ends in `.fits`.

The panorama is rendered from the loaded images at their full size: half the camera resolution if **half size** was on when you loaded them.

Panoramas wider or taller than 40,000 px are refused. This almost always means that one pair is matched wrongly or that the projection is unsuitable; try cylindrical or spherical.

---

11. Troubleshooting

Problem	What to try
No window appears	Wait: the first start after a code change takes longer. Watch the terminal for errors. Make sure you started `bin/panostitch.jl`.
"Busy – wait…"	A step is still running; wait for the status line to change.
An image is skipped while loading	The status line names the file and the reason. For RAW, try another converter in **RAW via**. For `.fz` FITS, decompress the file first.
Panorama is mostly black	Photos: click **Auto exposure** or raise **Exposure (EV)** (night shots often need +1.5 to +4), or edit the photos in RawTherapee (their `.pp3` files are then used). FITS and other linear data: click **Auto stretch**.
FITS images look black or white after loading	The automatic stretch on loading is based on all FITS images; one very over- or underexposed frame can throw it off. Remove such frames, then click **Auto stretch** (or **Reset stretch** and set it by hand).
FITS images look green	Raw colour-camera frames are not white-balanced. Stack and colour-calibrate them first, or correct the colour of the result in astronomy software.
Few yellow keypoints	Lower the **Corner threshold**; raise **Max keypoints**; raise **Detection size**.
Keypoints mostly on grass, sky or noise	Raise **Denoise** to 2–3.
Images marked UNLINKED	Look at them: do they really overlap another image? Raise **Ratio test** (0.85–0.9) and **Max distance** (0.4), lower **Min. inliers**, raise **Denoise**, then **Match** again. If it still fails, switch on **show unlinked images** and place them with **Ctrl+drag**.
Clouds, water, or other moving things	They change between shots, so they cannot be matched reliably (frames showing only clouds usually stay unlinked). Shoot such parts quickly one after another, or place them by hand.
A wrong pair is used (lines in all directions, images in the wrong place)	Select it in the **Pair** menu and click **Discard pair**. With **refine** on, most such pairs are rejected automatically.
Ghosting (doubled objects)	Keep **refine** on and use **Blend → smart** (default). Remaining problems come from things that changed between shots (e.g. a torch switched on in only one photo), or from **parallax**: close objects shift against the background when the camera is not rotated around its lens (the "nodal point").
Visible brightness steps	**Even out**, then fine-tune per image with **Brightness (sel.)**.
Horizon curved	Adjust **Pitch** (and **Roll** if tilted).
Strongly stretched top or bottom	Use the **spherical** projection; the status line suggests it when the panorama reaches far up or down.
Fly[illegible] images	[illegible] about 300 MP from 24 MP images. With many images, all pairs matching takes longer; grid is faster when you know the layout.


12. Tips for good panoramas

- **Overlap** neighbouring shots by 30–50 %, also between rows. For telescope mosaics, 15–25 % is usually enough.
- **Rotate the camera** around the lens, not around yourself. Use a tripod if you can, ideally with a panoramic head.
- **Lock exposure, white balance and focus** (manual mode), so all frames match.
- Avoid moving objects in the overlap areas, or shoot them in one frame only.
- **Keep the camera level.** A tilted camera bends the horizon (fix with Pitch and Roll).
- For long series, check the result with **half size** on first.
- Do not save the result into the folder of the source images if you load images by folder. Files named `panorama…` are skipped, but other names are not.

---

13. Star stacking

The second tab, **Star stacking (landscape / trails)**, combines many exposures of the same scene into one image: a low-noise sky with sharp stars, or star trails. It is made for landscape astrophotography: the camera stands on a tripod, the sky moves between the frames, the foreground does not.



Click an entry in the input list or the settings list: its options and an explanation appear below the lists.

13.1 Quick start

1. Highlight **Star images**, click **Add…** and choose the star shots (or type a file or folder path into the path box and press Enter).
2. Highlight **Sky region**, choose **Boundary line** and drag a line along the horizon in the base image view. Stars are searched for only above it.
3. Click **Quick preview**: a small, fast result from up to 10 frames, to check the settings. Nothing is saved.
4. Highlight **Output** and choose where to save (default: `stacked.tif` next to the first star image), then click **Start**.
5. Adjust the post-processing on the right; the result updates at once. Click **Save result…** to save it again with the new settings.

13.2 Input files

Entry	What to shoot
Star images	The shots of the sky: same focal length, aperture and exposure. RAW is best; TIFF, FITS or XISF only if the data is still linear (not edited). **Unify exposure** evens out frames taken under different conditions.
Base image	The frame the others are aligned to. Empty = the middle star image. Highlight a star image and click **Use as base** to choose another.
Noise images	Dark frames: lens cap on, same ISO and exposure time, taken just before or after the star images. Removes thermal noise and hot pixels.
Bias images	Shortest exposure, lens cap on, same ISO.
Vignetting images	Flat frames: an evenly lit white surface, same focal length and aperture. Corrects darker corners and dust shadows.
Flat-dark images	Darks for the flats: same ISO and exposure time as the vignetting images.
Output	`.tif` (16-bit), `.jpg` (8-bit), or `.fits` / `.xisf` (32-bit float, linear, for further processing in Siril, PixInsight etc.).

All calibration frames are optional. Even a few noise images help a lot at high ISO.

13.3 Settings

Setting	What it does
Composition	**Align stars**: the frames are aligned on the stars and combined. **Accumulation** averages them; **Select best pixels** (default) drops outliers (planes, satellites); **Freeze ground** aligns only the sky, so sky and foreground both stay sharp (needs a sky region); **Align only** just writes the aligned frames. **Star trails**: no alignment, the sky keeps the brightest value of every pixel; **Motion effect** fades the start of the trails.
Sky region	Where the sky is. **Boundary line**: drag a line along the horizon. **Gradient**: the line plus a soft transition. **Irregular mask**: paint the sky with the left mouse button, erase with the right one, mouse wheel = brush size. Paint roughly, but don't touch the foreground.
Sigma clipping	How strictly outliers are removed (low / high × σ). 2–3 is usual; lower removes more but leaves more noise. Needs at least 4 frames, works best with 10+.
Frame rejection	Leaves out frames clearly worse than the typical one: clouds or dew (dimmer stars), few stars, blurred or elongated stars (focus, wind, a bumped tripod).
RAW conversion	White balance (camera, image average, daylight), demosaicing (AHD by default; DHT or AAHD often give less colour noise at high ISO) and **half size** (4× fewer pixels, much faster).
Reduce dynamic noises	Finds and removes hot pixels without noise images.
Reduce distor. effects	Corrects lens distortion that leaves short trails in the corners of long sequences: **Lens**, **Complex** (ultra wide-angle lenses, refraction near the horizon) or **Auto**.
Merge 4 pixels	Adds up 2×2 pixels: brighter and less noisy, half the width and height.
Time-lapse	Stacks every N consecutive frames into one, giving a numbered sequence of low-noise frames in a folder next to the output.

13.4 The views

- **Base image**: the frame the others are aligned to; the sky region is drawn here. Click a file in the input list to see it.
- **Result**: the stack after post-processing. Drag to pan, mouse wheel to zoom, **Fit** to see all of it.
- **Frame report**: one line per star image: stars found, star size (FWHM), elongation, sky level, light (brightness of the stars compared with the base image), alignment error and whether the frame was used. **Click a frame** to exclude it (or include it again), then click **Start** again.

13.5 Post-processing

Applied to the stacked result at once; **Start** saves with these settings, **Save result…** saves again.

Setting	What it does
Background extraction	Subtracts a smooth model of the sky background (gradients from light pollution or moonlight).
Color calibration	Makes the sky background neutral grey and the average star white.
Reduce colour noise	Smooths only the colours, removing the coloured speckles of high-ISO shots.
Light pollution	**Deep sky**: removes a smooth glow. **Uneven**: follows the glow tile by tile (domes of city light in wide-angle shots). **Strength** sets how much is removed. Correct the vignetting first (vignetting images), or it gets worse.
Enhance star light	Lifts the stars above the sky background without boosting its noise.
Auto brightness	Puts the sky at a pleasant level without clipping the brightest stars.
High dynamic range	Compresses bright stars and lights instead of clipping them.
Tone	**sRGB curve** (as a camera does), **Stretch** (black point, midtones, white point; automatic or by hand) or **Linear** (no curve).
Color space	sRGB or Adobe RGB for TIFF and JPEG output.
Linear (for processing)	Switches everything off and saves a linear 32-bit FITS: what Siril or PixInsight expect.

13.6 Projects

Save project… writes a `.stackproj` file with the file lists, the sky region and every setting. **Open project…** (or `julia bin/panostitch.jl night.stackproj`) brings it back. Files are found by their full path, or relative to the project file if the folder was moved.

13.7 Tips

- Shoot at least 10–20 star images with the same settings, plus 10–20 noise images right after, without moving the camera.
- Set the sky region carefully: trees and buildings that are counted as sky are blurred by the alignment.
- Use **Freeze ground** when the foreground matters, **Select best pixels** when it does not.
- For processing in other programs, save as `.fits` and switch on **Linear (for processing)**.
- From a terminal, `julia bin/panostack.jl` stacks without the window; its options are listed at the top of the file.

14. Use from a script (no window)

```
include("examples/scripted_stitch.jl")
pano = Stitcher.stitch(["a.NEF", "b.NEF", "c.NEF"];
                       projection = :spherical, raw_half = true)
Stitcher.save_panorama("pano.tif", pano)
```

Options of `stitch`, with their defaults:

Option	Default	Meaning
`layout`	`:all`	which pairs to match: `:all`, `:sequential`, `:grid`
`cols`, `snake`	all images, `false`	grid layout
`refine`	`true`	global refinement
`feature_scale`	`0.5`	detection scale
`nkeypoints`	`5000`	
`denoise`	`1.5`	
`ratio`	`0.8`	
`max_distance`	`0.35`	
`model`	`:homography`	`:homography`, `:affine`, `:similarity`, `:translation`
`ransac_thresh`	`5.0`	
`min_inliers`	`20`	
`projection`	`:cylindrical`	any name from Projections as a symbol, e.g. `:fisheye`, `:little_planet`, `:mollweide`
`blend`	`:smart`	`:smart`, `:feather`, `:seam`, `:average`
`sharpness`	`3.0`	feather mode: higher = narrower transitions
`raw_half`	`false`	half size for RAW and colour-camera FITS

FITS mosaic with a stretched TIFF and a linear FITS result:

```
include("examples/scripted_stitch.jl")
tiles = filter(f -> endswith(f, ".fits"), readdir("tiles"; join = true))
mosaic = Stitcher.stitch(tiles; model = :similarity, refine = false,
                         projection = :rectilinear, denoise = 0.75)
Stitcher.save_panorama("mosaic.fits", mosaic)                          # linear
black, mid, white = Stitcher.auto_stretch(mosaic)
Stitcher.save_panorama("mosaic.tif", Stitcher.hist_stretch(mosaic, black, mid, white))
```

Other useful functions: `Stitcher.read_fits(path; half)` and `Stitcher.write_fits(path, image)`.

15. Files

File	Purpose
`bin/panostitch.jl`	Starts the program (the window).
`bin/panostack.jl`	Star stacking from the command line (options at the top of the file).
`examples/scripted_stitch.jl`	Loads the stitcher for use from your own scripts.
`src/stitcher.jl`	Stitching: loading (RAW, FITS), features, matching, projections, rendering, stretch.
`src/stacker.jl`	Star stacking.
`src/PanoStitch.jl`	Package entry point and precompilation (no graphics).
`ext/PanoStitchGUIExt/`	The window (loaded together with GLMakie).
`app/`	The program's package list: PanoStitch plus GLMakie (installed automatically).
`Project.toml`, `Manifest.toml`	Package list of the stitching and stacking code alone (for scripts).
`assets/fonts/`	Fonts used by the window (DejaVu).
`*.panoproj`	Your project files (wherever you save them).
`docs/manual_en.md`	This manual (English).
`docs/manual_cs.md`, `docs/manual_de.md`	The manual in Czech and German.
`docs/manual_*.pdf`, `docs/make_pdf.jl`	The manuals as PDF, and the script that makes them.
`build/build_app.jl`	Builds the standalone program (runs without Julia installed).