





Massachusetts
Institute of
Technology

Structure Discovery in Nonparametric Regression through Compositional Kernel Search

David Duvenaud, James Robert Lloyd, Roger Grosse,
Joshua B. Tenenbaum, Zoubin Ghahramani




Identifying structure is crucial for extrapolation



- Traditionally, a statistician proposes an appropriate model for the type of structures present
- Automatic model selection techniques already exist, typically choosing between a finite or restricted set of models
- Instead, we automate statistical model *construction*


Gaussian processes model structure through kernels

- The kernel specifies which structures are likely under the GP prior, which in turn determines the generalization properties of the model.
- Below we list standard base kernels, and draws from the corresponding GP priors:



Kernels can be Composed

- Constructing appropriate composite kernels has previously been done by experts





... defining an open-ended set of structures

- We consider all algebraic expressions involving a small number of base kernels and the operations '+' and 'x', including e.g.

Bayesian linear regression	LIN
Bayesian polynomial regression	$\text{LIN} \times \text{LIN} \times \dots$
Generalized Fourier decomposition	$\text{PER} + \text{PER} + \dots$
Generalized additive models	$\sum_{d=1}^D \text{SE}_d$
Automatic relevance determination	$\prod_{d=1}^D \text{SE}_d$
Linear trend with local deviations	$\text{LIN} + \text{SE}$
Linearly growing amplitude	$\text{LIN} \times \text{SE}$

... by a greedy search

- We try all base kernels, selecting the one with the highest (approximate) marginal likelihood which balances data fit and model complexity
- The search continues by adding an extra term to the current best kernel, stopping when marginal likelihood no longer improves



Compound Kernels are Interpretable

- Compound kernels decompose functions into additive components

