表 11-3 测量螺线管轴线上磁感应强度分布数据记录表

(IM = 0.800 A, Is = 8.00 mA)

| lm | U1/mv | U2/mv | U3/mv | U4/mv | UH/mv | B/kgs |
|--------|---------|---------|---------|---------|-------|--------|
| | +l_s1+B | +I_s1-B | -l_s1-B | -l_s1+B | | |
| -14.00 | 3.37 | -5.21 | 5.22 | -3.41 | 4.30 | 0.0286 |
| -13.50 | 4.64 | -6.37 | 6.41 | -4.60 | 5.51 | 0.0366 |
| -13.00 | 5.65 | -7.46 | 7.48 | -5.62 | 6.55 | 0.0436 |
| -12.50 | 6.57 | -8.41 | 8.44 | -6.56 | 7.50 | 0.0498 |
| -12.00 | 7.41 | -9.22 | 9.24 | -7.38 | 8.31 | 0.0553 |
| -9.00 | 9.35 | -11.14 | 11.17 | -9.32 | 10.25 | 0.0681 |
| -6.00 | 9.74 | -11.52 | 11.56 | -9.70 | 10.63 | 0.0707 |
| -3.00 | 9.81 | -11.62 | 11.64 | -9.80 | 10.72 | 0.0713 |
| 0.00 | 9.85 | -11.67 | 11.69 | -9.87 | 10.77 | 0.0716 |
| 3.00 | 9.90 | -11.71 | 11.75 | -9.89 | 10.81 | 0.0719 |
| 6.00 | 9.85 | -11.64 | 11.67 | -9.83 | 10.75 | 0.0715 |
| 9.00 | 9.58 | -11.33 | 11.37 | -9.53 | 10.45 | 0.0695 |
| 12.00 | 8.18 | -9.97 | 9.99 | -8.16 | 9.08 | 0.0603 |
| 12.50 | 7.65 | -9.40 | 9.44 | -7.63 | 8.53 | 0.0567 |
| 13.00 | 6.97 | -8.72 | 8.75 | -6.94 | 7.85 | 0.0522 |
| 13.50 | 5.97 | -7.73 | 7.76 | -5.97 | 6.86 | 0.0456 |
| 14.00 | 4.94 | -6.70 | 6.72 | -4.92 | 5.82 | 0.0387 |