

Lunar Refueling Station

Leticia Damian & Josh Lucas & Rowan Ranjbar


¹Dept. of Physics
California State University San Marcos

Goal of Project

- Design a habitat that is suitable for habitation by at least two humans.
- Maintain a stable temperature of $\approx 300K$
- Protect from environmental hazards (Solar flux, cosmic rays...)
- Generate power for air and water recycling and treatment.
- Assume food can be initially supplied from rations sent from Earth

The location of the base must then take in to account proximity to probable water locations as well as areas of illumination for solar power and heat generation as well as line of sight for communication.


Location of Habitat




Access to water, illumination, communication, and mobility. [6]

Why the lunar Poles

The moon resides along the elliptical plane. As a result the poles receive much less light than the lower latitudes. There are craters on the moon then that are permanently shadowed regions or **PSRs**. There are also highlands that remain permanently illuminated (**PIRs**).




Illumination at the Lunar South Pole




The incident angle of sunlight rotates by 360° over a month period. The further from the center of the pole the higher a solar collector would need to be receive maximum illumination. [1]

Solar-Thermal Power Generation




Schematic of a lunar based solar thermal power system [16]

The Stirling generator converts the thermal energy stored in lunar regolith into electrical power.[2][5]



Insulating and Protective Barrier

The moon regolith itself can be used as shielding and insulating material to protect against extreme temperatures and frequent micro-meteorite bombardment (10-30Km/s) as well as solar and cosmic radiation. [7]



Each inhabitant at a minimum will require 3kWe. Photovoltaic arrays have been extensively and reliably used in space and surface explorations. PV systems will require energy storage systems for times of little to no illumination. Nuclear power would provide continuous power but present several safety and political barriers to become feasible[4].

Food, Oxygen, and Water needs

Minimum and expanded mass inputs and outputs of human needs [11,13].

	Minimum (kg/day)	Expanded (kg/day)
Input		
O ₂	0.93	0.93
Food solids	0.70	0.70
Water in food	1.29	1.29
Food preparation & drinking water	2.50	2.50
Hygiene water	0.40	25.40
Total input	5.82	30.82

Life Support Systems (LSS) need efficient management of Oxygen, food, water, and safety.[3]

-  David Koebel, Michele Bonerba, Daniel Behrenwaldt, Matthias Wieser, Carsten Borowy, Analysis of landing site attributes for future missions targeting the rim of the lunar South Pole Aitken basin, Acta Astronautica, Volume 80, 2012, Pages 197-215
-  Xiaochen Lu, Wei Yao, Chao Wang, Rong Ma, Exergy analysis of a lunar based solar thermal power system with finite-time thermodynamics, Energy Procedia, Volume 158, 2019, Pages 792-796
-  Belz et al., 2011. Hybrid life support systems with integrated fuel cells and photobioreactors for a lunar base. Aerospace Science and Technology, pp.Aerospace Science and Technology.
-  Hickman, J.M., Curtis, H.B. & Landis, G., 1990. Design considerations for lunar base photovoltaic power systems, Washington, DC] : [Springfield, Va.]: National Aeronautics and Space Administration



Blai Climent, Oscar Torroba, Ricard Gonzlez-Cinca, Narayanan Ramachandran, Michael D. Griffin, Heat storage and electricity generation in the Moon during the lunar night, Acta Astronautica, Volume 93, 2014, Pages 352-358



Jennifer L. Heldmann, et al. Site selection and traverse planning to support a lunar polar rover mission: A case study at Haworth Crater, Acta Astronautica, Volume 127, 2016, Pages 308-320,



Toth, A.R. & Bagi, K., 2011. Analysis of a Lunar Base Structure Using the Discrete-Element Method. Journal Of Aerospace Engineering, 24(3), pp.397401.