

# Getting Started with Python Programming

QGIS Tutorials and Tips

**Ujaval Gandhi** [ujaval@spatialthoughts.com](mailto:ujaval@spatialthoughts.com)

# Getting Started With Python Programming

QGIS has a powerful programming interface that allows you to extend the core functionality of the software as well as write scripts to automate your tasks. QGIS has support for the popular Python scripting language. Even if you are a beginner, learning a little bit of Python and QGIS programming interface will allow you to be much more productive in your work. This tutorial assumes no prior programming knowledge and is intended to give you an introduction to python scripting in QGIS (PyQGIS).

## Overview of the task

We will load a vector point layer representing all major airports and use python scripting to create a text file with the airport name, airport code, latitude and longitude for each of the airport in the layer.

## Get the data

We will use the [Airports](#) dataset from Natural Earth.

Download the [Airports shapefile](#).

Data Source [NATURALEARTH]

## Procedure

1. In QGIS, go to Layers › Add Vector Layer. Browse to the downloaded *ne\_10m\_airports.zip* file and click Open. Select the *ne\_10m\_airports.shp* layer and click OK.



2. You will see the *ne\_10m\_airports* layer loaded in QGIS.



3. Select the Identify tool and click on any of the points to examine the available attributes. You will see that the name of the airport and it's 3 digit code are contained in the attributes *name* and *iata\_code* respectively.



4. QGIS provides a built-in console where you can type python commands and get the result. This console is a great way to learn scripting and also for quick data processing. Open the Python Console by going to Plugins > Python Console.



5. You will see a new panel open at the bottom of QGIS canvas. You will see a prompt like `>>>` at the bottom where you type commands. For interactive with the QGIS environment, we must use the *iface* variable. To access the currently active layer in QGIS, you can type the following and press Enter. This command fetches the reference to the currently loaded layer and stores it in the *layer* variable

```
layer = iface.activeLayer()
```



6. There is a handy function called `dir()` in python that shows you all available methods for any object. This is useful when you are not sure of what functions are available for the object. Run the following command to see what operations we can do on the `layer` variable

```
dir(layer)
```



7. You will see a long list of available functions. For now, we will use a function called `getFeatures()` which will get you all features of a layer. In our case, each feature will be a point representing an airport. You can type the following command to iterate through each of the features in the current layer. Make sure to add 2 spaces before typing the second line

```

for f in layer.getFeatures():
    print f

```





8. As you will see in the output, each line contains a reference to a feature within the layer. The reference to the feature is stored in the `f` variable. We can use the `f` variable to access the attributes of each feature. Type the following to print the `name` and `iata_code` for each airport feature.

```

for f in layer.getFeatures():
    print f['name'], f['iata_code']

```



9. So now you know how to programatically access the attribute of each feature in a layer. Now, let's see how we can access the coordinates of the feature. The coordinates of a vector feature can be accessed by calling the **geometry()** function. This function returns a geometry object that we can store in the variable **geom**. You can run **asPoint()** function on the geometry object to get the x and y coordinates of the point. If your feature is a line or a polygon, you can use **asPolyline()** or **asPolygon()** functions. Type the following code at the prompt and press Enter to see the x and y coordinates of each feature.

```

for f in layer.getFeatures():
    geom = f.geometry()
    print geom.asPoint()

```



10. What if we wanted to get only the **x** coordinate of the feature? You can call the **x()** function on the point object and get its x coordinate

```
for f in layer.getFeatures():
    geom = f.geometry()
    print geom.asPoint().x()
```



11. Now we have all the pieces that we can stitch together to generate our desired output. Type the following code to print the name, iata\_code, latitude and longitude of each of the airport features. The %s and %f notations are ways to format a string and number variables

```

for f in layer.getFeatures():
    geom = f.geometry()
    print '%s, %s, %f, %f' % (f['name'], f['iata_code'], geom.asPoint().y(), geom.asPoint().x())

```



12. You can see the output printed on the console. A more useful way to store the output would be in a file. You can type the following code to create a file and write the output there. Replace the file path with a path on your own system. Note that we add `\n` at the end of our line formatting. This is to add a newline after we add the data for each feature. You should also note the `unicode_line = line.encode('utf-8')` line. Since our layer contains some features with unicode characters, we can't simply write it to a text file. We encode the text using the UTF-8 encoding and then write to the text file.

```

output_file = open('c:/Users/Ujaval/Desktop/airports.txt', 'w')
for f in layer.getFeatures():
    geom = f.geometry()
    line = '%s, %s, %f, %f\n' % (f['name'], f['iata_code'], geom.asPoint().y(),
    unicode_line = line.encode('utf-8')
    output_file.write(unicode_line)
output_file.close()
  
```



13. You can go to the output file location you specified and open the text file. You will see the data from the airports shapefile that we extracted using python scripting.

airports.txt - Notepad

File Edit Format View Help

Sahnewal, LUH, 30.850360, 75.957072  
Solapur, SSE, 17.625415, 75.933060  
Birsamunda, IXR, 23.317725, 85.323597  
Ahwaz, AWZ, 31.343159, 48.747107  
Gwalior, GWL, 26.285488, 78.217219  
Hodeidah Int'l, HOD, 14.755253, 42.971096  
Devi Ahilyabai Holkar Int'l, IDR, 22.727749, 75.809292  
Gandhinagar, ISK, 19.966021, 73.810567  
Chandigarh Int'l, IXC, 30.670725, 76.801726  
Aurangabad, IXU, 19.867297, 75.395843  
Faisalabad Int'l, LYP, 31.362744, 72.987819  
Omsk Tsentralny, OMS, 54.957648, 73.316360  
Novosibirsk Tolmachev, OVB, 55.009585, 82.667152  
Zaporozhye Int'l, OZH, 47.873264, 35.301873  
Simpang Tiga, PKU, 0.464601, 101.446569  
Rota Int'l, ROP, 14.171771, 145.243980  
Surgut, SGC, 61.340167, 73.408496  
Tiruchirappalli, TRZ, 10.760357, 78.708958  
Turbat Int'l, TUK, 25.988795, 63.027933  
Quetta Int'l, UET, 30.249043, 66.948731  
Zahedan Int'l, ZAH, 29.475294, 60.900709  
Abdul Rachman Saleh, MLG, -7.929980, 112.711419  
Barnaul, BAX, 53.363385, 83.550453  
Adampur, NULL, 31.432942, 75.758483  
Bareilly, NULL, 28.421809, 79.452003  
Dhamial, NULL, 33.561415, 73.032050  
Cheongju Int'l, CJJ, 36.722023, 127.495916  
Gwangju, KWJ, 35.140005, 126.810839  
Daegu Int'l, TAE, 35.899928, 128.637538  
Ulsan, USN, 35.592896, 129.355731  
Radin Inten II, TKG, -5.242567, 105.176060  
Allahabad, IXD, 25.443522, 81.731727  
Chelyabinsk, CEK, 55.297792, 61.512259  
Tainan, TNN, 22.950668, 120.209733  
Taichung, RMQ, 24.266656, 120.630704  
Rotterdam The Hague, RTM, 51.949130, 4.433844  
Voronezh-Chertovitskoye, VOZ, 51.812617, 39.225450  
Liverpool John Lennon, LPL, 53.336375, -2.858621  
Vishakapatnam, VTZ, 17.727958, 83.223522  
Sultan Hasanuddin Int'l, UPG, -5.058937, 119.545691  
Vava'u Int'l, VAV, -18.586006, -173.968094  
Newcastle Int'l, NCL, 55.037085, -1.710346  
Goloson Int'l, LCE, 15.745160, -86.851469