Performing Table Joins

QGIS Tutorials and Tips



Author

Ujaval Gandhi

http://google.com/+UjavalGandhi

Translations by

Sylvain Dorey Allan Stockman

Les Jointures de tables (JOIN)

Tous les jeux de données utiles n'ont pas la forme d'un shapefile ou autre format spatial. Souvent il s'agit d'un simple tableau ou une spreadsheet et il faut alors la relier avec vos données géographiques pour effectuer des analyses. Cette opération s'appelle *Table Join*, ou *Jointure de Table*, et ce tutoriel explique comment les réaliser dans QGIS.

Description de la tache

Nous allons utiliser un fichier shapefile comprenant les zones de recensement de Californie et les données de population de l'US Census Bureau pour créer une carte de la population de la Californie.

Autres compétences abordées

- Créer un fichier `.csvt`pour indiquer le type de données des colonnes d'un fichier CSV.
- Chargement de fichiers CSV ne contentant pas de données Geometry dans QGIS.

Obtenir les données

Le bureau du recensement américain, US Census Bureau possède différentes données spatiales provenant de la base de données MAF/TIGER. Vous pouvez y télécharger les données des zones de recensement pour la Californie.

Americal FactFinder est un entrepôt des données de recensement pour les Etats-Unis. Vous pouvez utiliser la *Advanced Research* chercher *Topic - Total Population`et `Geographies - All Census Tracts in California`pour créer un fichier CSV et le télécharger. Ce tutoriel utilise les données Total Population 2010 Census Summary File 1*.

Source [TIGER] [USCENSUS]

Procedure

1. Nous allons d'abord charger les données des zones de recensement. Aller à *Layer* ■ *Add Vector Layer*.



2. Parcourir jusqu'au fichier zip téléchargé *tl_2013_06_tract.zip* et le sélectionner. QGIS peut directement ouvrir des fichiers zip, il n'est pas nécessaire de les décompresser.



3. Sélectionnez la couche *tl_2013_06_tract.shp* et cliquez sur *OK*.



4. Vous allez voir les zones de recensement chargées dans QGIS.



5. Clique droit sur la couche et sélectionnez *Open Attribute Table*.



6. Examine the attributes of the tracts shapefile. To join a table with this shapefile, we need a unique and common attribute for each feature. In this case, the **GEOID** field is a unique identifier for each tract and can be used to *link* this shapefile with any other table containing the same ID.



	STATEFP	COUNTYFP	TRACTCE	GEOID	NAME	NAMELSAD	MTFCC
0	06	001	442700	06001442700	4427	Census Tract 44...	G5020
1	06	001	442800	06001442800	4428	Census Tract 44...	G5020
2	06	037	204920	06037204920	2049.20	Census Tract 20...	G5020
3	06	037	205110	06037205110	2051.10	Census Tract 20...	G5020
4	06	037	205120	06037205120	2051.20	Census Tract 20...	G5020
5	06	037	206010	06037206010	2060.10	Census Tract 20...	G5020
6	06	037	206020	06037206020	2060.20	Census Tract 20...	G5020
7	06	037	206050	06037206050	2060.50	Census Tract 20...	G5020
8	06	037	207400	06037207400	2074	Census Tract 20...	G5020
9	06	001	442900	06001442900	4429	Census Tract 44...	G5020
10	06	037	192410	06037192410	1924.10	Census Tract 19...	G5020
11	06	037	192510	06037192510	1925.10	Census Tract 19...	G5020
12	06	037	192520	06037192520	1925.20	Census Tract 19...	G5020
13	06	037	192610	06037192610	1926.10	Census Tract 19...	G5020
14	06	037	192700	06037192700	1927	Census Tract 19...	G5020
15	06	037	194500	06037194500	1945	Census Tract 19...	G5020
16	06	037	195100	06037195100	1951	Census Tract 19...	G5020
17	06	037	195300	06037195300	1953	Census Tract 19...	G5020
18	06	001	443001	06001443001	4430.01	Census Tract 44...	G5020
19	06	001	443002	06001443002	4430.02	Census Tract 44...	G5020
20	06	001	443102	06001443102	4431.02	Census Tract 44...	G5020
21	06	001	443301	06001443301	4433.01	Census Tract 44	G5020

7. Ouvre le fichier CSV *ca_tracts_pop.csv* dans un éditeur de texte. Vous vous rendrez compte que chaque ligne du fichier contient des informations à propos d'une parcelle accompagnées de l'unique identifiant que nous avons vu dans l'étape précédente. Notez que ce champ est appelé **GEO.id2** dans le CSV. Vous noterez aussi que la colonne **D001** indique la valeur de la population pour chaque parcelle de recensée .



8. We could import this csv file without any further action and it would be imported. But, the default type of each column would be a *String* (text). That is ok except for the *D001* field which contains numbers for the population. Having those imported as text would not allow us to run any mathematical operations on this column. To tell QGIS to import the field as a number, we need to create a *sidecar* file with a *.csvt* extension. This file will have only 1 row specifying data types for each column. Save this file as *ca_tracts_pop.csvt* in the same directory as the original *.csv* file. You can also **download the csvt file from here.**



9. Now we are ready to import the CSV file to QGIS. Go to *Layer* ■ *Add Delimited Text Layer*.



10. Browse to the folder containing the CSV file and select it. Make sure you have selected *File format* as *CSV (comma separated values)*. Since we are importing this as a table, we must specify that our file contains no geometry. Select the *No geometry (attribute only table)* option. Click *OK*.



11. The CSV will now be imported as a table to QGIS.



12. Select the *tl_2013_06_tract* layer. Right-click on it and select *Properties*.



13. In the *Layer Properties* dialog, select the *Joins* tab. Click on the + button at the bottom to create a new table join.



14. In the *Add vector join* dialog, select *ca_tracts_pop* as the *Join layer*. Next we have to select the field with unique ids in both the shapefile and the CSV. Select *GEO.id2* and *GEOID* as the *Join field* and *Target field* respectively. Click *OK*.



15. Close the *Layer Properties* dialog and return to the main QGIS window. At this point, the fields from the CSV file are joined with the shapefile. Right-click on the *tl_2013_06_tract* layer and select *Open Attribute Table*.



16. You can now see a new set of fields, including *ca_tracts_pop_D001* field added to each feature. Now you have access to the population value of each tract from the CSV file. Close the attribute table and return to the main QGIS window.



17. Right-click the *tl_2013_06_tract* layer and select *Properties*.



18. Select the *Style* tab. Select the *Graduated* from the drop-down menu. As we are looking to create a population map, we want to assign different color to each census tract feature based on the population count. Select *ca_tracts_pop_D001* as the *Column*. Select a color ramp of your liking from the *Color ramp* drop-down. In the *Mode*, select *Quantile (Equal Count)*. Next click *Classify*. You will see a different color assigned to certain population ranges. Click *OK*.



19. You will now see a nice visualization of the census tracts as styled using population values. Use the *Zoom in* tool to select a smaller area from the layer.



20. You have a detailed and accurate population map of California. You can use the same technique to create maps based on variety of census data.


QGIS 2.0.1-Dufour
Project Edit View Layer Settings Plugins Vector Raster Database MMQGIS Processing Help
Layers
ca_tracts_pop
tl_2013_06_tract [8057]
0.0000 - 3157.2000 [1598]
3157.2000 - 4019.0000 [1599]
4019.0000 - 4865.8000 [1596]
4865.8000 - 5996.4000 [1598]
5996.4000 - 37452.0000 [1598]
Coordinate:
-122.527,37.601
Scale
1:287990
Render
EPSG:4269