

Työskentely attribuuteilla

QGIS Tutorials and Tips



Author

Ujaval Gandhi

<http://google.com/+UjavalGandhi>

Translations by

Kari Salovaara

Työskentely attribuuteilla

Paikkatiedon data on kaksiosainen – ominaisuudet ja attribuutit. Attribuutit ovat strukturoitua dataa ominaisuuksista. Tässä oppaassa tuodaan esille tavat katsoa attribuutteja ja tehdä peruskyselyjä niistä käyttäen QGIS ohjelmaa.

Katsaus tehtävään

Tässä oppaassa käytettävä tietojoukko sisältää informaatiota maailman aasutuista paikoista. Tehtävänä on kyselyllä löytää kaikki maailman suuret kaupungin joiden asukasluku on suurempi kuin 1,000,000.

Other skills you will learn

- Select features from a layer using expressions.
- Deselect features from a layer using the Attributes toolbar.
- Using Query Builder to show a subset of features from a layer.

Hanki tiedot

Natural Earth has a nice [Populated Places](#) dataset. Download the [simple \(less columns\) dataset](#)

For convenience, you may directly download a copy of datasets from the link below:

[ne_10m_populated_places_simple.zip](#)

Tietojen lähde [NATURALEARTH]

Menettely

1. Once you have downloaded the data, open QGIS. Go to Layer › Add Layer › Add Vector Layer.



2. Klikkaa Selaa ja siirry hakemistoon jonne latastit tiedot.



3. Paikallista ladattu zip tiedosto ***ne_10m_populated_places_simple.zip***. Pakkauksen purkaminen on tarpeetonta, koska QGIS pystyy lukemaan zip tiedostoja suoraan. Valitse tiedosto ja klikkaa Avaa.



4. Valitut tasot ladataan nyt QGIS karttapohjalle ja näet paljon pisteitä jotka edustavat maailman asuttuja paikkoja.



5. Right-click the layer and select Open Attribute Table.



6. Tutki eri attribuutteja ja niiden arvoja.

Attribute table - ne_10m_populated_places_simple :: Features total: 7322, filtered: 7322, selected: 0

| | scalerank | natscale | labelrank | featurecla | name | namepar | namealt |
|----|-----------|----------|-----------|-----------------|----------------------|---------|---------|
| 0 | 10 | 1 | 8 | Admin-1 capital | Colonia del Sacra... | NULL | NULL |
| 1 | 10 | 1 | 8 | Admin-1 capital | Trinidad | NULL | NULL |
| 2 | 10 | 1 | 8 | Admin-1 capital | Fray Bentos | NULL | NULL |
| 3 | 10 | 1 | 8 | Admin-1 capital | Canelones | NULL | NULL |
| 4 | 10 | 1 | 8 | Admin-1 capital | Florida | NULL | NULL |
| 5 | 10 | 1 | 8 | Admin-1 capital | Bassar | NULL | NULL |
| 6 | 10 | 1 | 8 | Admin-1 capital | Sotouboua | NULL | NULL |
| 7 | 10 | 1 | 7 | Admin-1 capital | Medenine | NULL | NULL |
| 8 | 10 | 1 | 7 | Admin-1 capital | Kebili | NULL | NULL |
| 9 | 10 | 1 | 7 | Admin-1 capital | Tataouine | NULL | NULL |
| 10 | 10 | 1 | 7 | Admin-1 capital | L'Ariana | NULL | NULL |
| 11 | 10 | 1 | 7 | Admin-1 capital | Jendouba | NULL | NULL |
| 12 | 10 | 1 | 7 | Admin-1 capital | Kasserine | NULL | NULL |
| 13 | 10 | 1 | 7 | Admin-1 capital | Sdid Bouzid | NULL | NULL |
| 14 | 10 | 1 | 7 | Admin-1 capital | Siliana | NULL | NULL |
| 15 | 10 | 1 | 7 | Admin-1 capital | Mahdia | NULL | NULL |
| 16 | 10 | 1 | 7 | Admin-1 capital | Monastir | NULL | NULL |
| 17 | 10 | 1 | 7 | Admin-1 capital | Zaghouan | NULL | NULL |
| 18 | 10 | 1 | 5 | Admin-1 capital | Tay Ninh | NULL | NULL |

Show All Features

7. Olenne kiinnostuneita jokaisen ominaisuuden asukasluvusta, joten **pop_max** on se tieto jota etsimme. Voit klikata tuplasti tietokentän otsikossa lajitellaksesi sarakkeen laskevaan järjestykseen.

Attribute table - ne_10m_populated_places_simple :: Features total: 7322, filtered: 7322, selected: 0

| | longitude | changed | namediff | diffnote | pop_max | pop_min | pop_other |
|------|------------------|----------------|----------|---------------------|----------|----------|-----------|
| 7312 | 139.75140742900 | 0.000000000000 | 0 | NULL | 35676000 | 8336599 | 1294525 |
| 7297 | -73.98001692880 | 0.000000000000 | 0 | NULL | 19040000 | 8008278 | 929260 |
| 7303 | -99.13098820170 | 0.000000000000 | 0 | NULL | 19028000 | 10811002 | 1001844 |
| 7313 | 72.85698929740 | 0.000000000000 | 0 | NULL | 18978000 | 12691836 | 1242608 |
| 7318 | -46.62501998040 | 0.000000000000 | 0 | NULL | 18845000 | 10021295 | 1152294 |
| 7221 | 77.23000402720 | 4.000000000000 | 0 | Changed feature... | 15926000 | 7633213 | 674738 |
| 7311 | 121.43650467800 | 0.000000000000 | 0 | NULL | 14987000 | 14608512 | 1680357 |
| 7316 | 88.32467565810 | 4.000000000000 | 1 | Name changed. ... | 14787000 | 4631392 | 778371 |
| 7248 | 90.40857946670 | 5.000000000000 | 0 | Changed scale ra... | 12797394 | 7000940 | 1499553 |
| 7290 | -58.39753137370 | 0.000000000000 | 0 | NULL | 12795000 | 10929146 | 1027145 |
| 7295 | -118.17998051100 | 0.000000000000 | 0 | NULL | 12500000 | 3694820 | 14226 |
| 7168 | 66.99000891000 | 5.000000000000 | 0 | Changed scale ra... | 12130000 | 11624219 | 1157027 |
| 7310 | 31.24996821970 | 0.000000000000 | 0 | NULL | 11893000 | 7734614 | 1372055 |
| 7317 | -43.22502079420 | 0.000000000000 | 0 | NULL | 11748000 | 2010175 | 182148 |
| 7280 | 135.46014481500 | 4.000000000000 | 0 | Changed feature... | 11294000 | 2592413 | 963078 |
| 7306 | 116.38828568400 | 0.000000000000 | 0 | NULL | 11106000 | 7480601 | 903323 |
| 7274 | 120.98221716200 | 0.000000000000 | 0 | NULL | 11100000 | 3077575 | 238128 |
| 7302 | 37.61552282590 | 0.000000000000 | 0 | NULL | 10452000 | 10452000 | 1058538 |
| 7299 | 29.01000158560 | 0.000000000000 | 0 | NULL | 10061000 | 9945610 | 965148 |

Show All Features

8. Now we are ready to perform our query on these attributes. QGIS uses SQL-like expressions to perform queries. Click Select features using an expression.

Attribute table - ne_10m_populated_places_simple :: Features total: 7322, filtered: 7322, selected: 0

| | longitude | changed | namediff | diffnote | pop_max | pop_min | pop_other |
|------|------------------|----------------|----------|---------------------|----------|----------|-----------|
| 7312 | 139.75140742900 | 0.000000000000 | 0 | NULL | 35676000 | 8336599 | 1294525 |
| 7297 | -73.98001692880 | 0.000000000000 | 0 | NULL | 19040000 | 8008278 | 929260 |
| 7303 | -99.13098820170 | 0.000000000000 | 0 | NULL | 19028000 | 10811002 | 1001844 |
| 7313 | 72.85698929740 | 0.000000000000 | 0 | NULL | 18978000 | 12691836 | 1242608 |
| 7318 | -46.62501998040 | 0.000000000000 | 0 | NULL | 18845000 | 10021295 | 1152294 |
| 7221 | 77.23000402720 | 4.000000000000 | 0 | Changed feature... | 15926000 | 7633213 | 674738 |
| 7311 | 121.43650467800 | 0.000000000000 | 0 | NULL | 14987000 | 14608512 | 1680357 |
| 7316 | 88.32467565810 | 4.000000000000 | 1 | Name changed. ... | 14787000 | 4631392 | 778371 |
| 7248 | 90.40857946670 | 5.000000000000 | 0 | Changed scale ra... | 12797394 | 7000940 | 1499553 |
| 7290 | -58.39753137370 | 0.000000000000 | 0 | NULL | 12795000 | 10929146 | 1027145 |
| 7295 | -118.17998051100 | 0.000000000000 | 0 | NULL | 12500000 | 3694820 | 14226 |
| 7168 | 66.99000891000 | 5.000000000000 | 0 | Changed scale ra... | 12130000 | 11624219 | 1157027 |
| 7310 | 31.24996821970 | 0.000000000000 | 0 | NULL | 11893000 | 7734614 | 1372055 |
| 7317 | -43.22502079420 | 0.000000000000 | 0 | NULL | 11748000 | 2010175 | 182148 |
| 7280 | 135.46014481500 | 4.000000000000 | 0 | Changed feature... | 11294000 | 2592413 | 963078 |
| 7306 | 116.38828568400 | 0.000000000000 | 0 | NULL | 11106000 | 7480601 | 903323 |
| 7274 | 120.98221716200 | 0.000000000000 | 0 | NULL | 11100000 | 3077575 | 238128 |
| 7302 | 37.61552282590 | 0.000000000000 | 0 | NULL | 10452000 | 10452000 | 1058538 |
| 7299 | 29.01000158560 | 0.000000000000 | 0 | NULL | 10061000 | 9945610 | 965148 |

Show All Features

9. In the Select By Expression window, expand the Fields and Values section and double-click the *pop_max* label. You will notice that it is added to the expression section at the bottom. If you aren't sure about the field values, you can click the Load all unique values to see what the attribute values are present in the dataset. For this exercise, we are looking to find all features that have a population greater than 1,000,000. So complete the expression as below and click Select.

"pop_max" > 1000000



10. Click on Close and return to the main QGIS window. You will notice that a subset of points is now rendered in yellow. This is the result of our query and you are seeing all places from the dataset that have the *pop_max* attribute value greater than 1,000,000.



11. The goal for this exercise is to find the places that are country capitals. The field containing this data is **adm0cap**. The value **1** indicates that the place is a capital. We can add this criteria to our previous expression using the **and** operator. Let's refine our query to select only those places which are capitals. Click on the Select feature using an expression button in the attribute table and enter the expression as below and click Select and then Close.

```
"pop_max" > 1000000 and "adm0cap" = 1
```



12. Return to the main QGIS window. Now you will see a smaller subset of the points selected. This is the result of the second query and shows all places from the dataset that are country capitals as well as have population greater than 1,000,000. If we wanted to do some further analysis on this subset of data, we can make this selection persistent. Right-click the *ne_10m_populated_places_simple* layer and select Properties.



13. In the General tab, scroll down to the Feature subset section. Click Query Builder.



14. Enter the same expression you had entered earlier and click OK.

```
"pop_max" > 1000000 and "adm0cap" = 1
```



15. Back in the main QGIS window, you will see rest of the points disappear. You may now perform any other analysis on this layer and only the features that match our expression will be used. You will notice that the points still appear in yellow. This is because they are still selected. Find the Deselect Features from All Layers button under the Attributes toolbar and click on it.



16. You will see that the points are now de-selected and rendered in their original color.

