## **CURSORES**

CURSOR	Valor	NS	ΙE	Ejemplo
ß	default	6+	4+	cursor:default
+	crosshair	6+	4+	cursor:crosshair
4	hand		4+	cursor:hand
4€	pointer	6+		cursor:pointer
€)	Cross browser		4+	cursor:pointer;cursor:hand
<b>‡</b>	move	6+	4+	cursor:move
Ι	text	6+	4+	cursor:text
$\overline{\mathbb{Z}}$	wait	6+	4+	cursor:wait
<b>⅓?</b>	help	6+	4+	cursor:help
Î	n-resize	6+	4+	cursor:n-resize
Ð	ne-resize	6+	4+	cursor:ne-resize
$\Rightarrow$	e-resize	6+	4+	cursor:e-resize
Ŋ	se-resize	6+	4+	cursor:se-resize
Î	s-resize	6+	4+	cursor:s-resize
ß	sw-resize	6+	4+	cursor:sw-resize
$\oplus$	w-resize	6+	4+	cursor:w-resize
ß	nw-resize	4+	4+	cursor:nw-resize
	progress		6+	cursor:progress
0	not-allowed		6+	cursor:not-allowed
₽0	no-drop		6+	cursor:no-drop
$\vdash\vdash$	vertical-text		6+	cursor:vertical-text
<b>.</b>	all-scroll		6+	cursor:all-scroll
<del>  </del>	col-resize		6+	cursor:col-resize
<b>‡</b>	row-resize		6+	cursor:row-resize
4	cursor:url(uri)		6+	cursor:url(uri)

Anexo D: Cursores.

Aplicaciones Web. 1º S.M.R.