Express Framework:

A framework on long Wade

- Nade jo is a Rubbino framework.

-> 5 apriles - Gramowork allows to make backerd le aur mobile.

-> Dossoode, Hiddlewae, +

An express borner.

client - side -> front-end bro-dia - rowar

reviews everyce & oppilars,

⇒ Create directory
 ⇒ Create index. js file
 ⇒ Initialize rpm. Expm install express!

-> I restall the somes Express package.

→ Write sorver application in index. is.

→ Start Sower. [node idea.js]

rafer document: Express js. com

.code:-

import express from "express";

const app = express();

app. lister (3000), () => {

consol. log ("sover running or part 3000"); 3); call lack,

whole is Dorol front?

- Making own awar compalies at however when Store in the Action

s har soon dies word hants on the server fort we can which which part on our computer is according for inferentians. Gram outside by

notatat - and 1 fidate "113 TEN WA" is wirdown sundo about -2 -12 -11 loop grap LISTEN so Marchanies

HTTP orguest: -

Learn the larguage to make sequent to your terver HTTP - Hypor Text Transfor Perolocal - work le Communicate bla Computers a via interest.

Request vocal:-

OGET - Requesta resource from server. [index. Him]

[most a sording a presource [enail-eign in etc...]

B PATCH Polith > Polith of a recourse.

DELETE -> Dabb remove.

code! inhost eather from , extens, court of = externs: app.got ("", (sug, ses) => f ; (" block allot ") bred . are ; (if

app. lister (3000, () => f D; consolo. log ("..."); render Dageri browlenger opie k. g. nadense Complete Ridou

- Postman and making other HTTP respects
- HTTP is to communicate to scruors

HTTP Rayranse alkabes code:

Lo indicates whether a specific HTTP request has been successfully completed. Perpones are grouped in 5 classes.

- (1991-001) scroper landlamespil (
- (PPS-005) asnopsed luperosul (300-299)
- (PPE-00E) associated (B)
- (PAL-004) savoyed roco-Inalo (A
- (600-6003) socrapporte rances (500-599)

WWW. postman.com/downloads/

Express Middleware:

- > request between the server and the Route [God, PUT, POST...] is called middlewase.
- -> Middlewore Preprocess She exequest, authoritisation

body-pooser. used to poose the body

establish report : establish as along a gillrad.

added import & dirname? from "path";

import & file & URTO PORT gran wal";

const-discome = discrame (file URL To Path Cimport-robate)

} !<= (cor, par ("/") top. "\") top. par ; (" < Alap . " + " + " + amonaid ...) shi throat .cor

; CE

```
To Loss Something:
      impart body Parson your "body - parson";
      abbahang
      app. use ( body Parser. wilencoded ( { extended: town 3);
      3 <= (core, pare), "timbus") too, sus)=> ?
         ; (ybod. par) polislands
      app. lister (part ...
  (1) morgan => logging:-
       inhag wador bow "warder,
       app. use Cmagan (" by biny"));
Building own middleware.
     eggn. wse (( seg, ses, nesot ) => }
        console log ("Request method", sog. method);
        noact ();
 Note:
     use "reg. body ['< for: ?" in label "]
          do get le value.
```