

C source code

```
1 #include <stdio.h>
2 int cap[100][100],n;
3 int bfs(int s,int t,int p[]){
4     int q[100],f=0,r=0,vis[100]={
5         0
6     };
7     q[r++]=s;
8     vis[s]=1;
9     p[s]=-1;
10    while(f<r){
11        int u=q[f++];
12        for(int v=1;v<=n;v++)if(!vis[v]&&cap[u][v]>0)vis[v]=1,p[v]=u,q[r++]=v;
13    }
14    return vis[t];
15 }
16 int main(){
17     int m,s,t;
18     scanf("%d%d",&n,&m);
19     for(int i=0;i<m;i++){
20         int u,v;
21         scanf("%d%d",&u,&v);
22         cap[u][v]++;
23         cap[v][u]++;
24     }
25     s=1;
26     t=n;
27     int p[100],flow=0;
28     while(bfs(s,t,p)){
29         int f=1e9;
30         for(int v=t;v!=s;v=p[v]){
31             int u=p[v];
32             if(cap[u][v]<f)f=cap[u][v];
33         }
34         for(int v=t;v!=s;v=p[v]){
35             int u=p[v];
36             cap[u][v]-=f;
37             cap[v][u]+=f;
38         }
39         flow+=f;
40     }
41     printf("%d\n",flow);
42     return 0;
43 }
```

Program output

2