

How to Delete a Bad Mudlog from RTS

KB0126921

28 views

How to Delete a Bad Mudlog from RTS

Scenario: The Mudlog Object has disappeared or is missing from SOAP, even though data is present in Insite and Cassandra.

Condition: Most likely, there is a mud log with no object name in Cassandra, which conflicts with the other Mudlogs and causes the mudlogs to disappear altogether.

To check this, query the “idsbywellbore” table and look for Mudlog entries with no names.

Example 1:

Example 2:

Also, the Object Leaf tables will be quite different for the “Bad” mudlog and a “Good” mudlog.

Example of Bad Mudlog ObjectLeaf:

Example of Good Mudlog ObjectLeaf:

Workaround: Once it has been identified that one or more mudlogs is present in Cassandra with no name, the “no name” mudlogs need to be deleted from the Platform to make the correct mudlogs available in SOAP.

- To delete the bad Mudlogs, post a mudlog delete message through Postman.

- Fill the Payload with the necessary details of the “Bad Mudlog”. See the example below.
- **Note:** Change the uid, uidWell, uidWellbore, nameWell, nameWellbore, and name appropriately for the mudlog to be deleted before posting the payload. The UUIDs and Names shown below are examples only and must be changed.
- Make sure a valid JWT token is sent with the message in the Authorization tab. (use the InsiteAgent SVC account)

Note: The workaround will only work if the Mudlog is in non-growing state. If the workaround doesn’t work, try again after 15 mins.

UKS Environment:

POST <https://rtsazukseuapix.corp.halliburton.com/api/v1/mudlogs>

```
{
  "rtsMessage": {
    "header": {
      "correlationId": "e65ca312-8f6f-4c66-b3db-21d04ddf4104",
      "originatingMachine": "WKS339360",
      "originatingIP": "::1",
      "objectKlass": "com.halliburton.domain.mudLog",
      "operation": "Delete",
      "timestamp": "a=2024-07-17T13:31:42.959#a=2024-07-17T13:31:42.279",
      "convertUids": false
    },
    "body": {
      "mudLog": {
        "uidWell": "b05b0737-f335-4b0f-8d94-fe8473a1c2a1",
```

```
"uidWellbore": "ae4d6aff-65a5-43d8-ace4-6deeb33331a9",  
"uid": "ef081ade-5bd4-323a-b6c4-871f16f779bf",  
"nameWell": "6507/2-7",  
"nameWellbore": "6507/2-7 S",  
"name": ""  
}  
}  
}  
}
```

Screenshots of PostMan

Authorization tab:

Body tab:

Once the payload is posted, check the Cassandra idsbywellbore table and confirm that the bad mudlog has been deleted. Once the workaround is completed successfully, the missing/disappeared mudlogs should be available in SOAP.

Example of idsbywellbore with only Good Mudlogs Remaining:

USC Environment:

POST <https://rtsazuscnaapix.corp.halliburton.com/api/v1/findmudLogs>

```
{
  "rtsMessage": {
    "header": {
      "correlationId": "e65ca312-8f6f-4c66-b3db-21d04ddf4104",
      "originatingMachine": "WKS339360",
      "originatingIP": "::1",
      "objectKlass": "com.halliburton.domain.mudLog",
      "operation": "Delete",
      "timestamp": "a=2024-07-17T13:31:42.959#a=2024-07-17T13:31:42.279",
      "convertUids": false
    },
    "body": {
      "mudLog": {
        "uidWell": "d4eacda5-300a-4381-b360-fe02111cfab9",
        "uidWellbore": "2a939f40-80cf-44bb-9d30-8c95bdb777ac",
```

```
"uid": "60664fbc-727e-3248-94e3-1e305dcec140",  
"nameWell": "YT_2P05",  
"nameWellbore": "YT_2P05",  
"name": ""  
}  
}  
}  
}
```

Screenshots of PostMan

Authorization tab:

Body tab:

Once the payload is posted, check the Cassandra idsbywellbore table and confirm that the bad mudlog has been deleted. Once the workaround is completed successfully, the missing/disappeared mudlogs should be available in SOAP.

Example of idsbywellbore with only Good Mudlogs Remaining:

Attachments [Pasted image.png](#)[Pasted image.png](#)[Pasted image.png](#)[Pasted image.png](#)[Pasted image.png](#)[Pasted image.png](#)[Pasted image.png](#)[Pasted image.png](#)[Pasted image.png](#)[Pasted image.png](#)

Authored by Thomas Dewayne Reed

Last modified 24/07/2024 20:04:00

Was this article helpful?