# Rajalakshmi Engineering College

Name: Atchaya R

Email: 241501026@rajalakshmi.edu.in

Roll no: 241501026 Phone: 6379572960

Branch: REC

Department: I AIML AD

Batch: 2028

Degree: B.E - AI & ML



### NeoColab\_REC\_CS23231\_DATA STRUCTURES

REC\_DS using C\_Week 2\_COD\_Question 5

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

### 1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

# Input Format

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

### **Output Format**

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

## Sample Test Case

```
Input: 4
1 2 3 4
```

Output: Data entered in the list:

node 1 : 1 node 2 : 2 node 3 : 3 node 4 : 4

Invalid position. Try again.

#### Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>
```

```
247507026
                                                   247501026
    // Node structure
struct Node {
      int data;
      struct Node* prev;
      struct Node* next;
   };
    // Function to create a node and append it to the end
   void append(struct Node** head, int data) {
      struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
      newNode->data = data;
      newNode->next = NULL;
                                                                              241501026
    if (*head == NULL) {
        newNode->prev = NULL;
        *head = newNode;
      } else {
        struct Node* temp = *head;
        while (temp->next != NULL)
          temp = temp->next;
        temp->next = newNode;
        newNode->prev = temp;
     }
   }
                                                   247501026
   // Function to display the list
   void display(struct Node* head) {
      struct Node* temp = head;
      int count = 1;
      while (temp != NULL) {
        printf(" node %d : %d\n", count, temp->data);
        count++;
        temp = temp->next;
      }
   }
   // Function to delete node at a given position
   int deleteAtPosition(struct Node** head, int pos, int n) {
                                                   241501026
                                                                              241501026
      if (pos < 1 \parallel pos > n)
       return 0; // invalid position
```

```
241501026
                                                     247507026
       struct Node* temp = *head;
      for (int i = 1; i < pos; i++)
         temp = temp->next;
       if (temp->prev != NULL)
         temp->prev->next = temp->next;
       else
         *head = temp->next; // deleting first node
       if (temp->next != NULL)
         temp->next->prev = temp->prev;
                                                                                241501026
return 1; // deletion successful
    int main() {
       int n, p, value;
       struct Node* head = NULL;
       scanf("%d", &n);
       for (int i = 0; i < n; i++) {
         scanf("%d", &value);
         append(&head, value);
                                                     247501026
                                                                                241501026
scanf("%d", &p);
       printf("Data entered in the list:\n");
       display(head);
       if (!deleteAtPosition(&head, p, n)) {
         printf("Invalid position. Try again.");
       } else {
         printf("\n After deletion the new list:\n");
         display(head);
       }
                                                                                241501026
                                                     247501026
       return 0;
247501
```

Status: Correct 

Marks: 10/10