

arange() Function

arange () Function is used to create an array with a group of elements from start to one element prior to stop in steps of stepsize.

Syntax:-

```
numpy.arange(start, stop, stepsize, dtype=None)
```

Where,

start – Start of interval. The interval includes this value. The default start value is 0.

stop – End of interval. The interval does not include this value, except in some cases where step is not an integer and floating point round-off affects the length of out.

stepsize – Spacing between values. The default step size is 1.

dtype – The type of output array.

Creating Array using arange () Function

Syntax:-

```
from numpy import *
```

```
array_name = arange(start, stop, stepsize, dtype=None)
```

Ex:-

```
from numpy import *
```

```
a = arange(5)
```

```
a = arange(5.0)
```

```
a = arange(1, 6)
```

```
a = arange(1, 10, 2,)
```

0.0	1.0	2.0	3.0	4.0
a[0]	a[1]	a[2]	a[3]	a[4]

Accessing One-D Array Elements

```
from numpy import *
```

```
a = arange(5)
```

```
print(a[0])
```

```
print(a[1])
```

```
print(a[2])
```

```
print(a[3])
```

```
print(a[4])
```

0.0	1.0	2.0	3.0	4.0
a[0]	a[1]	a[2]	a[3]	a[4]

Accessing using for loop

```
from numpy import *
```

```
a = arange(5)
```

Without index

```
for el in a:
```

```
    print(el)
```

With index

```
n = len(a)
```

```
for i in range(n):
```

```
    print(a[i])
```

Accessing using while loop

```
from numpy import *
```

```
a = arange(5)
```

```
n = len(a)
```

```
i = 0
```

```
while i < n :
```

```
    print(a[i])
```

```
    i+=1
```