ATHANASIOS GOURDOMICHALIS
Java Programms
App1.java

The election results among three mayoral candidates (**Y1**, **Y2**, and **Y3**) across five polling districts in a municipality were as follows:

Y1	Y2	Y3
182	41	202
145	85	325
195	15	115
110	24	407
255	11	357

Write a program (**App1.java**) that:

- **Creates** a 2D array of **5 rows** and **3 columns** using the results above. Assume that the votes received by candidate **Y1** are stored in **column 0**, candidate **Y2** in **column 1**, and candidate **Y3** in **column 2**. Similarly, results per candidate for the **1st polling district** are in **row 0**, for the **2nd polling district** in **row 1**, and so on.
- **Displays** the **table/array** exactly as shown above.
- **Calculates and displays** the **total number of votes** received by each candidate.
- **Calculates and displays** the **percentage** of total votes received by each candidate. Percentages must be formatted to **two decimal places** (e.g., 23.45%).
- Prints the name (Y1, Y2, or Y3) of the **winner of the election** if a candidate received **more than 50%** of the votes.

- States that a **runoff election** will take place between the **top two** candidates if **no candidate** received **more than 50%** of the votes, printing their names (Y1, Y2, Y3) and the percentages they received.

The program must work correctly with **any arbitrary input data** (vote counts), assuming there are always **three** candidates and **five** polling districts.

Complete the code in the file **App1.java**.

Every program must compile and run from the command line (not through an IDE).