


Question 7.

Q7. (a)



Code:

```
t=linspace(0,5,10000);
phi = log(t);
phi1 = (-2)*phi;
phi2 = -phi;
phi3 = -(0.5)*phi;
phi4 = -(0.2)*phi;
figure;

plot (t,phi1,'b');
hold on;
plot (t,phi2,'y');
hold on;
plot (t,phi3,'k');
hold on;
plot (t,phi4,'r');
hold on;
xlabel ('t axis');
ylabel ('phi axis');
title ('phi(T,t) = -Tlog(t), for different values of T');
xlim([0 5])
ylim([-4 12])
hold off;
legend('T = 2','T = 1','T = 0.5','T = 0.2');
```

Question 7.

Q7. (e)

>> taumain

(The iterative values of xhat has been shown for each value of tau. The final values are shown in bold.)

Iteration number: 1

Value of tau: 1

The number of iterations: 151

xhat =

0.1890

0.1382

0.0739

0.8807

Iteration number: 2

Value of tau: 5.000000e-01

The number of iterations: 158

xhat =

0.1890 **0.1320**

0.1382 **0.1055**

0.0739 **0.0413**

0.8807 **0.8665**

Iteration number: 3

Value of tau: 2.500000e-01

The number of iterations: 138

xhat =

0.1890 0.1320 **0.0925**

0.1382 0.1055 **0.0793**

0.0739 0.0413 **0.0222**

0.8807 0.8665 **0.8784**

Iteration number: 4

Value of tau: 1.250000e-01

The number of iterations: 835

Question 7.

xhat =

0.1890	0.1320	0.0925	0.0651
0.1382	0.1055	0.0793	0.0586
0.0739	0.0413	0.0222	0.0116
0.8807	0.8665	0.8784	0.9004

Iteration number: 5

Value of tau: 6.250000e-02

The number of iterations: 1564

xhat =

0.1890	0.1320	0.0925	0.0651	0.0459
0.1382	0.1055	0.0793	0.0586	0.0427
0.0739	0.0413	0.0222	0.0116	0.0060
0.8807	0.8665	0.8784	0.9004	0.9230

Iteration number: 6

Value of tau: 3.125000e-02

The number of iterations: 2953

xhat =

0.1890	0.1320	0.0925	0.0651	0.0459	0.0324
0.1382	0.1055	0.0793	0.0586	0.0427	0.0308
0.0739	0.0413	0.0222	0.0116	0.0060	0.0030
0.8807	0.8665	0.8784	0.9004	0.9230	0.9424

Iteration number: 7

Value of tau: 1.562500e-02

The number of iterations: 5596

xhat =

0.1890	0.1320	0.0925	0.0651	0.0459	0.0324	0.0229
0.1382	0.1055	0.0793	0.0586	0.0427	0.0308	0.0221
0.0739	0.0413	0.0222	0.0116	0.0060	0.0030	0.0015
0.8807	0.8665	0.8784	0.9004	0.9230	0.9424	0.9577

Question 7.

Iteration number: 8

Value of tau: 7.812500e-03

The number of iterations: 10583

xhat =

0.1890	0.1320	0.0925	0.0651	0.0459	0.0324	0.0229	0.0162
0.1382	0.1055	0.0793	0.0586	0.0427	0.0308	0.0221	0.0158
0.0739	0.0413	0.0222	0.0116	0.0060	0.0030	0.0015	0.0008
0.8807	0.8665	0.8784	0.9004	0.9230	0.9424	0.9577	0.9694

Iteration number: 9

Value of tau: 3.906250e-03

The number of iterations: 19986

xhat =

0.1890	0.1320	0.0925	0.0651	0.0459	0.0324	0.0229	0.0162	0.0114
0.1382	0.1055	0.0793	0.0586	0.0427	0.0308	0.0221	0.0158	0.0112
0.0739	0.0413	0.0222	0.0116	0.0060	0.0030	0.0015	0.0008	0.0004
0.8807	0.8665	0.8784	0.9004	0.9230	0.9424	0.9577	0.9694	0.9780

Iteration number: 10

Value of tau: 1.953125e-03

The number of iterations: 19999

xhat =

0.1890	0.1320	0.0925	0.0651	0.0459	0.0324	0.0229	0.0162	0.0114	0.0080
0.1382	0.1055	0.0793	0.0586	0.0427	0.0308	0.0221	0.0158	0.0112	0.0080
0.0739	0.0413	0.0222	0.0116	0.0060	0.0030	0.0015	0.0008	0.0004	0.0002
0.8807	0.8665	0.8784	0.9004	0.9230	0.9424	0.9577	0.9694	0.9780	0.9839

>>

Question 7.

Codes:

taumain.m

```
for i = 1:10
    tau = 2^(1-i);
    fprintf('Iteration number: %i\n', i);
    fprintf('Value of tau: %d\n', tau);
    if tau==1
        xxx = [1; 2; 3; 4];
        xhat(:,i) = tauf(tau,xxx)
    else
        xhat(:,i) = tauf(tau,xhat(:,i-1))
    end
end
```

tauf.m

```
function ret = tauf(taunum,xvect)
A = [1 -1 -1 0;2 0 3 0;-2 0 1 1;1 4 0 1;0 3 1 1];
y = [1;-1;1;2;0];
k = 1;
x(:,k) = xvect;

while (k < 20000)
d = 2*y'*A - 2*x(:,k)'*(A'*A) + taunum*[1/x(1,k) 1/x(2,k) 1/x(3,k) 1/x(4,k)];
d = d';
if (max(abs(d)) < (10^-4))
    break
end
a = 1;
for i = 1:4
    x(i,k+1) = x(i,k) + a*d(i);
end
while ((x(1,k+1) < 0) || (x(2,k+1) < 0) || (x(3,k+1) < 0) || (x(4,k+1) < 0))
    a = a/2;
    for i = 1:4
        x(i,k+1) = x(i,k) + a*d(i);
    end
end
pro(k) = x(1,k)*x(2,k)*x(3,k)*x(4,k);
pro(k+1) = x(1,k+1)*x(2,k+1)*x(3,k+1)*x(4,k+1);
fx(k+1) = -taunum*log(pro(k+1)) + (norm(y - A*x(:,k+1)))^2;
fx(k) = -taunum*log(pro(k)) + (norm(y - A*x(:,k)))^2;
while (fx(k+1) >= fx(k))
    a = a/2;
    for i = 1:4
        x(i,k+1) = x(i,k) + a*d(i);
    end
    pro(k+1) = x(1,k+1)*x(2,k+1)*x(3,k+1)*x(4,k+1);
    fx(k+1) = -taunum*log(pro(k+1)) + (norm(y - A*x(:,k+1)))^2;
end
k = k+1;
end
ret = x(:,k-1);
fprintf('The number of iterations: %i\n\n', k-1)
end
```

Question 7.