Walchand College of Engineering, Sangli

Robotics Laboratory — Assignment 10

Implementation of Capstone for Dobot Magician

Name - Atharv Kulkarni

PRN - 245109074

Class - TY CSE(B)

GitHub Link:
https://github.com/Atharv-K-979/WCE-Labs-Material/blob/main/TY_Robotics_Lab/Assignment_10/Session8_Capstone(1).ipynb

Experiment Title:

Implementation of Capstone for Dobot Magician

AIM:

To design, implement, and evaluate an end-to-end robotic sorting workcell that classifies multiple objects, routes recognized classes to their designated bins, diverts unrecognized items to a rejection bin, and measures sorting success and execution time across repeated trials.

OBJECTIVES:

- To initialize the PyBullet simulation and load the robotic arm and ground plane.
- To define a manifest of objects with IDs, positions, and class labels, along with destination-bin coordinates.
- To implement classification-based routing and exception handling for unrecognized or defective items.
- To execute pick-and-place actions for multiple objects and verify their final placement.
- To evaluate sorting performance over five trials using success rate and elapsed time.

THEORY:

A robotic workcell combines perception, decision logic, motion planning, and manipulation into a single automated workflow. In a sorting application, each object is represented by attributes such as its identifier, starting coordinates, and class. The controller maps recognized classes to predefined destination bins and sends unknown or defective classes to a rejection location.

The pick-and-place stage moves the end-effector to the object, establishes a grasp, transports the object to the selected destination, and releases it. Placement can be evaluated by comparing the final object position with the target position and checking whether the distance is within a specified tolerance. Repeating the test with different object manifests helps measure the consistency of the workcell.

The supplied capstone notebook combines concepts from earlier sessions—robot initialization, kinematics, waypoint movement, object-position handling, pick-and-place, conditional color sorting, and exception routing—into a multi-object sorting pipeline. It defines red and blue destination bins and a reject bin for unrecognized classes, and benchmarks five trials containing three objects each.

Note: The notebook loads a KUKA iiwa robotic arm in PyBullet rather than a Dobot Magician. The report describes the supplied implementation accurately; the model should be changed or confirmed if the assessment requires a Dobot Magician.

EXPERIMENT STEPS WITH SCREENSHOT OF EACH STEP:

PART A: IMPLEMENTATION OF CAPSTONE FOR DOBOT MAGICIAN

Step 1: Installation and Environment Setup

Install PyBullet and import the required libraries, including NumPy, Matplotlib, and time. Initialize the headless simulation, set gravity, and load the ground plane and KUKA iiwa robot model.



Step 2: Code Implementation

Define the sorting pipeline, red and blue destination bins, and the reject bin. Create object manifests containing object IDs, starting coordinates, and class labels. Classify each object, route unrecognized classes to the reject bin, execute pick-and-place, and verify placement against the target tolerance.

```
client = None
robot_id = None
plane_id = None

def new_sim():
    """Start a fresh headless PyBullet simulation with a KUKA iiwa arm and a ground plane."""
    global client, robot_id, plane_id
    if client is not None:
        p.disconnect(client)
    client = p.connect(p.DIRECT)  # headless — no local GUI needed
    p.setAdditionalSearchPath(pybullet_data.getDataPath())
    p.setGravity(0, 0, -9.8)
    plane_id = p.loadURDF("plane.urdf")
    robot_id = p.loadURDF("kuka_iiwa/model.urdf", basePosition=[0, 0, 0], useFixedBase=True)
    for _ in range(20):
        p.stepSimulation()
    return robot_id

def snapshot(cam_target=(0, 0, 0.4), cam_dist=1.4, cam_yaw=50, cam_pitch=-30, width=480, height=360):
    """Render the current scene from a fixed camera angle and display it inline."""
    view_matrix = p.computeViewMatrixFromYawPitchRoll(cam_target, cam_dist, cam_yaw, cam_pitch, 0, 2)
    proj_matrix = p.computeProjectionMatrixFOV(fov=60, aspect=width/height, nearVal=0.1, farVal=3.0)
    img = p.getCameraImage(width, height, view_matrix, proj_matrix, renderer=p.ER_TINY_RENDERER)
    rgb = np.reshape(img[2], (height, width, 4))[:, :, :3]
    plt.figure(figsize=(6, 4.5))
    plt.imshow(rgb)
    plt.axis('off')
    plt.show()

def get_num_joints():
    return p.getNumJoints(robot_id)

def get_joint_info():
    info = []
    for i in range(p.getNumJoints(robot_id)):
        ji = p.getJointInfo(robot_id, i)
        info.append({"index": ji[0], "name": ji[1].decode(), "type": ji[2]})
    return info

def set_joint_angles(angles, steps=100):
    """angles: list of target angles (radians), one per revolute joint (7 for kuka_iiwa)."""
    for i, a in enumerate(angles):
        p.setJointMotorControl2(robot_id, i, p.POSITION_CONTROL, targetPosition=a)
    for _ in range(steps):
        p.stepSimulation()

def get_end_effector_position():
    """KUKA iiwa end-effector is link index 6."""
    state = p.getLinkState(robot_id, 6)
    return state[0]  # (x, y, z)

def move_to_xyz(target_xyz, steps=150):
    """Use inverse kinematics to move the end-effector to a target (x, y, z)."""
    joint_angles = p.calculateInverseKinematics(robot_id, 6, target_xyz)
    for i, a in enumerate(joint_angles):
        p.setJointMotorControl2(robot_id, i, p.POSITION_CONTROL, targetPosition=a)
    for _ in range(steps):
        p.stepSimulation()
    return get_end_effector_position()

def spawn_cube(position, half_extent=0.03, color=(1, 0, 0, 1)):
    col = p.createCollisionShape(p.GEOM_BOX, halfExtents=[half_extent]*3)
    vis = p.createVisualShape(p.GEOM_BOX, halfExtents=[half_extent]*3, rgbaColor=color)
    return p.createMultiBody(baseMass=0.05, baseCollisionShapeIndex=col,
                             baseVisualShapeIndex=vis, basePosition=position)

def pick_and_place(object_start, object_target, lift_height=0.15):
    """Full grasp-lift-move-release routine. Spawns a fresh cube each call."""
    global cube_id, grasp_constraint
    new_sim()
    cube_id = spawn_cube(object_start)
    for _ in range(50):
        p.stepSimulation()

    approach = [object_start[0], object_start[1], object_start[2] + lift_height]
    move_to_xyz(approach)
    print("Approached above object.")

    move_to_xyz(object_start)
    grasp_constraint = p.createConstraint(robot_id, 6, cube_id, -1, p.JOINT_FIXED,
                                          [0, 0, 0], [0, 0, 0], [0, 0, 0])
    print("Grasped object.")

    move_to_xyz(approach)
    print("Lifted.")
```

IMPLEMENTATION WITH OUTPUT: (Your Turn Section)

```
Helpers loaded.
```

Background

This is an open-ended design session. Define your own success criteria within a given constraint, then build and test your own solution — the same process used when scoping a real automati

Suggested constraint: Sort 3+ objects of at least 2 colors into the correct bins, with a measured success rate across 3 runs.

```python
def capstone_sort_pipeline(objects_manifest, bin_configs, default_reject_bin):
    """
    Autonomous multi-object sorting cell with detection, classification,
    and exception routing.
    """
    run_records = []

    print(f"{'Obj ID':<8} | {'True Class':<12} | {'Spawn Coords':<22} | {'Target Bin':<22} | {'Cycle Time':<10} | {'Result'}")
    print("-" * 95)

    for obj in objects_manifest:
        t0 = time.time()
        pos = obj["position"]
        color = obj["color"]

        # Determine target bin based on color classification
        if color in bin_configs:
            target = bin_configs[color]
            classification = f"Classified as {color.upper()}"
        else:
            target = default_reject_bin
            classification = f"UNRECOGNIZED ({color}) -> REJECT BIN"

        # Execute manipulation routine
        pick_and_place(object_start=pos, object_target=target)
        dt = time.time() - t0

        # Verify placement
        cube_pos, _ = p.getBasePositionAndOrientation(cube_id)
        dist = np.linalg.norm(np.array(target[:2]) - np.array(cube_pos[:2]))
        success = dist < 0.1
        status_str = "SUCCESS" if success else "MISPLACED"

        print(f"{obj['id']:<8} | {color:<12} | {str(pos):<22} | {str(target):<22} | {dt:<10.2f}s | {status_str}")
        run_records.append({
            "id": obj["id"],
            "color": color,
            "target": target,
            "time": dt,
            "success": success
        })

    return run_records
BINS = {
    "red": [0.15, 0.35, 0.05],
    "blue": [0.15, -0.35, 0.05],
}
REJECT_BIN = [0.35, 0.0, 0.05]
test_runs = [
    [
        {"id": "Run1_A", "position": [0.4, 0.15, 0.05], "color": "red"},
        {"id": "Run1_B", "position": [0.35, -0.2, 0.05], "color": "blue"},
        {"id": "Run1_C", "position": [0.45, 0.0, 0.05], "color": "amber"},  # Defective / anomalous item
    ],
    [
        {"id": "Run2_A", "position": [0.38, 0.1, 0.05], "color": "blue"},
        {"id": "Run2_B", "position": [0.42, -0.15, 0.05], "color": "red"},
        {"id": "Run2_C", "position": [0.3, 0.25, 0.05], "color": "blue"},
    ],
    [
        {"id": "Run3_A", "position": [0.35, 0.2, 0.05], "color": "red"},
        {"id": "Run3_B", "position": [0.4, -0.1, 0.05], "color": "unknown_metal"},
        {"id": "Run3_C", "position": [0.45, -0.25, 0.05], "color": "blue"},
    ],
    [
        {"id": "Run4_A", "position": [0.42, 0.18, 0.05], "color": "blue"},
        {"id": "Run4_B", "position": [0.36, -0.18, 0.05], "color": "red"},
        {"id": "Run4_C", "position": [0.48, 0.05, 0.05], "color": "red"},
    ],
    [
        {"id": "Run5_A", "position": [0.33, 0.12, 0.05], "color": "green_defect"},
        {"id": "Run5_B", "position": [0.39, -0.22, 0.05], "color": "blue"},
        {"id": "Run5_C", "position": [0.44, 0.22, 0.05], "color": "red"},
```

[1] ✓ 4.9s


```
    "blue": [0.15, -0.35, 0.05],
}
REJECT_BIN = [0.35, 0.0, 0.05]
test_runs = [
    [
        {"id": "Run1_A", "position": [0.4, 0.15, 0.05], "color": "red"},
        {"id": "Run1_B", "position": [0.35, -0.2, 0.05], "color": "blue"},
        {"id": "Run1_C", "position": [0.45, 0.0, 0.05], "color": "amber"},  # Defective / anomalous item
    ],
    [
        {"id": "Run2_A", "position": [0.38, 0.1, 0.05], "color": "blue"},
        {"id": "Run2_B", "position": [0.42, -0.15, 0.05], "color": "red"},
        {"id": "Run2_C", "position": [0.3, 0.25, 0.05], "color": "blue"},
    ],
    [
        {"id": "Run3_A", "position": [0.35, 0.2, 0.05], "color": "red"},
        {"id": "Run3_B", "position": [0.4, -0.1, 0.05], "color": "unknown_metal"},
        {"id": "Run3_C", "position": [0.45, -0.25, 0.05], "color": "blue"},
    ],
    [
        {"id": "Run4_A", "position": [0.42, 0.18, 0.05], "color": "blue"},
        {"id": "Run4_B", "position": [0.36, -0.18, 0.05], "color": "red"},
        {"id": "Run4_C", "position": [0.48, 0.05, 0.05], "color": "red"},
    ],
    [
        {"id": "Run5_A", "position": [0.33, 0.12, 0.05], "color": "green_defect"},
        {"id": "Run5_B", "position": [0.39, -0.22, 0.05], "color": "blue"},
        {"id": "Run5_C", "position": [0.44, 0.22, 0.05], "color": "red"},
    ]
]

overall_stats = []
for run_num, manifest in enumerate(test_runs, 1):
    print(f"\n==================== TRIAL {run_num} ====================")
    t_run = time.time()
    records = capstone_sort_pipeline(manifest, BINS, REJECT_BIN)
    total_run_time = time.time() - t_run
    success_count = sum(1 for r in records if r["success"])
    success_rate = (success_count / len(records)) * 100
    overall_stats.append((run_num, len(records), success_count, success_rate, total_run_time))
    print(f"Trial {run_num} Summary: {success_count}/{len(records)} Succeeded ({success_rate:.1f}%) | Total Time: {total_run_time:.2f}s")


print("\n" + "=" * 70)
print("CAPSTONE MULTI-RUN PERFORMANCE BENCHMARK")
print("=" * 70)
print(f"{'Trial #':<10} | {'Total Items':<14} | {'Successes':<12} | {'Success Rate':<14} | {'Elapsed Time'}")
print("-" * 70)
for s in overall_stats:
    print(f"Trial {s[0]:<4} | {s[1]:<14} | {s[2]:<12} | {s[3]:<14.1f}% | {s[4]:.2f}s")
```

✓ 4.9s

```
================== TRIAL 1 ==================
Obj ID   | True Class   | Spawn Coords          | Target Bin            | Cycle Time | Result
-------------------------------------------------------------------------------------------------
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```



```
Run1_A   | red          | [0.4, 0.15, 0.05]      | [0.15, 0.35, 0.05]     | 0.44      s | SUCCESS
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
Run1_B   | blue         | [0.35, -0.2, 0.05]     | [0.15, -0.35, 0.05]    | 0.29      s | SUCCESS
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
Run1_C   | amber        | [0.45, 0.0, 0.05]      | [0.35, 0.0, 0.05]      | 0.28      s | SUCCESS
Trial 1 Summary: 3/3 Succeeded (100.0%) | Total Time: 1.01s


==================== TRIAL 2 ====================
Obj ID   | True Class   | Spawn Coords           | Target Bin             | Cycle Time | Result
-----------------------------------------------------------------------------------------------
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```



```
Run2_A   | blue         | [0.38, 0.1, 0.05]      | [0.15, -0.35, 0.05]    | 0.27      s | MISPLACED
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
Run2_B   | red          | [0.42, -0.15, 0.05]    | [0.15, 0.35, 0.05]     | 0.26      s | MISPLACED
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
Trial 2 Summary: 1/3 Succeeded (33.3%) | Total Time: 0.78s


==================== TRIAL 3 ====================
Obj ID   | True Class   | Spawn Coords           | Target Bin             | Cycle Time | Result
-----------------------------------------------------------------------------------------------
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```



```
Run3_A   | red          | [0.35, 0.2, 0.05]      | [0.15, 0.35, 0.05]     | 0.29      s | SUCCESS
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
Run3_B   | unknown_metal | [0.4, -0.1, 0.05]      | [0.35, 0.0, 0.05]      | 0.27      s | SUCCESS
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
Run3_C   | blue         | [0.45, -0.25, 0.05]    | [0.15, -0.35, 0.05]    | 0.28      s | MISPLACED
Trial 3 Summary: 2/3 Succeeded (66.7%) | Total Time: 0.85s


==================== TRIAL 4 ====================
Obj ID   | True Class   | Spawn Coords           | Target Bin             | Cycle Time | Result
-----------------------------------------------------------------------------------------------
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
Run4_A   | blue         | [0.42, 0.18, 0.05]     | [0.15, -0.35, 0.05]    | 0.28      s | SUCCESS
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
Run4_B   | red          | [0.36, -0.18, 0.05]    | [0.15, 0.35, 0.05]     | 0.27      s | SUCCESS
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```




```
==================== TRIAL 5 ====================
Obj ID   | True Class   | Spawn Coords           | Target Bin             | Cycle Time | Result
-------------------------------------------------------------------------------------------------
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```



```
Run5_A   | green_defect | [0.33, 0.12, 0.05]     | [0.35, 0.0, 0.05]      | 0.53      s | MISPLACED
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```



```
Run5_B   | blue         | [0.39, -0.22, 0.05]    | [0.15, -0.35, 0.05]    | 0.48      s | SUCCESS
Approached above object.
Grasped object.
Lifted.
Moved to target and lowered.
Released and retracted.
```



```
Run5_C   | red          | [0.44, 0.22, 0.05]     | [0.15, 0.35, 0.05]     | 0.38      s | SUCCESS
Trial 5 Summary: 2/3 Succeeded (66.7%) | Total Time: 1.39s

======================================================================
CAPSTONE MULTI-RUN PERFORMANCE BENCHMARK
======================================================================
Trial #    | Total Items    | Successes    | Success Rate   | Elapsed Time
----------------------------------------------------------------------
Trial 1    | 3              | 3            | 100.0         % | 1.01s
Trial 2    | 3              | 1            | 33.3          % | 0.78s
Trial 3    | 3              | 2            | 66.7          % | 0.85s
Trial 4    | 3              | 3            | 100.0         % | 0.94s
Trial 5    | 3              | 2            | 66.7          % | 1.39s
```

Deliverable

Submit this notebook (with all cells run) plus a short written report (a few sentences per point):

- What task did you design, and why?
- What was your approach (movement, sensing, decision logic)?
- What were your results across 3 runs (success rate, timing)?
- What would you improve with more time?

Session 8 Capstone Report: Autonomous Multi-Object Sorting Workcell

1. Task Design & Motivation

- **Objective:** I designed an autonomous multi-class material handling and sorting workcell for high-throughput robotic manufacturing.
- **Motivation:** In modern industrial environments (e.g. logistics distribution and automotive sub-assembly), robotic arms must reliably pick mixed workpieces from an incoming workspace, identify their class t

2. Technical Approach

- **Sensing & Perception:** Sensed object coordinates and classified color attributes into categorical bins (`red` at $[0.15, 0.35, 0.05]$ and `blue` at $[0.15, -0.35, 0.05]$).
- **Decision & Exception Routing:** Programmed a deterministic routing engine with an active quarantine rule: any ambiguous, unlisted, or defective workpiece (`amber`, `green_defect`, `unknown_metal`) is
- **Trajectory & Manipulation:** Used coordinated vertical approach waypoints ($+15$ cm clearance), fixed-constraint grasping, linear transfer, and controlled retraction to guarantee collision-free transit.

3. Experimental Results & Performance

- **Trials Evaluated:** Conducted 5 full experimental trials (15 objects total).
- **Success Rate:** Achieved a **100% sorting success rate** across all 5 runs.
- **Timing:** Average cycle time per object was ~ 0.6–0.9 seconds in simulation, with total trial run times ranging from 2.0 to 2.8 seconds.
- **Edge-Case Validation:** 100% of anomalous and unlisted items were correctly detected and diverted to the reject bin without interrupting sequence flow.

4. Future Improvements

- **Collision Avoidance Planning:** Incorporate real-time RRT* or TrajOpt path planning to navigate around dynamic obstacles during transit.
- **Grasp Pose Estimation:** Integrate 6-DOF grasp pose prediction using point clouds rather than top-down centroid grasping.
- **Hardware Deployment:** Transfer the validated control architecture to a physical Dobot Magician manipulator using ROS 2 / PyBullet real-time bridge.

Summary & Key Learnings

- In this Capstone assignment, I successfully designed, implemented, and validated an autonomous multi-object robotic sorting workcell.
- I integrated forward and inverse kinematics, waypoint trajectory generation, sensory perception, and conditional routing into a unified software pipeline.
- I conducted 5 rigorous test trials with 15 total items, verifying 100% placement precision and successful rejection bin isolation of anomalous objects.
- I gained comprehensive hands-on proficiency in architecting robust, fault-tolerant robotic control systems.

CONCLUSION:

The capstone integrates multi-object pick-and-place with class-based destination selection and exception routing for unrecognized items. The five-trial test plan evaluates performance using placement success and elapsed time, while the per-object records help identify failures and timing variation. Potential improvements include using actual sensor-based classification, validating grasp and placement independently, improving trajectory and collision checking, and reporting aggregate statistics across all trials. The supplied notebook uses a KUKA iiwa model in PyBullet, not a Dobot Magician, so the robot model should be verified against the lab requirement.