

WHERE B.BOOK_ID=C.BOOK_ID
AND C.BRANCH_ID=L.BRANCH_ID;

BOOK_ID	TITLE	NO_OF_COPIES
1	DBMS	10
1	DBMS	5
2	ADBMS	2
2	ADBMS	5
3	CN	7
5	OS	1
4	CG	3

2. Consider the following schema for Order Database:

SALESMAN (*Salesman_id, Name, City, Commission*)

CUSTOMER (*Customer_id, Cust_Name, City, Grade, Salesman_id*)

ORDERS (*Ord_No, Purchase_Amt, Ord_Date, Customer_id, Salesman_id*)


Write SQL queries to

1. Count the customers with grades above Bangalore's average.
2. Find the name and numbers of all salesmen who had more than one customer.
3. List all salesmen and indicate those who have and don't have customers in their cities (Use UNION operation.)
4. Create a view that finds the salesman who has the customer with the highest order of a day.

5. Demonstrate the DELETE operation by removing salesman with id 1000. All his orders must also be deleted.

Solution:

Entity-Relationship Diagram



Schema Diagram

Salesman

<u>Salesman_id</u>	Name	City	Commission
--------------------	------	------	------------

Customer

<u>Customer_id</u>	Cust_Name	City	Grade	Salesman_id
--------------------	-----------	------	-------	-------------

Orders

<u>Ord_No</u>	Purchase_Amt	Ord_Date	Customer_id	Salesman_id
---------------	--------------	----------	-------------	-------------

Table Creation

```
CREATE TABLE SALESMAN
(SALESMAN_ID NUMBER (4),
NAME VARCHAR2 (20),
CITY VARCHAR2 (20),
COMMISSION VARCHAR2 (20),
PRIMARY KEY (SALESMAN_ID));
```

```
CREATE TABLE CUSTOMER1
(CUSTOMER_ID NUMBER (4),
CUST_NAME VARCHAR2 (20),
CITY VARCHAR2 (20),
GRADE NUMBER (3),
PRIMARY KEY (CUSTOMER_ID),
SALESMAN_ID REFERENCES SALESMAN (SALESMAN_ID) ON DELETE SET NULL);
```

```
CREATE TABLE ORDERS
(ORD_NO NUMBER (5),
PURCHASE_AMT NUMBER (10, 2),
ORD_DATE DATE,
PRIMARY KEY (ORD_NO),
CUSTOMER_ID REFERENCES CUSTOMER1 (CUSTOMER_ID) ON DELETE CASCADE,
SALESMAN_ID REFERENCES SALESMAN (SALESMAN_ID) ON DELETE CASCADE);
```

Table Descriptions

```
DESC SALESMAN;
```

```
SQL> DESC SALESMAN;
```

Name	Null?	Type
SALESMAN_ID	NOT NULL	NUMBER(4)
NAME		VARCHAR2(15)
CITY		VARCHAR2(15)
COMMISSION		NUMBER(3,2)

```
DESC CUSTOMER1;
```

SQL> DESC CUSTOMER1;

Name	Null?	Type
CUSTOMER_ID	NOT NULL	NUMBER(4)
CUST_NAME		VARCHAR2(15)
CITY		VARCHAR2(15)
GRADE		NUMBER(3)
SALESMAN_ID		NUMBER(4)

DESC ORDERS;

SQL> DESC ORDERS;

Name	Null?	Type
ORD_NO	NOT NULL	NUMBER(5)
PURCHASE_AMT		NUMBER(10,2)
ORD_DATE		DATE
CUSTOMER_ID		NUMBER(4)
SALESMAN_ID		NUMBER(4)

Insertion of Values to Tables

INSERT INTO SALESMAN VALUES (1000, 'JOHN', 'BANGALORE', '25 %');
INSERT INTO SALESMAN VALUES (2000, 'RAVI', 'BANGALORE', '20 %');
INSERT INTO SALESMAN VALUES (3000, 'KUMAR', 'MYSORE', '15 %');
INSERT INTO SALESMAN VALUES (4000, 'SMITH', 'DELHI', '30 %');
INSERT INTO SALESMAN VALUES (5000, 'HARSHA', 'HYDRABAD', '15 %');

INSERT INTO CUSTOMER1 VALUES (10, 'PREETHI', 'BANGALORE', 100, 1000);
INSERT INTO CUSTOMER1 VALUES (11, 'VIVEK', 'MANGALORE', 300, 1000);
INSERT INTO CUSTOMER1 VALUES (12, 'BHASKAR', 'CHENNAI', 400, 2000);
INSERT INTO CUSTOMER1 VALUES (13, 'CHETHAN', 'BANGALORE', 200, 2000);
INSERT INTO CUSTOMER1 VALUES (14, 'MAMATHA', 'BANGALORE', 400, 3000);

INSERT INTO ORDERS VALUES (50, 5000, '04-MAY-17', 10, 1000);
INSERT INTO ORDERS VALUES (51, 450, '20-JAN-17', 10, 2000);
INSERT INTO ORDERS VALUES (52, 1000, '24-FEB-17', 13, 2000);
INSERT INTO ORDERS VALUES (53, 3500, '13-APR-17', 14, 3000);
INSERT INTO ORDERS VALUES (54, 550, '09-MAR-17', 12, 2000);

SELECT * FROM SALESMAN;

SALESMAN_ID	NAME	CITY	COMMISSION
1000	JOHN	BANGALORE	25 %
2000	RAVI	BANGALORE	20 %
3000	KUMAR	MYSORE	15 %
4000	SMITH	DELHI	30 %
5000	HARSHA	HYDRABAD	15 %

SELECT * FROM CUSTOMER1;

CUSTOMER_ID	CUST_NAME	CITY	GRADE	SALESMAN_ID
10	PREETHI	BANGALORE	100	1000
11	VIVEK	MANGALORE	300	1000
12	BHASKAR	CHENNAI	400	2000
13	CHEETHAN	BANGALORE	200	2000
14	MAMATHA	BANGALORE	400	3000

SELECT * FROM ORDERS;

ORD_NO	PURCHASE_AMT	ORD_DATE	CUSTOMER_ID	SALESMAN_ID
50	5000	04-MAY-17	10	1000
51	450	20-JAN-17	10	2000
52	1000	24-FEB-17	13	2000
53	3500	13-APR-17	14	3000
54	550	09-MAR-17	12	2000

Queries:

- Count the customers with grades above Bangalore's average.

```
SELECT GRADE, COUNT (DISTINCT CUSTOMER_ID)
FROM CUSTOMER1
GROUP BY GRADE
HAVING GRADE > (SELECT AVG(GRADE)
FROM CUSTOMER1
WHERE CITY='BANGALORE');
```

GRADE	COUNT(DISTINCTCUSTOMER_ID)
300	1
400	2

- Find the name and numbers of all salesmen who had more than one customer.

```
SELECT SALESMAN_ID, NAME
FROM SALESMAN A
WHERE 1 < (SELECT COUNT (*)
```

```
FROM CUSTOMER1
WHERE SALESMAN_ID=A.SALESMAN_ID);
```

```
SALESMAN_ID NAME
```

```
-----
1000 JOHN
2000 RAU
```

3. List all salesmen and indicate those who have and don't have customers in their cities (Use UNION operation.)

```
SELECT SALESMAN.SALESMAN_ID, NAME, CUST_NAME, COMMISSION
FROM SALESMAN, CUSTOMER1
WHERE SALESMAN.CITY = CUSTOMER1.CITY
UNION
SELECT SALESMAN_ID, NAME, 'NO MATCH', COMMISSION
FROM SALESMAN
WHERE NOT CITY = ANY
(SELECT CITY
FROM CUSTOMER1)
ORDER BY 2 DESC;
```

SALESMAN_ID	NAME	CUST_NAME	COMMISSION
4000	SMITH	NO MATCH	30 %
2000	RAU	CHETHAN	20 %
2000	RAU	MAMATHA	20 %
2000	RAU	PREETHI	20 %
3000	KUMAR	NO MATCH	15 %
1000	JOHN	CHETHAN	25 %
1000	JOHN	MAMATHA	25 %
1000	JOHN	PREETHI	25 %
5000	HARSHA	NO MATCH	15 %

4. Create a view that finds the salesman who has the customer with the highest order of a day.

```
CREATE VIEW ELITSALESMAN AS
SELECT B.ORD_DATE, A.SALESMAN_ID, A.NAME
FROM SALESMAN A, ORDERS B
WHERE A.SALESMAN_ID = B.SALESMAN_ID
AND B.PURCHASE_AMT=(SELECT MAX (PURCHASE_AMT)
FROM ORDERS C
WHERE C.ORD_DATE = B.ORD_DATE);
```

ORD_DATE	SALESMAN_ID	NAME
04-MAY-17	1000	JOHN
20-JAN-17	2000	RAVI
24-FEB-17	2000	RAVI
13-APR-17	3000	KUMAR
09-MAR-17	2000	RAVI

5. Demonstrate the DELETE operation by removing salesman with id 1000. All his orders must also be deleted.

Use ON DELETE CASCADE at the end of foreign key definitions while creating child table orders and then execute the following:

Use ON DELETE SET NULL at the end of foreign key definitions while creating child table customers and then executes the following:

```
DELETE FROM SALESMAN
WHERE SALESMAN_ID=1000;
```

```
SQL> DELETE FROM SALESMAN
      2  WHERE SALESMAN_ID=1000;
```

```
1 row deleted.
```

```
SQL> SELECT * FROM SALESMAN;
```

SALESMAN_ID	NAME	CITY	COMMISSION
2000	RAVI	BANGALORE	20 %
3000	KUMAR	MYSORE	15 %
4000	SMITH	DELHI	30 %
5000	HARSHA	HYDRABAD	15 %

3. Consider the schema for Movie Database:

ACTOR (Act_id, Act_Name, Act_Gender)

DIRECTOR (Dir_id, Dir_Name, Dir_Phone)