


GRAPH HACKS: CONTEXT FOR AI AGENTS / FALKORDB

One phished npm maintainer, 13 of 22 services exposed: how I built PatientZero on FalkorDB

I replayed the September 2025 npm qix compromise against a dependency graph in FalkorDB. Variable-length Cypher, graph memory and a four-agent crew answer the 2 AM questions: are we hit, how bad is it, and who do I wake?

Atharv Raotole / October 2026

On September 8, 2025, one npm maintainer clicked a phishing link. Within hours, 19 of his packages, including `debug` and `chalk`, shipped malware, and those packages had been downloaded 2.71 billion times the week before.

If you ran a platform team that night, you didn't care about the payload. You had three questions: **are we hit, how bad is it, and who do I wake up?** I built PatientZero to answer all three in seconds, and to show its work.

> **TL;DR**
>
> - PatientZero replays the real npm "qix" compromise (and the Shai-Hulud worm a week later) against a fleet graph in FalkorDB.
> - Exposure is a variable-length Cypher traversal plus an npm semver check on the last edge. On my 22-service test fleet: direct dependencies find **1** exposed service, four hops find **13**.
> - Incidents, approved playbooks, conversations and agent handoffs all live in the graph, so the agent remembers and can explain itself.
> - Four agents hand off work through `HANDED_OFF_TO` edges, the agent calls its tools through its own MCP server, and a live OSV watch checks new npm malware every 10 minutes.
> - **Live demo:** patientzero-production-2cb3.up.railway.app · **Code:** github.com/AtharvRaotole/FalkorDB

The 2 AM problem is a path problem

Here is one real chain from the test fleet:

```
img-service → sharp → color → color-string → simple-swizzle
```


`simple-swizzle` was one of the 19 compromised packages. `img-service` never mentions it. You'd only find it four hops down, and only if you went looking.

That is the whole problem in one line. Exposure is transitive, so a list of direct dependencies lies to you. On my fleet, checking direct dependencies flags **1 of 22** services. Following chains up to four hops flags **13**.

There's a second twist that took me a while to see. The malicious versions were unpublished within hours, so they never show up in anyone's resolved tree today. "Do we have `debug@4.4.2` installed?" is the wrong question. The right one is: **would a fresh install on September 8 have pulled it?** That depends on the semver range declared on the last edge of the chain. `^4.3.4` admits 4.4.2. An exact pin on `2.6.9` doesn't.

A graph stores both things a lockfile scan can't easily join: the chain, and the range on every hop.

The graph model



The model. Red is the exposure traversal and the `EXPOSED` edges it writes back. Everything in the top panel is written by the agents.

Three neighbourhoods share one graph:

- **npm supply chain (real data).** `Package`, `Version`, `Advisory` and `Maintainer`, from OSV, GitHub advisories, deps.dev and the npm registry. `REQUIRES` edges keep the declared range as a `requirement` property.
- **The org (synthetic, and labelled that way in the UI).** The Acme fleet: 22 services, 8 teams, 16 people, with on-call rotations. Services `DEPENDS_ON` real npm versions.
- **Memory and coordination.** `Incident`, `Finding`, `Playbook`, `CrewRun`, `AgentRun`, `Session`, `Turn` and `WatchEvent`. Nothing the agent knows lives in Python memory.


One query and a depth slider

This is the main query, from `queries/exposure.cypher` with a few output columns trimmed:

```
MATCH p = (s:Service)-[:DEPENDS_ON|REQUIRES*1..6]->(v:Version)
WHERE v.pkg IN $pkgs AND length(p) <= $depth
WITH s, p, v, last(relationships(p)) AS r
RETURN s.name AS service, v.pkg AS pkg, r.requirement AS requirement,
       length(p) AS hops, [n IN nodes(p) | n.name] AS via
ORDER BY service, hops
```

FalkorDB returns every candidate path from a service to any version of an affected package, with the range on the last hop. The app then runs real npm semver (`nodesemver.satisfies`) against the bad version. FalkorDB finds the paths and the app makes the semver call, and each does what it's good at.

One detail I learned the hard way: FalkorDB doesn't accept a parameter as a variable-length bound, so `*1..$depth` won't work. I fixed the pattern at `*1..6` and filter with `length(p) <= $depth`. That filter drives the depth slider in the UI.



Replaying the qix compromise. Red chains are exposed paths; hollow nodes reach an affected package but their ranges exclude the bad version.

Drag the slider and the story changes: 1 of 22 at depth 1, 13 at depth 4, 14 at depth 6. The answer also reports **honest negatives**. `checkout-api` reaches `debug` through `express@4.21.2`, but the exact pin `2.6.9` excludes `4.4.2`. At 2 AM, knowing why a service is safe saves you from waking a team you don't need.


Memory that lives in the graph

Every incident question writes an `(:Incident)` with one `EXPOSED {path}` edge per exposed service. The next question gets a fresh traversal, with the remembered incident shown next to it ("Seen before", plus what changed since).

The recall query is where storing memory in a graph started to feel like a superpower:

```
MATCH (i:Incident)-[:ABOUT]->(n)
WHERE (n:Maintainer AND n.npm = $entity_key)
   OR (n:Maintainer AND (n)-[:HAD_PUBLISH_RIGHTS]->(:Package)
         -[:HAS_VERSION]->(:Version {key: $entity_key}))
   OR (n:Maintainer AND (n)-[:HAD_PUBLISH_RIGHTS]->(:Package)
         -[:HAS_VERSION]->(:Version)<-[:AFFECTS]-(:Advisory {id: $entity_k
```


An incident filed about maintainer `qix` is recalled when someone later asks about `debug@4.4.2`, or about an advisory id, because memory is reached by traversal rather than string matching. In a new session, a bare `qix` is answered straight from memory, with the incident id and the patch on file.



A bare recall in a new session. Each recalled service still shows its full chain.

Two more kinds of memory sit on top of that:

- **Procedural.** "Generate fix" builds an install-safe `package.json` patch per service (verified with real `npm install`). When a human clicks **Approve**, it becomes a `(:Playbook)` that `COVERS {pin}` each package. Later incidents on the same packages find it by traversal, and every reuse bumps `uses_count`, so the Fixer prefers the playbook that has worked most often.
- **Conversational.** Every question is a `(:Turn)` linked `ABOUT` the nodes it resolved to. So "and at depth 6?" reruns the last question deeper, and "who should I wake for that?" knows what "that" is.



"who should I wake for that?" after "and at depth 6?". Eight teams, on-call first, highest tier first. "Seen before" flags one newly exposed service.

Because sessions live in FalkorDB, they survive restarts and every agent can see them.

Four agents, and the handoffs are edges


For Track 2, I wanted coordination you can actually inspect. The response crew is four deterministic specialists: **Triage** sizes the blast radius, **Investigator** explains paths and single points of failure, **Responder** decides who to page and drafts the messages, and

Fixer builds the patch plan. Investigator and Responder run concurrently, so the handoffs form a real DAG.

No agent passes anything to another in Python. Each one writes findings with `(:AgentRun)-[:PRODUCED]->(:Finding)`, and the next one reads them back by walking the handoff edges:

```
MATCH (src:AgentRun)-[:HANDED_OFF_TO*1..3]->(:AgentRun {id: $id})
WITH DISTINCT src
MATCH (src)-[:PRODUCED]->(f:Finding)
RETURN src.agent AS agent, f.kind AS kind, f.title AS title, f.data AS dat
ORDER BY f.seq
```


Since the whole run is nodes and edges, any run replays from the graph with a shareable `?run=` link.



A crew run done in 331 ms (replayed at reading speed). Each lane lists the upstream findings it read from FalkorDB. Page drafts are never sent.

The agent uses its own MCP server

PatientZero ships an MCP server you can plug into Claude Desktop or Cursor. The agent itself is a client of that same server, over the official SDK's in-memory transport. Each intent runs its own chain of `tools/call`s on one shared session. An exposure question runs five: `resolve_entity`, `recall`, `incident_scope`, `exposure`, `who_to_wake`.




Every answer is traced: each MCP call, then the named Cypher query it ran, with rows and milliseconds.

The deterministic router handles everything by default. With an OpenAI key, a model is consulted only when the router isn't confident, and even then it can only pick from the same tools. It never writes Cypher. Any name in its answer that isn't in the tool result gets the sentence rejected, and the templated answer is shown instead.

MCP isn't free. It costs about 1 ms of CPU per call, and locally that meant 77 req/s through the chain against 137 req/s with `MCP_AGENT=off` at 30 clients. I kept it on because routing through MCP is the point, and a parity test checks both paths give the same answers, field for field.


A live watch, and one graph per org

Every 10 minutes, PatientZero pulls new `MAL-*` npm advisories from OSV, writes them into every tenant's graph and runs the same traversal. Most polls end in "Not hit". A clearly labelled replay of the real `debug@4.4.2` advisory shows what a hit looks like: Acme 10 of 22, Globex 5 of 12.



The live watch. Real advisories with real publish dates; the replay is marked as a replay and never counted as a new alert.

Multi-tenancy came almost for free with FalkorDB's multi-graph support: Acme is `fleet:acme`, Globex is `fleet:globex`, same schema, separate memory. The Shai-Hulud worm (203 packages, 589 malicious versions) is the best demo of this. Acme is not hit. Globex has 4 of 12 services exposed. Nothing Acme approved is ever recalled in Globex.



Same question, different graph. Many worm packages have no clean version to pin to, and the answer says so.

The numbers, with their asterisks

I measured two different things, and I'm giving you both on purpose:

What	Result	Conditions
In-process database benchmark (live FalkorDB 4.22.1)	**740.6 ops/s**, p50 36 ms, p99 112 ms, 0 errors	30 clients for 20 s, no HTTP. 80% product reads, 20% **synthetic** writes into a scratch graph that's deleted afterwards, retry on busy
End to end over HTTP (live deploy)	**49.4 req/s**, p99 1.15 s, 0 errors	30 clients, read-only `/api/ask` and `/api/fleet`, one uvicorn process

The gap is the story: FalkorDB is not the bottleneck, my single Python process is. The benchmark also caught a real bug. The first live HTTP run returned four 500s, and all four were FalkorDB `Max pending queries exceeded` rejections (`MAX_QUEUED_QUERIES 25` on 2 threads). A rejected query never ran, so I added a retry with jittered backoff (safe even for writes) and raised the live queue to 200. The same 30-client run then finished with zero errors.

The bug that took my database down

During testing, one innocent query panicked the whole FalkorDB 6.0.1 server. The cause is FalkorDB#3150: a `RETURN` that mixes an aggregate with two or more grouping keys crashes when a non-first key is null. `who_to_wake` hit it through `Team` nodes without a Slack channel.

The fix is to aggregate in `WITH` and only project in `RETURN`:

```
// crashes 6.0.1:  MATCH (n:N) RETURN n.name AS x, n.missing AS a, count(r
MATCH (t:Team)-[:OWNS]->(s:Service) WHERE s.name IN $services
OPTIONAL MATCH (oc:Person)-[:ONCALL_FOR]->(t)
WITH s, t, collect(DISTINCT {name: oc.name, handle: oc.handle}) AS oncall
RETURN s.name AS service, t.name AS team,
       coalesce(t.slack, '#team-' + t.name) AS slack, oncall
```

I rewrote seven queries this way, gave Team fields defaults at load time, and added a test that parses every `.cypher` file and fails the build if that shape comes back. The backend suite, **256 tests**, passes on both FalkorDB 6.0.1 and 4.22.1, the version the live deploy runs.

What I learned

1. **Put the meaning on the edges.** Keeping the declared range on every `REQUIRES` edge is what made honest negatives possible. Without it, every reachable service looks exposed.
2. **Memory you can traverse beats memory you can search.** Recall through `HAD_PUBLISH_RIGHTS` connects a question about `debug@4.4.2` to an incident filed under `qix`, with no embeddings and no guessing.
3. **Deterministic first, LLM optional.** The router is the default, the fallback and the test oracle. The product works fully with no model at all, which made it testable.
4. **Async isn't magic.** My crew issued graph writes on the event loop, and under a stress test one `/health` probe took 22.7 seconds. Moving every crew graph call to a bounded thread pool and capping concurrent runs fixed it.
5. **Publish two numbers.** An in-process benchmark and an HTTP benchmark answer different questions. Labelling them honestly cost me a bigger headline and earned me

a bug fix.

The tradeoffs are real too. The Acme and Globex fleets are synthetic (the npm data is real), semver runs in the app rather than in the database, and bring-your-own-repo scans check the qix incident only.

Try it

Open the live app and type `qix`, `debug@4.4.2`, `who to wake for auth-service` or `path from img-service to simple-swizzle`. Then scroll to **Would you have been hit on Sept 8, 2025?** and paste a public repo. `github.com/axios/axios` comes back exposed through `https-proxy-agent` and `debug@4.4.2`.

The code, the 20 query files and the verification docs are at github.com/AtharvRaotole/FalkorDB. If you scan your own repo and something lights up red, I'd love to hear about it.

Built for Graph Hacks: Context for AI Agents by WeMakeDevs and FalkorDB, entered in Track 1 (Agents That Act on Connected Data) and Track 2 (Agent Memory and Coordination). Disclosure: I wrote PatientZero with Cursor as my AI coding assistant, using AI agents for research, code, tests and review. I chose the problem and the design, reviewed every build, and every Cypher query is parameterised and checked by the test suite.

#falkordb #graphdb #ai #hackathon