

FEATURE SELECTION



Outline

- Motivation behind the use of Feature Selection
- Theory-based approach
- Filter Methods
- Subset selection
- Shrinkage methods
- Dimension Reduction

Motivation for Feature Selection

- Parsimony is a desirable property for models
 - *Predictions from simple (versus complex models) are more stable across samples*
 - *Simple models are easier to interpret and communicate to stakeholders.*
- As number of predictors increases, the chance of finding correlations among a predictor or a set of predictors increases. Such correlations among predictors called *multicollinearity* inflates standard errors of coefficients, potentially leading to erroneous conclusions about the relevance of a predictor.
- In cases where $p > n$, traditional estimation techniques will not work.

Methods for Feature Selection

1. Theory
2. Filter Methods
3. Subset Selection
4. Shrinkage
5. Dimension reduction
6. Iterative Methods

Methods for Feature Selection

1. Theory: Use published literature or domain knowledge to pick variables.
2. Filter Methods: Keep predictors that are relevant but not redundant.
3. Subset Selection: Identify a subset of p predictors that are related to the outcome. Fit a model with this subset.
4. Shrinkage: Fit a model with all p predictors, but the estimated coefficients are shrunk towards zero relative to least squares estimates. This shrinkage (also known as regularization) has the effect of reducing variance and can also perform variable selection.
5. Dimension reduction: Group predictors into a reduced number of components based on similarity. Use the components as predictors.

PS: Above methods do not apply to predictive models (e.g., trees) which automatically pick features. Such models couple the predictor search algorithm with parameter estimation and are therefore thought to have built-in feature selection.

THEORY

Theory

- Begin with an understanding of the problem and of the features that would be expected to influence the outcome.
- Consider a team at Stanford engaged in designing a program to tell differences between pictures of healthy skin and pictures of skin cancer. The system developed was incredibly accurate in spotting skin cancer.
 - *Fortunately, researchers realized a serious flaw. Many of the tumors in the training data were photographed next to rulers for scale. They had trained a ruler detector ([Daily Beast](#))*

Theory:

Choice of Outcome

- The business problem (rather than algorithm) usually informs the choice of outcome. An incorrect choice can result in adverse consequences as illustrated below.
- A popular packaged good company purchased products from China to sell in the US. Products were selected based on a model that predicted sales in the US. Sales took off, until several months later, customers started returning products (HBR, 2016). Maybe the company should have selected products based on predicted customer satisfaction!
- Most SEO campaigns are designed to maximize website visits. But what good is a website visit if it does not result in a sale (HBR, 2016).
- For YouTube, it is reasonable to set a goal of maximizing user viewing time. After all, people will only watch things they are happy with. Much to Alphabet's disappointment, happiness was not the only reason people would spend more time watching a video. Often, it was because people were appalled or outraged. YouTube's algorithm was increasingly suggesting disturbing videos, conspiracy theories and bigotry. As it turns out these topics were sticky even though they didn't leave the viewers happy. This led Alphabet to rethink their algorithm. ([Google Blog](#), 2019)

Theory

Choice of Predictors

- Review published literature to determine which variables to include in the model
- Consult experts with extensive domain knowledge
- This theory-based variable selection must be done before examining the data
- Theory should always be the first line of attack for feature selection. It is unfortunate that with the availability of large datasets and powerful analytical techniques, this method is often overlooked.


FILTER METHODS

Filter Methods

- Predictors included in a model must be
- Relevant
 - *Related to the outcome variable*
- Non-redundant
 - *Not related to other predictors*

Bivariate Filter

- Examine bivariate correlation to assess relationship between pairs of variables
- Relevant
 - *High bivariate correlation between a predictor and outcome*
- Non-redundant
 - *Low bivariate correlation between a predictor and other predictors*
- In the correlation heatmap, quality is outcome and the rest are predictors.



Multivariate Filter

- Examine relevance and redundancy of all predictors together. Often, what is true in pairwise relationships may not be found when all variables are considered together.
- Relevance
 - *Significant regression coefficients for predictor in a multiple regression*
 - *However, note that this is not a sufficient condition as large sample sizes will render all coefficients statistically significant*
- Non-redundant
 - *Threat of collinearity can also come from linear relationships between sets of variables, known as multicollinearity.*
 - *Multicollinearity is measured by Variance Inflating Factor or Tolerance. $1 < VIF < \infty$*
 - $VIF > 10$: Serious multicollinearity; $VIF > 5$: Moderate-High multicollinearity.

SUBSET SELECTION

Subset Selection

1. Best subset selection
2. Forward
3. Backward
4. Stepwise

Best Subset Selection

1. Consider all possible subsets of p predictors.
2. Fit a model with each subset.
3. Pick the best performing model

Best Subset Selection: Problems

- As p increases, the computational requirements grow exponentially. For p predictors number of models estimated is given by
 - ${}^pC_1 + {}^pC_2 + {}^pC_3 + {}^pC_4 \dots {}^pC_p = 2^p$
- Larger the value of p , higher the chance of finding models that perform well on training data, even though they might not have any predictive power on future data. In other words, large p may result in overfitting and high variance of coefficient estimates.

Forward Selection

1. Forward selection method begins with a model containing no predictors and then adds predictors to the model, one at a time
2. Variables are added in order of the marginal improvement to the model. At each stage, the variable that gives the largest marginal improvement is added.
3. Addition of variables stops when marginal improvement is not significant

Forward Selection

- Compared to Best Subsets method, this method is computationally efficient. For p predictors, number of models estimated is: $1 + p(p+1)/2$
- The intuition behind forward selection method is illustrated using a model with eight predictors. In the following slides, marginal improvement is indicated by a green-red scale where green is significant marginal improvement and red is a non-significant improvement.

Y	X_1	X_2	X_3	X_4	X_5	X_6	X_7	X_8	Adj R^2
---	-------	-------	-------	-------	-------	-------	-------	-------	-----------

Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	Adj R ²
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	

Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	Adj R ²
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.3

Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	Adj R ²
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.3
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	

Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	Adj R ²
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.3
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.4

Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	Adj R ²
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.3
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.4
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	

Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	Adj R ²
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.3
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.4
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.45

Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	Adj R ²
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.3
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.4
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.45
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	

Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	Adj R ²
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.3
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.4
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.45
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	
Y	X ₁	X ₂	X ₃	X ₄	X ₅	X ₆	X ₇	X ₈	0.45

Backward Selection

1. Backward selection method begins with a model containing all predictors and then removes predictors from the model, one at a time
2. Variables are removed iteratively with the least useful predictor being dropped first.
3. Removal of variables stops when elimination of a predictor significantly worsens the model.

Backward Selection

- Backward selection is just forward selection in reverse. Like Forward selection, For p predictors, number of models estimated is: $1 + p(p+1)/2$
- However, one limitation of backward selection is that it cannot be used for models where $p > n$. On the other hand, forward selection can handle such high-dimensional models.

Stepwise

- Forward and Backward methods are run simultaneously
- Predictors may be added or removed at each stage until the optimal model is reached
- Stepwise method attempts to more closely mimic benefits of best subsets while retaining the computational advantages of forward and backward selection methods.

SHRINKAGE

Shrinkage Methods


- Shrinkage methods constrain or regularize coefficient estimates, or equivalently, shrink the coefficient estimates towards zero. They do so by adding a shrinkage penalty to punish a model for complexity.
- While OLS minimizes the residual sum of squares (sse) to estimate coefficients, shrinkage methods minimize the sum of squared errors (SSE), also known as residual sum of squares and a shrinkage penalty.
 - *OLS: $\min(\text{SSE})$*
 - *Shrinkage methods: $\min(\text{SSE} + \lambda * \text{shrinkage penalty})$*

Shrinkage Methods

- Based on the shrinkage penalty used, there are two shrinkage methods
 - *Ridge Regression (Shrinkage penalty is $\lambda \sum \beta_j^2$): Shrinking coefficient estimates can significantly reduce their variance and lead to better fit. However, ridge regression will include all predictors in the model.*
 - *Lasso (Shrinkage penalty is $\lambda \sum |\beta_j|$): With a small modification to the shrinkage penalty from ridge regression, Lasso is able to force some of the coefficients to equal zero.*
 - *The shrinkage penalty in Ridge regression suppresses all coefficients, on the other hand, the penalty in Lasso has the effect of forcing some, not all, coefficient estimates to be exactly zero. By forcing only some coefficient estimate to zero, Lasso in essence performs feature selection.*


Lasso

- The extent of shrinkage penalty depends on the value of the tuning parameter, λ (or α).
- When λ (or α) = 0, the penalty has no effect and Lasso will produce least square estimates.
- As λ (or α) gets larger, the penalty grows and coefficient estimates are forced to zero.
- The optimal value of λ (or α) is typically determined by examining cross-validation error of a set of λ (or α) using k-fold cross-validation.



Advantages of Lasso

- Performs better than stepwise selection
- Performs variable selection to any number of variables
- Can create models where $p > n$
- Statistically well founded
- Relatively fast



DIMENSION REDUCTION

Dimension Reduction

- p predictors are reduced to a smaller number of components based on a measure of similarity (e.g., correlation).
- One technique that does this is Principal Components Analysis (PCA)

Principal Components Regression (PCR)

- PCA generates linear combinations of original p predictors
- A matrix with p variables will generate p components such that the first component captures the most variance, followed by the second, and so on.
- Generally, the number of components to be retained is based on eigen-value of extracted components, a scree plot, and capturing a certain amount of variance (e.g., 70%).
- The reduced number of components are used to predict the outcome instead of the original set of predictors.

Summary

- We discussed the Motivation behind the use of Feature Selection, and examined six ways of carrying out feature selection
 1. *Theory-based approaches*
 2. *Manual approach*
 3. *Subset selection*
 4. *Shrinkage methods*
 5. *Dimensionality Reduction*