Fuzzy Systems and Soft Computing
ISSN : 1819-4362

SENTIMENT ANALYSIS: A COMPREHENSIVE REVIEW OF TECHNIQUES, APPLICATIONS AND CHALLENGES

P.Saravanan, Research Scholar, PG and Research Department of Computer Science,Government Arts College, Nandanam, Chennai-35, India
Dr.M.Sundara Rajan, Associate Professor, PG and Research Department of Computer Science,Government Arts College, Nandanam, Chennai-35, India
Vadivelan K, Research Scholar, PG and Research Department of Computer Science,Government Arts College, Nandanam, Chennai-35, India

ABSTRACT
The rapid expansion of Internet-based applications, such as social media platforms and blogs, has led to an overwhelming volume of user-generated content in the form of comments and reviews. Sentiment analysis is gathering and analyzing people's opinions, thoughts, and impressions on various topics, products, subjects, and services. These insights can be valuable for corporations, governments, and individuals to inform decision-making and strategy. However, sentiment analysis faces numerous challenges that hinder accurate interpretation and sentiment polarity classification. This study provides a comprehensive overview of sentiment analysis, exploring the methodologies involved, including natural language processing and text mining. Additionally, it evaluates and compares different approaches, highlighting their advantages and limitations. Finally, the challenges of sentiment analysis are discussed to outline potential future research directions.
Keywords—Sentiment analysis , Text analysis , Word embedding , Machine learning and Social media.

INTRODUCTION:
Sentiment analysis has gained significant attention in recent years among researchers, businesses, and governments. The rapid growth of the internet has made online platforms a primary source of public opinion, with users expressing their views through social media, blogs, and reviews. Automated sentiment analysis is essential to monitor public sentiment and support decision-making.
Also known as opinion mining, sentiment analysis has seen continuous growth in research and applications. Early studies, such as those by Ligthart et al. (2021) and Piryani et al. (2017), provided frameworks for processing unstructured data. Several recent surveys (Yousif et al. 2019; Birjali et al. 2021) have explored sentiment analysis challenges and future directions. Researchers have also investigated opinion spam detection (Soleymani et al. 2017; Yadav & Vishwakarma 2020) and the effectiveness of online reviews (Yue et al. 2019; Liu et al. 2012).
Sentiment analysis plays a vital role in various applications, such as product reviews, stock market predictions, and healthcare analysis. For instance, studies (Subhashini et al. 2021; Mowlaei et al. 2020) have focused on extracting meaningful insights from noisy data using machine learning and lexicon-based methods. Sentiment analysis has been widely applied in industries ranging from hospitality to finance and healthcare (Zvarevashe & Olugbara 2018; Valencia et al. 2019; Ahmad et al. 2019a).
Despite its advancements, sentiment analysis faces challenges like informal writing styles, sarcasm, and language-specific complexities. The interpretation of words varies by context, and limited tools exist for certain languages. Detecting sarcasm and irony remains a major challenge in sentiment analysis (Mayur Wankhade1, Annavarapu Chandra Sekhara Rao &•Chaitanya Kulkarni1 et al 2022).
This study explores sentiment analysis methodologies, applications, and challenges, providing comparisons through tables, flowcharts, and graphs. Unlike existing surveys that focus on specific aspects, this work presents a comprehensive view, covering all key techniques, including machine learning, lexicon-based, and hybrid approaches. Various descriptions of abbreviation which use in our work shown in Table 1.

Key Contributions:

- A thorough review of sentiment analysis techniques and technologies.
- Comparative analysis of different methods to identify the most suitable approach.
- Categorization of commonly used sentiment analysis techniques.
- Discussion of benefits and challenges in sentiment analysis research.
- Comparison of methods, highlighting their advantages and limitations.



Fig. 1 Level of sentiment analysis

Paper Organization are Section 2: Levels of Sentiment Analysis, Section 3: Data Collection, Feature Extraction, and Selection, Section 4: General Methodology and Summary, Section 5: Applications in Various Domains, Section 6: Challenges in Sentiment Analysis and Section 7: Conclusion.

SENTIMENT ANALYSIS LEVELS :

Sentiment analysis is conducted at multiple levels, including Document Level, Sentence Level, Phrase Level, and Aspect Level. Each level focuses on analyzing sentiments with varying granularity. Figure 1 illustrates sentiment analysis across these levels.

Phrase-Level Sentiment Analysis:

Phrase-level sentiment analysis focuses on identifying opinion words within phrases and classifying their sentiment. Each phrase may express a single or multiple aspects, making it useful for analyzing detailed product reviews (Thet et al. 2010). While document-level analysis categorizes an entire document as positive or negative, sentence-level analysis offers more granularity since a document may contain both sentiments.

Words play a crucial role in sentiment classification, as their polarity is closely tied to the sentence or document context. Sentences containing adjectives are more likely to be subjective (Fredriksen-Goldsen & Kim 2017). Additionally, word choice can reflect demographic traits such as gender, age, social status, and personality, making it a foundation for sentiment analysis (Flek 2020).

Aspect-Level Sentiment Analysis:

Aspect-level sentiment analysis examines individual aspects within a sentence, assigning sentiment polarity to each one. Since a sentence can contain multiple aspects, the overall sentiment is determined by aggregating the sentiment scores of all aspects (Schouten & Frasincar 2015; Lu et al. 2011).

TABLE I

VARIOUS DESCRIPTION OF ABBREVIATION

Abbreviation	Description of abbreviation
NLP	Natural Language Processing
NB	Naïve Bayes
SVM	Support Vector Machine
RF	Random Forest
LR	Logistic Regression
DT	Decision Tree
LSTM	Long Short-Term Memory
Bi-LSTM	Bi-directional Long Short-Term Memory

CNN	Convolutional Neural Network
RNTN	Recursive Neural Tensor Network
RNN	Recurrent Neural Network
ANN	Artificial Neural Network
RNTN	Recursive Neural Tensor Network
AI	Artificial Intelligence
KNN	K nearest Neighbours
LDA	Latent Dirichlet allocation
ME	Maximum Entropy
LSA	Latent Semantic Analysis
CBOW	Continuous Bag of words
SG	Skip Gram
TF-IDF	Term Frequency-Inverse Document Frequency
DNN	Deep Neural Network
BoW	Bag of Words
ABSA	Aspect Based Sentiment Analysis
PoS	Parts-of-Speech
NLTK	Natural Language tool kit
DCNN	Dynamic Convolutional Neural Network
BERT	Bidirectional Encoder Representations from Transformers
MSA	Multimodal Sentiment Analysis
GPT	Generative Pre-trained Transformer
SLC	Sentence Level Classification
AR-NN	Auto-regressive Neural Network
DMN	Dynamic Memory Networks
ELMo	Embedding Language Models

DATA COLLECTION AND FEATURE SELECTION:

Data Collection:

Data for sentiment analysis can be gathered from various online sources, including social media, news channels, e-commerce websites, forums, and blogs (Fig. 2). This is the first step in sentiment analysis. Depending on the task, text data can be combined with other formats like video, audio, and location data. Key sources include:

Social Media: Platforms where users interact, share opinions, and generate real-time data, making it a valuable source for sentiment analysis.

Forums: Online message boards where users discuss topics, exchange opinions, and seek assistance, offering domain-specific sentiment insights (Korkontzelos et al. 2016).

Blogs: Weblogs containing personal viewpoints, facts, or research-style articles, serving as a rich source for sentiment analysis (Kumar & Teeja 2012; Annett & Kondrak 2008).

E-Commerce Websites: Platforms where users post product reviews and feedback, offering insights into customer satisfaction and preferences (Jain et al. 2019).These diverse data sources help in extracting meaningful insights for sentiment analysis across various domains. (Mayur Wankhade1,Annavarapu Chandra Sekhara Rao &•Chaitanya Kulkarni1 et al 2022)



Fig. 2 General procedure of sentiment analysis

FEATURE SELECTION:

Feature selection is essential for building a sentiment classification model (Ritter et al. 2012). Reviews are broken down into words and added to a feature vector during model training.

N-grams:

Unigram: Uses single words.

Bigram: Uses two-word combinations.

Trigram: Uses three-word combinations.

A mix of unigram and bigram improves accuracy (Razon & Barnden 2015).

Pragmatic Features: Focus on word usage and context in language, including implicature, speech acts, and conversation relevance.

Emojis & Emoticons: Represent emotions such as happiness, sadness, and anger, aiding sentiment classification (Tian et al. 2017).

Positive Emoticons: Express love, joy, and happiness.

Negative Emoticons: Indicate sadness, depression, or frustration.

Punctuation Marks:

Exclamation Marks (!): Emphasize sentiment intensity.

Question Marks (?): Indicate inquiry or sarcasm.

Apostrophes ('): Affect word meaning and sentiment.

Slang Words: Terms like "LOL" and "ROFL" add humor and can indicate sentiment. Their meanings are substituted for analysis. These features enhance the accuracy of sentiment analysis by capturing text nuances.

FEATURE EXTRACTION:

Feature extraction plays a crucial role in sentiment classification by identifying key information from text data, directly affecting model performance. Since extracting features from text can be challenging, various techniques are used to enhance accuracy (Venugopalan & Gupta, 2015).

Term Frequency (TF) & TF-IDF:

Measures how often a term appears in a document.

Can use unigram (single word), bigram (two words), or trigram (three words).

TF-IDF (Term Frequency-Inverse Document Frequency) improves accuracy by weighting important words (Sharma et al., 2013).

Parts of Speech (PoS) Tagging:

Assign grammatical tags to words (e.g., noun, verb, adjective). Adjectives are crucial for sentiment analysis (Straka et al., 2016). Commonly used tools: Stanford PoS-tagger, NLTK, Spacy (Weerasooriya et al., 2016).

Negations:

Words like not, never, neither can reverse sentiment.

For example, "This movie is good." (positive) vs. "This movie is not good." (negative). Some systems mistakenly remove negations as stop words, reducing accuracy (George et al., 2013).

Neutral Sentiment Handling:

Neutral opinions are often ignored, but distinguishing them can improve performance (Valdivia et al., 2018).
Multi-level sentiment detection refines sentiment analysis by identifying ambivalence and emotion intensity (Wang et al., 2020).
Bag of Words (BoW):
Represents text as word frequency vectors without considering context.
Example:
Sentence 1: "The food was good."
Sentence 2: "The service was bad."
Vocabulary = {'the', 'food', 'was', 'service', 'bad', 'good'}
Vector representations:
S1: [1, 1, 1, 0, 0, 1]
S2: [1, 0, 1, 1, 1, 0]
TF-IDF improves BoW by reducing the weight of common words. These techniques help refine sentiment analysis by capturing text patterns, context, and polarity shifts.

FEATURE SELECTION APPROACH:
Feature selection helps identify relevant data characteristics while removing unnecessary or redundant features, improving sentiment classification accuracy (Ahmad et al., 2019; Lata et al., 2020). Two main approaches are used: lexicon-based and statistical methods.
Lexicon-Based Methods:
Uses predefined sentiment dictionaries like SentiWordNet, where words are assigned positive and negative sentiment scores.
Humans manually create feature sets, expanding them with synonyms or web resources (Kolchyna et al., 2015). Effective but time-consuming.
Statistical Methods:
Fully automated but may struggle to differentiate sentimental and non-sentimental features (Poria et al., 2014).
Example: SenticNet, which integrates logical reasoning into deep learning models (Cambria et al., 2020).
Types of Feature Selection Methods
Filter Approach:
Selects features based on data properties, independent of machine learning models.
Uses statistical metrics like Information Gain, Chi-square, Document Frequency, and Mutual Information (Adomavicius & Kwon, 2011). Fast and works well with high-dimensional data.
Wrapper Approach:
Uses machine learning models to evaluate feature subsets.
Computationally expensive but provides optimized feature sets. Techniques include forward or backward selection and algorithms like Naïve Bayes (NB) and Support Vector Machines (SVM).
Embedded Approach:
Integrates feature selection within the model training process. More efficient than the wrapper method but model-dependent (Das et al., 2020).
Common algorithms: Decision Trees (CART, C4.5, ID3) and LASSO (Kosamkar & Chaudhari, 2013).
Hybrid Approach:
Combines filter and wrapper methods for better performance.Uses multiple techniques to find the best feature subset.Achieves higher accuracy (Chiew et al., 2019). By selecting the right feature selection approach, sentiment analysis models become more accurate and efficient.

TASKS IN SENTIMENT ANALYSIS:
Sentiment analysis involves various tasks to understand emotions and opinions in text data. Fig. 3



Fig. 3 Task of sentiment analysis

SUBJECTIVITY CLASSIFICATION:
Identifies whether a text is subjective (opinion-based) or objective (factual).
Detects words like amazing, cheap, and hard to filter subjective content (Kasmuri & Basiron, 2017).Helps remove non-opinionated data before further analysis (Kamal, 2013).
SENTIMENT CLASSIFICATION:
Determines the polarity of text: positive, negative, or neutral (Wang et al., 2014).
Opinion-Level Context: Analyzes intra-opinion and inter-opinion relationships (Xia et al., 2015).
Cross-Domain Analysis: Predicts sentiment in a different domain by extracting universal features (Peng et al., 2018).
Cross-Language Analysis: Uses a model trained in one language to classify sentiment in another (Vechtomova, 2017).
Application: Used in customer reviews, recommendation systems, and feedback analysis (Cambria et al., 2017).
OPINION SPAM DETECTION:
Identifies fake reviews or biased opinions on online platforms. Uses text content, metadata (IP, location), and real-world product trends (Crawford et al., 2015).
Example: A product with mostly negative reviews suddenly gets high ratings—this may indicate spam activity.
IMPLICIT LANGUAGE DETECTION:
Detects sarcasm, irony, and humor, which can change a sentence's meaning.Example: "Brilliant, I just got fired." – Brilliant is usually positive but signals sarcasm here.
Methods: Uses emojis, punctuation patterns, and laughter markers (Fang et al., 2020).
ASPECT-BASED SENTIMENT ANALYSIS (ABSA):
Extracts specific aspects of a product or service and determines their sentiment.
Steps: Aspect extraction → Sentiment classification → Aggregation.
Methods:
Frequency-based: Identifies commonly mentioned aspects in reviews (Kanapala et al., 2019).
Syntax-based: Uses sentence structure to find aspects (e.g., "Awesome food" → food is the aspect) (Bai et al., 2020).
Each of these tasks plays a crucial role in improving sentiment analysis accuracy and effectiveness.

METHODOLOGY:
There are three main approaches used for Sentiment Analysis: Lexicon-Based Approach, Machine Learning Approach, and Hybrid Approach. Researchers are continuously working on improving these methods for better accuracy and lower computational costs(Mayur Wankhade1,Annavarapu Chandra Sekhara Rao &•Chaitanya Kulkarni1 et al 2022). Overview various methods used in Sentiment Analysis as shown in Fig. 4.
Lexicon-Based Approach:

Uses pre-built sentiment lexicons (e.g., SentiWordNet) to assign sentiment scores to words.
Pros: Simple and interpretable.
Cons: Limited by the lexicons' vocabulary and may struggle with sarcasm, negations, and context.
Machine Learning Approach:
Relies on labeled data to train models like Naive Bayes, Support Vector Machines (SVM), or Deep Learning models.
Pros: Capable of handling more complex tasks and context.
Cons: Requires large labeled datasets and higher computational power.
Hybrid Approach:
Combines both lexicon-based and machine-learning methods to capitalize on the strengths of each.
Pros: More robust and adaptable, especially for complex scenarios.
Cons: May require more computation and tuning.
Workflow Of Sentiment Analysis:
The general workflow for sentiment analysis includes the following steps:

DATA COLLECTION:
Collect data from various sources (social media, e-commerce sites, forums, etc.) for analysis.
Feature Selection
Choose important features from the text (e.g., terms, emojis, parts of speech) to help improve sentiment classification.
Sentiment Analysis Task:
Perform tasks such as subjectivity classification, sentiment classification, and aspect extraction to interpret the sentiment and its context.
These methods and workflows help analyze and understand the emotions expressed in text data efficiently.



Fig. 4 Approach of sentiment analysis

CORPUS-BASED APPROACH:
This method uses semantic and syntactic patterns to determine the emotional tone of sentences. It starts with a predefined list of sentiment terms and their polarity, then looks for patterns in a large corpus of text to identify sentiment-bearing words and their orientation. This approach requires a significant amount of labeled data for training and helps in resolving cases where sentiment words' meanings depend on context. For example, Park and Kim (2016) used this method by analyzing linguistic constraints and connectives (like "AND" and "OR") to identify sentiment in new tokens. Sentiment consistency suggests that words connected by "AND" tend to have the same sentiment, while those connected by "OR" might indicate a change in sentiment. However, this consistency is not always reliable in practice. They used a graph-based model to analyze and cluster words based on sentiment orientation (positive or negative).
Types of Corpus-Based Approaches:

STATISTICAL APPROACH:
This method identifies opinion words or co-occurrence patterns using statistical analysis. The basic idea is that words that frequently appear in similar contexts are likely to share the same sentiment orientation. For example, Turney and Littman (2003) used mutual information to determine the frequency of word co-occurrence, which helped predict the sentiment of new words based on context.
Semantic Approach
This method focuses on understanding the meaning of words and their relationships, often using thesauri or semantic networks like WordNet to expand the initial set of opinion words.

DICTIONARY-BASED METHOD:
The Dictionary-Based Approach uses a predefined set of opinion words collected manually or automatically. These words are expanded by including synonyms and antonyms to enhance the lexicon.
Synonyms are assumed to have the same polarity, while antonyms have the opposite polarity.
Large resources like WordNet or thesauruses are used to find these relationships.
Steps in this process:
Manual collection of sentiment words and their orientations.
Expansion of the list using synonyms and antonyms.
Iterative refinement of the list and manual correction to ensure quality. An example is SentiWordNet, which was created by automatically annotating WordNet's synsets. However, the domain-specificity of opinion words remains a challenge since word meanings may vary by domain.
Additional Tools and Resources:
LingPipe: A tool for various tasks including sentiment analysis, topic identification, and word segmentation.Apache OpenNLP: Provides tools for tasks like tokenization, part-of-speech tagging, and named entity extraction.Lexicon Sentiment Dictionary: Used in areas like politics to determine sentiment in text. These methods help identify and classify sentiment, but each has its strengths and limitations.

MACHINE LEARNING APPROACH:
Machine Learning (ML) is widely used for Sentiment Analysis, where algorithms classify sentiments in text or audio using techniques like Natural Language Processing and computational linguistics. Sentiment analysis can be approached using two primary methods:
Supervised Machine Learning
Lexicon-Based Unsupervised Learning
While both methods work well, Supervised Learning tends to give more accurate results. ML algorithms analyze syntactic and linguistic features to classify text as positive, negative, or neutral. These models require a training dataset to learn and then predict sentiment in unseen data.
Common Machine Learning Algorithms for Sentiment Analysis:

NAIVE BAYES (NB):
NB is a probabilistic classifier based on Bayes' Theorem, which calculates the likelihood of a sentiment based on input features.NB works well with smaller training datasets but may struggle with imbalanced datasets. It's commonly used for binary classification tasks, like identifying positive vs. negative sentiment.Example: Kang et al. (2012) improved NB's accuracy for restaurant reviews by addressing its imbalance problem.

SUPPORT VECTOR MACHINE (SVM):
SVM uses hyperplanes to separate data into distinct classes, making it effective for sentiment classification. It performs well with high-dimensional data and can handle both binary and multi-class

sentiment classification. Example: Borg and Boldt (2020) used Linear SVM to predict customer review sentiment with an F1 score of 83.4%.

LOGISTIC REGRESSION (LR):
LR is a classification technique that predicts probabilities for binary sentiment outcomes (e.g., positive or negative). It works by evaluating input features and determining the most relevant for classification. Example: Hamdan et al. (2015) used LR for binary sentiment classification with good results.
Decision Tree (DT):
DT splits data recursively based on conditions, creating a tree-like structure to classify sentiment. It's prone to overfitting, but Random Forest (RF) can help by combining multiple decision trees to improve accuracy. Example: Yan-Yan et al. (2010) used DT to classify camera reviews, comparing results with SVM and NB.
Maximum Entropy (ME):
ME classifiers use conditional probabilities to predict sentiment. They are useful for multi-class classification and feature selection. Example: Kaufmann (2012) applied ME to detect parallel sentences across languages.
K-Nearest Neighbors (KNN):
KNN classifies sentiment based on the similarity of new data points to nearby abelled instances. While not as popular, it can give good results with careful training and tuning of the K value.
Semi-Supervised Learning:
Involves a mix of labeled and unlabeled data for training. It's useful when labeling is expensive or labor-intensive. Example: Janjua et al. (2021) applied semi-supervised learning to improve sentiment classification of large unlabelled datasets.

HYBRID APPROACH:
The Hybrid Approach combines Machine Learning and Lexicon-Based methods to enhance sentiment analysis. This approach benefits from the strengths of both techniques and is gaining popularity for its higher accuracy. Example: Hassonah et al. (2020) combined SVM with feature selection techniques, achieving 84% accuracy on Amazon product reviews. Hybrid models can outperform individual models if designed with the right architecture and hyper parameters.
Summary of Sentiment Analysis Techniques
Approach- Machine Learning, Hybrid Approach
Advantages- High accuracy, Combines strengths of both methods
Disadvantages- Adaptable requires large training data, complex, Requires careful architecture and tuning
This hybrid model is a growing area of research, offering many opportunities to improve sentiment analysis results with the right combination of techniques.

NEURAL NETWORK:
Neural networks (NN) have been explored alongside other techniques like Support Vector Machines (SVM) for sentiment analysis. Researchers like Van de Camp and Van den Bosch (2012) found that combining SVM with a simple neural network improved results when analyzing biographical texts. In contrast, Moraes et al. (2013a) compared SVM and Artificial Neural Networks (ANN), highlighting that SVM was more commonly used due to its accuracy. However, ANN showed potential for better performance, especially when using product reviews. Both models have disadvantages, including the high computational cost of training and running them.
Traditional Recurrent Neural Networks (RNN) remember information from previous steps, which makes them useful for sequential data. However, they suffer from issues like the vanishing gradient problem, which limits their ability to capture long-term relationships. To address this, newer

architectures like Bi-LSTM (Bidirectional Long Short-Term Memory) and GRU (Gated Recurrent Units) process data in both directions (forward and backward) to improve accuracy.
Deep learning techniques, like LSTM, GRU, and attention models, have proven to be effective for sentiment analysis, especially when trained on large datasets. Models like BERT (Bidirectional Encoder Representations from Transformers) and GPT (Generative Pre-trained Transformer) are gaining attention for their ability to perform sentiment analysis effectively, as they are pre-trained on vast datasets and fine-tuned for specific tasks.
In recent advancements, transformer models have revolutionized natural language processing (NLP) tasks. These models rely on attention mechanisms that allow the model to focus on important parts of the input data, enabling better handling of long-term dependencies and improving performance across various NLP applications, including sentiment analysis.

OTHER APPROACHES:

Aspect-Based Sentiment Analysis (ABSA):

Aspect-based sentiment analysis (ABSA) is a growing field that focuses on identifying specific aspects or features mentioned in reviews and determining the sentiment associated with each aspect. ABSA consists of three main steps:
Aspect Detection: Identifying the aspects mentioned in a sentence.
Sentiment Categorization: Classifying the sentiment of each aspect (positive, negative, or neutral).
Aggregation: Combining sentiment scores for each aspect to determine the overall sentiment.
This approach is commonly used in product or hotel reviews to help consumers and producers understand which aspects of a product or service are being highlighted. For example, in a hotel review like "The food was awesome, but the service was slow," the aspects are "food" (positive sentiment) and "service" (negative sentiment), which can be aggregated to provide an overall sentiment.

TRANSFER LEARNING:

Transfer learning is an AI technique where a pre-trained model is used to transfer knowledge to a new model. This is useful when applying a model trained in one domain to a different but similar domain. Transfer learning reduces the need for large amounts of new training data, saving time and resources. It involves fine-tuning a pre-trained model to suit a new task, allowing it to leverage previously learned features. This method has been effective in sentiment analysis, enabling models to classify sentiments across different fields with greater accuracy and efficiency. For example, a model trained on one type of data can be adapted to another domain using transfer learning techniques like CNN-based approaches.

MULTIMODAL SENTIMENT ANALYSIS (MSA):

Multimodal Sentiment Analysis (MSA) goes beyond traditional text-based sentiment analysis by incorporating additional data sources such as audio and visual information. MSA uses multiple modalities—like text, voice, and facial expressions—to better understand sentiment in social multimedia platforms such as YouTube, video blogs, or spoken reviews.
In MSA, text, audio, and visual elements are often analyzed separately before combining the results in a post-processing step. MSA can be bimodal (using two modalities, such as text and audio) or trimodal (using three modalities, like text, audio, and visual data). The goal is to create more accurate sentiment analysis systems by fusing these different types of data.
Research in MSA has focused on improving how these different data sources are combined, with techniques like attention-based models and tensor-based fusion. Some methods use a hierarchical feature fusion approach, where two modalities are combined first, and then all three modalities are integrated. MSA is becoming an important area of research, especially for analyzing spoken language, which combines text, audio, and visual cues.

APPLICATIONS OF SENTIMENT ANALYSIS:

Sentiment analysis has a wide range of applications across different fields. Some of the key areas where sentiment analysis is commonly used are outlined below:

Business Analysis:

Sentiment analysis helps businesses understand customer feedback, improve products, and create effective marketing strategies. It is often used to analyze customer impressions of products or services and can guide businesses to make improvements based on customer opinions. Customers can also use sentiment analysis to compare products and make informed decisions.

Product Reviews:

With the rise of e-commerce, sentiment analysis is used to evaluate customer reviews of products. This helps customers make better purchasing decisions and gives businesses insights into customer reactions after a product launch.

Market Research and Competitor Analysis:

Sentiment analysis is valuable for market research and understanding competitors. It helps businesses gauge customer opinions from various platforms like social media, identify emerging trends, and evaluate the effectiveness of marketing campaigns.

Healthcare and Medical Domain:

Sentiment analysis is increasingly used in healthcare to analyze data from sources like surveys, social media posts, and news articles. It helps healthcare providers understand patient moods, detect adverse drug reactions, and improve healthcare services.

Reputation Management:

Sentiment analysis is used to monitor how customers view a brand or product. It helps businesses track customer opinions and identify areas for improvement, contributing to better reputation n management and brand monitoring.

Review Analysis:

Sentiment analysis is widely used to analyze movie, show, or product reviews, helping viewers make informed decisions and boosting the popularity of good content. It can also improve customer experiences in industries like travel, where customer reviews are used to make data-driven decisions.

Customer Reviews:

Sentiment analysis of reviews from hotels, restaurants, and other services helps customers choose better options and businesses improve their offerings by identifying strengths and weaknesses.

Aspect Analysis:

Aspect-based sentiment analysis identifies specific aspects of feedback, such as product features or service qualities, allowing businesses to focus on areas that need improvement based on customer sentiment.

Stock Market:

Sentiment analysis can be used to predict stock price trends by analyzing news articles, social media, and blogs related to companies. Positive or negative news can indicate whether stock prices will rise or fall, making sentiment analysis valuable for stock market predictions.

Voice of Customers:

By analyzing feedback from call centers, emails, surveys, and other sources, sentiment analysis can identify trends and recurring issues. This helps businesses improve their offerings and adapt to customer needs more effectively.

Social Media Monitoring:

Sentiment analysis is used to monitor customer sentiment on social media platforms in real time. This helps businesses react quickly to negative feedback, maintain a positive image, and gather valuable insights from honest customer opinions shared online.

CHALLENGES IN SENTIMENT ANALYSIS:

Sentiment analysis faces several challenges, particularly due to the complexity and variability of human language. These challenges include:

Structured Sentiments:

Structured sentiments appear in formal reviews and are typically related to factual or scientific matters, like research or books. These reviews are easier to analyze because they tend to be well-organized and clearly express the author's thoughts.

Semi-Structured Sentiments:

Semi-structured sentiments are between structured and unstructured types. They often include pros and cons in brief, separate sections. Analyzing such sentiments requires understanding various concerns expressed in short sentences.

Unstructured Sentiment:

Unstructured sentiment comes from informal, free-flowing writing, like social media posts. These reviews may mix positive and negative opinions, making them harder to analyze. Sometimes, the sentiment is implied rather than explicitly stated, which further complicates the analysis.

Methodological Challenges:

Sarcasm: Sarcasm is a big challenge, as machines often miss the intended negative sentiment in sarcastic remarks. It's culturally specific and hard for machines to detect. Human-to-Machine and Human-to-Human Interaction: These interactions often use emotions or expressions that may be difficult to label, impacting the reliability of sentiment analysis.Machine-based Limitations: Sentiment analysis tools are limited by the data they are trained on and the lack of deep context, such as tone or non-verbal cues.

OTHER CHALLENGES:

Informal Writing: People often use acronyms, emojis, and shortcuts that can confuse sentiment analysis tools, especially with regional variations.

Grammatical Errors: Spelling and grammatical mistakes are common in informal texts, which can reduce the accuracy of sentiment analysis.

Computational Cost: More complex models that provide higher accuracy require a large amount of data and computational power.

Data Availability: High-quality training data is hard to come by, especially for domain-specific tasks like aspect-based sentiment analysis (ABSA).

Language Adaptation: Sentiment analysis models struggle with different regional variations in language and can be affected by differences in spelling, meaning, and slang.

Degree Adverbs and Intensifiers: Words like "barely," "slightly," and "really" modify the intensity of sentiment, making it harder to determine the exact level of sentiment in a review.

These challenges make sentiment analysis a complex task, requiring advanced models and continuous improvement..

CONCLUSIONS:

This article provided an overview of sentiment analysis and its associated techniques. The main goal was to explore various classification methods, highlighting their advantages and disadvantages in sentiment analysis. The article began by discussing different levels of sentiment analysis, followed by an overview of key procedures such as data collection and feature selection. It then reviewed various sentiment categorization methods, comparing them based on their strengths and weaknesses. Supervised machine learning methods, particularly Naive Bayes (NB) and Support Vector Machine (SVM) algorithms are commonly used due to their simplicity and high accuracy. These methods often serve as benchmarks for evaluating new approaches.

The article also covered several key application areas of sentiment analysis and examined the challenges involved in sentiment evaluation. A comparison was made between different sentiment review structures and the challenges they pose, revealing that domain-specific factors play a critical

role in identifying sentiment issues. Looking ahead, further research will continue to expand the understanding of these challenges and methods, as sentiment analysis remains a relatively underexplored area of study.

REFERENCES:

[1] Adomavicius G, Kwon Y (2011) Improving aggregate recommendation diversity using ranking-based techniques. IEEE Trans Knowl Data Eng 24(5):896–911

[2] Ahmad S, Asghar MZ, Alotaibi FM, Awan I (2019) Detection and classification of social media based extremist affiliations using sentiment analysis techniques. Hum Centric Comput Inf Sci 9(1):1–23

[3] Annett M, Kondrak G (2008) A comparison of sentiment analysis techniques: Polarizing movie blogs. In:Conference of the Canadian Society for Computational Studies of Intelligence. Springer, pp 25–35

[4] Birjali M, Kasri M, Beni-Hssane A (2021) A comprehensive survey on sentiment analysis: approaches,challenges and trends. Knowl-Based Syst 226:107134

[5] Borg A, Boldt M (2020) Using VADER sentiment and SVM for predicting customer response sentiment.Expert Syst Appl 162:113746

[6] Fredriksen-Goldsen KI, Kim HJ (2017) The science of conducting research with LGBT older adults-an introduction to aging with pride: National health, aging, and sexuality/gender study (NHAS)

[7] George DR, Rovniak LS, Kraschnewski JL (2013) Dangers and opportunities for social media in medicine. Clin Obstet Gynecol 56(3)

[8] Hamdan H, Bellot P, Bechet F (2015) Lsislif: Crf and logistic regression for opinion target extraction and sentiment polarity analysis. In: Proceedings of the 9th international workshop on semantic evaluation (SemEval 2015), pp 753–758

[9] Hassonah MA, Al-Sayyed R, Rodan A, Ala'M AZ, Aljarah I, Faris H (2020) An efficient hybrid filter and evolutionary wrapper approach for sentiment analysis of various topics on twitter. Knowl-Based Syst 192:105353

[10] Jain PK, Pamula R, Ansari S, Sharma D, Maddala L (2019) Airline recommendation prediction using customer generated feedback data. In: 2019 4th international conference on information systems and computer networks (ISCON). IEEE, pp 376–379

[11] Janjua F, Masood A, Abbas H, Rashid I, Khan MMZM (2021) Textual analysis of traitor-based dataset through semi supervised machine learning. Futur Gener Comput Syst 125:652–660

[12] Jiménez-Zafra SM, Martín-Valdivia MT, Molina-González MD, Ureña-López LA (2019) How do we talk about doctors and drugs? sentiment analysis in forums expressing opinions for medical domain. ArtifIntell Med 93:50–57

[13] Kamal A (2013) Subjectivity classification using machine learning techniques for mining feature-opinion pairs from web opinion sources. arXiv preprint arXiv: 13126 962

[14] Kang H, Yoo SJ, Han D (2012) Senti-lexicon and improved Naïve Bayes algorithms for sentiment analysis of restaurant reviews. Expert Syst Appl 39(5):6000–6010.

[15] Kasmuri E, Basiron H (2017) Subjectivity analysis in opinion mining a systematic literature review. Int J Adv Soft Comput Appl 9(3):133–159

[16] Kaufmann M (2012) Jmaxalign: a maximum entropy parallel sentence alignment tool. In: Proceedings of COLING 2012: demonstration papers, pp 277–288

[17] Kolchyna O, Souza TT, Treleaven P, Aste T (2015) Twitter sentiment analysis: Lexicon method, machine learning method and their combination. arXiv preprint arXiv: 15070 0955

[18] Korkontzelos I, Nikfarjam A, Shardlow M, Sarker A, Ananiadou S, Gonzalez GH (2016) Analysis of the effect of sentiment analysis on extracting adverse drug reactions from tweets and forum posts. J Biomed Inform 62:148–158

[19] Kosamkar V, Chaudhari SS (2013) Improved intrusion detection system using c4. 5 decision tree and support vector machine. PhD diss, Doctoral dissertation, Mumbai University

[20] Kumar A, Teeja MS (2012) Sentiment analysis: a perspective on its past, present and future. Int J Intell Syst Appl 4(10):1
[21] Lata K, Singh P, Dutta K (2020) A comprehensive review on feature set used for anaphora resolution. ArtifIntell Rev 54:2917–3006
[22] Li F, Wang W, Xu J, Yi J, Wang Q (2019) Comparative study on vulnerability assessment for urban buried gas pipeline network based on SVM and ANN methods. Process Saf Environ Prot 122:23–32
[23] Ligthart A, Catal C, Tekinerdogan B (2021) Systematic reviews in sentiment analysis: a tertiary study. Artif Intell Rev 54:4997–5053
[24] Majumder N, Hazarika D, Gelbukh A, Cambria E, Poria S (2018) Multimodal sentiment analysis using hierarchical fusion with context modeling. Knowl-Based Syst 161:124–133
[25] Moraes R, Valiati JF, Neto WPG (2013) Document-level sentiment classification: an empirical comparison between SVM and ANN. Expert Syst Appl 40(2):621–633
[26] Mowlaei ME, Abadeh MS, Keshavarz H (2020) Aspect-based sentiment analysis using adaptive aspect- based lexicons. Expert Syst Appl 148:113234
[27] Park S, Kim Y (2016) Building thesaurus lexicon using dictionary-based approach for sentiment classification. In: 2016 IEEE 14th international conference on software engineering research, management and applications (SERA), pp 39–44, https:// doi. org/ 10. 1109/ SERA. 2016. 75161 26
[28] Peng M, Zhang Q, Jiang Yg, Huang XJ (2018) Cross-domain sentiment classification with target domain specific information. In: Proceedings of the 56th annual meeting of the association for computational linguistics (Volume 1: Long Papers), pp 2505–2513.

[29] Piryani R, Madhavi D, Singh VK (2017) Analytical mapping of opinion mining and sentiment analysis research during 2000–2015. Inf Process Manag 53(1):122–150
[30] Razon A, Barnden J (2015) A new approach to automated text readability classification based on concept indexing with integrated part-of-speech n-gram features. In: Proceedings of the international conference recent advances in natural language processing, pp 521–528
[31] Ritter A, Etzioni O, Clark S (2012) Open domain event extraction from twitter. In: Proceedings of the 18thACM SIGKDD international conference on Knowledge discovery and data mining, pp 1104–1112
[32] Schouten K, Frasincar F (2015) Survey on aspect-level sentiment analysis. IEEE Trans Knowl Data Eng 28(3):813–830
[33] Soleymani M, Garcia D, Jou B, Schuller B, Chang SF, Pantic M (2017) A survey of multimodal senti-ment analysis. Image Vis Comput 65:3–14
[34] Straka M, Hajic J, Straková J (2016) UDPipe: trainable pipeline for processing CoNLL-U files performing tokenization, morphological analysis, pos tagging and parsing. In: Proceedings of the tenth international conference on language resources and evaluation (LREC'16), pp 4290–4297
[35] Subhashini L, Li Y, Zhang J, Atukorale AS, Wu Y (2021) Mining and classifying customer reviews: a survey. Artif Intell Rev 54:6343–6389
[36] Thet TT, Na JC, Khoo CS (2010) Aspect-based sentiment analysis of movie reviews on discussion boards. J Inf Sci 36(6):823–848
[37] Tian Y, Galery T, Dulcinati G, Molimpakis E, Sun C (2017) Facebook sentiment: reactions and emo-jis. In: Proceedings of the fifth international workshop on natural language processing for social media, pp 11–16
[38] Turney PD, Littman ML (2003) Measuring praise and criticism: inference of semantic orientation from association. ACM Trans Inf Syst 21(4):315–346

[39] Valencia F, Gómez-Espinosa A, Valdés-Aguirre B (2019) Price movement prediction of cryptocurren-cies using sentiment analysis and machine learning. Entropy 21(6):589

[40] Van de Camp M, Van den Bosch A (2012) The socialist network. Decis Support Syst 53(4):761–769
[41] Vechtomova O (2017) Disambiguating context-dependent polarity of words: an information retrieval approach. Inf Process Manag 53(5):1062–1079
[42] Venugopalan M, Gupta D (2015) Exploring sentiment analysis on twitter data. In: 2015 eighth international conference on contemporary computing (IC3). IEEE, pp 241–247
[43] Wang Z, Ho SB, Cambria E (2020) Multi-level fine-scaled sentiment sensing with ambivalence handling. Int J Uncertain Fuzziness Knowl-Based Syst 28(04):683–697
[44] Weerasooriya T, Perera N, Liyanage S (2016) A method to extract essential keywords from a tweet using NLP tools. In: 2016 sixteenth international conference on advances in ICT for emerging regions (ICTer). IEEE, pp 29–34
[45] Xia H, Yang Y, Pan X, Zhang Z, An W (2020) Sentiment analysis for online reviews using conditional random fields and support vector machines. Electron Commer Res 20(2):343–360
[46] Yadav A, Vishwakarma DK (2020) Sentiment analysis using deep learning architectures: a review. Artif Intell Rev 53(6):4335–4385
[47] Yan-Yan Z, Bing Q, Ting L (2010) Integrating intra-and inter-document evidences for improving sentence sentiment classification. Acta Autom Sinica 36(10):1417–1425
[48] Yousif A, Niu Z, Tarus JK, Ahmad A (2019) A survey on sentiment analysis of scientific citations. Artif Intell Rev 52(3):1805–1838
[49] Yue L, Chen W, Li X, Zuo W, Yin M (2019) A survey of sentiment analysis in social media. Knowl Inf Syst 60(2):617–663
[50] Zvarevashe K, Olugbara OO (2018) A framework for sentiment analysis with opinion mining of hotel reviews. In: 2018 Conference on information communications technology and society (ICTAS). IEEE, pp1–4
[51] Mayur Wankhade1,Annavarapu Chandra Sekhara Rao,·Chaitanya Kulkarni1 (2022) A survey on sentiment analysis methods, applications,
and challenges, Artificial Intelligence Review (2022) 55:5731–5780