

LAB 4 CS2610- REPORT
ATHARVA MOGHE(CS23B096)

Q1)

```
cs23b096@kanal:~/Documents/CS2610/LAB4$ riscv64-unknown-elf-gcc lab4q1.c lab4q1.  
s  
cs23b096@kanal:~/Documents/CS2610/LAB4$ spike pk a.out  
bbl loader  
First_Name: Atharva ,Second_Name: Moghe , Course_Name:CS2610  
cs23b096@kanal:~/Documents/CS2610/LAB4$
```

PLEASE REFER TO THE INPUT STRINGS USED IN THE CODES

Commands used-

Spike pk a.out to get the output

In the assembly code, la was used to load the address;sd,ld was used to store and load the values respectively. Jump function was used to go to display profile name.

Additionally, all the functions and variables used in the C code were made global.

C code is a standard C code

Q2)

```
cs23b096@kanal:~/Documents/CS2610/LAB4$ riscv64-unknown-elf-gcc lab4q2.c lab4q2.  
s  
cs23b096@kanal:~/Documents/CS2610/LAB4$ spike pk a.out  
bbl loader  
reverse_string=ehgomavrahta,length=12  
/.cs23b096@kanal:~/Documents/CS2610/LAB4$
```

PLEASE REFER TO THE INPUT STRINGS USED IN THE CODES

Commands used-

Spike pk a.out

Global function reverse

Loop,addi,add,beq,li and all other standard functions have been used

In the C code, extern command is used which helps in linking all the files.