

# C2M3: Peer Reviewed Assignment

## Outline:

The objectives for this assignment:

1. Motivate the use of two-way ANOVA through real data analysis examples.
2. Interpret the two-way ANOVA model, with and without interaction terms.
3. Construct and interpret interaction plots to visually assess the importance of an interaction term.
4. Conduct hypothesis tests to decide whether a two-way ANOVA interaction term is statistically significant.
5. Use the two-way ANOVA and ANCOVA models to answer research questions using real data.

General tips:

1. Read the questions carefully to understand what is being asked.
2. This work will be reviewed by another human, so make sure that you are clear and concise in what your explanations and answers.

```
In [4]: # Load Required Packages
library(tidyverse)
library(ggplot2) # a package for nice plots!
library(dplyr)
library(emmeans)
```

```
— Attaching packages — tidyverse
rse 1.3.0 —
```

```
✓ ggplot2 3.3.0    ✓ purrr  0.3.4
✓ tibble  3.0.1    ✓ dplyr  0.8.5
✓ tidyr   1.0.2    ✓ stringr 1.4.0
✓ readr   1.3.1    ✓ forcats 0.5.0
```

```
— Conflicts — tidyverse_co
nflicts() —
✖ dplyr::filter() masks stats::filter()
✖ dplyr::lag()     masks stats::lag()
```

# Problem 1: e-reader data

In this assignment, we learn to answer our two-way ANOVA research questions through the analysis of real data. We will use the ereader data. The study that generated these data can be found here: [P.-C. Chang, S.-Y. Chou, K.-K. Shieh \(2013\). "Reading Performance and Visual Fatigue When Using Electronic Displays in Long-Duration Reading Tasks Under Various Lighting Conditions," Displays, Vol. 34, pp. 208-214. \(http://users.stat.ufl.edu/~winner/data/ereader1.txt\)](http://users.stat.ufl.edu/~winner/data/ereader1.txt)

Electronic paper display devices, such as the Amazon Kindle have changed the way that people read. But has it changed for the better? In a 2013 study titled "Reading Performance and Visual Fatigue When Using Electronic Displays in Long-Duration Reading Tasks Under Various Lighting Conditions", researchers set out to ask whether reading speed (a continuous variable) differed across different electronic paper displays. In addition, they were also interested in whether different lighting conditions impacted reading speed. As such, this experiment had one response with two different factors:

1. Device type: three different types.

- A. Sony PRS-700 with a 6-in. display,  $800 \times 600$  resolution;
- B. Amazon Kindle DX with a 9.7-in. display,  $1200 \times 824$  resolution; and
- C. iRex 1000S with a 10.2-in. display,  $1024 \times 1280$  resolution.

1. Lighting Condition: four different conditions (200Lx, 500Lx, 1000Lx, 1500Lx), Lx = lux, one lumen per square meter

1. Reading Time: measured in seconds.

With these data, we might ask the following **research questions**:

- 1. Are the effects of device type significant? That is, is there evidence that suggests that individuals read at different speeds based on the device that they are using?
- 1. Are the effects of lighting conditions significant? That is, is there evidence that suggests that individuals read at different speeds based on the reading lighting conditions?
- 1. Do device type and lighting conditions *interact*? For example, Suppose that, on average, people can read for longer on device A than on device B, in low light. Is that trend the same in medium light, or bright light? If not, for example, if B is better than A in bright light, then type and lighting interact.

Through this entire analysis, let's set  $\alpha = 0.05$ .

**First, let's read in the data, and store the appropriate variables as factors.**

```
In [5]: # Load the data
read = read.csv("ereader.txt", sep="\t")

names(read) = c("device", "light", "time")

read$device = factor(read$device)

read$light = factor(read$light, levels=1:4,
                    labels=c("200Lx", "500Lx", "1000Lx", "1500Lx"))

summary(read)
```

device	light	time
1:19	200Lx :14	Min. : 543.8
2:20	500Lx :15	1st Qu.: 861.4
3:20	1000Lx:15	Median :1105.4
	1500Lx:15	Mean :1090.2
		3rd Qu.:1300.0
		Max. :1797.2


**1.(a) Construct interaction plots, and visually assess and comment on whether interactions are present.**

In [6]: # Your Code Here

```
data_interaction <- read %>%
  group_by(light,device) %>%
  summarise(time=mean(time))

ggplot(data_interaction, aes(x = light, y = time, color = device))+
  geom_point(alpha = 0.8) +
  scale_color_manual(values=c('black', '#CFB87C', 'royalblue4'))+
  geom_smooth(method = "lm", se = F, alpha = 0.3)+
  xlab("Lighting condition (lux)") +
  ylab("Reading time (sec)") +
  theme_bw()
```

`geom\_smooth()` using formula 'y ~ x'



Differences across device types seems to be relatively constant, hence, there is not any visual indication of an interaction between light and device type.

**1.(b) Now, let's formally test for an interaction. Fit a model with an interaction, and one without, and conduct an F-test. State the appropriate decision for the test.**

```
In [9]: # Your Code Here
red_model <- lm(time ~ device + light, read)

ext_model <- lm(time ~ device + light + device:light, read)

summary(red_model)
summary(ext_model)
anova(red_model)
anova(red_model, ext_model)
```

Call:  
lm(formula = time ~ device + light, data = read)

Residuals:

	Min	1Q	Median	3Q	Max
	-500.0	-194.6	-24.8	204.9	460.5

Coefficients:

	Estimate	Std. Error	t value	Pr(> t )
(Intercept)	1438.25	87.22	16.489	< 2e-16 ***
device2	-209.73	83.89	-2.500	0.015547 *
device3	-227.93	83.89	-2.717	0.008879 **
light500Lx	-97.46	97.30	-1.002	0.321052
light1000Lx	-321.66	97.30	-3.306	0.001704 **
light1500Lx	-366.16	97.30	-3.763	0.000421 ***

---  
Signif. codes: 0 '\*\*\*' 0.001 '\*\*' 0.01 '\*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 261.7 on 53 degrees of freedom  
Multiple R-squared: 0.3455, Adjusted R-squared: 0.2838  
F-statistic: 5.596 on 5 and 53 DF, p-value: 0.0003268

Call:  
lm(formula = time ~ device + light + device:light, data = read)

Residuals:

	Min	1Q	Median	3Q	Max
	-497.41	-188.21	-17.28	207.16	463.53

Coefficients:

	Estimate	Std. Error	t value	Pr(> t )
(Intercept)	1413.63	138.44	10.211	1.62e-13 ***
device2	-163.44	185.74	-0.880	0.3833
device3	-205.28	185.74	-1.105	0.2747
light500Lx	-27.67	185.74	-0.149	0.8822
light1000Lx	-319.94	185.74	-1.723	0.0915 .
light1500Lx	-344.14	185.74	-1.853	0.0702 .
device2:light500Lx	-125.92	255.27	-0.493	0.6241
device3:light500Lx	-78.53	255.27	-0.308	0.7597
device2:light1000Lx	-16.24	255.27	-0.064	0.9495
device3:light1000Lx	15.99	255.27	0.063	0.9503
device2:light1500Lx	-38.04	255.27	-0.149	0.8822
device3:light1500Lx	-23.11	255.27	-0.091	0.9283

---  
Signif. codes: 0 '\*\*\*' 0.001 '\*\*' 0.01 '\*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 276.9 on 47 degrees of freedom  
Multiple R-squared: 0.3502, Adjusted R-squared: 0.1981  
F-statistic: 2.302 on 11 and 47 DF, p-value: 0.02369

A anova: 3 × 5

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
	<int>	<dbl>	<dbl>	<dbl>	<dbl>
<b>device</b>	2	563255.7	281627.86	4.113089	0.0218512377
<b>light</b>	3	1352514.1	450838.04	6.584352	0.0007263291
<b>Residuals</b>	53	3628970.0	68471.13	NA	NA

A anova: 2 × 6

	Res.Df	RSS	Df	Sum of Sq	F	Pr(>F)
	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>	<dbl>
<b>1</b>	53	3628970	NA	NA	NA	NA
<b>2</b>	47	3603108	6	25861.55	0.05622427	0.9992146

There is not enough statistical evidence to determine that the reduced model is not sufficient, therefore we assume that an interaction term is not needed at a 5% significance level.

**1.(c) Before we interpret this model with respect to research question #1 above (just below the data description), let's decide whether the differences that the model reports are statistically significant.**

**Investigate this question using Bonferroni post hoc comparisons. That is, conduct all pairwise post hoc comparisons for device type using a Bonferroni correction and an overall type I error rate of  $\alpha = 0.05$ . Comment on the results.**

In [11]: # Your Code Here

```
boxplot(time ~ device,
        data = read,
        main = "Reading time by device type",
        xlab = "Device type",
        ylab = "Reading time",
        col = "steelblue",
        border = "black")

n = length(read$time)

J = length(unique(read$device))

rss = sum(resid(red_model)^2)

sighat = sqrt(rss/(n-J))

ybar = tapply(read$time, read$device, mean)

diff = as.numeric(c(ybar[2]-ybar[1],
                    ybar[3]-ybar[1],
                    ybar[3]-ybar[2]))

diff

se = sighat*sqrt(1/9+1/9)

t = diff/se

p = 2*(1-pt(abs(t), df=n-J))

df = data.frame(diff, t, p)

names(df) = c("diff",
              "t",
              "p")


df
```



-199.392605263158 · -217.593105263158 · -18.2004999999999

A data.frame: 3 × 3

diff	t	p
<dbl>	<dbl>	<dbl>
-199.3926	-1.6615661	0.10218868
-217.5931	-1.8132334	0.07515615
-18.2005	-0.1516673	0.87999444



The results indicate that there is not a statistical significant effect of device type on reading time...

**1.(d) Using the post hoc comparisons from above, let's focus on research question #1 from above: Are the effects of device type significant? That is, is there any evidence that suggests that individuals read faster or slower based on the device that they are using**

No, they are not significant.

In [ ]: *# Your Code Here*