Assignment: Apache Sqoop and Hive assignments

1. Grant db access permission in MySQL
   GRANT ALL PRIVILEGES ON *.* TO 'neel'@'localhost' IDENTIFIED BY 'neel';

2. List all databases in mysql through SQOOP
   sqoop list-databases --connect jdbc:mysql://localhost?useSSL=flase --username neel --password neel

3. List all tables in selected database
   sqoop list-tables --connect jdbc:mysql://localhost?useSSL=false --username neel --password neel

4. Import table into HDFS using target-dir method
   sqoop import --connect jdbc:mysql://localhost/retail_db?useSSL=false --username neel -password neel --table orders --target-dir '/target-dir data'

5. Import table into HDFS using warehouse-dir method
   for warehouse-dir:
      1. create directory using command: hdfs dfs -mkdir /<folder_name>
      2. sqoop import --connect jdbc:mysql://localhost/retail_db?useSSL=false --username neel -password neel --table orders --warehouse-dir '/<Name of dir that we created>'

6. To import partial data from specified table

   sqoop import --connect jdbc:mysql://localhost/retail_db?useSSL=false --username neel -password neel --table orders --warehouse-dir '/SQOOP' --where "order_id > 68800"

7. To import only data from selected columns of table
   sqoop import --connect jdbc:mysql://localhost/retail_db?useSSL=false --username neel -password neel --columns order_id,order_customer_id --table orders --target-dir '/'

8. To import all tables from given database
   sqoop import-all-tables --connect jdbc:mysql://localhost/retail_db?useSSL=false --username neel -password neel --warehouse-dir '/ '

9. To exclude some tables while importing all tables
   sqoop import-all-tables --connect jdbc:mysql://localhost/retail_db?useSSL=false --username neel -password neel --warehouse-dir '/ ' --exclude-tables orders,customers

10. To export table from HDFS to local dB
    to export:
        1. need empty table in sql with same metadata.
        2. sqoop export --connect jdbc:mysql://localhost/test1?useSSl=false --username neel -password neel --table test_table --export-dir'/user/test1'

11. Create Hive table in HDFS
    CRETAE DATABASE >hivedemo<

12. Load data from HDFS to Hive table
    load data inpath '<path of hdfs>' into table <database name>.<table name we want to copy in>;

13. Run SQL query in Hive
    hive -e "SELECT * FROM my_table;"